

# Data Report for Evidence-Based Training

July 2013



# to order:Image: Note: N



# OBJECTIVE

The contents will be useful to the following entities:

- 1. Civil Aviation Authorities (CAAs)
- 2. Operators
- 3. Approved training organizations (ATOs)
- 4. Course developers
- 5. Pilot representative bodies

# CONTENT

The material in this manual is intended to compliment the following documents:

- 7 ICAO Annex 1
- 7 ICAO Annex 6
- ICAO Doc 9625 Manual of Criteria for the Qualification of Flight Simulation Training Devices, Volume 1 – Aeroplanes
- 7 ICAO Doc 9841 Manual on the Approval of Training Organizations
- 7 ICAO Doc 9868 PANS-TRG Chapter 5 & 6
- 7 ICAO Doc 9995 Manual of Evidence-Based Training

# **STRUCTURE OF THE REPORT**

The document is structured as a report of the objectives, methodology, analysis and conclusions resulting from the review of the data conducted in support of EBT development. It is intended as the first step in a process of continual review of real world data from accidents, incidents, flight operations and training to feed and validate course development. The purpose of the data collection and analysis is to provide the necessary information for development of a program of events based upon aircraft generations, to be utilized for the development of pilot competencies through the baseline EBT program. Data analyses described in this report have been used to construct the baseline EBT program, and will be reviewed and updated on a continual basis. The enhanced EBT program described in this manual is intended to create a delta to the baseline program, utilizing operator specific data.

# UPDATES

While the EBT data analysis is substantial and supportive of the program, there is a clear need for regular and where necessary, substantial update and expansion. New data will be acquired and analyzed according to the key principles established in this report. New sources will provide a continuing and expanding review of operations, training and safety events. The training criticality survey will be developed to provide corroboration and correlation across multisource data results and more importantly, will provide continual access to professional expertise. Data analysis undertaken with the rigor and spirit of the EBT data study is a key foundation for improving safety through improvements in training.

EBT is focused on developing and maintaining pilot competencies in identified areas specific to aircraft groupings and, in the case of an enhanced EBT programs, specific to an air operator. EBT represents a paradigm shift in recurrent training methodologies that will supplement the more traditional regulatory-prescribed training practices. EBT will continue to evolve as a result of continuous feedback and the incorporation of new evidence as it becomes available. This report will be updated based upon the analyses of new data.

# **EXECUTIVE SUMMARY**

The existing international standards and regulations for airline pilot training were originally derived in response to accidents involving early generation jet aircraft. Apart from 'bolt–on' additions, usually in the form of maneuver-based practices, standards have remained virtually unchanged since inception. During the same period progressive changes in aircraft design, including the developments in automation, system integration, reliability and significant changes in the operating environment have demonstrably improved operational safety, but also revealed new operational challenges.

The Evidence-Based Training (EBT) project is a global safety initiative, which arose from concerns that recurrent and type-rating training were no longer meeting the needs of airline pilots.

At the inception of the EBT project, a review of available data sources, their scope, and relative reliability was undertaken. This was followed by comprehensive analyses of the data sources chosen. The objective of these analyses was to determine the relevance of existing pilot training and to identify the most critical areas of training focus according to aircraft generation.

This report corroborates independent evidence from multiple sources, which include flight data analysis, reporting programs and a statistical treatment of factors reported from an extensive database of aircraft accident reports. Both process and results were peer-reviewed by experts in pilot training drawn from airline operators, pilot associations, civil aviation authorities and original equipment manufacturers, so as to provide transparency and to bring a qualitative and practical perspective. During this study, critical core competencies were examined, in technical and non-technical areas presenting the opportunity to train and assess flight crews according to a defined, useful and comprehensive set of measurement criteria.

Pilots often do not have the confidence and capability to operate the aircraft in all regimes of flight and to be able to recognize and manage unexpected situations. Results show that manual aircraft control, management of go-arounds, procedural knowledge of automation and flight management systems (FMS), monitoring, crosschecking, error detection and management of adverse weather are issues of concern. The report also reveals a significant and pervasive rate of unstable approaches continued to landing, illustrative of an endemic culture of intentional non-compliance across many flight regimes.

It is important that non-technical performance becomes part of an integrated approach to training, and the report reveals the significance of certain non-technical competencies in reducing risk in operations. The challenge of maintaining Situation Awareness in a highly automated and highly reliable system needs to be addressed through more effective training and exposure to rapidly developing and dynamic situations. Competencies of Leadership and Communication are revealed as key risk reducing countermeasures and should be a primary area of focus in training.

Data indicate a need for pilots to be exposed to the unexpected in a learning environment, and be more challenged and immersed in dealing with complex situations, rather than repetitively being tested in the execution of maneuvers. Training programs constrained by repetitive testing in the execution of maneuvers to comply with outdated regulation, lack the variability to train effectively in this way.

The report indicates significant differences across what can be considered as three different aircraft generations of jet transport aircraft and two generations of turbo-prop aircraft. While overlap in training clearly exists, there are quite distinct generational differences in patterns of existing risk that are not adequately addressed by current training.

This report evidentially illustrates inadequacies in the perpetuation of historical airline flight training regimes and identifies areas in which major change is necessary. It strongly supports the implementation of such change in both the regulation and development of recurrent airline pilot assessment and training. It identifies the areas for improvement, providing the prioritization of germane and relevant training topics to guide in the construction of suitable EBT programs.



# TABLE OF CONTENTS

Ex	ecutive	e Summary	ii
1	Introc 1.1 1.2 1.3 1.4 1.5 1.6 1.7	luction Data Streams Data Source – Category 1 Data Source – Category 2 Data Source – Category 3 Evidence table Types of Data Application of the results	1 3 4 4 4 5 5
2	Major 2.1 2.2 2.3 2.4 2.5 2.6 2.7	Findings Preface Flight Path – Manual Aircraft Control The Unstable Approach Paradox Catalysts in the Cockpit Surprise Prioritization of Training Topics Summary of Major Findings	7 7 8 .15 .17 .17 .18
3	Meth 3.1	bodology         LOSA Study         3.1.1       Objective         3.1.2       Background         3.1.3       Strengths and Weaknesses of LOSA	.21 .21 .21 .21 .21
	3.2	EBT Accident – Incident Study 3.2.1 Stage 1 3.2.2 EBT Accident-Incident Study – Stage 2	.22 .22 .30
	3.3	<ul> <li>EBT Flight DAta analysis &amp; additional FDA reports</li></ul>	.46 .46 .52 .53
	3.4	<ul> <li>3.3.4 Strengths and Weaknesses</li> <li>Training data (AQP &amp; ATQP)</li> <li>3.4.1 AQP Study</li> <li>3.4.2 ATQP Implementation Data</li> </ul>	.54 .55 .55 .57
	3.5	Airline Pilot Survey on Training Effectiveness         3.5.1       Background         3.5.2       Purpose         3.5.3       Strengths and weaknesses	. 58 . 58 . 58 . 58 . 59
	3.6	Meta Data from Accident & Incident Studies         3.6.1       IATA Safety Report 2008 & 2009         3.6.2       Incidents during training         3.6.3       UK CAA Accident Reports	.59 .59 .62 .63
	3.7	<ul> <li>Scientific Reports</li> <li>3.7.1 Skill Retention after Training (FAA Unpublished Report)</li> <li>3.7.2 FAA Human Factors Team Report 1996 on: The Interfaces</li> <li>between Flightcrews and Modern Flight Deck Systems</li> </ul>	.66 .66
		<ul> <li>3.7.3 Automation Training Practitioners' Guide</li></ul>	.67 .68 .68
	3.8	Accident STudy using Cast Data	.69

# Data Report for Evidence-Based Training

		3.8.2	Strengths and Weaknesses	70
	3.9	Training	Criticality Survey (TCS)	70
		3.9.1	Background	70
		3.9.2	Strengths and Weaknesses	75
	3.10 Correlation of Risk between TCS and Accident-Incident Study			
		3.10.1	Background	75
3.10.2 Strengths and Weaknesses				76
3.11 Evidence Table Methodology				
		3.11.1	Purpose	76
		3.11.2	Data Entry	76
		3.11.3	Evidence Table – Identifying the most Critical Training Topics	77
		3.11.4	Evidence Table – Analysis by Source	77
4	Analv	sis and R	esults	83
•	4.1	Summar	v Analysis by Topic	
		4.1.1	Unstable Approaches	83
		4.1.2	Automation	
		413	Frror Management	84
		414	Manual Aircraft Control	01
		415	Go-Arounds	01
		416	Adverse Weather	85
		417	System Malfunction	85
		4.1.7	Terrain	88
		4.1.0	Surnrise	88
		4 1 10	Landing Issues	88
		4.1.10	Compliance	00
		4.1.11 // 1.12	L adarchin	07
		1 1 13	Mismanaged Aircraft State	07
		1.10 1 1 11	Unset	07 88
	12	Analycia	by Source	00
	4.2	Analysis		00
		4.2.1	LOSA	106
		4.2.2	Elight Date Analysis	115
		4.2.3	Training Data (AOD & ATOD)	107
		4.2.4	Training Data (AQP & ATQP)	150
		4.2.5	Pilol Sulvey	. 152
		4.2.0	IATA Accident Reports 2008/2009	. 100
		4.2.7		. 1/4
		4.2.8	UK CAA Accident Studies.	. 182
		4.2.9	Skill Retention after Training/Skill Decay	. 10/
		4.2.10	Automation Training Practitionany' Quide	. 192
		4.2.11		. 205
		4.2.12	Appident Data Using Augmented Cost Data	. 210
		4.2.13	Accident Data Using Augmented Cast Data	. 211
Glo	ssary	of Terms		. 218
Def	inition	s		. 219
Ack	nowle	dgements	5	. 222



Appendix 1 LOSA Studies	225
Appendix 2 Accident Incident Analysis	268
Appendix 3 Evidence-Based Training Matrix	
Appendix 4 Airline Pilot Perceptions of Training Effectiveness by Boeing	465
Appendix 5 Assessment of Pilot Performance Maneuver Grades	488
Appendix 6 Analysis of Global Fatal Accident Data	515
Appendix 7 Flight Data Analysis (FDA)	525
Appendix 8 Definitions of Events Used in EBT FDA	536
Appendix 9 Advanced Qualification Program (AQP)	555
Appendix 10 ATQP Study	562
Appendix 11 Training Criticality Survey (TCS)	
Appendix 12 Evidence Table	596
Appendix 13 Matrix of Summaries from the Evidence Table	621
Appendix 14 Graphic Visualization of EBT Accident-Incident Data	638
Appendix 15 Cast Data for Jet Accidents 1987 – 2008	648
Appendix 16 Summary Training Topic Derivation Process	688
Appendix 17 Links to Additional Data Sources.	692
••	

Intentionally blank



# **1 INTRODUCTION**

The Evidence-Based Training project is a major safety initiative. It arose from an industry-wide consensus that, in order to reduce the airline accident rate, a strategic review of recurrent and type-rating training for airline pilots was necessary. Essential to ensuring regulatory support for this initiative was the objective consolidation of empirical data that provided substantial evidence that current training and checking practices were not, of themselves, fulfilling the safety needs of the industry. Keeping in mind that international standards and commensurate national regulations for airline pilot training largely evolved from the evidence of accidents involving early generation jet aircraft, the analysis of safety data involving other groupings of more modern aeroplanes did not always show a relationship to those prescriptive requirements. For the most part, the belief was that simply repeating pilot exposure to "worst case" events in training was considered sufficient to satisfy the industry's safety needs. Over time, 'novel' events resulting in serious occurrences were simply added to the requirements of progressively crowded training programs, which eventually resulted in an inventory or "tick box" approach to training being adopted. As a result, the industry was being forced to focus on their flight crews meeting the ever-increasing regulatory-imposed minimum performance standards rather than enhancing their overall abilities.

This report clearly demonstrates that training methodologies must and can be significantly improved. This improvement process begins with applying a different philosophy when developing and implementing recurrent training programs; a philosophy that inculcates best operating practices, which are relevant to both the equipment in use and the specific needs of the air operator.

The availability of data from both flight operations and training activity has improved substantially over the last 20 years. Sources such as flight data analysis, flight observations (e.g., line observation safety audits (LOSA) programs) and air safety reports give a detailed insight into the threats, errors and undesired aircraft states encountered in modern airline flight operations as well as their relationship to unwanted consequences. In light of evidence from these data sources, it was considered timely and important to review current training practices

A large-scale comprehensive study of a range of available data sources and analyses was conducted and important differences emerged between what can be considered as six different aircraft generations. The process and results of this quantitative analysis were reviewed by a team of internationally recognized experts in pilot training, representing airline operators, pilot associations, regulators, and original equipment manufacturers. This provided transparency as well as a bringing a well-rounded and experiential perspective to the data. Analysis of multiple sources using differing methods and tools revealed consistent findings and it became apparent that, while there remains overlap in areas of training needs across aircraft generations, there are also quite distinct differences in patterns of risk in the later generation aircraft that are currently not addressed. Certain critical pilot competencies emerged in technical and non–technical areas that clearly illustrate the need for a change of focus of airline pilot training, both in terms of concept and curriculum with respect to generational characteristic.

This report presents the methodology and results of a meta–analysis and makes a strong case for changes in recurrent airline pilot training. An intended second phase of the project will address type-rating training. The data analysis team comprised experts from many fields in the area of operational and flight data, pilot instructors, scientists, academic research professionals and a statistician, in addition to volunteer pilots-analysts from various locations around the world.



Results of the analyses described in this report have been used by the EBT working group, consisting of experienced instructors, to build the training scenarios for the Baseline Recurrent EBT Training Program specified for the different aircraft generations. The data sub-group worked directly with pilots developing the content for the suggested recurrent training programs. Results, while unsurprising to many industry experts, are too important to ignore. According to the EBT Pilot Survey, 54% of the respondents encountered an operational situation in 6 months prior to the survey, for which they felt insufficiently trained. 43.6% of respondents reported that the instructor in their last training session did not raise the level of their confidence.

Results contained within this report are drawn from multiple sources, some of which are readily available to the public. Some come from information, access to which is restricted to industry specialists, while other results were inferred from confidential, de-identified data, the specifics of which are made known only to the EBT project group and then only on a "need-to-know" basis.

While the EBT Data Report is not a meta-analysis in a pure sense, it is derived from an analysis of analyses using a variety of sources and techniques to corroborate and challenge its own findings. It consists of a large collection of results from primary and secondary studies that are consolidated to determine training needs.

Findings of this nature in this multi-sourced report come from various external studies, in addition to internally designed studies focusing on specific research questions. The criteria defining the usefulness of the various studies in this report are the following:

- 1. It is relevant from a training perspective (e.g., if incorporating a training change mitigates the risk found in the study).
- 2. There is evidence that it will assist with the identification of competencies to be developed in training in order to mitigate risks encountered in the evolving operational environment.
- 3. The study addresses one or more of the following objectives:
  - a. Substantiate the need for change in the assessment and training programs for commercial transport pilots.
  - b. Provide evidence from data analyses to support the development of training topics, prioritized according to aircraft generation.
  - c. Challenge and/or corroborate the Training Criticality Survey and the Training Guidance with operational data.
  - d. Provide feedback to determine the effectiveness of changes implemented through the adoption of competency-based training methodologies.
- 4. The findings of the study are corroborative or challenging across the spectrum of the multi-analysis study.
- 5. The findings from an outside report come from an industry-respected study.
- 6. Varied data sources and/or varied methodology mitigate inherent biases associated with individual types of source data.

Data were collected from the following sources:

- 1. Operators
- 2. Original Equipment Manufacturers Aircraft (OEM)
- 3. Accident Investigating bodies
- 4. International aviation organizations
- 5. Civil Aviation Authorities

**Note:** Some of the data and/or results in this report are sensitive either in terms of their context or in that the donor specifically provided data on a confidential basis.



#### **1.1 DATA STREAMS**

- 1. All analyses are based on 7 data streams that are listed in figure 1.1.
- 2. There are 18 specific data sources, which are presented in figure 1.1a.
- 3. The data streams represent not only a large set of relevant data, but also a variety of different kinds of data (e.g., flight data, observational data from LOSA, and scientific reports). The cross sectional approach strengthens the basis for analysis, by providing compensation for bias inherent within each data type. This is a strong rationale for the use of multiple data sources.

Data Streams
1. Cockpit Observation Reporting
2. Flight Data Analysis (FDA) Studies
3. Accident/Incident analyses
4. Training Studies
5. Airline Pilot Survey on Training Effectiveness
5. Airline Pilot Survey on Training Effectiveness 6. Scientific Reports

Figure 1.1

The data streams used can be divided into 3 categories based upon the means by which data are used in the analysis.

Data Sources		
LOSA Reports		
EBT Accident & Incident Study		
EBT Flight Data Analysis		
UK CAA Accident Reports	CAP 776 CAP 780	
IATA Safety Reports	2008 2009	
AQP Study		
ATQP Installation Data		
STEADES Training Query		
Airline Pilot Survey on Training Effectiveness		
Factors that Influence Skill Decay and Retention		
Skill Retention after Training - FAA		
Automation Training Practitioners' Guide		
The Interfaces Between Flight Crews & Modern Flight Deck Systems - FAA		
Long Aircraft Type/Variant difference on Landing		
A Study of Normal Operational Landing Performance on Subsonic Civil Narrow Body Jet Aircraft during ILS Approaches - NLR		
TAWS - 'Saves'		
Augmented CAST Accident Study		
Training Criticality Survey (TCS)		
Corrrelation of Risk Between Training Criticality Survey/Accident and Incident Study		

Figure 1.1a

# **1.2 DATA SOURCE – CATEGORY 1**

The first data category contains data from sources that are highlighted in blue in Fig 1.1a. Evidence from these sources has been formulated in the form of statements recorded in the Evidence Table (ET) [See section 1.5 for brief description of ET]. The specific methodology associated with each data source category is described in Chapter 3. The Evidence Table is a tool in the analysis, the specific evidence statements within being linked to different parameters.

# 1.3 DATA SOURCE – CATEGORY 2

The second data category consists of the data from the EBT Accident and Incident Study, which is highlighted in red in Fig 1.1a. The results from these analyses provide several means of ranking according to defined training need. The processes involved (described in section 3.2.) are algorithmic and result in distributions that do not translate easily into evidence statements, and therefore are not incorporated in the Evidence Table.

Merging of all results to reach a final training prioritization by generation is described in Chapter 3 Methodology.

#### **1.4 DATA SOURCE – CATEGORY 3**

The third data source category consists of the results from the Training Criticality Study, which are described in section 3.9, 3.10 and Appendix.11 are highlighted in amber.





# 1.5 EVIDENCE TABLE

Specific evidence taken from the particular studies of category 2 are consolidated into single declarative statements and entered into a database with links to the following:

- 1. Flight phases
- 2. Competencies
- 3. Objectives of the study
- 4. Training Topics
- 5. Context of the evidence if relevant
- 6. Factors analyzed in the Accident-Incident Study
- 7. Sources
- 8. Keywords associated with the conclusions of the report
- 9. Applicability to aircraft generations, if determined

The Evidence Table is displayed in Appendix 12 and the methodology associated with it is in Chapter 3

#### **1.6 TYPES OF DATA**

The following two types of data are used to provide systemic feedback for training criticality analysis in this report:

**Training data**, including the elements and structure of transition courses, recurrent training, line flights under supervision in addition to measurements of system performance. This type of data provides information relating to the effectiveness of the training system, the instructor and trainees, and for the purposes of this report is known as the internal training 'feedback' loop.

**Operational & Safety data** – Operators are required to collect data from operations, and this is sometimes used to analyze and determine risk mitigations through training. This is combined with subsequent measurement of the effectiveness of remedies. LOSA, pilot reports and flight data analysis (FDA) are prime examples. (The external training 'feedback' loop)

#### **1.7 APPLICATION OF THE RESULTS**

One of the major results of the data analyses is a collection of training topics ranked by criticality for each generation of aircraft.

All the results are detailed by training topics in chapter 4, (Analysis and Results) of the report and form the topics sections in this chapter.

Intentionally blank



# 2 MAJOR FINDINGS

#### 2.1 PREFACE

The term 'major' denotes not only the importance of the finding, but also the strength of the evidence and the preceding analysis. There are 6 major findings detailed in this chapter, five specific topics, and a synopsis of the most important results in the EBT study.

The major findings are not surprising to those experienced in training, but there are aspects of findings that initially appeared counterintuitive during the analysis. In such cases it wasn't until the analysis was complete, that the situation clarified and became consistent with professional experience and expectations. The unstable approach paradox is a good example of this phenomenon; the more it was investigated, the clearer the problems associated with these approaches became, including the means for resolution.

A comprehensive major finding, the ranking of the training topics, is based on a type of modeling, which uses risk as one of its major components. It is important to realize that while training has made a major contribution to the reduction of risk in the history of airline transport aviation, it is by no means the only contributor. Aircraft safety by almost any measure is a resounding success story for many reasons. When, for example, comparing generation 2 to generation 4, the safety situation is very different and when making cross-generational comparisons in terms of risk, it is important to normalize either by flight hours or by the number of take-offs. In this study, normalization was achieved by reference to the number of take-offs.

On the other hand, when comparing factors within a particular generation, it is the ordering of the factors in terms of risk that is important and while a specific factor may have a similar likelihood of occurrence in another generation; it may well have a very different ordering because its position in the order depends on all the other factors. Since the mission of the study is to provide evidence in the design of training programs for each specific generation; it is important to prioritize factors accordingly and therefore in this context, i.e., view risk relative to the generation of aircraft for which the training program is being built.

The focus of this chapter is on some powerful and interesting findings. It is important to note that these findings are by no means comprehensive. For a more comprehensive presentation of results, refer to Chapter 4, where there are more findings completing the report and providing the necessary scope and insight to be able to define the particular baseline recurrent training programs.

#### 2.2 FLIGHT PATH - MANUAL AIRCRAFT CONTROL

Several data sources highlight, in different ways, that manual aircraft control skills of pilots are deteriorating over time, as aircraft design improves and the use of automation increases. It should be emphasized that manual control skills consistently remain an issue. As other contributing factors decrease through improved design and reliability, manual control skills remain a substantial issue as a factor in accident rates.

The EBT Accident-Incident Study shows that manual aircraft control was a factor in 52% of all fatal accidents. In addition, manual aircraft control was a factor in 84% of accidents and serious incidents having a high probability of mitigation through training. The importance of manual aircraft control as a factor is increasing proportionally in the total number of accidents and serious incidents.

According to reports derived from LOSA data, observed manual aircraft control errors are revealed in adverse weather and turbulence, and with demanding and challenging ATC clearances. Pilots need to be able to confidently control the flight path without automation, understanding when and how to revert to manual flight. [Automation Training Practitioners' Guide (Lyall)]



Errors in manual aircraft control are the most frequently cited failures in flight crew performance, according to the IATA Safety Report/Accident Study. Manual aircraft control is the preeminent flight crew error, according to the IATA Safety Report/Accident Study. The top Undesired Aircraft State (UAS) in the same report is "Improper Landing", which has within it manual aircraft control elements. Industry comments from the report indicate the need to reinforce manual aircraft control skills and note that pilots are reluctant to revert to manual flight. Procedures not routinely flown present the greatest difficulty to crews and manual aircraft control is a key contributor to this, according to training data from ATQP.

The LOSA error management report indicates that pilots detect only around 40% of aircraft handling errors. In the case of self-detection, commanders detect 39% of handling errors of their first officers but only 9% of their own.

Degradation of manual aircraft control skills of pilots who use automation frequently, or who primarily fly very long sectors, is a concern, according to an FAA 1996 report.<sup>1</sup> Runway excursions accounted for almost 30% of all fatal accidents from 2000-2010, most included a manual aircraft control factor. This amounted to a 12% increase in fatal accidents classified as runway excursion compared to the previous decade. [Accident Study using augmented CAST data]

Skill decay/retention reports indicate that skill decay is currently not an issue in retaining manual flying skills. While this could be considered paradoxical, the manual skills required to execute maneuvers as part of maneuver validation, or skill test are resistant to decay but that test is given a vacuum of realism, with no attendant distractions or environmental challenges. The question of how good these skills are and how resistant to decay they are when required in a complex and dynamic situation is difficult to measure. However, there are indications from data to support the fact that manual handling is an increasing problem, when distracting factors, malfunctions and the environment draws pilot attention. This observation has to be considered in close relationship with indicated difficulties faced by pilots in the effective use of automation and the operator policies governing its use.

Automation has been the most important change in the operating environment of pilots in the last 30 years. There has been concern by many that manual aircraft control skills have decreased during this time. The evidence from the data is consistent with this concern.

Studies show that manual aircraft control is as important as always, with the attendant skills often being needed in unexpected and difficult situations.

#### 2.3 THE UNSTABLE APPROACH PARADOX

The unstable approach is addressed as follows: "While airline Standard Operating Procedures (SOP's) mandate a go-around if an approach is unstable, data indicates that landing from an unstable approach may be less risky." Landings that follow an unstable approach are usually uneventful. 97% of unstable approaches result in a landing, of which 90% are uneventful, according to the LOSA report. The EBT flight data analysis supports the LOSA results that in almost all cases (Approximately 98%) pilots land from unstable approaches as opposed to executing a go-around. Additionally, according to FDA when looking at the percentages of landings following unstable approaches versus stable approaches, the percentages of flights with FDA events do not differ significantly between the two categories of approaches.

To add to this, the go-arounds are not usually well performed. Results from flight data analysis show that a go-around from an unstable approach is almost twice as likely to produce FDA high severity risk events as one from a stable approach. [See Fig 2.3a] This result may underestimate the real risk because flight data analysis is not capable of detecting some excursions from the missed approach profile. Evidence from LOSA also indicates that a go-around is rarely performed without error.

<sup>&</sup>lt;sup>1</sup> FAA Human Factors team report 1996 on: The Interfaces Between Flightcrews and Modern Flight Deck Systems



Figure 2.3a

To summarize the paradox; pilots are expected to go-around from unstable approaches, but they usually do not; when they do go around: "the missed approach is rarely handled well by the crew". [LOSA]. In contrast, when landing from an unstable approach, they overwhelmingly do it "without issue" (90%) [LOSA]

This situation brings up various questions, such as:

- Why do pilots have difficulties with go-arounds?
- How serious are unstable approaches?
- Is landing really the best option from unstable approaches?

Looking firstly at the reasons why pilots have difficulties with go-arounds shows the following reasons:

- 1. A go-around is usually unexpected
- 2. Go-arounds rarely occur from the altitudes practiced in training
- 3. Go-arounds are usually performed with relatively low gross weight, at the end of a sector and with all engines operating.
- 4. Go-arounds performed in training are usually from defined approach minima without visual reference and with one engine inoperative.

The overall rate of go-arounds is very low in general, approximately 0.31%. [FDA] According to almost all airline SOPs, a go-around should occur every time there is an unstable approach, but in fact, it only occurs a very small percentage of the time [3% LOSA] [1.4% FDA]

The reasons why pilots continue unstable approaches to landing are as follows:

- 1. Failure to recognize deviations or to remember the stabilized approach criteria. [LOSA]
- 2. A belief that the aircraft will be stabilized shortly after the mandatory stabilization altitude. [LOSA]
- 3. PF/PM over reliance on each other to call excessive deviations or to call for a go-around. [LOSA]
- 4. Excessive confidence by the PM that the PF will achieve a timely stabilization before landing. [LOSA]
- According to the judgment by the pilot, the landing can be performed safely. [Pilot Survey per 82% of respondents]
- 6. Successful experience from previous landings reinforces continuation in an unstable state. [Multiple Sources]
- 7. Pilots are not routinely exposed to go-arounds in training except in routinely conducted exercises at expected altitudes. This is likely to produce a reluctance to execute the go-around maneuver due to lack of confidence when conditions are different from those for which they have been trained. [Confirmed by multiple data sources]
- 8. Both crewmembers seem willing to continue the approach even though it is unstable. [according to the LOSA report]
- 9. There frequently appears to be unspoken agreement between the crew that the approach will continue. This has been rationalized over time into normal behavior. [LOSA]
- 10. It is clear that the decision to continue is consciously and evidently made by both crewmembers, even if it is unspoken. [LOSA]

Looking at the flights with at least one event on landing, the profile is remarkably similar when comparing the sets of stable approaches and unstable approaches. (See figs 2.3b and 2.3c.) Surprising though it may be, it indicates that landings from stable approaches are not without problems and that eliminating unstable approaches will only partially solve landing problems

While the frequency of approaches with landing events is roughly the same as for stable and unstable approaches, (See Fig 2.3b and Fig 2.3c) data indicate that unstable approaches are more risky for both the subsequent landing or go-around if we look at the type of events that occur.



Figure 2.3b





Figure 2.3c

Even though the frequency of approaches with at least one landing events is approximately the same for stable and unstable approaches, data indicate that unstable approaches are more risky for the subsequent landing or go-around when we look at the event rate and severity of events that occur.

The all-event rate is higher, by a magnitude of 20% for landings and by a almost 60% for go-arounds. (See Fig 2.3c and Fig 2.3d)



Figure 2.3d





The event rate for landings is 140% higher for high severity events and 85% higher for go-arounds. (See Fig 2.3e and Fig 2.3f)



Figure 2.3f



Figure 2.3g

The event rate for the most dangerous landing events is 179% higher. (See Fig 2.3h)





After examining the landing and the go-around phases, we have a clearer picture of the associated risk. A subsidiary question naturally arises, about the quality of flight phases other than approach and landing in flights that have stable versus unstable approaches. According to flight data the overall event rate in those 'other' phases is approximately 20% higher for flights having unstable approaches and the severe event rate is 35% higher. (See Figures 2.3i and 2.3j)



Figure 2.3i





In summary, unstable approaches are endemic across the spectrum of aircraft operations, regions and types. However, landing problems are an important training topic for all types of approaches, keeping in mind that the frequency of high severity landing events is much more of a concern with unstable approaches. Given that the rate of flights with landing events is approximately the same for stable and unstable approaches, solving the unstable approach problem will not necessarily solve all landing problems. This is particularly concerning when we note that the ratio of stabilized approaches to unstable approaches is approximately 27:1.



Despite efforts to eradicate unstable approaches and to mandate a go-around when conditions require, the rate of occurrence remains significant. A major concern of unstable approaches is the disregard of the SOP's, in addition to the efficacy of threat and error management during the entire flight. According to the LOSA report, there is a "90% (SOP) violation factor" in terms of not executing a go-around from an unstable approach.

Unstable approaches are often a barometer for the flight itself. If an approach is poorly executed, there are strong indications that the rate of errors and risk events will be higher across the entire flight, according to FDA and LOSA. Data from multiple sources indicate problems with the go-around, because it is not usually expected, and may have to be executed under demanding environmental conditions, from altitudes other than those practiced in training, with all engines operating and necessarily often higher energy states. When unraveling the unstable approach paradox, one issue remained clear throughout: the flight crew clearly should be trained to confidently and effectively perform a go-around during the approach in almost any situation and condition.

#### 2.4 CATALYSTS IN THE COCKPIT

A catalyst is defined as an agent that provokes or speeds significant change or action. There are 2 types of catalysts: promoters and inhibitors. A promoter is a catalyst that accelerates and promotes a change or action; an inhibitor is a catalyst that slows or inhibits a change or action. As part of making assessments of the deployment of threat and error countermeasures, LOSA observers are asked to rate and comment on command leadership and the communication environment during the flight. The rating is completed on a 4-point scale: poor, marginal, good, and outstanding. The table below shows that flights with outstanding leadership and communication environment have on average 2.3 errors per flight versus an average 7.0 errors per flight for those with poor leadership and communication.

	LOSA Observer Ratings for Captain Leadership and Communication Environment			
TEM Indicator Average Number per Flight	Outstanding Leadership	Good/Outstanding Leadership	dership Poor Leadership	
	Outstanding Communication	Poor Communication	Poor Communication	
Threats	4.9	4.3	5.0	
Mismanaged Threats	0.3	0.7	1.1	
Errors	2.3	5.6	7.0	
UAS	0.4	1.4	1.8	

#### Figure 2.4

The flights with poor ratings have approximately 3 times as many mismanaged threats, errors and undesired aircraft states as a flights with outstanding leadership and communication environment, even though the number of threats is approximately the same for both categories of flights (4.9 versus 5.0 respectively). Looking at the chart it seems clear that both command leadership and outstanding communication are catalysts of the promoter type. It is also interesting to note that even when the command leadership is rated good or outstanding, a poor communication environment in the cockpit still produces a high rate of mismanaged threats, errors and undesired aircraft states.

These LOSA results highlight the value of effective working relationships in the cockpit and are reinforced by a study completed in 2001 by Lufthansa. According to an extensive study of AQP results, leadership is a competency that can be developed. The analysis further shows the growing importance of communication in the latest generation of aircraft, and how effective communication substantially mitigates risk in the cockpit. But even though the importance of effective communication in the cockpit is clear, the LOSA report indicates and 1996 FAA Automation Report stipulates: (there is... a lack of verbalization skills to share mental models particularly in regard to automation.")

In addition to these two positive catalysts, command leadership and communication, studies also determined the presence of a negative catalyst: intentional non-compliance. According to the LOSA Report: "there is a significant correlation between the number of intentional non-compliance errors observed on a flight and the number of mismanaged threats, unintentional errors, mismanaged errors, and undesired aircraft states". (See Figure 2.4a)

Intentional Noncompliance & TEM Indexes			
TEM Indicator	Flights with zero Intentional Noncompliance errors	Flights with one Intentional Noncompliance error	Flights with two or more Intentional Noncompliance errors
% of Flights in LOSA Archive	56%	24%	20%
Average number of threats per flight	4.4	4.7	4.8
Average number of errors per flight	1.9	3.7	6.6
% of flights with a mismanaged threat	23%	37%	50%
% of flights with a mismanaged error	27%	45%	65%
% of flights with an undesired aircraft state	25%	42%	59%

#### Figure 2.4a

The LOSA report states: "As the rate of intentional non-compliance increases, the rate of errors detected and acted on decreases." There is a negative correlation between the rate of non-compliance and the rate of errors detected and acted upon." That is to say that non-compliance is an inhibitor to detection and correction (i.e., multiplier in a negative sense). This is true across all error types".

Of the various intentional non-compliance error types, the higher rates generally occur with procedural errors. Commanders display significantly more non-compliance than first officers. Over 50% of checklist errors involve some form of intentional non-compliance. The vast majority of non-compliance checklist errors are attributable to the crew, only around 10% to external influences such as ATC. Almost half of all non-compliance checklist errors occur during pre-flight and taxi out, which may be related to on time performance pressures and distractions. There are multiple examples of high-risk situations exacerbated by non-compliance behavior, according to the LOSA Report, e.g., terrain, weather, traffic in addition to as well as approach and runway issues. Compliance issues are also highlighted in the IATA 2008/2009 accident reports. Furthermore, compliance is listed as one of the top 3 threats to safety according to the UK CAA CAP 776, "Global Fatal Accident Review 1997-2006". According to the EBT Pilot Survey on Training Effectiveness, 18% of respondents admit to deviating from checklists frequently and 21% of pilot respondents admit to deviations on virtually every flight.

One of the encouraging results from the EBT Accident Incident Study is that CRM has been improving over time. Compliance is not necessarily following this trend. Examining competencies as a percentage of accidents with high training effect over the last 15 years; deficiency in application of procedures according to published operating instructions was a factor in 49% of accidents. This evidence demands a change in compliance behavior of the flight crews by deliberate and focused attention during recurrent assessment and training in an EBT program.



## 2.5 SURPRISE

The element of surprise adds difficulty in dealing with any given situation. When determining the effect of surprise, it is important to clarify the meaning of the term, which in the context of this study denotes the appearance of something unexpected. It does not necessarily refer to a completely unforeseeable event (black swan), nor does it refer to physiological effects, typically referred to as 'startle;' although it is recognized that the emotional response to an unexpected event may be a factor in the crew's capability to handle it Pilots need to be provided with more opportunities to learn and practice, especially how to handle surprising situations according to the FAA Automation Report from 1996. Many abnormal situations that pilots encounter during normal operations are not addressed in training, according to the IATA Accident Classification Task Force (ACTF), These include automation surprises (sudden, slow, and subtle) as well as go-arounds from above DA/MDA. When examining the notion of surprise, it is important to analyze situation awareness, because the appearance of surprise can indicate the absence of situation awareness (SA), as pilots are by definition not necessarily anticipating and planning for those eventualities.

The later generations of aircraft present crews with sophisticated tools and displays to assist situation awareness, and so it seems counter intuitive, but in fact is the case, that these aircraft (generations 3 and 4) have a higher percentage of accidents where SA is a factor as opposed to aircraft with more primitive displays. Poor SA was noted to be present in a higher percentage of fatal accident than for non-fatal accidents. [EBT Accident-Incident study] In the set of accidents that were rated highly preventable by training, the presence of the SA problems occurred in over 41% with an increasing trend over the last 15 years. [EBT Accident-Incident study] Situation Awareness include vulnerabilities in automation mode awareness, flight path awareness including insufficient terrain awareness, energy awareness (especially low energy state) [FAA Automation Report 1996]. Traditional training and checking do not usually address the element of surprise.

#### 2.6 PRIORITIZATION OF TRAINING TOPICS

Prioritization of the training topics is probably the most important result from the EBT data analysis. It is a key part in the process for translating data into useful events and scenarios to assess and develop pilot performance in recurrent training programs. This result is the first rigorous attempt to rank parameters such as, threats, errors, competencies, along with factors affecting accidents and serious incidents, from multiple data sources systematically to formulate a recurrent training program.

The exercise shows the feasibility of collecting an adequate set of operational and training data; developing the necessary methods to analyze that data, while corroborating results to produce a criticality ranking of training topics. The prioritization process occurs for each of the 6 generations of aircraft by ordering critical parameters so as to highlight differences and commonality. There is sufficient flexibility in the process to allow enhancement according to mission, culture and type of aircraft. The data in the process is also used as material to build scenarios for use in recurrent assessment and training in an FSTD qualified for the purpose according to the Manual of Criteria for the Qualification of Flight Simulation Training Devices (Doc 9625), Volume I Aeroplanes.

The process used is transparent and repeatable and results in a unique prioritization, according to aircraft generation. Three levels of priority A, B and C, with A having the highest priority, were used to determine the frequency of pilot exposure to the defined training topics within a 3-year rolling recurrent training program.



Most data referred to in this report have been analyzed and are contained within the Evidence Table, and the EBT Accident and Incident Study. The Evidence Table consists of data from multiple sources and has the capability to sort as well as corroborate analytical results. It represents a robust set of evidence and it is a primary tool used in determining results. The EBT Accident Incident Study has 3045 reports feeding the analysis, making it comprehensive as well as sensitive in developing prioritization of results and discriminating by aircraft generation. Prioritization of training topics by generation uses both of these tools. In some cases, depending on the data, the assessment and training topics are drawn from both sources, in some from the Evidence Table alone, and in some from the Accident Incident Study alone. While the prioritization itself results from an algorithmic process, all analytical results were provided to the EBT Project Group comprising training experts and professionals in training scenario creation. Their utilization of the results served as an experiential validation.

Any set of historical data is necessarily finite. Using these data assumes that a large set of experience will have strong predictive validity even though the environment is constantly changing. These challenges were accepted because statistical and quality control principles were adhered to and more importantly, the results from data analysis were applied in the context of professional experience and expertise. For the creation of the EBT recurrent training program defined in this manual, a cautious approach was taken, and frequency of training suggested is equal to or higher than the results suggest unless the corroborating data is very strong. An example of this could be illustrated in the EBT Accident and Incident Study where the data imply different training frequency in adjacent generations. If the data are quite strong in the generation that demands more training, the training category in the adjacent generation is upgraded.

Operational and training data from multiple sources indicate that pilots operating the more modern generation aircraft take less time to achieve competence in the performance of certain maneuvers. Modern generation aircraft are also more complex, and pilots have more to learn in achieving a defined level of competency to operate. While the number of assessment and training topics is slightly fewer in early aircraft generations; the training time in the FTSD should be largely the same.

#### 2.7 SUMMARY OF MAJOR FINDINGS

It is important to note that these major findings are simply a small part of the results, and that further results are detailed in Chapter 4, where there are many opportunities to make additional inferences. The Evidence Table contains over 300 evidential statements that clearly indicate and demonstrate a need for change in the regulation of flight crew training. In addition, they reveal a disconnection between existing training content and the reality of exposure to events in flight operations.

An underlying hypothesis of EBT is that there is a set of competencies that span the capabilities needed by flight crews in operations. This notion is supported by the analyses in this report. Competency issues rank very highly on the relative risk scale when analyzed over accidents and incidents. Competencies were almost always judged as being deficient in any accident or incident that was classified as being possible to mitigate by improvements in training.

There are significant aircraft generational differences in the flight phases of accident occurrence, e.g., Ground and Landing phases are the two most significant flight phases for accidents in Generation 4 Jets, but for Generation 3, the Take-Off phase is particularly critical. Approach is the most significant phase for Generation 2 aircraft. Engine failure ranks as the fourth priority for Generation 2 Jets, and seventeenth for Generation 3 and 4 Jets.



Clear trends were established, for example, the **need for training** becomes more and more critical according to several interesting trends:

- Firstly, as the severity of the accidents increase (i.e., in each generation High training effect is substantially higher for fatal accidents).
- Secondly as the generations become newer and the design and reliability improve. (fig 2.7)



Figure 2.7

While the results of this study are in most cases not surprising, they are compelling when considered as a whole. It is clear that the current framework of regulated training requirements, usually based on an oversimplified view that replicating the same set of events and maneuvers, does not meet the need for pilots to maintain competence in modern air transport operations, nor does it prepare pilots for the challenges that they face in operations today.

Additionally we must:

- 1. Assess performance differently, and continue to develop and train, thereby maximizing learning throughout a pilots career.
- 2. Build upon the identified pilot core competencies to deal with much more than the simple maneuvers and standardized events used in checking and training today.
- 3. Understand and measure the factors, which contribute towards pilot performance, in order to develop and improve systematically, as well as determine the effectiveness of remediation in training through the EBT system.

There are many sources of data utilized in this study. Managing this volume of data was challenging and rewarding at the same time. In most cases results from independent sources relating to key topics showed consistent convergence.

While the process, analysis and findings represent an excellent beginning; a more comprehensive and structured use of pilot and instructor expertise is critical to the data gathering and analytical process. With any data source, there are always gaps between the information sought and what is available. The only exception to this comes from the professional experience of our flight crews within the system.

This EBT data report represents a big step in the process of making pilot training much more relevant to today's needs. However, the analysis must be updated on a continual basis as more information becomes available and the aviation system itself continues to evolve.

Intentionally blank



# **3 METHODOLOGY**

#### INTRODUCTION

This chapter describes in detail the methodologies applied during the analysis of each data source as well as the process that combines the data from various sources into meaningful results with respect to training. There are many graphical examples. The examples are intended to describe the methodology, and should not be used as excerpts of data analyzed. Source data is contained within the appendices, which should always be considered as the primary reference for any conclusions and findings.

#### 3.1 LOSA STUDY

#### 3.1.1 Objective

The objective of the LOSA Study for EBT is to provide a listing of systemic and pilot performance issues gathered from the LOSA Archive of over 9000 observations across 45 airlines around the world. The study identifies pilot performance issues according to both risk and the potential for mitigation through FSTD based recurrent training. The insight gained from the LOSA Study provides the EBT focus group with a unique contextual perspective of flight crew performance collected from the cockpit during normal operations. Findings provided from the study complement the findings from analyses of other data sources.

#### 3.1.2 Background

LOSA data is collected using the Threat and Error Management (TEM) framework. The LOSA Collaborative conducted a research study designed to highlight 10 areas of pilot performance, agreed between the LOSA Collaborative and the EBT Data Sub-group. Each target is supported with aggregated LOSA/TEM results and excerpts from de-identified observer narratives. Additionally, the LOSA collaborative provided a supplementary report on error detection. (See Appendix 1 for copies of the LOSA reports.)

All notable, specific evidentiary results were taken from the study and entered into the Evidence Table. (See Appendix 12 for the Evidence Table.)

#### 3.1.3 Strengths and Weaknesses of LOSA

Pilot behavior can be influenced by the presence of an observer. While this can be considered a weakness, the LOSA collaborative employs strict protocols in selection, training and operational guidance to observers in order to minimize bias emphasizing standardization, neutrality and objectivity.

The LOSA methodology enables the determination "what happened" in addition to detailed contextual data, recorded according to defined standardized parameters. This provides deeper insight and some indications of "why it happened". This strength comes from direct observation. The method provides a comprehensive insight into line operations as any data method in use today. Analysis of the LOSA database can be targeted and the EBT data study uses this focus to provide insight in the data analysis.

# 3.2 EBT ACCIDENT - INCIDENT STUDY

The accident incident analysis conducted by the EBT data subgroup is a two-stage analysis. The first stage involved reading the accident and incident reports by qualified pilot analysts to determine which factors and/or competency issues were involved in the accident or incident. Additionally, the analysts were asked to rate the degree to which improved training may have mitigated the results of the accident or incident. This general process was repeated by a second analyst for quality control and resulted in a spreadsheet for each individual type of aircraft analyzed. See Appendix 3 for the set of guidance provided for the analysts and figure 3.2.1.6 for an example of the spreadsheet.

The second stage of the study was based on the results of the first stage and involved analysis globally and individually within the 6 generations of aircraft. The process resulted in the prioritization of training topics by training criticality from a generational perspective, using the dimensionality of risk, clustering, and effectiveness of training.

#### 3.2.1 Stage 1

#### 3.2.1.1 Background

The NTSB database was used as the primary source of accident reports. The following western built aircraft types were considered:

- 1. Turbojet aircraft certified in accordance with CS-25 or FAR-25 with a seating capacity of 50 or more.
- 2. Turbo propeller aircraft certified in accordance with CS-25 or FAR-25 with a seating capacity of 30 or more.
- 3. 3045 accidents and incidents were considered over a period from 1962 up to 2010. Reports in this targeted group were omitted from the analysis if they were considered incomplete. Approximately 4% of the reports catalogued by the NTSB in our targeted category were not analyzed for this reason. If the report contained creditable and useful information to determine relevant factors it was used. In some of the cases the NTSB was not the investigating authority of record. In those cases, the official report or references to the official report were used.
- 4. Approximately 2600 jet aircraft and approximately 350 turbo propeller driven aircraft events were analyzed. Figure 3 below is the list of aircraft by generation. There are six defined aircraft generations, four applicable to jet aircraft and 2 applicable to turbo propeller aircraft.
- 5. Most aircraft in figure 3.2.1.1 were analyzed, but some aircraft types had almost no data available data or a qualified analyst was not available. This was particularly the case with very old aircraft.

Aircraft by Generation		
Generation 4 Jet	A318/A319/A320/A321, A330, A340-200/300, A340- 500/600, B777, A380, B787, A350, Bombardier C Series, Embraer E170/E175/E190/E195	
Generation 3 Jet	A310/A300-600, B737- 300/400/500, B737- 600/700/800 (NG), B757, B767, B747-400, B747-8, B717, BAE 146, MD11, MD80, MD90, F70, F100, Bombardier CRJ Series, Embraer ERJ 135/145	
Generation 3 Turboprop	ATR 42-600, ATR 72-600, Bombardier Dash 8 Q Series	
Generation 2 Jet	A300 (except A300-600), BAC111, B727, B737- 100/200, B747-100/200/300, DC9, DC10, F28, L1011	
Generation 2 Turboprop	ATR 42, ATR 72 (all series except -600), Embraer EMB- 120	
Generation 1 Jet	DC8, B707	

Figure 3.2.1.1

Aircraft Generations Analyzed in Accident		
and Incident Study		
Generation 4 Jet	Airbus A319, Airbus A320, Airbus A321, Airbus A330, Airbus A340, Boeing 777, Embraer 170/190	
Generation 3 Jet	Airbus A300-600, Airbus A310, Boeing 737-300,400,500,600,700,800, Boeing 747- 400, 800, Boeing 757, Boeing 767, Embraer ERJ 135/145, McDonnell Douglas MD-80 Series, McDonnell Douglas MD-11	
Generation 3 Turboprop	Bombardier Dash 8, British Aerospace Jetstream ATP, Embraer 120, Fokker F-27, SAAB 340	
Generation 2 Jet	Airbus A300, Boeing 727, Boeing 737- 100, 200, Boeing 747-100, 200, 300, McDonnell Douglas DC-9, McDonnell Douglas DC-10	
Generation 2 Turboprop	ATR 42, ATR 72, British Aerospace Jetstream 41, Convair 580/600 Series, De Havilland DH7, Fairchild-Dornier 328, Fokker F-27, Shorts SD330/360	
Generation 1	Boeing 707	

Figure 3.2.1.1a

The data sample of accidents and serious incidents analyzed is highly representative of Aircraft Generations 2, 3 and 4, both for jets and turbo propellers as applicable.

Only the B707 was analyzed in Generation 1. Because there are very few remaining in operation, the effect on the analysis is minimal. Generation 1 was only analyzed in stage 1 and its value lies in providing historical contextual reference.

A total of 27 pilot-analysts participated in stage 1 of the study. The analysts chosen were pilots currently or previously qualified on the relevant type. The only exception to this was for several Generation 2 turboprop types, where it was not possible to find type qualified pilots. In these few cases, experienced analysts on similar types from the same generation were used. Work done by the volunteer pilot analysts was extensive. The group worked in excess of 2,000 man-hours reading and analyzing accident and incident reports.

The NTSB database provided a convenient template for defining the database of accidents and incidents to be analyzed because of its large size, but wherever possible the report from the primary investigating authority was used to determine the necessary information for the analysis.

The NTSB classified approximately 50% of events analyzed as serious incidents, the remainder being accidents, 17% of which were fatal and 83% non-fatal.



#### 3.2.1.2 Description of the Method – Factor Analysis

For the purpose of this study, a factor is defined as a condition affecting an accident or incident with which the flight crew had to cope. The criterion for inclusion in the analysis was if a factor was mentioned directly in the report or if in the analysi's expert opinion the report logically implied the presence of a factor.

The accident-incident study is a factor analysis, consisting of the recording of factors related to the event. These factors may or may not be considered directly causal but should be relevant to the event.

The factors were originally defined in the Training Criticality Study by the EBT working group and can be described in character as threats, errors and "end-states" with the potential to become the focus of FSTD based training. These same factors were used in the EBT Accident-Incident Study enabling statistical correlation between the risk rankings for each study.

There are 40 factors and they are listed in figure 3.2.1.3.

A factor was noted if it was relevant to the event for the following reasons:

- 1. It was specifically listed in the report, or described with sufficient accuracy to be deemed present and relevant by the pilot analyst, without undue inference.
- 2. The factor may or may not have been causal; but it existed during and was relevant to the event.
- 3. The crew needed to manage or mitigate the factor.

Factor analysis is used to determine the distribution or frequency of factors occurring in accidents and incidents. (See Appendix 2 and 3)

#### 3.2.1.3 Factors used in the Analysis

Factors in EBT Accidents and Incidents Study		
Ground Equipment	Runway Incursion	
Ground Maneuvering	Poor Visibility	
Runway/Taxi Condition	Upset	
Adverse Weather/Ice	Wake Vortex	
Windshear	Terrain	
Crosswind	Birds	
Air Traffic Control	Engine Failure	
Navigation	Minimum Equipment List	
Loss of Communications	Fire	
Traffic	System Malfunction	
Operation/Type Specific	Crew Resource Management	
Cabin	Physio	
Compliance	Workload Distraction Pressure	
Deficiency in Manuals	Manual Aircraft Control	
Deficiency in Operational Data	Dangerous Goods	
Deficiency in Charts	Loading, Fuel, Performance	
Deficiency in Check Lists	Mismanaged-AFS	
Deficiency in Data Bases	Mismanaged Aircraft State	
Deficiency in Procedures	Mismanaged System	
Fatigue	Pilot Incapability	

Figure 3.2.1.3

#### 3.2.1.4 Competencies

All incident and accident reports were further analyzed to determine whether an area of competency was in some way reported as an issue and contributory to the event. For the purposes of the study, 9 competencies (technical and non-technical) were considered and they are listed and described in figure 3.2.1.4. Analysts were restricted to note only the 2 most important non-technical competencies in the report. That restriction was lifted for the technical competencies for which any deficiency could be noted. The reason for the restriction is the overlapping nature of non-technical competencies, leading to a tendency to over assign them. By limiting the number available in each event the analysts tended to be more careful in the selection process.

**Note:** The competencies listed in figure 3.2.1.4 were used for the accident and incident analysis. There have subsequently been some changes to this, which are reflected in ICAO Doc 9995 Manual of EBT.

## Methodology



Competencies			
		Competencies	
Competency	Competency Description	Performance Indicator – Observable Behaviour	
		Follows SOP's unless a higher degree of safety dictates otherwise	
Demonstrates the	Applies procedures	Identifies and applies all (operating instructions) in a timely manner	
application of procedures	operating instructions	Safely manages the aircraft to achieve best value for the operation, including fuel, the environment.	
		passenger comfort and punctuality	
		Knows what, when, how much and with whom he or she needs to communicate	
	Demonstrates effective use of language, responsiveness to feedback and that plans are stated and ambiguities resolved.	Ensures the recipient is ready and able to receive the information	
		Checks that the other party has the correct understanding when passing important information	
Demonstrates effective		Listens actively, patiently and demonstrates understanding when receiving information	
communication		Asks relevant and effective questions, and offers suggestions	
		Uses appropriate body language, eye contact and tone, and correctly interprets non-verbal	
		Is receptive to other people's views and is willing to compromise	
Domonatratas offective	Demonstrates proficient	Knows how and when to use flight management system(s), guidance and automation	
flight path management.	and appropriate use of	Demonstrates correct methods for engagement and disengagement of auto flight system(s)	
through proper use of	flight management	Demonstrates appropriate use of flight guidance, auto thrust and other automation systems	
flight management	system(s), guidance and automation including transitions between modes, monitoring, mode	Reverts to different modes when appropriate	
system(s), guidance and		Detects deviations from the desired aircraft state (flight path, speed, attitude, thrust, etc.) and takes	
automation		appropriate action	
	Demonstrates knowledge	Demonstrates practical and applicable knowledge of limitations and systems and of their interaction	
Demonstrates	and understanding of	Demonstrates required knowledge of published operating instructions	
knowledge	operating instructions, aircraft systems and the	weather, airports and the operational infrastructure	
J. J		Demonstrates knowledge of and compliance with applicable legislation.	
	operating environment.	Knows where to source required information	
		Agrees with and is clear about the team's objectives and the crew members' roles	
		Uses initiative, gives direction and takes responsibility when required	
Demonstrates leadership	Uses appropriate authority	Anticipates other crew members' needs and carries out instructions when directed	
and teamwork	task. Supports others in completing tasks.	Is open and honest about thoughts, concerns and intentions	
		Gives and receives both criticism and praises well, and admits mistakes	
		Demonstrates empathy, respect and tolerance for other people	
		Involves others in planning and allocates activities fairly and appropriately according to abilities	
	Maintains control of the	Demonstrates manual aircraft control skills with smoothness and accuracy as appropriate to the situation	
Demonstrates manual	aircraft in order to assure the successful outcome of a procedure or manoeuvre.	Detects deviations through instrument scanning Maintains share mental capacity during manual aircraft control	
aircraft control		Maintains spare mental capacity during manual ancian control Maintains the aircraft within the flight envelope	
		Applies knowledge of the relationship between aircraft attitude, speed and thrust	
		Identifies and verifies why things have gone wrong and does not jump to conclusions or make uninformed	
	Detects deviations from the desired state, evaluates problems, identifies risk, considers alternatives and selects the best course of action. Continuously reviews progress and adjust plans.	assumptions	
		Perseveres in working through a problem	
Demonstrates effective		Uses or agrees to an appropriate decision making process	
decision making		Applies essential and desirable criteria and prioritizes	
Ŭ		Considers as many options as practicable Makes decisions when needed, reviews and changes them if required	
		Considers risks but does not take unnecessary risks	
		Improvises appropriately when faced with unforeseen circumstances to achieve the safest outcome	
	Has an awareness of the aircraft state in its environment; projects and anticipates changes.	Is aware of what the aircraft and its systems are doing	
		Is aware of where the aircraft is and what its environment is	
Demonstrates situation		Is aware of the condition of people involved in the operation including passengers	
awareness		Recognises what is likely to happen, plans and stays ahead of the situation	
		Develops "what if" scenarios and plans for contingencies	
		Identifies threats to the safety of the aircraft and people, and takes appropriate action	
	Prioritises, delegates and receives assistance to maximise focus on the task. Continuously monitors the flight progress.	Is calm, relaxed, Careful and not impuisive Prenares, prioritises and schedules tasks effectively	
		Uses time efficiently when carrying out tasks	
Demonstrates effective		Offers and accepts assistance, delegates when necessary and asks for help early	
workload management		Reviews, monitors and cross-checks actions conscientiously	
		Follows procedures appropriately and consistently Ensures tasks are completed	
		Manages interruptions, distractions, variations and failures effectively	

Key

Technical

Non-technical

Figure 3.2.1.4

#### 3.2.1.5 Training Effect

Training effect is considered as the potential effect of FSTD training in preventing the accident or incident from occurring or mitigating the severity of the event, on a 5-point scale, as follows:

- U Unknown
- N No effect
- L Low effect
- M Medium effect
- H High effect

#### 3.2.1.6 Summary of Parameters in the Report Analysis

Other parameters were recorded for analysis in the EBT report as follows:

- 1. Date
- 2. Severity of event (fatal, non-fatal or serious incident)
- 3. Phase of flight
- 4. Aircraft generation
- 5. Location
- 6. Region of the world
- 7. Aircraft type
- 8. Competencies
- 9. Training effect

See Fig 3.2.1.6 for an excerpt sample of the analysis matrix. (See Appendix 3 for a full representation accident-incident analysis including the entire analysis matrix.)



Figure 3.2.1.6


# 3.2.1.7 Quality Control

In order to achieve consistency and standardization across stage 1 of the analysis, two different pilot experts independently analyzed each accident or incident. The first analysis was conducted by a pilot currently or previously qualified on the aircraft type (the analyst), the second was conducted by a pilot (the checker) qualified on type, or on an aircraft of the same generation. Any discrepancy between the first and second analysis was noted, then reconciled by a separate team of 3 pilots, at least 2 of which working together to reconcile the differences. The reconciliation team was limited to the same 3 pilots for the entire study.

### 3.2.1.8 Strengths and Weaknesses

Accident analysis has been the bedrock of safety analysis for a very long time, providing the context and framework for all other safety analysis and reporting. The NTSB database consists of an extensive collection of accidents and incidents spanning 60 years, providing historical perspective and trending data over time, thereby enabling dimensional comparisons across generations of aircraft. It is the largest single source of this kind of data. The biggest strength of accident and incident type of data is its relevancy to safety and training (i.e., evidence based training in a pure sense). The substantial amount of data over an extended period provides, in most cases, statistical significance in terms of frequency and risk. A large sample such as this was considered necessary in order to provide a sufficient data source for factor analysis.

The biggest weakness in accident-incident reports is the inconsistency and lack of standardization of reports. Older reports lack information on human factors as well as factors that were relevant but not judged as causal. While the NTSB database is the largest collection of accident and incident reports, a number of accidents outside North America are not included.

The search for direct and final causation means that some underlying factors are missing from reports.

In order to obtain realistic values from analysis, a large number of events are needed. Conversely if the events sample size is small, the usefulness of the analysis diminishes. When 'drilling down' the data sample can become small very quickly with a resulting impact on reliability, so that in-depth analysis for specific factors must be done very carefully by re-reading source reports, itself a very time consuming process.

The factor analysis is primarily statistical in nature, but whenever the result could be questioned for consistency, or there was a need for additional information, a "drill down" was accomplished.

Aircraft A	nalyzed in EBT Accident and Incident Study
Generation 4 Jet	Airbus A319, Airbus A320, Airbus A321, Airbus A330, Airbus A340, Boeing 777, Embraer 170/190
Generation 3 Jet	Airbus A300-600, Airbus A310, Boeing 737-300,400,500,600,700,800, Boeing 747- 400, 800, Boeing 757, Boeing 767, Embraer ERJ 135/145, McDonnell Douglas MD-80 Series, McDonnell Douglas MD-11
Generation 3 Turboprop	Bombardier Dash 8, British Aerospace Jetstream ATP, Embraer 120, Fokker F-27, SAAB 340
Generation 2 Jet	Airbus A300, Boeing 727, Boeing 737- 100, 200, Boeing 747-100, 200, 300, McDonnell Douglas DC-9, McDonnell Douglas DC-10
Generation 2 Turboprop	ATR 42, ATR 72, British Aerospace Jetstream 41, Convair 580/600 Series, De Havilland DH7, Fairchild-Dornier 328, Fokker F-27, Shorts SD330/360
Generation 1	Boeing 707

Figure 3.2.1.1a (duplicate)

# 3.2.2 EBT Accident-Incident Study – Stage 2

### 3.2.2.1 Purpose

The purpose of the stage 2 analyses is to utilize results from stage 1 to analyze accidents and incidents in each aircraft generation and across all generations.

### 3.2.2.2 The Master File

Stage 2 analyses are completed in one master file unlike stage one where the analysis is done in individual files for each type. The master file is created by integrating files from the analysis of different aircraft types from stage 1. The analysis for a specific generation could only be carried out after all the aircraft types for that generation had been through the stage 1 process.

Files from each aircraft generation are integrated into the master file as they became available. Each row in the master file represents one accident or incident (event).



Columns of the master file contain the following data for each event from the Stage 1 analysis:

- 1. Date
- 2. Severity class (fatal accident/non-fatal accident/incident)
- 3. Active link to the event narrative in the NTSB database
- 4. Phase of flight during which the accident occurred
- 5. Generation of aircraft
- 6. Location of accident Region
- 7. Aircraft type
- 8. Factor one for each of the 40 factors defined [Ref Figure 3.2.1.3]
- 9. Competencies one for each of the 9 Competencies defined [Ref Figure 3.2.1.4]
- 10. Training effect

[See Figure 3.2.1.6 for an example or Appendix 1 Core Analysis Matrix Stage 1]

In order to accomplish the stage two analyses, 6 additional parameters are studied, adding 6 columns as follows:

- 1. Year of event (directly derived from the event date)
- 2. Column indicating whether the event took place within the last 15 years or not
- 3. The decade of the event
- 4. Event Identification number
- 5. Sum of Factors present in the event. This helped in calculating the Clustering tendency of each factor and to make integrity checks on the Master File.
- 6. Sum of competencies present in the event, for same reasons as 5 above.

(See Figure 3.2.2.2 for an example)

		Ac	cidents l	Info					TI	hreats and	l Erro	rs							Compe	encie	es						Stag	je Two Par	ameters			
Date	Fatal Non-Fatal Incidents	Link	Phase	Gen	Region	Туре	Ground equipment	Ground maneuvering	Rurway/Taxi Condition		Mis-AFS	Mis A/C State	Mis-Sys	Pilot Incap	Communication	SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control	Improved Training	YEAR (nb)	Last 15 Y	Decade	wo blanks	YEAR (text)	Event ID number	nb of Factors	nb of KSAs
05/09/04	N	Proba	LDG	P3	NA	ATR72								_					1				1	Н	2004	Last 15 Y	2000	5/9/2004	2004	2554	1	2
08/06/05	F	Proba	CRZ	P3	EUR	ATR72													1	2				Ν	2005	Last 15 Y	2000	8/6/2005	2005	2557	3	0
04/28/07	N	Proba	DES	P3	NA	ATR72													12	2				N	2007	Last 15 Y	2000	4/28/2007	2007	2558	1	0
03/01/03	N	Proba	CRZ	P3	NA	ATR72				Note: For								<u> </u>	$\sim$	$\sim$				N	2003	Last 15 Y	2000	3/1/2003	2003	2559	1	0
02/08/03	N	Proba	GRD	P3	NA	ATR72				this								<u>(</u> )		10				N	2003	Last 15 Y	2000	2/8/2003	2003	2560	1	0
11/20/00	N	Proba	DES	P3	NA	ATR72				example,					1	- 6	$\sim$	$\sim$	~					M	2000	Last 15 Y	2000	11/20/2000	2000	2561	2	2
03/10/00	N	Proba	CRZ	P3	NA	ATR72				33 factors					-0		14	$\Delta h$						N	2000	Last 15 Y	2000	3/10/2000	2000	2562	1	0
12/01/98	N	Proba	DES	P3	NA	ATR72				removed				~	7	0	$\square$	Š.					1	M	1998	Last 15 Y	1990	12/1/1998	1998	2563	1	1
10/31/94	F	Proba	CRZ	P3	NA	ATR72				remoted.			0	10			3							н	1994	Older	1990	10/31/1994	1994	2569	6	0
06/04/93	N	Proba	CLB	P3	NA	ATR72						1	ЦL	11	$\sim$	SY.			1					н	1993	Older	1990	6/4/1993	1993	2571	3	2
04/20/09	N	Proba	GRD	P3	NA	DHC8	1	1				2	Б.											н	2009	Last 15 Y	2000	4/20/2009	2009	2574	3	1
02/12/09	F	Proba	APR	P3	NA	DHC8					1	2		2						1	1		1	н	2009	Last 15 Y	2000	2/12/2009	2009	2575	7	3
02/03/08	N	Proba	DES	P3	NA	DHC8						14	$p^{\nu}$											L	2008	Last 15 Y	2000	2/3/2008	2008	2577	1	0
01/31/07	N	Proba	DES	P3	NA	DHC8						0	_											L	2007	Last 15 Y	2000	1/31/2007	2007	2578	1	0
08/29/05	N	Proba	GRD	P3	NA	DHC8		1																N	2005	Last 15 Y	2000	8/29/2005	2005	2579	1	0
01/08/03	N	Proba	APR	P3	NA	DHC8																		N	2003	Last 15 Y	2000	1/8/2003	2003	2583	2	0
10/14/02	N	Proba	APR	P3	NA	DHC8																		L	2002	Last 15 Y	2000	10/14/2002	2002	2584	2	0
03/06/01	N	Proba	APR	P3	NA	DHC8				1														Ν	2001	Last 15 Y	2000	3/6/2001	2001	2587	2	0
10/06/99	N	Proba	CRZ	P3	NA	DHC8				1														Ν	1999	Last 15 Y	1990	10/6/1999	1999	2589	1	0
09/27/98	N	Proba	APR	P3	NA	DHC8	1											1		1				L	1998	Last 15 Y	1990	9/27/1998	1998	2590	1	0

Figure 3.2.2.2

# 3.2.2.3 Methodology for Analysis

Demographics of the data set are considered, in order to determine the opportunities and limitations of the analysis

- 1. **Time** is an important parameter for charting the evolution of accidents and incidents and understanding the most critical factors for consideration in training today. In addition to sorting data by decades, events are divided into 2 intervals, the last fifteen years and the preceding 35. Several important studies, including the FAA Automation Report, the UK CAA Accident Studies (CAP 776 & 780) and other safety studies in the meta-analysis, focus on changes in safety and training during the last 15 to 20 years.
- 2. Severity, a component of risk, classified in terms of fatal accidents, non-fatal accidents and incidents.
- 3. Flight phases as they vary in the types of demands on flight crews.
- 4. **Regional distinctions** enable a regional geographical perspective.
- 5. **Training Effect** is an important dimension as it can be a measure of how effective potential training can be in mitigating accidents and incidents. Just as importantly, in this study it is used to sort the data set itself such that the competencies, factors, generations can be viewed in terms of training effectiveness.

Data is normalized in two ways in the stage two analyses:

- 1. The percentages of all accidents, fatal accidents, and incidents for each generation. This is important as it shows the frequency of factor occurrence within each generation of aircraft indicating likelihood, a component of risk that is one of the dimensions of Training Criticality, which is subsequently calculated.
- 2. Normalizing by 1M TOs (1 million take-offs) relates to a more universal and comparable reference. It is useful in showing trends across aircraft generations (and/or time periods.) It also has the notion of probability: i.e., what is the probability within a certain time interval and/or generation of encountering an accident with a particular factor.

Examining the ranking of factors with all the dimensions listed above for each of the 6 generations creates 2x3x9x8x6=2592 charts. In addition, ranking by factor is only one aspect of the data analysis. After experimenting for some time with what could be the most informative ways to look at the data, the following views were chosen to be the standard set for each aircraft generation

### 3.2.2.4 General View of Accidents and Incidents

In this section all accidents, fatal accidents and/or incidents are broken down by decades in terms of:

- Generations
- Raw numbers
- Percentage of occurrences
- Rate of occurrences (per 1 million Take-offs)
- Flight phases

The following figures are some examples of these partitions of the EBT accident incident database to demonstrate the steps of the analysis; a more complete breakdown for each generation occurs in Chapter 4 Analysis and Appendix 2:

1. The first illustration (fig 3.2.2.4) shows the actual raw number of accidents and incidents by generation per decade from 1960 to 2010. This allows a basic look at which aircraft generations dominate the safety scene and a general look at the historical trends.





Figure 3.2.2.4

2. The next chart (fig 3.2.2.4a) shows all accidents (Fatal and Nonfatal) divided by generation in percentages per decades from 1960 to 2010. The breakdown here is similar to the previous graph except that it is normalized by percentages and only refers to accidents.





3. Figure 3.2.2.4b denotes the number of accidents (Fatal and Non fatal) for each flight phase by decade.



Figure 3.2.2.4b

4. Figure 3.2.2.4c shows the same breakdown of the data except as an accident rate (normalized per 1 million take-offs).

5.





### 3.2.2.5 View of Accidents Historically and by Phase of Flight

When looking at accidents as evidence for training from a historical perspective, more recent occurrences tend to be more useful for training criticality analysis than the older accidents. However, the older period does provide a good measure for comparison. Interestingly when splitting the EBT accident database into two equal parts, the corresponding time periods turn out to be the last 15 years and the previous 33. The next set of illustrations show some examples providing a breakdown of the above two time periods by aircraft generation in terms of phases of flight and:

- Number of accidents (all accidents and fatal only)
- Percentage of accident occurrence (all accidents and fatal only)
- Proportion of factors involved



These few examples demonstrate the type of analyses performed; the values and the inferences will be looked at more closely in the next chapters with a more complete breakdown and exhaustive case review. The purpose of the graphs in this chapter is to exemplify methods and process.



Figure 3.2.2.5 - Example Gen 2 Jet

**Note:** Breakdown is number of fatal accidents per phase of flight in the last 15 years for a specific generation.



Figure 3.2.2.5a - Example Gen 3 Jets

The breakdown in figure 3.2.2.5 is percentages of all accidents per flight phase for a specific generation. Additionally proportionality of factors depicted by color. Notice the sum of the bars exceeds 100%, since each accident normally contains more than one factor.



Figure 3.2.2.5b – Example Gen 3 Jets – Previous time period

The next chart (figure 3.2.2.5c) shows an alternate view (i.e., complete percentage breakdown of factors in each phase) to better highlight the dominating factors in each phase. In this calculation each bar represents the proportion of the factors occurring for the set of accidents within that specific phase; meaning that color length is not comparable across phases.



Figure 3.2.2.5c - Example Gen 2 Jets

# 3.2.2.6 Ranking Factors in Accidents by Occurrence

This step in the EBT accident and incident analysis orders and compares the factors by frequency of occurrence in the last 15 years versus the previous time period. Figure 3.2.2.6 is an example of the comparative rankings in terms of percentage of all accidents with each factor while figure 3.2.2.6a makes the same comparison but normalized by exposure (i.e., 1 million take-offs).



Figure 3.2.2.6 - Gen 2 Jet



Figure 3.2.2.6a – Gen 2 Jet

# 3.2.2.7 Comparing Competencies Historically

A similar study is made for each of the generations for the competencies in terms of time periods. The display is alphabetical but the results are easily understood, as there are only 9 competencies. Figure 3.2.2.7 is a singular example of this analysis showing accident rates, with specific competency issues as a rate of occurrence per 1 million flights. See Chapter 4 and Appendix 2 for the generations, normalizations and accident/incident classifications.



Figure 3.2.2.7

# 3.2.2.8 Competencies by Flight Phase

Analogous to the study of factor proportionality by flight phase above, a study of the occurrence of competency issues in accidents by flight phase is shown in the next two figures. The breakdown is for all accidents, all time periods. Figure 3.2.2.8 and 3.2.2.8a are alternative examples of these distributions for Gen 3 Jets.



Figure 3.2.2.8



Figure 3.2.2.8a – shows the proportions in terms of percentages within a given flight phase.

# 3.2.2.9 Training Effect

Training effect is considered as the potential effect of FSTD training in preventing or mitigating an accident or incident. It is calculated by generation, time period and/or phase of flight, to be able to indicate the mitigating effect training has in a particular dimension (In the case of figure 3.2.2.9 training effectiveness is measured by generation in terms of percentage of occurrence in accidents. Additionally it is used as a sorting parameter offering valuable insight as to how effective training is with respect to specific factors for other partitions, such as shown in figure 3.2.2.9 where it is depicted as a function of time.



Figure 3.2.2.9





Figure 3.2.2.9a

Master analysis sheets are created for each generation, with the above-listed panes. The analysis of the accident-incident data is carried out with several different methods. Initially two approaches are used in the methodology:

- Comparative approach The same set of agreed charts and histograms are created for all aircraft generations, grouping charts thematically on Excel panes. Each pane is analyzed by the two analysts and their analytical comments are noted and presented in Chapter 4.2.2; they are integrated into the overall analyses in the Analysis Worksheets for Topics (See Appendix 13) and presented in Chapter 4.1: Summary Analysis by Topics. The analysts create specific drill-in charts and/or tables to study questions raised based on questions elicited during the comparison. The comparative analysis is used to:
  - a. Ensure that the overall results are consistent.
  - b. Cross check for anomalies in the RRR results.
  - c. Feed interesting findings directly to the instructors in the EBT group, thereby enriching the creation of the training content
- 2. "Data-Mining" approach. The whole data set (for generations 2-4) is analyzed with a data-mining tool called "R". This shows general footprints of the events in a visual format, which is ideal for detecting patterns. It is also the easiest way to see how much the factors cluster with each other. A dedicated analyst knowledgeable with the tool carried out the data mining analysis. (See Appendix 14.)



# 3.2.2.10 Relative Risk Ranking (RRR)

Relative risk ranking (RRR) is the next step in the process of measuring parameters enabling translating data into training. It is an important input that is used in an algorithm to prioritize training topics and determine training criticality.

Specifically RRR is the ordering of risk for a given factor in each generation. For example, if we look at system malfunction (sys mal) in generation 3 Jets, we see in the table below that it is ranked 3<sup>rd</sup> in total risk for gen 3 jets. (See figure 3.2.2.10.) Notice that the percentage of occurrence of sys mal is 29% for fatal accidents, 19% for non-fatal accidents and 55% for incidents. The word 'Relative' refers to the notion that the resulting value is only valid relative to the generation for which it is calculated and cannot be compared cross generationally except in terms of order or ranking.

			Relative	e Risk Ra	nking					
			Freque	ncy				Frequency	x Severity	/
	% of event	ts in the last	15 years	(	0.01) % x 5		Separatel	y at 3 Seve	rity levels	
	% of recent fatal accidents	% of recent non-fatal accidents	% of recent incidents	Fatal accidents	Non-fatal Accidents	Incidents	Fatal Acc (5)	Non-fatal Accidents (3)	Incidents (1)	Total risk
Mis A/C State	56%	32%	17%	2.79	1.62	0.83	13.97	4.87	0.83	19.67
CRM	47%	30%	12%	2.35	1.52	0.59	11,76	4.57	0.59	16.93
System malfunction	29%	19%	55%	1.47	0.93	2.75	7.35	2.80	2.75	12.90
Adverse Weather/Ice	21%	41%	8%	1.03	2.05	0.41	5.15	6 15	0.41	11.70
Compliance	21%	14%	7%	1.03	0.72	0.36	5.15	2.16	0.36	7.67
Poor Visibility	18%	9%	3%	0.88	0.46	0.15	4.41	1.38	0.15	5.94
Fire	12%	5%	18%	0.59	0.26	0.88	2.94	0.79	0.88	4.61
Mis-Sys	15%	4%	1%	0.74	0.20	0.05	3.68	0.59	0.05	4.32
Ground manoeuvring	3%	18%	14%	0,15	0.90	0.69	0.74	2.70	0.69	4.14
Terrain	15%	2%	0%	0.74	0.10	0.02	3.68	0.30	0.02	3.99
Crosswind	12%	5%	2%	0.59	0.25	0.08	2.94	0.74	0.08	3.76
ATC	9%	5%	11%	0.44	0.26	0.54	2.21	0.79	0.54	3.54
Workload Distraction Pressure	12%	3%	1%	0.59	0.16	0.07	2.94	0.49	0.07	3.50
Ground equipment	6%	10%	4%	0.29	0.49	0.22	1.47	1.48	0.22	3.17
Def-Proc's	9%	4%	2%	0.44	0.18	0.08	2.21	0.54	0.08	2.83
Upset	9%	2%	2%	0.44	0.08	0.08	2.21	0.25	0.08	2.54
Eng Fail	3%	3%	13%	0.15	0.15	0.64	0.74	0.44	0.64	1.82
Cabin	3%	4%	3%	0.15	0.20	0.14	0.74	0.59	0.14	1.46
Windshear	6%	2%	1%	0.29	0.08	0.03	1.47	0.25	0.03	1.75
Runway/Taxi condition	3%	5%	3%	0.15	0.26	0.17	0.74	0.79	0.17	1.69
Traffic	3%	3%	5%	0.15	0.15	0.25	0.74	0.44	0.25	1.43

Figure 3.2.2.10

For consistency in the ranking process and so that risk will have the same range as it has in the Training Criticality Study, the percentages are normalized so that values are between 0 and 5. This is simply done by multiplying the percentages by 5 and moving the decimal point two places to the left. The results for sys mal in gen 4 jets are the following:

- Fatal 1.47
- All accidents 0.93
- Incidents 2.75



Because risk is generally measured by likelihood times severity, a value must be assigned for severity to be able to calculate RRR. Again we chose values to be consistent with the TCS, which uses a five-point scale. The severity values are defined by the seriousness of the event in which the factor was involved and are as follows:

- Fatal accidents 5
- All accidents 3
- Incidents 1

Then likelihood and severity are multiplied for each factor and the risk values are summed to provide a total risk for the factor relative to a given generation. This ranking is useful for comparative purposes across generations, phases of flight and to be able to correlate to other risk rankings of sets or subsets incorporating the same factors. RRR is not only a ranking of the factors, but also a proportional representation of the importance of a factor in terms of the classical notion of risk within (or relative to) the generation of aircraft.

The weakness of this model is that assigning specific coefficients of severity, however several sets of coefficients were tried assuming axiomatically that fatal accidents are more severe than accidents in general and that accidents are more severe than incident. The results being that the ordering only changed when the data became very sparse. Additionally the process rests on the assumption that the severity associated with a factor is dependent on the severity of the event itself, or put another way: factors which are present more frequently in more severe events carry more risk. This is not always the case, but the factors themselves were defined to be relevant to the event and with a large sample of events, and generally the relationship holds. Lastly, there is the usual assumption that the past is a predictor of the future. Again there is more confidence with large and recent sets of data like the set that is used in this study.

### 3.2.2.11 Clustering and Training effect of each factor

Risk is an important factor in the prioritization but it is not the only consideration, for it has the following limitations:

- It focuses on individual factors separately, as if they did not have any influences on each other or their combined effects.
- It only highlights what should be addressed and not the efficiency of pilot training in the mitigation process.

Hence, two additional analytical results are included in the prioritization process:

1. Factor clustering – the extent to which a factors cluster with other factors is important from a training point of view. Factors that cluster significantly can be considered more important to address in training because they appear in complex and difficult situations, potentially requiring a higher level of competency than simpler and more straight forward events. Figure 3.2.2.11 is an example of a table that represents clustering as a function of additional factor occurrence in accidences and incidents.



Factor	Raw Cluster	Filter	Clustering
Crosswind	9.0	1	9.0
Terrain	9.0	1	9.0
Physio	9.0	1	9.0
Mis-Sys	8.8	1	8.8
MEL	8.3	1	8.3
Workload Distraction Pressure	7.6	A1	7.6
Poor Visibility	7.5	5 KB	7.5
Runway/Taxi Condition	7.3	) (111	7.3
Mis A/C State	6.9	<b>5</b> 1	6.9
Compliance	6.2	1	6.8
CRM	5 62	1	6.2
ATC 🔨	4.2	1	4.2
Ground Maneuvering	3.0	1	3.0
Adverse Weather/Ice	2.7	1	2.7
Syst Mal	2.5	1	2.5
Ground Equipment	2.2	1	2.2
Fire	2.0	1	2.0
Eng Fail	1.9	1	1.8
Windshear	11.0	0	0.0
NAV	0.0	0	0.0
Loss of Communications	0,0	0	0.0

Figure 3.2.2.11 – Factor Clustering

2. The last dimension considered in the prioritization process is the Training Effect. Training Effect is a measure of the mitigation that training could have on accidents and incidents. When deciding how important training is to cope with a situation, it is not only important to identify what needs to be addressed, but also how effective the training remedy is for that situation. Refer to Figure 3.2.2.9, which is an example that depicts the percentages of the levels of Training Effect for Jet Generations 2, 3 and 4 (Fig 3.2.2.9) and (Fig 2.3.3.9a), which shows the ranking of factors with high training effect for a specific generation over two time periods.

### 3.2.2.12 Final Step

The final result of the Accident-Incident Study is the prioritization of factors in terms of training criticality, which is the arithmetic combining of three resulting ranking lists from the processes described (RRR, Clustering and Training Effect).

The preference is to use a simple arithmetic algorithm taking into consideration all the variables and producing results that are in line with expert opinion and analyses from other data.

When examining the rankings in the form of graphs (e.g., RRR in figure 3.2.2.12), there are some natural breaking points. If a curve were superimposed over the bar graphs, then some of the points of inflection can be seen and used to determine natural groupings. In this way the first three groupings in terms of importance are found.





Figure 3.2.2.12

The first three groupings in the order of importance are labeled A, B and C The boundaries between classes are determined graphically by respecting the natural cut-points in the data while also maintaining a degree of consistency among different ranking lists and aircraft generations. Because the analysts agree that relative risk is the most important component of training criticality, more weight is given to the RRR compared to the other two ranking lists. Simply allowing a higher number of factors to populate the groupings A, B, and C for the RRR parameter does this.

The method described above results in each factor having a 3-dimensional ranking.

The dimensions are collapsed arithmetically and a final ranking is obtained in the following way:

- 1. The letters ABC are assigned numerical values, such that: A=3, B=2, C=1.
- The score for each factor is summed using these numerical values. For example, if the particular factor in the RRR ranking is in group A and the same factor is in group C for the clustering, and that same factor is in group B for the Training effect, then the result is: 3+1+2=6.
- 3. Such summations give values in the range from 0 to 9. This result then is an additive measure of the training criticality taking into consideration all three dimensions and resulting in prioritizing the need for training.



Training is considered as a broad concept with a variety of methods and tools. The mandate for this analysis is limited to training conducted in a qualified FSTD, creating a need to consider how well each factor could be mitigated by training according to industry standard FSTD capability. This constraint is treated in the following way in the analysis:

- 1. The capability and the need to train are treated as two separate issues and are kept separate in this analysis. This is because it is firstly most important to determine the need, and then to consider whether an FSTD environment can be effective in meeting this need.
- Instructors within the EBT working group dedicated a specific session to assess the FSTD trainability (i.e., the capability to train in a qualified FSTD) for each factor. This was done on a five point scale from A to E (A being the highest capability)
- 3. The EBT Working Group agreed that any factor rated below a C for "trainability" should be filtered out from the final ranking list as being too difficult to train in the FSTD device.

It is also important to grade the need and ability separately for the following reasons:

- 1. The risk ascribed to a factor does not diminish just because the factor is difficult mitigate in FSTD training.
- 2. Such factors should remain in the analysis to highlight the need to improve the trainability in the FSTD, thereby feeding FSTD improvement projects.

Figure 3.2.2.12a demonstrates an example of the algorithm for combining the 3 dimensional ranking and the filtering for trainability.

Re	esult				Rank	Priority			Factors	Cmb
Factor	RRR	Cluster	Hi Tr Effect	Sim Tr (FILTER)	Value	Level		Levei	Factors	Score
CRM	3	3	3	Yes	9	A			CRM	9A
Mis A/C State	3	3	3	Yes	9	Α	→	^	Mis A/C State	9A
Compliance	3	3	2	Yes	8	Α		^	Compliance	8C
Weather	3	2	2	Yes	7	Α			Weather	7C
Syst mal	3	2	1	Yes	6	В			Syst mal	6A
Poor Visibility	3	2	1	Yes	6	В			Poor Visibility	6A
Mis-Sys	2	3	0	Yes	5	В	→	в	Crosswind	5A
Crosswind	2	2	1	Yes	5	В		D	Mis-Sys	5B
Ground manoeuvring	2	2	1	Yes	5	В			Ground manoeuvring	5C
Workload Distraction Pressure	2	2	0	Yes	4	В			Workload Distraction Pressure	4C
Runway/Taxi condition	1	2	0	No	3				Fire	3A
Fire	2	1	0	Yes	3	С			ATC	3C
Terrain	2	1	0	Yes	3	С		0	Windshear	3B
ATC	2	1	0	Yes	3	C	7	U.	Terrain	С
Windshear	1	2	0	yes	3	C			Eng Fail	3A
Ground equipment	1	1	0	No	2				Upset	2C
Eng Fail	1	1	0	Yes	2	C		Cmb S	core is the Combination Score -	Rank
Upset	1	1	0	Yes	2	C	7	value (	9 highest) and the Simulator Trair	nability
MEL	0	0	0	Yes	0			(A bein	g most Trainable)	
Cabin	0	0	0	Yes	0					
Traffic	0	0	0	Yes	0					
Physio	0	0	0	No	0					

Figure 3.2.2.12a – Algorithm Demonstrating Factor Priority for Training

# 3.2.2.13 Strengths and Weaknesses

The development of the training priorities is based on proportionality rankings of factors in a given generation of accidents and incidents, rather than the rate of occurrence per million flights. The advantage is that, this provides results from the perspective of type or generation (i.e., training criticality for a specific group of aircraft), which is the main concern of a fleet training manager. The ranking process included multiple criteria to provide comprehensive results. By taking into account event severity, the ranking reflects risk and not only likelihood. The use of clustering and training effect provides more effective and compelling results for the development of programs. FSTD "trainability" ensures the results are pragmatic as well as providing information about improvements for FSTD future development. Merging of the various criteria based on the simple A-B-C classification is straightforward and consistent with the natural distribution of the data. The selection of 5-point scales for frequency, severity and training effect are subjective but were done to be as consistent as possible with the Training Criticality Study, thereby enabling cross correlations of the two studies. (See Appendix 11) Training experts in the working group are in agreement with the principles behind the 3-dimensional analysis. The decision on the weight to be assigned to each criterion and the inflection points for each of the rankings, are decisions that were taken by the data group to provide as much standardization as possible recognizing the variance in the data. The purpose is to try to maintain a consistency of approach across aircraft generations and other ranking lists.

# 3.3 EBT FLIGHT DATA ANALYSIS & ADDITIONAL FDA REPORTS

# 3.3.1 EBT Flight Data Analysis

### 3.3.1.1 Background

Flight Data Analysis is a tool intended for safety monitoring and is capable of providing continual feedback from flight operations. It has many potential uses in terms of influencing procedural development, evaluating operations into specific airports and most importantly has tremendous potential to determine systemic issues and provide data for remediation in training. There are 3 types of FDA data in this report.

- 1. Specific EBT Flight Data Analysis (the subject of this section)
- 2. FDA studies undertaken by organizations provided to us (secondary data typical of a meta-study)
- 3. The Long Body Aircraft Studies (secondary data typical of a meta-study)

**Note:** The 2<sup>nd</sup> and 3<sup>rd</sup> study are discussed in later sections of this report.

The EBT Flight Data Analysis is a primary data study created for specific objectives defined as follows:

- 1. To study unstable approaches in relation to landings and go-around across aircraft generations over several regions.
- 2. To determine a representative sample of go-around initiation altitudes for go-arounds in operational situations
- 3. To challenge and/or validate evidence from other data sources, specifically LOSA, secondary FDA studies, and to the Pilot Survey.

Flight data used in this study were collected from three regions of the world:

- 1. Europe
- 2. Middle-East
- 3. Asia



In excess of 1.7 million flights were collected for generation 3 and generation 4 aircraft spanning 9 different types from several manufacturers. The data available for this study were collected from 2005 to 2010, with all participating operators providing a continuous data stream. The shortest duration of operator specific data was for a 3-year period. Operators participating in the study either provided raw data and/or data processed through the AirFASE application. This largely depended on whether the operators were AirFASE users.

# 3.3.1.2 Data Processing

Flight recorder raw data is processed by the AirFASE system (a flight data analysis application) into an event database. The analysis was done at a statistical level rather than drilling down into Individual flights. The analysis is conducted in terms of the risk of the member events from specially defined sets of FDA events rather than looking at individual flights. In order to facilitate a consistent approach, a standard FDA flight profile was created, by which all data received could be analyzed. This meant that the same or equivalent events, triggers and parameters are used in order to derive all results and make valid comparisons. All data and events are validated for consistency before being used for analysis.

### 3.3.1.3 Objectives of the Study

The main purpose of this FDA data analysis is to study the effects of unstable approaches on the safety of flight, particularly in the landing and go-around phases. The study generally compares unstable with stable approaches by identifying risk events in the phases immediately following the approach (i.e., landing or go-around). The second purpose of the study is to corroborate the results of LOSA (See Analysis Chapter for LOSA results regarding unstable approaches) in terms of:

- 1. The rates of unstable approaches
- 2. Landing performance
- 3. Go around performance
- 4. Go around initiation altitude

### 3.3.1.4 The Analysis Process

#### 3.3.1.4.1 Defining Unstable Approaches

The first step of the analysis involved finding a set of events that would capture all flights that contained an unstable approach. To do this, events that showed continuous deviations from the approach trajectory and speed were chosen. (See Figure 3.3.1.4.1) The particular events used to do this in the study are called combination events because they consist of a set of specified individual events over a time period and are more dynamic, continuous and nuanced than simply measuring speed, vertical speed and altitude and certain gates on the approach.

	Unstable Approach Event Set
2000	Continuously Low during final
2001	Continuously Slow during final
2002	Continuously High during final
2003	Continuously Fast during final
2004	Continuously Steep during final
2009	Late Offset in Short Final
2012	Roll Oscillations prior to Flare

Figure 3.3.1.4.1

If an approach triggers any event from this set, it is defined as an unstable approach. If an approach does not trigger an event from the set it is defined to be a stabilized approach. This effectively partitions all the flights in the database into two classes, the class of flights with stable approaches and the class of flights with unstable approaches.

#### 3.3.1.4.2 Sorting Process

Data (numerical counts) are collected in an excel file for the following categories for each type of aircraft per operator per year in the sample. Figure 3.3.1.4.2 show the parameters for which raw counts and rates are calculated.

EBT FDA Partitions
All flights
All go-arounds
All stable approaches
All unstable approaches
Go-arounds from unstable approaches
Go-arounds from stable approaches
Landing from unstable approaches
Landing from unstable approaches with a detected event at landing (high, medium or low)
Landing from unstable approaches with a detected event at landing (high, medium)
Landing from unstable approaches with a detected event at landing (high)
Landing from stable approaches
Landing from stable approaches with a detected event at landing (high, medium or low)
Landing from stable approaches with a detected event at landing (high, medium)
Landing from stable approaches with a detected event at landing (high)
Events in stable landings (high, medium or low)
Events in stable landings (high, medium)
Events in stable landings (high)
Events in unstable landings (high, medium or low)
Events in unstable landings (high, medium)
Events in unstable landings (high)

Figure 3.3.1.4.2

Specific panes are created to depict event distributions in the following situations:

- 1. Unstable approaches (before potential go-around)
- 2. GA following both unstable and stable approaches
- 3. Landing following both unstable and approaches

Results are calculated as a rate of occurrence in percentage to allow comparisons.



### 3.3.1.4.3 Research Questions

The research questions can be summarized as follows:

- 1. How frequent are unstable approaches, in other words, what is the unstable approach rate?
  - a. For each aircraft type in the sample
  - b. For each aircraft type specific to operator
  - c. For each aircraft type specific to operator, per year
- 2. What percentage of unstable approaches result in a go-around?
- 3. To what extent does an unstable approach continued to a landing result in risk events in the landing phase?
- 4. What are the landing events triggered? (See Figure 3.3.1.4.4) below for a list of landing events.)
- 5. What is the landing event rate triggered per level of severity? (In most cases, each event in the landing set has three levels of severity.)
  - a. Low
  - b. Medium
  - c. High
- 6. What are the landing event rates according to the level of severity:
  - a. For each aircraft type in the sample
  - b. For each aircraft type specific to operator
  - c. For each aircraft type specific to operator, per year
- 7. Compare the landings from unstable approaches to the landing from stable approaches in each of the above, defined cases.
- 8. Compare flight data from go-arounds performed from unstable approaches with go-arounds performed from stable approaches, using a defined set of events and a corresponding severity scale. (See Figure 3.3.1.4.4a below for the list of go-around Events.) A total of 21 major queries were created to determine approach rates, go-around rates, landing rates and performance in terms of risks for the related phase of flight.

Specific panes were created to list which events are triggered in a given situation:

- a. Event distribution during an unstable approach (before potential go-around)
- b. Event distributions in GA following a unstable and stable approaches
- c. Event distribution at landing following a unstable and stable approaches

Results are calculated as a rate of occurrence in percentage to allow comparisons. Data for landings for both stable and unstable approaches are combined in one table to allow easy comparisons. The events applicable to landing are highlighted on the column listing all events.

### 3.3.1.4.4 Comparing Risk as a Function of the Approach

To look at the ramifications of unstable approaches and compare them to stabilized approaches; a landing event set and a go-around event set are also defined. See Figure 3.3.1.4.4 and 3.3.1.4.4a. (See Appendix 8 for the definitions of the events used in EBT FDA)

	EBT Flight Data Analysis
Event ID	Landing Events
1022	Speed High at Touch Down
1023	Speed Low at Touch Down
1024	Speed Above Maximum Tire Speed
1029	Braking Delayed at Landing
1033	Tail Wind High at Landing
1035	Braking Questionable at Landing
1105	Pitch Input Cycling at Landing (below 100ft)
1108	Pitch High at Touch Down
1109	Pitch low at Touch Down
1111	Pitch Rate High at Landing
1200	Bank High in Approach (below 100ft)
1205	Roll Input Cycling (below 200ft)
1210	Bank High during Flare (below 100ft)
1211	Bank Oscillation in Approach (below 100ft)
1219	Roll Spoilers Extension at Landing (below 50ft)
1405	Path High at Landing (below 20ft)
1504	Vertical Acceleration High at Touchdown
1505	High Lateral Load at Touch Down
1510	Lateral Acceleration High at Touchdown
1602	Flaps Questionable Setting at Landing
1611	Late Reverser Use at Landing
1619	Reversers High Thrust at Low Speed
1703	Thrust Reduction Late at Landing
1706	Thrust Asymmetry in Reverse
1714	Thrust Low at Landing (50ft)
1807	Heading Deviation at Landing (above 60kts)
1808	Long Flare Time
1812	Height Low at Threshold
1813	Height High at Threshold
1815	Heading Excursion During Landing Roll
1817	Short Flare Distance
1818	Long Flare Distance
1819	Short Flare Time
1820	High Vertical Speed before Touchdown
1821	Localizer Deviation at Landing (threshold)
1822	Aircraft not on Center Line
1905	Engine Reverser Selected in Flight
1906	Bounced Landing
1917	Dual Input
1950	Questionable Decrab
2206	Wing Strike Risk at Landing
2207	Hard Landing Risk

Figure 3.3.1.4.4

	EBT Flight Data Analysis
Event ID	Go-Around Events
1008	Speed Above VLO Retraction
1009	Speed Above VLE
1016	Speed Above VLO Extension
1017	Speed Above VFE
1025	Speed Above Recommended Turbulence Speed
1028	Speed Low
1032	Speed High in Climb (below 1000ft)
1038	Speed Low in Climb (100ft – 1500ft)
1100	Pitch High at Take Off
1101	Pitch Rate High at Take Off
1102	Pitch Rate Low at Take Off
1103	Pitch High in Climb
1104	Pitch Low in Climb
1206	Bank High in Climb (Take Off – 100ft)
1207	Bank High in Climb (100ft – 400ft))
1208	Bank High in Climb (400ft – 1000ft)
1209	Bank Cycling at Take Off
1407	Rate of Climb Low in Climb (below 1000ft AFE)
1500	Vertical Acceleration High at Take Off
1501	Vertical Acceleration Hi in Flight
1600	Flaps Early Retraction at Take Off
1605	Configuration Change Questionable during Go-Around
1609	Landing Gear at Late Retraction
1913	Speed Brakes Out with Significant Thrust
1618	Rudder Large Inputs (above 200ft)
1702	EGT High
1800	HDG Deviation at Take Off (100kts – Rotation)
1903	Windshear Warning
1909	Alpha Floor
1910	Alternate Law
1911	Direct Law
1917	Dual Inputs
1918	TCAS Resolution Advisory
1921	GPWS Warning (1000ft – 500ft)
1922	GPWS Warning (below 500ft)
1930	Stall Warning

Figure 3.3.1.4.4a

The landing event set contains risk events from the landing phase as defined by AirFASE in addition to certain events occurring during the last 50 ft. before touchdown.

Note: AirFASE contains two types of events: risk events and information events. While both types are used in the study, any result expressed in event rates only includes risk events.

The go-around event set contains risk events from the following AirFASE phases of flight:

- 1. Go-around
- Touch and go with low speed events restricted to after the approach phase.
  Initial climb phase restricted to events after the approach phase.
- 4. Climb phase restricted to events after approach.

In order to determine degree of risk in the phases following the approach, risk event rates are examined by categories of severity. The events themselves have a 3-point severity scale (low, medium and high) allowing for the definition of the following 3 categories:

- 1. Cat I Rate of any event (low, medium or high severity) or sometimes referred to as the all event rate.
- 2. Cat II Rate of events of concern (medium or high severity)
- 3. Cat III Rate of high risk events (high severity only)

Even though each event usually has three severity levels (Low, Medium and High), the events intrinsically are not all equal in terms of risk. Some events are more much more serious in terms of safety than others with the same severity level. To compensate for this factor as well as increase the sensitivity of the analysis, a relatively small set of serious events is selected for the landing phase. (See Figure 3.3.1.4.4b) This enables extending the trending along the severity axis (e.g., a landing with an event with high severity from the serious category is classified as a dangerous event). Serious events allowed the examination of the rate of events that could be considered as near accidents.

	EBT Flight Data Analysis
Event ID	Serious Landing Events
1200	Bank High in Approach (below 100ft)
1210	Bank High During Flare (below 10ft)
1211	Bank Oscillation in Approach (below 100ft)
1812	Height Low at Threshold
1815	Heading Excursion During Landing Roll
1906	Bounced Landing
2206	Wing Strike Risk at Landing
2207	Hard Landing Risk
1922	GPWS Warning (below 500ft)

Figure 3.3.1.4.4b

### 3.3.1.5 Initial Approach Altitude

AirFASE has a specific go-around report, which records altitude at the time of initial power application even though it is not part of the event itself (See definition of event in Appendix 8). A special analysis of these reports is done to retrieve the altitudes as evidence to corroborate similar findings from others sources. See Chapter 4 Analysis and Results.

# 3.3.2 Long Body Aircraft Studies

### 3.3.2.1 Landing Study

A study of in-service flight data focusing on long body aircraft operations during final approach and landing was reviewed and analyzed. The review had been triggered by airline reports of incidents of high acceleration landings for aircraft with a long fuselage. An aircraft manufacturer decided to launch a wide-scale flight data analysis project to address this subject. 6 operators provided large volumes of flight data recordings. These data recordings were analyzed with strong emphasis placed on establishing statistically generated findings from a substantial number of flights.



The project aimed to provide an overview of in-service events from a variety of operations, focused on handling behavior related parameters in the final 200ft prior to touchdown, comparing between types and variants based on fuselage length. The purpose is to identify contributing factors associated with high acceleration landings and use the results to make recommendations for operations, training and aircraft design. In addition, participating operators are provided with a statistical view of their own operations in comparison with operations from the worldwide fleet. Data from all participating airlines are grouped together into one de-identified database. The number of flights used for the project is 3575 long-fuselage variants and 2051 shorter variants. Some of the following parameters are monitored and analyzed closely across the two variants during the last 200ft before touchdown:

- 1. Max vertical acceleration at touchdown.
- 2. Max vertical speed at touchdown.
- 3. Flare initiation height.
- 4. Evolution of vertical speed.
- 5. Time from 30 feet to touchdown.
- 6. Evolution of pitch inputs.
- 7. Evolution of pitch angle.
- 8. Average slope before flare
- 9. Slope at start of flare.
- 10. Evolution of thrust.
- 11. Evolution of lateral handling.
- 12. Weather conditions at landing.

# 3.3.2.2 Take-off Study

A similar study was done for take-offs comparing long and shorter aircraft variants within the same type. Similar techniques are used as described above. The notable difference is that the study only involved a single aircraft type.

The standard process for entering evidence in the Evidence Table is used for this source. Several analysts read the report, working collaboratively to draft related evidence statements. The content and detailed wording of the evidence statements are reviewed and edited by the core analysts in the data-analysis working group. Evidence statements are reviewed and verified independently to ensure accurate reflection of the original source report material.

# 3.3.3 A Study of Normal Operational Landing Performance on Subsonic Civil Narrow Body Jet Aircraft during ILS Approaches

The purpose of the study is to examine operational landing performance on subsonic, civil, narrow body jet aircraft during ILS approaches. The study is conducted using in-flight recorded data collected from landings in normal operations. These data are obtained from the quick access recorder for two types of narrow body jet aircraft, one belonging to Generation 3 and one to Generation 4. Data from quick access recorders can be used effectively to analyze performance from engine and aerodynamic to pilot handling. A statistical analysis is undertaken in this study to examine performance and flight control parameters with respect to the landing phase of flight. The purpose is to identify empirical distributions of the landing distance parameters such as the approach speed at threshold, the touchdown point, rollout distance, and total landing distance. Both aircraft types are comparable in size and general performance (e.g., range, payload) and are used by many operators all over the world. All flight data analyzed in this study were obtained from a European operator. The recording effort lasted for more than 7 months over winter, spring and summer time operations. In addition to flight data, relevant aviation routine weather reports (METAR) are collected. The data collection effort was set to obtain landing data for 50,000 landings in total (all types combined). [Figure 3.3.3 Landings in NLR Study]

Landing	gs in NLR Study
Aircraft Type	Number of Landings
G4 <sub>1</sub>	7,474
G42	12,245
G4 <sub>3</sub>	5,952
G3 <sub>1</sub>	12,093
Aircraft Types	have been de-identified.
Subscripts ind	icate de-identified type.

i igui e 0.0.0
----------------

The data quality is good with a high level of consistency. There were some limitations in the data frames that required some derivations and smoothing (See Appendix 6 for the explanation in the Report.)

The standard process for entering evidence in the Evidence Table was used for this source. Several analysts read the report, working collaboratively to draft related evidence statements. The content and detailed wording of the evidence statements are reviewed and edited by the core analysts in the dataanalysis working group. Evidence statements were reviewed and verified independently to ensure accurate reflection of the original source report material.

### 3.3.4 Strengths and Weaknesses

The analyses for the Long Aircraft Study exceeded the usual scope of FDA analysis, and a number of special algorithms were created for the study. In addition, some more precise techniques than normally used in FDA analysis are incorporated. The data used for the study represents flights flown in a variety of different operator route networks, airports, ATC and geographic environments. The obvious limitation of this study is that it is limited to very specific aircraft.

In contrast, the EBT FDA Analysis involves considerably more aircraft types as well as a very large number of flights. This research is quite focused and the technique is statistical in nature, which is in line with the strength of FDA. While FDA is designed primarily for safety trend monitoring, it is capable of identifying a near accident, in addition to measuring flight parameters precisely subject to the defined events and the sampling rate. The data is quantifiable for comparison, trending and benchmarking, and if the volume of recorded flights is sufficient, drilling down to examine operational and training issues more closely can be undertaken. Data analyzed only shows what occurred and provides little context. By the nature of parameters available for capture, there are many flight crew errors that cannot be captured. Results are constrained by event design, meaning that the analysis generally shows what the analyst expects to find. Any surprises in the findings are usually restricted to severity and frequencies of the exceedances of the events. Event sets, their associated parameters and triggers are nonstandard across types, and manufacturers of flight data analysis software. However in EBT FDA study, all flights were processed using the same software, parameters, and event sets making the study more rigorous than normal. Additionally because of the extensive data set, some novel opportunities were available to use in this analysis.

The Study of Normal Operational Landing Performance on Subsonic Civil Narrow Body Jet Aircraft during ILS Approaches utilized a data sample that is very large, but limited to one European operator and 2 aircraft types. Due to the scope limitations, only a few results are taken from this study for the EBT evidence table. The results are considered scientifically reliable.

FDA analysis results generally are very compelling due to the precise and mathematical means with which they can be displayed. But it is this attribute that is its biggest trap, for in many cases the results lack context and present an incomplete picture requiring it to be used specifically, carefully and validated by other sources.



# 3.4 TRAINING DATA (AQP & ATQP)

# 3.4.1 AQP Study

### 3.4.1.1 Background

The Advanced Qualification Program (AQP) is a voluntary alternative to the traditional regulatory requirements under the FARs for pilot training and checking. Under the AQP the FAA is authorized to approve significant departures from traditional requirements, subject to justification of an equivalent or better level of safety.

Specific data were provided for this study, from an existing and mature AQP program. AQP programs are highly developed, sophisticated training programs that share many goals set by EBT. The advantages of collecting information on these programs are obvious. Airlines are providing information on course structure and content, flight operational data as well as metrics on training system performance. Additionally, all AQP programs have the capability to provide insight into continual proficiency and skill decay because of their continual monitoring of training and operations.

The data package received from donor airlines was substantial, encompassing grading data from all pilot training events (i.e., type rating related, recurrent, IOE and line checks) for a period of two years. The data set includes over 600 pages, including charts, data tables and instructor comments related to specific training events. The data set includes drill-ins to all sub-topics within the training events, e.g., Engine Failure at V1, and Windshear. There are multiple aircraft types in the data set, including generations 2, 3 and 4. The data analyzed for this report are based on the numeric pilot grades across all measured training events.

The data set is presented in a de-identified format in Chapter 4 and Appendix 9. The findings from this study are presented in 2 formats:

- 1. Results from the donor airlines' own analyses.
- 2. Results from the EBT data subgroup analysis using the airline results and raw data provided to re-sort from a training topic perspective. (See Chapter 4.2.4. and Appendix 9)

The data describing the pilot grading results are based on a multi-level grading system where the grading scale can be divided in three categories:

- 1. Failed
- 2. Passed but not reaching the desired company standard and requiring additional training
- 3. Reaching the company standard

**Note:** For the purpose of this study, scores in the first and second category are given the term PNG (Pilot Non-Proficient Grade).

The performance scores utilized in this particular AQP program are at the level of a training topic within a specific training event for a given aircraft type. (e.g., CAT I precision approach in the Maneuver Validation at the conclusion Type Rating course). The study compares and contrasts the percentages of the graded pilots who did not meet the company standard during validation. For practical purposes, this is the Percentage of Non-Conforming Grades (PNG).

# 3.4.1.2 Purpose

The objectives of the AQP analysis were:

- 1. To view a large sample of training data and quantitatively measure developmental apprehension, skill mastery, and knowledge and skill retention over a two-year training cycle.
- 2. To determine where learning takes place in training as well as on the line.
- 3. To determine which learning objectives present difficulty to the pilots and whether aircraft from different generations behave similarly or differently in this respect.

Average values over the 24 months are entered in separate excel tables for the analysis. For each training period (e.g., maneuver training in recurrent training), a histogram is created comparing the PNG (Pilot Non-proficient Grade) for the different aircraft types per training topic. (See Appendix 8) Footprints for the different types of aircraft are compared but the specific focus is to compare aircraft generations rather than just types. Queries resulting from these comparisons determine the scope of further analysis and drill down into detailed instructor comments.

Another analysis using the same numerical data trends the PNG's of the different training events over the period starting from the Type Rating, through IOE to the Line Check and subsequent Recurrent Training. This is an attempt to examine the spectrum of pilot performance according to defined norms at different stages of training. The rate of PNG is considered as indicative, and can highlight problem areas during the training process. This evolution is plotted for Generation 3 Jets and Generation 4 Jets. For each generation, the average PNGs by types and generation are compared for each defined training event.

A third study measures pilot error types by fleet for each training event.

A fourth study, done by the airline solely and provided to the EBT data subgroup, considers skill decay, based upon the continual measurement and grading of psychomotor skill based maneuvers over time, comparing pilots with different exposures to training according to fleet specific programs. Domestic pilots complete a 'First Look' exercise during continuing qualification once a year. International pilots undergo the same 'First Look' exercise twice a year. The operator uses 'First Look' to evaluate pilot performance in maneuvers, which depend largely on psychomotor skill, at the end of the interval between the continuing qualification training periods.

The standard process for entering evidence in the Evidence Table is used for this source. Several analysts read the report, working collaboratively to draft related evidence statements. The content and detailed wording of the evidence statements are reviewed and edited by the core analysts in the data-analysis working group. Evidence statements are reviewed and verified independently to ensure accurate reflection of the original source report material.

### 3.4.1.3 Strengths and Weaknesses

The Study was comprehensive with multiple aircraft over an extended period of time. The data ranged from results provided by the airline, to the EBT subgroup re-sorting the data from different pilot training perspectives to raw instructor comments allowing many issues to be examined in depth. The grading was multi-point, providing sensitivity. It was also well instructor-calibrated, and the program had been in use for an extended period of time. Results range from pre-analyzed findings by the airline to the EBT analysts trending of the raw grades and drill downs of instructor comments.

Once the results were ready, they are shown to the data donors to ensure integrity. There was agreement on the findings, plus the provision of additional background information providing additional perspective for the analyses.



# 3.4.2 ATQP Implementation Data

The objective of this study is to examine lessons learned during the process of ATQP implementation with a major European operator. The ATQP study is distinct from the AQP study used in this report; the latter being derived from data from a very mature training system while the former being analysis of the data focused on measuring the effect of program implementation.

### 3.4.2.1 Background

Data were provided from several ATQP operators, with, (in certain cases) extensive and highly sensitive information. As might be expected, most of the important results come from these sources. The ATQP implementation at one operator was a four-step process, which comprised the following elements in accordance with EU-OPS 1.978 (Alternative Training and Qualification Program):

- 1. A job task analysis defining pilot tasks during operations
- 2. A training needs analysis, identifying tasks o be trained
- 3. Developing the means of training
- 4. Establishing the mechanism for monitoring the outcomes of training

Several precautions were taken in order to minimize possible risks to safety including a phased implementation. ATQP is part of a system that monitors safety performance in normal operations, and consequently, the effectiveness of remediation through training. A "First-Look" analysis was also implemented as well as an enhanced data analysis. Simultaneously with implementation of ATQP, a new and comprehensive risk model was created to monitor any effects on safety and training that could result due to change.

The pilot performance grading structure was redesigned to meet the following objectives:

- 1. To measure system performance
- 2. To reflect the assessment of non-technical skills
- 3. To develop realistic Line Orientated Evaluation (LOE) scenarios
- 4. To develop a new program for instructor qualification and training
- 5. To develop a sophisticated instructor calibration program

A data management and reporting system was also developed to:

- 1. Build and implement a risk assessment model
- 2. Analyze data from multiple data streams
- 3. Track and trend key incidents based upon recent LOSA experience

The implementation process was monitored closely for risk over 2-years, as follows:

- 1. Monitoring of grades that were determined to be below the operator standard over the two-year implementation process
- 2. Training system performance over 2 years for crew capability in managing 32 categories of training events
- 3. Training system performance over 2 years for crew capability in 8 competency areas
- 4. Unstable approach trends from operations data
- 5. Landing performance in operations across several variables by FDA and a pilot reporting system.
- 6. Go-arounds in operations by cause and initiation altitude

The operator provided data to this study over the 2-year implementation process, as follows:

- 1. Continual risk assessment data.
- 2. FDA results and reports.
- 3. All training and checking data for pilots and instructors, including instructor calibration data.
- 4. Voluntary and mandatory occurrence reporting by pilots.
- 5. Detailed safety performance indicators of pilot errors and aircraft limit exceedances, including trends.
- 6. Altitude excursion information by cause.
- 7. Detailed analysis of engine-out pilot performance in training prior to, and post implementation.
- 8. Detailed analysis from operations of rejected take-offs by cause over a two-year period.
- 9. Airline's own analysis of the data above, in addition to recommendations and raw numbers

Data and results from all the above numbered items were made available to the EBT data subgroup as well as consultations with the key training and operational analysts from the airlines to well understand the processes and the results.

The standard process for entering evidence in the Evidence Table was used for this source. Several analysts read the report, working collaboratively to draft related evidence statements. The content and detailed wording of the evidence statements are reviewed and edited by the core analysts in the dataanalysis working group. Evidence statements are reviewed and verified independently to ensure accurate reflection of the original source report material.

### 3.4.2.2 Strengths and Weaknesses

Most evidence coming from the data sources were processed by the airlines and while some of it could be crosschecked, much of it was accepted at face value. The spectrum of data provided by the donors was wide and extremely useful in verifying results from other sources. Unlike data from AQP, which are extremely focused with long standing experience, the information and analysis provided from ATQP is broader in scope but less specific in some respects. Most of the results were discussed with their source providing perspective and better understanding of the analyses.

# 3.5 AIRLINE PILOT SURVEY ON TRAINING EFFECTIVENESS

A survey was created by the EBT data group with a series of questions to airline pilots relating to the effectiveness of training they had received. The survey was made available via a link through the website of the International Federation of Air Line Pilots Association (IFALPA). The survey was active for a 110-day period from  $17^{th}$  November 2010 –  $7^{th}$  March 2011.

# 3.5.1 Background

An independent web-survey provider hosted it and all responses were anonymous. There were a total of 966 respondents, pilots being notified via an announcement on the IFAPLA daily news message and by word of mouth. IFALPA provided a means to reach a global sample of airline pilots. Data were collected from the web site into a data file, then summarized by survey probe.

# 3.5.2 Purpose

The survey probes are designed to fill gaps in existing EBT data set, to probe additional specific topics of interest for this study and verify and cross check results from other sources. The probe formats include multiple choices, and open-ended questions with percentage distributions.



Data are then grouped by topic and analyzed qualitatively for trends. Results of the analysis are included in the topic analysis in chapter 4 and the complete pilot survey "Airline Pilot Perceptions of Training Effectiveness" is reproduced in Appendix 4. Respondents were allowed to make comments, which are analyzed for trends. Evidence statements from the analysis of the survey are entered into the Evidence Table.

The standard process for entering evidence in the Evidence Table is used for this source.

Several analysts studied the statistical results and had access to the textual comments. One analyst drafts the evidence statements relating to training issues. The content and detailed wording of the Evidence Statements are reviewed and edited by the core analysts then reviewed independently for completeness and accuracy in representing information from the source report. The textual comments create a very large additional source of information, especially two open-ended questions. This textual material is analyzed separately by one analyst and reviewed by the core team. (See Appendix 4 for the survey questions and results.)

# 3.5.3 Strengths and Weaknesses

Surveys are based on samples of populations and are subject to sampling error, which reflects the effects of chance and uncertainty in the sampling process. The pilot survey attracted a fairly large number of respondents from many areas of the world providing balance and minimizing bias. Expert opinion is particularly useful as a data source. Surveying line pilots provide balance to the training criticality survey, which sampled largely the opinions of training experts. The margin of error in terms of pilot point of view for the questions, subject to its demographic distribution, is approximately 3% in this pilot survey. The pilot survey is anonymous allowing the respondents to express themselves with no accountability, which generally gives rise to comments and responses that are more pejorative than would normally be given if the names were attached to the survey. The strength of any survey is ability to focus on very specific issues and elicit data that are difficult to find using other methods of research. Because of the voluntary nature of the pilot survey, it necessarily had to be short so as to attract a suitable number of respondents, which, in some respects, can limit the scope.

# 3.6 META DATA FROM ACCIDENT & INCIDENT STUDIES

# 3.6.1 IATA Safety Report 2008 & 2009

### 3.6.1.1 Background

IATA produces safety reports on an annual basis including a detailed summary of statistics, trends and contributing factors involved in accidents. This study includes an analysis of the 2008 and 2009 safety reports. The first part of the reports contains a summary review of western built jet hull losses and passenger fatality rates for the preceding 10-year period. In addition, the reports contain comments from the Accident Classification Task Force (ACTF), an industry-working group charged with accident analysis, identifying contributory factors, determining trends and areas of concern relating to safety, and developing prevention strategies. (See figures 3.6.1.1 and 3.6.1.1a for ACTF membership list.)

Accident Classification Task Force	
2008	
Name	Organization
Capt. Georges Merkovic	Air France
Mr. Jean Daney	Airbus Industrie
Dr. Dieter Reisinger	Austrian Airlines (Chairman)
Capt. David. C. Carbaugh	The Boeing Company
Mr. David Fisher	Bombardier Aerospace
Capt. Mattias Pak	Cargolux Airlines International
Mr. Mišo Klarić	Croatia Airlines
Mr. Savio dos Santos	Embraer Aviation International
Mr. Don Bateman	Honeywell
Mr. Martin Maurino	ΙΑΤΑ
Capt. Karel Mündel	IFALPA
Mr. Bert Ruitenberg	IFATCA
Capt. Keiji Kushino	Japan Airlines International
Mr. Richard Fosnot	Jeppesen
Capt. Joachim Fleger	Lufthansa German Airlines
Capt. Jean-Lucien Tarrillon	Régional
Capt. Ayedh N. Al-Motairy	Saudi Arabian Airlines
Capt. Peter Eggler	Swiss International Airlines
Mr. Gustavo Rocha	Tam Linhas Aéreas
Capt. Carlos dos Santos Nunes	TAP Air Portugal

Figure 3.6.1.1

Accident Classification Task Force	
2009	
Name	Organization
Mr. Marcel Comeau	Air Canada
Capt. Georges Merkovic	Air France
Mr. Albert Urdiroz	Airbus Industrie
Dr. Dieter Reisinger	Austrian Airlines (Chairman)
Capt. David. C. Carbaugh	The Boeing Company
Capt. Thomas Philips	The Boeing Company
Mr. Andre Tousignant	Bombardier Aerospace
Capt. Mattias Pak	Cargolux Airlines International
Mr. Savio dos Santos	Embraer Aviation International
Mr. Don Bateman	Honeywell
Mr. Michael Goodfellow	IATA
Capt. Karel Mündel	IFALPA
Capt. Keiji Kushino	Japan Airlines International
Mr. Richard Fosnot	Jeppesen
Capt. Peter Krupa	Lufthansa German Airlines
Capt. Jean-Lucien Tarrillon	Régional
Capt. Peter Eggler	Swiss International Airlines
Mr. Gustavo Rocha	Tam Linhas Aéreas
Capt. Carlos dos Santos Nunes	Tap Air Portugal



Aircraft accidents are categorized and analyzed according to:

- 1. Region
- 2. Threat and Error Management As part of the report ACTF analyzed accidents using a taxonomy based on TEM) The purpose of this taxonomy is to:
  - a. Acquire more meaningful data
  - b. Extract further information and intelligence
  - c. Formulate relevant mitigation strategies and safety recommendations
- 3. Hull losses The IATA report breaks down accidents using hull loss as a category to provide a notion of severity.
- 4. Phase of flight.
- 5. Consequences, as follows:
  - a. Controlled flight into terrain (CFIT)
  - b. Gear-up landing
  - c. Ground damage
  - d. Hard landing
  - e. In-flight damage
  - f. Loss of control in flight
  - g. Mid-air collision
  - h. Runway excursion
  - i. Tail strike
  - j. Undershoot
- 6. Contributing factors as follows:
  - a. Latent conditions
  - b. Threats
  - c. Flight crew errors
  - d. Undesired aircraft states

Correlations of interest are made to highlight some results that imply mitigating strategies. These correlations are between the classifications and other types of breakdowns of the accident analysis. The technique is generally used where causality is suspected in order to support it. Most often in these reports an accident classification is correlated to a threat or error. For example: In 33% of CFIT accidents, the flight crew committed errors relating to SOP adherence and/or SOP cross-verification and the aircraft underwent vertical, lateral or speed deviations prior to a potential terrain proximity event.

The IATA safety reports are primarily used in the EBT study to challenge and validate analyses from other sources, particularly LOSA, FDA, EBT Accident and Incident Study and the meta analysis from the UK CAA publications CAP 776 and 780. The standard process for entering evidence in the Evidence Table is used for this source. Several analysts read the reports, working collaboratively to draft related evidence statements. The content and detailed wording of the evidence statements are reviewed and edited by the core analysts in the data-analysis working group.

Evidence statements were reviewed and verified independently to ensure accurate reflection of the original source report material.

### 3.6.1.2 Strengths and Weaknesses

The IATA safety reports have the same strengths and weaknesses as other accident reports. Accident analysis has been the bedrock of safety analysis, providing the context and framework for all other safety analysis and reporting. The biggest strength of accident and incident data is its relevancy to safety and training (i.e., Evidence Based Training in a pure sense).

The biggest weakness in accident-incident analysis is the inconsistency and lack of standardization among the original investigative reports from which the analysis is drawn. Additionally some reports lack information on human factors and in the search for direct and final causation some underlying factors are usually missing. Because the IATA accident reports are annual studies, the data samples are statistically quite small. It is helpful that at the beginning of the report a 10-year accident review is made. It is also helpful that the IATA safety reports analyze the data from various perspectives including causality, factors, and a threat and error framework.

# 3.6.2 Incidents During Training

This study includes a query of an Air Safety Report database to compare frequency distributions of the top 20 STEADES descriptors of normal flights versus training flights. A search of the STEADES database was performed using a word search "training/trainee flight". The intent is to denote the differences between the pilot performance during Initial Operating Experience (IOE), where pilots are supervised during line flying on a new type versus their performance in normal operations. The analysis highlights the descriptors that differ significantly. (See figure 3.6.2.1 STEADES Descriptors used.)

# 3.6.2.1 STEADES – Global Aviation Safety Data Sharing Program

The STEADES database of de-identified airline incident reports is the world's largest, offering a secure environment for airlines to pool safety information for global benchmarking and analysis needs. STEADES provides rates on safety performance indicators as well as continually producing report on many safety subjects.

STEADES Top 20 Descriptors		
During Training Flights	During Normal Operations	
Severe Weather	Flight/Ground Crew Communications	
Communications with ATC Lost	Approach/Landing Aids	
Windshear	Hard/Heavy Landing	
Flight Crew Auto Handlings	Flight Plan	
Flight/Ground Crew	Other Operational Data	
Communications Flight Plan	Operational Procedures	
Flight Crew Fatigue/Stress	Severe Weather	
EGPWS/GPWS – Sink Rate	Flight Crew Fatigue/Stress	
Tailwind	Insufficient Visual Reference	
Other Operational Data	Tailwind	
Aircraft Anti/De-Icing	Communications with ATC Lost	
Checklist/SOP Use	Flight Crew Manual Handling	
Aircraft Limit Exceedence	Checklist/SOP Use	
EGPWS/GPWS – Glideslope	Inadequate Separation	
Operational Procedures	Windshear	
Deep Landing	Other Aircraft – Slow to Clear Runway	
Hard/Heavy Landing	Flight Crew Mis-Selection	
Flight Crew Mis-Selection	Turbulence	
Flight Crew Manual Handling	High Energy/Unstable Approach	
High Energy/Unstable Approach	Aircraft Limit Exceedence	

Figure 3.6.2.1



### 3.6.2.2 Strengths and Weaknesses

A word search does not necessarily find all the training flights nor does it restrict the findings only to IOE. Air Safety Reports have to be considered in terms of the reporting culture, the motivations of the reporter, and whether the report is attributable or not. Analysis from these sources can be sometimes unreliable. For the above reasons this source was not used to produce any primary results but only to corroborate evidence found from other analyses.

# 3.6.3 UK CAA Accident Reports

### 3.6.3.1 Background

Two CAA (UK) 10 year global fatal accident reviews are referenced and excerpted in this report, as follows:

- CAP 776 Global Fatal Accident Review 1997 2006, published July 2008
- CAP 780 Aviation Safety Review 2008, published November 2008

Additionally, assistance from the UK CAA was provided, creating a mapping of some of the applicable results of the reports to factors defined in the EBT Training Criticality Survey. The outcome of this process appears in the Evidence Table and the mappings appear in Chapter 4.2.8 Analysis and in the appendices (See Appendix 6).

The EBT study draws information from the CAA accident reports themselves as well as the additional analysis provided from the CAA and makes inferences from the findings relating to training need. The Inferences are entered in the Evidence Table.

### 3.6.3.2 CAP 776

The primary aim of the CAA analysis is to extract safety related information from fatal accidents so that strategies could be developed to help reduce the worldwide fatal accident rate in the future. In this endeavor, the UK CAA Accident Analysis Group (AAG) decided to routinely assess all fatal accidents on a worldwide basis. The AAG's assessment process consisted of three main parts:

- 1. Causal factors
- 2. Circumstantial factors
- 3. Consequences

This is accompanied, according to AAG, by an evaluation of the level of confidence in the information available.

# 3.6.3.3 Causal Factors

For the purpose of the study and this report, a causal factor is an event or item, which is judged to be directly instrumental in the causal chain of events leading to the accident. AAG select 1 primary causal factor for each accident. The causal factors are listed in groups such as "Flight Crew" and then divided further into specific factors such as "Lack of positional awareness – in air". An accident may have been allocated any number of causal factors from any one group, and any combination of groups. There are a total of 67 causal factors from which to choose.

### 3.6.3.4 Circumstantial Factors

A circumstantial factor is an event or item, which was judged not to be directly in the causal chain of events but could have contributed to the accident. These factors are present in the situation and are felt to be potentially relevant to the accident. There are a total of 22 circumstantial factors.

# 3.6.3.5 Consequences

A list of consequences is used to record the outcomes of fatal accidents. An accident may have been allocated any number of consequences. There are a total of 15 consequences from which to choose:

- 1. Controlled flight into terrain (CFIT)
- 2. Collision with terrain, water or obstacle
- 3. Mid-air collision
- 4. Ground collision with other aircraft
- 5. Ground collision with object or obstacle
- 6. Loss of control in flight
- 7. Fuel exhaustion
- 8. Runway Excursion or overrun
- 9. Undershoot
- 10. Structural failure
- 11. Post crash fire
- 12. Fire or smoke during operation
- 13. Emergency evacuation difficulties
- 14. Forced landing land or water
- 15. Other cause of fatality

### 3.6.3.6 Cap 780

The Aviation Safety Review, CAP 780 covers the ten-year period 1998-2007. The document includes an overview of worldwide and European Union aviation safety statistics, before concentrating in more detail on UK aviation safety. For the purpose of the EBT data study, the focus is on worldwide data.

The data for this Review is derived from a variety of sources:

- 1. Worldwide accident statistics by the International Civil Aviation Organization (ICAO)
- 2. European Union fatal accident statistics and worldwide utilization have been derived from Ascend\*
- 3. UK accident, serious incident and occurrence data is sourced from the CAA Mandatory Occurrence Reporting Scheme
- 4. UK utilization is supplied by the CAA Air Transport Statistics Department, CAA Aircraft Register,
- 5. NATS
- 6. Eurocontrol
- 7. Airprox statistics, from the UK Airprox Board. (An Airprox is a situation in which, in the opinion of a pilot or a controller, the distance between aircraft as well as their relative positions and speed have been such that the safety of the aircraft involved was or may have been compromised.)

\*Ascend is a private provider of specialized information and consultancy to the global air transport industry with various aviation data including accident and logistical information on most all aircraft types and categories of aircraft. Some of the databases maintained by Ascend are as follows:

- World Aircraft Accident Summary (WAAS) Researched and published on behalf of the UK CAA, WAAS includes detailed descriptions for 8,000 accidents involving jet and turbo-powered aircraft and helicopter accidents.
- Jet Operator Statistics (JOS) Accident and exposure statistics over 45 years, across more than 1200 airlines, available as a comprehensive database or a subset of.


- Special Bulletin When a major accident occurs, Ascend publishes a Special Bulletin summarizing all the available information about the event and following up with quarterly updates and a special end-ofyear report.
- Major Loss Record (MLR) MLR provides comprehensive details of 7,000 accidents incurred by jet, turbo-props and business jets since entry into service.
- Airliner Loss Rates (ALR) ALR provides annual figures for all major airline types covering the different measures of exposure and five-year accident rates.

### 3.6.3.7 Strengths and Weaknesses

The source of data is used as a secondary (meta) source analysis for this report. Both CAP reports are quite exhaustive in terms of data assimilated and the analysis conducted. While the studies performed by the UK CAA and the EBT accident/incident analysis are not directly comparable, (the CAA study is more causal in nature while the EBT accident study is a factor analysis) the results can be contrasted and both are used in this Meta study. All accident studies suffer from the lack of capability to provide depth in certain areas. This is because the data becomes thin rapidly when drilling down, as accidents fortunately are limited. As soon as we begin to partition the accident sample by almost any parameter, it quickly becomes statistically less significant and of limited value as a predictor of future probability, hence risk. An additional problem with a causal accident analysis is that it does not compare easily with a threat and error analysis. CAP 776 mitigates this limitation by analyzing circumstantial factors as well as consequences and causal factors.

### 3.6.3.8 Special CAA Analysis of Global Fatal Accident Data using EBT factors

Worldwide fatal accidents were analyzed using the EBT Training Criticality Survey listing of potential threats, errors and aircraft states. The following criteria are applied to the data:

- 1. Fixed-wing jet and turbo-prop aircraft originally certified MTWA above 5,700 kg or 12,500 lbs.
- 2. Civil passenger and cargo flights only
- 3. Fatalities within 30 days of the accident (as per ICAO Annex 13 definition)
- 4. Occurring between 1 January 1997 and 31 December 2008 (inclusive)
- 5. Excluding violent acts (e.g., sabotage, terrorism, etc.)

Data is also analyzed for the following five separate categories:

- 1. All fatal accidents
- 2. Passenger flights only
- 3. Cargo flights only
- 4. Western-built jets only
- 5. Western-built jets on passenger flights only

See Appendix 6 for the study.

# 3.7 SCIENTIFIC REPORTS

# 3.7.1 Skill Retention after Training (FAA Unpublished Report)

### 3.7.1.1 Background

This study was undertaken during 2008 analyzing a very large set of pilot performance data obtained from the Federal Aviation Administration. The data is de-identified Maneuver Validation (MV) and First Look (FL) grades given to pilots during continuing qualification evaluations from operators applying the AQP. The primary purpose of the analyses is to examine skill decay over the course of the retention interval between successive training visits during the program. In addition, several other variables are examined including:

- 1. Phase of flight
- 2. Normal and abnormal maneuvers
- 3. Aircraft type

The objective of the study is to identify data that would support optimal intervals of retraining for different types of pilots and different types of tasks, in addition to determining optimal recurrent training intervals.

The following data were examined:

- 1. Retention interval
- 2. Practice level
- 3. Task type

The data analyzed in this study are de-identified maneuvers validation grades collected from 8 operators, with a total of 25 fleets ranging from B747, B777, B757/767 to turbo-prop aircraft across a range of operations. The data set comprises in excess of 2,000,000 maneuver grades collected between 2000 and 2008. The data represent an extensive range of maneuvers occurring across all phases of flight under both normal and abnormal (e.g., engine-out) conditions. All pilots were subject to a 12-month training exposure interval. Each training session began with a first look (FL) evaluation prior to any retraining, followed by maneuvers validation (MV) training, which enabled the assessment of psychomotor skill retention by comparing grades collected during MV training with FL grades collected 12 months later, the decay effect being equivalent to MV-FL. This calculation of the decay effect was repeated annually over the period. (See Appendix 5 for the full study.) Among all the 2,098,946 evaluations, 1,685 evaluations were excluded giving a study sample of 2,097,261.

The study investigated whether simulator effect within these three fleets was confounded with a certain maneuver type, retention interval or phase of flight.

#### 3.7.1.2 Strengths and Weaknesses

This study had access to a substantial amount of data, was highly controlled and analyzed according to rigorous statistical principles. The study was very narrow in scope but it did provide definitive results and allow cross checking with the AQP study in 2 areas:

- 1. Skill decay
- 2. Training proficiency by phase of flight.



### 3.7.2 FAA Human Factors Team Report 1996 on: The Interfaces between Flightcrews and Modern Flight Deck Systems

### 3.7.2.1 Background

The objective of the study is to evaluate current generation transport category airplane flight deck design with respect to human interfaces with aircraft systems and the effect of these interfaces on airplane safety. The study concentrates on the design, training/flight-crew qualification, and operation of those systems dealing with flight path management.

The report considers all factors that can influence the pilot's ability to safely operate the airplane during all phases of flight, including, but not limited to, mode and situation awareness, pilot expectations regarding the automatic systems and the subsequent pilot response when those expectations are not met, in addition to crew resource management in modern flight decks.

The following aircraft types are included in the evaluation:

- 1. Airbus: Models A300-600/A310/A320/A330/A340
- 2. Boeing: Models 737/757/767/747-400/777
- 3. Fokker: Model F28-0100/-0070
- 4. McDonnell Douglas: Models MD-80/MD-90/MD-11

The standard process for entering evidence in the Evidence Table was used for this source. Several analysts read the report. One analyst drafts the evidence statements relating to training issues. The content and detailed wording of the Evidence Statements are reviewed and edited by the core analysts. The evidence statements are reviewed independently for completeness and accuracy in representing information from the source report.

#### 3.7.2.2 Strengths and Weaknesses

The Report was issued in 1996 and changes and improvements in automation systems have been implemented since publication. The Generation 4 aircraft sample is small, so results are limited in this area. Discussions with the authors updating the study confirmed the relevance of many issues reported in the original report in the area of training today.

#### 3.7.3 Automation Training Practitioners' Guide

#### 3.7.3.1 Background

This work was supported by the Federal Aviation Administration through FAA grants to George Mason University and to the University of Central Florida; and through a contract to Research Integrations, Inc. The guide was first published in May 2008. The document serves to provide a consolidated and concise review of research addressing pilot training for automated aircraft, ("automation training" for short). The research is based on accidents, incidents, research experiments and studies. Each section begins with a brief summary of the concept followed by two subsections: Best Practices and More Information. In the Best Practices subsection, recommendations based on the research are made for improving automation training. Relevant best practices and supporting rationale in this document that deal directly with training itself in FSTD's are paraphrased into evidence statements and entered into the EBT evidence table.

### 3.7.3.2 Strengths and Weaknesses

This document is based on professional interpretation of a large a body of various types of data. It is a meta-analysis with the challenge of assimilating data from various sources. The study relates directly to training issues and specifically automation, and this is considered strength. The study is supported by an extensive human factors database.

## 3.7.4 Factors that Influence Skill Decay and Retention

### 3.7.4.1 Background

This Report was created by Winfred Arthur Jr., Pamela L Standush, and Theresa L McNelly from the Department of Psychology at Texas A & M as well as Winston Bennett Jr. from Armstrong laboratory. Copyright 1998

The study uses meta-analytic techniques that apply to data extracted from 53 studies. The study presents a review of skill retention and skill decay that focuses on factors that influence the loss of trained skills and/or knowledge over extended periods of non-use. The objective of the study is to review scientific skill decay and skill retention literature to delineate the effects of factors that influence the retention of trained skills over extended periods of non-use. The study presents a review of the following factors hypothesized to affect knowledge and skill retention:

- 1. Length of the retention interval
- 2. The degree of over-learning
- 3. Task characteristics e.g.,
  - a. Closed loop versus open loop tasks
  - b. Physical versus cognitive tasks
- 4. Methods of testing for learning
- 5. Instructional strategies or training methods
- 6. Differences among individuals

#### 3.7.4.2 Strengths and Weaknesses

This is part of the meta-analysis and the study involves a well-researched paper. A substantial volume of data was analyzed. Much of the data is not related to aviation, but is rather analogical in nature.

The results of this study are applicable to the tasks as well the type of training germane to commercial airline flight crews. Even though the results are qualitative, they are useful in principle when designing flight crew training programs particularly in terms of program efficiency.

While meta-analysis of secondary data is useful in providing a large source of data to analyze, they have some standardization issues and can sometimes be difficult to quantify.

# 3.7.5 TAWS 'Saves'

#### 3.7.5.1 Background

This paper studies six approach and landing incidents involving the potential for a Controlled Flight Into Terrain (CFIT) event. The term 'saves' is defined as accidents avoided. All had the potential to become fatal accidents, but were avoided by the Terrain Awareness Warning System (TAWS) alerting the crews to the hazard. The analyses below were conducted by the author and reviewed by a select group of safety professionals in addition to a number of airline pilots.



There were no narrative reports or crew interviews. EGPWS digital memory data provided aircraft location, altitude, and speed information; the approach charts were used to determine the expected flight path in normal operations. All 6 events involved premature descents and the incidents were examined for the attending threats and errors. The technique was to hypothesize realistic scenarios that fit the data to derive lessons learned, in a process similar to that used in the analysis of accidents.

#### 3.7.5.2 Strengths and Weaknesses

The data sample was extremely limited forcing the author to speculate in terms of flight profile and scenarios. The results as well were limited. The major strength of this study is that it could be performed because the data were available to the analysts in a non-accident situation. The evolution of the TAWS technology, just culture and confidential reporting should enable studies of this sort to be able to be expanded in scope accomplished more easily with the ensuing lessons learnt.

# 3.8 ACCIDENT STUDY USING CAST DATA

### 3.8.1 Background

This study is primarily an accident analysis focusing on large commercial jets operated by operators over the last 20 years. Non-western jets are excluded. Standard ICAO accident definitions were used. The accident data was extracted from the CAST database provided to the EBT Data Subgroup. Because the CAST database only contained accidents through 2008, it was supplemented by the NTSB database for the years 2009 and 2010 so as to more consistent time wise with the other accident studies in the metaanalysis. There are 457 accidents used to compile the statistics.

Accidents were analyzed from three perspectives:

- 1. Accidents normalized by exposure (number of flight cycles) over time (trends)
- Categories The analysis of accidents by categories are accomplished using a zero sum methodology meaning that each accident is only assigned a single category such that the percentages for all categories total 100%. (The categories are shown in Figure 3.8.1 below.)
- 3. Flight Phases

Accident Study by Category (CAST Data)
System Malfunction
Abnormal Runway Contact
Runway Excursion
CFIT
Loss of Control
Undershoot
Fuel Starvation
Ground Collision
Fire (leading to an accident)
lcing
Turbulence
Birds
Air Collision (Mid-air)
Unknown

Figure 3.8.1

### 3.8.2 Strengths and Weaknesses

There are advantages and disadvantages in using an accident, zero sum methodology. Trending is very clear, but assigning a single cause to an accident with many factors can lead to oversimplification, particularly when trying to isolate areas of crew performance to enhance training. This method also has a tendency to hide certain factors, which can be relevant. When conducting analyses based upon causation, there is a strong dependency on the categories for analysis. These categories must be clearly defined and be determined as true causes, and not simply effects. In some of the categorizing in this study, as is with many similar studies today, the lines between cause and effect are sometimes indistinguishable.

The EBT Data subgroup undertook this study to counterbalance the EBT Accident-Incident Factor analysis, which is its antithesis in terms of source biases.

# 3.9 TRAINING CRITICALITY SURVEY (TCS)

# 3.9.1 Background

One of the elements of the EBT methodology is based on a training criticality survey, identifying potential threats and errors in each phase of flight. (See appendix 11 for sample of Survey Worksheet.) Aircraft types included in the survey are listed in figure 3.9.1. Pilots experienced in operations and training were asked to assess threats and errors by phase of flight according to their experiences, projections and their intuitive view of risk. There are 161, 3-part questions asked in each survey concerning 40 threats and errors over all phases of flight. 167 pilots completed a Training Criticality worksheet over most of the aircraft generations and 51 aircraft types/variants. There were no respondents for Generation 1 (Jet). Figure 3 represents a list of aircraft that is representative of the 6 generations of aircraft.

Air	rcraft Generations Analyzed Criticality Survey					
Generation	Aircraft Type					
	A319 A320 A321					
	A330 200/300					
	A340 200/300					
Generation 4	A340 500/600					
	A380					
	B777					
	EMB 170 190					
	A300-600					
	A310					
	CE525A, B, C					
	CE 550B, CE 560XL/XLS					
	B737 300-500					
	B737 600-800					
	B747-400					
	B757					
	BE 40					
	CE-680					
	CE560XL					
Generation 3	CE560XLS					
	CE-550B					
	CE750					
	CE560					
	Falcon 900EX					
	Falcon DA 2000					
	Falcon 200EX FASy					
	Gulfstream 450					
	Gulftream IV					
	Hawker 800/850					
	MD80					
Generation 2	L-1329 Lockheed JetStar					
	Hawker 400					
Ν/Δ	Simulators					
IN/A	Enter/Select type					

Figure 3.9.1

Aircraft by Generation								
	A318/A319/A320/A321							
	A330, A340- 200/300, A340-							
Concretion 4 let	500/600, B777, A380, B787							
Generation 4 Jet	A350, Bombardier C Series							
	Embraer							
	E170/E175/E190/E195							
	A310/A300-600							
	B737-300/400/500							
	B737-600/700/800 (NG), B757							
Conception 2 lat	B767, B747-400, B747-8							
Generation 3 Jet	B717, BAE 146, MD11							
	MD80, MD90, F70, F100							
	Bombardier CRJ Series							
	Embraer ERJ 135/145							
Generation 3 Turbonron	ATR 42-600, ATR 72-600							
Generation 3 Turboprop	Bombardier Dash 8 Q Series							
	A300 (except A300-600)							
Generation 2 Jet	BAC111, B727, B737-100/200							
	B747-100/200/300							
	DC9, DC10, F28, L1011							
Constation 2 Turbonron	AIR 42, AIR 72 (all series							
Generation 2 Turboptop	Embraer EMB-120							
Generation 1 Jet	DC8. B707							

Figure 3.2.1.1 (duplicate)

The respondents were volunteers from all over the world, multiple organizations, and airlines. It was not always possible to find volunteers for every aircraft listed in the figure 3.2.1.1 (duplicate) but certain volunteers came forward from aircraft that were not in the table. When this occurred, the aircraft involved were grouped with aircraft having similar characteristics as the aircraft in the table.

The threats and errors used in the survey were defined by the EBT Project Group specific to flight phases and considered relevant to training. In addition, the potential threats and errors that could occur in all flight phases are listed separately in a phase, defined as Phase  $\Phi$ .

TCS Flight Phase Definitions										
Flight Phase	Numerical Order of Flight Phase	Definition								
All	Phase Φ	Potential threats/errors in any or all phases of flight Phase (1-8)								
Pre-Flight/Taxi	Phase 1	Pre-flight and taxi – flight preparation to completion of line-up								
Take-off	Phase 2	From the application of take-off thrust until the completion of flap and slat retraction								
Climb	Phase 3	From the completion of flap and slat retraction until the top of climb								
Cruise	Phase 4	From top of climb until top of descent								
Descent	Phase 5	From top of descent until the earlier of first slat/flap extension or crossing the initial approach fix								
Approach	Phase 6	Form the earlier of first slat/flap extension or crossing the initial approach fix until 15m (50ft) AAL, including go- around								
Landing	Phase 7	From 15m (50ft) AAL until reaching taxi speed								
Taxi/Post-Flight	Phase 8	From reaching taxi speed until engine shutdown								

Figure 3.9.1a

The defined threats and errors were evaluated on a scale of 1 to 5, according to likelihood of occurrence; severity of outcome, and the benefit training could have in mitigating the outcome. These three parameters are more fully described below.

**Likelihood** describes the probability that over the course of a defined period in time a pilot will experience a threat, requiring intervention. Five levels of likelihood were used as defined by the EBT international working group:

- 1. Rare once in a career or less;
- 2. Unlikely a few times in a career;
- 3. Moderately likely once every 3-5 years;
- 4. Likely probably once a year; and
- 5. Almost certain more than once a year.

**Severity** describes the most likely outcome based on the assumption that the pilot has not received training to manage the defined event in five levels as follows:

- 1. Negligible insignificant effect not compromising safety;
- 2. Minor reduction in safety margin (but not considered a significant reduction);
- 3. Moderate safety compromised or significant reduction in safety margin;
- 4. Major aircraft damage and/or personal injury; and
- 5. Catastrophic significant damage or fatalities.

**Training Benefit** describes the effect of training to reduce the severity by at least one level, and is assessed in a five level scale as follows:

- 1. Unimportant training does not reduce severity;
- 2. Minor enhances performance in managing an event;
- 3. Moderate having no training compromises safety;
- 4. Significant safe outcome is unlikely without effective training;
- 5. Critical essential to understanding the event and coping with it.

For the purpose of this survey, the notion of risk is defined as likelihood x severity and is calculated for all threats and errors by phase of flight for each aircraft.

See Appendix 11 for a list of the aircraft involved in the Training Criticality Survey as well as the respondent's ATO or operator. The representation of each generation in terms of the number of surveys completed is displayed in Appendix 11.

Originally when the survey was sorted by threats and errors according to aircraft generation, all the factors in phase  $\phi$  went to the bottom of the sort. This is because the factors in this phase were only assessed once even though they appear in multiple phases, hence their cumulative scoring was artificially small. Since risk is a weighted probability (by severity) and all the phases of flight are mutually exclusive, the risk of any given flight is the sum of the risks for each individual phase. This makes it important to assess a threat or error each time it appears. To compensate for the way the survey was structured, in not always asking the questions in the same way ( $\phi$  phase issue), a rule was made to multiply the risk value times the number of phases where the risk is relevant in the sense that it could well have been a factor in an accident.

There were two other problems in the survey that needed to be corrected:

- 1. **Questions unanswered by the respondents.** An unanswered question automatically assigns an unwanted 0 risk. In order to correct this, the average risk per factor per phase of flight was calculated and used this value to fill in for unanswered question. (See Appendix 11 Analysis for this calculation)
- 2. **Outliers.** An outlier is an observation that lies an abnormal distance from other values in a random sample from a population. This definition provides discretion for the analyst to determine the distance.

Trimming of the outliers was done only on the high side of the mean because of the multiplicative effect of the risk formula, the effects of outliers on that side are exaggerated. All outliers were trimmed 1.6 standard deviations greater than the mean consistent with the advice of the statistician in the EBT Data Subgroup. Trimming was done at the finest level (risk per factor per phase per generation). This is because risk varies per factor with the phase of flight; that is another reason that questions regarding each factor should be asked for each phase. The correlations could have been accomplished using the corrected average risk per factor per generation but the cumulative value gives the same results and is one less step. The methodology yields the following results:

- 1. Average risk for each threat or error per each phase of flight per generation on a scale of 1-25
- 2. Cumulative risk scoring for each threat or error for a given flight per generation.
- 3. Corrected (for unanswered questions and outliers) average risk for each threat and error in each phase of flight per generation on a scale of 1-25
- 4. Corrected cumulative risk scoring per threat and error by generation leading to ranking
- 5. Training Criticality in the same format as risk values above.
- 6. Distribution of the risk by factor per phase
- 7. Distribution of the risk by factor per phase by generation
- 8. Standard Deviation of risk (generation factor and phase)



## 3.9.2 Strengths and Weaknesses

The survey is too small to reach an acceptable margin of error. This weakness is amplified by the fact that the interest lies in examining risk and training criticality according to aircraft generation, implying a partition of the data set. The data are heavily biased towards Generation 4, because that is the generation for which most of the surveys were completed. The structure of the questions (i.e., phase  $\Phi$ ) necessitated a rule to compensate for the fact that the threats and errors were not assessed every time they might actually appear. The correction required for the outliers was minimal and turned out not to change the outcome. The response rate to questions was very high requiring only a minor correction for that problem. Because of the problem with the size of the survey as well as the bias towards generation 4, the results were not integrated into any conclusions in this report other than to correlate them with the EBT Accident Incident study (See Appendix 11 for the correlative results.). With the several corrections noted above, the methodology can lead to a robust process, which can be utilized for the next round of investigation. Using expert opinion for a survey like the training criticality analysis is an excellent means for providing perspective, correlation and a continuous spectrum of data that is easily updatable and usually difficult to secure in other domains.

### 3.10 CORRELATION OF RISK BETWEEN TCS AND ACCIDENT-INCIDENT STUDY

### 3.10.1 Background

A standard statistical correlation was completed between the rankings of the sum of the corrected risk per factor according to aircraft generation in the TCS and the relative risk rankings by generation in the EBT accident incident analysis.

Data Sample Comparisons – The data sample for Generation 4 was the best for Training Criticality Survey while the data sample for Generation 2 was the best in terms of the Accident-Incident Analysis. Given that this study is intended to identify discriminators between aircraft generations with respect to training, only correlations from the same generation in the TCS to the same generation in Accident/Incident Study were calculated. Because there were no responses in the Training Criticality Survey for Generation 1 aircraft, there were only three correlations calculated i.e., generations 2, 3, and 4. No correlation was calculated from the all-generation ranking of the TCS to the all-generation ranking of the Accident/Incident analysis because of the asymmetric generational sizes of the raw data sets.

It is important to note that only the rankings are correlated. The amplitude of the risks for each factor was not taken into consideration, only its positional relation along the X-axis, as the primary objective of the analysis is only the prioritization of the threats and errors. A graphical presentation of the results of the correlation is available in Appendix 11. Consideration was given to correlating criticality (i.e., need for training) from the two analyses. This was not done for the following reasons:

- 1. While both analyses considered training effect on a five-point scale, the scales were significantly different and mapping would have been difficult.
- 2. Training effect in the training criticality survey was measured at the level of the threat and error while in the accident and incident study it was measured at the level of the event (accident–incident).

# 3.10.2 Strengths and Weaknesses

While the data sets correlate fairly well and with remarkable consistency according to aircraft generation, (see Appendix 11) there are several problems with the process. Firstly, the survey has too few responses to achieve an acceptable margin of error. Secondly, the data samples did not match well in terms of size. The data sample of the TCS for Generation 4 was the best with Generation 2 being the worst. The reverse was true for the Accident-Incident Analysis with Generation 4 the largest and Generation 2 the smallest. No correlations were done for the turbo-props because of the very limited number of respondents available for them. The survey correlations indicate consistency and promise; however, the survey, itself, is too small to use as extensively as had originally been planned. Never the less, the exercise demonstrated its value and it will be developed further in the future. The fact that the generational correlations tend to be quite good, offer additional confidence in the accident-incidence study.

# 3.11 EVIDENCE TABLE METHODOLOGY

# 3.11.1 Purpose

Most of the evidence from analyzed data sources is managed by using the Evidence Table. Meaningful outcomes from the individual analyses are phrased as Evidence Statements and recorded there. The only exceptions to this are the EBT Accident-Incident study and the Training Criticality Survey, the management of each being covered in their respective sections.

The purpose of the Evidence Table is to integrate evidence, identify meaningful patterns and enable the grouping of evidence to support key findings and is the major tool for the final analysis in chapter 4. The table also facilitates the prioritization of results. The ET was created as an excel file with columns to accommodate all necessary categorizations as follows:

(See Appendix 12 for representation of the Evidence Table)

- 1. Reference Number a unique identifier for the statement
- 2. **Evidence Statement** statements of evidence that range from a short sentence to a small paragraph or a bulleted list
- 3. **Objective Relevance** 3 columns tracking evidence relating to the stated objectives of the study
- 4. Flight Phase applicability to one or more phases of flight
- 5. Applicability to Gen applicability to aircraft generation
- 6. **Source** origin of the data; each individual source is uniquely named in this column
- 7. **Keywords** keywords matching the evidence and allocated to the statements. Each statement may have none, 1 or more keywords.
- 8. **Context & Remarks** usually there are several statements with the same context. This column also hosts remarks of any kind that may be relevant to the evidence statement
- 9. Training Topic linking between the Evidence Statements and Training Topics
- 10. **Factors** each evidence statement is linked, where applicable, to one or more relevant factors as defined in EBT Accident Incident Analysis in this column.
- 11. Competencies Each Evidence Statement is linked with the relevant competencies in this column.

# 3.11.2 Data Entry

Prior to entry, each evidence statement is reviewed according to a standard process. Several analysts read the report, working collaboratively to draft related evidence statements. The content and detailed wording of the evidence statements are reviewed and edited by the core analysts in the data-analysis working group. Evidence statements are then reviewed and verified independently to ensure accurate reflection of the original source report material.



# 3.11.3 Evidence Table – Identifying the most Critical Training Topics

Once the Evidence Table (ET) was sufficiently complete, an analysis was performed on its contents. The first step involved doing a cross sectional verification of the finding by individual sources in the Evidence Table. The table is searched and filtered in multiple ways to identify information associated with specific topics and their importance. In assessing the evidence, attention is paid to the number of Evidence Statements supporting the topic, the number of independent sources listed to support the topic, along with the weight and credibility of the Evidence Statements involved.

Training Topics that are highly supported with strong evidence from multiple sources are labeled as the "A" topics. Training Topics that are supported with good credible evidence but not necessarily coming from as many independent sources is labeled as the "B" topics.

The end result of this process is a number of Training Topics, divided into two categories (A and B) with Category A being the more important. Each Training Topic has a specific pane with a Supporting Table listing all relevant Evidence Statements, in addition to an overall summary. The Evidence Statements are also linked to the appropriate factors defined in the EBT Accident-Incident Study as well as the relevant competencies to provide further analytical capability.

The list of A and B topics used in the training prioritization is one of the most important conclusions in the study. (See Chapter 2 Major Findings.)

The content and structure of the Evidence Table serves as a tool for continual analysis. It is a tool that has the capability to evolve and should be continually updated with more and new data.

### 3.11.4 Evidence Table – Analysis by Source

Chapter 4 begins by providing summaries of all the training topics that resulted from the EBT data study. These are the results of the convergence of all data analyzed to compile this report. This is followed immediately by reverting to the beginning of the analysis process: analyses by source.

After the training topics were identified and ranked (See 3.11.3 – Identifying the most critical Training Topics and 2.6 – Prioritization of Training Topics) an in depth analysis beginning with the sources was undertaken in order to:

- 1. Integrate and condense the various analyses to synthesize the results in terms of training topics.
- 2. Provide transparency in the analytical transformation of the information from pre-analysis to conclusions in terms of methods and tools.

#### 3.11.4.1 Filtering and Word Searches to Create Support Tables

Each of the 17 sources (See 1.1, figure 1.1a) was analyzed using the linked evidence statements of the Evidence Table with one notable exception: the EBT Accident-Incident Study. (A discussion of the analysis of this source appears in 3.2). The method primarily used with the Evidence Table was simply filtering by the topic sequentially. In some cases additional searches according to synonym or related issue, were done in order to provide additional information for the topic. The results are tabulated in support tables, which are simply excerpts of the evidence table containing the evidence statements relating to the searches. Figure 3.11.4.1 is an example of a support table for Unstable Approaches in FDA. (Ref: 4.2.3 Unstable Approaches for the actual analysis.)



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
170	3.5% of approaches are unstable	APR	34	34	FDA	Unstable APR/GA	Unstable APP	Mis A/C Stable	All
171	Only 1.4% of them lead to a Go-Around	APR	34	34	FDA	Unstable APR/GA	Unstable APP Go-Arounds	Mis A/C Stable Compliance	Application of Procedures/Knowledge
178	Frequency of fits having at least one FDA event (all severity levels) is the same for stable and Unstable Approaches (83.63 vs 81.11 stable vs unstable respectively) indicating there are landing problems with stable approaches as well.	APR	34	34	FDA	Unstable APR/GA	Landing Issues	Compliance Mis A/C State Mis-Sys	All
179	Comparing events per flt (all severities) stable vs unstable is 2.24:2:84 or r=1.3 (approx.)	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	All
180	Comparing events rates (high severity stable vs unstable is 8.11% vs 19.53 (approximately 2.4 times) indicating that there are more than double the hi risk events on landing with Unstable Approaches	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	All
181	Comparing event rates stable vs Unstable Approaches (all severities) for the selected 10 serious landing events stable vs unstable is 14.33% to 34.52% or r=2.4 (approx.)	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	All
182	Comparing event rate (high severity) stable vs unstable for the set of 10 serious events is 1.96% vs 5.47% or r=2.8 (approx.) indicating that there are almost 3 times the hir isk events on landing with Unstable Approaches	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	All
183	Unstable Approaches are not the cause of all landing problems. This is particularly concerning if we remember that the ratio of stable approaches over Unstable Approaches is approx. 27:1	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	Manual AC Control
184	But if we drill down we see that when Unstable Approaches occur, there are many more of severe events during landings (things go more wrong when unstable.)	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	Manual AC Control
185	Flights with Unstable Approaches produce more events than flights with Stable Approaches even in phases of flight outside of Approaches and Landings.	All	34	All	FDA	Unstable APR/GA	Unstable APP Error Mgt	Compliance Mis A/C State Mis-Sys	All

#### Figure 3.11.4.1

Bullets immediately following the topic title (e.g., 4.2.3.1.1 Unstable Approaches) define how each search was accomplished in order to build the particular support table for the specific topic. An example of the terminology used in defining the searches that produced the table in Fig 3.11.4.1 is given below with an explanation appearing in italics:

- Filter Evidence Table for FDA (The evidence table is first filtered for all the rows with evidence statements relating to the source, Flight Data Analysis)
- Filter for [Unstable Approaches)(Landing Issues)(Error Management)] (This terminology indicates that the results of the previous filtering are then filtered again for Unstable Approaches then combined with filtered results for Landing Issues and lastly combined with filtered results with Error Management. The rows resulting from the filtering processes are combined into a matrix.)

If any of the evidence statements are not relevant to the topic, unstable approaches, the analyst manually suppresses them from the support table. The technique is to over-search and suppress rather than lose any relevant information.

This type of technique was used to accumulate the data from each source in terms of the individual topics. Three other support tables in addition to the training topics using the same techniques were also built to make sure that no useful information relevant to training was lost. These other related topics are:

- Generational Aspects
- · Phase of Flight
- Training Effect

The results from the ensuing support tables of the above three topics were used later in the analysis. (See the Note in 3.11.4.4)



# 3.11.4.2 Summary Process for Each Topic

The next step in the analysis is a two-part process:

- 1. The analyst organizes the evidence statements from the support tables into 'result' bullets that better reflect the overall meaning of the evidence statements. This falls under the heading: Results that follow the search definitions.
- 2. These result-statements are then summarized into brief one or two paragraphs reflecting the implications of the particular training topic per specific source, which are titled summaries.

#### 3.11.4.3 Summary Analysis Matrix

There are 16 sources, 14 training topics and 3 other topics used in the described process. This could yield up to (16X17) individual summaries. Many sources contain little or no information for a given topic. No individual source covers all training topics. In order to aid in further analysis, a matrix was considered useful and constructed with the rows being the sources and the columns being the topics i.e., training topics and other relevant topics. An excerpt of the Summary Analysis Matrix is shown in Fig 4.11.4.3. See Appendix 13 for the entire matrix.

The matrix is a transformation of the data from the sources to the topics. One of the benefits of this informational array is that it shows the density of the data as a function of source and topic. It is easy to see what and how much support exists for a given topic; as well as how many sources contain information relevant to the topic.

EVIDENCE TABLE - SUMMARY ANALYSIS												
	Unstable Approach	Automation	Error Management	Manual Aircraft Control	Go-Around							
LOSA Study 4.1	Unstable approaches remain a consistent problem at a rate of approximately 4%. They almost always result in an unventful landing. The crews in most cases have mismanaged the situation but are willing to continue the appropriate satisfact approach orbits. Landings are often performed in the wrong alricraft configuration.	The oversiching sockers with automation for the light crews is monitoring and cross checking, 28% of the lights have at least one automation error with almost half of them not detected or acted upon by the crew. In addition mode conduction and using the automation and/or flying manually at inappropriate times.	A key strategy for managing flight crew errors is monitoring and croaschecking. The situation is indeal onesware acteletical and rectilicit. The highlight rak is crosschecking errors (e.g. omfalled deviations as they errors could be the safety that and the situation errors could be a situation of the safety of the errors could be any bases of they are errors and the first of the errors and be first. They are detecting the could be any bases of the errors any bases of the detecting base on errors (to be first.)	According to LOBA, manual control errors, while not the most Request type of error (41% most and the second second second second second advantation errors. Many manual control errors advantation the improper technique, fifth creve graving or "hing through" the indicated light according to advance second second second second accordination advance weather. The technique accordination advance weather. The technique accordination advances weather. The technique according to advance weather. The technique advances (Solowad Colorgity Verlations in landing, lateral, speed and improper finust.	According to LOSA, go-around from unstable approaches occur only 3% of the time (contrary to too b). LOS (and the time) contrary too too b). LOS (and the LOS (and the too number 3 non-compliance from in the LOSA database). When a do-around too an unstable approaches to the crieve and poorly executed.							
EBT Flight Data analysis 4.2.1	The FDA unstable approach rate is around 3.5%. This is consistent across aircraft types and geographical regions. There are as many flights that have landing events approaches. Solving the unstable approache poside multi not address all landing issues. The increased risk associated with unstable approaches becomes evident when examining event rates and event severity. Landings set to the events there are an event severed to the events therease become more severes. The event case becomes even higher. Unstable approaches can be viewed as a baroneter of the fight taket. If the approaches generally have more FDA events all approach.	Intertional Blank	intentionali Blank	Intentional Blank	Only 1.4% of unstable approaches lead to a go- around, with an FDA all event rate of 1.6 occurrences in the immediate phases after go- around (GA, CLB) The high-risk event rafe for the same period is 0.2.4. Both these rates are capture many of the creve errors that could occur. Ca capture many of the creve errors that could occur ca around initiation heights overwhelmingly occur at heights different from those briefed.							
Long body aircraft Studies 4.2.2	Intentionali Blank	Intertional Blank	Intentional Blank	Long body aircraft are more prone to high 'G' landings. Because of geometric considerations, perspectives from the cockplat are signify different steeper approach gradients judy for the fare are a certefined explanement in crosswinds. To compensate for this crows should be alternive to when and a therdon jo under date. There is a tendency to under-rotate in ingo yau craft, which degrades take of performance, picka which degrades take of performance, picka which degrades take of performance, picka pick decades take of performance.	intentional Blank							

Figure 3.11.4.3 – A small excerpt of the Evidence Table Summary Analysis

#### 3.11.4.4 Summary Analysis Templates

The next tool to be used in the analytical process is the summary analysis template. (See figure 3.11.4.4. for an example.) There are 14 of these, one for each Training Topic. See Appendix 13 for all of the summary analysis templates.



	Summary Analysis - Automation									
Sources	Summaries	Outline	Excerpts	Narrative						
LOSA	The overarching problem with automation for the flight crews is monitoring and cross checking. 28% of the flights have at least one automation error with almost half of them not detected or acted upon by the crew. In addition there is a basic problem with understanding the system, mode confusion and using the automation and/or flying manually at inappropriate times.		28% of the flights have at least one automation error with almost half of them not detected or acted upon by the crew LOSA Automation is an issue of concern regarding assessments in AQP in both the planning and execution phases of flight - AQP Mismanaged auto-flight is a major factor, contributing to unstable approaches and go- around errors, both in training and line operations. This remains constant, whether in the all engines operating, or engine-out case ATQP	According to LOSA almost 30% of the flights have at least one						
AQP	Automation is an issue of concern regarding assessments in AQP in both the planning and execution phases of flight. The phases most concerned are CRZ and DES.	Problem	Problem	Problem	In reality 61% [of survey pilots] had multiple encounters on the line during their first 6 months of flying where they reported being involved in uncomfortable situations Pilot Survey The IATA accident reports generally support the LOSA finding with regard to automation. Specifically, flight crews were found reluctant to revert to manual flying	automation error with almost half of them not detected or acted upon by the crew. Training reports that automation is an issue of concern regarding assessments in both the planning and execution phases of flight. Pilots themselves are heavily critical of automation training during the initial type rating with only 25% of the pilots feeling prepared to utilize the automation when released to line				
ATQP	Mismanaged auto-flight is a major factor, contributing to unstable approaches and go- around errors, both in training and line operations. This remains constant, whether in the all engines operating, or engine-out case.			even when the situation required it IATA Safety The ranking of automation as a causal factor is generally low in accident reporting and the CAA accident reporting is no exception at 1.9% CAA Accident Reports The FAA automation report found that pilots have various situation awareness issues with automation EAA HE Report	operations. A major accident investigation agency believes that because mismanaged automation is further upstream in the error chain, it is under reported in causal accident investigation. Another authority states that many pilots use the autoflight when inappropriate and fail to revert to manual flight when required. The skill decay study					
	The pilot survey was heavily critical of automation training during the initial type rating. Only 25% of the pilots felt prepared to utilize the automation when released to line operations. In reality 61% had multiple		Many pilots use the autofight when inappropriate and fail to revert to manual flight FAA HF Report Input from EVIdence Table Input from EBT Accident-Incident Study	shows that skill losses can be substantial and decay without practice. This deterioration is much greater for skilled tasks, such as certain automation skills making it important to assess these skills in training particularly for pilots that do on operate routinely. All of this points to a need to change the way current training is accomplished. A total of 60% of pilots reported that operational						
Pilot Survey	encounters on the line during their trist o months of flying where they reported being involved in uncomfortable situations. Over 60% felt that the operational aspect of FMS training was missing during training requiring them to learn to use the system effectively during the first year after training. When asked		The overarching problem with automation for the flight crews is monitoring and cross checking - LOSA The phases most concerned are CRZ and DES AQP The prevailing opinion by many analysts is that because mismanaged automation is further upstream in the error chain, it is under reported in causal accident investigation CAAAccident Reports	FMS training was not provided during initial training, and that they were left to self-learn during line operations. Recommendations to improve training include that training enhances mode and position awareness when using automation, particularly with regard to terrain, energy and upset. In addition, there should be adequate training content to ensure airmanship, CDM dealistic particle and workload of the addition.						
	during the first year after training. When asked how the training could be improved, the majority felt that automation surprises was the most important issue followed by hands on use in operational situations; while about a third recommended better training in transitioning between beween. The nervilles continuent the	Specifics	They [Flight crews] are vulnerable to lack of flight path and energy awareness when using autollight. In addition they are surprised by the subtleties and complexities of automation and the training courses fail to focus on operation principles of the autoflight architecture FAA HF Report Ioput from Evidence Table	CrkM, decision-making and workload management when utilising automation, especially in demanding situations. Training should also include multiple assessment techniques, confirming that pilots understand the logic, design purpose and limitations of the automation. Practice and reinforcement should be accomplished in an operational setting, managing automation at all levels and including reversions to manual flight.						
	that the operational aspect of the FMS was seriously lacking in training, the focus being on		Input from EBT Accident-Incident Study							
	the functional, such as basic knowledge and programming The IATA accident reports generally support the LOSA finding with regard to automation. Specifically, flight crews were found reluctant		When asked how the training could be improved, the majority felt that automation surprises was the most important issue followed by hands on use in operational situations; while about a third recommended better training in transitioning between levels Pilot Survey							
IATA Safety	Specifically, light clews were round relucant to revert to manual flying even when the situation required it. In addition, crosschecking is promoted to be the best countermeasure to mitigate automations errors and further finds that gross error checks should be made when inputtion data into the FMS to tran errors easily	to revert to manual flying even when the situation required it. In addition, crosschecking is promoted to be the best countermeasure to mitigate automations errors and further finds that gross error checks should be made when imputing data into the FMS to trap errors easily	Training Effect	In addition, crosschecking is promoted to be the best countermeasure to mitigate automations errors IATA Safety The training courses at the time of the study tended to be checking rather than learning oriented and had not kept pace with human factor issues in regard to automation FAA HF Report						
CAA ACCIDENT	made with this function The ranking of automation as a causal factor is generally low in accident reporting and the CAA accident reporting is no exception at 1.9%. The prevailing opinion by many analysts is that because mismoneed automation is						The Automation Training Practitioners' Guide advocates a new training concept. Specifically it recommends training in blocks, adapting to individual trainees, integrating CRM throughout training, and major emphasis on the "need to know" items AUTO PRACT GUIDE Input from Evidence Table			
REPORTS	further upstream in the error chain and under		Input from EBT Accident-Incident Study							
Skill Decay	reported in causal accident investigation The skill decay study shows that skill losses can be substantial and decay without practice. This deterioration is much greater for skilled tasks, such as certain automation skills making		The pilot survey was heavily critical of automation training during the initial type rating. Only 25% of the pilots felt prepared to utilize the automation when released to line operations Pilot Survey Over 60% felt that the operational aspect of FMS training was missing during training							
	it important to assess these skills in training particularly for pilots that do on operate routinely.			requiring them to learn to use the system effectively during the first year after training Pilot Survey The prevailing sentiment was that the operational aspect of the FMS was seriously lacking in training, the focus being on the functional, such as basic knowledge and						
	have various situation awareness issues with automation. They are vulnerable to lack of flight path and energy awareness when using autoflight. In addition they are surprised by the subtleties and complexities of automation and	Criticality	programming - Pilot Survey The skill decay study shows that skill losses can be substantial and decay without practice. This deterioration is much greater for skilled tasks, such as certain automation skills making it important to assess these skills in training particularly for pilots that do							
FAA HF Report	the training courses fail to focus on operation principles of the autoflight architecture. Many pilots use the autoflight when inappropriate and fail to revert to manual flight. The training courses at the time of the study tended to be checking rather than learning oriented and had not kept pace with human factor issues in record to autoration. The sport procemende	Criticality	on operate routinely Skill Decay The report recommends that training enhance mode and position awareness when using automation, particularly with regard to terrain, energy and upset. In addition, the report recommends that there be adequate training content to insure airmaship. CRM, decision-making, workload/task management when utilizing automation especially in demanding situations FAA HF Report							
	legato to aductination: The report recommends that training enhance mode and position awareness when using automation, particularly with regard to terrain, energy and upset. In addition, the report recommends that there be adequate training content to insure airmanship, CRM, decision-making, workload/task management when utilizing automation especially in demanding situations		In addition it recommends using multiple assessment techniques, confirming that pilots understand the logic, design purpose and limitations of the automation. Lastly it recommends practice in operational setting of managing automation throughout the various levels including eversion to manual flight AUTO PRACT GUIDE Input from EVIdence Table Input from EBT Accident-Incident Study							
AUTO PRACT GUIDE	The Automation Training Practitioners' Guide advocates a new training concept. Specifically it recommends training in blocks, adapting to individual trainese, integrating CRM throughout training, and major emphasis on the "need to know" items. In addition it recommends using multiple assessment techniques, confirming that pilots understand the logic, design purpose and limitations of the automation. Lastly it recommends practice in operational setting of managing automation throughout the various levels including eversion to manual flight									

Figure 3.11.4.4



The synthesis works from left to right with the first two columns depicting the topic summary by source. In the case of the example for Automation in the figure above, there are 8 sources providing summary results for the training topic.

These summaries from the applicable sources were transcribed from the Summary Analysis Matrix i.e., the appropriate column (e.g., Automation) with the empty cells collapsed.

The next step is to excerpt from all the summaries and reorganize these excerpts in terms of the following four constructs:

- 1. Problem
- 2. Specifics of the problem
- 3. The effect of training in mitigating the problem or its ramifications
- 4. The Training Criticality

**Note:** There were no templates created for the topics other than the 14 training topics. The other summaries from the other topic classifiers (i.e., Generational Aspects, Phase of flight and Training Effect) are excerpted and added to the outline under the appropriate construct (Problem, Specifics, Training Effect and Training Criticality), as these issues are highly germane to training.

#### 3.11.4.4.1 Assimilating the Results of the EBT Accident-Incident Study

The sections in Chapter 4 (4.2.2.1 - 4.2.2.9) contain the results of the EBT accident-incident analysis in statement form and titled by training topic. The appropriate statements from these sections are added into the respective summary analysis template in the Excerpt column and in the appropriate construct section to augment the body of information that is used to infer the last stage in the argument.

#### 3.11.4.5 Narratives of Training Topics

The final step in the process is to summarize and deduce the conclusions in a short narrative form from all the excerpts in the format of the constructs. These narratives, one for each of the 14 training topics, are in the last column of the associated summary analysis template as well as in the opening section of Chapter 4 – Analysis and Results.

# 4 ANALYSIS AND RESULTS

## INTRODUCTION

This chapter has a pyramidal organization much like the report itself, beginning with the findings and continuing down through the analyses to the data. It commences with the training topics that resulted from the summation of all the various analyses followed by the supporting analyses.

13 topic worksheets integrate the EBT Accident-Incident Study factor analysis with the Evidence Table Summary matrix, providing singular results according to each Training Topic. See Appendix 13 for the worksheets for each of the training topics.

This type of layout provides a clear view of the information from its source and the logic of the analysis. It also demonstrates the results in terms of their relevance to training.

# 4.1 SUMMARY ANALYSIS BY TOPIC

# 4.1.1 Unstable Approaches

The rate of unstable approaches remains a consistent problem at approximately between 3 - 4% across aircraft generations and geographical regions. The increased risk that is associated with unstable approaches becomes evident when examining event rates and event severity. Landings from unstable approaches have a higher risk and as the events themselves become more severe, the risk escalates in an accelerated manner.

As pilots continue to make unstable approaches they continue to land from them instead of executing the go-around required by SOP. Pilots admit to this violation, citing many reasons including the fact that they feel less comfortable with the go-around than the subsequent landing. The data support that go-arounds are usually not well executed.

Interestingly, unstable approaches can be viewed as a barometer of the flight itself; flights with unstable approaches generally have more FDA risk events in all flight phases, including phases not associated with the approach.

Training should address this issue, not only for the approach, but the go-around as well. Associated issues of non-compliance and pilot confidence should also be addressed to effectively treat the continuing problem of the unstable approach.

### 4.1.2 Automation

According to LOSA almost 30% of the flights have at least one automation error with almost half of them not detected or not acted upon by the crew. Training reports that automation is an issue of concern regarding assessments in both the planning and execution phases of flight. Pilots themselves are heavily critical of automation training during the initial type rating with only 25% of the pilots feeling prepared to utilize the automation when released to line operations.

A major accident investigation agency believes that because mismanaged automation is further upstream in the error chain, it is under reported in causal accident investigation. Another authority states that many pilots use the autoflight when inappropriate and fail to revert to manual flight when required. The skill decay study shows that skill losses can be substantial and decay without practice. This deterioration is much greater for skilled tasks, such as certain automation skills making it important to assess these skills in training particularly for pilots that do on operate routinely. All of this points to a need to change the way current training is accomplished. A total of 60% of pilots reported that operational FMS training was not provided during initial training, and that they were left to self-learn during line operations.

Recommendations to improve training include that training should enhance mode and position awareness when using automation, particularly with regard to terrain, energy and upset. In addition, there should be adequate training content to ensure airmanship, CRM, decision-making and workload management when utilizing automation, especially in demanding situations. Training should also include multiple assessment techniques, confirming that pilots understand the logic, design purpose and limitations of the automation. Practice and reinforcement should be accomplished in an operational setting, managing automation at all levels and including reversions to manual flight.

# 4.1.3 Error Management

Effective monitoring and error detection are increasingly important when operating highly reliable, automated aircraft. Multiple data sources provide evidence of substantial rates of undetected error. Error management is reported as a very significant countermeasure in current operations with one accident study espousing that it is the most significant tool available to pilots for the prevention of accidents. Multiple sources of data show that there is a high level of intentional non-compliance and so any error management strategy must include greatly reducing its incidence.

Error management skills are subject to decay. Error management currently does not form part of any strategy developed through the regulation of flight crew training, so consequently it is lacking in most training programs. It is a key topic and needs to be incorporated into training strategies in order to raise flight crew situation awareness and further develop the professional capabilities of pilots.

# 4.1.4 Manual Aircraft Control (Flight Path Management – Manual)

Manual aircraft control is one of the most important topics in operations and training. It ranks very highly as a competency issue in accident reports. Various sources of flight operations data show substantial competency issues associated with manual control. The phases of flight that routinely involve manual aircraft control such as take-off, landing and taxing show a very significant percentage increase in accidents over the last decade. Unintentional deviations and failure to follow flight guidance, plus speed and thrust errors, exacerbated by adverse weather, are some of the issues being observed. Landings with high vertical acceleration, difficulties in crosswinds, long touchdowns and substantial handling errors during go-arounds are amongst the problems revealed by flight data. While training data indicate rapid mastery of manual control especially in Gen 4 jets, this effect can easily be undermined in complex and unexpected situations. Results show that safety while using automation depends on flight crews having the confidence to fly manually.

Data across the EBT study highlight the importance of training to mitigate an obvious deterioration in manual aircraft control skills. Pilots are well aware of the need for manual aircraft control training and clearly expressed this need when responding to the Airline Pilot Perceptions of Training Effectiveness Survey. Training data effectively shows that the trend can be reversed providing the skill is mastered. Skill retention data in two independent reports show that manual aircraft control skills are resistant to decay as long as they are practiced.

Good manual control skills include transitioning in and out of automation, with attendant and realistic distractions and threats from the environment, aircraft systems and ATC. Simply to continue practicing only traditional and rote maneuvers is insufficient for crew confidence and proficiency required for modern aircraft in today's environment.



# 4.1.5 Go-Arounds

Despite efforts to eradicate unstable approaches and to mandate go-arounds should an unstable approach occur, the occurrence rate of unstable approaches remains significant as well as the fact that flight crews simply do not go around as mandated. A major concern of unstable approaches is the disregard of the SOP's, in addition to the efficacy of threat and error management during the entire flight. According to the LOSA report, there is a "90% (SOP) violation factor" in terms of not executing a go-around from an unstable approach.

Unstable approaches are often a barometer for the flight itself. If an approach is poorly executed, there are strong indications from the data that the rate of errors and risk events will be higher across the entire flight, according to FDA and LOSA. Data from multiple operational and training sources indicate that crews almost universality have problems with the go-around. This is because it is not usually expected, and may have to be executed under demanding conditions, from altitudes and energy states other than those practiced in training. When unraveling the unstable approach paradox, one issue remained clear throughout; flight crews must acquire the necessary capability to execute a go-around from any situation, utilizing automation and/or manual control skills as appropriate.

The multi-source data are quite compelling on the current state of the go-around in operations and training today. Yet variable Go Around management with all engines operating does not form part of any strategy developed through the regulation of flight crew training. This is a key topic and needs focus to raise awareness and develop pilot capability. A strategy for training should address multiple intersecting issues in addition to providing exposure and building confidence in this area.

# 4.1.6 Adverse Weather

Despite improvements in aircraft design and automation systems, it is clear from multi-source data that adverse weather is still a very substantial threat to the safety of commercial air transport operations. Accident and serious incident data indicate a strong presence of adverse weather as a factor, and this is corroborated by operations data. The trend is particularly concerning in Gen 2 aircraft where the percentage of fatal accidents in which weather has been a factor has doubled in the last 15 years. Adverse weather increases workload, distracts the crew from normal tasks, including monitoring, and increases the risk of mismanagement of crew error.

The data indicate that operations in adverse weather should be effectively trainable, and that the creation of training scenarios should include dynamic and variable weather conditions, forcing crews to consider and manage, avoid and react, as conditions require. This EBT study is rich with data about adverse weather from many sources offering the opportunity to create realistic training to mitigate the seemingly ever-present threats to flight crews from adverse weather.

# 4.1.7 System Malfunction

According to EBT accident-incident data, system malfunction has reduced as a factor in accidents and major incidents as design and reliability of modern aircrafts have evolved. This is not the case for Gen 2 Jet aircraft, and system malfunctions are a significant contributor to undesired aircraft states, which are or can be a pre-cursor to incidents and accidents The management of an unexpected malfunction induces crew error, and according to operations data, remains a threat partly due to the distraction from normal duties, intentional noncompliance with procedures and the vulnerability of closed loop tasks.

Improvements in engine reliability are well documented and understood, and the rate of engine failures has reduced substantially. However, training data indicate that handling the aircraft in unexpected engine-out situations still presents difficulty to crews, and there remains a clear need to continue to practice the psychomotor skills based capability to fly the aircraft with an engine inoperative as part of an EBT program.



# 4.1.8 Terrain

There has been a significant reduction in accidents and incidents with terrain as a factor since the inception of TAWS regulation. However, the data from several sources indicate a decline in flight crew situation awareness with regard to terrain and terrain remains one of the most important mismanaged threats in the cockpit. While advancing technology has provided a very effective alerting system, attention needs to be placed on the need to ensure crews are vigilant and maintain at a high level of SA and not become complacent with regards to terrain.

# 4.1.9 Surprise

As design and reliability improve, the likelihood of crews facing specific malfunctions and events reduces. Isolated and unexpected events become more problematic as reliability is improved while attending to the overall system becomes more complex. A lack of effective procedural and conceptual knowledge of automation often leads to surprises in operations. Data indicate that cognitive tasks have potential for skills decay and flight path control in dynamic situations is often more demanding especially where there are attendant distractions from the environment, system or ATC.

Pilots reported that they often face operational surprises for which they have not been trained. In modern generation aircraft, the accident and serious incident data show an increase in poor situation awareness when things go wrong.

Despite all the data, current training is driven by highly prescriptive regulatory requirements based on evidence from early jets and training programs containing many elements, most of which are highly predictable. Data from operations and training indicate crews face substantial problems when dealing with unexpected events, for example executing an unanticipated all engine operative go-around, simply because they are unexpected and often performed in conditions not experienced in training.

# 4.1.10 Landing Issues

According to multiple accident studies the landing phase ranks first or second as the phase with the highest percentage of accidents and this trend is increasing. One study shows that accidents involving a landing short of the runway have doubled in the last decade. Landing problems are complex, as the accident-Incident data rank landing accidents number 1 in the clustering of factors. According to operational data the third most frequent non-compliance item is landing from an unstable approach; the same study also indicated that handling errors on landing are not well detected.

Training data indicates that landing skills take time to develop, while other studies show deterioration in the skills necessary in landing without practice, as well as the need for emphasis on training to better understand environmental and aerodynamic effects associated with landing. Most importantly realistic training should continually emphasize when and how to apply the go–around as a landing escape maneuver.



# 4.1.11 Compliance

Intentional non-compliance remains a substantial problem, and while the level of crew non-technical competency has shown signs of improvement over the most recent periods examined, non-compliance remains a serious weakness in current operations. It has decreased somewhat in the last 15 years but not at the same rate as has accidents. A notable exception to this is Gen 2 Jet where the rate has actually increased. There are many potential reasons for crews to deviate routinely from SOP's and these include attempts to optimize the operation, particularly in time-constrained situations. Complacency due to familiarity is another factor. However, the data show significant correlation between non – compliance and large increases in risk of undetected errors and undesired aircraft states. Checklist and call-out protocols show substantial signs of weakness. The failure of crews to execute a Go-round under conditions when SOP requires it is a very significant area of intentional non-compliance. Pilots admit to call-out and checklist deviations on a regular basis, as well as the failure to adhere to approach procedures and execute Go-rounds when required.

Crew discipline has always been assumed to be a pillar supporting operational safety and now the data show its breakdown. Crews must understand that intentional non-compliance, correlates highly with errors resulting in undesired aircraft states and that compliance failures also rank highly in accident data.

Crews are currently trained to comply and demonstrate adherence to SOP, but detecting and addressing non-compliance is not a feature of existing training programs. Data indicate that effective training and appropriate focus on areas such as leadership can address non-compliance.

# 4.1.12 Leadership

Leadership and teamwork as a competency issue has more than doubled in recent years. This is the case for all generations but it is even more pronounced for modern generation aircraft. The prevalence of a noncompliance culture is indicative of lack of appropriate leadership focus. In addition several sources point to a well understood need and desire for better leadership from flight crews. Data from pilots indicate a willingness to demonstrate effective leadership and make decisions enhancing and protecting the level of operational safety.

The absence of effective leadership in the cockpit adds substantially to the risk of mismanaged threats and errors leading to undesired aircraft states. Conversely, leadership when coupled with effective communication proves to be a very effective catalyst for managing threats and both reducing and managing errors.

From a training perspective, data indicate that leadership can be effectively developed, when there is a strong compliance culture, which in turn necessitates the careful design of effective procedures and adherence to them. The fact that leadership and teamwork is not reported as a competency issue in serious incidents indicates the importance of it as a mitigating agent in accidents as well as its importance in training. Strengthening leadership in training improves compliance, hence risk will be reduced and crews should be able to deal more effectively as a team with today's complex environment and function more effectively when faced with unfamiliar situations.

### 4.1.13 Mismanaged Aircraft State

Mismanaged aircraft state is a leading factor in the accident and serious incident reports in all generations and during all time periods. There is a reported weakness in prevention of mismanaged aircraft states as well as in the skills to recover from them after entry. Examples are landing incidents following unstable approaches and manual aircraft control competency issues. Mismanaged aircraft states occur for many reasons, all of which are of significance from a training perspective.

Aircraft states cited include flight path issues involving potential and actual loss of control, terrain and energy awareness. The flight phases having the most mismanaged aircraft states are descent, approach and landing. Effort needs to focused on detecting the errors that lead to mismanaged states as evidence shows that during these dynamic phases a large percentage are not detected until after the state becomes critical.

Recommendations include regular training to avoid mismanaged aircraft states as well as recovery from inadvertent entries and reinforcement training in basic flying skills such as manual handling, landings and go-arounds. Flight crews are reluctant to revert to manual flight from automation, while basic maneuvers such as landings and go-arounds continue to be a problem. The reports propose that proficiency, discipline and confidence be fostered during training to combat mismanaged aircraft states.

# 4.1.14 Upset

While upset still ranks as a major cause of accidents when measured as a category in several accident reports, its percentage of total accidents has remained steady in the last two decades. Several reports in the meta-study list this category of accidents as a concern.

Training should prepare pilots for any contingency whether expected or not. Manual aircraft control skills are important as reiterated many times in this report and pilots must have the skills to recognize and execute the recoveries from developing upsets (any time the aeroplane begins to unintentionally diverge from the intended flight path or airspeed). Prevention is key, with a strong focus on the detection and early intervention to prevent upsets from occurring. This is the essential strategy that must become an integral part of training.

# 4.2 ANALYSIS BY SOURCE

# 4.2.1 LOSA

### Introduction

The LOSA study was specifically targeted to address issues likely to receive effective mitigation by appropriate training. The information that follows in this section illustrates the various areas of risk, as determined by LOSA data from approximately 9,000 observed flights across multiple airlines in various regions of the world when training intervention is considered likely to mitigate risk substantially.

The bullet statements at the beginning of each subsection of a particular source depict the processes used in the analysis of the Evidence Table. The functions (e.g., Filter) used to sort the respective data create specific support tables, shown as associated figures for each training topic per source.

### 4.2.1.1 Unstable Approaches and Go-Arounds

- Filter Evidence Table LOSA Reports
- Filter Topic Unstable Approach
  - See Figure 4.2.1.1
  - Result LOSA Unstable approach
    - The unstable approach rate is 4%.of all approaches
    - 97% of all the unstable approaches terminate in landing, 90% of which are uneventful.
    - In virtually all cases both pilots are willing to continue to land even though the approach is not stabilized.
    - Missed approaches as a result of unstable approaches are usually a surprise to the crew and rarely well executed.
    - In many cases the pilots act as if they are not aware that the approach is not stabilized or do not know the criteria for a stabilized approach.



- 97% of unstable approaches are not linked to weather or ATC. Failure to go-around from an unstable approach is the 3<sup>rd</sup> ranked non-compliance issue. .
- Crews sometimes volunteer to assist ATC, and this compromises a stabilized approach.
- The effects of unstable approaches are consistently in the top five undesired aircraft states in . the LOSA archives.
- Summary Unstable approaches remain a consistent problem at a rate of approximately 4%. They 0 almost always result in an uneventful landing. The crews in most cases have mismanaged the situation but are willing to continue the approach, violate SOPs and/or are unsure of the appropriate stabilized approach criteria.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicable to Generations	Source	Training Topics	Factors	Competencies
1	Unstable Apprs: 4% of approaches were unstable. 97% continued to landing.1% of such landings were abnormal. Both crew members willing to continue even if unstable.	APR	234	All	LOSA	Unstable APP Go Arounds	CRM Mis A/C State Compliance	Application of Procedures/Knowledge
2	Pilots did not know stable approach criteria.	APR	234	All	LOSA	Unstable APP Go Arounds	CRM	Knowledge
3	3% of Unstable Appes are linked to weather and ATC.	APR	234	All	LOSA	Unstable APP WX	Adverse Weather/Ice ATC	
4	Missed Approaches as result of Unstable Appes are rarely handled well. Risk rises dramatically which is problematic.	APR GA	234	All	LOSA	Unstable APP Go Arounds	Mis A/C State	Application of Procedures/Knowledge
5	Usually a surprise to the crew. None occurred at standard missed approach height briefed.	APR	234	All	LOSA	Go Arounds Surprise	Compliance CRM	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual AC Control
33	Number 3 non-compliance item: Fail to execute missed appr when required	APR	234	All	LOSA	Unstable APP Landing Issues Go Arounds	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making Application of Procedures/Knowledge
44	Crews often agree to ATC clearances in order to "help".	CLB DES APR	234	All	LOSA	Error Mgt Leadership	ATC Workload Distraction Pressure Mis A/C State Mis-AFS	Communication Flight Management Guidance and Automation Manual AC Control Problem Solving Decision Making
52	In top 5 - UAS in DES/APR/LND: speed too high	DES APR LDG	234	All	LOSA	Unstable APP Landing Issues	ATC Compliance CRM Mis A/C State	SA Workload Management Problem Solving Decision Making Flight Management Guidance and Automation
53	In Top 5 - UAS in DES/APR/LND: Unstable App	DES APR LDG	234	All	LOSA	Unstable APP Landing Issues	ATC Compliance CRM Mis A/C State	SA Workload Management Problem Solving Decision Making Flight Management Guidance and Automation Application of Procedures/Knowledge
54	In top 5 - UAS in DES/APR/LND: incorrect A/C config-Automation	DES APR LDG	234	All	LOSA	Unstable APP	Compliance CRM Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance and Automation Application of Procedures/Knowledge
55	In top 5 - UAS in DES/APR/LND: incorrect A/C config-systems	DES APR LDG	234	All	LOSA	Unstable APP Go Arounds	Compliance CRM Mis A/C State Mis-Sys	Problem Solving Decision Making Application of Procedures/Knowledge
56	In top 5 - UAS in DES/APR/LND: continued landing after Unstable App	DES APR LDG	234	All	LOSA	Unstable APP	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making

Figure 4.2.1.1 – Unstable Approach/LOSA

# 4.2.1.2 Automation

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Topic [Automation]
  - See Figure 4.2.1.2
  - Result LOSA Automation
    - 28% of flights in the LOSA database have an automation error. Almost 1% of flights have automation errors that lead to consequences, in LOSA terms UAS.
    - 21% of automation UAS result from monitoring and crosschecking errors.
    - Mismanaged flight guidance is the most prevalent automation error, followed by late disengagement of the system in DES, APP and LDG and manual flight at inappropriate times. Failures to cross check SID and STAR is also listed as an automation error.
    - A major reported problem is lack of understanding of the automation systems.
    - Pilots do not communicate mental models of the automation in the cockpit.
    - Automation mode confusion is a significant issue.
    - The overarching problem with automation is monitoring and crosschecking.
    - 47% of all automation errors are not detected or acted upon by the crews.
  - Summary Statement: The overarching problem with automation for the flight crews is monitoring and crosschecking. 28% of the flights have at least one automation error with almost half of them not detected or acted upon by the crew. In addition there is a basic problem with understanding the system, mode confusion and using the automation and/or flying manually at inappropriate times.

E re	Evidence Statement	Flight Phase	Gen Specific	Applicable to Gens	Source	Keywords	Training Topics	Factors	Competencies
7	In terms of mismanaged errors guidance are far more prevalent than programming errors.	All	234	All	LOSA	Error Automation Training	Automation Error Mgt	Mis-AFS	Flight Management Guidance/Automation
8	Technical understanding of the Automation	All	234	All	LOSA	Automation Competencies Training	Automation	Mis-AFS CRM	Flight Management Guidance/Automation Knowledge
ę	A lack of "verbalization" by crew to share mental models	All	234	All	LOSA	Competencies Automation Training	Automation Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Communication
1	The late engagement of autopilot after takeoff or early disengagement in Descent/Approach/Land,Basically hand flying at an inappropriate time. Common errors include hand flying in a busy Terminal Area.	CLB APP	234	All	LOSA	Automation Competencies	Automation Manual AC Control Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Problem Solving Decision Making
1	Control Zone, looking through the FD, not checking modifications to the SID, STAR or Approach profile and relying on the PM to effect FMC/FMGC changes.	CLB APP	234	All	LOSA	Automation Training	Automation Manual AC Control Monitor Xcheck	Mis-AFS CRM	Flight Management Guidance/Automation Workload Management Manual Aircraft Control Application of Procedures/Knowledge
1	The overarching element is Monitoring/Cross-Checking, with little to no dialogue between the pilots during most of the errors.	All	234	All	LOSA	Automation Error MonitoringXchecking Training	Automation Monitor Xcheck Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Communication SA
1	21% of the Automation induced undesired aircraft states result from SOP Cross-Verification errors	All	234	All	LOSA	Automation Error MonitoringXchecking UAS	Automation Monitor Xcheck Error Mgt	Mis-AFS CRM Mis A/C State	Flight Management Guidance/Automation SA
1	There are often misunderstandings of autopilot modes.	All	234	All	LOSA	Automation Competencies Training	Automation Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Knowledge
4	ATC threat 2: Runway Changes, leading to Automation Issues, Briefing errors, SOP errors, Aircraft configuration issues.	APP GND	234	All	LOSA	Communication Automation Error	Error Mgt Automation	ATC Workload Distraction Mis A/C State Mis-AFS CRM Compliance	Communication Application of Procedures/Knowledge Flight Management Guidance/Automation
11	41% of Aircraft Handling errors are detected and acted upon vs. 2 16% of Procedural errors Automation has the best rate of all error types. (53%)	All	234	234	LOSA 2	Error ManualACControl MonitoringXchecking	Error Mgt Automation Monitor Xcheck	Compliance CRM Mis A/C State Mis-Sys	SA Leadership and Tearnwork Workload Management Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
13	Automation errors have the best detection with action rates of all error types - 53% of Automation errors are detected and acted upon by flight crews.	All	234	234	LOSA 2	Error MonitoringXchecking	Automation Error Mgt	Mis-AFS	Flight Management Guidance/Automation

Figure 4.2.1.2 - Automation/LOSA



# 4.2.1.3 Error Management

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Topic [Error management]
  - See Figure 4.2.1.3
  - Result LOSA Error Management
    - LOSA archive shows that 26% of all errors logged by observers are detected and acted upon by flight crews.
    - A key error management strategy is monitoring and crosschecking.
    - Two of the more frequent monitoring and crosschecking errors logged in LOSA are callout and SOP cross verification errors.
    - The highest risks among callout errors are omitted deviations (65% result in UAS).
    - The flight phase with most threats is pre-departure.
    - Flight phases with the most mismanaged errors and UAS are DES, APP, LDG
    - Error management is generally better in the first four flight phases.
    - The rates of error detection and action are much higher for aircraft handling errors than for procedural errors.
    - Automation errors have the best detection/action rates of all error types 53% of Automation errors are detected and acted upon by flight crews.
    - 41% of aircraft handling errors are detected and acted upon versus 16% of procedural errors.
    - For procedural error types, checklist error detection is better in CRZ and DES/ APP/LDG, while callout error detection is better in TO/CLB.
    - There is little difference in the error detection rate when crewmembers are PM.
    - Once an error has been committed, crews are more capable of detecting other people's errors than their own.
    - Captains detect 27% of the First Officer errors; First Officers detect 18% of the Captain's errors.
    - Both Captains and First Officers detect only 5-6% of the errors that they individually make.
  - Summary Statement: A key strategy for managing flight crew errors is monitoring and crosschecking. The situation is critical as just over 25% of the errors made by the flight crews are detected and rectified. The highest risk is crosschecking errors (e.g., omitted deviations as they result in 65% of UAS). The flight phase with the most threats is pre-departure, while the most mismanaged errors occur in DES, APP and LDG. Error detection is generally better in the early phases of flight with automation error captured being the best overall (53%) and procedure (16%) being the poorest. The Captain detects more errors than the First Officer (27% versus 18%) but neither rates highly at detecting their own errors (5-6%).



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Generations	Source	Training Topics	Factors	Competencies
18	About 4% of all flights are rated poor or marginal on Monitoring/Cross-Checking in at least one phase of flight. Flights with poor or marginal monitoring/Cross-Checking ratings have double the rate of mismanaged threats than those with Good or above.	All	234	All	LOSA	Monitoring Xcheck Error Mgt	CRM Workload Distraction Pressure Compliance	SA Workload Management Application of Procedures/Knowledge
19	Two of the more frequent Monitor/Cross-Checking errors logged in LOSA are Callout and SOP Cross verification errors.	All	234	All	LOSA	Monitoring Xcheck Error Mgt	CRM Workload Distraction Pressure Compliance	SA Workload Management Application of Procedures/Knowledge
20	Among callout errors, the ones for omitted deviation callouts have the highest risk (65% UAS/added error rate).	All	234	All	LOSA	Leadership Error Mgt Monitoring Xcheck	Compliance	Leadership and Teamwork Application of Procedures/Knowledge
23	28% of flights in the LOSA Archive have an SOP Cross-Verification error. 1% of these are mismanaged.	All	234	All	LOSA	Monitor Xchk Error Mgt	Mis-AFS Mis A/C State Mis-Sys	Application of Procedures/Knowledge Flight Management Guidance and Automation Manual AC Control
25	Most Risky cross-verification errors: Failure to cross-verify alt setting, Failure to cross-verify FMS settings (14% UAS/added error rate)	All	234	All	LOSA	Monitor Xchk Error Mgt	Mis-Sys Mis-AFS	SA Flight Management Guidance and Automation
26	Most important mismanaged Threat: Terrain. Both omitted callouts and failure to select Terrain feature on Nav Display are a common and risky combination. Airlines that operate in high Terrain areas tend to get too used to this threat.	TO CLB DES APR LDG	234	All	LOSA	Terrain Monitor Xchk Error Mgt	Mis-Sys Compliance	SA Application of Procedures/Knowledge
30	Intentional Noncompliance: significant positive correlation between this and the number of mismanaged threats, unintentional errors, mismanaged errors and UAS.	All	234	All	LOSA	Error Mgt	Compliance CRM Mis-AFS Mis A/C State Mis-Svs	Leadership and Teamwork Application of Procedures/Knowledge
38	If communication is poor, TEM is poor despite good Leadership by captain.	All	234	All	LOSA	Error Mgt	CRM	Communication Leadership and Teamwork
50	Flight phases: most threats in pre-departure.	GRD	234	All	LOSA	Error Mgt	Cabin CRM	Leadership and Teamwork Workload Management
51	Flight phases: most mismanaged errors and UAS in DES, APR, LND	DES APR LDG	234	All	LOSA	Error Mgt	Workload Distraction Pressure CRM Workload Distraction Pressure Mis A/C State Mis-Svs	Leadership and Teamwork Workload Management
58	Predeparture/Taxi-out are extremely important phases from the point of view that they are fertile territory for mitigating threats by training.	GRD	234	All	LOSA	Error Mgt	Ground manoeuvring CRM	SA Leadership and Tearnwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance and Automation
110	ManualACControl/Flight Control error detection/action taken is notably stronger in Predeparture/Taxi-Out than in the other phases of flight	GRD	234	All	LOSA 2	Manual AC Control Error Mgt Monitoring Xcheck	Mis-Sys Mis A/C State	SA Problem Solving Decision Making Manual AC Control
111	Callout error detection is better in Takeoff/Climb.	CLB	234	All	LOSA 2	Error Mgt Monitoring Xcheck	Compliance CRM	Communication SA Application of Procedures/Knowledge
112	4 41% of Aircraft Handling errors are detected and acted upon vs. 16% of Procedural errors Automation has the best rate of all error types. (53%)	All	234	234	LOSA 2	Error Mgt Automation Monitoring Xcheck	Compliance CRM Mis A/C State Mis-Sys	SA Leadership and Teamwork Workload Management Application of Procedures/Knowledge Flight Management Guidance and Automation Manual AC Control
113	Captains detect 27% of the First Officer mistakes; First Officers detect 18% of the Captain's errors.	All	234	234	LOSA 2	Error Mgt Monitoring Xcheck	Compliance Mis-AFS Mis A/C State Mis-Sys	Application of Procedures/Knowledge Flight Management Guidance and Automation Manual AC Control Communication
114	Once an error has been committed, people are more capable of detecting other people's errors than their own.	All	234	All	LOSA 2	Error Mgt Monitoring Xcheck	Compliance Mis-AFS Mis A/C State Mis-Sys	Application of Procedures/Knowledge Flight Management Guidance and Automation Manual AC Control Communication
115	Across all three error groups, the Captain as PF detects/acts on more errors than does the First Officer as PF, particularly for Communication errors. There is little difference in PM rates.	All	234	All	LOSA 2	Error Mgt Monitoring Xcheck	Compliance Mis-AFS Mis A/C State Mis-Sys	Application of Procedures/Knowledge Flight Management Guidance and Automation Manual AC Control Communication
116	As the rate of Intentional Noncompliance increases, the rate of errors detected and acted on decreases.	All	234	All	LOSA 2	Error Mgt	Compliance	Application of Procedures/Knowledge
117	The LOSA Archive shows that 26% of all errors logged by observers are detected and acted upon by flight crews.	All	234	234	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
118	Error detection is most closely aligned with the quality of Monitoring/Cross-Checking in all phases of flight and the quality of the Briefing.	All	234	All	LOSA 2	Error Mgt Monitoring Xcheck	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
119	One-quarter of all errors in the cockpit are detected, acted upon and inconsequential.	All	234	234	LOSA 2	Error Mgt	Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
120	One-half of all errors in the cockpit go undetected/not acted upon and are also inconsequential.	All	234	234	LOSA 2	Error Mgt	Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
121	taking shortcuts' reinforces over and over that most errors are inconsequential, whether they act on them or not. <b>PARADOX</b>	All	234	234	LOSA 2	Error Mgt complaince	CRM Compliance	Application of Procedures/Knowledge leadership and Teamwork
122	An error that is detected and acted upon does not guarantee an inconsequential outcome. In fact, 1% of errors detected and acted upon by a flight crew link to an additional error or undesired aircraft state due to active misManagement.	All	234	234	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
123	There is little difference amongst the first four phases of flight in that 25-30% of errors are detected and acted upon.	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Svs	Communication Application of Procedures/Knowledge Manual AC Control
124	Taxi/Park has the lowest rate of errors detected and acted upon (17%) because approximately one-half of the errors in Taxi/Park are Intentional Noncompliance errors vs. about one-quarter of errors in the other phases.	GRD	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
126	ManuaAcControl/Flight Control errors - error detection/action is notably stronger in Predeparture/Taxi-Out than in the other phases of flight (53% of ManuaACControl/Flight Control errors are detected and acted upon during Predeparture/Taxi-Out vs. 21-30% of ManuaACControl/Flight Control errors being detected and acted upon in later phases of flight	GRD ALL	234	All	LOSA 2	Error Mgt	Mis A/C State	Manual AC Control
127	vnen compared with the other Aircraft Handling error types, it seems that error detection for ManualACControl/Fight Control errors weakens notably after departure/Taxi-Out, while Automation and System/Instrument/Radio error detection rates stay relatively the same	GRD ALL	234	All	LOSA 2	Error Mgt	Mis A/C State	Manual AC Control

Figure 4	.2.1	3 –	Error	Management	t/LOSA
•					

_								
128	Procedural error types, Checklist error detection is better in Cruise and Descent/Approach/Land while Callout error detection is better in Takeoff/Climb.	TO CLB CRZ DES LDG	234	All	LOSA 2	Error Mgt	Mis-Sys Compliance	Application of Procedures/Knowledge
129	The rates of error detection and action are much higher for Aircraft Handling errors than for Procedural errors.	All	234	All	LOSA 2	Error Mgt	Mis-Sys Compliance Mis A/C State	Application of Procedures/Knowledge Manual AC Control
130	Specifically, 41% of Aircraft Handling errors are detected and acted upon vs. 34% of Communication errors and 16% of Procedural errors.	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Svs	Communication Application of Procedures/Knowledge Manual AC Control
131	The detection and action rates for Procedural errors are shown below: o Briefing 20%, o Callout 22%, o Checklist 20%, o Documentation 30%, o General Procedural 7%, o PF/PM Duty 5%.	All	234	All	LOSA 2	Error Mgt Monitoring Xcheck	Compliance	Communication Application of Procedures/Knowledge
132	Automation errors have the best detection with action rates of all error types - 53% of Automation errors are detected and acted upon by flight crews.	All	234	234	LOSA 2	Automation Error Mgt	Mis-AFS	Flight Management Guidance and Automation
133	The Aircraft handling with the lowest rate of detection are: (Many are not detected until UAS) o Unintentional vertical deviation 41% o Wrong speed brakes setting 39% o Ioncorrect Nav Display setting 35% o Unintentional landing deviation 32% o Wrong radar setting 30% o Unintentional speed deviation 24% o Unintentional speed deviation 24% o Wrong power/thrust setting 22% o Wrong power/thrust setting 22%	All	234	All	LOSA 2	Landing Issues Manual AC Control Error Mgt	Mis-AFS Mis A/C State Mis- Sys	Problem Solving Decision Making Manual AC Control
135	Both Captains and First Officers detect only 5-6% of the errors that they make.	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
137	Both Captains and First Officers detect only 5-6% of the errors that they make.	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
138	The general pattern is consistent across error types i.e. o Captains can deted 39% of the Aircraft Handling errors made by First Officers but only 9% of their own Aircraft Handling errors o First Officers can detect 12% of the Procedural errors made by Captains, but only 4% of their own Procedural errors.	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
139	There is very little difference in error rate detection between the crew member position as PF and PM and very little difference between Capt and F/O as error detectors with the Capt detecting slightly more in either case. 0 Capt as PF $-7\%$ vs Capt as PM $-7\%$ 0 F/O as PF $-4\%$ vs F/O as PM $-6\%$	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
140	There is however a difference between Capt's and F/Os when action is combined with detection. The Capt is much more likely to act when detecting own error while pilot flying VS the F/O (23% vs 13%)	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
141	When the Capt is PM the rate for detecting own error and taking action is about the same as F/O as PM (25% vs 22% respectively)	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
142	25% of all errors are recorded as Intentional Noncompliance errors,	All	234	All	LOSA 2	Error Mgt	Compliance	Application of Procedures/Knowledge

Figure 4.2.1.3 continued

# 4.2.1.4 Manual Aircraft Control

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Topic [Man A/C Control]
  - See Figure 4.2.1.4
  - Result LOSA Manual Aircraft Control
    - Failure to follow flight guidance commands, not checking SID, STAR or approach profile and relying on the PM to make FMS changes.
    - Manual aircraft control errors are exacerbated by thunderstorms and adverse weather
    - Many manual aircraft control errors result from crew accepting clearances in order to "assist" ATC.
    - 41% of aircraft handling errors are detected and acted upon.
    - The leading manual aircraft control problem is vertical deviation (41%), followed by landing deviation (32%), followed by lateral deviation (29%) then speed deviation (24%), and finally improper thrust setting (22%).
    - Captains detect 39% of the aircraft handling errors made by First Officers but only 9% of their own.
  - Summary According to LOSA, manual control errors, while not the most frequent type of error (41% occurrence by flight), are only exceeded by automation errors. Many manual control errors result from the improper technique, flight crews ignoring or "flying through" the indicated flight guidance. Manual control problems are exacerbated in adverse weather. The leading error type is unintentional vertical deviation (32%) followed closely by deviations in landing, lateral, speed and improper thrust.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Generations	Source	Training Topics	Factors	Competencies
11	Control Zone, looking through the FD, not checking modifications to the SID, STAR or Approach profile and relying on the PM to effect FMC/FMGC changes.	CLB APR	234	All	LOSA	Automation Manual AC Control Monitoring Xcheck	Mis-AFS CRM	Flight Management Guidance and Automation Workload Management Manual AC Control Application of Procedures/Knowledge
27	Thunderstorms/Turbulence: Common errors associated are ManualACControl, Flight control and System, Instrument and Radio error. – exacerbate the situation.	TO CLB DES APR	234	All	LOSA	WX Error Mgt Manual AC Control	Adverse Weather/Ice Workload Distraction Pressure Mis A/C State Mis-Sys	Communication SA Workload Management Application of Procedures/Knowledge Manual AC Control
44	Crews often agree to ATC clearances in order to "help".	CLB DES APR	234	All	LOSA	Error Mgt Leadership	ATC Workload Distraction Pressure Mis A/C State Mis-AFS	Communication Flight Management Guidance and Automation Manual AC Control Problem Solving Decision Making
110	ManualACControl/Flight Control error detection/action taken is notably stronger in Predeparture/Taxi-Out than in the other phases of flight	GRD	234	All	LOSA 2	Manual AC Control Error Mgt Monitoring Xcheck	Mis-Sys Mis A/C State	SA Problem Solving Decision Making Manual AC Control
112	41% of Aircraft Handling errors are detected and acted upon vs. 16% of Procedural errors Automation has the best rate of all error types. (53%)	All	234	234	LOSA 2	Error Mgt Automation Monitoring Xcheck	Compliance CRM Mis A/C State Mis-Sys	SA Leadership and Teamwork Workload Management Application of Procedures/Knowledge Flight Management Guidance and Automation Manual AC Control
129	The rates of error detection and action are much higher for Aircraft Handling errors than for Procedural errors.	All	234	All	LOSA 2	Error Mgt	Mis-Sys Compliance Mis A/C State	Application of Procedures/Knowledge Manual AC Control
130	Specifically, 41% of Aircraft Handling errors are detected and acted upon vs. 34% of Communication errors and 16% of Procedural errors.	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
133	The Aircraft handling with the lowest rate of detection are: o Unintentional vertical deviation 41% o Unintentional landing deviation 32% o Linitentional lateral deviation 29%.	All	234	All	LOSA 2	Landing Issues Manual AC Control Error Mgt	Mis-AFS Mis A/C State Mis-Sys	Problem Solving Decision Making Manual AC Control
138	Captains can detect 39% of the Aircraft Handling errors made by First Officers but only 9% of their own. oerrors.	All	234	All	LOSA 2	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control

Figure 4.2.1.4 - Manual Aircraft Control/LOSA





### 4.2.1.5 Go-Around

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Word search [(GA) (Go-around) (Missed Approach)]
  - See Figure 4.2.1.5
  - Result LOSA Go-Around
    - Only 3% of unstable approaches resulted in a go-around.
    - Missed Approaches as a result of unstable approaches are usually poorly executed.
    - Missed approaches are usually a surprise to flight crew and none in LOSA database occurred at the altitude briefed during the approach briefing.
    - One of top 5 contributory factors to the unstable approach UAS is incorrect aircraft configuration.
    - One of top 5 UAS after unstable approach is a failure to go-around, which is also and number 3 in non-compliance items.
  - Summary According to LOSA, go-around from unstable approaches occur only 3% of the time (contrary to SOP's). Landings from unstable approaches rank in the top 5 UAS during the LDG phase and are the number 3 non-compliance item in the LOSA database). When a go-around from an unstable approach is performed it is usually a surprise to the crew and poorly executed.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
1	Unstable Apprs: 4% of approaches were unstable. 97% continued to landing.10% of such landings were abnormal. Both crew members willing to continue even if unstable.	APR	234	All	LOSA	Unstable APR/GA	Unstable APP Go Arounds	CRM Mis A/C State Compliance	Application of Procedures/Knowledge
4	Missed Approaches as result of Unstable Appes are rarely handled well. Risk rises dramatically which is problematic.	APR GA	234	All	LOSA	Competencies Unstable APR/GA	Unstable APP Go Arounds	Mis A/C State	Application of Procedures/Knowledge
5	Usually a surprise to the crew. None occurred at standard missed approach height briefed.	APR	234	All	LOSA	Competencies Unstable APR/GA	Go Arounds Surprise	Compliance CRM	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual AC Control
33	Number 3 non-compliance item: Fail to execute missed appr when required	APR	234	All	LOSA	Unstable APR/GA Compliance	Unstable APP Landing Issues Go Arounds	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making Application of Procedures/Knowledge
55	In top 5 - UAS in DES/APR/LND: incorrect A/C config-systems	DES APR LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP Go Arounds	Compliance CRM Mis A/C State Mis-Sys	Problem Solving Decision Making Application of Procedures/Knowledge
56	In top 5 - UAS in DES/APR/LND: continued landing after Unstable App	DES APR LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making

Figure 4.2.1.5 - Go-Around/LOSA

## 4.2.1.6 Weather

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Word search [(WX) (Adverse Weather)]
  - See Figure 4.2.1.6
  - Result LOSA Weather
    - Weather is the most common threat in the LOSA database and in the top 3 for all flight phases
    - 3% of unstable approaches are linked to weather and ATC.
    - Thunderstorms and turbulence exacerbate common errors associated with manual aircraft control and instrument/radio errors.
    - The most common error associated with icing conditions is the failure to select the anti-ice system on.
    - 8% of LOSA flights encounter thunderstorms.
    - Over 6% of thunderstorm encounters lead to UAS.
    - 25% of weather avoidance events involve non-compliance of SOPs.
    - The key theme in weather avoidance events is poor planning and late identification.
    - The most important radar errors are failure to select radar on, and use of incorrect "tilt."
  - Summary Weather is the number 1 threat in the LOSA database and significant in all flight phases. 8% of all flights encounter thunderstorms with over 6% of these encounters resulting in UAS. Less than 3% of unstable approaches are due to weather. Turbulence exacerbates other common errors, specifically manual aircraft control. Weather avoidance errors are associated with SOP non-compliance (25%), poor planning and radar misuse. The number 1 error associated with ice and snow is failure to select the anti-ice system on.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicable to Gen	Source	Keywords	Training Topics	Factors	Competencies
3	3% of Unstable Approaches are linked to weather and ATC.	APR	234	All	LOSA	Unstable APR/GA	Unstable APP WX	Adverse WX ATC	
27	Thunderstorms/Turbulence: Common errors associated are ManualACControl, Flight control and System, Instrument and Radio error. – exacerbate the situation.	TO CLB DES APR	234	All	LOSA	ManualACControl Error	WX Error Mgt Manual AC Control	Adverse WX Workload Distraction Mis A/C State Mis-Sys	Communication SA Workload Management Application of Procedures/Knowledge Manual AC Control
29	Icing and Snow – The most common error associated with this threat is failure to select anti-ice on. That situation leads to a UAS. Usually coupled with poor/marginal monitoring / cross-checking.	All	234	All	LOSA	Error MonitoringXchecking UAS	WX Error Mgt Monitor Xchk	Adverse WX Compliance CRM Workload Distraction Mis-Sys	SA Workload Management Application of Procedures/Knowledge
39	Most common threat type: Adverse weather.	All	234	All	LOSA	wx	wx	Adverse WX Windshear Crosswind Poor Visibility	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual AC Control
46	Weather radar usage: 8% of flights face Thunderstorm, 1% mismanaged; half of errors lead to UAS. Most common linked errors are: Wrong radar settings, Course or heading deviations without ATC clearance, Weather penetration.	All	234	All	LOSA	Compliance Error UAS WX	wx	Adverse WX ATC CRM Mis A/C State Mis-Sys Compliance	Knowledge Communication Application of Procedures/Knowledge
47	About 25% of Weather avoidance events involve intentional non-compliance: deviation without ATC clearance and deliberately penetrating bad weather. Offsets are often less than company requirements.	CLB CRZ DES	234	All	LOSA	Compliance Error WX	wx	Adverse WX ATC CRM Mis A/C State Compliance	Communication Application of Procedures/Knowledge Problem Solving Decision Making
48	Key theme in weather avoidance errors is lack of forward planning. Late identification contributed in all penetration events.	All	234	All	LOSA	Error WX	wx	Adverse WX CRM Mis A/C State	SA Problem Solving Decision Making
49	The two most important radar errors were: radar not switched on and incorrect use of gain and especially tilt.	All	234	All	LOSA	Error WX	WX Error Mgt	Compliance CRM Mis-Sys	Knowledge Workload Management Application of Procedures/Knowledge
57	In all phases, according to LOSA, weather is either the most significant threat or in the top three.	All	234	All	LOSA	Error Management WX	wx	Adverse WX	

Figure	4216-	Weather/I	OSA
iguic	<b>-</b> . <b>2</b> .1.0 -	vvcather/L	-004



# 4.2.1.7 System Malfunction

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Topics [(Sys Mal]
  - See Figure 4.2.1.7 0
  - **Result LOSA System Malfunction** 0
    - With respect to predicted or expected system malfunctions, e.g., MEL dispatch, crews are often observed applying engineering shortcuts or workarounds, instead of following defined procedures, which results in a high degree of intentional non-compliance.

    - Unexpected aircraft malfunction is ranked 4<sup>th</sup> as a threat in the LOSA database. Unexpected aircraft malfunction is ranked 5<sup>th</sup> in mismanaged threats, from the LOSA database.
    - Aircraft system malfunction is the 3<sup>rd</sup> ranked contributor to UAS in the LOSA database.
  - Summary There is a high degree of intentional non-compliance associated with procedures 0 during the management of unexpected system malfunctions. In addition, unexpected system malfunction is in the top 5 threats as well as in the top 5 mismanaged threats in LOSA database. System malfunction ranks 3<sup>rd</sup> as a contributory factor in UAS.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicable to Gen	Source	Keywords	Training Topics	Factors	Competencies
28	Unexpected aircraft malfunction. Crew applying engineering shortcuts or workarounds instead of following ECAM, QRH, MEL. High degree of intentional non-compliance.	All	234	All	LOSA	Compliance	Error Mgt System Malfunction Surprise	Syst mal Compliance CRM Workload Distraction	Application of Procedures/Knowledge
311	Aircraft malfunction unexpected by crew is number 4 of top five threats in LOSA database	All	234	All	LOSA	Threats malfunction	System Malfunction Surprise	Syst mal	SA Application of Procedures/Knowledge
312	Aircraft malfunction unexpected by crew is number 4 of top five mismanaged threats in LOSA database	All	234	All	LOSA	Mismanaged Threats malfunction	System Malfunction Surprise	Syst mal	SA Workload Management Application of Procedures/Knowledge
313	Aircraft malfunction is number 3 of top five UAS in LOSA database	All	234	All	LOSA	UAS	System Malfunction	Syst mal	SA Workload Management Application of Procedures/Knowledge

Figure 4.2.1.7 – System Malfunction/LOSA

### 4.2.1.8 Leadership

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Topics [Leadership] combine with...
- Word-search for Leadership all columns with editing superfluous or redundant statements.
  - See Figure 4.2.1.8 0
  - Result LOSA Leadership 0
    - Captains display significantly more non-compliance than first officers.
    - Flights with outstanding ratings for "Leadership and Communication Environment" have on average 2.3 errors per flight, versus 7 Errors per flight for poor "Leadership and Communication Environment." Flights with poor Leadership ratings have approximately 3 times the number of mismanaged threats to those without poor ratings.
    - If communication is poor, TEM often rated poor, despite good leadership by the Captain.
  - Summary Leadership is an effective positive catalyst in terms of reducing errors per flight, provided that it is accompanied by good communications.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicable to Gen	Source	Keywords	Training Topics	Factors	Competencies
36	Captains display significantly more non-compliance than first officers.	All	234	All	LOSA	Compliance	Leadership	Compliance CRM	Leadership and Teamwork Application of Procedures/Knowledge
37	Flights with outstanding ratings for Leadership and Communication Environment have on average 2.3 errors/flights for poor Leadership and Communication Environment. Flights with poor ratings have approximately 3 times the number of mismanaged threats.	All	234	All	LOSA	Leadership Communication Error	Leadership Error Mgt Surprise	CRM Mis A/C State	Communication Leadership and Teamwork
38	If communication is poor, TEM is poor despite good Leadership by captain.	All	234	All	LOSA	Leadership Communication	Error Mgt	CRM	Communication Leadership and Teamwork

Figure 4.2.1.8 - Leadership/LOSA

# 4.2.1.9 Terrain

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Topics [Terrain]
  - See Figure 4.2.1.9
  - Result LOSA Terrain
    - Many flights have improperly set secondary altimeters. Proper altimeter use is not re-enforced in training or imbedded in SOPs
    - The most important mismanaged threat is terrain. Omitted callouts and failure to select the "terrain" feature on navigation displays are a common and risky combination.
    - Crews with airlines that operating in high terrain areas show a tendency towards complacency, as they become very used to the threat. This process of "normalization" reduces perception of true level of risk.
  - Summary LOSA indicates that proper altimeter use should be emphasized during training and that terrain is one of the most important mismanaged threats in LOSA database. In addition, airlines that operate in high terrain environment tend to be complacent to terrain threats.

r	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicable to Gen	Source	Keywords	Training Topics	Factors	Competencies
1	16	Many flights have improperly set secondary altimeters. Proper use of secondary altimeters does not seem to be taught in training or imbedded in SOPs	All	234	All	LOSA	Error	Error Mgt Terrain	Mis-Sys Mis A/C State Def-Proc's	SA
2	26	Most important mismanaged Threat: Terrain. Both omitted callouts and failure to select Terrain feature on Nav Display are a common and risky combination. Airlines that operate in high Terrain areas tend to get too used to this threat.	TO CLB DES APR LDG	234	All	LOSA	Terrain MonitoringXchecking	Terrain Monitor Xchk Error Mgt	Mis-Sys Compliance	SA Application of Procedures/Knowledge

Figure 4.2.1.9 – Terrain/LOSA

# 4.2.1.10 Surprise

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Topics [Surprise]
  - See Figure 4.2.1.10
  - Result LOSA Surprise
    - "Go-around" is usually a surprise to the crew. No "go-arounds" in the LOSA database occurred at the standard missed approach altitude and almost all were poorly executed.
    - Aircraft malfunction unexpected by crew is number 4 of top five threats in LOSA database.
    - Aircraft malfunction unexpected by crew is number 4 of top five mismanaged threats in LOSA database.
  - Summary Go-around is generally a surprise to crew and not well executed. An unexpected malfunction is number 4 threat as well as number 4-mismanaged threat in LOSA database.

r	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicable to Gen	Source	Keywords	Training Topics	Factors	Competencies
	5	Usually a surprise to the crew. None occurred at standard missed approach height briefed.	APR	234	All	LOSA	Competencies Unstable APR/GA	Go Arounds Surprise	Compliance CRM	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual AC Control
3	11	Aircraft malfunction unexpected by crew is number 4 of top five threats in LOSA database	All	234	All	LOSA	Threats malfunction	System Malfunction Surprise	Syst mal	SA Application of Procedures/Knowledge
3	12	Aircraft malfunction unexpected by crew is number 4 of top five mismanaged threats in LOSA database	All	234	All	LOSA	Mismanaged Threats malfunction	System Malfunction Surprise	Syst mal	SA Workload Management Application of Procedures/Knowledge

Figure 4.2.1.10 – Surprise/LOSA



### 4.2.1.11 Landing Issues

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Training Topics [Landing Issues] combined with...
- Word search (landing) or (LDG) in Evidence Statement column with suppression of extraneous and/or redundant data.
  - o See Figure 4.11
  - Result LOSA Landing Issues
    - According to LOSA only 1% of unstable approaches to landing resulted in an abnormal landing.
    - The 3<sup>rd</sup> ranked non-compliance item is an unstable approach continued to landing.
    - The 5<sup>th</sup> ranked non-compliance item is commencing taxi duties during the landing "roll-out."
    - Aircraft handling errors rank 2<sup>nd</sup>, and the error least detected is "landing deviation."
  - Summary 1% of all landings in LOSA database result in an abnormal landing. The number 3 noncompliance item in the database is landing from an unstable approach. Aircraft handling errors on landing are not well detected as they rank 2<sup>nd</sup> in least detected error during landing phase. The early commencement of after landing and taxi-in during the landing rollout is prevalent and ranked 5 overall in non-compliance.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicable to Gen	Source	Keywords	Training Topics	Factors	Competencies
1	Unstable Apprs: 4% of approaches were unstable. 97% continued to landing.10% of such landings were abnormal. Both crew members willing to continue even if unstable.	APR	234	All	LOSA	Unstable APR/GA	Unstable APP Go Arounds	CRM Mis A/C State Compliance	Application of Procedures/Knowledge
33	Number 3 non-compliance item: Fail to execute missed appr when required	APR	234	All	LOSA	Unstable APR/GA Compliance	Unstable APP Landing Issues Go Arounds	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making Application of Procedures/Knowledge
35	Number 5 non-compliance item: Taxi duties commence before runway exit	GRD	234	All	LOSA	Compliance	Monitor Xchk Error Mgt Leadership Landing Issues	Compliance CRM Ground manoeuvring	Communication SA Leadership and Teamwork Workload Management Application of Procedures/Knowledge
52	In top 5 - UAS in DES/APR/LND: speed too high	DES APR LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP Landing Issues	ATC Compliance CRM Mis A/C State	SA Workload Management Problem Solving Decision Making Flight Management Guidance/Automation
56	In top 5 - UAS in DES/APR/LND: continued landing after Unstable App	DES APR LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making
133	The Aircraft handling with the lowest rate of detection are: o Unintentional vertical deviation 41% o Unintentional landing deviation 23% o Unintentional lateral deviation 29% o Unintentional speed deviation 24% o Wrong power/thrust setting 22%	All	234	All	LOSA 2	Error ManualACControl MonitoringXchecking UAS	Landing Issues Manual AC Control Error Mgt	Mis-AFS Mis A/C State Mis-Sys	Problem Solving Decision Making Manual AC Control

Figure 4.2.1.11 – Landing Issues/LOSA

### 4.2.1.12 Compliance

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Factors [Compliance] combined with...
- Word search [(compliance) or (noncompliance)]
- Suppression of extraneous or redundant data.
- See Figure 4.2.1.12
  - Result LOSA Compliance
    - There is a significant correlation of non-compliance and UAS.
    - There is a negative correlation between non-compliance and error rate (exclusive of noncompliance errors)
    - 25% of all errors are non-compliance errors.
    - 20% of omitted callouts are intentional.
    - The 1<sup>st</sup> ranked non-compliance issue is checklist protocol with 50% occurring on the ground.
    - The 2<sup>nd</sup> ranked non-compliance issue is omitted call-outs.
    - Omitted call outs of deviations have the highest risk with 65% resulting in UAS.

- The 3<sup>rd</sup> ranked noncompliance issue is failure to execute missed approach when required.
- Both crewmembers regularly continue to land from unstable approaches in violation of SOPs.
- The 4<sup>th</sup> ranked non-compliance issue is PF making own changes in violation of SOPs.
- The 5<sup>th</sup> ranked non-compliance issue is commencing taxi duties before clearing runway.
- 25% of weather avoidance errors are associated with deviations without ATC clearances.
- There is a high degree of non-compliance regarding shortcuts and workarounds associated with abnormal procedures for unexpected malfunctions.
- Most errors are inconsequential reinforcing crew inaction.
- Summary There is a significant positive correlation between non-compliance and UAS. 25% of all errors are non-compliance errors. The top ranked non-compliance error is checklist protocol, followed by omitted call-outs. The 3<sup>rd</sup> ranked non-compliance issue is failure to execute a missed approach when required. The 4<sup>th</sup> and 5<sup>th</sup> ranked non-compliances are PF making their own changes and PM commencing taxi duties before leaving runway respectively. With respect to weather avoidance errors, 25% result from deviations without ATC clearances. Paradoxically, the fact that most errors are inconsequential reinforces crew inaction, creating additional non-compliance with associated negative effects.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gen	Source	Keywords	Training Topics	Factors	Competencies
1	Unstable Apprs: 4% of approaches were unstable. 97% continued to landing.10% of such landings were abnormal. Both crew members willing to continue even if unstable.	APR	234	All	LOSA	Unstable APR/GA	Unstable APP Go Arounds	CRM Mis A/C State Compliance	Application of Procedures/Knowledge
19	Two of the more frequent Monitor/Cross-Checking errors logged in LOSA are Callout and SOP Cross verification errors.	Ali	234	All	LOSA	MonitoringXchecking	Monitoring Xcheck Error Mgt	CRM Workload Distraction Compliance	SA Workload Management Application of Procedures/Knowledge
20	Among callout errors, the ones for omitted deviation callouts have the highest risk (65% UAS/added error rate).	All	234	All	LOSA	MonitoringXchecking UAS	Leadership Error Mgt Monitoring Xcheck	Compliance	Leadership and Teamwork Application of Procedures/Knowledge
21	2% of omitted callouts are intentional.	Ali	234	All	LOSA	MonitoringXchecking Compliance	Leadership Error Mgt	Compliance	Communication SA Leadership and Teamwork Application of Procedures/Knowledge
22	There is a strong association between non compliance and poor TEM performance.	All	234	All	LOSA	Compliance	Error Mgt	Compliance CRM	Communication SA Leadership and Tearnwork Workload Management Problem Solving Decision Making Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation Manual AC Control
28	Unexpected aircraft malfunction. Crew applying engineering shortcuts or workarounds instead of following ECAM, QRH, MEL. High degree of intentional non-compliance.	Ali	234	All	LOSA	Compliance	Error Mgt System Malfunctiof Surprise	Syst mal Compliance CRM Workload Distraction	Application of Procedures/Knowledge
30	Intentional Noncompliance: significant positive correlation between this and the number of mismanaged threats, unintentional errors, mismanaged errors and UAS.	Ali	234	All	LOSA	Compliance UAS	Error Mgt	Compliance CRM Mis-AFS Mis A/C State Mis-Sys	Leadership and Teamwork Application of Procedures/Knowledge
31	Number 1 non-compliance item: Non standard checklist protocol. Almost half during ground/taxi out.	Ali	234	All	LOSA	Compliance	Error Mgt Leadership	Ground manoeuvring CRM Compliance	Application of Procedures/Knowledge
32	Number 2 non-compliance item: Omitted altitude callouts	Ali	234	All	LOSA	Compliance Error	Monitor Xchk Error Mgt	Compliance CRM Workload Distraction	Communication SA Application of Procedures/Knowledge
33	Number 3 non-compliance item: Fail to execute missed appr when required	APR	234	All	LOSA	Unstable APR/GA Compliance	Unstable APP Landing Issues Go Arounds	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making Application of Procedures/Knowledge
34	Number 4 non-compliance item: PF makes own changes	Ali	234	All	LOSA	Compliance	Leadership Error Mgt Monitor Xchk	Compliance CRM	Communication SA Leadership and Teamwork Application of Procedures/Knowledge
35	Number 5 non-compliance item: Taxi duties commence before runway exit	GRD	234	All	LOSA	Compliance	Monitor Xchk Error Mgt Leadership Landing Issues	Compliance CRM Ground manoeuvring	Communication SA Leadership and Teamwork Workload Management Application of Procedures/Knowledge
36	Captains display significantly more non-compliance than first officers.	Ali	234	All	LOSA	Compliance	Leadership	Compliance CRM	Leadership and Teamwork Application of Procedures/Knowledge
47	About 25% of Weather avoidance events involve intentional non- compliance: deviation without ATC clearance and deliberately penetrating bad weather. Offsets are often less than company requirements.	CLB CRZ DES	234	All	LOSA	Compliance Error WX	wx	Adverse WX ATC CRM Mis A/C State Compliance	Communication Application of Procedures/Knowledge Problem Solving Decision Making
121	'taking shortcuts' reinforces over and over that most errors are inconsequential, whether they act on them or not. <b>PARADOX</b>	Ali	234	234	LOSA 2	Error MonitoringXchecking	Error Mgt Compliance	CRM Compliance	Application of Procedures/Knowledge Leadership and Teamwork
142	25% of all errors are recorded as Intentional Noncompliance errors, of which 96% are not acted upon.	All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt Leadership	Compliance	Application of Procedures/Knowledge
143	There is a negative correlation between the rate of noncompliance and the rate of errors, other than noncompliance, detected and acted upon. That is to say that noncompliance is an inhibitor to detection and correction. (multiplier in a negative sense) This is true across all error types	Ali	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance	Application of Procedures/Knowledge

Figure 4.2.1.12 - Compliance/LOSA
_@_
J E
ΙΑΤΑ

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
20	Among callout errors, the ones for omitted deviation callouts have the highest risk (65% UAS/added error rate).	All	234	All	LOSA	MonitoringXchecking UAS	Leadership Error Mgt Monitoring Xcheck	Compliance	Leadership and Teamwork Application of Procedures/Knowledge
25	Most Risky cross-verification errors: Failure to cross-verify alt setting, Failure to cross-verify FMS settings (14% UAS/added error rate).	All	234	All	LOSA	MonitoringXchecking UAS	Monitor Xchk Error Mgt	Mis-Sys Mis-AFS Compliance	SA Flight Management, Guidance/Automation Application of Procedures & Knowledge
29	lcing and Snow – The most common error associated with this threat is failure to select anti-ice on. That situation leads to a UAS. Usually coupled with poor/marginal monitoring / cross-checking.	All	234	All	LOSA	Error MonitoringXchecking UAS	WX Error Mgt Monitor Xchk	Adverse WX Compliance CRM Workload Distraction Mis-Sys	SA Workload Management Application of Procedure/Knowledge
30	Intentional Noncompliance: significant positive correlation between this and the number of mismanaged threats, unintentional errors, mismanaged errors and UAS.	All	234	All	LOSA	Compliance UAS	Error Mgt	Compliance CRM Mis-AFS Mis A/C State Mis-Sys	Leadership and Teamwork Application of Procedure/Knowledge
46	Weather radar usage: 8% of flights face Thunderstorm, 1% mismanaged; half of errors lead to UAS. Most common linked errors are: Wrong radar settings, Course or heading deviations without ATC clearance, Weather penetration.	All	234	All	LOSA	Compliance Error UAS WX	wx	Adverse WX ATC CRM Mis A/C State Mis-Sys Compliance	Knowledge Communication Application of Procedures/Knowledge
51	Flight phases: most mismanaged errors and UAS in DES, APR, LND	DES APR LDG	234	All	LOSA	Error Mgt UAS	Error Mgt	CRM Workload Distraction Pressure Mis A/C State Mis-Sys	Leadership and Teamwork Workload Management
52	In top 5 - UAS in DES/APR/LND: speed too high	DES APR LDG	234	All	LOSA	Unstable APR/Go Arounds UAS	Unstable APP Landing Issues	ATC Compliance CRM Mis A/C State	SA Workload Management Problem Solving Decision Making Flight Management, Guidance/Automation
53	In Top 5 - UAS in DES/APR/LND: Unstable App	DES APR LDG	234	All	LOSA	Unstable APR/Go Arounds UAS	Unstable APP Landing Issues	ATC Compliance CRM Mis A/C State	SA Workload Management Problem Solving Decision Making Flight Management, Guidance/Automation Application of Procedures/Knowledge
54	In top 5 - UAS in DES/APR/LND: incorrect A/C config- Automation	DES APR LDG	234	All	LOSA	Unstable APR/Go Arounds UAS	Unstable APP	Compliance CRM Mis A/C State Mis-AFS Mis-Sys	Flight Management, Guidance and Automation Application of Procedures & Knowledge
55	In top 5 - UAS in DES/APR/LND: incorrect A/C config- systems	DES APR LDG	234	All	LOSA	Unstable APR/Go Arounds UAS	Unstable APP Go Arounds	Compliance CRM Mis A/C State Mis-Sys	Problem Solving Decision Making Application of Procedures/Knowledge
56	In top 5 - UAS in DES/APR/LND: continued landing after Unstable App	DES APR LDG	234	All	LOSA	Unstable APR/Go Arounds UAS	Unstable APP	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making
133	The Aircraft handling with the lowest rate of detection are: (Many are not detected until UAS) o Unintentional vertical deviation 41% o Wrong speed brakes setting 39% o Incorrent Nav Display setting 35% o Unintentional landing deviation 32% o Wrong radar setting 30% o Unintentional speed deviation 29% o Unintentional speed deviation 24% o Wrong power/thrust setting 22%	All	234	All	LOSA 2	Error Manual AC Control MonitoringXchecking UAS	Landing Issues Manual AC Control Error Mgt	Mis-AFS Mis A/C State Mis-Sys	Problem Solving Decision Making Manual Aircraft Control

Figure 4.2.1.12a – Compliance cont.

# 4.2.1.13 Phase of Flight

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Search all columns [Phase]
- Filter Flight Phase [(TAXI)U(TO)U(CLB)U(CRZ)U(DES)U(APP)U(LDG)]
- Suppression of extraneous and/or redundant data.
- See Figure 4.2.1.13
  - Result LOSA Phase of Flight
    - Weather is in the top three threats in all phases of flight.
    - TAXI
      - The majority of threats are revealed pre-departure.
      - Pre-departure taxi is an extremely important phase for training mitigation.
      - Detection of manual aircraft control errors is notably stronger in taxi out than any other phase, but also notably weakens after this phase.
      - A runway change is major threat.
      - The lowest rate of error detection is reported as taxi-in and parking phase after landing.
    - TO/CLB
      - Late engagement of the autopilot is a major automation error as well as ignoring or "flying through" the flight guidance.
      - Callout error detection is best in TO/CLB.
    - CRZ
      - Procedural error detection is best in CRZ
    - DES/APP
      - Late disengagement of autopilot is a major automation error as well as "flying through" the flight guidance.
      - There are frequent mismanaged errors and UAS.
      - Speed too high is a frequent error
      - The most frequent non-compliance error is the failure to execute a go-around when appropriate.
      - Another frequent error is incorrect aircraft configuration.
    - LDG
      - Speed control is frequent error.
      - Continuation of a landing from an unstable approach is a frequent error.
      - Commencing after landing and taxi items before clearing the runway is frequent procedural error.
  - Summary Weather is considered a major threat in all flight phases. LOSA data shows that it is in the top three threats for all flight phases. Flight phases have different characteristics in terms of threats, errors, error detection rates and undesired aircraft states.

3.6
ΙΑΤΑ

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicabilit v to Gens	Source	Keywords	Training Topics	Factors	Competencies
10	The late engagement of autopilot after takeoff or early disengagement in Descent/Approach/Land,Basically hand flying at an inappropriate time. Common errors include hand flying in a busy Terminal Area.	CLB APR	234	All	LOSA	Automation Competencies	Automation Manual AC Control Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Problem Solving Decision Making
11	Control Zone, looking through the FD, not checking modifications to the SID, STAR or Approach profile and relying on the PM to effect FMC/FMGC changes.	CLB APR	234	All	LOSA	Automation	Automation Manual AC Control Monitoring Xcheck	Mis-AFS CRM	Flight Management Guidance/Automation Workload Management Manual Aircraft Control Application of Procedures/Knowledge
33	Number 3 non-compliance item: Fail to execute missed appr when required	APR	234	All	LOSA	Unstable APR/GA Compliance	Unstable APP Landing Issues Go Arounds	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making Application of Procedures/Knowledge
35	Number 5 non-compliance item: Taxi duties commence before runway exit	GRD	234	All	LOSA	Compliance	Monitor Xchk Error Mgt Leadership Landing Issues	Compliance CRM Ground manoeuvring	Communication SA Leadership and Teamwork Workload Management Application of Procedures/Knowledge
42	ATC threat 2: Runway Changes, leading to Automation Issues, Briefing errors, SOP errors, Aircraft configuration issues.	APR GRD	234	All	LOSA	Communication Automation Error Mgt	Error Mgt Automation	ATC Workload Distraction Mis A/C State Mis-AFS CRM Compliance	Communication Application of Procedures/Knowledge Flight Management Guidance/Automation
50	Flight phases: most threats in pre-departure.	GRD	234	All	LOSA	Error Mgt	Error Mgt	Cabin CRM Workload Distraction	Leadership and Teamwork Workload Management
51	Flight phases: most mismanaged errors and UAS in DES, APR, LND	DES APR LDG	234	All	LOSA	Error Mgt UAS	Error Mgt	CRM Workload Distraction Mis A/C State Mis-Sys	Leadership and Teamwork Workload Management
52	In top 5 - UAS in DES/APR/LND: speed too high	DES APR LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP Landing Issues	ATC Compliance CRM Mis A/C State	SA Workload Management Problem Solving Decision Making Flight Management Guidance/Automation
53	In Top 5 - UAS in DES/APR/LND: Unstable App	DES APR LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP Landing Issues	ATC Compliance CRM Mis A/C State	SA Workload Management Problem Solving Decision Making Flight Management Guidance/Automation Application of Procedures/Knowledge
54	In top 5 - UAS in DES/APR/LND: incorrect A/C config-Automation	DES APR LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP	Compliance CRM Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Application of Procedures/Knowledge
55	In top 5 - UAS in DES/APR/LND: incorrect A/C config-systems	DES APR LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP Go Arounds	Compliance CRM Mis A/C State Mis-Sys	Problem Solving Decision Making Application of Procedures/Knowledge
56	In top 5 - UAS in DES/APR/LND: continued landing after Unstable App	DES APR LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP Landing Issues	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making
57	In all phases, according to LOSA, weather is either the most significant threat or in the top three.	All	234	All	LOSA	Error Mgt WX	wx	Adverse WX	
58	Predeparture/Taxi-out are extremely important phases from the point of view that they are fertile territory for mitigating threats by training. 4	GRD	234	All	LOSA	Error Mgt	Error Mgt	Ground manoeuvring CRM	SA Leadership and Tearmwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
##	ManualACControl/Flight Control error detection/action taken is notably stronger in Predeparture/Taxi-Out than in the other phases of flight	GRD	234	All	LOSA 2	ManualACControl Error Mgt	Manual AC Control Error Mgt Monitoring Xcheck	Mis-Sys Mis A/C State	SA Problem Solving Decision Making Manual AC Control
111	Callout error detection is better in Takeoff/Climb.	CLB	234	All	LOSA 2	Error Mgt MonitoringXcheck	Error Mgt Monitoring Xcheck	Compliance CRM	Communication SA Application of Procedures/Knowledge
##	Iaxi/Park has the lowest rate of errors detected and acted upon (17%) because approximately one-half of the errors in Taxi/Park are Intentional Noncompliance errors vs. about one-quarter of errors in the other phases.	GRD	234	All	LOSA 2	Error Mgt MonitoringXcheck	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual AC Control
##	ManualACControl/Flight Control errors - error detection/action is notably stronger in Predeparture/Taxi-Out than in the other phases of flight (3% of ManualACControl/Flight Control errors are detected and acted upon during Predeparture/Taxi-Out vs. 21-30% of ManualACControl/Flight Control errors being detected and acted upon in later phases of flight	GRD All	234	All	LOSA 2	ManualACControl Error Mgt MonitoringXcheck	Error Mgt	Mis A/C State	Manual AC Control
##	When compared with the other Aircraft Handling error types, it seems that error detection for ManualACControl/Flight Control errors weakens notably after departure/Taxi-Out, while Automation and System/Instrument/Radio error detection rates stay relatively the same	GRD All	234	All	LOSA 2	Error Mgt ManualACControl MonitoringXcheck	Error Mgt	Mis A/C State	Manual AC Control
##	Procedural error types, Checklist error detection is better in Cruise and Descent/Approach/Land while Callout error detection is better in Takeoff/Climb.	GRD All	234	All	LOSA 2	Error Mgt MonitoringXcheck	Error Mgt	Mis-Sys Compliance	Application of Procedures/Knowledge

Figure 4.2.1.13 – Phase of Flight/LOSA

# 4.2.1.14 Training Effect

- Filter Evidence Table for LOSA 1 or LOSA 2 reports
- Filter Keywords [Training]
  - See Figure 4.2.1.14
  - Result LOSA Training Effect
    - LOSA data highlights the unstable approach and go-around problem that is not addressed in training, placing particular emphasis on SOP knowledge and discipline as well as citing difficulties in go-around execution.
    - Automation needs to be addressed; automation errors occur on 28% of LOSA archive flights. Issues cited are as follows:
      - Guidance errors
      - Technical understanding and poor grasp of the "mental model."
      - Poor monitoring and crosschecking.
    - Threat and error management in terms of:
      - SOP Cross-verification
      - Altimeter crosschecking
      - Intentional non-compliance.
      - Low error detection rates relating to specific aircraft handling issues.
    - LOSA cites the pre-departure and taxi phase as "fertile territory for mitigating threats by training".
    - Communication, particularly with ATC, remains a frequent threat and is often linked with poor TEM.
  - Summary The LOSA study was specifically targeted to address issues likely to receive effective mitigation in training. Some of the more important findings in the report highlight automation problems, specifically in terms of operational performance as well as conceptual understanding and procedural knowledge. Monitoring and crosschecking is the overarching element that needs to be improved according to the LOSA report and this is emphasized repetitively in the data. Communication, particularly with ATC, remains a frequent threat and is often linked with poor TEM. Findings in most cases are presented in terms of TEM and show specific operational areas such as, the pre-departure/taxi that in the words of the report: "are fertile territory for mitigating threats by training".



e r	E ef	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	2	Pilots did not know stable approach criteria.	APR	234	All	LOSA	Unstable APR/GA	Unstable APP G0 Arounds	CRM	Knowledge
	4	Missed Approaches as result of Unstable Appes are rarely handled well. Risk rises dramatically which is problematic.	APR GA	234	All	LOSA	Competencies Unstable APR/GA	Unstable APP G0 Arounds	Mis A/C State	Application of Procedures/Knowledge
	6	28% of flights in the LOSA Archive have an Automation error. Almost 1% of total flights have Automation errors that have consequential results.	All	234	All	LOSA	Automation Error Mgt	Automation Error Mgt	Mis-AFS Mis A/C State	Flight Management Guidance/Automation
	7	In terms of mismanaged errors guidance are far more prevalent than programming errors.	All	234	All	LOSA	Error Mgt Automation	Automation Error Mgt	Mis-AFS	Flight Management Guidance/Automation
	8	Technical understanding of the Automation	All	234	All	LOSA	Automation Competencies	Automation	Mis-AFS CRM	Flight Management Guidance/Automation Knowledge
	9	A lack of "verbalization" by crew to share mental models	All	234	All	LOSA	Competencies Automation	Automation Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Communication
1	11	Control Zone, looking through the FD, not checking modifications to the SID, STAR or Approach profile and relying on the PM to effect FMC/FMGC changes.	CLB APR	234	All	LOSA	Automation	Automation Manual AC Control Monitoring Xcheck	Mis-AFS CRM	Flight Management Guidance/Automation Workload Management Manual Aircraft Control Application of Procedures/Knowledge
1	12	The overarching element is Monitoring/Cross-Checking, with little to no dialogue between the pilots during most of the errors.	All	234	All	LOSA	Automation Error Mgt MonitoringXcheck	Automation Monitoring Xcheck Communication Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Communication SA
1	13	21% of the Automation induced undesired aircraft states result from SOP Cross-Verification errors	All	234	All	LOSA	Automation MonitorXchk Error Mgt UAS	Automation Monitoring Xcheck Error Mgt	Mis-AFS CRM Mis A/C State	Flight Management Guidance/Automation SA
1	14	There are often misunderstandings of autopilot modes.	All	234	All	LOSA	Automation Competencies	Automation Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Knowledge
2	23	28% of flights in the LOSA Archive have an SOP Cross-Verification error. 1% of these are mismanaged.	All	234	All	LOSA	MonitoringXcheck	Monitoring Xcheck Error Mgt	Mis-AFS Mis A/C State Mis- Sys	Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
2	24	Most Frequent cross-verification errors: Omitted flight mode verification – 2%, Failure to cross-verify alt setting – 18%, Failure to cross-verify FMS settings – 16%, Failure to cross verify documentation and performance – 9%	All	234	All	LOSA	MonitoringXcheck	Monitoring Xcheck Error Mgt	Mis-Sys Mis-AFS Compliance	SA Flight Management Guidance/Automation Application of Procedures/Knowledge
2	25	Most Risky cross-verification errors: Failure to cross-verify alt setting, Failure to cross-verify FMS settings (14% UAS/added error rate).	All	234	All	LOSA	MonitoringXcheck UAS	Monitoring Xcheck Error Mgt	Mis-Sys Mis-AFS Compliance	SA Flight Management Guidance/Automation Application of Procedures/Knowledge
2	26	Most important mismanaged Threat: Terrain. Both omitted callouts and failure to select Terrain feature on Nav Display are a common and risky combination. Airlines that operate in high Terrain areas tend to get too used to this threat.	TO CLB DES APR LDG	234	All	LOSA	Terrain MonitoringXcheck	Terrain Monitoring Xchk Error Mgt	Mis-Sys Compliance	SA Application of Procedures/Knowledge
3	30	Intentional Noncompliance: significant positive correlation between this and the number of mismanaged threats, unintentional errors, mismanaged errors and UAS.	All	234	All	LOSA	Compliance UAS	Error Mgt	Compliance CRM Mis-AFS Mis A/C State Mis- Sys	Leadership and Teamwork Application of Procedures/Knowledge
з	38	If communication is poor, TEM is poor despite good Leadership by captain.	All	234	All	LOSA	Leadership Communication	Error Mgt	CRM	Communication Leadership and Teamwork
4	40	ATC threats are the second most common threat type observed in the LOSA Archive.	All	234	All	LOSA	Communication		ATC	Communication
4	45	ATC induced problems often linked with poor communication and cross-checking in the cockpit.	TO CLB DES APR	234	All	LOSA	Communication MonitoringXcheck	Error Mgt Monitoring Xcheck	ATC CRM	Communication SA Application of Procedures/Knowledge
5	50	Flight phases: most threats in pre-departure.	GRD	234	All	LOSA	Error Mgt	Error Mgt	Cabin CRM Workload Distraction	Leadership and Teamwork Workload Management
5	58	Predeparture/Taxi-out are extremely important phases from the point of view that they are fertile territory for mitigating threats by training. 4	GRD	234	All	LOSA	Error Mgtt Training	Error Mgt	Ground manoeuvring CRM	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
1'	18	Error detection is most closely aligned with the quality of Monitoring/Cross-Checking in all phases of flight and the quality of the Briefing.	All	234	All	LOSA 2	Error MonitoringXcheck	Error Mgt Monitoring Xcheck	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
1:	33	The Aircraft handling with the lowest rate of detection are: (Many are not detected until UAS) o Unintentional vertical deviation 41% o Wrong speed brakes setting 39% o Incorrect Nav Display setting 35% o Unintentional landing deviation 32% o Wrong radar setting 30% o Unintentional lateral deviation 29% o Unintentional speed deviation 24% o Wrong power/thrust setting 22% o Wrong anti-jce setting 19%	All	234	All	LOSA 2	Error ManualACControl MonitoringXcheck UAS	Landing Issues Man Handling Error management	Mis-AFS Mis-A/C State Mis-Sys	Problem Solving Decision Making Manual Aircraft Control

Figure 4.2.1.14 – Training Effect/LOSA

# 4.2.2 Accident Incident Analysis

The following statements are listed under relevant topics, in some cases considered as factors in the analysis, and in other cases the competencies analyzed. The graphics relating to the information listed are referenced in Appendix 2.

# 4.2.2.1 Adverse Weather

#### Gen4 Jet

- As the overall accident rate has reduced, exposure to weather related accidents has reduced from 0.8 to 0.65 per million take-offs.
- When comparing the last 11 years compared to the previous era, adverse weather is a greater factor in accidents and incidents, rising from 37% to 46%
- Adverse weather is the number 1 factor in accidents over the last in last 11 years for all accidents
- Adverse weather is ranked 3<sup>rd</sup> after non-compliance and CRM, as a factor in accidents with high training effect. It has increased by a factor of 2 when comparing the previous 11-years data.

#### Gen3 Jet

- Adverse weather has reduced slightly as a factor, in comparison to the period prior to the last 15years. Over the last 15-years, adverse weather remains the number 1 ranked factor in accidents and serious incidents, evident in 40% of events.
- When considering fatal accidents only, adverse weather is ranked 3<sup>rd</sup> after CRM and system malfunction, at 20% of all fatal accidents over the last 15 years.
- Adverse weather is currently ranked 3<sup>rd</sup> as a factor in accidents with high training effect, at 30% overall, implying substantial benefit from mitigation through training.

#### • Gen2 Jet

- Adverse weather is ranked 2<sup>nd</sup> as a factor in accidents, and has increased in the most recent 15year period from 30% to 35%.
- Adverse weather is now the number 1 ranked factor by percentage of occurrence in fatal accidents, having doubled in the most recent 15-year period to 60%.
- Exposure data indicates adverse weather as a factor in fatal accidents at the rate of 1 per million take-offs, over the most recent 15-year period.
- For accidents with high training effect, adverse weather is ranked 3<sup>rd</sup> after CRM and poor visibility, at 40% with no significant change over the last 15-year period and before, implying substantial benefit from mitigation through training.

#### • Gen3 Turboprop

#### Note, there was no available exposure data

- Adverse weather has increased as a factor in accidents from 25% to 40% when comparing the most recent 15-year period to the previous period.
- Adverse weather is now the number 1 ranked factor by percentage of occurrence in accidents, having risen from a previous ranking of 3<sup>rd</sup>.
- For accidents with high training effect, adverse weather is now ranked 2<sup>nd</sup> at 60% after CRM. Prior to the last 15 years it was a factor in 65% of accidents.

#### • Gen2 Turboprop

#### Note, there was no available exposure data

- Prior to the last 15-years, adverse weather was ranked 2<sup>nd</sup> with a 40% rate of reported occurrence in accidents.
- There was insufficient data to draw further conclusions over the most recent 15-year period.





# 4.2.2.2 Competencies – General

Manual Aircraft Control is the most important competency expressed in all accidents, followed by Situation Awareness, and Application of Procedures and Knowledge.

With respect to the most critical flight phases, TO/LDG/APP, patterns are consistent with the statements above, except that the peaks with respect to Manual Aircraft Control, Situation Awareness and Application of Procedures and knowledge, are much more pronounced.

In less critical flight phases, the difference is very small, except in GND, where Situation Awareness is predominant.

- Gen4 Jet
  - Competency issues most prevalent are:in
    - Manual Aircraft Control
    - Situation Awareness
    - Application of Procedures and knowledge
  - In the APP phase over the last 21 years, the competency issues most prevalent are:
    - Manual Aircraft Control
    - Situation Awareness
    - Application of Procedures and knowledge
  - In the LDG phase over the last 21 years, the competency issues most prevalent are
    - Manual Aircraft Control
    - Situation Awareness
    - Application of Procedures and knowledge
  - This pattern remains consistent when combining the APP and LDG phases
    - Manual Aircraft Control
    - Application of Procedures and knowledge
    - Situation Awareness

#### Gen3 Jet

- Competency issues most prevalent are:
  - Manual Aircraft Control
  - Situation Awareness
  - Application of Procedures and knowledge
- Gen2 Jet
  - Competency issues most prevalent are:
    - Manual Aircraft Control (which is very dominant)
    - Problem Solving and decision-making
    - Situation Awareness
    - Application of Procedures and knowledge
- Gen3 Turboprop
  - Competencies most prevalent are:
    - Manual Aircraft Control
    - Application of Procedures and knowledge
    - Knowledge
    - Situation Awareness

- Gen2 Turboprop
  - Competencies most prevalent are:
    - Manual Aircraft Control
    - Problem Solving and decision-making
    - Situation Awareness

# 4.2.2.3 Compliance

#### Gen4 Jet

- During the last 11-year period, compliance as factor has decreased from being ranked 3<sup>rd</sup> at 36%, to 23%.
- $\circ~$  For accidents with a high training effect, compliance is a substantial factor, at 75% having risen from 63%

#### Gen3 Jet

- During the last 15-year period, compliance as factor has reduced from being ranked 5<sup>th</sup> at 24% to 14%.
- For fatal accidents, the rate of occurrence of this factor has reduced from 50% to 21%.
- For accidents with a high training effect, compliance is a substantial factor, at 50% overall and ranked 2<sup>nd</sup>.

#### Gen2 Jet

- The rate of accidents involving compliance has increased slightly over the most recent 15-year period considered, but other factors have increased much more.
- Compliance is now ranked 9<sup>th</sup> at 13%, having decreased from 22%.
- For fatal accidents, the rate of occurrence of compliance has decreased from 33% to 7%.
- For accidents with a high training effect, compliance is a substantial factor, at 39% overall and ranked 5<sup>th</sup>.

# Gen3 Turboprop

#### Note, there was no available exposure data

- During the last 15-year period, compliance as factor has decreased from 25% to 11% when compared to the previous period.
- For accidents with a high training effect, compliance remains is a substantial factor, at 50% overall and ranked 3<sup>rd</sup>.

# • Gen2 Turboprop

#### Note, there was no available exposure data

- During the last 15-year period, compliance as factor has risen from 28% to 38% when compared to the previous period.
- For accidents with a high training effect, compliance is a substantial factor, at 78% having risen from 65% overall and ranked 2<sup>nd</sup>.

# 4.2.2.4 Landing

- Gen4 Jet
  - The highest total numbers of accidents occur in the LDG & GND phases. In the period considered before 2000, LDG was the flight phase with the largest number of accidents, twice as many as any other phase. Over the most recent 11-year period considered, the trend has decreased with the APP phase becoming predominant.
  - The APP phase is now considered as the number 1 flight phase in terms of the number of accidents.
  - $\circ$   $\;$  The factors which contribute to accidents in the LDG phase are:
  - Compliance/CRM/Adverse Weather/Adverse Wind (These factors occur in 50% of accidents)



- When considering the sum of all factors in all accidents, there are more factors occurring in accidents in the LDG phase than in any other phase.
- For fatal accidents, the LDG phase is ranked 3<sup>rd</sup> after APP and TO
- When considering the sum of all factors in fatal accidents, there are more factors occurring in accidents in the LDG phase than in any other phase.
- The factors, which are most prevalent in fatal accidents during LDG over the most recent 11-year period are:
  - Adverse weather/CRM/Compliance

#### Gen3 Jet

- The LDG phase which was previously ranked 3<sup>rd</sup> in accidents, has now climbed to number 1, over the last 15-years.
- When considering the sum of all factors in all accidents, there are more factors occurring in accidents in the LDG phase than in any other phase.
- The factors which are most prevalent in accidents in the LDG phase are:
- o CRM/Adverse Weather/System Malfunction/Poor visibility/Compliance
- The LDG phase is not the highest ranked phases for fatal accidents.
- When considering the sum of all factors in fatal accidents, there are more factors occurring in accidents in the LDG phase than during any other phase.
- The factors which are most prevalent in fatal accidents during LDG over the most recent 15-year period are:
  - CRM/Adverse Weather/Windshear/System Malfunction/Adverse Weather/Mismanaged System

#### Gen2 Jet

- The LDG phase which was previously ranked number 1 in accidents has dropped to a ranking of number 2 over the last 15-years.
- The APP phase is now ranked number 1 over the last 15-year period.
- For all accidents, the most prevalent factors are:
  - CRM/System Malfunction
- For fatal accidents in the last 15 years, APP was the predominant phase
- When considering the sum of all factors in fatal accidents, there are more factors occurring in accidents during in the APP phase than in any other phase.
- The factor most prevalent in fatal accidents during LDG over the most recent 15-year period are:
  - Poor visibility/Runway taxiway condition

# • Gen3 Turboprop

#### Note, there was no available exposure data

- The LDG phase was previously ranked 2<sup>nd</sup> but has now dropped to 5<sup>th</sup> overall in the most recent 15-year period.
- The factors which are most prevalent in all accidents during LDG over the most recent 15-year period are:
  - CRM/Adverse Weather/System Malfunction/Runway taxiway condition/Poor visibility.

# • Gen2 Turboprop

#### Note, there was no available exposure data

- LDG is ranked number 1 in flight phases for the most accidents for all periods considered.
- When considering the sum of all factors in all accidents, there are more factors occurring in accidents in the LDG phase than in any other phase.
- The factors which are most prevalent in accidents during the LDG phase are:
  - System malfunction/Compliance/CRM.

# 4.2.2.5 Leadership & Teamwork

- Gen4 Jet
  - Exposure to an accident or serious incident involving Leadership and teamwork as a competency issue has risen from 0.12 per million take-offs to 0.4 per million take-offs in the most recent 11-year period.
  - Leadership and teamwork is reported as a competency issue in 8% of all accidents, which is a reduction from 18% in the previous 11-year period.
  - When considering serious incidents, Leadership and teamwork is not reported as a competency issue, perhaps indicating that effective Leadership can prevent more serious events.

#### Gen3 Jet

- Exposure to an accident or serious incident involving Leadership and teamwork as a competency issue has reduced from 0.23 per million take-offs to 0.08 per million take-offs in the most recent 15year period.
- Leadership and teamwork is reported as a competency issue in 5% of all accidents, which is a reduction from 13% in the previous 15-year period.
- However the trend is reversed for fatal accidents where Leadership and teamwork is reported as a competency issue has risen from 7% to 15% in the most recent 15-year period
- In serious incidents, where in many cases an accident was prevented by the crew action, Leadership and teamwork is conspicuously not reported as a competency issue providing evidence for research that effective Leadership could well have prevented an accident.

# Gen2 Jet

- Exposure to an accident or serious incident involving Leadership and teamwork as a competency issue has increased from 0.11 per million take-offs to 0.19 per million take-offs in the most recent 15-year period.
- Leadership and teamwork is reported as a competency issue in 4% of all accidents
- The percentage of fatal accidents with a Leadership and teamwork as a competency issue has risen from 4% to 7% in the most recent 15-year period.
- In serious incidents, Leadership and teamwork as a competency issue is only reported at 3%, providing evidence for research that effective Leadership could prevent more serious events.

# • Gen3 Turboprop

#### Note, there was no available exposure data

- Leadership and teamwork is reported as a competency issue in 8% of all accidents
- When considering serious incidents, Leadership and teamwork as a competency issue has risen from 3%, to 7% over the last 15-years.

#### • Gen2 Turboprop

#### Note, there was no available exposure data

• Leadership and teamwork is reported as a competency issue in 38% of all accidents, and this has risen from a previous figure of 17%.



# 4.2.2.6 Manual Aircraft Control (Flight Path Management – Manual)

#### • Gen4 Jet

- Of the 9 competencies analyzed, the competency most reported as a problem is Manual Aircraft Control; it is a competency issue in 22% of accidents over the most recent period. It does show improvement from the previous 11-year study, where it was at more than 35%
- For the period up to 2000, more than 0.8 accidents per million take-offs showed manual aircraft control as a competency issue, which then declined to 0.3 in the period 2000-2010.
- For accident with a high training effect, manual aircraft control remains the highest competency issue from data over the last 11 years as well as in the previous period.
- There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.

#### Gen3 Jet

- The exposure to accidents with manual aircraft control as a competency issue is stable over time, at approximately 30%. This is more than double the percentages of the other competencies.
- There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.
- For accidents with a high training effect, manual aircraft control remains the highest competency issue from data over the last 15-years as well as in the previous period.
- Manual aircraft control, as a competency issue stands at 40% in fatal accidents more than 15-years ago, as compared to over 50% in the most recent 15-year period.

#### Gen2 Jet

- Of the 9 competencies analyzed, the competency at issue most often is Manual Aircraft Control, a competency issue in 40% of accidents over the period 1995-2010. This has increased by a magnitude of 3 times from the previous 15-year period.
- There are 4 accidents per million take-offs, 50% of them showing manual aircraft control as a competency issue.
- Manual aircraft control has always been amongst the top ranked competency issues in fatal accidents, but has risen in the most recent 15-year period to 60%.
- There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.
- For accidents and serious incidents with a high training effect, manual aircraft control is now considered a competency issue in 80% of events, an increase of 100% over the previous 15-yearperiod.
- Exposure data indicates an increase in manual aircraft control as a competency issue, from of 0.2 to 0.7 for accidents with a high training effect, over the most recent 15-year period.



# Gen3 Turboprop

#### Note, there was no available exposure data for this generation

- Manual aircraft control as a competency issue in all accidents has risen from 13% to 16% in the most recent 15-year period.
- Manual aircraft control is now ranked as the number 1 competency issue in accidents. There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.

# Gen2 Turboprop

#### Note, there was no available exposure data for this generation

- Manual aircraft control shows an increase from 27% to 38% as a competency issue in all aircraft accidents, and is now ranked 2.
- There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.

# 4.2.2.7 Surprise (Situation Awareness)

Little information can be directly inferred from accident and incident reports with respect to unexpected or surprise events being considered as competency issues. Surprise was not considered directly as a competency issue. It can however be indirectly inferred, that when there is a reported breakdown in situation awareness, there is a greater likelihood of unexpected events, and the management of surprises is more difficult. For this reason, situation awareness is considered as a competency issue affecting surprise.

#### Gen4 Jet

- For all accident data, Situation Awareness is among the top 3 ranked competency issues, the rate rising from 18% to 22% in the last 11-years, when compared with the previous time period.
- Situation Awareness is the number 1 competency, alongside Manual Aircraft Control, when analyzing competency issues in accidents and incidents.
- When analyzing incidents alone, Situation Awareness is the highest ranked competency issue at over 20%.

# Gen3 Jet

- For all accident data, Situation Awareness is among the top 3 ranked competency issues, with the rate rising from 13% to 28% in the last 15-years, when compared with the previous period.
- Situation Awareness is now ranked 2<sup>nd</sup> as the most significant competency issue, after Manual Aircraft Control.
- When considering fatal accidents, Situation Awareness is ranked 2<sup>nd</sup>, in 29% of fatal accidents.
- There is a significant difference in the rate of Situation Awareness as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through the maintenance or regaining of Situation Awareness.

# Gen2 Jet

- For all accident data, Situation Awareness is among the top 3 ranked competency issues with, the rate rising from 16% to 24% in the last 15-years, when compared with the previous period.
- When considering fatal accidents, Situation Awareness is ranked 2<sup>nd</sup> as a competency, contributory to 21% of fatal accidents, with a slight reduction from 23% in the previous period.



 There is a significant difference in the rate of Situation Awareness as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through the maintenance or regaining of Situation Awareness.

# Gen3 Turboprop

#### Note, there was no available exposure data for this generation

- For all accident data, Situation Awareness is ranked among the top 3 competency issues with, the rate decreasing from 17% to 14% in the last 15-years, when compared with the previous period.
- Situation Awareness is now ranked 3<sup>rd</sup> after Manual Aircraft Control and Application of Procedures and Knowledge.
- When considering incidents alone, Situation Awareness is the highest ranked competency issue at 18%.

#### Gen2 Turboprop

#### Note, there was no available exposure data for this generation

• For all accident data, Situation Awareness is currently ranked 4<sup>th</sup>, with the rate rising from 15% to 17% in the last 15-years, as compared with the previous period.

# 4.2.2.8 System Malfunction

#### Gen4 Jet

- System malfunction is ranked 5<sup>th</sup> as a factor and present in 15% of all accidents over the latest 11year period.
- As a factor all accidents, system malfunction has increased from below 10% to above 15% from the previous period.
- For accidents with high training effect, system malfunction has decreased in occurrence from 25% of accidents to 5%. Although the available volume of data is relatively small, it seems reasonable to infer that training is an effective remediation tool.

# Gen3 Jet

- System malfunction is ranked 3<sup>rd</sup> as a factor and present in 19% of accidents over the latest 15-year period.
- As a factor system malfunction has increased from 14% to 19% in the last 15-year period.
- For fatal accidents, system malfunction is ranked 2<sup>nd</sup> and stable at 30% over the 2 time periods analyzed.
- For accidents with high training effect, system malfunction is ranked 6<sup>th</sup> and present in 18% of accidents over the last 15-years. Prior to this the figure was 27%, and therefore it seems reasonable to infer that training is an effective remediation tool.

# Gen2 Jet

- System malfunction is ranked number 1 as a factor and is present in 45% of accidents over the latest 15-year period.
- As a factor system malfunction has increased from 25% to 45% in the last 15-year period and has gone from 3<sup>rd</sup> to 1<sup>st</sup> in ranking.
- For fatal accidents, system malfunction is ranked 3<sup>rd</sup> occurring more than 50% of the time compared to the previous time period when it ranked 5<sup>th</sup> and only occurred at 20%.
- For accidents with high training effect, system malfunction is ranked 4<sup>th</sup> and present in over 40% of accidents over the last 15-years. This is up from an occurrence rate of about 20%.



### • Gen3 Turboprop

#### Note, there was no available exposure data

- System malfunction is ranked 3<sup>rd</sup> as a factor and is present in 22% of accidents over the latest 15year period.
- As a factor system malfunction has decreased as a percentage from 42% to 22% in the last 15year period with a ranking down from 1<sup>st</sup> to 3<sup>rd</sup>.
- For accidents with high training effect, system malfunction is present in 17% of accidents over the last 15-years.

#### • Gen2 Turboprop

#### Note, there was no available exposure data

- System malfunction is ranked number 1 as a factor and is present in 50% of accidents over the latest 15-year period.
- As a factor system malfunction is stable at 50% and remains number 1 for all flights analyzed.
- For accidents with high training effect, system malfunction is ranked 3<sup>rd</sup> and present in over 70% of accidents over the last 15-years. The rate went from 50% to over 70% in the latest period, although the available data set is small.

# 4.2.2.9 Terrain

#### Gen4 Jet

- Terrain as a threat generally ranks low according to Gen4 Jet accident and incident data.
- As a contributory factor in accidents, terrain has reduced from 5% to 1% when comparing older data to that from the last 11-year period.
- When considering accidents with a high training effect, there has been a reduction in accidents including terrain as a factor, from 13% to 5% over the 2 periods analyzed.

#### Gen3 Jet

- Terrain as a threat generally ranks low according to Gen3 Jet accident and incident data, currently it is a factor in 2% of all accidents in the most recent 15-year period, compared to 3% previously.
- When considering fatal accidents, terrain ranks 6<sup>th</sup> overall but has decreased in the rate of occurrence from 21% to 15%.
- When considering accidents with a high training effect, the rate is low at 3% overall.

#### Gen2 Jet

- Terrain as a threat generally ranks 11th according to Gen2 Jet accident and incident data, but has increased in the most recent 15-year period to 11%, from 3% previously.
- When considering fatal accidents only, terrain ranks 8<sup>th</sup> overall but has increased in the rate of occurrence from 16% to 23% in the most recent 15-year period.
- When considering accidents with a high training effect, the rate of accidents with terrain as a contributory factor is at 14% overall.

#### • Gen3 Turboprop

#### Note, there was no available exposure data for this generation

• Terrain as a threat generally ranks low according to Gen3 Turboprop accident data.

#### • Gen2 Turboprop

#### Note, there was no available exposure data for this generation

• Terrain as a threat generally ranks low according to Gen2 Turboprop accident and incident data.



# 4.2.3 Flight Data Analysis

# 4.2.3.1 EBT FDA

#### 4.2.3.1.1 Unstable Approaches

- Filter Evidence Table for FDA
- Filter result for [Unstable Approaches)(Landing Issues)(Error Management)]
  - See Figure 4.2.3.1.1
  - Result FDA Unstable Approach
    - 3.5% of approaches are unstable
    - The frequency of flights having at least one FDA event (all severity levels) during landing is the same for stable and unstable approaches indicating there are landing problems with stable approaches as well as unstable approaches.
    - In order to determine the increased risk associated with unstable approaches the event rate and severity are examined in the relevant subsequent phases of flight after the approach (LDG and GA/CLB).
    - Comparing events rates (all severities) stable versus unstable the ratio is 2.24:2.84 (i.e., ratio≈1.3)



Figure 2.3d (duplicate)

 Comparing high severity event rates, for stabilized versus unstable approaches, the ratio is 8.11% versus 19.53 (ratio≈2.4) indicating that there are more than double the high risk events during landing from unstable approaches.





Comparing high severity event rates for stabilized versus unstable approaches, for a defined set of serious events, the rates are 1.96% versus 5.47% (ratio≈2.8). This indicates that examining events of increasing severity produces a greater differential between risks on landing associated between the two types of approach.



Figure 2.3h (duplicate)

■ Flights with unstable approaches generally have more FDA events even in flight phases other than APP and LDG. i.e., ratio ≈1.2 for all event and 1.35 for high severity events.





Figure 2.3i (duplicate)





Summary – The FDA unstable approach rate is around 3.5%. This is consistent across aircraft types and geographical regions. There are as many flights that have landing events following stable approaches as there are following unstable approaches. Solving the unstable approach problem will not address all landing issues. The increased risk associated with unstable approaches becomes evident when examining event rates and event severity. Landings from unstable approaches have a higher event rate and as the events themselves become more severe, the event rate becomes even higher. Unstable approaches can be viewed as a barometer of the flight itself; flights with unstable approaches generally have more FDA events all in-flight phases, including phases not associated with the approach.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
170	3.5% of approaches are unstable	APR	34	34	FDA	Unstable APR/GA	Unstable APP	Mis A/C Stable	All
171	Only 1.4% of them lead to a Go-Around	APR	34	34	FDA	Unstable APR/GA	Unstable APP Go-Arounds	Mis A/C Stable Compliance	Application of Procedures/Knowledge
178	Frequency of fits having at least one FDA event (all severity levels) is the same for stable and Unstable Approaches (83.63 vs 81.11 stable vs unstable respectively) indicating there are landing problems with stable approaches as well.	APR	34	34	FDA	Unstable APR/GA	Landing Issues	Compliance Mis A/C State Mis-Sys	AI
179	Comparing events per fit (all severities) stable vs unstable is 2.24:2:84 or r=1.3 (approx.)	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	All
180	Comparing events rates (high severity stable vs unstable is 8.11% vs 19.53 (approximately 2.4 times) indicating that there are more than double the h irisk events on landing with Unstable Approaches	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	AI
181	Comparing event rates stable vs Unstable Approaches (all severities) for the selected 10 serious landing events stable vs unstable is 14.33% to 34.52% or r=2.4 (approx.)	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	AI
182	Comparing event rate (high severity) stable vs unstable for the set of 10 serious events is 1.96% vs $5.47\%$ or r=2.8 (approx) indicating that there are almost 3 times the hi risk events on landing with Unstable Approaches	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	AI
183	Unstable Approaches are not the cause of all landing problems. This is particularly concerning if we remember that the ratio of stable approaches over Unstable Approaches is approx. 27:1	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	Manual AC Control
184	But if we drill down we see that when Unstable Approaches occur, there are many more of severe events during landings (things go more wrong when unstable.)	APR	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	Manual AC Control
185	Flights with Unstable Approaches produce more events than flights with Stable Approaches even in phases of flight outside of Approaches and Landings.	All	34	AI	FDA	Unstable APR/GA	Unstable APP Error Mgt	Compliance Mis A/C State Mis-Sys	All

Figure 4.2.3.1.1 – Unstable Approach/EBT FDA

# 4.2.3.1.2 Go-Around

- Filter Evidence Table for FDA
- Filter result for [Unstable Approaches (GA)(Unstable Approaches Surprise)]
  - See Figure 4.2.3.1.2b
  - Result FDA 2 Go-Around (FDA)
    - 1.4% of unstable approaches lead to a go-around.
    - The rate of FDA events for a go-around from an unstable approach is 1.6 events per flight.
    - There is an average increase of 85% in the rate of high-risk events when a go-around is executed from an unstable approach, when compared to go-arounds executed from stabilized approaches.



•



Figure 2.3g (duplicate)

- The FDA event rates are conservative, because many errors are not captured due to technical reasons. (Parameter, software and hardware limitations)
- In the FDA database of 1.6 million flights across multiple types (Gen 3 and 4) the average go-. around initiation height above the aerodrome was over 800 ft. with a ratio of over 6:1 of initiation heights > 200 ft. to initiation heights  $\leq$  200 ft.



Average Go-Arounds Height by Year

Figure 4.2.3.1.2







 Summary – Only 1.4% of unstable approaches lead to a go-around, with an FDA all event rates of 1.6 occurrences in the immediate phases after go-around (GA, CLB). The high-risk event rate for the same period is 0.24. Both these rates are conservative because the flight recorder cannot capture many of the crew errors that could occur. Go-around initiation heights overwhelmingly occur at heights different from those briefed.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
171	Only 1.4% of them lead to a Go-Around	APR	34	34	FDA	Unstable APR/GA	Unstable APP Go Arounds	Mis A/C State Compliance	Application of Procedures/Knowledge
172	(0.31% of stable approaches lead to a Go-Around)	APR	34	34	FDA	Unstable APR/GA	Unstable APP Go Arounds		
173	A GA from an Unstable App causes on average 1.6 FDA risk event	APR GA	34	34	FDA	Unstable APR/GA	Unstable APP Go Arounds	Mis A/C State	All
174	24% rate of hi risk events during GA from unstable apprs	APR GA	34	34	FDA	Unstable APR/GA	Unstable APP Go Arounds	Mis A/C State	All
175	FDA cannot detect many errors; e.g. Lat Flight Plan deviations.	APR GA	34	All	FDA	Unstable APR/GA	Go Arounds	Mis A/C State Mis-AFS Mis-Sys	
177	The ratio of GA>200' To GA ≤200' is more than 6:1 The ratio for Stable Approaches is higher	APR GA	34	34	FDA	Unstable APR/GA	Go Arounds Surprise		All
187	Looking at a cross secton of types (5 types and 9 models) over a three year period including 1.6 million flights and approximately 5700 go- arounds) the average height above the field was over 800 at the initiation of the GA. All types in the study had a least one GA from 0 ft agl. Many GAs occured close to 2000 agl.	APR	34	234	FDA	Unstable APR/GA	Go Arounds Surprise		All

Figure 4.2.3.1.2b - Go-Around/EBT FDA

# 4.2.3.2 Long Body Aircraft Studies

# 4.2.3.2.1 Manual Aircraft Control

- Filter Evidence Table for Long Aircraft FDA Study
  - Filter Topics [Manual Aircraft Control]
  - See Figure 4.2.3.2.1b
  - Result Long body aircraft study manual aircraft control
    - Long aircraft compared to shorter versions of the same type have a greater frequency of high vertical acceleration landings.



Figure 4.2.3.2.1

 They tend to have steeper approach gradients just prior to flare and a shorter time to touchdown from flare initiation.





• There is a higher tendency "duck under" the glideslope.

- Greater attention is required during landings in crosswinds, with pitch-down and under-flare as well as the aircraft geometric limits.
- Crews need to be made aware that the tendency to under-rotate in long body aircraft degrades take-off performance; pilots should make smooth accurate rotations avoiding "pilot induced oscillations".
- Summary Long body aircraft are more prone to high "G" landings. Because of geometric considerations, perspectives from the cockpit are slightly different laterally and vertically and tend to produce steeper approach gradients just prior to flare as well as centerline displacement in crosswinds. To compensate for this crews should be attentive to landings in crosswind, avoid last minute pitch-down and a tendency to under-flare. There is a tendency to under-rotate in long body aircraft, which degrades take-off performance; pilots should make smooth accurate rotations avoiding "pilot induced oscillations.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
297	Long aircraft type variant landings with vertical acceleration above 1.5g were more frequent compared to the shorter versions resulting in higher scatter of the landing assessment parameters.	LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual Aircraft Control	Knowledge Application of Procedures/Knowledge Manual Aircraft Control
298	for 1.3% of the landings, the long aircraft type variant had a higher rate of high vertical acceleration landings compared to the shorter type variant. From the data - the probability of a landing > 1.75 g was found to be 0.25 % on long aircraft type variant compared to 0.04 % on shorter versions.	LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual Aircraft Control	Manual Aircraft Control
299	It was noted that the obvious difference in inertia implied that in certain circumstances (such as recovery from a steep approach gradient) more anticipation would be needed in the long aircraft type/variant than the shorter versions	APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual Aircraft Control	Manual Aircraft Control Knowledge
302	One of the most interesting results is a strong correlation between high V2 at touchdown and a lack of effective pitch stick input. This is either due to insufficient or late aft input and provides a clear implication that pitch control authority is not in question	LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual Aircraft Control	Manual Aircraft Control SA Application of Procedures/Knowledge
303	Compared to the shorter version, statistically the long aircraft type variant shows: – A slightly steeper approach gradient at the start of the flare – More forward stick input below 150 ft – A shorter time from flare to touchdown	APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual Aircraft Control	Manual Aircraft Control SA
304	A dedicated examination of all the hard landings* available in the database confirmed that a majority (60%) of these cases involved a late "Duck Under" (pilot action to steepen the slope at or just below 150 feet AFE to bring the touch down point closer to the threshold), followed by an insufficient flare (too low and/or not enough nose up pitch input) * Landings having a maximum vertical acceleration > 1.75g (Note that this is not the AMM definition of hard landing	APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual Aircraft Control Mis A/C State	Manual Aircraft Control SA Application of Procedures/Knowledge
305	There is a need for pilots to better anticipate and monitor the final approach and flare on the long aircraft type variant has become evident.	APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual Aircraft Control Mis A/C State	Manual Aircraft Control SA
306	To avoid hard landings, handling recommendations include: - Maintaining a stable slope prior to flare (no "duck under") - Avoidance of under flaring - Avoidance of significant nose down inputs during flare - Crosswind landing reminders - Reminder of pitch monitoring and aircraft pitch geometric	APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control Monitor xcheck Surprise	Manual Aircraft Control Mis A/C State Compliance	Manual Aircraft Control SA Communication Application of Procedures/Knowledge
307	<ul> <li>It is recommended to highlight differences to pilots receiving training to operate long aircraft type variant either in a mixed fleet or single fleet environment. These differences can be highlighted within the scope of type rating training and recurrent.</li> </ul>	APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing issues unstable approach Manual AC Controll Compliance Error Mgt	Crosswind Compliance CRM mis A/C state	Knowledge Application of Procedures/Knowledge Manual Aircraft Control
308	On difficult runways, use of dedicated markings in conjunction with a predetermined Auto-brake setting may increase crew confidence to achieve the proper touchdown point without the need to duck under.	APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual Aircraft Control Mis A/C State Compliance	Knowledge Application of Procedures/Knowledge Manual Aircraft Control

Figure 4.2.3.2.1b



# 4.2.3.2.2 Landing Issues

- Filter Evidence Table for Long Aircraft FDA Study
- Filter Topics [Landing Issues]
  - See Figure 4.2.3.2.2a
  - Result Long Body Aircraft Study Landing Issues
    - The probability of a landing > 1.75 g was found to be 0.25% on long aircraft type variant compared to 0.04% on shorter versions.





- The difference in inertia implies recovery from a steep approach gradient demands greater anticipation on long body aircraft
- Compared to shorter versions, long body aircraft show a slightly steeper approach gradient at flare initiation, with greater forward control input below 150 ft and shorter time from flare to touchdown.
- There is a need for pilots to better anticipate and monitor the final approach and flare on a long body aircraft type.
- Pilots should maintain a stable slope prior to flare initiation, avoiding the tendency to "duck under" the glideslope.
- Pilots should avoid "under flaring."
- Close attention is required when performing approaches and landing in crosswinds.
- Summary Landing events are statistically more likely with long body aircraft, especially with respect to heavy landings. Pilots need to be especially cognizant of not 'ducking under' the glideslope. In addition, pilots need to understand the differences in ground speed and momentum as well as perceptual differences both laterally and vertically resulting from the extended length between the main gear and cockpit.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
297	Long aircraft type variant landings with vertical acceleration above 1.5g were more frequent compared to the shorter versions resulting in higher scatter of the landing assessment parameters.	LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Knowledge Application of Procedures/Knowledge Manual AC Control
298	for 1.3% of the landings, the long aircraft type variant had a higher rate of high vertical acceleration landings compared to the shorter type variant. From the data - the probability of a landing > 1.75 g was found to be 0.25% on long aircraft type variant compared to 0.04% on shorter versions.	LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Manual AC Control
299	it was noted that the obvious difference in inertia implied that in certain circumstances (such as recovery from a steep approach gradient) more anticipation would be needed in the long aircraft (type/variant than the shorter versions	APR LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Manual AC Control knowledge
302	One of the most interesting results is a strong correlation between high Vz at touchdown and a lack of effective pitch stick input. This is either due to insufficient or late aft input.	LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Manual AC Control SA Application of Procedures/Knowledge
303	Compared to the shorter version, statistically the long aircraft type variant shows: – A slightly steeper approach gradient at the start of the flare – More forward stick input below 150 ft – A shorter time from flare to touchdown	APR LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Manual AC Control SA
304	A dedicated examination of all the hard landings* available in the database confirmed that a majority (60%) of these cases involved a late "Duck Under" (pilot action to steepen the slope at or just below 150 feet AFE to bring the touch down point closer to the threshold), followed by an insufficient flare (too low and/or not enough nose up pitch input) * Landings having a maximum vertical acceleration > 1.75g (Note that this is not the AMM definition of hard landing	APR LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control Mis A/C State	Manual AC Control SA Application of Procedures/Knowledge
305	There is a need for pilots to better anticipate and monitor the final approach and flare on the long aircraft type variant has become evident.	APR LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control Mis A/C State	Manual AC Control SA
306	To avoid hard landings, handling recommendations include: - Maintaining a stable slope prior to flare (no 'duck under') - Avoidance of under flaring - Avoidance of significant nose down inputs during flare - Crosswind landing reminders - Reminder of pitch monitoring and aircraft pitch geometric limits	APR LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control Monitoring Xcheck Surprise	Manual AC Control Mis A/C State Compliance	Manual AC Control SA Communication Application of Procedures/Knowledge
307	It is recommended to highlight differences to pilots receiving training to operate long aircraft type variant either in a mixed fleet or single fleet environment.	APR LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing issues Unstable APP Manual AC Control Compliance Error Mgt	Crosswind Compliance CRM Mis A/C state	Knowledge Application of Procedures/Knowledge Manual AC Control

Figure	42322	– Landing	Issues/FRT	FDΔ
riguie	4.2.3.2.20		155UE5/ED1	FDA

# 4.2.3.2.3 Crosswind

•

- Filter Evidence Table for Long Aircraft FDA Study
  - Word search [Crosswind]
  - See Figure 4.2.3.2.3
    - Result Long Body Aircraft Study Weather
      - Avoidance of "duck under" the glideslope.
      - Crosswind landing reminders
    - Summary In low visibility and/or crosswind conditions common errors such as "duck under" and misalignment with the runway centerline are more critical in long body aircraft.

E	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors
:	To ave - Mai 306 - Avo - Avo - Cro - Rer	void hard landings, handling recommendations include: aintaining a stable slope prior to flare (no "duck under") oidance of under flaring oidance of significant nose down inputs during flare osswind landing reminders eminder of pitch monitoring and aircraft pitch geometric limits	APR LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control Monitoring Xcheck Surprise	Manual AC Control Mis A/C State Compliance

Figure 4.2.3.2.3 – Crosswind/EBT FDA





# 4.2.3.2.4 Compliance

- Filter Evidence Table for Long Aircraft FDA Study
- Filter Factors [Compliance]
- Suppress superfluous
  - See Figure 4.2.3.2.4
  - Result Long Body Aircraft Study Compliance
    - To avoid high "G" landings associated with long body aircraft, it important to follow any specific recommendations provided by the OEM.
    - The phases of flight most affected by the recommendations are TO, APP and LDG.
  - Summary In long aircraft, following the recommendations of the manufacturer provided in SOP's and training mitigates the tendency toward high "G" landings. Application of take-off procedures is equally important in the prevention of "pilot induced oscillations" during take-off.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
306	To avoid landings, handling recommendations include: -Maintaining a stable slope prior to flare (no "duck under") -Avoidance of under flaring -Avoidance of significant nose down inputs during flare -Cross wind landing reminders -Reminder of pitch monitoring and aircraft pitch geometric limits	APR LDG	4	4	Long Aircraft FDA Study	Hard Landing	Landing Issues Manual AC Control Monitoring Xcheck Surprise	Manual AC Control Mis A/C State Compliance	Flight Management, Guidance/Automation SA Communication Application of Procedures/Knowledge
307	It is recommended to highlight differences to pilots receiving training to operate long aircraft type variant either in a mixed fleet or single fleet environment. These differences can be highlighted within the scope of type rating training and recurrent.	APR LDG	4	4	Long Aircraft FDA Study	Hard Landing	Landing Issues Unstable APP Manual AC Control Compliance Error Mgt	Crosswind Compliance CRM Mis A/C State	Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
308	On difficult runways, use of dedicated markings in conjunction with a predetermined Auto-brake setting may increase crew confidence to achieve the proper touchdown point without the need to duck under.	APR LDG	4	4	Long Aircraft FDA Study	Hard Landing	Landing Issues Manual AC Control	Manual AC Control Mis A/C State Compliance	Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
310	Long aircraft with high power tend to have: -Lower rotation rates which could result in degraded TO performance -Require a greater attention to making a smooth rotation to avoid PIO on takeoff.	то	4	All	Long Aircraft FDA Study	Rotation Technique PIO	Manual AC Control	Mis A/C State Compliance	Flight Management Guidance/Automation SA Application of Procedures/Knowledge

Figure 4.2.3.2.4 - Compliance/EBT FDA

# 4.2.3.3 A Study of Normal Operational Landing Performance on Subsonic Civil Narrow Body Jet Aircraft during ILS Approaches

### 4.2.3.3.1 Landing Issues

- Filter Evidence Table NLR
- Filter Topics [Landing Issues]
  - See Figure 4.2.3.3.1
  - Result Aircraft during ILS Approaches Landing Issues
    - Threshold crossing height has strongest influence on airborne distance over the runway.
    - Speed loss from flare initiation height to touchdown has a significant effect on airborne distance over the runway.
    - Gen 4 jet aircraft have fewer tendencies to over-speed at the runway threshold, compared with other types, due to the use of autothrottle/autothrust during the landing.
    - Autolands have a lower average airborne distance over the runway than manual landings.
  - Summary FDA statistical analysis on a large sample of Gen 3 and 4 jet aircraft indicated that automation (autoland and autothrottle/autothrust) provide greater touchdown accuracy, with Gen 4 jet aircraft being more accurate than Gen 3 jet aircraft. The two parameters most affecting airborne distance are threshold crossing height and airspeed over-speed at threshold, in that order.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
188	The influence of the threshold crossing height appears to have the strongest influence on the airborne distance.	LDG	34	All	NLR	Generation Automation Unstable APR/GA	Error Mgt Landing Issues	Compliance Mis A/C State	Application of Procedures/Knowledge Flight Management, Guidance/Automation
189	The speed loss from flare initiation to touchdown has a very significant influence on the airborne distance.	LDG	34	All	NLR	Generation Automation Unstable APR/GA	Error Mgt Landing Issues	Mis A/C State	Manual AC Control
190	The difference in the actual speed and the reference speed over the threshold has a strong influence on the airborne distance.	LDG	34	All	NLR	Generation Automation Unstable APR/GA	Error Mgt Landing Issues	Mis A/C State	Application of Procedures/Knowledge Flight Management, Guidance/Automation
191	The Gen 3 type shows a higher tendency to over speed at the threshold compared to the other types. This is most likely caused by the fact the fly-by-wire aircraft usually fly with the auto thrust (A/THR) engaged during a landing whereas a conventional controlled aircraft with wing mounted engines disengages the A/THR as soon as the auto pilot is disengaged to avoid pitch up tendencies (like on the B737). With A/THR engaged the speed control is more accurate.	LDG	34	34	NLR	Generation Automation Unstable APR/GA	Landing Issues	Mis A/C State	Flight Management, Guidance/Automation
192	The autolands have a lower average airborne distance than manual landings and also show less deviation from the average airborne performance.	LDG	34	34	NLR	Generation Automation Unstable APR/GA	Landing Issues	Mis A/C State	Flight Management, Guidance/Automation

Figure 4.2.3.3.1



# 4.2.4 Training Data (AQP & ATQP)

# 4.2.4.1 AQP Study

#### 4.2.4.1.1 Automation

- Filter Evidence Table AQP
  - Filter Topic [Automation]
    - See Figure 4.2.4.1.1
    - Result AQP Study Automation
      - Gen 4 jet has a significantly higher rate of NCGs (non-conforming grades below company standard) in GND and CRZ phases of flight due to automation issues and international procedures.
      - The descent phase for Gen 3 and Gen 4 jet aircraft has the highest rate of NCGs, automation being a significant area weakness.
    - Summary Automation is an issue of concern regarding assessments in AQP in both the planning and execution phases of flight. The phases most concerned are CRZ and DES.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
157	The two flight phases where the GEN IV - TYPE has a significantly higher rate of non-conforming grades are Ground Operations and Cruise, which are preparatory phases. Based on instructor comments, in cruise the high rate is driven by difficulties with international procedures - some problems also related to the use of Automation. For the Ground phase, the instructor comments were not specific enough to determine the types of problems.	GRD CRZ	234	34	AQP	ATQP/AQP Generation Automation phases of flight	Automation	CRM Mis-AFS	Application of Procedures/Knowledge Flight Management Guidance/Automation
165	The descent phase has the highest non-conforming grades. Based on the instructor comments, the three areas of concern are Automation, System Management and Briefings.	DES	234	234	AQP	ATQP/AQP Generation	Automation Compliance	Mis-AFS Mis-Sys	Communication Application of Procedures/Knowledge Flight Management Guidance/Automation

Figure 4.2.4.1.1 – Automation/AQP

# 4.2.4.1.2 Error Management

- Filter Evidence Table AQP
- Filter Topic [Error management]
  - See Figure 4.2.4.1.2a
  - Result AQP Study Error Management
    - The largest numbers of errors in all evaluations, both in IQ (Initial Qualification) and in CQ (Continuing Qualification), are policy errors.
    - Policy errors average 50% of the total errors
    - The 2<sup>nd</sup> ranked error type is procedural.
    - Crews operating Gen 3 jet aircraft show a greater percentage of intentional non-compliance and decision making errors than crews operating Gen 4 jet aircraft. This difference increases as the training cycle progresses. This same phenomenon exists with non-technical skills.



Figure 4.2.4.1.2 – Error Proportionality

Summary – In all AQP evaluations, whether type rating courses (IQ) or recurrent training (CQ), policy and procedural error types are ranked 1<sup>st</sup> and 2<sup>nd</sup>, accounting for the majority of all errors. Crews operating Gen 3 jet aircraft show a proportionally greater percentage of errors relating to proficiency, situation awareness, non-compliance and decision making when compared with crews operating Gen 4 jets. This trend increases as the training cycle progresses from the type rating to recurrent line checks.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
166	The biggest error category is Policy. It is equally present for all types and makes about 50% of all errors. The second biggest category is Procedural.	All	234	All	AQP	Competencies Error ATQP/AQP Procedures	Error Mgt	Compliance	Application of Procedures/Knowledge
167	In the OE 1 <sup>st</sup> flight error distribution charts, the Gen III types present errors related to Proficiency and Situational Awareness while this is not the case for GEN IV - TYPE.	All	234	34	AQP	Competencies Error SA ATQP/AQP Generation	Error Mgt		SA
168	The more the training cycle advances towards the line check, the more the Gen III types present Intentional Non-Compliance and Decision Making errors. This is not the case for GEN IV - TVPE, which on the contrary presents some Intentional Non- Compliance during TR. This difference is noticeable.	All	234	34	AQP	Competencies Error ATQP/AQP Generation Compliance Decision Making	Error Mgt	Compliance	Problem Solving Decision Making Procedures/Knowledge
169	The more the training cycle advances towards the line check, the more the Gen III types present errors related to non- technical skills, compared to the GEN IV - TYPE.	All	234	34	AQP	Competencies Error ATQP/AQP Generation	Error Mgt		Communication SA Leadership and Teamwork Workload Management Problem Solving Decision Making

Eiguro	1 2 1 1	20	Error	Monoa	omont	
riuuie	4.2.4.1	.zd –	EIIUI	Ivialiau	emenu	AUF

#### 4.2.4.1.3 Manual Aircraft Control

- Filter Evidence Table AQP
- Filter Topic [Manual Aircraft Control]
  - See Figure 4.2.4.1.3b

# • Result – AQP Study – Manual Aircraft Control

 Gen 4 jet aircraft have best pilot performance results for manual aircraft control maneuvers during type ratings.



#### Figure 4.2.4.1.3

 The percentage of NCGs grades for manual aircraft control remains fairly constant from Initial Qualification through to Continuing Qualification especially for Gen 4 jet aircraft. Gen 3 jet aircraft pilot performance improves slightly from Initial to Continuing Qualification but remains consistently poorer than that for Gen 4 jets.



Figure 4.2.4.1.3a

 Summary – Training results from AQP demonstrate that pilots achieve a more rapid mastery of manual aircraft control skills during initial training in Gen 4 jet aircraft. Manual aircraft control skills demonstrated in Gen 3 jet aircraft improve as training progresses, but the assessment level consistently remains below that of the Gen 4 aircraft.

E	ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
1	44	The significant finding is the clear advantage of GenIV-type over the Gen II/III aircraft in Type Rating results.	All	234	34	AQP	ATQP/AQP Generation	Error Mgt Manual AC Control	Mis A/C State Mis-AFS Mis-Sys	All
1	150	TR/MV validation data indicate that pilots have less difficulty to perform the defined maneuvers in the GEN IV –TYPE (gen.IV) vs. gen III -type – with the exception of the windshear maneuvers.	All	234	34	AQP	ATQP/AQP Generation WX	Manual AC Control	Manual AC Control	Flight Management, Guidance/Automation
1	151	In the most extreme case (eng failure at V1) the failure rates were 0.208 (Gen III –type) and 0.074 (GEN IV -TYPE) which indicates a significant difference in difficulty.	то	234	34	AQP	ATQP/AQP Generation	Manual AC Control	Eng Fail Manual AC Control	Flight Management, Guidance/Automation
1	152	Exceptionally, the only two items in TR/MV where the GEN IV -TYPE proved more difficult were the two windshear items (takeoff and approach). The most extreme case is approach where the failure rates were 0.084 (Gen III -type) and 0.154 (GEN IV -TYPE).	TO APR	234	34	AQP	ATQP/AQP Generation	Manual AC Control	Manual AC Control	Flight Management, Guidance/Automation
1	62	Overall, the grades in both generations are better than in TR- LOE but for Gen III significantly worse than in OE certification or RT-MV.	All	234	34	AQP	ATQP/AQP Generation	Manual AC Control	Manual AC Control	Flight Management, Guidance/Automation

Figure 4.2.4.1.3b – Manual Aircraft Control/AQP





# 4.2.4.1.4 Compliance

- Filter Evidence Table AQP
- Filter Topic [Compliance] in Training Topics
  - See Figure 4.2.4.1.4.
  - Result AQP Study Compliance
    - Instructor comments indicate that non-compliance with international procedures, particularly in CRZ, in addition to non-compliance with navigation procedures, are the most significant issues.
    - The DES phase reveals substantial non-compliance during line checks.
    - The largest error category is non-compliance with company policy, which accounts for 50% of the total errors made by the flight crew.
  - Summary The biggest problem with NCGs (non-conforming grades) throughout all operational evaluations is non-compliance with airline policy, amounting to 50% of errors committed. In addition, non-compliance with international procedures is also substantial. The flight phase where the crews have the most difficulty in following procedures is DES. Data from international flights show that the CRZ phase has significantly more NCGs than domestic flights.

Ī	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	The two flight phases where the GEN IV –TYPE has a significant higher rate of non-conforming grades are Ground Operations and Cruise, which are preparatory phases. Based on instructor 157 comments, in cruise the high rate is driven by difficulties with international procedures – some problems also related to the use Automation. For the Ground phase, the instructor comments wer not specific enough to determine the types of problems.	GRD GRZ	234	34	AQP	ATQP/AQP Generation Automation phases of flight	Automation Compliance	CRM Mis-AFS	Application of Procedures/Knowledge Flight Management Guidance/ Automation
	In the OE cert profiles, the only significant variation across types the rate for GEN IV –TYPE in cruise, which is around 10% where 159 the other types are in the range 2%-3%. Based on instructor comments, the reason for the high GEN IV –TYPE rate is international procedures related to navigation.	s as CRZ	234	34	AQP	ATQP/AQP Generation phase	Compliance	Compliance	Application of Procedures/Knowledge
	The descent phase has the highest non-confirming grades. Base on the instructor comments, the three areas of concern are Automation, system Management and briefings. Line check	DES	234	234	AQP	ATQP/AQP Generation Trainability	Automation Compliance	Mis-AFS Mis-Sys	Communication Application of Procedures/Knowledge Flight Management Guidance/Automation
	The biggest error category is Policy. It is equally present for all types and makes about 50% of all errors. The second biggest category is Procedural.	ALL	234	All	AQP	Competencies Error ATQP/AQP Procedures	Error Mgt Compliance	Compliance	Application of Procedures/Knowledge

Figure 4.2.4.1.4 – Compliance/AQP

# 4.2.4.1.5 Generational Aspects

- Filter Evidence Table AQP
- Filter Keywords [Generations]
- Suppress superfluous.
  - See Figure 4.2.4.1.5d
  - Result AQP Study Generations
    - Evaluation data for type ratings shows a marked difference in the rate of NCGs (nonconforming grades) between pilots under training on Gen 4 jet aircraft, and Gen 3 jet aircraft, with the Gen 4 jet pilots demonstrating higher performance.
    - There is a very significant peak in NCGs during the first flight, OE (Operational Evaluation) on all types, the most pronounced being for Gen 4 jet. The negative slope following the peak reflects learning during IOE, and this indicates a training gap; the type-rating course does not sufficiently prepare the crew for line operations.



Figure 4.2.4.1.5

- After the first flight (OE) Gen 3 jet NCGs increase during recurrent training and MV (Maneuvers Validation) and forms a secondary peak for the recurrent training Line Orientated Evaluation (LOE), indicating possible skill decay which is not evident in the Gen 4 jet data.
- Gen 4 jet aircraft have a significantly lower rate of NCGs (better pilot performance grades) for flight maneuvers. The most significant difference is seen with "engine failure between V1 and V2", NCG rates are 21% (Gen 3 jet) and 7.4% (Gen 4 jet).





- The first flight (OE) performances vary considerably by type with differences of 20 percentage points, indicating a need to vary training according to type and generation. See Fig 4.2.4.1.5c.
- Two flight phases where Gen 4 jet shows a higher rate of NCGs are GND and CRZ, which are preparatory phases.





- Gen 4 jet data shows a significantly higher rate of NCG than Gen 3 jet (10% versus 2-3%). This is explained by instructor comments and pertains more to international procedures rather than generational differences.
- The overall advantage of Gen 4 aircraft in NCG rate gradually disappears in recurrent training (CQ) but the grade distribution by phase of flight remains different.





- During line checks, the generational differences are much smaller than in other phases of the training cycle. While the overall rate is lower, some areas remain a problem indicating that recurrent training is not addressing certain issues.
- Summary Certain manual aircraft control maneuver skills are demonstrably easier to acquire in Gen 4 jet aircraft, when compared to Gen 3 jets, and performance data indicates a lower level of skill decay. This advantage is minimized in recurrent training (CQ) but training challenges remain different across generations with certain phases of flight, certain issues being more problematic for different types. This clearly makes a case for the regulation of training being adapted to aircraft generation, and for the focus of assessments to be aligned with overall competency, rather than pure maneuver based skills.



E	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
144	The significant finding is the clear advantage of GenIV-type over the Gen III aircraft in Type Rating results.	All	234	34	AQP	ATQP/AQP Generation	Error Mgt Manual AC Control	Mis A/C State Mis-AFS Mis-Sys	All
145	There is a very significant peak in NCG in the 1 <sup>st</sup> flight (OE) on all types. The peak is most pronounced on the GEN IV -TYPE. The downhill after the peak reflects the huge amount of learning and training on the aircraft during IOE. Such significant learning at this stage of the training program is not desirable. It reflects that the training does not really prepare the trainess for the real operation	All	234	4	AQP	ATQP/AQP Generation Learning on Line. Trainability			All
146	Post-first flight, the Gen IV –type continues at the same low level as in TR, but the curve for Gen III increases for RT-MV and forms a secondary peak for RT-LOE.	All	234	34	AQP	ATQP/AQP Generation Learing on line. Trainability			All
147	Compared to the significant advantage of the GEN IV –TYPE in TR, this advantage has to a large extent disappeared post-first flight.	All	234	4	AQP	ATQP/AQP Generation Trainability			All
148	Generally, the data supports the notion that generation IV aircraft are easier to train. However, the training challenge on GEN IV –TYPE for windshear scenarios illustrates that training data needs to be analysed to optimize the training program.	Ali	234	4	AQP	ATQP/AQP Generation WX. Trainability			All
150	Post-first flight, the Gen IV –type continues at the same low level as in TR, but the curve for Gen III increases for RT-MV and forms a secondary peak for RT-LOE.	All	234	43	AQP	ATQP/AQP Generation WX. Trainability	Manual AC Control	Manual AC Control	Flight Management, Guidance/Automation
151	In the most extreme case (eng failure at V1) the failure rates were 0.208 (Gen III –type) and 0.074 (GEN IV -TYPE) which indicates a significant difference in difficulty.	Ali	234	34	AQP	ATQP/AQP Generation Trainability	Manual AC Control	Eng Fail Manual AC Control	Flight Management, Guidance/Automation
156	The 1 <sup>st</sup> flight <i>profiles</i> are still different across all types, with differences exceeding 20 percentage points.	All	234	All	AQP	ATQP/AQP Generation Trainability			All
157	The two flight phases where the GEN IV –TYPE has a significantly higher rate of non-conforming grades are Ground Operations and Cruise, which are preparatory phases. Based on instructor comments, in cruise the high rate is driven by difficulties with international procedures – some problems also related to the use of Automation. For the Ground phase, the instructor comments were not specific enough to determine the types of problems.	GRD CRZ	234	34	AQP	ATQP/AQP Generation Automation generation phases of flight	Automation Compliance	CRM Mis-AFS	Application of Procedures/Knowledge Flight Management Guidance/Automation
159	In the OE cert profiles, the only significant variation across types is the rate for GEN IV $-TYPE$ in cruise, which is around 10% whereas the other types are in the range 2%-3%. Based on instructor comments, the reason for the high GEN IV $-TYPE$ rate is international procedures related to navigation.	CRZ	234	34	AQP	ATQP/AQP Generation phase	Compliance	Compliance	Application of Procedures/Knowledge
160	The advantage of the GEN IV –TYPE has disappeared to the point that the Type A (Gen III) now shows less non-conforming grades (average 3.6%).	All	234	234	AQP	ATQP/AQP Generation Trainability			
161	Even though the overall performance is similar between these two best performing types (Type A (Gen III) and GEN IV -TYPE), their profiles are very different, indicating that what needs to be emphasized in training is very different.	Ali	234	34	AQP	ATQP/AQP Generation Trainability			
162	Overall, the grades in both generations are better than in TR-LOE but for Gen III significantly worse than in OE certification or RT-MV.	All	234	34	AQP	ATQP/AQP Generation Trainability	Manual AC Control	Manual AC Control	Flight Management, Guidance/Automation
163	In RT-LOE, the GEN IV -TYPE performs generally better than the gen III types, but not to the extent it does in TR. The main changes are in ground and approach phases where the advantage of the GEN IV -TYPE has disappeared (otherwise its profile is similar to TRLOE). The GEN V -TYPE is significantly better than Gen III in takeoff, climb and cruise phases – by a factor of three to one or more.	GRD APR	234	34	AQP	ATQP/AQP Generation Trainability			All
164	At line check, the rates are quite similar for all types. In cruise, descent, approach and landing, the Type A (Gen III) and GEN IV –TYPE both have higher rates of non-confirming grades than the other two types. Paradoxically, these two were the best performers during training. This is an indicator that the initial training performance does not necessarily correlate well with the actual operational performance.	CRZ DES APR LDG	234	234	AQP	ATQP/AQP Generation Trainability			All

Figure 4.2.4.1.5d – Generational Aspects/AQP



# 4.2.4.1.6 Phase of Flight

- Filter Evidence Table AQP
- Filter Keywords [Generations] combine with
- Word search all columns [phase]
- Suppress superfluous.
  - See Figure 4.2.4.1.6b
    - Result AQP Study Generations
      - During Initial Qualification (IQ), Gen 4 jet data shows a significantly lower rate of NCGs than Gen 3 jet (the only exception is the slightly better performance after landing phase for one type). The effect is even greater in TO, CLB and CRZ by 1:2 ratio (i.e., 6.4% to 13.3%).





- The two flight phases with the greatest rate of NCGs in the IQ Line Orientated Evaluation (LOE) are the GND and DES, which could be considered planning or preparatory phases. (See Fig 4.2.4.1.6)
- In the CQ (Continuing Qualification) LOE Gen 4 jet data indicate a lower rate of NCGs, but not in all phases. In GND and APP the there is little difference. In TO, CLB and CRZ Gen 4 jet data show the lower rates of NCGs, by a factor of 3 to 1.
- During line checks, NCGs are similar for all types. The phases with most predominant NCG rates are CRZ, DES, APP and LDG. Interestingly the Gen 3 jet types with the lowest rates of NCGs during IQ have the highest rate in line checks. This is an indicator that the initial training performance does not correlate well with the actual operational performance for Gen 3 jets.
- In line checks DES has the highest NCGs. Based on the instructor comments, the areas of concern are automation, system management and briefings.





#### Figure 4.2.4.1.6a

Summary – During the type-rating course (IQ) the crews of Gen 4 jet aircraft performed considerably better than those operating Gen 3 jet aircraft in all evaluations. For recurrent training (CQ) Gen 4 jet crews maintained this advantage but to a lesser degree, and not in all phases of flight. GND and DES become equally problematic, especially with regard to flight preparation and automation issues. During line checks the Gen 4 jet advantage was less significant, except that there was a marked deterioration with certain Gen 3 jet types. This could indicate a lack of relevancy for the training courses, and consequent preparedness for line operations.

Ī	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	153	The two flight phases with the highest non-conforming grades in TR/LOE were the Ground and Descent phases, which could be considered planning or preparatory phases.	GRD DES	234	All	AQP	ATQP/AQP Trainability		CRM Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation
	154	In every phase the GEN 4 –TYPE (gen 4) has a significantly lower rate of non-conforming grades than types A, B and C (all gen III). (the only exception is the slightly better performance of type A in the After landing phase). The effect is even greater in Takeoff, Climb and Cruise. The average over all flight phases for GEN 4 –TYPE is 6.4% and for the other types 13.3%, in other words the ratio is about 1:2.	TO CLB CRZ ALL	234	34	AQP	ATQP/AQP Generation. Trainability Phase			All
	163	In RT-LOE, the GEN IV –TYPE performs generally better than the gen III types, but not to the extent it does in TR. The main changes are in ground and approach phases where the advantage of the GEN IV –TYPE has disappeared (otherwise its profile is similar to TRLOE). The GEN IV –TYPE is significantly better than Gen III in takeoff, climb and cruise phases – by a factor of three to one or more.	GRD APR ALL	234	34	AQP	ATQP/AQP Generation Trainability			All
	164	At line check, the rates are quite similar for all types. In cruise, descent, approach and landing, the Type A (Gen III) and GEN IV —TYPE both have higher rates of non-confirming grades than the other two types. Paradoxically, these two were the best performers during training. This is an indicator that the initial training performance does not necessarily correlate well with the actual operational performance.	CRZ DES APR LDG	234	234	AQP	ATQP/AQP Generation Trainability			All
	165	The descent phase has the highest non-confirming grades. Based on the instructor comments, the three areas of concern are Automation, system Management and briefings. Line check	DES	234	234	AQP	ATQP/AQP Generation Trainability	Automation Compliance	Mis-AFS Mis-Sys	Communication Application of Procedures/Knowledge Flight Management Guidance/Automation

Figure 4.2.4.1.6b - Phase of Flight/AQP


#### 4.2.4.1.7 AQP – Trainability

• Filter Evidence Table AQP

.

- Filter result for [Trainability] in Keywords, Suppress superfluous.
- See Figure 4.2.4.1.7b
  - Result AQP Study Trainability
    - Generally, the data support the notion that pilots acquire certain skills more easily during training in Gen 4 jets, when compared with gen 3 jets
    - In the most significant case, "engine failure between V1 and V2", the NCGs were: 0.208 (Gen 3) and 0.074 (Gen 4). See Fig 4.2.4.1.5a
    - The two flight phases with the highest NCGs in IQ were the GND and DES phases (preparatory phases). See Figure 4.2.4.1.6
    - The training efficiency is even greater for Gen 4 in TO, CLB and CRZ with Gen 3 aircraft as indicated by significantly higher percentages of NCGs.



Figure 4.2.4.1.7

For the line check, the NCG rates are similar for the generations.



Figure 4.2.4.1.7a

- Paradoxically, the two best performers during IQ turn out to be worst performers in IQ/Line checks indicating that IQ does not well prepare the crews for line operations.
- In the first flight (OE) error distribution charts, Gen 3 jet has a higher rate of errors related to proficiency and situation awareness than Gen 4 jet.
- As the training cycle advances towards the line check, data indicate a higher rate of Gen 3 jet pilot errors related to non-technical skills, when compared to Gen 4 jets.



Figure 4.2.4.1.2 (duplicate) – Error Proportionality

Summary – Training results from AQP demonstrate that pilots achieve a more rapid mastery of certain skills during initial training in Gen 4 jet aircraft. As the training cycle progresses, the difference between Gen3 Jet and Gen4 Jet becomes smaller. Conversely, data show that non-technical skills improve more readily during training for Gen 3 versus Gen 4. In addition, the skills most easily acquired during initial training appear to most problematic during line-checks. The maneuvers showing the highest rate of NCGs in both IQ and CQ is "engine failure between V1 and V2" and this effect is most pronounced in Gen 3 jet, IQ by a factor of more than 3 to 1 (Gen3 Jet versus Gen4 Jet). At the end of type rating course (IQ) Gen3 Jet evaluations show the highest deficiencies in situation awareness and maneuver proficiency. The phases of flight with highest NCGs are GND and DES (preparatory phases) while the phases where training effect is highest are CLB and CRZ.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
145	There is a very significant peak in NCG in the 1 <sup>sh</sup> flight (OE) on all types. The peak is most pronounced on the GEN 4 TYPO. The downhill after the peak reflects the huge amount of learning and training on the aircraft during IOE. Such significant learning at this stage of the training program is not desirable. It reflects that the training does not really prepare the trainees for the real operation	All	234	4	AQP	ATQP/AQP Generation Learning on Line. Trainability			All
147	Compared to the significant advantage of the GEN 4 – TYPE in TR, this advantage has to a large extent disappeared post-first flight.	All	234	4	AQP	ATQP/AQP Generation Trainability			All
151	In the most extreme case (eng failure at V1) the failure rates were 0.208 (Gen 3 -type) and 0.074 (GEN 4 -TYPE) which indicates a significant difference in difficulty.	то	234	34	AQP	ATQP/AQP Generation Trainability	Manual AC Control	Eng Fail Manual Aircraft Control	Manual Aircraft Control
153	The two flight phases with the highest non-conforming grades in TR/LOE were the Ground and Descent phases, which could be considered planning or preparatory phases.	GRD DES	234	All	AQP	ATQP/AQP Trainability		CRM Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation
154	In every phase the GEN 4 – TYPE (gen 4) has a significantly lower rate of non-conforming grades than types A, B and C (all gen 3), (the only exception is the slightly better performance of type A in the After landing phase). The effect is even greater in Takeoff, Climb and Cruise. The average over all flight phases for GEN 4 – TYPE is 6.4% and for the other types 13.3%, in other words the ratio is about 1:2.	TO CLB CRZ ALL	234	34	AQP	ATQP/AQP Generation. Trainability Phase			All
155	There is a very significant overall increase in the non- confirming grades compared to LOEs in TR and RT. The values have roughly doubled. This appears to be an indication that the type rating course is not adequately preparing the pilots for IOE.	All	234	All	AQP	ATQP/AQP. Trainability			All
156	The 1 <sup>st</sup> flight <i>profiles</i> are still different across all types, with differences exceeding 20 percentage points.	All	234	All	AQP	ATQP/AQP Generation Trainability			All
160	The advantage of the GEN 4 –TYPE has disappeared to the point that the Type A (Gen 3) now shows less non-conforming grades (average 3.6%).	All	234	234	AQP	ATQP/AQP Generation Trainability			
161	Even though the overall performance is similar between these two best performing types (Type A (Gen 3) and GEN 4 -TYPE), their profiles are very different, indicating that what needs to be emphasized in training is very different.	All	234	34	AQP	ATQP/AQP Generation Trainability			
162	Overall, the grades in both generations are better than in TR- LOE but for Gen 3 significantly worse than in OE certification or RT-MV.	All	234	34	AQP	ATQP/AQP Generation Trainability	Manual AC Control	Manual Aircraft Control	Manual Aircraft Control
163	In RT-LOE, the GEN 4 –TYPE performs generally better than the gen 3 types, but not to the extent it does in TR. The main changes are in ground and approach phases where the advantage of the GEN 4 –TYPE has disappeared (otherwise its profile is similar to TRLOE). The GEN 4 –TYPE is significantly better than Gen 3 in takeof, climb and cruise phases – by a factor of three to one or more.	GRD APP ALL	234	34	AQP	ATQP/AQP Generation Trainability			All
164	At line check, the rates are quite similar for all types. In cruise, descent, approach and landing, the Type A (Gen 3) and GEN 4 –TYPE both have higher rates of non-confirming grades than the other two types. Paradoxically, these two were the best performers during training. This is an indicator that the initial training performance does not necessarily correlate well with the actual operational performance.	CRZ DES APP LDG	234	234	AQP	ATQP/AQP Generation Trainability			All
165	The descent phase has the highest non-confirming grades. Based on the instructor comments, the three areas of concern are Automation, system Management and briefings. Line check	DES	234	234	AQP	ATQP/AQP Generation Trainability	Automation Compliance	Mis-AFS Mis- Sys	Communication Application of Procedures/Knowledge Flight Management Guidance/Automation
169	The more the training cycle advances towards the line check, the more the Gen 3 types present errors related to non- technical skills, compared to the GEN 4 -TYPE	All	234	34	AQP	Competencies Error ATQP/AQP Generation trainability	Error Mgt	CRM	Communication SA Leadership and Tearnwork Workload Management Problem Solving Decision Making

Figure 4.2.4.1.7b - Trainability/AQP

## 4.2.4.2 ATQP Study

#### 4.2.4.2.1 Unstable Approaches

- Filter Evidence Table ATQP
- Filter result for [Unstable Approaches]
  - See Figure 4.2.4.2.1
  - Result ATQP Study Unstable Approaches
    - During transition from a conventional course to ATQP the operational rate of unstable approaches remained unchanged
    - Approximately 50% of go-arounds resulted from unstable approaches
    - Factors affecting unstable approaches in order of importance are:
      - Accepting constraining ATC clearances
      - Mismanaged visual approaches
      - Mismanaged auto-flight
      - Energy mismanagement
      - Manual aircraft control
  - Summary Unstable approaches were closely monitored during the transition to ATQP and the rate of unstable approach remained constant, indicating that a major change in training can be performed without increasing risk as far as approaches are concerned. Approximately 50% of goarounds during this transition resulted from unstable approaches. The causes of unstable approaches in order of importance were poor decisions in accepting ATC clearances, mismanaged visual approaches, mismanaged energy, and poor manual aircraft control.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
 91	During ATQP implementation period Stability remaining static at 1000' and 500'.	APR	34	34	ATQP airline	Unstable APR	Unstable APP	Mis A/C State	Application of Procedures/Knowledge
 92	During ATQP implementation period G/A's from Unstable Appes account for approximately 1/2 of all G/A's	APR GA	34	34	ATQP airline	Unstable APR/GA Compliance	Go Arounds Unstable APP	Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
93	Factors contributing to Unstable Appes are: 1. Accepting ATC vectors or speed control. 2. Turning too tight when visual, 3. FMGS mis-selections, 4. Energy Management 5. Lack of proficiency when manually flying instrument approaches.	APR	34	34	ATQP airline	Unstable APR/GA	Unstable APP	ATC Mis A/C State Mis-AFS	SA Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control

Figure 4.2.4.2.1 – Unstable Approaches/ATQP



#### 4.2.4.2.2 Automation

- Filter Evidence Table ATQP
- Filter Competencies [Automation]
  - See Figure 4.2.4.2.2
  - Result ATQP Study Automation
    - FMS miss-selection is ranked 3<sup>rd</sup> as cause for unstable approaches
    - Flight management (auto-flight) is the biggest factor in mismanaged go-arounds.
    - Mismanaged auto-flight is a major factor during engine-out non-precision approaches conducted in training.
    - Mismanaged auto-flight is a major factor in engine-out go-arounds during training.
  - Summary Mismanaged auto-flight is a major factor, contributing to unstable approaches and goaround errors, both in training and line operations. This remains constant, whether in the all engines operating, or engine-out case.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
93	Factors contributing to Unstable Appes are: 1. Accepting ATC vectors or speed control. 2. Turning too tight when visual, 3. FMGS mis-selections, 4. Energy Management 5. Lack of proficiency when manually flying instrument approaches.	APR	34	34	ATQP airline	Unstable APR/GA	Unstable APP	ATC Mis A/C State Mis-AFS	SA Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
95	During ATQP implementation period (Missed Approach 1. Approximately 1/10 G/A's failed to comply with SOP's and just over 1/10 G/A's resulted in a flap over speed. 2. There has been no significant change in G/A rates3. Flight Management remains the biggest cause	APR GA	34	34	ATQP airline	GA	Go Arounds	Compliance CRM Mis-AFS Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation
101	vi. Single Engine NPA 1. Just over 1% failed 2. 5% were procedural errors, 3. 2% Automation, 4. 2% situational awareness. 5. 5% were handling errors	APR	34	34	ATQP airline	Manual A/C Control Automation	System Malfunction Manual AC Control Automation	Eng Fail Syst mal Compliance CRM Mis-Sys Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
102	<ul> <li>vii. SE Go-Around</li> <li>1. Approximately 2% failed or only passed after a repeat</li> <li>2. Of the repeats</li> <li>a. just over 4% were procedural errors,</li> <li>b. just over 4% handling</li> <li>3. Of the failed</li> <li>a. 2% Automation and a 2% situational awareness.</li> <li>b. Approx 1/3 were procedural errors and ½ handling.</li> </ul>	GA	34	34	ATQP airline	Manual A/C Control Automation GA	Go Arounds Automation Error Mgt	Eng Fail Compliance CRM Mis-AFS Mis A/C State	SA Application of Procedures/Knowledge Flight Management GuidanceAutomation Manual Aircraft Control
106	2 Eng G/A should be scheduled into recurrent training.	GA	34	34	ATQP airline	GA Manual AC Control	Go Arounds	Mis A/C State	Application of Procedures/Knowledge Flight Management GuidanceAutomation Manual Aircraft Control
108	Innovative training solutions should be sought for crew to maintain currency with FMGS and technical / procedural Knowledge.	all	34	34	ATQP airline	Automation	Automation	Compliance CRM Mis-AFS	Knowledge Application of Procedures/Knowledge Flight Management GuidanceAutomation



#### 4.2.4.2.3 Error Management

- Filter Evidence Table ATQP
- Filter result for [Automation]
  - See Figure 4.2.4.2.3c
  - Result ATQP Study Error Management
    - Inadvertent selections occur during operations not routinely practiced, in particular all engines go-around, "engine failure between V1 and V2", engine out non-precision approach, and engine out go-around.
    - By far the two biggest categories of errors were procedural and manual aircraft control. (Note. The data set is predominantly related to Gen 4 jets)







Figure 4.2.4.2.3a





- Training in descent planning and energy management during the descent and approach, is not adequate.
- Summary Both operational and training data confirm that crews have problems with maneuvers that are not routinely practiced. Procedural and manual control skills need reinforcement, as these areas are where most of the errors occur. In addition, descent planning and energy management also need specific training.

l re	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
9	During ATQP implementation period, inadvertent mis-selections appear to occur most during operations that are not routinely practised	All	3 4	34	ATQP airline	Error	Error Mgt Surprise	Mis-Sys Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge
9	During ATQP implementation period, dual Inputs have reduced but need to be carefully monitored.	All	34	34	ATQP airline	ManualACControl Monitoring Xchecking	Error Mgt Manual AC Control	Mis-Sys Ops/Type Spec Compliance	SA Manual AC Control Application of Procedures/Knowledge
10	<ul> <li>vii. SE Go-Around</li> <li>1. Approximately 2% failed or only passed after a repeat</li> <li>2. Of the repeats</li> <li>a. just over 4% were procedural errors,</li> <li>b. just over 4% handling</li> <li>3. Of the failed</li> <li>a. 2% Automation and a 2% situational awareness.</li> <li>b. Approx 1/3 were procedural errors and ½ handling.</li> </ul>	GA	34	34	ATQP airline	ManualACControl Automation GA	Go Arounds Automation Error Mgt	Eng Fail Compliance CRM Mis-AFS Mis A/C State	SA Application of Procedures:Knowledge Flight Management Guidance and Automation Manual AC Control
10	ii. Procedures not routinely flown, 2 Eng G/A, EFATO, SE NPA and SE G/A appear to present the greatest difficulty to crew, with procedural error and Manual/ACControl being the biggest factors.	TO GA	34	34	ATQP airline	ManualACControl GA	Go Arounds System Malfunctionf Error Mgt Surprise	Eng Fail Syst mal Compliance CRM Mis A/C State	Application of Procedures/Knowledge Manual AC Control
10	77 Training in energy Management and environmental descent planning needs to be more specific.	DES	34	34	ATQP airline	Unstable APR	Error Mgt Unstable APP	Mis A/C State	Problem Solving Decision Making SA

Figure 4.2.4.2.3c - Error Management/ATQP

#### 4.2.4.2.4 Manual Aircraft Control

- Filter Evidence Table Source ATQP
- Filter Topics for [(Manual)(Man)] combine with
- Filter Competencies [Manual Aircraft Control]
  - See Figure 4.2.4.2.4
  - Result ATQP Study Manual Aircraft Control
    - Manual control issues remained stable or improved slightly during ATQP implementation
    - Handling problems remain one of the biggest concerns particularly with maneuvers not using the autopilot and not routinely practiced. See Fig 4.2.4.2.3 and Fig 4.2.4.2.3b
  - Summary The evidence gathered during ATQP shows that manual aircraft control is a problem on modern aircraft and more practice in training is needed.

l r	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
9	During ATQP implementation period There has been an increase in the number of fast touchdowns. AND There has been a reduction in landing events	LDG	34	34	ATQP airline	ATQP/AQP	Landing Issues	Mis A/C State	Manual AC Control
9	During ATQP implementation period, dual Inputs have reduced but need to be carefully monitored.	All	34	34	ATQP airline	Manual AC Control Monitoring Xchecking	Error Mgt Manual AC Control	Mis-Sys Ops/Type Spec Compliance	SA Manual Aircraft Control Application of Procedures/Knowledge
11	vi. Single Engine NPA 1. Just over 1% failed 2. 5% were procedural errors, 3. 2% Automation, 4. 2% situational awareness. 5. 5% were handling errors	APR	34	34	ATQP airline	Manual AC Control Automation	System Malfunction Manual AC Control Automation	Eng Fail Syst mal Compliance CRM Mis-Sys Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
1	Procedures not routinely flown, 2 Eng G/A, EFATO, SE NPA and SE G/A flown with Automation the error rate is reduced.	TO GA	34	34	ATQP airline	Manual AC Control Automation GA	Manual AC Control	Workload Distraction	Problem Solving Decision Making Manual Aircraft Control

Figure 4.2.4.2.4 – Manual Aircraft Control/ATQP

#### 4.2.4.2.5 Go-Around

- Filter Evidence Table Source ATQP
- Filter Topics for [GA]
  - See Figure 4.2.4.2.5a
  - Result ATQP Study Go-Around
    - Mismanaged auto-flight remains the biggest contributory factor in go-arounds
    - 10% of go-arounds failed to comply with SOP.
    - 10% of go-arounds had flap over-speeds.
    - Procedural and handling errors are the biggest factors in engine-out go-arounds.
    - Data indicates that all-engine go-arounds are a problem not dealt with in training.
  - Summary Mismanagement of auto-flight systems, resulting in unstable approaches, are the biggest cause for go-arounds in operations. A significant percentage of go-arounds result in flap over-speeds and violations of SOP. Engine out go-arounds form part of the regulated training program, but still result in a significant percentage of unacceptable performance grades. Surprise go-arounds do not form part of the training program, and are not well executed by crews in line operations. Consequently, the all-engines go-around from various altitudes is a target for improvement in ATQP.

•

#### Distribution of GA Altitudes by initiation Altitude N = 333



Figure 4.2.4.2.5

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
95	During ATQP implementation period (Missed Approach 1. Approximately 1/10 G/A's failed to comply with SOP's and just over 1/10 G/A's resulted in a flap over speed. 2. There has been no significant change in G/A rates3. Flight Management remains the biggest cause	APR GA	34	34	ATQP airline	GA	Go Arounds	Compliance CRM Mis-AFS Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/ Automation
96	During ATQP implementation period, the number of APProaches not meeting company criteria at 1000 ft has significantly reduced.	APR	34	34	ATQP airline	Unstable APR	Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
102	<ul> <li>vii. SE Go-Around</li> <li>1. Approximately 2% failed or only passed after a repeat</li> <li>2. Of the repeats</li> <li>a. just over 4% were procedural errors,</li> <li>b. just over 4% handling</li> <li>3. Of the failed</li> <li>a. 2% Automation and a 2% situational awareness.</li> <li>b. Approx 1/3 were procedural errors and ½ handling.</li> </ul>	GA	34	34	ATQP airline	Manual AC Control Automation GA	Go Arounds Automation Error Mgt	Eng Fail Compliance CRM Mis-AFS Mis A/C State	SA Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
103	ii. Procedures not routinely flown, 2 Eng G/A, EFATO, SE NPA and SE G/A appear to present the greatest difficulty to crew, with procedural error and ManualACControl being the biggest factors.	TO GA	34	34	ATQP airline	Manual AC Control GA	Go Arounds System Malfunction Error Mgt Surprise	Eng Fail Syst mal Compliance CRM Mis A/C State	Application of Procedures/Knowledge Manual Aircraft Control
106	2 Eng G/A should be scheduled into recurrent training.	GA	34	34	ATQP airline	GA Manual AC Control	Go Arounds	Mis A/C State	Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control



145

#### 4.2.4.2.6 System Malfunction

- Filter Evidence Table Source ATQP
- Filter Topics for [Sys Mal]
  - See Figure 4.2.4.2.6
  - Result ATQP Study System Malfunction
    - "Engine failures between V1 and V2" is the maneuver with the highest rate of unacceptable performance, almost 50% of failures involving procedural errors.
    - The 2<sup>nd</sup> ranked maneuver in terms of unacceptable performance is the engine-out go-around, with procedural and handling errors most prevalent.
    - The 3<sup>rd</sup> ranked maneuver in terms of unacceptable performance is the engine out nonprecision approach, with procedures and handling being the biggest issues, followed by situation awareness and automation errors.
  - Summary Procedures and handling associated with maneuvers after engine failure result in the highest rates of unacceptable performance in training. Despite the emphasis in training on engine failure, its effects continue to be problematic to crews in terms of procedures and manual aircraft control.

E rei	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
10	Engine Failure on TO: 1. Approximately a 1/5 failed or only passed with a repeat 2. Almost ½ were procedural errors. 3. 1% related to Situational awareness or Decisions Making	то	34	34	ATQP airline	Manual AC Control	System Malfunction	Eng Fail Syst mal Compliance CRM Mis-Sys	SA Problem Solving Decision Making Application of Procedures/Knowledge
10	vi. Single Engine NPA 1. Just over 1% failed 2. 5% were procedural errors, 3. 2% Automation, 4. 2% situational awareness. 5. 5% were handling errors	APR	34	34	ATQP airline	Manual AC Control Automation	System Malfunction Manual AC Control Automation	Eng Fail Syst mal Compliance CRM Mis-Sys Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/ Automation Manual Aircraft Control
10	vii. SE Go-Around 1. Approximately 2% failed or only passed after a repeat 2. Of the repeats a. just over 4% were procedural errors, b. just over 4% handling 3. Of the failed a. 2% Automation and a 2% situational awareness. b. Approx 1/3 were procedural errors and ½ handling.	GA	34	34	ATQP airline	Manual AC Control Automation GA	Go Arounds Automation Error Mgt System Malfunction	Eng Fail Compliance CRM Mis-AFS Mis A/C State	SA Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
10	Procedures not routinely flown, 2 Eng G/A, EFATO, SE NPA and SE G/A appear to present the greatest difficulty to crew, with procedural error and Manual AC Control being the biggest factors.	TO GA	34	34	ATQP airline	Manual AC Control GA	Go Arounds System Malfunctionf Error Mgt Surprise	Eng Fail Syst mal Compliance CRM Mis A/C State	Application of Procedures/Knowledge Manual Aircraft Control
10	5 EFATO, SE NPA and SE GA should be retained in the ISS.	TO APR GA	34	34	ATQP airline	Manual AC Control GA	System Malfunctionf Go Arounds	Eng Fail Syst mal	Manual Aircraft Control

Figure 4.2.4.2.6 - System Malfunction/ATQP



#### 4.2.4.2.7 Surprise

- Filter Evidence Table Source ATQP
- Filter Topics for [Surprise]
- Word search all columns [SA and/or Situation Awareness]
- Suppress superfluous
  - See Figure 4.2.4.2.7
    - Result ATQP Study Surprise
      - Inadvertent system and automation selections occur when not sufficiently practiced
      - In engine-out situations, situation awareness is an issue resulting in a high rate of unacceptable performance.
      - Surprise all engine go-arounds are a problem and should be incorporated into training situations.
      - Descent and automation planning are problematic and precipitate unanticipated situations.
    - Summary Surprises need to be incorporated in training particularly with respect to automation and engine failure situations both from a proactive and reactive perspective.

	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	During ATQP implementation period, inadvertent mis-selections appear to occur most during operations that are not routinely practised	All	34	34	ATQP airline	Error	Error Mgt Surprise	Mis-Sys Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge
1	vi. Single Engine NPA 1. Just over 1% failed 2. 5% were procedural errors, 32% Automation, 4. 2% situational awareness. 5. 5% were handling errors	APR	34	34	ATQP airline	Manual AC Control Automation	System Malfunction Manual AC Control Automation	Eng Fail Syst mal Compliance CRM Mis-Sys Mis A/C State	SA Problem Solving Decisio Making Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
1	vii. SE Go-Around         1. Approximately 2% failed or only passed after a repeat         2. Of the repeats         a. just over 4% were procedural errors,         b. just over 4% handling         3. Of the failed a         a. Ye Automation and a 2% situational awareness.         b. Approx 1/3 were procedural errors and ½ handling.	GA	34	34	ATQP airline	Manual AC Control Automation GA	Go Arounds Automation Error Mgt	Eng Fail Compliance CRM Mis-AFS Mis A/C State	SA Application of Procedures/Knowledge Flight Management and Guidance Manual Aircraft Control
1	III. Procedures not routinely flown, 2 Eng G/A, EFATO, SE NPA and SE G/A appear to present the greatest difficulty to crew, with procedural error and Manual/ACControl being the biggest factors.	TO GA	34	34	ATQP airline	Manual AC Control GA	Go Arounds System Malfunction Error Mgt Surprise	Eng Fail Syst mal Compliance CRM Mis A/C State	Application of Procedures/Knowledge Manual Aircraft Control
1	2 Eng G/A should be scheduled into recurrent training.	GA	34	34	ATQP airline	GA Manual AC Control	Go Arounds Surprise	Mis A/C State	Application of Procedures/Knowledge Flight Management Guidance and Automation Manual Aircraft Control
1	Training in energy Management and environmental descent planning needs to be more specific.	DES	34	34	ATQP airline	Unstable APR	Error Mgt Unstable APP	Mis A/C State	Problem Solving Decision Making SA

Figure 4.2.4.2.7 – Surprise/ATQP

#### 4.2.4.2.8 Leadership

- Filter Evidence Table Source ATQP
- Filter Topics for [Leadership] combine with
- Filter Competencies [Decision Making]
- Suppress superfluous
  - See Figure 4.2.4.2.8
    - Result ATQP Study Leadership
      - Many unstable approaches result from accepting inappropriate ATC clearances.
      - Effective training encourages and enhances leadership, and this is demonstrated by improved leadership and workload management performance grades data in training, in addition to better adherence to company criteria in operations.
    - Summary ATQP training and operational data provide encouraging results showing that leadership showed remarkable improvement in training as well as better performance on the line.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
93	Accepting ATC vectors or speed control.     Turning too tight when visual,     FMGS mis-selections,     4. Energy Management     Lack of proficiency when manually flying instrument	APR	34	34	ATQP airline	Unstable APR/GA	Unstable APP	ATC Mis A/C State Mis- AFS	SA Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
96	During ATQP implementation period, the number of APProaches not meeting company criteria at 1000 ft has significantly reduced.	APR	3 4	34	ATQP airline	Unstable APR	Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
109	Data shows that leadership and workload mgt can be taught / learned. 7% to 2%.	All	34	34	ATQP airline	Leadership	Leadership	Workload Distraction	Leadership and Teamwork Workload Management







#### 4.2.4.2.9 Mismanaged Aircraft State

- Filter Evidence Table Source ATQP
- Filter Factors [Mis A/C State]
- Suppress superfluous
  - See Figure 4.2.4.2.9
  - Result ATQP Study Mismanaged Aircraft State
    - Unstable approaches accounted for 50% of go-arounds in operations
    - 10% of go-arounds resulted in flap over-speed.
    - 10% of go-arounds resulted in SOP violations.
    - Mismanaged autoflight is cited as cause of most problems during go-around execution.
    - Implementation of ATQP reduced the rate of unstable approaches in operations.
    - Training in descent planning and energy management are needed to reduce mismanaged aircraft states.
  - Summary Studies during ATQP highlight the need for specific training in planning and energy management to reduce mismanaged aircraft states. Go-arounds continue to be mismanaged and 50% of them result from mismanaged approaches. During the go-around, mismanaged autoflight continues to result in mismanaged aircraft states including flap over-speeds and SOP violations.

E ret	F Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
92	During ATQP implementation period G/A's from Unstable Appes account for approximately 1/2 of all G/A's	APR GA	34	34	ATQP airline	Unstable APR/GA Compliance	Go Arounds Unstable APP	Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
95	During ATQP implementation period (Missed Approach) 1. Approximately 1/10 G/A's failed to comply with SOP's and just over 1/10 G/A's resulted in a flap over speed. 2. There has been no significant change in G/A rates 3. Flight Management remains the biggest cause	APR GA	34	34	ATQP airline	GA	Go Arounds	Compliance CRM Mis-AFS Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation
96	During ATQP implementation period, the number of APProaches not meeting company criteria at 1000 ft has significantly reduced.	APR	34	34	ATQP airline	Unstable APR	Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
##	Engine Failure on TO: 1. Approx 1/5 failed or only passed with a repeat 2. Almost ½ were procedural errors 3. 1% related to SA or Decisions making.	то	34	34	ATQP airline	ManualACControl	System Malfunction	Eng Fail System Malfunction Compliance CRM Mis-Sys	SA Problem Solving Decision Making Application of Procedures/Knowledge
##	Training in energy Management and environmental descent planning needs to be more specific.	DES	34	34	ATQP airline	Unstable APR	Error Mgt Unstable APP	Mis A/C State	Problem Solving Decision Making SA

Figure 4.2.4.2.9 – Mismanaged Aircraft State/ATQP

#### 4.2.4.2.10 Phase of Flight

- Filter Evidence Table Source ATQP
- Suppress Flight Phase [All]
  - See Figure 4.2.4.2.10
  - Result ATQP Study Phases of Flight
    - Unstable approaches accounted for 50% of go-arounds in operations
    - 10% of go-arounds resulted in flap over-speed.
    - 10% of go-arounds resulted in SOP violations.
    - Mismanaged autoflight is cited as cause of most problems during go-around execution.
    - Implementation of ATQP reduced the rate of unstable approaches in operations.
    - Training in descent planning and energy management is needed to reduce mismanaged aircraft states.
    - The descent phase is often mismanaged.
    - "Engine failures between V1 and V2" is the maneuver with the highest rate of unacceptable performance, 50% of failures involving procedural errors.
  - Summary APP, TO and GA appear most in the ATQP data as expected in training courses. DES is noted because of planning and energy management problems. Autoflight accounts for most of the problems in the go-around because of the dynamic nature of the phase.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
92	During ATQP implementation period G/As fm Unstable Apprs acount for approximately 1/2 of all G/As	APR GA	34	34	ATQP airline	Unstable APR/GA Compliance	Go Arounds Unstable APP	Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
93	Factors contributing to Unstable Apprs are: 1 Accepting ATC vectors or speed control 2 Turning too tight when visual 3 FMCS mis-selections 4 Energy Management 5 Lack of proficiency when manually flying instrument approaches	APR	34	34	ATQP airline	Unstable APR/GA	Unstable APP	ATC Mis A/C State Mis-AFS	SA Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
95	During ATQP implementation period (Missed Approach): 1 Approximately 1/10 G/As failed to comply with SOPs and just over 1/10 G/As resulted in a flap over speed 2 There has been no significant change in G/A rates 3 Flight Management remains the biggest cause	APR GA	34	34	ATQP airline	GA	Go-Arounds	Compliance CRM Mis-AFS Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation
96	During ATQP implementation period, the number of Approaches not meeting company criteria at 1000ft has significantly reduced.	APR	34	34	ATQP airline	Unstable APR	Go-Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
100	Engine Failure on TO: 1 Approximately 1/5 failed or only passed with a repeat 2 Almost 1/2 were procedural errors 3 1% related to SA or Decision Making	то	34	34	ATQP airline	Manual AC Control	System Malfunction	Eng Fail Syst mal Compliance CRM Mis-Sys	SA Problem Solving Decision Making Application of Procedures/Knowledge
101	<ul> <li>V. Single Engine NPA:</li> <li>1 Ajust over 1% failed</li> <li>2 5% were procedural errors</li> <li>3 2% Automation</li> <li>4 2% Situational Awareness</li> <li>5 5% were handling errors</li> </ul>	APR	34	34	ATQP airline	Manual AC Control Automation	System Malfunction Manual AC Control Automation	Eng Fail Syst mal Compliance CRM Mis-Sys Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance Automation Manual Aircraft Control
104	Procedures not routinely flown, 2 Eng G/A, EFATO, SE NPA and SE G/A flown with Automation the error rate is reduced.	TO GA	34	34	ATQP airline	Manual AC Control Automation GA	Manual AC Control	Workload Distraction	Problem Solving Decision Making Manual Aircraft Control
107	Training in energy Management and environmental descent planning needs to be more specific.	DES	34	34	ATQP airline	Unstable APR	Error Mgt Unstable APP	Mis A/C State	Problem Solving Decision Making SA

Figure 4.2.4.2.10 – Phase of Flight/ATQP





#### 4.2.4.2.11 Training Effect

- Filter Evidence Table Source ATQP
- Filter Keyword [Training]
  - See Figure 4.2.4.2.11
  - Result ATQP Study Training Effect
    - Training in dynamic use of autoflight (mode transitions) will improve go-around performance.
    - ATQP type course implementation reduces unstable approaches.
    - Mismanaged autoflight is cited as cause of most problems during go-around execution.
    - Training in descent planning and energy management are needed to reduce mismanaged aircraft states.
    - ATQP data show that leadership can be effectively be improved through training.
    - "Engine failures between V1 and V2" is the maneuver with the highest rate of unacceptable performance, 50% of failures involving procedural errors.
  - Summary Data gathered from operations and training show that ATQP type training is effective in improving crew performance, reducing the rate of unstable approaches in addition to improving leadership. It also shows a need for specific training dedicated to planning and energy management, as well as autoflight training in highly dynamic and unexpected situations.

n n	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
ç	During ATQP implementation period (Missed Approach) 1. Approximately 1/10 G/A's failed to comply with SOP's and just 5 over 1/10 G/A's resulted in a flap over speed. 2. There has been no significant change in G/A rates 3. Flight Management remains the biggest cause	APR GA	34	34	ATQP airline	GA Training	Go Arounds	Compliance CRM Mis-AFS Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation
ç	6 During ATQP implementation period, the number of APProaches not meeting company criteria at 1000 ft has significantly reduced.	APR	34	34	ATQP airline	Unstable APR Training	Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
ç	8 appear to occur most during operations that are not routinely practised	All	34	34	ATQP airline	Error management Training	Error Mgt Surprise	Mis-Sys Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge
#	Procedures not routinely flown, 2 Eng G/A, EFATO, SE NPA and SE G/A flown with Automation the error rate is reduced.	TO GA	34	34	ATQP airline	Manual AC Control Automation GA Training	Manual AC Control	Workload Distraction	Problem Solving Decision Making Manual Aircraft Control
#	Training in energy Management and environmental descent planning needs to be more specific.	DES	34	34	ATQP airline	Unstable APR Training	Error Mgt Unstable APP	Mis A/C State	Problem Solving Decision Making SA
#	Data shows that leadership and workload mgt can be taught / learned. 7% to 2%.	All	34	34	ATQP airline	Leadership Training	Leadership	Workload Distraction	Leadership and Teamwork Workload Management

Figure 4.2.4.2.11 – Training Effect/ATQP

# 4.2.5 Pilot Survey

#### 4.2.5.1 Unstable Approaches

- Filter Evidence Table Pilot Survey
- Filter Topics [Unstable Approach]
- See Figure 4.2.5.1
  - Result Pilot Survey Unstable Approach
    - The major reason pilots do not execute go-arounds from unstable approaches is that they believe that it is safe to land. [82%].
    - 37% of respondents admit to a psychological barrier, as go-arounds are rare. This is a selfperpetuating effect.
    - 35% of respondents cite operational inconvenience while 24% admit that a go-around is professionally embarrassing.
    - 17% of respondents admit to being unfamiliar with the SOP criteria for stable approaches.
    - According to the survey results, unstable approach rates are less than 5%. This is consistent with LOSA and FDA results.
  - Summary The pilot survey shows that unstable approaches are a consistent problem, with rates similar to those from LOSA and FDA data. The fact that pilots believe that they can and in most case do make a successful landing when unstable reinforces the continuation of this problem. (82% cite belief that landing can be safely made even though approach is not stable.) Other reasons that pilots continue to land are that they admit to a psychological barrier inhibiting a go-around (37%); it is operationally inconvenient (35%); it is professionally embarrassing (24%); 17% admit that they are unfamiliar with the stable approach criteria and others simply do not want to write the mandatory report. From this information it is clear that there are issues of knowledge, skills and particularly attitudes that foster an unstable approach culture, which needs to be treated on several levels, one certainly being training.

Î	E ref	Evidence Statement	Flight Phas	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	257	Neither pilot suggesting a go-around implies pilots are making it work by applying judgment.	APR	234	All	Survey		Go Arounds Unstable APP	Compliance CRM Mis A/C State	Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
	258	Reasons pilots give for not going-around from an Unstable App: 1. Pilot judgment that landing is still safe even though the approach is unstable (82%) 2. There is a psychological barrier because go-arounds are rare (37%) 3. Operational inconvenience (35%) 4. Embarrassment (24%) 5. Unfamiliar with criteria (17%) 6. Mandates a report	APR LDG GA	234	All	Survey	GA	Go Arounds Leadership Unstable APP	Compliance CRM Mis A/C State	Knowledge Flight Management Guidance/Automation Problem Solving Decision Making Application of Procedures/Knowledge Leadership and Teamwork
	268	Unstalble approach deviations are infrequent but consistent	ALL	234	All	Survey	Unstable APR/GA Error	Unstable APP	Mis A/C State	SA Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
	269	Unstable approach rate calculated from Pilot Survey Reponse is consistent with LOSA and FDA rates and Survey.	APR	234	All	Survey	Unstable APR	Unstable APP	Mis A/C State	All

Figure 4.2.5.1 – Unstable Approaches/Pilot Survey





## 4.2.5.2 Automation

- Filter Evidence Table Pilot Survey
- Filter Topics [Automation]
  - See Figure 4.2.5.2b
  - Result Pilot Survey Automation
    - Pilots were asked about whether they had difficulty on type after initial training. They
      responded accordingly:
      - 25% felt prepared
      - 14% had one encounter where they felt unprepared
      - 61% had multiple encounters where they felt unprepared.



56%

Frequently



- Only about 50% felt the FMS training adequate during initial training.

14%

- Only 15% felt comfortable operating the FMS after the type rating course.
- 62% felt that operational training of the FMS was insufficient, the acquisition of operational capability and comfort with the FMS typically being achieved only after 1 year of line experience.



Figure 4.2.5.2a

- When surveying pilots regarding how FMS training could be improved, the majority felt that automation surprises were the most important followed by hands on use in operational situations.
- One third felt that training needed to be improved in transitioning between the various modes of autoflight.
- The only part of automation training not heavily criticized was the functional aspect, such as basic knowledge of the system and programming.
- An analysis of survey comments ranked flight management 3<sup>rd</sup> in pilot discomfort in line operations
- Summary The pilot survey was heavily critical of automation training during the initial type rating. Only 25% of the pilots felt prepared to utilize the automation when released to line operations. In reality 61% had multiple encounters on the line during their first 6 months of flying where they reported being involved in uncomfortable situations. Over 60% felt that the operational aspect of FMS training was missing during training requiring them to learn to use the system effectively during the first year after training. When asked how the training could be improved, the majority felt that automation surprises was the most important issue followed by hands on use in operational situations; while about a third recommended better training in transitioning between levels. The prevailing sentiment was that the operational aspect of the FMS was seriously lacking in training, the focus being on the functional, such as basic knowledge and programming.



T	E	Evidence Statement	Flight	Gen	Applicability	Source	Keywords	Training	Factors	Competencies
	ref		Phase	Specific	to Gens	000.00	noynorae	Topics	1 401010	
		Difficulty with Automation in first 6 mos on type								
1	246	• 25% were prepared	All	234	34	Survey	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation
		14% had one encounter						Surprise		Knowledge
		61% had multiple encounters								
		<ul> <li>42 % of the Pilots believe that the training of the FMS on the type they are currently flying needs to be improved</li> </ul>								Fileband Onidana (Automation
1	247	Only 51% believed it was adequate	All	234	34	Survey	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation
		32% believed it was minimal								i interesse
ŀ		Only 15% of pilots felt "comfortable" operating the FMS After type								
		rating course,								Flight Managemen Guidance/Automation
	248	41% acquired comfort after 3 months of operation	All	234	34	Survey	Automation	Automation	MIS-AFS	Knowledge
		21% acquired comfort after 6 to 12 months of operation								
		Distribution of learning the operational use of the FMS :								
	240	In training: 38%	All	234	34	Survey	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation
	243	On the line: 42%								Knowledge
		Self study: 20%								
		62% acquired comfort during 3-12 months of line experience.								
	250	The results suggest that comfort in using the FMS develops over	All	234	34	Survey		Automation	Mis-AFS	Flight Management Guidance/Automation
		time with 3 months of line experience being the critical learning								Knowledge
ŀ		period for the respondents followed by 6 months, then one year.								
		operating the FMS after completion of their initial operating								Flight Management Guidance/Automation
	251	experience (IOE). The remaining 59% acquired comfort during the	All	234	34	Survey		Automation	Mis-AFS	Knowledge
		3 to 12 month period following completion of training								
		Pilots often report that the learning of the flight management								
	252	line-42%.	A II	224	24	Suprov		Automotion	MicAES	Flight Management Guidance/Automation
1	202	FMS learning from training—38%.	All	234	34	Survey		Automation	IVIIS-AFS	Knowledge
		<ul> <li>FMS learning through selfstudy—20%.</li> </ul>								
		Areas where FMS training can be improved in order of importance								
		per surveyed pilot opinion:								
		1. Automation surprises - 57.1%					A	A		Knowledge
	253	2. Hands on use in the operational situation – 52%	All	234	34	Survey	Criticality	Surprise	Mis-AFS	Flight Management Guidance/Automation
		3. Transitions between modes – 32.8%					Ontiodaity	Ourprise		Problem Solving Decision Making
		<ol> <li>Basic Knowledge of the system – 26.7%</li> </ol>								
		5. Programming – 21%								
		Training needs (per analyzed survey comments) in terms of pilot-								
		operational disconfort by order of priority: 1. Adverse weather 30%								
		2 Crew Resource Management 23%							Syst mal	
		3 Non-normal checklists 16%						WX	CRM	
	277	3 Flight management 15%	All	234	All	Survey	Criticality	Automation	Adverse WX	All
		A Airplane bandling 13%						INIAN A/C CTI	Mis AFS	
		5. Svetome 12%								
		6. Manauwara 10%								
1		o. Maneuvers 10%								

Figure 4.2.5.2b – Automation/Pilot Survey

#### 4.2.5.3 Error Management

- Filter Evidence Table Pilot Survey
- Filtered Topic [Error Mgt] combined with
- Filtered results Keywords [MonitorXchk]
- Suppress superfluous
  - See Figure 4.2.5.3b
    - Result Pilot Survey Error Management
      - Over 90% of pilots believe that detecting and managing errors is the most effective strategy concerning errors in the cockpit.
      - When asked, most pilots responded that monitoring and crosschecking is taught in training.
      - Survey shows that monitoring and crosschecking is poorest in the CLB phase because of complacency (48%) and too many secondary duties (30%).

# Research indicates monitoring and cross-checking is poorest during the climb phase

Figure 4.2.5.3

- Noncompliance is major problem in error management:
  - 21% of pilots admit to call out deviations on every flight.
  - 18% admit to checklist deviations frequently while 13% admit to deviations that are intentional.
- The level of assertiveness seems to be related to the level of the resulting intervention. Routine
  issues such as identifying a deviation in the flight path or proposing a checklist occur at a high
  percentage of the time while demanding a GA in an appropriate situation is considerably less
  likely to occur.

Response Categories	Distribution
Tell the pilot flying about a deviation	92%
Take control from the pilot flying	49%
Propose a checklist if the pilot flying delays asking for it	91%
Propose a go-around during an unstable approach	83%
Verbally demand a go-around if you think it is required	80%

Figure 4.2.5.3a



Summary – Almost all pilots believe that the most important strategy in error management is monitoring and crosschecking and that it is emphasized most of the time in training and taught explicitly about half of the time. There are, however, problems in error management that are not so well addressed. Non-compliance with procedures is too high, for example 21% of pilots admit to call out deviations on virtually every flight; cross checking is particularly bad in the CLB phase because of complacency and too many secondary duties. Intentional non-compliance on a fairly regular basis was reported by 13% of those surveyed. The issue of assertiveness was questioned and while the monitoring pilot almost always speaks up if there is a flight path deviation (90%), but less than half of the respondents (49%) reported that they would be willing to take control from the flying pilot.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
259	Pilot response to the question of whether monitoring and cross checking is taught in training: •47% explicitly •34% include it implicitly •15% marginally •4% not at all	All	234	All	Survey	MonitorXchk	Monitoring Xcheck	CRM	SA Application of Procedures/Knowledge
261	Survey implies that pilots believe that monitoring and cross-checking is the poorest during the CLIMB phase because of complanency (57%) and too many secondary duties (36%).	All	234	All	Survey	MonitorXchk	Monitoring Xcheck	CRM Workload Distraction	SA Application of Procedures/Knowledge Workload Management
262	90% of surveyed pilots believe that detecting and managiung errors is the most effective strategy concerning errors on the flight deck	All	234	All	Survey	Error Mgt	Error Mgt Monitoring Xcheck	CRM	SA Problem Solving Decision Making Knowledge
263	More than 2/3 of pilots report that they get a chance to practice approach briefings during training	CRZ APR	234	All	Survey	Error Mgt	Error Mgt	CRM	SA Application of Procedures/Knowledge Workload Management
266	18% if pilots admit to deviating from checklists frequently	All	234	All	Survey	Error Mgt Compliance	Error Mgt Leadership	Compliance CRM	Application of Procedures/Knowledge
267	Approximately 21% of the pilot respondents admit to call out deviations on virtually every flight. Approximately 28% of the pilot respondents admit to call out deviation on about every 10 flights.	All	234	All	Survey	Error Mgt Compliance	Error Mgt	Compliance CRM Workload Distraction	Leadership and Teamwork Application of Procedures/Knowledge
312	Pilots report high levels of assertiveness in 4 of 5 categories, with taking control from the pilot flying registering the lowest at 49%. The level of assertiveness appears to be linked to the level of resulting intervention. Tasks such as identifying a deviation (92%) or proposing a checklist (91%) are more likely to be asserted than tasks such as proposing a GA (83%) or demanding a GA (80%).	APR LDG GA	All	All	Survey	GA Descision Making Assertiveness	Leadership Error Mgt Monitoring Xcheck Go Arounds	Compliance CRM	Communication Leadership and Teamwork Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
314	Most pilots (93%) believe detecting and managing errors is the most effective strategy for error management (Figure ). A small percentage of pilots (7%) believe that errors should not be committed.	All	All	All	Survey	MonitoringXchecking Error Mgt	Monitoring Xcheck		Leadership and Teamwork Application of Procedures/Knowledge
316	Intentional deviations from checklists occurred a reported every ten flights by 13% of the respondents, a few times a year by 30% of the respondents, and once a year by 36% of the respondents. Very few (4%) reported a deviation on every flight. Checklist deviations occurring at this high of a rate suggest other factors may be involved not related to compliance.	All	All	All	Survey	Compliance Error Mgt	Error Mgt Leadership	Compliance CRM	Application of Procedures/Knowledge

Figure 4.2.5.3b - Error Management/Pilot Survey

#### 4.2.5.4 Manual Aircraft Control

- Filter Evidence Table Pilot Survey
- Filtered result for Topics [Man A/C Ctl]
  - o See Figure 4.2.5.4a
  - Result Pilot Survey Manual A/C Control
    - Aircraft handling ranked 5<sup>th</sup> (13%) and maneuver training ranked 7<sup>th</sup> (10%) in the comments regarding training needs.



Figure 4.2.5.4 – Training Needs per Pilot Survey

Summary – The pilots were allowed to make whatever comments on any training subject and these comments were subsequently analyzed and added to the results from the formal survey questions. There were a significant number of comments on training needs and these needs were prioritized according to the analysis of the comments. Two categories referred to manual aircraft control, manual handling and maneuvers. Together they indicated that pilots feel quite strongly that manual aircraft control is a high priority item in training.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
277	Training needs (per analyzed survey comments) in terms of pilot- operational disconfront by order of priority: 1. Adverse weather 30% 2. Crew Resource Management 23% 3. Non-normal checklists 16% 4. Fiight management 15% 5. Airplane handling 13% 6. Systems 12% 7. Maneuvers 10%	All	234	All	Survey	Criticality	WX Automation Man A/C Control	Syst mal CRM Adverse WX Manual AC Control Mis AFS	All

Figure 4 2 5 4a -	Manual Aircraf	t Control/Pilot	Survey
1 iyule 4.2.3.4a –	Manual Ancial		Survey



## 4.2.5.5 Go Around

- Filter Evidence Table Pilot Survey
- Filter Topic [GA]
  - See Figure 4.2.5.5
  - Result Pilot Survey Go-Around
    - In over 70% of the cases where a go-around should have been performed neither pilot even suggested a go around.
    - When a go-around was suggested by the PM, in 30% of the cases the PF continued to land; in most of these cases the PF was the captain.
    - The reasons that pilots gave in the survey for not going around in order of importance are:
      - Pilot judged landing would be safe (82%).
      - Psychological barrier because go-around's are rare (37%).
      - Operationally inconvenient (35%).
      - Embarrassing (24%).
      - Not familiar with SOP criteria requiring a go-around (17%).
      - Mandates a report (10%).
    - While pilots tend to report high levels of assertiveness in the survey, taking over control in a situation such as when the PF does not go-around appropriately is judged the least likely to occur.
  - Summary The survey shows as pilots readily admit that they are not going around per the airline SOP. The reason most often cited is a feeling that the landing can be successful despite the unstable condition. In the majority of the cases the prospect of a go-around is not discussed during an unstable approach. Pilots report a psychological barrier to performing a go-around.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
254	In cases where Go-arounds should have been performed: • 71% of the cases neither pilot suggested a go-around	All	234	All	Survey	GA	Go Arounds Leadership Compliance	Compliance CRM Mis A/C State	Flight Management Guidance/Automation Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
255	In almost 30% of the cases when a Go-around was suggested the other pilot disagreed (Influenced by rank)	APR	234	All	Survey		Go Arounds Leadership	Compliance CRM Mis A/C State	Problem Solvin Decision Making Knowledge Application of Procedures/Knowledge
256	Psychological barriers to a go around suggests more practice in training may be beneficial, especially for all engine scenarios	APR	234	All	Survey	Criticality	Go Arounds Leadership	Compliance CRM Mis A/C State	All
257	Neither pilot suggesting a go-around implies pilots are making it work by applying judgment.	APR	234	All	Survey		Go Arounds Unstable APP	Compliance CRM	Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
258	Reasons pilots give for not going-around from an Unstable App: 1. Pilot judgment that landing is still safe even though the approach is unstable (82%) 2. There is a psychological barrier because go-arounds are rare (37%) 3. Operational inconvenience (35%) 4. Embarrassment (24%) 5. Unfamiliar with criteria (17%) 6. Mandates a report	APR LDG GA	234	All	Survey	GA Descision making Complaince	Go Arounds Leadership Unstable APP	Compliance CRM Mis A/C State	Flight Management Guidance/Automation Problem Solving Decision Making Knowledge Application of Procedures/Knowledge Leadership and Teamwork
311	Go-Around Maneuvers: 1. I suggested a go-around, but the other pilot disagreed (20%). 2. The other pilot suggested a go-around, but I disagreed (8%). 3. Neither pilot suggested a go-around (72%).	APR LDG GA	All	All	Survey	GA Descision making Compliance	Go Arounds Surprise	Compliance CRM	Communication Leadership
312	Pilots report high levels of assertiveness in 4 of the 5 categories, with taking control from the pilot flying registering the lowest at 49%. The level of assertiveness appears to be linked to the level of resulting intervention. Tasks such as identifying a deviation (92%) or proposing a checklist (91%) are more likely to be asserted than tasks such as proposing a GA (83%) or demanding a GA (80%).	APR LDG GA	All	All	Survey	GA Descision making Assertiveness	Leadership Error Mgt MonitorXcheck Go Arounds	Compliance CRM	Communication Leadership Problem Solving Decision Making Knowledge Application of Procedures/Knowledge

Figure 4.2.5.5 – Go Around/Pilot Survey



## 4.2.5.6 Weather

- Filter Evidence Table Pilot Survey
- Filter Topic [WX]
  - See Figure 4.2.5.6
  - Result Pilot Survey WX
    - In the analysis of training needs conducted from the voluntary comments by the pilots, WX ranked as the number 1 training need (30% of the comments). (See Fig 4.2.5.4)
  - Summary The survey showed that in the opinion of the pilots, WX is the most important training need. This result came from the analysis of voluntary comments made by the pilots.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
277	Training needs (per analyzed survey comments) in terms of pilot- operational discomfort by order of priority: 1. Adverse weather 30% 2. Crew Resource Management 23% 3. Non-normal checklists 16% 4. Flight management 15% 5. Airplane handling 13% 6. Systems 12% 7. Maneuvers 10%	All	234	All	Survey	Criticality	WX Automation Manual AC Control	System Malfunction CRM Adverse WX Manual AC Control Mis AFS	All

Figure 4.2.5.6 - Weather/Pilot Survey

# 4.2.5.7 System Malfunction

- Filter Evidence Table Pilot Survey
- Filter Factor [Sys Mal]
  - o See Figure 4.2.5.6
  - Result Pilot Survey Sys Mal
    - In the analysis of training needs conducted from the voluntary comments by the pilots, Non-Normal checklists for system malfunctions ranked as the number 3 training need (16% of the comments). (See Graphic 4.2.5.4)
  - Summary The survey showed that in the opinion of the pilots, Sys Mal is an important training need in terms of the non-normal checklists (ranked 3<sup>rd</sup>). This result came from the analysis of voluntary comments made by the pilots.





## 4.2.5.8 Surprise

- Filter Evidence Table Pilot Survey
- Filter Topic [Surprise]
  - See Figure 4.2.5.8b
  - Result Pilot Survey Surprise
    - 75% of the survey respondents said that they had one or more FMS encounters in their first six months for which they were unprepared.



Figure 4.2.5.8

- When asked about areas for FMS training improvement, the number one issue reported was Automation Surprises (57.1%).
- 54% of the pilots (includes experienced pilots) said that they had at least one operational situation for which they were unprepared.



Figure 4.2.5.8a

Summary – A high percentage of pilots found themselves in a 'surprise' situation after initial training. These uncomfortable situations continued despite experience on type. Automation surprises are particularly problematic as the majority of respondents report this issue as the number 1 topic for automation training improvement. It is clear from what the pilots are saying that current training does not deal adequately with unexpected operational situations.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
246	Difficulty with Automation in first 6 months on type: - 25% were prepared - 14% had one encounter - 61% had multiple encounters	All	234	34	Survey	Automation	Automation Surprise	Mis-AFS	Flight Management Guidance/Automation Knowledge
253	Areas where FMS training can be improved in order of importance per surveyed pilot opinion: 1 Automation surprises - 57.1% 2 Hands on use in the operational situation - 52% 3 Transitions between modes - 32.8% 4 Basic knowledge of the system - 26.7% 5 Programing - 21%	All	234	34	Survey	Automation Criticality	Automation Surprise	Mis-AFS	Knowledge Flight Management Guidance/Automation Problem Solving Decision Making
271	54% of pilots encountered an operational situation in the past 6 months in which they were not comfortable - of the Yes category: - 57% are Captains - 43% are FOs	All	234	34	Survey	Criticality	Surprise	Mis-AFS Mis A/C State Mis-Sys	Knowledge Problem Solving Decision Making

Figure 4.2.5.8b - Surprise/Pilot Survey

## 4.2.5.9 Compliance

- Filter Evidence Table Pilot Survey
- Filtered Topic [Compliance] combined with
- Filtered Keyword [Compliance]
  - See Figure 4.2.5.9
  - Result Pilot Survey Compliance
    - In cases where pilots admit that a go-around should have been performed, 71% of the respondents advised that neither pilot mentioned a go-around.
    - 18% of pilots admit that they deviate from checklists frequently.
    - 21% of pilots admit to call out Intentional deviations on virtually every flight.
    - 13% of pilots admit to intentional deviations on a frequent basis.
  - Summary The pilot survey is probably most revealing in the subject of compliance. If what LOSA postulates is true i.e., that the error rate is multiplicative when noncompliance is involved, then the following statistics speak for themselves:
    - 21% of pilots admit to call out Intentional deviations on virtually every flight.
    - 13% if pilots admit to intentional deviations from checklists on a frequent basis.
    - In a go around situation 71% of time neither pilot mentioned a go-around.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
254	In cases where Go-arounds should have been performed: • 71% of the cases neither pilot suggested a go-around	All	234	All	Survey	GA	Go Arounds Leadership Compliance	Compliance CRM Mis A/C State	Flight Management Guidance/Automation Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
266	18% if pilots admit to deviating from checklists frequently	All	234	All	Survey	Error Mgt Compliance	Error Mgt Leadership	Compliance CRM	Application of Procedures/Knowledge
267	Approximately 21% of the pilot respondents admit to call out deviations on virtually every flight. Approximately 28% of the pilot respondents admit to call out deviation on about every 10 flights.	All	234	All	Survey	Error Compliance	Error Mgt	Compliance CRM Workload	Leadership and Teamwork Application of Procedures/Knowledge
311	Go-Around Maneuvers: 1. I suggested a go-around, but the other pilot disagreed (20%). 2. The other pilot suggested a go-around, but I disagreed (8%). 3. Neither pilot suggested a go-around (72%).	APR LDG GA	All	All	Survey	GA Descision making Compliance	Go Arounds Surprise	Compliance CRM Workload	Communication Leadership and Teamwork
315	Intentional deviations from checklists occurred a reported every ten flights by 13% of the respondents, a few times a year by 30% of the respondents, and once a year by 36% of the respondents. Very few (4%) reported a deviation on every flight. Checklist deviations occurring at this high of a rate suggest other factors may be involved not related to compliance.	All	All	All	Survey	Compliance Error Mgt	Error Mgt Leadership	Compliance CRM Workload	Application of Procedures/Knowledge

Figure 4.2.5.9 - Compliance/Pilot Survey

## 4.2.5.10 Leadership

- Filter Evidence Table Pilot Survey
- Filtered result for Topic [Leadership]
  - See Figure 4.2.5.10
  - Result Pilot Survey leadership
    - In cases where a GA should have been performed, 71% of the times neither pilot mentioned GA.
    - Approach briefings is concluded and conducted in training but an analysis of pilot comments indicate that content is not well understood and practiced.
    - Pilots deviate frequently (18% of the time) from checklists and most often the deviation is intentional.
    - A majority of respondent would deviate from SOPs if it would improve safety.
  - Summary The pilot survey provided both encouraging and discouraging results with regard to leadership. On the one hand most pilots are willing to make appropriate decisions to promote safety. However, there is too often a casual attitude indicated by significant intentional disregard for procedural compliance.

E	ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
4	254	In cases where Go-arounds should have been performed:	All	234	All	Survey	GA	Go Arounds Leadership Compliance	Compliance CRM Mis A/C State	Flight Management Guidance/Automation Problem Solving Decision Making Knowledge
	264	The approach briefing is included and conducted in training. However based on comments, appropriate briefing content may not be known or practiced.	APR	234	All	Survey		Leadership	CRM	Application of Procedures/Knowledge Communication Application of Procedures/Knowledge
2	266	18% if pilots admit to deviating from checklists frequently	All	234	All	Survey	Error Compliance	Error Mgt Leadership	Compliance CRM	Application of Procedures/Knowledge
3	312	Pilots report high levels of assertiveness in 4 of the 5 categories, with taking control from the pilot flying registering the lowest at 49%. The level of assertiveness appears to be linked to the level of resulting intervention. Tasks such as identifying a deviation (92%) or proposing a checklist (91%) are more likely to be asserted than tasks such as proposing a GA (83%) or demanding a GA (80%).	APR LDG GA	All	All	Survey	GA Descision making Assertiveness	Leadership Error Mgt MonitorXcheck Go Arounds	Compliance CRM	Communication Leadership Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
~	314	A majority of the respondents (53%) would deviate if they believe it increases safety and twenty nine percent would deviate if it resulted in no reduction in safety. Overall, most (83%) pilots would exercise judgment to intentionally deviate from company SOPs with their judgment being the pilot's assessment of safety. Another seven percent reported they would never deviate.	All	All	All	Survey	Compliance Error	Error Mgt Leadership	Compliance CRM	SA Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
e,	315	Intentional deviations from checklists occurred a reported every ten flights by 13% of the respondents, a few times a year by 30% of the respondents, and once a year by 36% of the respondents. Very few (4%) reported a deviation on every flight. Checklist deviations occurring at this high of a rate suggest other factors may be involved not related to compliance.	All	All	All	Survey	Compliance Error	Error Mgt Leadership	Compliance CRM	Application of Procedures/Knowledge

Figure 4.2.5.10 – Leadership/Pilot Survey

## 4.2.5.11 Mismanaged Aircraft State

- Filter Evidence Table Pilot Survey
- Filtered result for Factors [Mis A/C State]
  - See Figure 4.2.5.11
  - Result Pilot Survey Mismanaged Aircraft State
    - Pilots rarely go around from a mismanaged approach and most often the reason is that they believe and do perform a successful landing.
    - Unstable approaches seem to remain consistent over time as indicated by various data sources.
    - The majority of pilot respondents in the survey indicated that they encountered an aircraftoperating situation in which they were not comfortable.
  - Summary The survey asked questions regarding a specific mismanaged aircraft state, the unstable approach. This provided considerable reinforcement of results from other data sources. In the 6 months prior to responding, pilots detailed other situations they found uncomfortable and had difficulty managing.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
258	Reasons pilots give for not going-around from an Unstable App: 1. Pilot judgment that landing is still safe even though the approach is unstable (82%) 2. There is a psychological barrier because go-arounds are rare (37%) 3. Operational inconvenience (35%) 4. Embarrassment (24%) 5. Unfamiliar with criteria (17%) 6. Mandates a report	APP LDG GA	234	All	Survey	GA Descision making Complaince	Go Around Leadership Unstable APP	Compliance CRM Mis A/C State	Knowledge Flight Management Guidance/Automation Problem Solving Decision Making Knowledge Application of Procedures/Knowledge Leadership and Teamwork
268	Unstalble approach deviations are infrequent but consistent	ALL	234	All	Survey	Unstable APR/GA Error	Unstable APP	Mis A/C State	SA Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
269	Unstable approach rate calculated from Pilot Survey Reponse is consistent with LOSA and FDA rates and Survey.	APR	234	All	Survey	unstable apr	Unstable APP	Mis A/C State	All
271	Unstable approach rate calculated from Pilot Survey Reponse is consistent with LOSA and FDA rates and Survey.	APR	234	All	Survey	unstable apr	Unstable APP	Mis A/C State	All

Figure 4.2.5.11 – Mismanaged Aircraft State/Pilot Survey





## 4.2.5.12 Training Effect

- Filter Evidence Table Pilot Survey
- Filtered Keywords [Criticality]
  - See Figure 4.2.5.12
  - Result Pilot Survey Training Effect
    - Psychological barriers to a go around suggest more practice in training may be beneficial, especially for all engine scenarios.
    - Training must address the operational as well as the functional as such need is exemplified by the fact that the majority of pilots face operational situations on a frequent basis that they feel ill equipped to address.
    - According to pilot comments the topics in priority that need to be addressed in training is similar to the rankings found in other data sources e.g., weather, system malfunctions, automation and manual aircraft control.
  - Summary The pilot survey highlighted some important topics for which training is needed. Pilots indicated the need for more training in go-arounds from various altitudes especially with all engines operating. Training also needs to be more operational in nature to deal with the shortfalls commented on by the survey respondents. In addition, the ranking of topics where effective training is needed parallels the priorities established by other data analyses in the EBT data study.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
253	Areas where FMS training can be improved in order of importance per surveyed pilot opinion: 1. Automation surprises - 57.1% 2. Hands on use in the operational situation - 52% 3. Transitions between modes - 32.8% 4. Basic Knowledge of the system - 26.7% 5. Programming - 21%	ALL	234	34	Survey	Automation Criticality	Automation Surprise	Mis-AFS	Knowledge Flight Management Guidance/Automation Problem Solving Decision Making Knowledge
256	Psychological barriers to a go around suggests more practice in training may be beneficial, especially for all engine scenarios	APP	234	All	Survey	Criticality	Go Around Leadership	Compliance CRM Mis A/C State	All
271	Unstable approach rate calculated from Pilot Survey Reponse is consistent with LOSA and FDA rates and Survey.	APP	234	All	Survey	Unstable APR/GA Criticality	Unstable APP	Mis A/C State	All
272	54% had a negative experience in training in the last 5 years	ALL	234	All	Survey	Criticality			
276	Training is multi-dimensional. All dimensions must be addressed for improvement to be successful and sustainable: • Content (operational and functional) • Delivery methods and tools • Airline Culture	ALL	234	All	Survey	Criticality			
277	Training needs (per analyzed survey comments) in terms of pilot-operational discomfort by order of priority: 1. Adverse weather 30% 2. Crew Resource Management 23% 3. Non-normal checklists 16% 4. Flight management 15% 5. Airplane handling 13% 6. Systems 12% 7. Maneuvers 10%	ALL	234	All	Survey	Criticality	WX Automation Manual AC Control	Syst mal CRM WX Manual AC Ccontrol Mis AFS	All

Figure 4.2.5.12 – raining Effect/Pilot Survey

# 4.2.6 IATA Accident Reports 2008/2009

#### 4.2.6.1 Unstable Approaches

- Filter Evidence Table IATA Reports
- Filter Topics [Unstable Approaches]
- See Figure 4.2.6.1
  - Result IATA Reports Unstable Approaches
    - Failure to go-around is number 3 error at 11% in 2009 report.
    - IATA Accident Reports recommend introducing special training to reduce Unstable Approaches
  - Summary The IATA Accident Reports find unstable approaches to be a concern and a frequent error. The report recommends FTSD training in order to reduce the problem.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
74	Top errors Manual Handling (33%), SOP 30%, Fail to GA 11%	All	All	All	ACC IATA	Error	Manual AC Control Error Mgt Unstable APP Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control
85	Introduce Unstable App training in simulators	APR	All	All	ACC IATA Comments	Unstable APR/GA	Unstable APP	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge

Figure 4.2.6.1 – Unstable Approaches/IATA Accident Reports

## 4.2.6.2 Automation

- Filter Evidence Table IATA Reports
  - Filter Keywords for [Automation]
  - $\circ$  See Figure 4.2.6.2
    - Result IATA Reports Automation
      - IATA Accident reports fully support LOSA findings regarding Automation
      - Automation error countermeasure involves crosschecking.
      - Crews are reluctant to revert to manual aircraft control.
      - Gross error checks are necessary when imputing data into FMS.
    - Summary The IATA accident reports generally support the LOSA finding with regard to automation. Specifically, flight crews were found reluctant to revert to manual flying even when the situation required it. In addition, crosschecking is promoted to be the best countermeasure to mitigate automations errors and further finds that gross error checks should be made when imputing data into the FMS to trap errors easily made with this function.

l	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	72	IATA 29 ACC statistics: Flight Crew Errors fully in support of LOSA results (ManualACControl, compliance, failure to go-around, Automation)	All	All	All	ACC IATA	Manual AC Control Compliance Automation	Manual AC Control Go Arounds Automation	Compliance CRM Mis A/C State Mis- AFS	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control Flight Management Guidance/Automation
	77	Countermeasures include monitoring / cross-checking and Automation mgt	All	All	All	ACC IATA	Monitoring Xcheck Automation	Error Mgt Automation Monitor Xchk	Mis-AFS CRM	SA Flight Management Guidance/Automation
	79	Flight Crews are becoming more reluctant to revert to manual flying when Automation fails.	All	All	34	ACC IATA Comments	Automation Manual AC Control	Manual AC Control Error Mgt Automation	CRM Mis-AFS Syst mal Mis A/C State	Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
	80	Gross error checks are required when inputting data in FMS.	All	All	34	ACC IATA Comments	Automation Error Management	Automation Error Mgt	CRM Mis-AFS	SA Flight Management Guidance/Automation

Figure 4.2.6.2 - Automation/IATA Accident Reports



## 4.2.6.3 Error Management

- Filter Evidence Table IATA Reports
- Filter Topics [Error Management]
  - See Figure 4.2.6.3
  - Result IATA Reports Error management
    - Top errors are Manual Aircraft Control followed by failure to GA.
    - Improved training could have prevented 23% of the accidents in IATA 2009 Accident Report.
    - Most important countermeasure in accident prevention is monitoring and crosschecking.
    - Specifically, gross error checks must be incorporated in imputing data into the FMS.
    - GA decision must be reinforced in training
    - Briefing must be adapted to the particular situation.
  - Summary Error management results from the IATA studies echo the LOSA findings. Error management is listed as being the most important countermeasure to accident prevention. In addition, training is recommended to reinforce go-around in appropriate situations. Manual aircraft handling is also cited as an area to be improved by training in addition to automation management i.e., flight path management. Other specific areas noted are gross error checks when inputting FMS data as well as dealing with pilot reluctance to revert to manual flying when appropriate.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
74	Top errors Manual Handling (33%), SOP 3%, Fail to GA 11%	All	All	All	ACC IATA	Error Management Training Effect	Manual AC Control Error Mgt Unstable APP Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control
76	For 23% of 29 accidents, training could have been effective in reducing the likelihood	All	All	All	ACC IATA	Error Management Training Effect	Error Mgt		
77	Countermeasures include monitoring / cross-checking and Automation mgt	All	All	All	ACC IATA	MonitoringXchecking Automation	Error Mgt Automation Monitoring Xcheck	Mis-AFS CRM	SA Flight Management Guidance/Automation
79	Flight Crews are becoming more reluctant to revert to manual flying when Automation fails.	All	All	34	ACC IATA Comments	Automation ManualACControl	Manual AC Control Error Mgt Automation	CRM Mis-AFS Syst mal Mis A/C State	Problem Solving Decision Making Flight Management Guidance/ Automation Manual Aircraft Control
80	Gross error checks are required when inputting data in FMS.	All	All	34	ACC IATA Comments	Automation Error Management	Automation Error Mgt	CRM Mis-AFS	SA Flight Management Guidance/Automation
81	Decision to GA needs to be reinforced in training for abnormal landings (existing training counterproductive to this objective 4)	LDG	All	All	ACC IATA Comments	Unstable APR/GA Compliance Training Effect	Go Arounds Landing Issues Error Mgt	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
84	g. Briefing should be adapted to the situation.	All	All	All	ACC IATA Comments	Error Management	Error Mgt	CRM	Communication SA

Figure 4.2.6.3 – Error management/IATA Accident Reports

# 4.2.6.4 Manual Aircraft Control

- Filter Evidence Table Sources IATA Reports
- Filter Topics [Manual Aircraft Control] combined with
- Filter Competencies [Manual Aircraft Control]
  - See Figure 4.2.6.4
  - Result IATA Reports Manual Aircraft Control
    - The IATA accident reports support LOSA's conclusion that manual aircraft control skills are critical, and is the top reported error at 33%.
    - The top UAS is improper landing.
    - The report recommends the reinforcement of manual aircraft control skills in training.
    - Pilots of highly automated aircraft are reluctant to revert to manual flight.
    - Go-arounds are problematic, a contributory factor being poor manual aircraft control.
  - Summary The IATA report recommends reinforcing manual aircraft control skills through training and notes that crews are reluctant to revert to manual flying from automation. Poor manual aircraft control ranks as the number 1 error in their accident reports. The report cites problems during landing in addition to go-arounds.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
72	IATA 29 ACC statistics: Flight Crew Errors fully in support of LOSA results (ManualACControl, compliance, failure to go-around, Automation)	All	All	All	ACC IATA	ManualACControl Compliance Automation	Manual AC Control Go Arounds Automation	Compliance CRM Mis A/C State Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control Flight Management Guidance/Automation
74	Top errors Manual Handling (33%), SOP 3%, Fail to GA 11%	All	All	All	ACC IATA	Error Management	Manual AC Control Error Mgt Unstable/ Approaches Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control
75	Top UAS: improper landing 21%	LDG	All	All	ACC IATA	Error Management ManualACControl UAS	Landing Issues	Rwy/Taxi condition Mis A/C State	Problem Solving Decision Making Manual Aircraft Control
78	ManualACControl needs to be reinforced in Training	All	All		ACC IATA Comments	ManualACControl	Manual AC Control	Mis A/C State	Manual AC Control
79	Flight Crews are becoming more reluctant to revert to manual flying when Automation fails.	All	All	34	ACC IATA Comments	Automation ManualACControl	Manual AC Control Error Mgt Automation	CRM Mis-AFS Syst mal Mis A/C State	Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
86	b. Go-Arounds need training in terms of Decision making, surprise, execution, two engine, any point during the approach and landing	APR LDG GA	All	All	ACC IATA Comments	GA	Go Arounds Surprise	CRM Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control

Figure 4.2.6.4 – Manual Aircraft Control/IATA Accident Reports



#### 4.2.6.5 Go-around

- Filter Evidence Table Sources IATA Reports
- Filter Topics [GA]
  - See Figure 4.2.6.5
  - Result IATA Reports Go-Around
    - IATA statistics support LOSA results regarding failure to go-around from unstable approaches.
    - Failure to go-around ranks number 2 in percentage of errors in accidents.
    - The go-around decision needs to be reinforced in training as well as the execution (all engine and engine out).
    - Coping with surprise and proficiency established in go-around at any point during the approach.
  - Summary The results from IATA accident statistics support the LOSA findings in terms of the high degree of failure to go-around when the approach is unstable. This crew error is ranked high in IATA accident analysis and the report recommends training in go-arounds with regard to decision-making and execution of any type of go-around, at any point during the approach.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
72	IATA 29 ACC statistics: Flight Crew Errors fully in support of LOSA results (ManualACControl, compliance, failure to go-around, Automation)	Ali	All	All	ACC IATA	ManualACControl Compliance Automation	Manual AC Control Go Arounds Automation	Compliance CRM Mis A/C State Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control Flight Management Guidance/Automation
74	Top errors Manual Handling (33%), SOP 3%, Fail to GA 11%	All	All	All	ACC IATA	Error Management	Manual AC Control Error Mgt Unstable APP Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control
81	Decision to GA needs to be reinforced in training for abnormal landings (existing training counterproductive to this objective 4)	LDG	All	All	ACC IATA Comments	Unstable APR/GA Compliance	Go Arounds Landing Issues Error Mgt	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
86	Go-Arounds need training in terms of Decision making, surprise, execution, two engine, any point during the approach and landing	APR LDG GA	All	All	ACC IATA Comments	GA	Go Arounds Surprise	CRM Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control

Figure 4.2.6.5 - Go Around/IATA Accident Reports

#### 4.2.6.6 Weather

- Filter Evidence Table Sources IATA Reports
  - Filter Topics [WX]
  - See Figure 4.2.6.6
  - Result IATA Reports WX
    - The top threat in the IATA accident reports is weather.
  - Summary The top threat in the IATA accident reports is weather.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
73	Top threat weather 29%	All	All	All	ACC IATA	Error Management WX	WX	Adverse WX Windshear Crosswind Poor Visibility	SA Problem Solving Decision Making Application of Procedures/Knowledge

Figure 4.2.6.6 – Weather/IATA Accident Reports

## 4.2.6.7 Surprise

- Filter Evidence Table Sources IATA Reports
- Filter Topics [Surprise] combined with
- Filter Competencies [SA]
- Suppress superfluous.
  - See Figure 4.2.6.7
    - Result IATA Reports Surprise
      - Important countermeasures to enhance situation awareness include monitoring and crosschecking.
      - Many abnormal situations that crews encounter are not covered in training.
      - Briefings to cover the specific situations that crews are encountering enhance awareness.
      - Training should be designed to go to the "edge of the envelope."
      - The IATA report specifically recommends training to cope with surprise go-around situations.
    - Summary Maintaining situation awareness by specific briefings as well as monitoring and cross checking are effective countermeasures for dealing with all operational situations, including surprises. The IATA accident reports recommend training to deal with unusual "edge of the envelope" situations as well as specific training to cope with surprise go-arounds.

ľ	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
-	Countermeasures include monitoring / cross-checking and Automation mgt	All	All	All	ACC IATA	MonitoringXchecking Automation	Error Mgt Automation Monitoring Xcheck	Mis-AFS CRM	SA Flight Management/Guidance/Automation
8	Many abnormal events that crews face are not covered in training.	All	All	34	ACC IATA Comments	Surprise	Surprise		SA
8	Training should be designed to take pilots to the edge of the envelope. (black/grey Surprise)	All	All	All	ACC IATA Comments	Surprise	Surprise		SA Problem Solving Decision Making Application of Procedures/Knowledge
8	<sup>34</sup> Briefing should be adapted to the situation.	All	All	All	ACC IATA Comments	Error Management	Error Mgt	CRM	Communication SA
5	Go-Arounds need training in terms of Decision making, surprise, execution, two engine, any point during the approach and landing	APR LDG GA	All	All	ACC IATA Comments	GA	Go Arounds Surprise	CRM Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control

Figure 4.2.6.7 – Surprise/IATA Accident Reports

## 4.2.6.8 Landing Issues

- Filter Evidence Table Sources IATA Reports
  - Filter Topics [Landing Issues]
    - See Figure 4.2.6.8
    - Result IATA Reports Landing Issues
      - The top UAS in the IATA accident reports is improper landings at 21%.
      - Training should reinforce go-around in appropriate situations.
    - Summary According to the IATA accident reports, the number 1 UAS is improper landing. Training should reinforce go-around from abnormal landings.

E		Flight	Gen	Applicability					
ref	Evidence Statement	Phase	Specific	to Gens	Source	Key Words	Training Topics	Factors	Competencies
75	Top UAS: improper landing 21%	LDG	All	All	ACC IATA	Error Management Manual AC Control UAS	Landing Issues	Runway Taxi Condition Mis A/C State	Problem Solving Decision Making Manual AC Control
81	Decision to GA needs to be reinforced in training for abnormal landings (existing training counterproductive to this objective 4)	LDG	All	All	ACC IATA Comments	Unstable APR/GA Compliance	Go-Arounds Landing Issues Error Mgt	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge

Figure 4.2.6.8 - Landing Issues/IATA Accident Reports





## 4.2.6.9 Compliance

- Filter Evidence Table Sources IATA Reports
- Filter Factors [Compliance]
  - See Figure 4.2.6.9
  - Result IATA Reports Compliance
    - IATA accident reports support compliance findings in LOSA.
    - SOP issues are rated in the top 3 category of errors.
    - Training to reinforce SOP in approach and landings should be included in an FSTD-based program.
  - Summary The IATA reports echo LOSA findings. Compliance is rated as one of the top errors and specific training is recommended particularly with respect to following SOPs (i.e., to go-around) when an approach is not stable, and when the landing is improper.

l re	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
7	IATA 29 ACC statistics: Flight Crew Errors fully in support of LOSA results (ManualACControl, compliance, failure to go-around, Automation)	All	Ali	All	ACC IATA	ManualACControl Compliance Automation	Manual AC Control Go Arounds Automation	Compliance CRM Mis A/C State Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control Flight Management Guidance/Automation
7.	4 Top errors Manual Handling (33%), SOP 3%, Fail to GA 11%	All	Ali	All	ACC IATA	Error Management	Manual AC Control Error Mgt Unstable APP Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control
8	Decision to GA needs to be reinforced in training for abnormal landings (existing training counterproductive to this objective 4)	LDG	All	All	ACC IATA Comments	Unstable APR/GA Compliance	Go Arounds Landing Issues Error Mgt	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
8	a. Introduce Unstable App training in simulators	APR	All	All	ACC IATA Comments	Unstable APR/GA	Unstable APP	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge

Figure 4.2.6.9 – Compliance/IATA Accident Reports

## 4.2.6.10 Mismanaged Aircraft State

- Filter Evidence Table Sources IATA Reports
- Filter Factors [Mis A/C State]
  - See Figure 4.2.6.10
  - Result IATA Reports Mismanaged Aircraft State
    - Improper landing is the top UAS.
    - Manual aircraft control is a problem and should be reinforced during training.
    - Pilots are reluctant to revert to manual flight.
    - IATA reports recommend training for landings and go-around.
  - Summary Mismanaged aircraft states occur for many reasons. The IATA report recommends reinforcement training in basic flying skills such as manual handling, landings and go-arounds. Flight crews are reluctant to revert to manual flight from automation, while basic maneuvers such as landings and go-arounds continue to be a problem. The reports propose that proficiency and confidence be fostered during training.

E re	f Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
74	Top errors Manual Handling (33%), SOP 3%, Fail to GA 11%	All	Ali	All	ACC IATA	Error Management	Manual AC Control Error Mgt Unstable APP Go Arounds	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control
7!	5 Top UAS: improper landing 21%	LDG	All	All	ACC IATA	Error ManualACControl UAS	Landing Issues	Runway/Taxi condition Mis A/C State	Problem Solving Decision Making Manual Aircraft Control
78	ManualACControl needs to be reinforced in Training	All	All		ACC IATA Comments	ManualACControl	Manual AC Control	Mis A/C State	Manual Aircraft Control
79	Flight Crews are becoming more reluctant to revert to manual flying when Automation fails.	All	Ali	34	ACC IATA Comments	Automation ManualACControl	Manual AC Control Error Mgt Automation	CRM Mis-AFS Syst mal Mis A/C State	Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
8	Decision to GA needs to be reinforced in training for abnormal landings (existing training counterproductive to this objective 4)	LDG	Ali	All	ACC IATA Comments	Unstable APR/GA Compliance	Go Arounds Landing Issues Error Mgt	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
8	Introduce Unstable App training in simulators	APR	All	All	ACC IATA Comments	Unstable APR/GA	Unstable APP	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
8	Go-Arounds need training in terms of Decision making, surprise, execution, two engine, any point during the approach and landing	APR LDG GA	Ali	All	ACC IATA Comments	GA	Go Arounds Surprise	CRM Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control

Figure 4.2.6.10 – Mismanaged Aircraft State/IATA Accident Reports

## 4.2.6.11 Upset

- Filter Evidence Table Sources IATA Reports
- Filter Factors [Upset]
  - See Figure 4.2.6.11
  - Result IATA Reports Upset
    - Training should be designed to take pilots to the edge of the envelope (Black/grey Surprise)
  - Summary Training should enable pilots to respond to unexpected events throughout the flight regime at various levels of difficulties.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
83	Training should be designed to take pilots to the edge of the envelope. (black/grey Surprise)	All	All	All	ACC IATA Comments	Surprise	Surprise Upset		SA Problem Solving Decision Making Application of Procedures/Knowledge

Figure 4.2.6	11 – Unset/IAT	A Accident	Reports
i iyule 4.2.0.			reports




#### 4.2.6.12 Training Effect

- Filter Evidence Table Sources IATA Reports
  - Filter Keywords [Training Effect]
  - See Figure 4.2.6.12
  - Result IATA Reports Training Effect
    - Unstable approach training should be introduced as part of an FSTD based program.
    - Decision to go-around should be reinforced in training as well as the execution of the maneuver from any point on the approach.
    - Training should be designed to maximize pilot exposure to potentially challenging events.
  - Summary As evidenced by the recommendations in the IATA accident reports, the analysts and authors believe that FSTD training would be effective to mitigate unstable approaches, reinforce the decision to go-around when appropriate as well as improve the performance of the go-around maneuver itself.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
81	Decision to GA needs to be reinforced in training for abnormal landings (existing training counterproductive to this objective 4)	LDG	All	All	ACC IATA Comments	Unstable APR/GA Compliance Training effect	Go Arounds Landing Issues Error Mgt	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/ Knowledge
83	f. Training should be designed to take pilots to the edge of the envelope. (black/grey Surprise)	All	All	All	ACC IATA Comments	Training effect	Surprise Upset		SA Problem Solving Decision Making Application of Procedures/ Knowledge
85	a. Introduce Unstable App training in simulators	APR	All	All	ACC IATA Comments	Unstable APR/GA Training Effect	Unstable APP	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/ Knowledge
86	b. Go-Arounds need training in terms of Decision making, surprise, execution, two engine, any point during the approach and landing	APR LDG GA	All	All	ACC IATA Comments	GA Training Effect	Go Arounds Surprise	CRM Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control

Figure 4.2.6.12 - Training Effect/IATA Accident Reports

# 4.2.7 Incidents during Training

#### 4.2.7.1 Unstable Approaches

- Filter Evidence Table Incidents During Training
- Filter Topics [Unstable APP]
  - See Figure 4.2.7.1 and Fig 4.2.7.1a
  - Result Incidents during Training Unstable Approaches
    - Unstable approaches are the number 1 reported event in the STEADES database for training flights at 16.7%.
    - Unstable approaches are the number 2 reported event in the STEADES database for all-flights at 8.3%.
    - There is twice the percentage of ASRs for unstable approaches during training flights compared to the all-flights ASR database.



Figure 4.2.7.1

 Summary – According to pilot reporting, not only do the unstable approaches rank high in reported incidents; but also the percentage of reports is twice as high during training flights.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
333	Top 10 ASR's in operations in percentage of reports o Aircraft limit exceedance 9.2% o Unstable approach 8.3% o Turbulence 7.6% o Flight crew missed selection 6.3% o Traffic on runway during short final 5.9% o Windshear 4.2% o ATC traffic separation 3.8% o Checklist/SOP use 3.5% o Manual handling 3.4% o ATC communication lost 3.1%	All	Ali	All	Incid Anal STEADES		Manual AC Control Automation WX Unstable APP Compliance	Adverse WX ATC Loss of comms Traffic Windshear Compliance Mis A/C State Mis-Sys Manual AC Control	Communication Application of Procedures/Knowledge Workload Management SA
337	Manual handling is number 2 in percentage of ASRs for training flights (9.2%) but number 9 for normal ops at 3,5%.	All	All	All	Incid Anal STEADES		Manual AC Control	Mis A/C State	Manual AC Control

Figure 4.2.7.1a – Unstable Approaches/Training Incidents

# 4.2.7.2 Error Management

- Filter Evidence Table Incidents During Training
- Filter Topics [Error Mgt]
  - See Figure 4.2.7.2
  - Result Incidents during Training Error Management
    - The majority of incidents reported on training flights are errors while in the majority of incidents in the database for all flights refer to threats.
    - Flight crew mis-selection is ranked similarly in both databases but generates twice the percentage of reports during training flights as compared to normal operations.
    - Problems with checklist use and SOPs is ranked 8<sup>th</sup> in percentage of ASRs reported in the main database and ranked 9<sup>th</sup> for training flights. The percentage of occurrence for both is nearly the same at approximately 3.5%.
  - Summary Comparing the subjects of the incident reports for the training flights with the main ASR database provides some insight into the evolution of pilots as they acquire more experience on the line. The training flight database is heavily populated with errors, rather than threats, but not the case for the main database. This is not only true for the rankings of the incidents, but also for the percentages of actual reports with similar rankings across the two groupings of flights.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
334	Top 10 ASR's in training flights o Unstable approach 16.7% o Manual handling 9.4% o Flight crew missed selection 9.2% o Heavy/hard Landlings 7.5% o Deep (long) Landlings 5.5% o Procedures (operational) 5.2% o EGPWS G/S Alert 4.3% o Aircraft limit exceedance 3.6% o Checklist/SOP use 3.3% o Aircraft anti/de-ice 3.1%	All	All	All	Incid Anal STEADES		Unstable APP Manual AC Control Error Mgt Landing Issues Compliance WX	Adverse WX Compliance Mis-AFS Mis-A/C State Mis-Sys Manual AC Control	Leadership and Teamwork Application of Procedures/Knowledge Manual Aircraft Control Workload Management
338	Flight crew mis-selection is ranked 4 <sup>th</sup> in both databases but generates twice the percentage of reports during training flights as compared to normal operations.	All	All	All	Incid Anal STEADES		Error Mgt	Mis-Sys Mis A/C State Mis-AFS	Leadership and Teamwork Workload Management
339	Problems with checklist use and SOPs is ranked 8 <sup>th</sup> in ASR percentage in the main database and ranked 9 <sup>th</sup> for training flights. The percentage of occurrence for both is nearly the same at approximately 3.5%.	All	All	All	Incid Anal STEADES	Criticality	Compliance Error Mgt	Compliance Workload distraction	Application of Procedures/Knowledge Workload Management

Figure 4.2.7.2 – Error management/Training Incidents			
	Eiguro 1272 Error	management/Training	Incidente
	FIQUE 4.2.7.2 - EII0E		IIICIUEIIIS

# 4.2.7.3 Manual Aircraft Control

- Filter Evidence Table Incidents During Training
  - Filter Topics [Manual A/C Control]
    - See Figure 4.2.7.3b
    - Result Incidents during Training Manual Aircraft Control
      - Manual handling accounts for 9.4% of the reported incidents for training flights in the ASR database.

#### Top 20 Training/Trainee ASRs





• Manual handling accounts for 3.4% of the reported incidents for all flights in the ASR database.





- Manual handling is ranked 2<sup>nd</sup> in percentage of reported incidents for training flights while it is ranked 9<sup>th</sup> overall.
- Summary Reported incidents show manual aircraft control is a concern, as it is 3.4% of the total incidents reported. However it is three times more likely to be reported when the flight is a training flight and it is the 2<sup>nd</sup> most reported incident for the set of training flights.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
333	Top 10 ASR's in operations in percentage of reports o Aircraft limit exceedance 9.2% o Unstable approach 8.3% o Turbulence 7.6% o Flight crew missed selection 6.3% o Traffic on runway during short final 5.9% o Windshear 4.2% o ATC traffic separation 3.8% o Checklist/SOP use 3.5% o Manual handling 3.4% o ATC communication lost 3.1%	All	All	All	Incid Anal STEADES		Manual AC Control Automation WX Unstable APP Compliance	Adverse WX ATC Loss of comms Traffic Windshear Compliance Mis A/C State Mis- Sys Manual AC Control	Communication Application of Procedures/Knowledge Workload Management SA
337	Manual handling is number 2 in percentage of ASRs for training flights (9.2%) but number 9 for normal ops at 3,5%.	All	All	All	Incid Anal STEADES		Manual AC Control	Mis A/C State	Manual AC Control

Figure 4.2.7.3b - Manual Aircraft Control/Training Incidents



# 4.2.7.4 Weather

- Filter Evidence Table Pilot Survey
- Filter Topics [WX]
  - See Figure 4.2.7.4
  - Result Incidents during Training Weather
    - Weather threats are reported at 17.8% in the all-flight database, while only at 4.8% rate for training flights. See figures above in Section 4.2.7.3.
    - The majority of incidents reported during training flights are errors, while the overall majority of incidents refer to threats in the database for all flights
  - Summary Weather is a major threat for flight crews, and this source continues to corroborate the threat. The fact that it is ranked so low according to the training flight ASR data (4.8% versus 17,8% in all-flight database), indicates that new pilots are absorbed with other concerns, related to errors.

1	E ref	Evidence Statement	Flight Phase	Gen Specifi	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	333	Top 10 ASR's in operations in percentage of reports o Aircraft limit exceedance 9.2% o Unstable approach 8.3% o Turbulence 7.6% o Flight crew missed selection 6.3% o Traffic on runway during short final 5.9% o Windshear 4.2% o ATC traffic separation 3.8% o Checklist/SDP use 3.5% o Manual handling 3.4% o ATC communication lost 3.1%	All	All	All	Incid Anal STEADES		Manual AC Control Automation WX Unstable APP Compliance	Adverse WX ATC Loss of comms Traffic Windshear Compliance Mis A/C State Mis-Sys Manual Aircraft Control	Communication Application of Procedures/Knowledge Workload Managementt SA
	334	Top 10 ASR's in training flights o Unstable approach 16.7% o Manual handling 9.4% o Flight crew missed selection 9.2% o Heavy/hard Landings 7.5% o Deep (long) Landings 5.5% o Procedures (operational) 5.2% o EGPWS G/S Alert 4.3% o Aircraft limit exceedance 3.6% o Checklist/SOP use 3.3% o Aircraft anti/de-ice 3.1%	All	All	All	Incid Anal STEADES		Unstable APP Manual AC Control Error Mgt Landing Issues Compliance WX	Adverse WX Compliance Mis-AFS Mis A/C State Mis-Sys Manual Aircraft Control	Leadership and Teamwork Application of Procedures/Knowledge Manual Aircraft Control Workload Management

Figure 4.2.7.4 – Weather/Training Incidents





#### 4.2.7.5 Landing Issues

- Filter Evidence Table Incidents During Training
- Filter Topics [Landing Issues]
  - See Figure 4.2.7.5
  - See figures above in Section 4.2.7.3
  - Result Incidents during Training Landing Issues
    - Manual handling accounts for 9.4% of the reported incidents for training flights in the ASR database.
    - Heavy or hard landings account for 7.5% of the reported incidents for training flights.
    - Deep (long) landings account for 5.5% of the reported incidents for training flights.
    - Manual handling accounts for 3.4% of the reported incidents for all flights in the ASR database.
    - Heavy or hard landings account for 2.3% of the reported incidents for all flights.
  - Summary Reported landing incidents account for 13% of reports for training flights. This coupled with the fact that manual handling is ranked 2<sup>nd</sup> imply that there is still a considerable amount of learning skills are not fully acquired prior to IOE.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
334	Top 10 ASR's in training flights -Unstable approach 16.7% -Manual handling 9.4% -Flight crew missed selection 9.2% -Heavy/hard landings 7.5% -Deep (long) landings 5.5% -Procedures (operations) 5.2% -EGPWS G/S alert 4.3% -Aircraft limit exceedance 3.6% -Checklist/SOP use 3.3% -Aircraft anti/de-ice 3.1%	All	All	All	Incid Anal STEADES		Unstable APP Manual AC Control Error Mgt Landing Issues Compliance WX	Adverse WX Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	Leadership and Teamwork Application of Procedures/Knowledge Manual Aircraft Control Workload Management
336	Heavy/hard landings is number 4 in terms of percentage of reports during training flights but outside of the top twenty for normal ops.	All	Ali	All	Incid Anal STEADES	Criticality	Landing Issues	Mis A/C State	Manual AC Control

Figure 4.2.7.5 – Landing Issues/Training Incidents

# 4.2.7.6 Compliance

- Filter Evidence Table Incidents During Training
- Filter Topics [Compliance]
  - See Figure 4. 4.2.7.6
  - Result Incidents during Training Compliance
    - Checklist use is cited in 3.3% of reported incidents for training flights in the ASR database, and ranked 9<sup>th</sup> overall.
    - Checklist use is cited in 3.4% of the reported incidents for all flights in the ASR database, and ranked 8<sup>th</sup> overall.
  - Summary STEADES data draws little distinction between the two groupings of flights (training and all flights). Most of the training flights are for the purpose of IOE, and data indicates issues with checklists and SOPs, which are similar despite varying experience levels.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
333	Top 10 ASR's in operations in percentage of reports o Aircraft limit exceedance 9.2% o Unstable approach 8.3% o Turbulence 7.6% o Flight crew missed selection 6.3% o Traffic on runway during short final 5.9% o Windshear 4.2% o ATC traffic separation 3.8% o Checklist/SOP use 3.5% o Manual handling 3.4% o ATC communication lost 3.1%	All	All	All	Incid Anal STEADES		Manual AC Control Automation WX Unstable APP Compliance	Adverse WX ATC Loss of comms Traffic Windshear Compliance Mis A/C State Mis-Sys Manual AC Control	Communication Application of Procedures/Knowledge Workload Management SA
334	Top 10 ASR's in training flights o Unstable approach 16.7% O Manual handling 9.4% o Flight crew missed selection 9.2% o Heavy/hard Landings 7.5% o Deop (long) Landings 5.5% o Procedures (operational) 5.2% o EGPWS G/S Alert 4.3% o Aircraft limit exceedance 3.6% o Checklist/S0P use 3.3% o Aircraft anti/de-ice 3.1%	All	All	All	Incid Anal STEADES		Unstable APP Manual AC Control Error Mgt Landing Issues Compliance WX	Adverse WX Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	Leadership and Teamwork Application of Procedures/Knowledge Manual Aircraft Control Workload Management

Figure 4.2.7.6 - Compliance/Training Incidents



# 4.2.7.7 Mismanaged Aircraft State

- Filter Evidence Table Incidents During Training
- Filter Factors [Mis A/C State]
  - See Figure 4.2.7.7
  - See figures above in Section 4.2.7.3
  - Result Incidents during Training Mismanaged Aircraft State
    - There is twice the percentage of ASRs (Air Safety Reports) for unstable approaches during training flights when compared to the all flight ASR database.
    - "Heavy or hard" landing is ranked 4<sup>th</sup> in terms of percentage of reports during training flights, but outside of the top twenty for normal operations.
    - Looking at the top ten incidents in each grouping, there are twice as many incident types classified as mismanaged aircraft states in the grouping of training flights as opposed to the database of all flights.
  - Summary The training flight database is heavily populated with incidents that are classified as mismanaged aircraft states while this is not nearly the case for the database of all flights. This fact is not only true for the rankings of the incidents, but also true for the percentages of actual reports with similar rankings across the two groupings of flights. Examples of this are unstable approaches (16.7% versus 8.3%), landing with incident, EGPWS and manual handling.

,	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
3	Top 10 ASR's in operations in percentage of reports       o Aircraft limit exceedance 9.2%       o Unstable approach 8.3%       o Turbulence 7.6%       o Flight crew missed selection 6.3%       30 Traffic on runway during short final 5.9%       o Windshear 4.2%       o ATC traffic separation 3.8%       o Checklist/SOP use 3.5%       o Manual handing 3.4%       o ATC communication lost 3.1%	All	All	All	Incid Anal STEADES		Manual AC Control Automation WX Unstable APP Compliance	Adverse WX ATC Loss of comms Traffic Windshear Compliance Mis A/C State Mis-Sys Manual AC Control	Communication Application of Procedures/Knowledge Workload Management SA
3	Top 10 ASR's in training flights         o Unstable approach 16.7%         o Manual handling 9.4%         o Flight crew missed selection 9.2%         o HeavyInard Landings 7.5%         304       o Deep (long) Landings 5.5%         o Procedures (operational) 5.2%         o EGPWS G/S Alert 4.3%         o Aircraft limit exceedance 3.6%         o Aircraft anti/de-ice 3.1%	All	All	All	Incid Anal STEADES		Unstable APP Manual AC Control Error Mgt Landing Issues Compliance WX	Adverse WX Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	Leadership and Teamwork Application of Procedures/Knowledge Manual Aircraft Control Workload Management
3	There are twice the percentage of ASRs for unstable approaches during training flights compared to the main ASR database	All	All	All	Incid Anal STEADES	Criticality	Unstable APP	Mis A/C State Compliance	Leadership and Teamwork Application of Procedures/Knowledge Manual Aircraft Control Workload Management
3	Heavy/hard landings is number 4 in terms of percentage of reports during training flights but outside of the top twenty for normal ops.	All	All	All	Incid Anal STEADES	Criticality	Landing Issues	Mis A/C State	Manual Aircraft Control
3	Manual handling is number 2 in percentage of ASRs for training flights (9.2%) but number 9 for normal ops at 3,5%.	All	All	All	Incid Anal STEADES		Manual AC Control	Mis A/C State	Manual Aircraft Control
3	Flight crew mis-selection is ranked approximately the same in both databases but generates a 50% higher the percentage figure of reports during training flights as compared to normal operations.	All	All	All	Incid Anal STEADES		Error Mgt	Mis-Sys Mis A/C State Mis-AFS	Leadership and Teamwork Workload Management

Figure 4.2.7.7 – Mismanaged Aircraft State/Training Incidents

# 4.2.8 UK CAA Accident Studies

#### 4.2.8.1 Automation

•

- Filter Evidence Table UK CAA
- Filter Topics [Automation]
- See Figure 4.2.8.1
  - Result UK Accident Reports Automation
    - The UK accident analysis ranked accidents by cause, ranking "mishandled autoflight" 10th in order of priority at a 1.9% rate of occurrence.
  - Summary The ranking of automation as a causal factor is generally low in accident reporting and the CAA accident reporting is no exception at 1.9%. The prevailing opinion by many analysts is that because mismanaged automation is further upstream in the error chain it is under reported in causal accident investigation.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	General Operational Threats by Rank - (TEM Phase)								
	a. Human Factors – 32.3%								
	<ul> <li>b. Compliance failure – 19.1%</li> </ul>								
	c. Mishandled Aircraft – 13%								
	d. Mismanaged Aircraft State - 7.8%							Compliance Dof Manuals	
	e. Procedures – 6.9%							Def-Charts	
	f. Performance – 4.2%						Automation	Fatique	Workload Management
325	g. Mishandled systems (other than FMS) – 3.8%	All	All	All	ACC CAA	Threats & Errors	Compliance	CRM	Application of Procedures/Knowledge
	h. Workload Distribution – 3.4%					IEM	Error Mgt	Mis-AFS	Flight Management Guidance/Automation
	i. Fatigue – 3.4%							Mis-A/C State	
	j. Mishandled Auto-Flight – 1.9%							Mis-Sys	
	k. Performance Miscalculation – 1.7%							Manual AC Control	
	<ol> <li>Deficiencies in Manuals – 0.8%</li> </ol>								
	m. Physiological – 0.8%								
	n. Cabin – 0.6%								
	<ul> <li>Deficiencies in Charts – 0.4%</li> </ul>								

Figure 4.2.8.1 – Automation/UK CAA Accident Studies





#### 4.2.8.2 Error Management

- Filter Evidence Table UK CAA
- Filter Topics [Error Mgt]
  - See Figure 4.2.8.2
  - Result UK Accident Reports Error Management
    - CAA reports main TEM issues are compliance human factors, CRM, mishandling aircraft and SOP compliance issues.
    - Top five accident causes are:
      - Omissions/inappropriate actions 38%.
      - Flight mishandling 28%.
      - Lack of positional awareness 25%.
      - Failure of CRM 22%.
      - Major concern for accident causation is the category of human factors.
  - Summary The CAA accident reports (CAP 776 & CAP 780) cite human factors as the major concern in accident causation. The top five HF issues with their percentage rate of occurrence in accidents are inappropriate actions or omissions (38%), flight mishandling (28%), lack of positional awareness (25%) and failure of CRM (22%).

	E ref	Evidence Statement	Flight Phase	Specifi	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
:	87	CAA report supports main threats (compliance, HF/CRM, mishandling a/c, SOP's). Compared to LOSA, bigger bars in CRZ and APR.	All	All	All	ACC CAA	Compliance ManualACControl	Error Mgt	CRM Mis A/C State Compliance	Communication SA Leadership and Teamwork Workload Management Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
3	26	Five most common causal factor groups (CAP 780) a. Omission/inappropriate Action – 36% b. Flight Handling – 28% c. Lack of Positional awareness – 25% d. Failure of CRM – 22%	All	All	All	ACC CAA	Causes Criticality Errors SA	Manual AC Control Error Mgt Leadership	CRM Manual AC Control	Application of Procedures/Knowledge Leadership and Teamwork Manual Aircraft Control
3	29	Further analysis to determine the areas of general operational threat it is clear that the major threat is that of the non-technical area of human factors	All	All	All	ACC CAA	Criticality CRM	Manual AC Control Error Mgt Leadership	CRM Workload Distraction Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge
3	30	The UK Civil Aviation Authority publications CAP 776 Global Fatal Accident Review 1997 – 2006 and CAP 780 Aviation Safety Review 2008 both suggest that the main areas of concern are non technical ones by nature	All	All	All	ACC CAA	Criticality CRM	Manual AC Control Error Mgt Leadership	CRM Workload Distraction Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge
3	31	(CAP 776) demonstrates that the top two primary causal factors, accounting for 36.4% of accidents, are non technical in nature. This is further reinforced by data from the CAP 780 which shows that the top five most common causal factors groups contain a significant component of non-technical elements (Human Factors).	All	All	All	ACC CAA	Criticality CRM	Manual AC Control Error Mgt Leadership	CRM Workload Distraction Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge
3	32	(CAP 780) again demonstrates that the most frequently occurring causal factors are crew related	All	All	All	ACC CAA	Criticality CRM	Error Mgt Leadership Compliance Manual AC Control	CRM Workload Distraction Compliance Mis-AFS Mis A/C State Mis-Sys	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge

Figure 4.2.8.2 – Error Management/UK CAA Accident Studies

# 4.2.8.3 Manual Aircraft Control

- Filter Evidence Table UK CAA
- Filter Topics [Manual AC Control]
  - See Figure 4.2.8.3a

- Result UK Accident Reports Manual Aircraft Control
  - Top five accident causes are:
    - Omissions/inappropriate actions 38%.
    - Flight mishandling 28%.
    - Lack of positional awareness 25%.
    - Failure of CRM 22%.



#### Five most common causal factors by category

Figure 4.2.8.3

- CAP 780 reports that the most frequent causal factors are crew related.
- Summary Flight mishandling is ranked second in percentage of occurrence in accidents (28%) by the UK Accident Report CAP 780.

	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
		Five most common causal factor groups (CAP 780)								
		a. Omission/inappropriate Action – 36%					Causes Criticality Errors SA			
32	326	b. Flight Handling – 28%	All	All	All	ACC		Manual AC Control	CRM	Application of Procedures/Knowledge
	020	c. Lack of Positional awareness – 25%	7.01	7.01	7 41	CAA		Leadership	Manual AC Control	Manual AC Control
		d. Failure of CRM – 22%								
		e. Poor Judgment/Airmanship – 20%								
	332	(CAP 780) again demonstrates that the most frequently occurring causal factors are crew related	All	All	All	ACC CAA	Criticality CRM	Error Mgt Leadership Compliance Manual AC Control	CRM Workload Distraction Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge

Figure 4.2.8.3a – Manual Aircraft Control/UK CAA Accident Studies



# 4.2.8.4 Compliance

- Filter Evidence Table UK CAA
- Filter Topics [Compliance]
  - See Figure 4.2.8.4a
  - Result UK Accident Reports Compliance
    - Compliance failure is ranked number 2 in terms of TEM by the UK accident investigation team at 19.1% occurrence rate.



Figure 4.2.8.4

 Summary – Part of the team that authored CAA CAP 780 Report analyzed the fatal accidents set used in the CAP 780 Report (i.e., occurring during the period between 1 January 1997 and 31 December 2008 (inclusive)) for the EBT Data Report. The analysis was made in terms of the threats and errors defined in the EBT Training Criticality Survey (TCS) and the study determined that compliance failure ranked number 2 at a 19.1% rate of occurrence.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
325	General Operational Threats by Rank - (TEM Phase) a. Human Factors - 32.3% b. Compliance failure - 19.1% c. Mishandled Aircraft - 13% d. Mismanaged Aircraft State - 7.8% e. Procedures - 6.9% f. Performance - 4.2% g. Mishandled systems (other than FMS) - 3.8% h. Workload Distribution - 3.4% i. Fatigue - 3.4% j. Mishandled Auto-Flight - 1.9% k. Performance Miscalculation - 1.7% l. Deficiencies in Manuals - 0.8% m. Physiological - 0.8% n. Cabin - 0.6%	All	All	All	ACC CAA	Threats and Errors TEM	Automation Compliance Error Mgt	Compliance Def Manuals Def-Charts Fatique CRM Workload Distraction Mis-AFS Mis A/C State Mis-Sys Manual AC Control	Workload Management Application of Procedures/Knowledge Flight Management Guidance/ Automation Manual Aircraft Control
331	(CAP 776) demonstrates that the top two primary causal factors, accounting for 36.4% of accidents, are non technical in nature. This is further reinforced by data from the CAP 780 which shows that the top five most common causal factors groups contain a significant component of non-technical elements (Human Factors).	All	All	All	ACC CAA	Criticality CRM	Error Mgt Leadership Compliance	CRM Workload Distraction Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge

#### 4.2.8.5 Phase of Flight

- Filter Evidence Table UK CAA
  - Filter Keyword [Phase]
  - See Fig 4.2.8.5

•

- Result UK Accident Reports Phase of Flight
  - Accidents by Phase of Flight
    - Pre-Flight and Taxi-Out 0.7%
    - Take-Off 11.9%
    - Climb 19.1%
    - Cruise 15.8%
    - Descent 4.3%
    - Approach 35.6%
    - Land 11.9%
    - Post-Flight and Taxi-In 0.7%

Phase of Flight	All Fatal Accidents	Passenger Flights Only	Cargo Flights Only	Western- Built Jets Only	Western- Built Jets on Passenger Flights Only
Pre-Flight and Taxi-					
Out	2	1	1	1	1
Take-Off	36	23	13	12	10
Climb	58	32	26	16	11
Cruise	48	33	15	13	12
Descent	13	8	5	4	3
Approach	108	74	34	32	25
Landing	36	30	6	18	18
Post-Flight	2	2	0	2	2
Total	303	203	100	98	82

Figure 4.2.8.5 – Accidents by Phase of Flight

 Summary – According to the UK Fatal Accident Report CAP 780, the APP phase of flight hosts the most accidents (35.6%) followed by the CLB phase at 19.1%. The rankings change significantly if all accidents are considered.



# 4.2.9 Skill Retention after Training/Skill Decay

#### 4.2.9.1 Unstable Approaches

- Filter Evidence Table Pilot Survey
  - Filter Topics [Unstable APP]
  - See Figure 4.2.9.1
  - Result Skill Decay/Skill Retention Studies Unstable Approaches
    - Skill loss can be substantial and increases over time without practice.
  - Summary The skill decay study shows that skill losses can be substantial and decay without practice, making the case for including energy management and recoveries from unstable approaches as part of a training curriculum.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
317	Skill loss can be substantial and generally increases with the duration of non-use / non-practice	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Unstable APP Go Arounds Automation Landing Issues		All

Figure 4.2.9.1 – Unstable Approaches/Skill Decay

#### 4.2.9.2 Automation

- Filter Evidence Table Pilot Survey
  - Filter Topics [Automation]
  - See Figure 4.2.9.2
    - Result Skill Decay/Skill Retention Studies Automation
      - There is less decay for physical versus cognitive skills.
      - Skill loss can be substantial and increases over time without practice.
      - Skill decay for accuracy is 3 times higher if it is necessary to perform the action quickly.
    - Summary The skill decay study shows that skill losses can be substantial and decay without practice. This deterioration is much greater for skilled tasks, such as certain automation skills making it important to assess these skills in training particularly for pilots that do on operate routinely.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
70	There is less skill decay for physical tasks compared to cognitive tasks.	All	All	All	Skill Decay & Skill Retention Studies	Skill Decay	Automation Surprise Error Mgt	Manual AC Control	Communication SA Problem Solving Decision Making Knowledge
317	Skill loss can be substantial and generally increases with the duration of non-use / non-practice	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Unstable APP Go Arounds Automation Landing Issues		All
319	Skill decay for "accuracy" tasks was three times higher than for "speed" tasks, i.e. for tasks where it was necessary to perform the trained skill fast.	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Automation		All

Figure 4.2.9.2 - Automation/Skill Decay

#### 4.2.9.3 Error Management

- Filter Evidence Table Pilot Survey
- Filter Topics [Error Mgt]
  - See Figure 4.2.9.3
  - Result Skill Decay/Skill Retention Studies Error Management
    - There is less decay for physical versus cognitive skills.
      - Skill retention for open loop tasks is better than for closed loop tasks.
  - Summary Error management is cognitive in nature implying that its rate of decay is greater than for many other the tasks that pilot perform. This decay aspect makes it important that error management be assessed and reinforced as necessary.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
70	There is less skill decay for physical tasks compared to cognitive tasks.	All	All	All	Skill Decay & Skill Retention Studies	Skill Decay	Automation Surprise Error Mgt	Manual AC Control	Communication SA Problem Solving Decision Making Knowledge
318	Retention of open-loop tasks was better than of closed-loop tasks.	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Error Mgt Leadership		All

Figure 4.2.9.3 – Error Management/Skill Decay

# 4.2.9.4 Manual Aircraft Control

- Filter Evidence Table Pilot Survey
  - Filter Topics [Manual A/C Control]
  - See Figure 4.2.9.4
    - Result Skill Decay/Skill Retention Studies Manual Aircraft control
      - Skill loss can be substantial and increases over time without practice.
      - There is no evidence that levels of maneuver-based skill decay among pilots in 12-month training cycles are worse than pilots in 6-month cycles. This is derived from the AQP Maneuver Validation (MV) and the subsequent "First Look" data.
      - There is no evidence of significant skill decay differential between normal and abnormal maneuvers.
    - Summary Manual aircraft control shows greater resistance to skill decay over time than other competencies. This is supported by two skill studies, (see appendix 5). The first is a meta study published by Texas A&M and the second was provided by the FAA, which ran for almost 10 years and included over 2 million training sessions across multiple types of aircraft.

E ret	f Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
317	Skill loss can be substantial and generally increases with the duration of non-use / non- practice	Ali	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Go Arounds Automation Unstable APP Landing Issues		All
320	There was no evidence of significant skill decay among pilots in 12-month training cycle (Maneuver Validation vs. First Look grades).	All	Ali	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge
321	There were no detectable trends in the MV-FL difference within the 2000 -2008 period.	All	Ali	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Landing Issues	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge
322	There was no significant difference between normal vs. abnormal maneuvers; except for the takeoff flight phase, where the "normal" got significantly better grades at all times during the 12-month retention interval.	All	All	All	Skill Decay & Skill Retention Studies	Criticality	System Malfunction Compliance Manual AC Control	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge

Figure 4.2.9.4 - Manual Aircraft Control/Skill Decay



# 4.2.9.5 System Malfunction

- Filter Evidence Table Pilot Survey
- Filter Topics [Sys Mal]
  - See Figure 4.2.9.5
  - Result Skill Decay/Skill Retention Studies System Malfunction
    - There is less skill decay for physical tasks when compared with cognitive tasks.
      - There is no significant difference in data when comparing normal and abnormal maneuvers for skill decay measured in a 6-month versus 12-month training intervals.
      - There is no evidence that levels of maneuver-based skill decay among pilots in 12-month training cycles are worse than pilots in 6-month cycles. This is derived from the AQP Maneuver Validation (MV) and the subsequent "First Look" data.
  - Summary The FAA skill decay study tends to support the notion that system malfunction proficiency is resistant to skill decay over time. The skill retention study conclusions are consistent with this finding. Management of the majority of malfunctions involves following defined procedures and checklists, the exception being a malfunction not anticipated by procedure and checklist design, or one with unexpected consequences. It is likely that skills required in dealing with a less defined problem or malfunction will be more vulnerable to decay.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
70	There is less skill decay for physical tasks compared to cognitive tasks.	All		All	Skill Decay & Skill Retention Studies	Skill Decay	Automation Surprise Error Mgt Manual AC Control System Malfunction	Manual AC Control	Communication SA Problem Solving Decision Making Knowledge Manaul Aircraft Ccontrol
317	Skill loss can be substantial and generally increases with the duration of non-use / non- practice	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Go Arounds Automation Unstable APP Landing Issues		All
320	There was no evidence of significant skill decay among pilots in 12-month training cycle (Maneuver Validation vs. First Look grades).	All	Ali	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge
321	There were no detectable trends in the MV-FL difference within the 2000 -2008 period.	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Landing Issues	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge
322	There was no significant difference between normal vs. abnormal maneuvers; except for the takeoff flight phase, where the "normal" got significantly better grades at all times during the 12-month retention interval.	All	All	All	Skill Decay & Skill Retention Studies	Criticality	System Malfunction Compliance Manual AC Control	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge

Figure 4.2.9.5 - System Malfunction/Skill Decay

## 4.2.9.6 Landing Issues

- Filter Evidence Table Pilot Survey
- Filter Topics [Landing Issues]
  - See Figure 4.2.9.6
  - Result Skill Decay/Skill Retention Studies Landing Issues
    - Skill loss can be substantial and increases over time without practice.
    - There is no evidence that levels of maneuver-based skill decay among pilots in 12-month training cycles are worse than pilots in 6-month cycles. This is derived from the AQP Maneuver Validation (MV) and the subsequent "First Look" data.
  - Summary Landings are generally practiced in the interval between training cycles and so not generally a problem for skill decay. This is indicated in the FAA skill decay study. Skill decay is a problem for pilots without landing practice, and this may affect those involved in ultra-long haul operations.

	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
3	Skill loss can be substantial and generally increases with the duration of non-use / non- practice	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Go Arounds Automation Unstable APP Landing Issues		All
3	There was no evidence of significant skill decay among pilots in 12-month training cycle (Maneuver Validation vs. First Look grades).	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge
3	There were no detectable trends in the MV-FL difference within the 2000 -2008 period.	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Landing Issues	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge
00	The results suggest pilots maintain their proficiency across the 12-month re-training interval	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Go Arounds System Malfunction Landing Issues	System Malfunction Compliance	Manual Aircraft Control Application of Procedures/Knowledge

Figure 4.2.9.6 - Landing Issues/Skill Decay



# 4.2.9.7 Training Effect

- Filter Evidence Table Pilot Survey
- Filter Keywords [Criticality]
  - See Figure 4.2.9.7
  - Result Skill Decay/Skill Retention Studies Training Effect
    - Skill loss can be substantial and increases over time without practice.
    - There is no evidence that levels of maneuver-based skill decay among pilots in 12-month training cycles are worse than pilots in 6-month cycles. This is derived from the AQP Maneuver Validation (MV) and the subsequent "First Look" data.
    - There is no significant difference in data when comparing normal and abnormal maneuvers for skill decay measured in a 6-month versus 12-month training intervals.
  - Summary The FAA skill decay study tends to support the notion that system malfunction proficiency is resistant to skill decay over time. The skill retention study conclusions are consistent with this finding. Management of the majority of malfunctions involves following defined procedures and checklists, the exception being a malfunction not anticipated by procedure and checklist design, or one with unexpected consequences. It is likely that skills required in dealing with a less defined problem or malfunction will be more vulnerable to decay.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
317	Skill loss can be substantial and generally increases with the duration of non-use / non-practice	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Go Arounds Automation Unstable APP Landing Issues		All
318	Retention of open-loop tasks was better than of closed-loop tasks.	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Error Mgt Leadership System Malfunction		All
319	Retention of open-loop tasks was better than of closed-loop tasks.	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Automation		All
320	There was no evidence of significant skill decay among pilots in 12- month training cycle (Maneuver Validation vs. First Look grades).	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge
321	There were no detectable trends in the MV-FL difference within the 2000 -2008 period.	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Landing Issues	Manual AC Control	Manual AC Control Application of Procedures/ Knowledge
322	There was no significant difference between normal vs. abnormal maneuvers; except for the takeoff flight phase, where the "normal" got significantly better grades at all times during the 12-month retention interval.	All	Ali	All	Skill Decay & Skill Retention Studies	Criticality	System Malfunction Compliance Manual AC Control	System Malfunction Compliance	Manual Aircraft Control Application of Procedures/Knowledge
323	The results suggest pilots maintain their proficiency across the 12- month re-training interval	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Go Arounds System Malfunction Landing Issues	System Malfunction Compliance	Manual Aircraft Control Application of Procedures/Knowledge

Figure 4.2.9.7 – Training Effect/Skill Decay

# 4.2.10 FAA Human Factors Team Report 1996

#### 4.2.10.1 Automation

- Filter Evidence Table FAA 1996 Automation Report
  - Filter Topics [Automation]
    - See Figure 4.2.10.1
    - Result FAA 1996 Automation Report Automation
      - Pilot SA automation awareness issues are understanding of capabilities, limitations and modes along with nonstandard levels of use.
      - Pilot vulnerabilities are: flight path, terrain and energy awareness.
      - Pilot training needs to address that pilots are surprised by subtle behavior and complexities of the automation.
      - The training course should focus on design principles that have operational consequences.
      - Existing methods are inadequate to evaluate human performance issues.
      - Current regulations have not kept pace with technical and human factors issues flight crew training needs to be re-balanced to cover automation issues.
      - The report recommends training to enhance mode and position awareness as well as potential causes, detection and recovery regarding hazardous conditions concerning traffic, terrain and upset while using the autoflight system.
      - The report recommends reassessing requirements of initial and recurrent training course to ensure that there is adequate content to cover mode and automation awareness regarding basic airmanship, CRM, decision- making including unanticipated events and workload/task management.
      - The report recommends that airman certification criteria be amended so that pilots have the appropriate automation skills.
      - Pilots have inappropriately used automation instead of reverting to manual flight.
      - The emphasis should be on learning instead of checking.
    - Summary The FAA automation report found that pilots have various situation awareness issues with automation. They are vulnerable to lack of flight path and energy awareness when using autoflight. In addition they are surprised by the subtleties and complexities of automation and the training courses fail to focus on operation principles of the autoflight architecture. Many pilots use the autoflight when inappropriate and fail to revert to manual flight. The training courses at the time of the study tended to be checking rather than learning oriented and had not kept pace with human factor issues in regard to automation. The report recommends that training enhance mode and position awareness when using automation, particularly with regard to terrain, energy and upset. In addition, the report recommends that there be adequate training content to insure airmanship, CRM, decision-making, workload/task management when utilizing automation especially in demanding situations.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
193	Identified issues show vulnerabilities in flightcrew Management of Automation and situation awareness are: • Pilot understanding of the Automation's capabilities, limitations, modes, and operating principles and techniques. • Differing pilot Decisions about the appropriate Automation level to use.	All	34	34	FAA 1996 Automatio n Report	Automation Generation Error Mgt	Automation	Mis-AFS	SA Problem Solving Decision Making Knowledge Flight Management/ Guidance/Automation
194	Flightcrew SA issues included vulnerabilities in: • Automation/mode awareness. • Flight path awareness: • including insufficient Terrain awareness sometimes involving loss of control or controlled flight into Terrain) and energy awareness (especially low energy state).	All	34	34	FAA 1996 Automatio n Report	Automation Generation SA Error Mgt UAS Competencies	Automation Terrain Error Mgt	Mis-AFS Mis A/C State Terrain	SA Flight Management Guidance/Automation
195	Processes for design, training, and regulatory functions inadequately address human performance issues: • users can be surprised by subtle behavior • overwhelmed by the complexity embedded in current systems operated within the current operating environment	All	34	34	FAA 1996 Automatio n Report	Automation Generation Error Mgt	Surprise Automation	Ops/Type Spec Mis-AFS	SA Flight Management Guidance/Automation
197	Existing methods, data, and tools are inadequate to evaluate and resolve many of the important human performance issues	All	34	All	FAA 1996 Automatio n Report	Automation Generation Error Mgt	Automation		Flight Management Guidance/Automation
199	Two-thirds to three-quarters of all accidents have flightcrew error cited as a major factor. Flightcrew training investments should be re- balanced to ensure appropriate coverage of Automation issues.	All	34	34	FAA 1996 Automatio n Report	Automation Error Mgt	Error Mgt Automation	Mis-AFS	Flight Management Guidance/Automation
200	Current Regulatory standards for type certification and operations have not kept pace with changes in technology and increased Knowledge about human performance.	All	34	34	FAA 1996 Automatio n Report	Automation Generation Error Mgt	Automation		Flight Management Guidance/Automation
201	Recommendation SA-1: The FAA should require operators to increase flightcrews' understanding of and sensitivity to maintaining situation awareness, particularly: • Mode and airplane energy awareness issues associated with autoflight systems (i.e., autopilot, autothrottle, flight Mgt system, and fly-by-wire flight control systems); • Position awareness with respect to the intended flight path and proximity to Terrain, obstacles, or traffic; and • Potential causes, flight crew detection, and recovery from hazardous pitch or bank angle Upsets while under autopilot control (e.g., wake vortex, subtle autopilot failures, engine failure in cruise, atmospheric turbulence).	All	34	34	FAA 1996 Automatio n Report	Automation Upset Generation Error Mgt	Error Mgt Automation Terrain	Mis-AFS Terrain	SA Flight Management Guidance/Automation Knowledge
202	Recommendation SA-2: The FAA should require operators' initial and recurrent training programs as well as appropriate operating manuals to: Explicitly address autoflight mode and airplane energy awareness hazards; • Provide information on the characteristics and principles of the autoflight system's design that have operational safety consequences; and • Provide training to proficiency of the flight Management system capabilities to be used in operations.	All	34	34	FAA 1996 Automatio n Report	Automation Generation	Error Mgt Automation	Mis-AFS	SA Flight Management/Guidance/Automation Knowledge
				Continued	on next page	9			

Figure	4 2 10 1 -	Automation	/FAA	HF	Report
riguie	4.2.10.1 -	Automation	I/FAA		report



	Continued from previous page											
207	Recommendation Knowledge-2: The FAA should reassess the requirements that determine the content, length, and type of initial and recurrent lightcrew training. Ensure that the content appropriately includes: • Management and use of Automation, including mental models of the Automation and moving between levels of Automation; • Flightcrew situation awareness, including mode and Automation awareness; • Basic airmanship; • Crew Resource Management; • Examples of specific difficulties encountered either in service or in training; and • Workload Management (task Management).	All	34	All	FAA 1996 Automatio n Report	Automation Competencies Generation SA	Leadership Automation	Compliance CRM	SA Problem Solving Decision Making Workload Management			
209	Recommendation Knowledge-5: The FAA should reassess the airman certification criteria to ensure that pilots are released with a satisfactory level of skills for managing and using Automation. Since current training is often oriented toward preparing pilots for checkrides, the airman certification criteria should be reassessed to ensure appropriate coverage of the topics listed in Recommendation Knowledge-2.	All	34	34	FAA 1996 Automatio n Report	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation			
219	There have been situations where flightcrews have either inappropriately continued to use the Automation when they found themselves in an abnormal situation.	All	34	34	FAA 1996 Automatio n Report	Automation Error Mgt	Automation Surprise	Mis-AFS	Problem Solving Decision Making Knowledge Flight Management Guidance/Automation			
220	Flightcrews should be given sufficient training on using the FMS to ensure proficiency at least for those capabilities used in normal day- to-day operations. The HF Team considers the practice of expecting flightcrews to acquire these basic skills while flying the line to be inappropriate.	All	34	34	FAA 1996 Automatio n Report	Automation Competencies	Automation Terrain Error Mgt	Mis-AFS	Flight Management Guidance/Automation			
221	The flightcrew must be able to understand the Automation's status and behavior, especially during unusual or demanding situations.	All	34	34	FAA 1996 Automatio n Report	Automation Error Mgt SA	Automation Surprise	Mis-AFS Workload Distraction	Flight Management Guidance/Automation Knowledge			
227	Invest in more coaching and less pass/fail testing.: • Improve the debriefing of flightcrew performance after simulator sessions, IOE, proficiency checks, etc. (e.g., standardization of instructor debriefs, video replays). • Focus more on practicing how to manage the different automated systems in different circumstances, especially the judgments that have to be made on transitioning between different levels of Automation (e.g., when to turn it off or on, or to change to a different level or mode). • Encourage initial/recurrent assessments or checks to be more "learning oriented." Emphasis should be focused so that learning becomes the primary objective rather than passing or failing.	All	34	All	FAA 1996 Automatio n Report	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge			
238	Initial and recurrent training should provide a clear understanding of operationally relevant Automation principles and ensure user proficiency for the cockpit automated systems	All	34	34	FAA 1996 Automatio n Report	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge Problem Solving Decision Making			

Figure 4.2.10.1 (continued)





#### 4.2.10.2 Error Management

- Filter Evidence Table FAA 1996 Automation Report
- Filter Topics [Error Management]
  - See Figure 4.2.10.2
  - Result FAA 1996 Automation Report Error Management
    - The report recommends educating crews as to hazardous states of awareness and the need for countermeasures to maintain vigilance.
    - Share operational information.
    - At the time of the report the writers acknowledged insufficient countermeasures to address human factor performance issues.
    - Identify and correct pilot insufficient mental models of automation to prevent operational errors.
    - Current evaluation criteria do not address the skills in areas such as automation.
  - Summary The report recognized that monitoring and awareness skills were lacking in the automation environment at the time the report was issued. It begins by recommending education of the "hazardous states of awareness", a term it uses to denote a certain phenomenon with respect to situation awareness. Next it recommends sharing operational information to learn from crew errors, followed by proposing to improve the training of operational understanding of the automated systems in order to improve performance. Finally the report recognizes that the evaluation process simply does not address automation skill and should be modified

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
205	Recommendation SA-8: The FAA should ensure that flightcrews are educated about hazardous states of awareness and the need for countermeasures to maintain vigilance. The FAA should encourage operators to: Develop operational procedures and strategies to foster attention Management skills with the objective of avoiding hazardous states of awareness: and	All	34	All	FAA 1996 Automation Report	MonitoringXchecking Error SA UAS	Error Mgt	Compliance CRM	SA
	Develop techniques to apply during training to identify and minimize hazardous states of awareness.								
206	Recommendation Comm/ Coord-3: The FAA should lead an industry-wide effort to share safety information obtained from in- service data and from difficulties encountered in training. This effort should be capable of assisting in the identification and resolution of problems attributed to flight crew error.	All	34	All	FAA 1996 Automation Report	Criticality	Error Mgt	Mis A/C State Compliance Mis Sys Mis-AFS	All
214	Insufficient criteria, methods, and tools for design, training, and evaluation. Existing methods, data, and tools are inadequate to evaluate and resolve many of the important human performance issues. It is relatively easy to get agreement that Automation should be human-centered, or that potentially hazardous situations should be avoided; it is much more difficult to get agreement on how to accomplish these objectives.	All	34	All	FAA 1996 Automation Report	Competencies	Automation Error Mgt	Mis-AFS Mis-Sys	SA Problem Solving Decision Making Knowledge Flight Management Guidance/Automation
233	Identify and correct oversimplifications in pilots' mental models of system functions.	All	34	All	FAA 1996 Automation Report	Criticality Competencies Knowledge	Automation Error Mgt	Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Knowledge
243	Checkride criteria do not include or emphasize some of the skill areas mentioned above, such as Management of Automation or other known problem areas of line operation.	All	34	34	FAA 1996 Automation Report	Generation Automation Competencies	Automation Error Mgt	Mis-AFS	Flight Management Guidance/Automation Knowledge Problem Solving Decision Making

Figure 4.2.10.2 – Error Management/FAA HF Report

# 4.2.10.3 Manual Aircraft Control

- Filter Evidence Table FAA 1996 Automation Report
- Filter Topics [Manual Aircraft Control]
- Suppress superfluous.
  - See Figure 4.2.10.3
    - Result FAA 1996 Automation Report Manual Aircraft Control
      - Report found that pilots who used automation frequently and/or flew long haul flights experience degradation in manual handling skills.
      - Report recommends that flight crews receive explicit instruction and practice in reverting to manual flight.
    - Summary The FAA 1996 automation report found that pilots who utilized automation frequently and/or flew long haul flights experienced degradation in manual aircraft control skill and recommended explicit instruction and practice in reverting to manual flight path control.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
240	Based on the incident data, accident data, and pilot and operator input evaluated by the HF team the following concerns surfaced: • degradation of manual flying skills of pilots who use Automation frequently, or who participate in long-hau loperations, • A second area of concern is in the skills needed to perform recovery from unusual aircraft attitudes.	All	34	All	FAA 1996 Automation Report	Generation Automation Competencies Upset ManualACControl	Manual AC Control Automation	Upset Mis A/C State	Flight Management Guidance/Automation Manual Aviation Control
241	Flightcrews should explicitly receive instruction and practice in when and how to: (1) appropriately use Automation; (2) transition between various levels of Automation,; and (3) revert to manual flight.	All	34	34	FAA 1996 Automation Report	Generation Automation Competencies	Manual AC Control Automation	Compliance CRM Mis-AFS	Flight Management Guidance/Automation Manual Aviation Control Application of Procedures/Knowledge

Figure 4.2.10.3 - Manual Aircraft Control/FAA HF Report



# 4.2.10.4 Terrain

- Filter Evidence Table FAA 1996 Automation Report
- Filter Topics [Terrain]
  - See Figure 4.2.10.4
  - Result FAA 1996 Automation Report Terrain
    - Report found insufficient terrain awareness sometimes involving loss of control and energy awareness.
    - Recommends increasing flight crew understanding and awareness of the hazards involved in maintaining situation awareness in regards flight path proximity to terrain.
  - Summary The FAA Automation report found disturbing occurrences of lack of situation awareness in regards to flight path proximity to terrain. It recommends increasing the understanding of the crews with regard to this deficiency and the potential risks involved.

r I	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
1	Flightcrew situation awareness issues included vulnerabilities in: • Automation/mode awareness. 94 • Flight path awareness: involving loss of control or controlled flight into Terrain) and energy awareness (especially low energy state).	All	34	34	FAA 1996 Automation Report	Automation Generation SA Error Mgt UAS Competencies	Automation Terrain Error Mgt	Mis-AFS Mis A/C State Terrain	SA Flight Management Guidance/Automation
20	<ul> <li>Recommendation SA-1: The FAA should require operators to increase flightcrews' understanding of and sensitivity to maintaining situation awareness, particularly:</li> <li>Mode and airplane energy awareness issues associated with autoflight systems (i.e., autopilot, autothrottle, flight Management system, and fly-by-wire flight control systems);</li> <li>Position awareness with respect to the intended flight path and proximity to Terrain, obstacles, or traffic; and</li> <li>Potential causes, flight crew detection, and recovery from hazardous pitch or bank angle Upsets while under autopilot control (e.g., wake vortex, subtle autopilot failures, engine failure in cruise, atmospheric turbulence).</li> </ul>	All	34	34	FAA 1996 Automation Report	Automation Upset Generation Error Mgt	Error Mgt Automation Terrain	Mis-AFS Terrain	SA Flight Management Guidance/Automation
20	Recommendation SA-3: The FAA should encourage the aviation industry to develop and implement new concepts to provide better Terrain awareness.	All	34	ALL	FAA 1996 Automation Report	MonitoringXche cking Terrain SA	Terrain	Terrain	SA
2'	Flightcrew situation awareness issues included vulnerabilities in, for example: • Automation/mode awareness. This was an area where we heard a universal message of concern 12 about each of the aircraft in our charter. • Flight path awareness, including insufficient Terrain awareness (sometimes involving loss of control or controlled flight into Terrain) and energy awareness (especially low energy state).	All	34	34	FAA 1996 Automation Report	Terrain SA Automation UAS Competencies	Automation Terrain	Terrain Mis-AFS Mis A/C State	SA Flight Management Guidance/Automation

Figure	4.2.10.4 -	Terrain/FAA	HF Report
iguio	1.2.10.1	1011011/1703	in itopoit

#### 4.2.10.5 Surprise

- Filter Evidence Table FAA 1996 Automation Report
- Filter Topics [Surprise]
  - See Figure 4.2.10.5
  - Result FAA 1996 Automation Report Surprise
    - Pilots can be surprised by subtle behavior, overwhelmed by complexity of current systems operated in current environment.
    - Evidence shows vulnerabilities in pilots' understanding of system behavior creating 'automation surprises' resulting in differing nonstandard set of decisions regarding levels of automation to use and various inappropriate responses.
    - Current training not effectively dealing with flight crew vulnerabilities in above areas.



- Report writers believe that training need better prepare pilots for automation surprises as
  opposed to trial and error on the line.
- Use feedback from line operations in training to better train for surprises.
- Dedicated LOFT type simulator training needs to be developed and implemented to respond to above problems.
- Provide more opportunities to learn and practice as well as promote understanding rather than rote exercises.
- Summary The report found that pilots could be surprised by subtle behavior and overwhelmed by complexity of current systems operated in current flight environment. The evidence shows vulnerabilities to surprise because of incomplete system understanding as well as the lack of appropriate responses in terms of utilizing the appropriate responses in dealing with the situations. The report recommends dedicated LOFT type training to give pilots practice in responding to system surprises, promoting better system understanding through training and developing good decisions and proper execution regarding reversion to appropriate levels of automation when surprises occur.

r	E ef	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
1	95 <sup>h</sup> 0	Processes used for design, training, and regulatory functions nadequately address uman performance issues: users can be surprised by subtle behavior overwhelmed by the complexity embedded in current systems perated within the current operating environment	ALL	34	34	FAA 1996 Automation Report	Automation Generation Error Mgt	Surprise Automation	Ops/Type Spec Mis-AFS	SA Flight Management Guidance/Automation
2	FvsN・li 11vevfi・let	rom the evidence, the HF Team identified issues that show ulnerabilities in flightcrew Management of Automation and ituation awareness. Issues associated with flightcrew danagement of Automation include concerns about: Pilot understanding of the Automation's capabilities, mitations, modes, and operating principles and techniques. The HF Team frequently heard about Automation "surprises," where the Automation behaved in ways the flightcrew did not xpect. "Why did it do that?" "What is it doing now?" and "What will it do next?" were common questions expressed by gliptcrews from operational experience. Differing pilot Decisions about the appropriate Automation evel to use or whether to turn the Automation on or off when nev get into unusual or non-normal situations.	ALL	34	34	FAA 1996 Automation Report	Automation SA Generation Error Mgt	Automation Surprise	Mis-AFS	Flight Management Guidance/Automation Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
2	13 13 13 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Processes used for design, training, and regulatory functions adequately address human performance issues. As a result, isers can be surprised by subtle behavior or overwhelmed by ne complexity embedded in current systems operated within he current operating environment. Process improvements are eeded to provide the framework for consistent application of rrinciples and methods for eliminating vulnerabilities in design, raining, and operations.	ALL	34	ALL	FAA 1996 Automation Report	Automation Competencies	Surprise	Mis A/C State Mis-AFS Mis-Sys	SA Problem Solving Decision Making Knowledge
2	T 19 ii fe	here have been situations where flightcrews have either happropriately continued to use the Automation when they bound themselves in an abnormal situation.	ALL	34	34	FAA 1996 Automation Report	Automation Error Mgt	Automation Surprise	Mis-AFS	Problem Solving Decision Making Knowledge Flight Management Guidance/Automation
2	T 21 s s	The flightcrew must be able to understand the Automation's tatus and behavior, especially during unusual or demanding ituations.	ALL	34	34	FAA 1996 Automation Report	Automation Error SA	Automation Surprise	Mis-AFS Workload Distraction	Flight Management Guidance/Automation Knowledge
2	25   P  i   P	repared by their training (as opposed to "picking it up on the ne"), so that they will be prepared to successfully cope with robable, but unusual situations.	ALL	34		FAA 1996 Automation Report	Competencies Surprise	Automation Surprise	Mis-AFS	Flight Management Guidance/Automation Knowledge
2	30 ti h	Jse Automation surprises that occur on the line as subsequent raining opportunities to learn more about the Automation and low to manage it.	ALL	34	34	FAA 1996 Automation Report	Criticality Competencies	Automation Surprise	Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Knowledge
2	31 e	Support follow-up of Automation surprises in a simulator invironment in LOFT scenarios or line operational evaluations.	ALL	34	34	FAA 1996 Automation Report	Criticality Competencies	Automation Surprise	Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Knowledge
2	32 F h	Provide more opportunities to learn and practice, especially low to handle surprising situations.	ALL	34	All	FAA 1996 Automation Report	Criticality Competencies Surprise	Automation Surprise	Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Knowledge
2	34 F	Promote understanding rather than using rote training.	ALL	34	All	FAA 1996 Automation Report	Criticality Competencies Knowledge	Automation Surprise	Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Knowledge
2	37 ti a	Continuous learning is one way to help ensure that pilots have he Knowledge they will need in order to effectively manage nd use the Automation in a wide range of situations.	ALL	34	All	FAA 1996 Automation Report	Automation Knowledge Criticality Competencies	Automation Surprise	Mis-AFS	Flight Management Guidance/Automation Knowledge

Figure 4.2.10.5 – Surprise/FAA HF Report





#### 4.2.10.6 Leadership

- Filter Evidence Table FAA 1996 Automation Report
- Filter Competencies [Leadership]
  - See Figure 4.2.10.6
  - Result FAA 1996 Automation Report Leadership
    - Important knowledge and skills required in modern automated aircraft include understanding the decision-making process especially in regards to unexpected events; workload and attention management; familiarity with the cognitive processes, especially as they relate to flight crew problem solving in airline operations.
  - Summary The report found that leadership in the complex automated airline environment is especially important. The traits involved relate to understanding the process as well as making good decisions as a team, particularly in unfamiliar situations.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
242	Other important Knowledge and skill areas for flightcrews are: • understanding of Decision making processes (including team Decision making and handling unanticipated events), • workload and attention Management, and • understanding of other human cognitive processes (especially cognitive biases and limitations as they apply to flightcrew problem solving in airline operations).	All	34	All	FAA 1996 Automation Report	Competencies	Surprise Leadership	Workload Distraction	Leadership and Teamwork Problem Solving Decision Making Knowledge

Figure 4.2.10.6 – Leadership/FAA HF Report

#### 4.2.10.7 Mismanaged Aircraft State

- Filter Evidence Table FAA 1996 Automation Report
- Filter Factors [Mis AC State]
- Suppress superfluous.
  - See Figure 4.2.10.7
    - Result FAA 1996 Automation Report Mismanaged Aircraft State
      - Vulnerabilities lie in flight path awareness sometimes involving LOC, terrain and energy awareness.
      - Flight crews are sometimes overwhelmed by subtleties and complexities of automated systems.
      - Based on incident, accident and operational data, recovery skills, (including manual handling) from mismanaged aircraft are not sufficient.
      - The report goes on to recommend regular training to minimize identified vulnerabilities.
    - Summary The report found weakness in prevention of mismanaged aircraft states as well as in the skills to recover from them after entry. The states cited include flight path issues involving loss of control, terrain and energy awareness. Recommendations include regular training to avoid mismanage aircraft states as well as recovery from inadvertent entries.

Ī	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	208	Recommendation Knowledge-3: The FAA should strongly encourage or provide incentives to make advanced maneuvers training an integral part of the training curriculum, especially in recurrent training.	All	34	ALL	FAA 1996 Automation Report	Competencies Generation ManualACControl Upset		Upset Adverse WX Mis A/C State	Manual Aircraft Control
	212	Flightcrew situation awareness issues included vulnerabilities in, for example: • Automation/mode awareness. This was an area where we heard a universal message of concern about each of the aircraft in our charter. • Flight path awareness, including insufficient Terrain awareness (sometimes involving loss of control or controlled flight into Terrain) and energy awareness (especially low energy state).	All	34	34	FAA 1996 Automation Report	Terrain SA Automation UAS Competencies	Automation Terrain	Terrain Mis-AFS Mis A/C State	SA Flight Management Guidance/Automation Manual Aircraft Control
	213	Processes used for design, training, and regulatory functions inadequately address human performance issues. As a result, users can be surprised by suble behavior or overwhelmed by the complexity embedded in current systems operated within the current operating environment. Process improvements are needed to provide the framework for consistent application of principles and methods for eliminating vulnerabilities in design, training, and operations.	All	34	All	FAA 1996 Automation Report	Automation Competencies	Surprise	Mis A/C State Mis-AFS Mis-Sys	SA Problem Solving Decision Making Knowledge
	240	Based on the incident data, accident data, and pilot and operator input evaluated by the HF team the following concerns surfaced: • degradation of manual flying skills of pilots who use Automation frequently, or who participate in long-haul operations, • A second area of concern is in the skills needed to perform recovery from unusual aircraft attitudes.	All	34	All	FAA 1996 Automation Report	Generation Automation Competencies Upset ManualACControl	Manual AC Control Automation	Upset Mis A/C State	Flight Management Guidance/Automation Manual Aircraft Control

Figure 4.2.10.7 – Mismanaged Aircraft State/FAA HF Report



# 4.2.10.8 Upset

- Filter Evidence Table FAA 1996 Automation Report
- Filter Keywords [Upset]
- Suppress superfluous.
  - See Figure 4.2.10.8
  - Result FAA 1996 Automation Report Upset
    - An area of concern is in the skills to detect and recover from unusual attitudes
    - Pilots could benefit from unusual attitude training
    - Recommend increase flight crew understanding and sensitivity in maintaining situation awareness regarding potential causes and detection of upsets from wake vortex, autopilot failures, engine failures and atmospheric disturbances.
    - Further recommend making advance maneuvers a part of training.
  - Summary The FAA automation report cited detection and recovery from unusual attitudes as an area of concern. It went on to recommend increasing flight crew understanding and sensitivity in maintaining situation awareness regarding potential causes and detection of upsets from wake vortex, autopilot failures, engine failures and atmospheric disturbances as well as recommending advance maneuver training an integral part of training.

1	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	201	Recommendation SA-1: The FAA should require operators to increase flightcrews' understanding of and sensitivity to maintaining situation awareness, particularly: • Potential causes, flight crew detection, and recovery from hazardous pitch or bank angle Upsets while under autopilot control (e.g., wake vortex, subtle autopilot failures, engine failure in cruise, atmospheric turbulence).	ALL	34	34	FAA 1996 Automation Report	Automation Upset Generation Error Mgt	Error Mgt Automation Terrain	Mis-AFS Terrain	SA Flight Management Guidance/Automation Knowledge
	208	Recommendation Knowledge-3: The FAA should strongly encourage or provide incentives to make advanced maneuvers training an integral part of the training curriculum, especially in recurrent training.	ALL	34	ALL	FAA 1996 Automation Report	Competencies Generation ManualACControl Upset		Upset Adverse WX Mis A/C State	Manual Aircraft Control
	239	Pilots benefit from increased: Basic airmanship, unusual attitude recovery, CRM, team Decision making, awareness of operational aspects of aircraft design philosophy, Automation and mode Management;	ALL	34	ALL	FAA 1996 Automation Report	Automation Upset Criticality Competencies	Manual AC Control Monitoring Xcheck Error Mgt Leadership	Upset Compliance CRM	SA Leadership and Teamwork Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
	240	Based on the incident data, accident data, and pilot and operator input evaluated by the HF team the following concerns surfaced: • degradation of manual flying skills of pilots who use Automation frequently, or who participate in long-haul operations, • A second area of concern is in the skills needed to perform recovery from unusual aircraft attitudes.	ALL	34	ALL	FAA 1996 Automation Report	Generation Automation Competencies Upset ManualACControl	Manual AC Control Automation	Upset Mis A/C State	Flight Management Guidance/Automation Manual Aircraft Control

Figure 4.2.10.8 – Upset/FAA HF Report

#### 4.2.10.9 Generational Aspects

- Filter Evidence Table FAA 1996 Automation Report
- Filter Keywords [Generation] combine with...
- Filter Topics [Automation]
- Suppress superfluous.
  - See Figure 4.2.10.9
  - Result FAA 1996 Automation Report Generation
    - Situation awareness and automation issues include a general understanding of capabilities, limitations and modes, in addition to hazards of non-standard utilization.
    - Pilot vulnerabilities are flight path, terrain and energy awareness.
    - Pilot training needs to address the fact that pilots are surprised by subtle behavior and complexities of automation.
    - Training should focus on design principles that have operational consequences.
    - Existing methods of assessment are inadequate to evaluate human performance issues.
    - Current regulations have not kept pace with technical and human factors issues. Flight crew training needs to be re-balanced to cover automation issues.
    - The report recommends training to enhance mode and position awareness. In addition, training in the detection and recovery from hazardous conditions concerning traffic, terrain and upset is needed while using autoflight systems.
    - The report recommends reassessing requirements of initial and recurrent training to ensure that there is adequate content addressing mode and automation awareness, basic airmanship, CRM, and decision-making Training should include exposure to unanticipated events and workload/task management.
    - The report recommends that airman certification criteria be amended so that pilots have appropriate automation skills.
    - Pilots use automation when the situation requires a reversion to manual flight.
    - The emphasis in training should be on learning, instead of checking.
    - Regulated training and checking maneuvers should be evaluated for relevance and phased out if not appropriate.
    - Training should be adapted to background of trainees.
  - Summary The FAA automation report found that pilots have various situation awareness issues with automation. Pilots need a general understanding of capabilities, limitations and modes, in addition to hazards of non-standard utilization. They are vulnerable to lack of flight path and energy awareness when using autoflight. In addition they are surprised by the subtleties and complexities of automation and the training courses fail to focus on operational principles of the autoflight architecture. Many pilots use the autoflight when inappropriate and fail to revert to manual flight. The training courses at the time of the study tended to be checking rather than learning oriented and had not kept pace with human factor issues in regard to automation, particularly with regard to terrain, energy and upset. In addition, the report recommends that there be adequate training content to ensure airmanship, CRM, decision-making, workload/task management when utilizing automation especially in demanding situations. Care should be taken to adapt training to the background of trainees. On the other hand, maneuvers not relevant to Gen 3 and 4 should be eliminated from checking. While using automation pilots continue to have difficulties detecting deviations from desired energy states and trajectories.

**Note:** Fig 4.2.10.1 and Fig 4.2.10.9 are the support tables for Generational Aspects (See fig 4.2.10.1 above) as these two tables contain the same evidence statements when filtering by generation + automation.



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Key Words	Training Topics	Factors	Competencies
208	Recommendation Knowlege-3: The FAA should strongly encourage or provide incentives to make advanced maneuvers training an integral part of the training curriculum, especially in recurrent training.	All	34	All	FAA 1996 Automation Report	Competencies Generation Manual AC Control Upset		Upset Adverse WX Mis A/C State	Manual Aircraft Control
244	Maneuvers included in checkrides should be evaluated for continued relevance, be phased out.	All	34	All	FAA 1996 Automation Report	Competencies Generation			All
245	Training should also be adapted to the background of the pilot.	All	34	All	FAA 1996 Automation Report	Competencies Generation			

Figure 4.2.10.9 – Generational Aspects/FAA HF Report

# 4.2.10.10 Training Effect

- Filter Evidence Table FAA 1996 Automation Report
- Filter result for Keywords [Criticality]
- Combine with Search [Train]
- Suppress superfluous.
  - See Figure 4.2.10.10
  - Result FAA 1996 Automation Report Training Effect
    - Ensure flight crews are educated about hazardous states of awareness in terms of identification of them and need for countermeasures to maintain vigilance.
    - Ensure content of training courses contain automation management including transitioning between levels of automation, basic airmanship, CRM, decision making including unexpected events, and workload and task management.
    - Training courses should be rebalanced to ensure proper coverage of automation.
    - Pilots should practice what they lean in LOFT type training.
    - Training should include 'automation surprises' that occur in line operations.
    - Provide an accurate and operational mental model of automation.
    - Emphasize understanding rather than rote memorization.
  - Summary The FAA 1996 automation report strongly emphasizes the effect of training and recommends major changes quite specifically in order to enhance operational safety. The report firstly promotes education regarding what it calls hazardous states of awareness in automated aircraft and promotes training to identify these states and stresses countermeasures to maintain vigilance. Training should include automation management including transitioning between levels of automation, basic airmanship, CRM, decision making including unexpected events, and workload and task management. The elements learned should also be practiced in LOFT type scenarios including unanticipated events taken from actual operational situations. The report goes on to recommend that training provide and accurate operational model of the automation for pilots so as to be able to cope with its management particularly in terms of levels of appropriate usage.



	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
2	205	Recommendation SA-8: The FAA should ensure that flightcrews are educated about hazardous states of awareness and the need for countermeasures to maintain vigilance. The FAA should encourage operators to: - Develop operational procedures and strategies to foster attention Management skills with the objective of avoiding hazardous states of awareness; and - Develop techniques to apply during training to identify and minimize hazardous states of awareness.	ALL	34	All	FAA 1996 Automation Report	MonitoringXchecking Error SA UAS	Error Mgt	Compliance CRM	SA
2	207	Recommendation Knowledge-2: The FAA should reassess the requirements that determine the content, length, and type of initial and recurrent flightcrew training. Ensure that the content appropriately includes: • Management and use of Automation, including mental models of the Automation and moving between levels of Automation; • Flightcrew situation awareness, including mode and Automation awareness; • Basic airmanship; • Crew Resource Management; • Decision making, including unanticipated event training; • Examples of specific difficulties encountered either in service or in training; and • Workload Management (task Management).	ALL	34	All	FAA 1996 Automation Report	Automation Competencies Generation SA	Leadership Automation	Compliance CRM	SA Problem Solving Decision Making Workload Management
2	208	Recommendation Knowledge-3: The FAA should strongly encourage or provide incentives to make advanced maneuvers training an integral part of the training curriculum, especially in recurrent training.	ALL	34	All	FAA 1996 Automation Report	Competencies Generation ManualACControl Upset		Upset Adverse WX Mis A/C State	Manual AC Control
2	216	Flightcrew training investments should be re-balanced to ensure appropriate coverage of Automation issues.	ALL	34	34	FAA 1996 Automation Report	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation
2	220	Flightcrews should be given sufficient training on using the FMS to ensure proficiency at least for those capabilities used in normal day-to-day operations. The HF Team considers the practice of expecting flightcrews to acquire these basic skills while flying the line to be inappropriate.	ALL	34	34	FAA 1996 Automation Report	Automation Competencies	Automation Terrain Error Mgt	Mis-AFS	Flight Management Guidance/Automation
2	226	Pilots must have the opportunities to practice what they have learned in realistic operational settings through Line Operational Simulations (LOS) and LOFT scenarios: • Oreate a larger set of line-oriented scenarios to practice • Update these scenarios regularly to reflect the latest information about vulnerabilities from incident reporting systems or other sources. • Expand scenarios to focus more on unique error-vulnerable situations.	ALL	34	ALL	FAA 1996 Automation Report	Error	Automation Surprise	Mis-AFS Workload Distraction	Flight Management Guidance/Automation Knowledge Problem Solving Decision Making
2	230	Use Automation surprises that occur on the line as subsequent training opportunities to learn more about the Automation and how to manage it.	ALL	34	34	FAA 1996 Automation Report	Criticality Competencies	Automation Surprise	Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Knowledge
2	232	Provide more opportunities to learn and practice, especially how to handle surprising situations.	ALL	34	ALL	FAA 1996 Automation Report	Criticality Competencies Surprise	Automation Surprise	Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Knowledge
2	233	Identify and correct oversimplifications in pilots' mental models of system functions.	ALL	34	ALL	FAA 1996 Automation Report	Criticality Competencies Knowledge	Automation Error Mgt ManACControl	Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Knowledge
2	234	Promote understanding rather than using rote training.	ALL	34	ALL	FAA 1996 Automation Report	Criticality Competencies Knowledge	Automation Surprise	Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Knowledge
2	238	Initial and recurrent training should provide a clear understanding of operationally relevant Automation principles and ensure user proficiency for the cockpit automated systems	ALL	34	34	FAA 1996 Automation Report	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge Problem Solving Decision Making
2	239	Pilots benefit from increased: Basic airmanship, unusual attitude recovery, CRM, team Decision making, awareness of operational aspects of aircraft design philosophy, Automation and mode Management;	ALL	34	ALL	FAA 1996 Automation Report	Automation Upset Criticality Competencies	Manual AC Control Monitoring Xcheck Error Mgt Leadership	Upset Compliance CRM	SA Leadership and Teamwork Problem Solving Decision Making Flight Management Guidance/Automation Manual AC Control

Figure 4.2.10.10 – Training Effect/FAA HF Report



# 4.2.11 Automation Training Practitioners' Guide

#### 4.2.11.1 Automation

- Filter Evidence Table Automation Training Practitioners' Guide
- Filter Keywords [Automation]
- See Figure 4.2.11.1
  - Result Automation Training Practitioners' Guide Automation
    - There is strong support for a new training concept
    - Training should be adapted to the individual.
    - Trainees need to understand why the automation system behaves and not just what the expected outcome is
    - CRM should be integrated throughout training.
    - Trainees should be taught all critical information, what they "need to know"
    - Automation monitoring should be a facet of all training programs.
    - Multiple assessment techniques are required to ascertain the acquisition of knowledge and competency.
    - Pilots need to understand the logic, design function and limitations of automation.
    - Pilots need to practice appropriate use of automation, transition between levels of automation and reversion to manual flight.
  - Summary The Automation Training Practitioners' Guide advocates a new training concept. Specifically it recommends training in blocks, adapting to individual trainees, integrating CRM throughout training, and major emphasis on the "need to know" items. In addition it recommends using multiple assessment techniques, confirming that pilots understand the logic, design purpose and limitations of the automation. Lastly it recommends practice in operational setting of managing automation throughout the various levels including eversion to manual flight.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
59	Strong support for a new kind of training concept: Scenario-based, matter brought in blocks, gradually, adapted individually. Teach Automation Knowledge, the why's. Teach and test the conceptual Knowledge.	All	All	All	Automation Lyall	Automation		Mis-AFS	Knowledge Flight Management Guidance/Automation
61	Good CRM is especially important in automated aircraft; CRM should be integrated and used throughout the training.	All	All	34	Automation Lyall	Automation	Automation	CRM Workload Distraction Mis A/C State	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
62	Decide what pilots really need to learn about the Automation. (don't try to teach everything).	All	All	34	Automation Lyall	Automation Error MonitoringXchecki ng	Automation	CRM	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management/Guidance Automation
63	Train also to monitor Automation. (This point is strongly underlined by the LOSA data	All	All	34	Automation Lyall	Automation	Automation Monitoring Xcheck	Compliance CRM Workload Distraction	SA Communication Flight Management Guidance/Automation
64	Use multiple assessment techniques to evaluate Automation Knowledge.	All	All	34	Automation Lyall	Automation	Automation		Knowledge Flight Management Guidance/Automation
65	Pilots need to be taught how the components of Automation work together in the overall system.	All	All	34	Automation Lyall	Automation	Automation		Knowledge Flight Management Guidance/Automation
66	Provide as much hands-on experience with the Automation as possible. (One cannot learn by just watching).	All	All	34	Automation Lyall	Automation	Automation		Flight Management Guidance/Automation
68	Teach the logic underlying the Automation and cover its limitations	All	All	34	Automation Lyall	Automation	Automation		Knowledge Flight Management Guidance/Automation
69	Flight crews should explicitly receive instruction and practice in when and how to:a. Appropriately use Automation;b. Transition between levels of Automation.Revert to manual flight."	All	All	34	Automation Lyall	Automation ManualACControl	Automation	Mis-AFS	Knowledge SA Problem Solving Decision Making Manual Aircraft Control Flight Management Guidance/Automation

Figure 4.2.11.1 – Automation/Automation Guide

#### 4.2.11.2 Error Management

- Filter Evidence Table Automation Training Practitioners' Guide
- Filter Topics [Error Management] combine with
- Filter Factors [CRM]
  - See Figure 4.2.11.2
  - Result Automation Training Practitioners' Guide Error Management
    - Good CRM is especially important in automated aircraft.
    - Training should address the monitoring and cross-checking of tasks where automation systems are involved
    - In order to manage automation errors in is important to know how and when to transition levels of automation, in addition to reversions to manual flight.
  - Summary The Automation Training Practitioners' Guide stresses that good CRM is particularly important with automation. It espouses monitoring of automation and notes that this skill must be taught and practiced. Finally it points that in order to deal with unexpected situations, including crew errors, pilots must be skilled in managing the transition between the various levels of automation including reversion to manual flight.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
61	Good CRM is especially important in automated aircraft; CRM should be integrated and used throughout the training.	All	All	34	Automation Lyall	Automation	Automation	CRM Workload Distraction Mis A/C State	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
63	Train also to monitor Automation. (This point is strongly underlined by the LOSA data	All	All	34	Automation Lyall	Automation	Automation Monitoring Xcheck Error Mgt	Compliance CRM Workload Distraction	SA Communication Flight Management Guidance/Automation
69	Flight crews should explicitly receive instruction and practice in when and how to:a. Appropriately use Automation,b. Transition between levels of Automation.Revert to manual flight."	All	All	34	Automation Lyall	Automation ManualACControl	Automation	Mis-AFS	Knowledge SA Problem Solving Decision Making Manual Aircraft Control Flight Management Guidance/Automation

Figure 4.2.11.2 - Error Management/Automation Guide



# 4.2.11.3 Manual Aircraft Control

- Filter Evidence Table Automation Training Practitioners' Guide
- Filter result for Topics [Manual Aircraft Control]
  - See Figure 4.2.11.3
  - Result Automation Training Practitioners' Guide Manual Aircraft Control
    - Ensure flights crew can fly manually without automation.
    - Flight crews need instruction, practice and assessment on being able to revert to manual flight.
  - Summary The Automation Training Practitioners' Guide explicitly states that flight crews need to be able to fly manually in automated aircraft. It continues by saying that trainees should receive instruction on when and how to revert to manual flight and practice accordingly in training.

K	E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
	60	Make sure flight crews learn to fly manually without the Automation.	All	All	34	Automation Lyall	ManualACControl Automation	Manual AC Control Automation	Mis-AFS Pilot Incap	Manual Aircraft Control Flight Management Guidance/Automation
	69	Flight crews should explicitly receive instruction and practice in when and how to: a. Appropriately use Automation; b. Transition between levels of Automation.Revert to manual flight."	All	All	34	Automation Lyall	Automation ManualACControl	Automation Error Mgt Manual AC Control	Mis-AFS	Knowledge SA Problem Solving Decision Making Manual Aircraft Control Flight Management Guidance/ Automation

Figure 4.2.11.3 - Manual Aircraft Control/Automation Guide

#### 4.2.11.4 Generational Aspects

- Filter Evidence Table Automation Training Practitioners' Guide
- Filter Applicability to Gens [34]
- Suppress Superfluous.
- See Figure 4.2.11.4
  - o Result Automation Training Practitioners' Guide Generational Aspects
    - There is strong support for a new training concept
    - Training should be adapted to the individual.
    - Trainees need to understand why the automation system behaves and not just what the expected outcome is
    - CRM should be integrated throughout training.
    - Trainees should be taught all critical information, what they "need to know"
    - Automation monitoring should be a facet of all training programs.
    - Multiple assessment techniques are required to ascertain the acquisition of knowledge and competency.
    - Pilots need to understand the logic, design function and limitations of automation.
    - Pilots need to practice appropriate use of automation, transition between levels of automation and reversion to manual flight.
  - Summary The Automation Training Practitioners' Guide advocates a new training concept, adapted to Gen 3 and gen 4 aircraft. Specifically it recommends training in blocks, adapting to individual trainees, integrating CRM throughout training, and major emphasis on the "need to know" items. In addition it recommends using multiple assessment techniques, confirming that pilots understand the logic, design purpose and limitations of the automation. Lastly it recommends practice in operational setting of managing automation throughout the various levels including eversion to manual flight.

e re	E Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Training Topics	Factors	Competencies
5	Strong support for a new kind of training concept: Scenario- tige based, matter brought in blocks, gradually, adapted individually. Teach Automation Knowledge, [betails: see Lyall] and test the conceptual Knowledge. [details: see Lyall]	Ali	All	All	Automation Lyall	Automation Generation	Manual AC Control Automation		Mis-AFS	Knowledge Flight Management Guidance/Automation
6	Make sure flight crews learn to fly manually without the Automation.	All	All	34	Automation Lyall	ManualACControl Automation Generation	Automation Error Mgt	Manual AC Control Automation	Mis-AFS Pilot Incap	Manual AC Control Flight Management Guidance/ Automation
6	Good CRM is especially important in automated aircraft; CRM should be integrated and used throughout the training.	All	All	34	Automation Lyall	Automation Generation	Automation Monitoring Xcheck Error Mgt	Automation Error Mgt	CRM Workload Distraction Mis A/C State	SA Leadership and Tearnwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance/ Automation
6	2 Decide what pilots really need to learn about the Automation. (don't try to teach everything).	All	All	34	Automation Lyall	Automation Error MonitoringXchec k Generation	Automation	Automation	CRM	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Communication Decision Making Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
6	Train also to monitor Automation. (This point is strongly underlined by the LOSA data	All	All	34	Automation Lyall	Automation Generation	Automation	Automation Monitoring Xcheck Error Mgt	Compliance CRM Workload Distraction	SA Communication Flight Management Guidance/Automation
6	Pilots need to be taught how the components of Automation work together in the overall system.	All	All	34	Automation Lyall	Automation Generation	Automation	Automation		Knowledge Flight Management Guidance/Automation
6	Teach the logic underlying the Automation and cover its limitations	All	All	34	Automation Lyall	Automation Generation	Automation Error Mgt Manual AC Control	Automation		Knowledge Flight Management Guidance/Automation
6	Flight crews should explicitly receive instruction and practice in when and how to: a. Appropriately use Automation, Transition between levels of Automation.Revert to manual flight."	All	All	34	Automation Lyall	Automation ManualACControl generation	Automation Error Mgt Manual AC Control	Automation Error Mgt Manual AC Control	Mis-AFS	Knowledge SA Problem Solving Decision Making Manual Aircraft Control Flight Management Guidance/Automation

Figure 4.2.11.4 - Generational Aspects/Automation Guide


## 4.2.11.5 Training Effect

- Filter Evidence Table Automation Training Practitioners' Guide
- Filter result for Key Words [Training]
  - See Figure 4.2.11.5
  - Result Automation Training Practitioners' Guide Training Effect
    - Ensure that flight crews learn to fly manually without the automation.
    - CRM is integrated throughout training.
    - Train monitoring of the automation.
    - Pilots need to understand the logic, design function and limitations of automation.
    - Pilots need to practice appropriate use of automation, transition between levels of automation and reversion to manual flight
  - Summary The Automation Training Practitioners' Guide specifies certain training to effect improved operational safety with regard to automation. The guide states that automation safety depends on teaching flight crews to effectively fly manually. CRM should be integrated throughout training and monitoring of the automation does not come automatically, it must be taught. Pilots need to have hands on experience using the autoflight and should be given practice, particularly in mode transitions and reversions. Finally the pilots must understand the logic, design and the limitations of the automation in order to respond appropriately in various situations.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
60	Make sure flight crews learn to fly manually without the Automation.	All	All	34	Automation Lyall	ManualACControl Automation Generation Training	Manual AC Control Automation	Mis-AFS Pilot Incap	Manual Aircraft Control Flight Managemen/Guidance/Automation
61	Good CRM is especially important in automated aircraft; CRM should be integrated and used throughout the training.	All	All	34	Automation Lyall	Automation Generation Training	Automation Error Mgt	CRM Workload Distraction Mis A/C State	SA Leadership and Tearnwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
63	Train also to monitor Automation. (This point is strongly underlined by the LOSA data	All	All	34	Automation Lyall	Automation Generation Training	Automation Monitoring Xcheck Error Mgt	Compliance CRM Workload Distraction	SA Communication Flight Management Guidance/Automation
65	Pilots need to be taught how the components of Automation work together in the overall system.	All	All	34	Automation Lyall	Automation Generation Training	Automation		Knowledge Flight Management Guidance/Automation
66	Provide as much hands-on experience with the Automation as possible. (One cannot learn by just watching).	All	All	34	Automation Lyall	Automation Generation Training	Automation		Flight Management Guidance/Automation
68	Teach the logic underlying the Automation and cover its limitations	All	All	34	Automation Lyall	Automation Generation Training	Automation		Knowledge Flight Management Guidance/Automation
69	Flight crews should explicitly receive instruction and practice in when and how to:a. Appropriately use Automation;b. Transition between levels of Automation.Revert to manual flight.*	All	All	34	Automation Lyall	Automation ManualACControl Generation Training	Automation Error Mgt Manual AC Control	Mis-AFS	Knowledge SA Problem Solving Decision Making Manual Aircraft Control Flight Management Guidance/Automation Manual Aircraft Control

Figure 4.2.11.5

## 4.2.12 TAWS Saves

### 4.2.12.1 Terrain

- Filter Evidence Table TAWS Saves
- Filter Topics [Terrain]
- See Figure 4.2.12.1
  - Result TAWS Saves Terrain
    - EGPWS has entered commercial aviation in the last decade and to a great extent has minimized CFIT accidents.
    - The TAWS Saves confirms that it is and effective safety tool but it still depends on trained crew actions to pull up when the warning occurs.
  - Summary The TAWS Saves report is essentially an accident report without an accident. Five incidents that the writers of the report felt would probably have resulted in accidents are studied in an accident-investigation format. Two major points emerge from this report. Firstly, a proper EGPWS is an effective tool in reducing CFIT accidents and secondly, that no matter how good the warning system is, terrain avoidance still depends on a properly trained reaction of the flight crew.

E rei	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
294	EGPWS / TAWS technology has entered airline and corporate porrations during the last five years; to date no aircraft fitted with such a system has been involved in a CFIT accident.	Ali	All	All	TAWS Saves	Terrain	Landing Issues Terrain	Mis A/C State	
29	The 'saves' confirm that TAWS is a very effective safety tool yet it 5 still depends on crew action for the last defence; always pull up when a warning is given.	APR	All	Ali	TAWS Saves	Terrain	Terrain	Terrain Compliance	SA Application of Procedures/Knowledge

Figure 4.2.12.1 - Terrain/TAWS Saves



## 4.2.13 Accident Data Using Augmented Cast Data

### 4.2.13.1 Manual Aircraft Control

- Filter Evidence Table Pilot Survey
- Filter Keywords [Manual Aircraft Control]
  - See Figure 4.2.13.1c
  - Result Augmented CAST Data Manual Aircraft Control
    - In the decades 2000 and 2010, runway excursions accounted for around 23% of total accidents.
    - In the decade from 2000 to 2010, landing short accidents or undershoots tripled from the previous decade and accounted for 8% of total accidents.



Figure 4.2.13.1

 Runway accidents in general have increased significantly to almost 50% of all accidents in the last 10 years.





Figure 4.2.13.1a

 Summary – A review of accident data over the last 20 years from the CAST archives, augmented with NTSB data from 2009 and 2010, indicates a significant rise in events during flight phases where, pilots always or usually often fly the aircraft manually (take-off, landing and taxying). While a definitive conclusion relating to the deterioration of manual control skills cannot be made directly, the trend is consistent with this hypothesis and supported by many other sources.



Figure 4.2.13.1b



E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
283	Runway Excursion, together with Controlled Flight Into Terrain (CFIT), Loss Of Control (LOC), System/Component Failure (SCF) and Abnormal Runway Contact (ARC) accounted for 78% of all accidents.	All	All	All	CAST+	ManualACControl	Manual AC Control Runway Issues Landing Issues System Malfunction	Upset Syst mal Mis A/C State	ALL
284	Runway excursion (RE), which accounted for 26% of all accidents between 1991 and 2000, increased by almost 10% in the 2001- 2010 period	TO LDG	All	All	CAST+	ManualACControl	Manual AC Control Landing Issues	Mis A/C State	
285	Between the 90 decade and 2000 decade CFIT decreased 17% to 9%	All	All	All	CAST+	Terrain	Manual AC Control Runway Issues Landing Issues	Terrain	SA
289	Between the 90 decade and 2000 decade Land Short or Undershoot Runway Excursions doubled from 3% to 7% (Manual Handling)	APP LDG	All	All	CAST+	ManualACControl	Manual AC Control Runway Issues	Mis A/C State	Manual Aircraft Control SA
290	Looking at Runway Issues comparing the 90 decade and the 2000 decade, the percentage of accidents for wihich runway issues were considered causal was almost 50% (47% and 49%)	TO LDG	All	All	CAST+	ManualACControl	Manual AC Control Landing Issues	Mis A/C State	Manual Aircraft Control SA
291	Undershoot emerged as important categories (ie > 5%) during the 2000 decade a 8%	TAXI	All	All	CAST+	ManualACControl	Manual AC Control Landing Issues	Mis A/C State	Manual Aircraft Control SA
292	Over the last 20 years, 84% of all accidents happened during the approach/ landing or takeoff/climb phases. The approach/landing is by far the most critical of the flight phases, accounting for 63% of all occurrences. The takeoff/climb phase is the second most hazardous phase, accounting for 21% of all events.	APP LDG TO CLB	All	All	CAST+	Phase	Manual AC Control Landing Issues	Mis A/C State	Manual Aircraft Control SA

## 4.2.13.2 System Malfunction

- Filter Evidence Table Pilot Survey
- Filter Topics [Sys Mal]
  - See Figure 4.2.13.2
    - Result Augmented CAST Data System Malfunction
      - System Malfunction ranks as a major accident category.
        - System malfunctions as an accident category remains significant but has decreased somewhat from 14% and 11% in the last 20 years. (See Fig 4.2.13.1)
    - Summary While system malfunctions still rank as a major cause of accidents at around 11% to 14%.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
283	Runway Excursion, together with Controlled Flight Into Terrain (CFIT), Loss Of Control (LOC), System/Component Failure (SCF) and Abnormal Runway Contact (ARC) accounted for 78% of all accidents.	ALL	All	All	CAST+	ManualACControl	Manual Handling Runway Issues Landing Issues System Malfunction	Upset System Malfunction Mis A/C State	All
287	Between the 90 decade and 2000 decade System Malfunction accidents decreased (14% to 11%)	ALL	All	All	CAST+		System Malfunction	System Malfunction	

Figure 4.2.13.2 – System Malfunction/CAST+Data



## 4.2.13.3 Upset

- Filter Evidence Table Pilot Survey
- Filter Factors [Upset]
  - See Figure 4.2.13.3
  - Result Augmented CAST Data Upset
    - Upset ranks as a major accident category.
    - Upset as an accident category has on average shown a slight increase in the last 20 years.
  - Summary Upset still ranks as a major cause of accidents. its percentage of total accidents has remained steady at around 13% in the last two decades.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
286	Between the 90 decade and 2000 decade Loss or Control accidents remained steady at around 13%.	ALL	All	All	CAST+		Terrain	Upset Mis A/C State	All

Figure 4.2.13.3 - Upset/CAST+Data

### 4.2.13.4 Landing Issues

- Filter Evidence Table Pilot Survey
- Filter result for Topics [Landing Issues]
  - See Figure 4.2.13.4a
  - Result Augmented CAST Data Landing Issues
    - Runway Excursions (majority on landing) accounted for 26% of all accidents in the last decade and increase of 10% over the previous decade.
    - In the last decade landing short (undershoots) were 7%, more than double the previous decade.
    - Runway issues (majority on landing) accounted for almost 50% of all accidents. (See Fig 4.2.13.1)
    - The phase with the highest percentage of accidents is the landing phase at 41%.



Figure 4.2.13.4

Summary – Landing issues are a major component of all aircraft accidents and are increasing, according to the data from the last 2 decades. 41% of all accidents happen in the landing phase, by far the leading phase in which accidents occur. In the last two decades the statistics show a significant increase in the proportion of accidents related to various landing issues, particularly with regard to runway excursions and landing short.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
283	Rumway Excursion, together with Controlled Flight Into Terrain (CFIT), Loss Of Control (LOC), System/Component Failure (SCF) and Abnormal Runway Contact (ARC) accounted for 78% of all accidents.	ALL	All	All	CAST+	ManualACControl	Manual Handling Runway Issues Landing Issues System Malfunction	Upset System Malfunction Mis A/C State	All
284	Runway excursion (RE), which accounted for 26% of all accidents between 1991 and 2000, increased by almost 10% in the 2001- 2010 period	TO LDG	All	All	CAST+	ManualACControl	Manual Handling Landing Issues	Mis A/C State	Manual AC Control SA
289	Between the 90 decade and 2000 decade Land Short or Undershoot Runway Excursions doubled from 3% to 7% (Manual Handling)	APR LDG	All	All	CAST+	ManualACControl	Manual Handling Runway Issues	Mis A/C State	Manual AC Control SA
290	Looking at Runway Issues comparing the 90 decade and the 2000 decade, the percentage of accidents for wihich runway issues were considered causal was almost 50% (47% and 49%)	TO LDG	All	All	CAST+	ManualACControl	Manual Handling Landing Issues	Mis A/C State	Manual AC Control SA
291	Undershoot emerged as important categories (ie > 5%) during the 2000 decade a 8%	TAXI	All	All	CAST+	ManualACControl	Manual Handling Landing Issues	Mis A/C State	Manual AC Control SA
293	Accidents by Phase: o Parking/Taxi 4% o Takeed/Initial Climb 16% o Climb 5% o Cruise 7% o Descent 5% o Approach & GA 22% (GA 3%) o Landing 41%	ALL	All	All	CAST+	Phase	Landing Issues Unstable APP	Mis A/C State	All

Figure 4.2.13.4a - Landing Issues/CAST+Data

### 4.2.13.5 Mismanaged Aircraft State

- Filter Evidence Table Pilot Survey
- Filter result for Factors [Mis A/C State]
  - See Figure 4.2.13.5
  - Result Augmented CAST Data Mismanaged Aircraft State
    - In the last 10 years runway excursions accounted for 26% of all accidents
    - In the last decade landing short (undershoots) were 7%, more than double the previous decade and emerged as a major accident category.
    - Runway issues (majority on landing) accounted for almost 50% of all accidents.
  - Summary Even though the accident rate has decreased in the last 20 years, the rate of accidents due to a "mismanaged aircraft state" has increased. Runway excursions, landing short and ground collision are all up and exemplify this trend.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
282	From 1991 to 2010, Runway Excursion (RE) represented by far the main accident category, accounting for 28% of all events.	TO LDG	All	All	CAST+	ManualACControl	Landing Issues	Mis A/C State	
283	Runway Excursion, together with Controlled Flight Into Terrain (CFIT), Loss Of Control (LOC), System/Component Failure (SCF) and Abnormal Runway Contact (ARC) accounted for 78% of all accidents.	ALL	All	All	CAST+	ManualACControl	Manual Handling Landing Issues System Malfunction	Landing problems Upset System Malfunction Mis A/C State	All
284	Runway excursion (RE), which accounted for 26% of all accidents between 1991 and 2000, increased by almost 10% in the 2001- 2010 period	TO LDG	All	All	CAST+	ManualACControl	Manual Handling Landing Issues	Mis A/C State	
289	Between the 90 decade and 2000 decade Land Short or Undershoot Runway Excursions doubled from 3% to 7% (Manual Handling)	APR LDG	All	All	CAST+	ManualACControl	Manual Handling Runway Issues	Mis A/C State	Manual AC Control SA
290	Looking at Runway Issues comparing the 90 decade and the 2000 decade, the percentage of accidents for wihich runway issues were considered causal was almost 50% (47% and 49%)	TO LDG	All	All	CAST+	ManualACControl	Manual Handling Landing Issues	Mis A/C State	Manual AC Control SA
291	Undershoot emerged as important categories (ie > 5%) during the 2000 decade a 8%	TAXI	All	All	CAST+	ManualACControl	Manual Handling Landing Issues	Mis A/C State	Manual AC Control SA

Figure 4.2.13.5 - Mismanaged Aircraft State/CAST+Data



## 4.2.13.6 Phases of Flight

- Filter Evidence Table Pilot Survey
- Filter Keywords [Phase]
  - See Figure 4.2.13.6
  - Result Augmented CAST Data Phases of Flight
    - In the last 20 years over 84% of all accidents during the approach/landing or the take-off/climb phases. (See Fig 4.12.4a)
    - The approach/landing accounted for more than 63% of all accidents.
    - The landing phase has by far the most accidents at 41%
    - The take-off/climb phase is second with 21% of all accidents.
    - 4% of all accidents take place in taxi phases of flight.
  - Summary 84% of all accidents occur in the APP/LDG phases of flight or in the TO/CLB with the leading phase being LDG at 41%. The phases of flight, which show an increasing trend in terms of percentage of total accidents, are LDG and TAXI.

E ref	Evidence Statement	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
292	Over the last 20 years, 84% of all accidents happened during the approach/ landing or takeoff/climb phases. The approach/landing is by far the most critical of the flight phases, accounting for 63% of all occurrences. The takeoff/climb phase is the second most hazardous phase, accounting for 21% of all events.	APR LDG TO CLB	All	All	CAST	Phase	Manual AC Control Landing Issues	Mis A/C State	Manual AC Control SA
293	Accidents by Phase: o Parking/Taxi 4% o Takeoff/Initial Climb 16% o Climb 5% o Cruise 7% o Descent 5% o Approach & GA 22% (GA 3%) o Landing 41%	ALL	All	All	CAST	Phase	Landing Issues Unstable APP	Mis A/C State	All

Figure 4.2.13.6 – Phases of Flight/CAST+Data

## **GLOSSARY OF TERMS**

### ACRONYMS

A/C	Aircraft
ACAS	Airborne Collision Avoidance System
AirFASE	EBT Flight Data Analysis tool used in this report
AQP	Advanced Qualification Program
ATA	Air Transport Association
ATC	Air Traffic Control
ATO	Approved Training Organization
ATQP	Alternative Training and Qualification Program
CAA	Civil Aviation Authority
CRM	Crew Resource Management
EBT	Evidence-Based Training
FDA	Flight Data Analysis
FMS	Flight Management System
FOQA	Flight Operations Quality Assurance
FSTD	Flight Simulation Training Device
IOE	Initial Operating Experience
LOFS	Line Orientated Flight Scenario
LOFT	Line Oriented Flight Training
LOSA	Line Operational Safety Audit
PF	Pilot Flying
PIC	Pilot-in-Command
PM	Pilot Monitoring
PNF	Pilot Not Flying (former term for PM)
QAR	Quick Access Recorder
SOP	Standard Operating Procedure
STEADES	IATA Safety Trend Evaluation, Analysis and Data Exchange System
TEM	Threat and Error Management
TCS	Training Criticality Survey
UAS	Undesired Aircraft State

## **FLIGHT PHASE ABBREVIATIONS**

The following abbreviations are used in this document. For full details see ICAO Doc 9995 3.3.3 GND Pre-flight, taxi, post-flight

ТО	Take-off
CLB	Climb
CRZ	Cruise
DES	Descent
APP	Approach
LDG	Landing



## DEFINITIONS

**Assessment.** The determination as to whether a candidate meets the requirements of the competency standard.

**ATA Chapters.** The chapter numbering system controlled and published by the Air Transport Association, which provides a common referencing standard for all commercial aircraft documentation.

**Behavior.** The way a person responds, either overtly or covertly, to a specific set of conditions, which is capable of being measured.

**Behavioral indicator.** An overt action performed or statement made by any flight crewmember that indicates how the crew is handling the event.

*Competency.* A combination of skills, knowledge and attitudes required to perform a task to the prescribed standard.

**Competency-based training.** Training and assessment that are characterized by a performance orientation, emphasis on standards of performance and their measurement and the development of training to the specified performance standards.

**Core competencies.** A group of related behaviors, based on job requirements, which describe how to effectively perform a job. They describe what proficient performance looks like. They include the name of the competency, a description, and a list of behavioral indicators.

*Closed loop task.* A Task that has a definite beginning and end.

Critical flight maneuvers. Maneuvers that place significant demand on a proficient crew.

*Critical system malfunctions.* Aircraft system malfunctions that place significant demand on a proficient crew. These malfunctions should be determined in isolation from any environmental or operational context.

Developed upset. A condition meeting the definition of an aeroplane upset.

**Developing upset.** Any time the aeroplane begins to unintentionally diverge from the intended flight path or airspeed.

**Evidence-based training (EBT).** Training and assessment that is characterized by developing and assessing the overall capability of a trainee across a range of competencies rather than by measuring the performance of individual events or maneuvers.

**EBT instructor.** A person who has undergone a screening and selection process, successfully completed an approved course in delivering competency-based training, and is subsequently authorized to conduct recurrent assessment and training within an approved EBT program.

**EBT module.** A session or combination of sessions in a qualified FSTD as part of the 3-year cycle of recurrent assessment and training.

**EBT session.** A single defined period of training in a qualified FSTD that normally forms part of an EBT module.

**EBT scenario.** Part of an EBT session encompassing one or more scenario elements, constructed in to facilitate real time assessment or training.

EBT scenario element. Part of an EBT session designed to address a specific training topic

*Error.* An action or inaction by the flight crew that leads to deviations from organizational or flight crew intentions or expectations.

*Error management.* The process of detecting and responding to errors with countermeasures that reduce or eliminate the consequences of errors, and mitigate the probability of further errors or undesired aircraft states.

*Exposure.* The historical rate of occurrence i.e., the number of flights with a given condition, (factor, threat, error, etc.) divided by the number of flights (in this case take-offs) for a given grouping of aircraft. Note: In this report, the only grouping used was the aircraft generation.

*Facilitation technique.* An active training method, which uses effective questioning, listening and a non-judgmental approach and is particularly effective in developing skills and attitudes, assisting trainees to develop insight and their own solutions and resulting in better understanding, retention and commitment.

Factor. A reported condition affecting an accident or incident.

*Flight crew member.* A licensed crew member charged with duties essential to the operation of an aircraft during a flight duty period.

Inter-rater reliability. The consistency or stability of scores between different raters.

*Line orientated flight scenario (LOFS).* LOFS refers to training and assessment involving a realistic, 'real time', full mission simulation of scenarios that are representative of line operations.

**Note:** Special emphasis should be given to scenarios involving a broad set of competencies that simulate the total line operational environment, for the purpose of training and assessing flight crew members.

*Maneuvers.* A sequence of deliberate actions to achieve a desired flight path. Flight path control may be accomplished by a variety of means including manual aircraft control and the use of auto flight systems.

*Meta analysis.* Synthesizing research results by using various statistical methods to retrieve, select and combine results from previous separate but related studies.

**Open loop task.** Tasks involving continuous responses that are repeated and do not have a definite beginning and end

**Outcome Grading.** Assessment using a grading scale with two or more grades describing the overall outcome in relation to a defined outcome (not assessing the individual competencies in depth).

Phase of flight. A defined period within a flight.

Scenario. Part of a training module that consists of predetermined maneuvers and training events.

*Threat.* Events or errors that occur beyond the influence of the flight crew, increase operational complexity and must be managed to maintain the margin of safety.

*Threat management.* The process of detecting and responding to threats with countermeasures that reduce or eliminate the consequences of threats and mitigate the probability of errors or undesired aircraft states.

Training Criticality. The need for training



*Training criticality survey.* Pilot survey of training criticality in terms of threats and errors by aircraft per flight phase

*Training effect.* The potential effect of FSTD training in preventing or reducing the severity of an accident or incident.

*Training event.* Part of a training scenario that enables a set of competencies to be exercised.

**Training objective.** A clear statement that is comprised of three parts, i.e., the desired performance or what the trainee is expected to be able to do at the end of training (or at the end of particular stages of training), the performance standard that must be attained to confirm the trainee's level of competence and the conditions under which the trainee will demonstrate competence.

**Undesired** aircraft state. A position, condition, or attitude of an aircraft that clearly reduces safety margins and is a result of actions by the flight crew. It is a safety-compromising state that results from ineffective error management. Examples include unstable approaches, lateral deviations, firm landings, and proceeding towards wrong taxiway/runway. Events such as equipment malfunctions or ATC command errors can also place the aircraft in a compromised position, but these would be considered threats.

Unsafe situation. A situation, which has led to an unacceptable reduction in safety margin.



## ACKNOWLEDGEMENTS

This report would not have been possible without the assistance and contributions of people drawn from many disciplines both within and outside the aviation community. Most of the people listed provided their support on a voluntary basis. Their contributions are greatly appreciated, but the listing here does not imply endorsement of the results or this report.

John Scully – Author

Michael Varney	Pilot/Instructor	Project Leader – EBT, authoring and editing of the report, ensuring consistency of EBT programs with the results
Jari Nisula	HF/Engineer	EBT Accident Incident Analysis, sorting and classification of data, translation of results into training topics
Dr Simon Henderson	Pilot/Instructor/Scientist	Assistance with guidance in construction of the report, as well as editing
Dr Barbara Holder	Scientist	Collaboration to create the pilot survey. Distribution of the questionnaire, collection and analysis of results
Jean-Max Huet	Software Engineer	Assistance with FDA including analysis of flights across aircraft types, regions and operators
Dr James Klinect	Scientist	Assistance in developing the methodology for the EBT Data Study. The LOSA analysis of training issues
Dr Ashleigh Merritt	Statistician	Analysis, development and authoring of LOSA reports
Professor Patrick Murray	Pilot/Instructor/Scientist	Assistance with authoring elements of the report, in addition to guiding its construction and editing
Hugh Webbon	Pilot/Analyst	Specification of research questions, analysis, development and authoring of LOSA reports
Dr Douglas Farrow	Scientist	Assistance and support for the study, advice based on experience from AQP
Anne Guerin	Engineer	Independent analysis of accidents and incidents, validation of EBT
		analysis and creator of mega patterns
Dr Duncan Harris	HF Specialist	Assistance in a study conducted by the UK CAA classifying their accident study for EBT
Harald Hendel	Engineer	Assistance and expertise on the sorting and display of mega data patterns to obtain an intuitive notion of the results
Gavin McKellar	Pilot	Provided independent oversight and review of both process and data
Dr Christian Norden	Pilot/Instructor	Assistance with guidance in construction of the report, in addition to editing
James Pegram	Pilot/Instructor	Training and operational expertise
Dr David Robinson	Statistician	Assistance in reviewing results from the Training Criticality Study and correlations to the EBT Accident Incident Study
David Swarthout	Pilot/Instructor	Analysis of accidents and incidents and part of the Accident Incident Study reconciliation team
Jon Tovani	Pilot/Instructor	Training and operational expertise
Sam Daniels	Analyst	Assistance and support in creating graphics from data to be inserted into the report
Carey Edwards	HF Specialist	Assistance and insight from his work in the CRM field with analysis
Johan Engstrom	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Peter Fogtman	Pilot/Instructor	Training and operational expertise in addition to analysis for the EBT Accident Incident Study
Sören Foss	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Vinod Gopalakrishnan	Safety Specialist	Safety and operational expertise
Dieter Harms	Pilot/Instructor	Training and operational expertise
Magnus Hellstrom	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Arto Helovuo	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Mark L'Esperance	Pilot/Analyst	Analysis for the EBT Accident Incident Study
Mary Leiran	System analyst	Assistance with sorting of the Training Criticality Survey data
Mathias Nordsiek	Pilot/Instructor	Analysis for the EBT Accident Incident Study



Glenn Rowlandnorth	Pilot/Instructor	Analysis for the EBT Accident Incident Study
J Michael Scully	Pilot/Analyst	Analysis of accidents and incidents and part of the Accident Incident
		Study reconciliation team
Vivek Sood	Scientist	Safety and operational expertise
Gerard Van Es	Engineer	Safety and operational expertise
Adrian Akers-Douglas	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Frederic Baudin	Software Specialist	Assistance and advice in the report formatting
Roggeri Benoi	Pilot/analyst	Analysis for the EBT Accident Incident Study
David Body	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Jean-Pierre Bordeux	Pilot/Instructor	Analysis for the EBT Accident Incident Study
David Bracewell	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Thorsten Brandt	Pilot/Instructor	Training and operational expertise, analysis for the EBT Accident
		Incident Study
Dave Conrad	Pilot	Analysis for the EBT Accident Incident Study
Jean-Marc Elias	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Dr Paul Gay	Statistician	Training and operational expertise
Simon Henchie	Software specialist	Safety and operational expertise
William Johnson	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Tom O'Kane	Pilot	Editing and proof reading of the report
David Owens	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Andrew Pousen	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Ernst Scharp	Pilot/Safety specialist	Analysis for the EBT Accident Incident Study
Dr Daniel Scully	Mathematician	Statistical analysis
Pieter Sevensma	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Roy Spencer	Pilot/Instructor	Analysis for the EBT Accident Incident Study
Eric Vannier	Pilot/Instructor	Analysis for the EBT Accident Incident Study

# **APPENDICES**

## APPENDIX 1 LOSA REPORTS

# LOSA Archive Report: 10 Target Areas for Evidence Based Training

## IATA ITQI EBT Working Group Report

April 2010



PO Box 684645 Austin, Texas USA 78768 www.losacollaborative.org

## **Table of Contents**

INTRODUCTI	ION	1			
GLOSSARY OF TERMS USED IN THIS REPORT 5					
SECTION 1	UNSTABLE APPROACH	7			
SECTION 2	AUTOMATION	14			
SECTION 3	PRIMARY/SECONDARY ALTIMETERS	20			
SECTION 4	MONITOR/CROSS-CHECK	22			
SECTION 5	FREQUENTLY MISMANAGED THREATS	27			
SECTION 6		34			
SECTION 7	CAPTAIN LEADERSHIP / COMMUNICATION ENVIRONMENT	39			
SECTION 8	ATC THREAT MANAGEMENT	43			
SECTION 9	TEM BY PHASE OF FLIGHT	48			
SECTION 10	WEATHER RADAR USAGE	51			

## Introduction

The IATA Evidence Based Training (EBT) study group, as part of IATA's Training Quality Initiative (ITQI), contacted The LOSA Collaborative seeking Line Operations Safety Audit (LOSA) information that could help shape future EBT curriculum for commercial airline pilots and instructors. The primary objective was for The LOSA Collaborative to mine the LOSA Archive and provide a list of systemic and/or pilot performance issues that could be used to direct and validate current EBT risk analyses, training products, and pilot skill sets.

## **Executive Summary**

This report highlights 10 performance targets that The LOSA Collaborative recommends for further investigation by the ITQI/EBT study group. These recommendations are based on content analyses of LOSA observers' narratives and statistical analyses of the aggregated data in the LOSA Archive. The evidence for each target is provided in the report sections that follow.

- 1. Unstable Approach
- 2. Automation
- 3. Primary/Secondary Altimeters
- 4. Monitor/Cross-Check
- 5. Frequently Mismanaged Threats
- 6. Intentional Noncompliance
- 7. Captain Leadership / Communication Environment
- 8. ATC Threat Management
- 9. TEM by Phase of Flight
- 10. Weather Radar

The next few pages outline The LOSA Collaborative's Quality Assurance Process and introduce the reader to the LOSA Archive, the Threat and Error Management Framework, and the terms used in the report. The body of the report is then taken up with statistical evidence and narrative examples to support the above targets.

## LOSA Quality Assurance Process

To ensure LOSA data quality, airlines are required to participate in a five-part quality assurance process in order for the data to meet The LOSA Collaborative standard. This process is outlined below.

- An agreement is reached between airline management and the pilots' association or representatives of the pilot group. This agreement ensures that all data will be de-identified, confidential, and sent directly to The LOSA Collaborative for analysis. It also states that once the LOSA results are presented, both parties have an obligation to use the data to improve safety.
- 2. The airline is assisted in selecting a diverse and motivated group of observers. A typical observer team will have representatives from a number of different airline departments, such as flight operations (all fleets), training, safety, and the flight crew association.
- 3. The observers receive training in the TEM framework, the observation methodology, and the LOSA software tool, which organizes data input. The LOSA Collaborative software also provides data security through automatic encryption. After the initial observer training, observers conduct at least two sample observations and then reconvene for recalibration sessions. During this time, observers are given one-on-one feedback on the quality of their observations and authorized to continue as observers on the project. The observer training and recalibration are considered essential for a standardized LOSA dataset.
- 4. When the encrypted observations are sent to The LOSA Collaborative, analysts read the observers' flight narratives and check that every threat and error has been coded accurately. This data integrity check ensures the airline's data are of the same standard and quality as other airlines in the LOSA Archive.
- 5. Once the initial data integrity check is complete, airline representatives who are fleet experts attend a data-verification roundtable with The LOSA Collaborative analysts. Together, they review the data against the airline's procedures, manuals, and policies to ensure that events and errors are valid and have been correctly coded. After the roundtable is completed, airline representatives are required to sign off on the data set as being an accurate rendering of threats and errors. Only then does analysis for an airline's final report begin.

## The LOSA Archive

The LOSA Archive currently houses over 10,000 observations and more than 50 LOSA projects. The statistics in this document are drawn from a slightly smaller dataset: 8,375 flight observations from 42 LOSA Projects conducted during the years 2003 - 2010. The LOSAs conducted prior to 2003 (when the coding system was still being refined and before the data collection tool was introduced) are excluded from these analyses to enhance the stability and reliability of the findings.

AeroMexico Continental Airlines Mount Cook Airlines ٠ ٠ ٠ Air Canada Continental Express Oantas ٠ ٠ . • Air Freight New Zealand ٠ Continental Micronesia ٠ Regional Express Airline Air Hong Kong Delta Air Lines Saudi Arabian Airlines ٠ • ٠ DHL Air • Air New Zealand ٠ • SilkAir Air Nelson Emirates Singapore Airlines • ٠ ٠ Air Transat EVA Air / UNI Air ٠ Singapore Airlines Cargo • • Alaska Airlines Frontier Airlines TACA International ٠ ٠ All Nippon Airways Horizon Air ٠ TACA Peru • • Asiana Airlines Japan Airlines ٠ **TAP** Portugal • ٠ Braathens ASA ٠ JetBlue ٠ Thomas Cook . Cathay Pacific LACSA • US Airways ٠

Malaysia Airlines

•

China Airlines

• WestJet

## **Threat and Error Management Framework**

The data collected during a LOSA allow an airline to understand the safety and flight crew performance issues that arise during daily flight operations before an incident or accident. To best facilitate this understanding, all LOSA data are collected and analyzed with the Threat and Error Management (TEM) framework.

The Threat and Error Management (TEM) framework conceptualizes operational activity as a series of ongoing threats and errors that flight crews must manage to maintain adequate safety margins. Threats are external events or errors outside the influence of the flight crew that increase the operational complexity of a flight. Threats are everywhere in flight operations (thunderstorms, terrain, poorly signed runways, late changes from ATC, inoperable NAVAIDS events at the gate, ground crew not ready, mistakes in Dispatch paperwork, etc.) and flight crews have to divert their attention from normal duties to manage them. The more complex, challenging, and/or distracting the threat environment, the greater is the crew's workload.

Crew errors can vary from minor deviations, such as entering the wrong altitude but quickly catching the mistake, to something more severe, such as failing to set flaps before airplane takeoff. Regardless of cause or severity, the outcome of an error depends on whether the crew detects and manages the error before it leads to an unsafe outcome. This is why the foundation of TEM lies in understanding error management rather than focusing solely on error avoidance or error commission.

The Threat and Error Management (TEM) framework has been adopted by ICAO and the FAA:

- As of November 2006, TEM and LOSA concepts were added to several of the Annexes to the Convention on International Civil Aviation (Chicago Convention). In Annex 1 (Personnel Licensing), TEM is now a requirement for all pilot and ATCO licenses (standard). Annex 6 was amended to require TEM for all initial and recurrent flight crew training. In Annex 14 (Aerodromes), the new Safety Management System standards highlight LOSA as a recommended practice for normal operations monitoring.
- LOSA is officially recognized as an FAA Voluntary Safety Project. The current FAA Advisory Circular on LOSA (120.90) was drafted by members of The LOSA Collaborative in partnership with The University of Texas at Austin.

## **Glossary of Terms Used in this Report**

Threat & Error Management (TEM): A framework for understanding operational performance in complex environments. It is designed to capture performance in its "natural" operating context by quantifying the specifics of the environment and the effectiveness of performance in that environment.

#### Threat

Threat: An event or error that occurs outside the influence of the flight crew, but which requires crew attention and management if safety margins are to be maintained. There are Environmental and Airline threats.

Environmental Threat: Threats that are outside the direct control of the flight crew and the airline. Four types – Weather, ATC, Airport and Terrain/Traffic/Communication.

Airline Threat: Threats that are outside the direct control of the flight crew but within the management purview of the airline. Seven types –Airline Operational Pressure, Aircraft, Cabin, Dispatch/Paperwork, Ground Maintenance, Ground/Ramp and Charts and Manuals.

Mismanaged Threat: A threat that is linked to or induces flight crew error.

Threat Prevalence Index: The percentage of flights with one or more threats.

Threat Mismanagement Index: The percentage of threats that are mismanaged.

#### Error

Flight Crew Error: An observed flight crew deviation from organizational expectations or crew intentions. There are Handling errors, Procedural errors, and Communication errors.

Aircraft Handling Error: Five types - Manual Handling, Automation, Flight Controls, System/Instrument/Radio and Ground Taxi.

Procedural Error: Seven types -Checklist, Callout, Briefing, SOP Cross-Verification, Documentation, PF/PM duty and "Other".

Communication Error: Pilot-to-Pilot Communication and Crew-External Communication.

Mismanaged Error: An error that is linked to or induces additional error or an undesired aircraft state.

Error Prevalence Index: The percentage of flights with one or more errors.

Error Mismanagement Index: The percentage of errors that are mismanaged.

#### Undesired Aircraft State

Undesired Aircraft State (UAS): A flight-crew-induced aircraft state that clearly reduces safety margins (i.e., a safety-compromised situation resulting from ineffective threat and error management).

Mismanaged UAS: A UAS that is linked to or induces additional error.

UAS Prevalence Index: The percentage of flights with one or more UAS.

UAS Mismanagement Index: The percentage of UAS that are mismanaged.

# **Statistical and Content Analyses**

## Section 1 Unstable Approach

4% of flights in the LOSA Archive have an unstable approach. The evidence indicates that when the aircraft is unstable at the airline mandatory go around point, the crew elected to continue the approach 97% of the time.

Event	Outcome of the Event	
	87% continued the approach and landed without issue	
4% of flights in LOSA Archive have an Unstable Approach	10% continued the approach and landed long, short, or significantly off centerline	
	3% executed a missed approach (9 of 337 unstable approaches observed)	

**Unstable Approach Outcomes** 

It is The LOSA Collaborative's experience that the majority of airline observers attending training courses are unsure or slow to recall the criteria and equally unsure of the "bottom line" where a mandatory missed approach is required for their airline. Lengthy discussion always occurs as to the definition of IMC and VMC and the applicability to the 1000ft or 500ft minimum stabilization heights. Very rarely is the mandatory missed approach point fully understood. It seems that all crew start with the aim of being stabilized at 1,000ft, unless on a visual circuit, but when this is not achieved there is much confusion. In fact, few airline manuals define what needs to happen if the approach becomes unstable below the mandatory missed approach point.

Visual meteorological conditions are usually defined by certain visibility minimums, cloud ceilings for landing, and cloud clearances. The exact requirements vary by type of airspace, whether it is day or night, and from country to country. Typical visibility requirements vary from one statute mile to five statute miles (many countries define these in metric units as 1,500m to 8km). Typical cloud clearance requirements vary from merely remaining clear of clouds to remaining at least one mile away (1,500m in some countries) from clouds horizontally and one thousand feet away from clouds vertically. Some observers say VMC is being able to continuously see the approach lights and touchdown zone, some just want to see approach lights and some just the ground. Frequently Managers, Instructors and Pilots cannot agree. Again, airline SOP tends to be confusing, often with differing definitions of VMC in Operating and Training Manuals.

Despite clear parameters for deviation alert calls, these are also flexible depending on the size of the excess and the recovery trend. By experience and report, required deviation callout figures are not readily recalled by crew. When under pressure, it can be difficult to apply a limit of +10 knots to an approach speed that is just a bug or electronic line, not a figure. It becomes a matter of visual judgment and not mathematics. The event list to be

recalled at stressful times is large. Most crew regard close to a limit as "good enough" or "acceptable deviation", especially if it "looks OK".

The typical CRM mitigation for an unstable approach is Monitoring/Cross-Checking by the PM, designed to bring attention to the event with a deviation callout. However, if the PF considers that the situation can be recovered in time to make a landing, there frequently appears to be unspoken agreement between the crew that the approach will continue. In 95% of the recorded occurrences the observer selected "All Crew Members" as causing the event and 45-50% of the flights were rated poor or marginal by the observers for Monitoring/Cross-Checking and Inquiry during Descent/Approach/Land. It is clear that the decision to continue is consciously and evidently made by both crew members, even if it is unspoken.

## **Threat-Linked Unstable Approaches**

The LOSA Archive indicates approximately 30% of unstable approaches are linked to a discernable threat as defined by The LOSA Collaborative. It would be possible to argue that good technical and commercial judgment on behalf of the crew makes the airline definition highly flexible. In some cases the observer appears to agree with the decision of the crew, as evidenced by the words "technically unstabilized" or "unstabilized by the definition of SOP".

Of the unstable approaches that are linked to a threat, the LOSA Archive suggests there are only two significant threat types: ATC and Weather. These threats are typically in one of three categories:

- Controller-induced circumstances resulting in insufficient time to plan, prepare, and execute a safe approach. This includes accepting requests from ATC for flying higher and/or faster than desired or flying shorter routings than desired.
- ATC instructions that result in flying too high and/or too fast during the initial or final approach (e.g., request for maintaining high speed down to the [outer] marker or for GS capture from above slam-dunk approach).
- Insufficient management of wind conditions:
  - Tailwind component;
  - Low altitude wind shear;
  - Local wind gradient and turbulence (e.g., caused by terrain, forest or buildings).

There is the evidence from the observers' narratives that the following is happening:

- Failure to recognize deviations or to remember stabilized approach criteria.
- Belief that the aircraft will be stabilized shortly after the stabilization height.
- Excessive confidence by the PM that the PF will achieve a timely stabilization before landing.
- PF/PM over reliance on each other to call excessive deviations or to call for a go-around.

35% of the flights with threat-linked unstable approaches were rated poor or marginal for Inquiry vs. 45% of the flights with unstable approaches that were not linked to threats. These results suggest the PM is somewhat more likely to speak up if the PF has maneuvered an unstable approach in response to a threat vs. an unstable approach due to the PF's own flying, i.e., without a contributing threat.

## Missed Approach Performance after an Unstable Approach

Evidence from the LOSA Archive indicates a missed approach is rarely handled well by the crew. The event is uncommon and, as illustrated below in the narrative excerpts, the level of safety risk rises dramatically. Below are the most common characteristics of missed approach events in the LOSA Archive:

- The event is a surprise to the crew.
- None occur at the standard missed approach point, which had in all cases been briefed.
- A crew error usually precedes the event (e.g., having the incorrect missed approach altitude in the MCP/FCU).

## Section 2 Automation

28% of flights in the LOSA Archive have an Automation error. Two-thirds of Automation errors are usually well-managed or remain inconsequential. The table below lists the most mismanaged Automation errors. The 10 errors listed below in descending order of frequency account for three-quarters of all the mismanaged Automation errors that are observed in the LOSA Archive.

	Error Codes	% of all Mismanaged Automation Errors
1.	Wrong flight guidance altitude entered	21%
2.	Failure to execute an MCP/FCU/Flt guidance mode when needed	13%
3.	Omitted/wrong waypoint or route settings put in FMGC/FMS	9%
4.	Wrong MCP/FCU/flight guidance mode executed	8%
5.	Wrong flight guidance speed setting dialed	6%
6.	Wrong speed entered into the FMC/FMGC	5%
7.	Other wrong FMC/FMGC/FMS entries	5%
8.	Wrong flight guidance heading set or dialed	5%
9.	(Intentional) Nonstandard automation usage	3%
10.	Wrong MCP/FCU/flight guidance mode left engaged	3%

#### Top 10 Mismanaged Automation Errors

Various training issues arise from an examination of the database and narratives on automation errors. The principal issues are:

- Technical understanding of the automation
- A lack of "verbalization" by crew to share mental models
- The late engagement of autopilot after takeoff or early disengagement in Descent/Approach/Land, basically hand flying at an inappropriate time. Common errors include hand flying in a busy Terminal Control Zone, looking through the FD, not checking modifications to the SID, STAR or Approach profile and relying on the PM to effect FMC/FMGC changes.
- The overarching element is Monitoring/Cross-Checking, with little to no dialogue between the pilots during most of the errors. Monitoring/Cross-Checking is treated as a separate target later in this report.

## Automation and SOP Cross-Verification

The LOSA Archive shows that 21% of the Automation induced undesired aircraft states result from SOP Cross-Verification errors, i.e., an Automation error is committed and the crew fails to detect it on procedural crosscheck.

## Automation and the Autopilot

The LOSA Archive indicates there is often a misunderstanding of the various autopilot modes and how they should be used to achieve the desired path. This was evident on all types of aircraft and manufacturer.

## Section 3 Primary/Secondary Altimeters

In the age of RVSM, precise altimeter settings are critical. Unfortunately, the LOSA Archive shows a high prevalence of altimeter errors compared to other aircraft systems and instruments.

## **Primary Altimeter Setting Errors**

"Wrong primary altimeter setting" errors occur on about 3-4% of flights in the LOSA Archive. In addition, 46% of these errors are mismanaged to an additional error or an undesired aircraft state making it one of the most often mismanaged System/Instrument/Radio errors observed in the LOSA Archive. Of particular note, 25% of the mismanaged primary altimeter errors occur below 8,000 ft.

## Secondary Altimeter Usage

The secondary or standby altimeter has a function to provide backup in case of primary failure. It needs to be cross-checked for accuracy during predeparture, but its use thereafter varies across airlines. Some airlines successfully use it as a tool to provide increased situational awareness with regard to terrain during climb and descent. In such cases the secondary altimeter is set at a different time to the primary in order to display a height reference to critical terrain. More frequently among airlines, the secondary altimeter setting is simply changed together with the primary. This results in a climb or descent while below MSA with no height reference.

The following general comments are drawn from The LOSA Collaborative observers' experience and link altimeter setting with general terrain awareness. Setting can involve using the 'preset' function of barometric display on the PFD to provide a local QNH.

• <u>Takeoff/Climb</u>

LOSA observers have noted that many operators set all three altimeters to QNE above transition altitude, even when below area or en route climb MSA. There is no height reference for the pilots in the climb to assist situational awareness in the event of engine failure, oxygen failure or pressurization failure.

• <u>Cruise:</u>

A regional or local QNH is rarely obtained or preset when overflying terrain above 10,000ft in preparation for emergency descent or drift-down.

Temperature corrections for any altimeter setting are rarely considered.

Radius of turn is rarely considered for turn back on terrain critical route segments. Often the radius will take an aircraft outside the flight plan MSA into an area with a higher figure.

On "Direct to" clearances, where the new routing is outside the flight plan "corridor" for the MSA figures, a revised MSA is rarely sought from charts.

• Descent/Approach/Land:

In some cases, when operating near areas of high terrain during descent, no altimeter is set to QNH below the descent en-route MSA. In briefing, only the 25 mile airfield MSA is considered, not that for the descent corridor.

## Section 4 Monitor/Cross-Check

Across all the TEM countermeasures, Monitoring/Cross-Checking consistently emerges as the weakest at every airline. About 40% of all flights are rated poor or marginal on Monitoring/Cross-Checking in at least one phase of flight, be it Predeparture/Taxi-out, Takeoff/Climb or Descent/Approach/Land.

Poor		Marginal		Good	Outstanding
Observed performance had an imp on safety	act	Observed performance was barely adequate	Observed performance was effective		Observed performance was truly noteworthy
MONITOR / CROSS- CHECK	Crev	w members actively monitored and cross- cked systems and other crew members		Aircraft position, setting	s, and crew actions were verified

Scale used by LOSA Observers

LOSA Archive statistics show flights with poor or marginal Monitoring/Cross-Checking ratings have more mismanaged threats, more Handling and Procedural errors, more mismanaged errors, and more undesired aircraft states than flights with standard or outstanding Monitoring/Cross-Checking ratings. In fact, the rates are almost double, i.e., the flights with sub-standard ratings for Monitoring/Cross-Checking have twice as many errors, mismanaged threats, mismanaged errors, and undesired aircraft states.

Two of the more frequent Monitor/Cross-Checking errors logged in LOSA are Callout and SOP Cross-verification errors. Some LOSA Archive results for these error types are shown below:

## **Callout Errors**

The table below lists the most frequent Callout errors in the LOSA Archive and compares their relative occurrence and how often they are consequential.

Omitted Callout	% of all Observed Callout Errors	% of these errors that were Inconsequential	% of these errors leading to Added Error or UAS
Altitude Callouts (e.g., 1000 to level off calls)	55%	99%	1%
Descent/Approach Callouts (e.g., FAF call)	17%	92%	8%
Transition Callouts	2%	58%	42%
Deviation Callouts (Speed and Vertical)	2%	35%	65%

### A Comparison of Omitted Callouts and Their Outcomes

The first point to make is that more than half of all Callout errors are omitted altitude callouts (1,000 to go calls). Yet, as the table above shows, only 1% of these omitted calls have been consequential. [To be precise: There are 1,741 instances of omitted altitude callouts in the LOSA Archive presently, and 17 of them have led to additional error.] In fact, omitted altitude callouts are the most frequently logged error in the LOSA Archive by a factor of two, i.e., there are twice as many omitted altitude callouts as the next most frequently observed error in the LOSA Archive.

A concern related to this error is the high rate of Intentional Noncompliance. 20% of these calls are intentional (meaning the altitude calls are omitted systematically and multiple times). As the section on Intentional Noncompliance will show, there is a strong association between Intentional Noncompliance and poor TEM performance.

## **SOP Cross-Verification Errors**

28% of flights in the LOSA Archive have an SOP Cross-Verification error; one in ten of these errors are mismanaged to a UAS or additional error.

SOP Cross-Verification Error	% of all SOP Cross- Verification Errors	% of these errors leading to Added Error or UAS
1. Omitted flight mode verification	20%	4%
2. Failure to cross-verify MCP/FCU/altitude alerter setting	18%	14%
3. Failure to cross-verify FMC/FMGC entries	16%	14%
4. Failure to cross-verify documentation/paperwork/takeoff figures/calculations	9%	7%

## Section 5 Frequently Mismanaged Threats

Using the LOSA/TEM coding scheme, almost every flight in the LOSA Archive has a threat. In fact, the average is 4 or 5 threats per flight. Hence, threat management is a core pilot skill. 90% of threats are successfully managed by flight crews; however, about 10% of all threats contribute or link to a crew error, some of which continue on through mismanagement to become an undesired aircraft state.

The table below shows the most frequently encountered threats in the left column and the most common of the mismanaged threats in the right column. As the lists are very similar, it is clear these are the threats to focus on first.

	ALL THREATS Threat Code in Descending Order of Frequency		ALL MISMANAGED THREATS Threat Code in Descending Order of Frequency
1.	Terrain	1.	ATC challenging clearances or tough to meet restrictions
2.	Thunderstorms/turbulence	2.	Terrain
3.	ATC Challenging clearances or tough to meet restrictions	3.	Thunderstorms/turbulence
4.	Aircraft Malfunction unexpected by the crew	4.	Aircraft Malfunction unexpected by the crew
5.	Icing or snow	5.	Icing or snow

Top 5 Threats Encountered & Top 5 Mismanaged Threats

# 1. Mismanaged Threat: ATC Challenging Clearances or Tough to Meet Restrictions

As one might expect, the key factors in ATC threat mismanagement are:

- Accepting a visual while high on profile and/or fast
- ATC request for high speed to the OM or Final fix
- Being left high on the FMS/FMGC generated profile by ATC

## 2. Mismanaged Threat: Terrain

In the LOSA Archive, the most common errors associated with Terrain mismanagement are Briefings, Callouts, and System/Instrument/Radio errors. Failing to mention terrain as part of the briefing was the most common Briefing error, and it occurred about equally in Pre-departure/Taxi-out and Takeoff/Climb as it did in Descent/Approach/Land. Of the Callout errors, omitting the MSA or safe justification call was the most common.

The most common System/Instrument/Radio error was failing to select terrain on the Nav. Display. Terrain poses a further problem when

- No terrain briefing is coupled with
- No selection of terrain on the Nav. Display and
- The flight is in terrain critical environment.

This combination produces a high severity of risk and leaves a crew severely exposed to a CFIT, with only GPWS to protect the aircraft. These events tend to occur in 'pockets', i.e., in areas where there is extensive terrain and the threat becomes normalized within an airline and so is not recognized as such.

## 3. Mismanaged Threat: Thunderstorms/Turbulence

As might be expected, thunderstorms with turbulence are most problematic during Takeoff/Climb and Descent/Approach/Land. In the LOSA Archive, the 2 most common errors associated with this threat are Manual Handling/Flight Control and System/Instrument/Radio errors.

## 4. Mismanaged Threat: Aircraft Malfunction Unexpected by Crew

The errors associated with aircraft malfunctions mainly focus on crews applying engineering shortcuts or workarounds rather than following ECAM, QRH or MEL procedures and most occur pre-flight or on start up. Rarely do these errors have a consequence. However, there was a high degree of intentional non-compliance in all actions and there are training implications if divergence from SOP is encouraged during route or line training.

### 5. Mismanaged Threat: Icing and Snow

The most common error associated with icing and snow is the failure to select anti-ice protection ON. In the majority of cases, this situation persists for a significant amount of time and is thereby coded as an undesired aircraft state (Incorrect Aircraft Configuration-Systems UAS). These flights are usually rated poor or marginal for Monitoring/Cross-Checking due to the time it takes the crew to detect the error, if at all.
# Section 6 Intentional Noncompliance

All Intentional Noncompliance errors observed in LOSA must meet one of four conditions:

- 1. The error is committed multiple times during one phase of flight, e.g., missing multiple altitude callouts during descent (if this condition is met, the error is coded as one Intentional Noncompliance error);
- 2. The crew openly discusses that they are intentionally committing an action that is against published SOP;
- 3. The observer determines that the crew is time-optimizing SOP when time is otherwise available (i.e., performing a checklist from memory); or
- 4. An aircraft handling error is determined by the observer to involve an increase in risk when more conservative options were available (e.g., intentionally ducking under a glideslope).

The observer decides that it is an intentional noncompliance, not The LOSA Collaborative, and this judgment is confirmed by the airline representatives at the data cleaning roundtable.

To understand the relationship between Intentional Noncompliance and Threat and Error Management (TEM), a number of statistical analyses were conducted on data in the LOSA Archive. While there is no correlation between the number of threats on a flight and the number of Intentional Noncompliance errors, i.e., the level of threat complexity is the same, there is a significant positive correlation between the number of Intentional Noncompliance errors observed on a flight and the number of mismanaged threats, unintentional errors, mismanaged errors, and undesired aircraft states. In other words, *the more Intentional Noncompliance that occurs on a flight, the less effective is the flight crew's TEM performance.* 

To see these relationships more clearly, the 8,000+ flights in the LOSA Archive were divided into three groups – those with zero noncompliance errors (56% of flights), those with one Intentional Noncompliance error (24%), and those with two or more Intentional Noncompliance errors (20%). The table below highlights the notable findings that underscore the above conclusion.

TEM Indicator	Flights with zero Intentional Noncompliance errors	Flights with one Intentional Noncompliance error	Flights with two or more Intentional Noncompliance errors
% of Flights in LOSA Archive	56%	24%	20%
Average number of threats per flight	4.4	4.7	4.8
Average number of errors per flight	1.9	3.7	6.6
% of flights with a mismanaged threat	23%	37%	50%
% of flights with a mismanaged error	27%	45%	65%
% of flights with an undesired aircraft state	25%	42%	59%

Intentional Noncompliance & TEM Indexes

The first table below shows Intentional Noncompliance varies by Error Type with higher rates generally but not always observed with the Procedural errors. The most frequent Intentional Noncompliance Error Codes are shown in the second table below.

Error Type	% of these Error Types that are Intentional Noncompliance
PF/PM Duty	100%
Checklist	55%
Briefings	26%
Documentation	23%
Ground Taxi	23%
Callouts	18%
SOP Cross-Verification	18%
Manual Handling/Flight Control	15%
Communication	10%
Automation	7%
System/Instrument/Radio	5%

#### Intentional Noncompliance by Error Type

#### Top 5 Intentional Noncompliance Error Codes

	Error Code
1.	(Intentional) Checklist performed from memory / Use of nonstandard checklist protocol
2.	(Intentional) Omitted altitude callouts
3.	(Intentional) Failure to execute a mandatory missed approach
4.	(Intentional) PF makes own changes
5.	(Intentional) Taxi duties performed before leaving runway

Note: Errors #2 and #3 are discussed in other parts of this report.

It would be easy to draw the conclusion that noncompliance is just experienced pilots taking optimizing shortcuts. Pilots think of it as "using common sense" to get the job done and no big deal. This is reinforced by the fact that Captains display significantly more noncompliance than First Officers. However, as stated earlier, the relationship between noncompliance and TEM performance is more complex.

## Intentional Noncompliance: Checklists

Checklists are the backbone of the SOP structure and compliance is a central tenet of training techniques. Yet, over half of all Checklist errors involve some form of noncompliance.

- The vast majority of these noncompliance Checklist errors are attributable to the crew alone less than 10% of them are prompted by a threat such as Airline Operational Pressure, ATC or Aircraft Malfunction.
- Almost half of all noncompliance Checklist errors occur during Predeparture/Taxi-out.
- All showed a willingness by the crew to accept the error.

### Intentional Noncompliance: PF Makes their Own Changes

All PF/PM Duty errors are coded as intentional noncompliance since these events are considered by The LOSA Collaborative as purposeful or willful acts to short-cut well-established SOPs. Of the PF/PM Duty errors, the PF making their own changes are the most common. These errors include the PF changing the MCP/FCU/flight guidance, the FMC/FMGCFMS, and system switches and settings.

- The LOSA Archive shows most of these errors occurred when hand flying.
- One-half of them occurred during Takeoff/Climb.
- The Captain committed two-thirds of these errors. (Note: The Captain was the PF for 56% of the flights in the LOSA Archive.)

## Intentional Noncompliance: Taxi Duties Performed before Leaving Runway

This is a very common area of noncompliance. There are no threats attached to the errors and the responsibility rests entirely with the crew. The observers' narratives indicate no evidence of short taxi distances that might require urgent commencement of the duties. Many Flight Manuals permit some post-landing items to be actioned, such as stowing spoilers, but there is an observed tendency to complete many of the minor items by memory while still on the active runway.

# Section 7 Captain Leadership / Communication Environment

Communication in the cockpit is addressed in this issue; specifically, the Captain's role in matching the appropriate level of direction and consultation to the crew's skills, background and experience level. The information in this section should be of particular interest to CRM instructors and training content providers.

As part of assessing a flight's TEM countermeasure performance, The LOSA Collaborative observers are asked to rate and comment on the perceived qualities of Captain Leadership and the Communication Environment using the following scale and definitions.

Poor		Marginal		Good	Outstanding
Observed performance had an ir on safety	npact	Observed performance was barely adequate	Observed performance was effective		Observed performance was truly noteworthy
				-	
COMMUNICATION ENVIRONMENT	Envii estat	Environment for open communication was established and maintained.		Good cross talk – flow and direct.	of information was fluid, clear,
LEADERSHIP	Capt coord	Captain showed leadership and verbally coordinated flight deck activities.		In command, decisive participation.	, and encouraged crew

As one might hope, the large majority of flights in the LOSA Archive are rated good or outstanding for Captain Leadership and Communication Environment and the TEM statistics bear out the effectiveness of these behaviors.

The table below shows that despite having the same level of threat complexity (i.e., the same number of threats per flight on average), flights that have outstanding ratings for Leadership and Communication Environment have an average 2.3 errors per flight vs. an average 7.0 errors on flights rated poor for Leadership and Communication Environment. In fact, the flights with poor ratings have approximately 3 times the number of mismanaged threats, errors and undesired aircraft states as the flights with outstanding ratings for Leadership and Communication Environment.

Ratings for Leadership, Communication Environment and TEM Indicators

	LOSA Observer Ratings for Captain Leadership and Communication Environment				
I EM Indicator Average Number per Flight	Outstanding Leadership	Good/Outstanding Leadership	Poor Leadership		
	Outstanding Communication	Poor Communication	Poor Communication		
Threats	4.9	4.3	5.0		
Mismanaged Threats	0.3	0.7	1.1		
Errors	2.3	5.6	7.0		
UAS	0.4	1.4	1.8		

The center column in the table is particularly informative because it shows that even when the Captain's Leadership is rated good or outstanding, a poor communication environment in the cockpit still produces poor results as evidenced by the TEM indicators – mismanaged threats, errors, and UAS – these being notably higher especially undesired aircraft states.

This result suggests there can be the perception of good leadership with a 'directive' Captain; however, this is really only acceptable in certain circumstances (to be illustrated in narrative below). The Captain can direct the flight in a manner that produces a text book performance. However, the resultant communication environment is not conducive to the First Officer providing effective monitoring/cross-checking or input should it be needed. Hence, *the much needed improvement in Monitoring/Cross-Checking that earlier targets have identified is inextricably linked to the Communication Environment established by the Captain.* 

# Section 8 ATC Threat Management

ATC threats are the second most common threat type observed in the LOSA Archive (just behind Adverse Weather). About 12% of ATC threats induce or contribute to a crew error such that 10% of flights in the LOSA Archive have a mismanaged ATC threat.

ATC Threat	% of all ATC Threats	% of All Mismanaged ATC Threats	Most Common ATC-Linked Errors	% of ATC- Linked UAS	Most Common UAS
Challenging clearances or tough to meet restrictions	39%	44%	Manual Handling /Flight Control Automation	60%	70% are Aircraft Handling Deviations
Runway changes	13%	18%	Automation Briefing SOP Cross-Verification	14%	70% are Incorrect Aircraft Configurations
Difficulty understanding controller accent or language	11%	14%	Communication	5%	50% are Ground Navigation UAS

**Top 3 ATC Threats & Their Outcomes** 

The table above shows that of all the ATC threats encountered, about 40% involve challenging clearances or tough to meet restrictions, 15% involve runway changes, and 10% involve difficulty understanding the controllers' language (though of course this last threat varies depending on the airline and the routes flown).

The errors prompted by challenging clearances/tough to meet restrictions are predominantly Manual Handling/Flight Control and Automation errors. About 60% of all the undesired aircraft states that are linked to a mismanaged ATC threat via crew error are the result of mismanaged challenging clearances/tough to meet restrictions, and most of the UAS are Aircraft Handling Deviations such as speed, lateral and vertical deviations.

The errors prompted by runway changes tend to be Automation, Briefing, and SOP Cross-Verification errors. Of the undesired aircraft states that result from a mismanaged ATC threat, about 15% of them link back to these runway changes, and most of them involve Incorrect Aircraft Configurations such as wrong settings.

Finally, the errors prompted by difficulty understanding what the controller is saying are usually Communication errors (wrong readbacks or callbacks). Only 5% of the linked undesired aircraft states are due to these threats, and about half of them are Ground Navigation UAS such as a taxiway/ramp incursion.

The conclusion from this analysis is that challenging clearances/tough to meet restrictions pose the greatest risk to the crews. Crews often agree to clearances in order to 'help or 'assist' ATC (this is evident from the observers' narratives). The 'challenge' in the clearance is as a result of subsequent pilot mismanagement and was never the

intention of the Controller. Many of the errors could be considered 'minor' or 'nit picking' by pilots, but they all display a common theme of poor communication and cross-monitor when under operational time pressure.

# Section 9 TEM by Phase of Flight

If asked what phase of flight poses the greatest risk to flight crew, most people would say Descent/Approach/Land. And as more than half of all undesired aircraft states occur in Descent/Approach/Land, this intuitive response would appear to be correct. Extrapolating from this finding, one might also assume that Descent/Approach/Land has the most threats; however, the LOSA Archive proves this assumption wrong.

The table below highlights some of the similarities and differences between the two phases of flight in relation to TEM indicators. For example, 41% of all threats occur during Predeparture/Taxi-Out as compared 31% in Descent/Approach/Land, while the majority of undesired aircraft states (54%) occur in Descent/Approach/Land vs. 18% in Predeparture/Taxi-Out.

TEM Indicator % occurring in each phase	Phase of Flight		
	Predeparture/Taxi-out	Descent/Approach/Land	
Threats	41%	31%	
Mismanaged Threats	36%	38%	
Errors	29%	39%	
Mismanaged Errors	23%	51%	
UAS	18%	54%	

A Comparison of TEM Rates in Predeparture/Taxi-out vs. Descent/Approach/Land

The tables below list the most common threats, errors and undesired aircraft states in the two busiest phases of flight.

Threat	Error	Undesired Aircraft State
MEL/CDL with operational implications	Incorrect or incomplete briefing	Incorrect Aircraft Configuration - Systems
On-time performance pressure	Checklist performed from memory	Incorrect Aircraft Configuration - Automation
Aircraft malfunction unexpected by the crew	Wrong readback or callback to ATC	Incorrect Operation with MEL/Malfunction
Flight attendant interruption to pilot duties	Missed checklist item	Incorrect Aircraft Configuration - Engines
Terrain	Failure to cross-verify FMC/FMGC entries	Taxi too Fast

#### Top 5 Threats, Errors & Undesired Aircraft States in Predeparture/Taxi-out

#### Top 5 Threats, Errors & Undesired Aircraft States in Descent/Approach/Land

Threat	Error	Undesired Aircraft State
Challenging clearances or tough to meet restrictions	Omitted Altitude Callout	Speed too High
Terrain	Unintentional speed deviation	Unstable Approach
Thunderstorms/turbulence	Incorrect or incomplete briefing	Incorrect Aircraft Configuration - Automation
Icing or snow	Omitted Descent/Approach callouts	Incorrect Aircraft Configuration - Systems
Runway change	Wrong flight guidance altitude entered	Continued Landing after Unstable Approach

## Threats by Phase of Flight

Phase of Flight	% of All Threats	% of Environmental Threats	% of Airline Threats	% of Mismanaged Threats
Predeparture/Taxi-out	41%	24%	76%	36%
Takeoff/Climb	16%	20%	5%	17%
Cruise	8%	10%	5%	6%
Descent/Approach/Land	31%	42%	8%	38%
Taxi-in/Park	4%	4%	6%	4%

The three busiest phases of flight are charted below showing the frequency and type of threats that were observed. Each bar represents the total number of threats in each threat type. The blue portion of each bar represents the number of threats that were well-managed or inconsequential while the red portion represents the number of threats that linked to or induced a crew error. All three charts have been drawn to the same scale to visually emphasize the difference in threat profile across phase of flight.



#### Threats by Phase of Flight

## **Errors by Phase of Flight**

Phase of Flight	% of All Errors	% of Aircraft Handling Errors	% of Procedural Errors	% of All Mismanaged Errors
Predeparture/Taxi-out	29%	26% 31% 23%		
Takeoff/Climb	19%	19%	18%	18%
Cruise	7%	6% 7% 4%		
Descent/Approach/Land	39%	43% 37% 51%		
Taxi-in/Park	6%	6% 7% 4%		

The three busiest phases of flights are charted below. Each bar represents the total number of errors in each error type. The blue portion of each bar represents the number of errors that were well-managed or inconsequential, the pink portion represents the number of errors that were mismanaged to additional error, and the red portion represents the number of errors that were mismanaged to an undesired aircraft state. All three charts have been drawn to the same scale to visually emphasize the difference in error profile across phase of flight.



#### Errors by Phase of Flight

# Section 10 Weather Radar Usage

8% of LOSA Archive flights face a Thunderstorm Threat, and 10% of these threats are mismanaged. The most common linked errors are:

- Wrong radar settings
- Course or heading deviations without ATC clearance
- Weather penetration

About half of these thunderstorm-induced errors result in an undesired aircraft state such as Incorrect Aircraft Configurations, Lateral or Speed Deviations.

The LOSA Collaborative has observed a wide range of effectiveness in weather radar usage and weather avoidance techniques. In most cases the onboard equipment is utilized to provide warning of weather and there is discussion of a suitable track to avoid weather penetration. The fact that the PM is handling the radios ensures the PF has to liaise in order to request a track deviation from ATC.

It is evident from the observers' narratives that the "normal" request for deviation is "up to 10 miles", even when avoiding amber or red radar returns. For many of the airlines there was an operations manual requirement to avoid weather by margins greater than this, especially on the downwind side of a cell. In practice, much closer margins are applied, usually less than 10 miles.

On departure there is sometimes a conflict between display of TERR and Radar, which is not addressed early enough. In the cruise phase radar settings and tilt management is variable but is usually adjusted when first making visual contact with cells during daylight or lightning flashes at night.

The overarching theme in weather avoidance is lack of forward planning. In all of the penetration events, late identification of the threat was a contributory factor.

## Wrong Radar Settings

These errors were divided equally between crew members. Two behaviors in particular were significant – weather radar not switched ON when required, and incorrect use of Tilt or Gain functions. It seems one of the least understood aspects of airborne weather radar is the subject of antenna tilt.

## Weather Avoidance and Intentional Noncompliance

About a quarter of the Thunderstorm-linked errors involve some form of Intentional Noncompliance, the most common being deviations without ATC clearance and deliberating navigating through known bad weather. As mentioned previously, the overarching theme in weather avoidance is lack of forward planning. In all of the penetration events, late identification of the threat was a contributory factor.

# Appendix. Error Detection

# LOSA Archive Report: 10 Target Areas for **Evidence Based Training**

# IATA ITQI EBT Working Group Report

September 2010



PO Box 684645 Austin, Texas USA 78768

# **Table of Contents**

INTRODUCTION	1
SUMMARY OF KEY FINDINGS	1
Phase of Flight	3
Q. Are there phase of flight differences with error detection and action?	3
Q. Does error detection vary across phases of flight for different types of errors?	3
Error Type	4
Q. Are there errors that are detected and acted upon more than others?	4
ERROR CAUSATION	5
Q. Does the person who commits the error also detect it or is it more often the other person?	5
Q. Does the pattern differ for different types of errors?	5
PILOT FLYING/PILOT MONITORING	6
Q. Does the Pilot Monitoring (PM) detect more errors than the Pilot Flying (PF)?	6
INTENTIONAL NONCOMPLIANCE	7
Threat & Error Management Countermeasures	8
Q. Which TEM countermeasures are most associated with the ability to detect errors?	8
THE ERROR DETECTION DILEMMA	9
Q. Why are so many errors not acted upon by flight crews in LOSA?	9

## Introduction

The LOSA Archive shows that 26% of all errors logged by observers are detected and acted upon by flight crews. This appendix explores some of the underlying factors that give rise to this error detection rate.

In LOSA, there are two primary responses to flight crew error that can be logged by observers. They are:

- 1. Detected with Action
- 2. No Action Taken (Undetected or Ignored)

Error responses in LOSA are limited to what an observer can see in the cockpit without querying the flight crew. It is this methodological restriction that explains why error detection is further substantiated by requiring observers to record whether a flight crew attempts to correct an error upon detection. Those errors not acted upon are assumed to be ignored or undetected.

It is also important to note that error responses collected during LOSA are mutually exclusive of error outcome. In other words, an error that is detected and acted upon does not guarantee an inconsequential outcome. In fact, 1% of errors detected and acted upon by a flight crew link to an additional error or undesired aircraft state due active mismanagement.

## **Summary of Key Findings**

- Manual Handling/Flight Control error detection/action taken is notably stronger in Predeparture/Taxi-Out than in the other phases of flight.
- Checklist error detection is better in Cruise and Descent/Approach/Land than in other phases of flight. Callout error detection is better in Takeoff/Climb.
- 41% of Aircraft Handling errors are detected and acted upon vs. 16% of Procedural errors. Automation has the best rate of all error types 53% of Automation errors are detected and acted upon.
- Captains detect 27% of the First Officer mistakes; First Officers detect 18% of the Captain's errors.
- Once an error has been committed, people are more capable of detecting other people's errors than their own.
- Across all three error groups, the Captain as PF detects/acts on more errors than does the First Officer as PF, particularly for Communication errors. There is little difference in PM rates.
- As the rate of Intentional Noncompliance increases, the rate of errors detected and acted on decreases.

- Of the TEM Countermeasures, error detection is most closely aligned with the quality of Monitoring/Cross-Checking in *all* phases of flight and the quality of the Briefing in Predeparture/Taxi-Out.
- One-quarter of all errors in the cockpit are detected, acted upon and inconsequential. One-half of all errors in the cockpit go undetected/not acted upon and are *also* inconsequential. This reinforcement for non-action encourages crews to 'take shortcuts' as experience has taught them over and over that most errors are inconsequential, whether they act on them or not.

## **Phase of Flight**

Phase of Flight	% of Errors Detected with Action
Predeparture/Taxi-Out	30%
Takeoff/Climb	25%
Cruise	25%
Descent/Approach/Land	27%
Taxi-in/Park	17%

#### Q. Are there phase of flight differences with error detection and action?

There is little difference amongst the first four phases of flight in that 25-30% of errors are detected and acted upon. Taxi/Park has the lowest rate of errors detected and acted upon (17%) because approximately one-half of the errors in Taxi/Park are Intentional Noncompliance errors vs. about one-quarter of errors in the other phases. These errors include taxi duties performed before leaving the runway, admin duties performed at inappropriate times, and checklists performed from memory, omitted, or self-initiated. [Using the LOSA definition, Intentional Noncompliance errors are typically not corrected because they are intentionally committed by the crew. See the later section on Intentional Noncompliance and error detection.]

Error Turo	% of Errors Detected with Action in each Phase of Flight						
спогтуре	Predeparture/Taxi-Out	Takeoff/Climb	Cruise	Descent/Approach/Land	Taxi/Park		
Manual Handling/Flight Control	53%	21%	25%	30%	27%		
Automation	60%	50%	50%	52%	-		
System/Instrument/Radio	50%	36%	44%	39%	43%		
Checklist	17%	17%	32%	30%	14%		
Callout	-	29%	16%	19%	-		

Q. Does error detection vary across phases of flight for different types of errors?

Detection rates do differ for some error types across different phases of flight. The largest difference is seen with Manual Handling/Flight Control errors - error detection/action is notably stronger in Predeparture/Taxi-Out than in the other phases of flight (53% of Manual Handling/Flight Control errors are detected and acted upon during Predeparture/Taxi-Out vs. 21-30% of Manual Handling/Flight Control errors being detected and acted upon in later phases of flight). When compared with the other Aircraft Handling error types, it seems that error detection for Manual Handling/Flight Control errors weakens notably after Predeparture/Taxi-Out, while Automation and System/Instrument/Radio error detection rates stay relatively the same.

Of the Procedural error types, Checklist error detection is better in Cruise and Descent/Approach/Land while Callout error detection is better in Takeoff/Climb.

## **Error Type**

#### Q. Are there errors that are detected and acted upon more than others?

The rates of error detection and action are much higher for Aircraft Handling errors than for Procedural errors. Specifically, 41% of Aircraft Handling errors are detected and acted upon vs. 34% of Communication errors and 16% of Procedural errors.

The detection and action rates for Procedural errors are shown below:

Procedural Errors	% of Errors Detected with Action
Briefing	20%
Callout	22%
Checklist	20%
Documentation	30%
General Procedural	7%
PF/PM Duty	5%
SOP Cross-Verification	9%

Automation errors have the best detection with action rates of all error types - 53% of Automation errors are detected and acted upon by flight crews.

Of the more common Aircraft Handling errors, those with the lowest rates of error detection are listed in the table below. Many of the errors in these categories become undesired aircraft states before the crew becomes aware of the problem.

Aircraft Handling Error Code	% of Errors Detected with Action
Unintentional vertical deviation	41%
Wrong speed brakes setting	39%
Incorrect Nav Display setting	35%
Unintentional landing deviation	32%
Wrong radar setting	30%
Unintentional lateral deviation	29%
Unintentional speed deviation	24%
Wrong power/thrust setting	22%
Wrong anti-ice setting	19%

## **Error Causation**

	Detected with Action By					
Who Caused the Error	Captain	First Officer	Both Pilots at the Same Time	Other (e.g., ATC)	Nobody	
Captain	6%	18%	28%	5%	43%	
First Officer	27%	5%	22%	8%	38%	

#### Q. Does the person who commits the error also detect it or is it more often the other person?

The LOSA Archive data show that people are not good at detecting their own errors, once they have been committed. Both Captains and First Officers detect only 5-6% of the errors that they make. About one-quarter of the time, the pilots detect the error together. It is informative that First Officers detect 18% of Captain's errors, whereas Captains detect 27% of the First Officer's mistakes.

#### Q. Does the pattern differ for different types of errors?

	Detected with Action By			
Error Type Caused By	Captain	First Officer	Both Pilots at the Same Time	
Aircraft Handling Errors - caused by Captains	9%	24%	17%	
Aircraft Handling Errors - caused by First Officers	39%	8%	10%	
Procedural Errors - caused by Captains	3%	12%	39%	
Procedural Errors - caused by First Officers	17%	4%	34%	
Communication Errors - caused by Captains	4%	27%	14%	
Communication Errors - caused by First Officers	37%	3%	8%	

The general pattern is consistent across error types, i.e., Captains detect more errors than First Officers and people are more capable of detecting other people's errors than their own. For example, Captains can detect 39% of the Aircraft Handling errors made by First Officers but only 9% of their own Aircraft Handling errors. And similarly, First Officers can detect 12% of the Procedural errors made by Captains, but only 4% of their own Procedural errors.

## **Pilot Flying/Pilot Monitoring**

	All Errors – Who Detected the Error?					
Captain as PF First Officer as PF Captain as PM First Officer as PM Both						Other/Nobody
	7%	4% 7% 6%			26%	50%

#### Q. Does the Pilot Monitoring (PM) detect more errors than the Pilot Flying (PF)?

The table above shows very little difference in detection rates – 11% of errors are detected by the PF (Captain and First Officer numbers combined) and 13% of errors are detected by the PM. A difference starts to emerge when information about response to error is combined with information about who detected the error, as shown in the table below. Of the errors that are detected and acted upon, the Captain as PF detects/acts on more than does the First Officer as the PF (rates for PM are about the same).

Of the Error Detected with Action . Who Detected the Error?					
	OI the En	UIS DELECTED WITH ACTION			
Captain as PF	Captain as PF First Officer as PF Captain as PM First Officer as PM Both Other/N				
23%	13%	25%	22%	13%	4%

The table below goes down one more level, to the type of error that is detected and acted upon. Here you can see that across all three error groups, there is little difference in PM rates, while the Captain as PF detects/acts on more than does the First Officer as PF, particularly for Communication errors.

Error Typo	Of the Errors Detected with Action - Who Detected the Error?						
Enor type	Captain as PF	First Officer as PF	Captain as PM	First Officer as PM	Both	Other	
Aircraft Handling	20%	11% 29% 24%	•		14%	2%	
Procedural	21%	14% 24% 22%	,		13%	6%	
Communication	45%	20% 15% 12%	,		7%	1%	

## **Intentional Noncompliance**

All Intentional Noncompliance errors observed in LOSA must meet one of four conditions:

- The error is committed multiple times during one phase of flight, e.g., missing multiple altitude callouts during descent (if this condition is met, the error is coded as one Intentional Noncompliance error);
- The crew openly discusses that they are intentionally committing an action that is against published SOP;
- The observer determines that the crew is time-optimizing SOP when time is otherwise available (i.e., performing a checklist from memory); or
- An aircraft handling error is determined by the observer to involve an increase in risk when more conservative options are available (e.g., intentionally ducking under a glideslope).

In the LOSA Archive, one-quarter of all observed errors were rated by the observers (and later verified by airline representatives at the data roundtables) as Intentional Noncompliance using the definitions above. Errors that are committed intentionally are rarely rectified, because they are not seen as errors in the first place but rather as time-optimizing short-cuts or 'pilot knows best' personal procedures. The table below shows that 25% of all errors are recorded as Intentional Noncompliance errors, of which 96% are not acted upon.

Error Type	Detected with Action	No Action Taken	Total
Intentional Noncompliance	4%	96%	100% [25%]
Unintentional error	34%	66%	100% [75%]

To highlight the relationship between Intentional Noncompliance and error detection, the table below shows the percentage of each error type that is Intentional Noncompliance and the percentage of errors detected and acted upon. Note the negative correlation, i.e., as the rate of Intentional Noncompliance increases, the rate of errors detected/acted upon decreases. An obvious challenge for improving error detection rates is to first get pilots to recognize Intentional Noncompliance as another form of error to be detected and corrected.

Error Type	% of Errors that are Intentional Noncompliance	% of Errors Detected with Action
All Aircraft Handling Errors	9%	41%
All Communication Errors	10%	34%
All Procedural Errors	38%	16%

## **Threat & Error Management Countermeasures**

Threat and error countermeasures are techniques used to anticipate threats, avoid errors, and detect and mitigate events/errors that do occur. There are many hardware design and procedural countermeasures employed in aviation to minimize adverse outcomes. The countermeasures observed in a LOSA refer specifically to crew behaviors that have been shown to enhance crew performance. These countermeasures were derived from research performed at The University of Texas at Austin and are grouped into four higher-level activities: Team Climate, Planning, Execution, and Review/Modify.

LOSA Observers rate a countermeasure only when they observe it or if its absence is significant (e.g., a crew fails to evaluate the flight plan in light of new information). A one-time rating is given for Leadership, and Communication Environment; other countermeasures are rated across different phases of flight. Observers rate the crew's performance with the following scale:

1	2	3	4	-
Poor	Marginal	Good	Outstanding	Not Observed
Observed performance had an impact on safety	Observed performance was barely adequate	Observed performance was effective	Observed performance was truly noteworthy	Behavior was not observed

#### Q. Which TEM countermeasures are most associated with the ability to detect errors?

To answer this question, flights from the LOSA Archive that had one or more errors were divided into 7 groups flights where all the errors were detected and acted upon, flights with one error not detected/acted upon, flights with two errors not detected/acted upon, and on up to flights with 6 or more errors not detected and/or acted upon. A multivariate discriminant analysis then employed all of the countermeasure ratings across Predeparture/Taxi-Out, Takeoff/Climb, and Descent/Approach/Land to find the best combination of countermeasures that could predict this grouping of flights.

The answer was statistically stable, simple and sensible. The systematic differences in rates of error detection were due to the quality of Monitoring/Cross-Checking in *all* 3 phases of flight and the quality of the Briefing in Predeparture/Taxi-Out.

While the analysis may seem complex, the results can be interpreted with relative ease. First, a lapse in Monitoring/Cross-Checking in *any* part of the flight is likely to lead to errors being not detected/acted upon. And second, the Briefing in Predeparture sets the tone for the rest of the flight. Recall that errors not detected/acted upon include those Intentional Noncompliance errors that are knowingly committed and ignored. It can be the initial Briefing that directly or indirectly sets the expectation for the acceptable level of noncompliance as well as adherence to procedures and attention to detail.

## The Error Detection Dilemma

#### Q. Why are so many errors not acted upon by flight crews in LOSA?

Of all the errors committed in the cockpit, 26% are detected and acted upon, while 74% are not acted upon by the crew. In such a safety-conscious industry, why is the rate so high?

Error Response	Outcome		
	Inconsequential	Additional Error or Undesired Aircraft State	Total
Detected and acted upon	95%	5%	100%
Undetected and/or not acted upon	71%	29%	100%

95% of all errors that are detected and acted upon are inconsequential and 5% lead to additional error or an undesired aircraft state. By comparison, 71% of all errors that go without action taken are inconsequential with 29% linking to an additional error or an undesired aircraft state. On the surface, it appears obvious that errors that are detected and acted upon have a higher 'success rate' (defined as inconsequential outcome). However, it is important to remember that only 26% of all errors fit this first category of detected/acted upon error and that error detection needs to be understood in the context of all errors.

Error Response	Outcome		
	Inconsequential	Additional Error or Undesired Aircraft State	Total
Detected with Action	25%	1%	26%
No Action Taken	52%	22%	74%
Total	77%	23%	100%

Unlike the first table, this table shows each cell as a percentage of *all observed* errors to highlight the dilemma with error detection. Of all the errors committed in the cockpit, one-quarter are detected and acted upon and are then inconsequential (25%). However, one-half of all errors in the cockpit (52%) go undetected/not acted upon and are *also* inconsequential. This lack of consequential outcome provides powerful reinforcement for not detecting and/or acting upon all errors. It encourages crews to 'take chances' or 'take shortcuts' as experience has taught them over and over that most errors are inconsequential, whether they act on them or not. The fact that three-quarters of all errors (77%) are inconsequential is a testament to the safety measures and redundancies built into the system. And while these checks are clearly a good thing, the unintended consequence has been weakened monitoring and error detection over time.

This then is the dilemma of error detection. On the one hand, pilots learn over time that most errors are inconsequential even when they don't act on them. And on the other hand, they learn (to their surprise) that nearly all the errors that are consequential are the errors they have missed or overlooked.



## APPENDIX 2 Accident incident analysis



## INTRODUCTION

This appendix contains statements of results drawn from the EBT Accident-Incident analysis containing information, which follows from factor analyses and relates to the objectives of the study. The statements are organized by topics relative to training and emanate from the rankings of occurrence of the factors and competencies reported in accidents and incidents. The statements are followed by graphical representations of data providing an intuitive demonstration of the results.

### 2.1 ADVERSE WEATHER

#### Gen4 Jet

- As the overall accident rate has reduced, exposure to weather related accidents has reduced from 0.8 to 0.65 per million take-offs.
- When comparing the last 11 years compared to the previous era, adverse weather is a greater factor in accidents and incidents, rising from 37% to 46%.
- Adverse weather is the number 1 factor in accidents over the last in last 11 years for all accidents
- Adverse weather is ranked 3<sup>rd</sup> after non-compliance and CRM, as a factor in accidents with high training effect. It has increased by a factor of 2 when comparing the previous 11-years data.

#### Gen3 Jet

- Adverse weather has reduced slightly as a factor, in comparison to the period prior to the last 15-years. Over the last 15-years, adverse weather remains the number 1 ranked factor in accidents and serious incidents, evident in 40% of events.
- When considering fatal accidents only, adverse weather is ranked 3<sup>rd</sup> after CRM and system malfunction, at 20% of all fatal accidents over the last 15 years.
- Adverse weather is currently ranked 3<sup>rd</sup> as a factor in accidents with high training effect, at 30% overall, implying substantial benefit from mitigation through training.

#### Gen2 Jet

- Adverse weather is ranked 2<sup>nd</sup> as a factor in accidents, and has increased in the most recent 15year period from 30% to 35%.
- Adverse weather is now the number 1 ranked factor by percentage of occurrence in fatal accidents, having doubled in the most recent 15-year period to 60%.
- Exposure data indicates adverse weather as a factor in fatal accidents at the rate of 1 per million take-offs, over the most recent 15-year period.
- For accidents with high training effect, adverse weather is ranked 3<sup>rd</sup> after CRM and poor visibility, at 40% with no significant change over the last 15-year period and before, implying substantial benefit from mitigation through training.

#### Gen3 Turboprop

#### Note, there was no available exposure data for this generation

- Adverse weather has increased as a factor in accidents from 25% to 40% when comparing the most recent 15-year period to the previous period.
- Adverse weather is now the number 1 ranked factor by percentage of occurrence in accidents, having risen from a previous ranking of 3<sup>rd</sup>.
- For accidents with high training effect, adverse weather is now ranked 2<sup>nd</sup> at 60% after CRM. Prior to the last 15 years it was a factor in 65% of accidents.



#### • Gen2 Turboprop

Note, there was no available exposure data for this generation

- Prior to the last 15-years, adverse weather was ranked 2<sup>nd</sup> with a 40% rate of reported occurrence in accidents.
- o There was insufficient data to draw further conclusions over the most recent 15-year period.

## 2.2 COMPETENCIES - GENERAL

Combining results from both Gen4 and Gen3 Jets, it is clear that some patterns emerge in respect of competencies.

Manual Aircraft Control is the most noted competency in all accidents, followed by Situation Awareness, and Application of Procedures and Knowledge.

With respect to the most critical flight phases, TO/LDG/APP, patterns are consistent with the statements above, except that the peaks with respect to Manual Aircraft Control, Situation Awareness and Application of Procedures and knowledge, are much more pronounced.

In less critical flight phases, the difference is very small, except in GND, where Situation Awareness is predominant.

#### Gen4 Jet

- Competency issues most prevalent are:
  - Manual Aircraft Control
  - Situation Awareness
  - Application of Procedures and knowledge
- In the APP phase over the last 21 years, the following competency issues most prevalent are:
  - Manual Aircraft Control
  - Situation Awareness
  - Application of Procedures and knowledge
- In the LDG phase over the last 21 years, the following competency issues most prevalent are:
  - Manual Aircraft Control
  - Situation Awareness
  - Application of Procedures and knowledge
- This pattern remains consistent when combining the APP and LDG phases
  - Manual Aircraft Control
  - Application of Procedures and knowledge
  - Situation Awareness

#### Gen3 Jet

- Competency issues most prevalent are:
  - Manual Aircraft Control
  - Situation Awareness
  - Application of Procedures and knowledge

- Competency issues most prevalent are:
  - Manual Aircraft Control (which is very dominant)
  - Problem Solving and decision-making
  - Situation Awareness
  - Application of Procedures and knowledge



#### Gen3 Turboprop

• Competency issues most prevalent are:

- Manual Aircraft Control
- Application of Procedures and knowledge
- Knowledge
- Situation Awareness

#### • Gen2 Turboprop

- Competency issues most prevalent are:
  - Manual Aircraft Control
  - Problem Solving and decision-making
  - Situation Awareness

#### 2.3 COMPLIANCE

#### Gen4 Jet

- During the last 11-year period, compliance as factor has decreased from being ranked 3<sup>rd</sup> at 36%, to 23%.
- For accidents with a high training effect, compliance is a substantial factor, at 75% having risen from 63%.

#### Gen3 Jet

- During the last 15-year period, compliance as factor has reduced from being ranked 5<sup>th</sup> at 24% to 14%.
- For fatal accidents, the rate of occurrence of this factor has reduced from 50% to 21%.
- For accidents with a high training effect, compliance is a substantial factor, at 50% overall and ranked 2<sup>nd</sup>.

#### Gen2 Jet

- The rate of accidents involving compliance has increased slightly over the most recent 15-year period considered, but other factors have increased much more.
- Compliance is now ranked 9th at 13%, having decreased from 22%.
- For fatal accidents, the rate of occurrence of compliance has decreased from 33% to 7%.
- For accidents with a high training effect, compliance is a substantial factor, at 39% overall and ranked 5<sup>th</sup>.

#### Gen3 Turboprop

#### Note, there was no available exposure data for this generation

- During the last 15-year period, compliance as factor has decreased from 25% to 11% when compared to the previous period.
- For accidents with a high training effect, compliance remains is a substantial factor, at 50% overall and ranked 3<sup>rd</sup>.

#### • Gen2 Turboprop

#### Note, there was no available exposure data for this generation

- During the last 15-year period, compliance as factor has risen from 28% to 38% when compared to the previous period.
- For accidents with a high training effect, compliance is a substantial factor, at 78% having risen from 65% overall and ranked 2<sup>nd</sup>.

## 2.4 LANDING

- Gen4 Jet
  - The highest total numbers of accidents occur in the LDG & GND phases. In the period considered before 2000, LDG was the flight phase with the largest number of accidents, twice as many as any other phase. Over the most recent 11-year period considered, the trend has decreased with the APP phase becoming predominant.
  - The APP phase is now considered as the number 1 flight phase in terms of the number of accidents.
  - $\circ$   $\;$  The factors which contribute to accidents in the LDG phase are:
  - Compliance/CRM/Adverse Weather/Adverse Wind (These factors occur in 50% of accidents)
  - When considering the sum of all factors in all accidents, there are more factors occurring in accidents in the LDG phase than in any other phase.
  - For fatal accidents, the LDG phase is ranked 3<sup>rd</sup> after APP and TO.
  - When considering the sum of all factors in fatal accidents, there are more factors occurring in accidents in the LDG phase than in any other phase.
  - The factors, which are most prevalent in fatal accidents during LDG over the most recent 11-year period are:
    - Adverse weather/CRM/Compliance

#### Gen3 Jet

0

- The LDG phase which was previously ranked 3<sup>rd</sup> in accidents, has now climbed to number 1, over the last 15-years.
- When considering the sum of all factors in all accidents, there are more factors occurring in accidents in the LDG phase than in any other phase.
  - The factors which are most prevalent in accidents in the LDG phase are:
    - CRM/Adverse Weather/System Malfunction/Poor visibility/Compliance.
- The LDG phase is not the highest ranked phases for fatal accidents.
- When considering the sum of all factors in fatal accidents, there are more factors occurring in accidents in the LDG phase than during any other phase.
- The factors which are most prevalent in fatal accidents during LDG over the most recent 15-year period are:
  - CRM/Adverse Weather/Windshear/System Malfunction/Adverse Weather/Mismanaged System

#### Gen2 Jet

- The LDG phase which was previously ranked number 1 in accidents has dropped to a ranking of number 2 over the last 15-years.
- o The APP phase is now ranked number 1 over the last 15-year period.
- For all accidents, the most prevalent factors are:
  - CRM/System Malfunction
- For fatal accidents in the last 15 years, APP was the predominant phase.
- When considering the sum of all factors in fatal accidents, there are more factors occurring in accidents during the APP phase than in any other phase.
- The factor most prevalent in fatal accidents during LDG over the most recent 15-year period are:
  - Poor visibility/Runway taxiway condition.

#### Gen3 Turboprop

#### Note, there was no available exposure data for this generation

- The LDG phase was previously ranked 2<sup>nd</sup> but has now dropped to 5<sup>th</sup> overall in the most recent 15-year period.
- The factors which are most prevalent in all accidents during LDG over the most recent 15-year period are:
  - CRM/Adverse Weather/System Malfunction/Runway taxiway condition/Poor visibility.



#### Gen2 Turboprop

#### Note, there was no available exposure data for this generation

- LDG is ranked number 1 in flight phases for the most accidents for all periods considered.
- When considering the sum of all factors in all accidents, there are more factors occurring in accidents in the LDG phase than in any other phase.
- The factors which are most prevalent in accidents during the LDG phase are:
  - System malfunction/Compliance/CRM.

#### 2.5 LEADERSHIP & TEAMWORK

#### Gen4 Jet

- Exposure to an accident or serious incident involving Leadership and teamwork as a competency issue has risen from 0.12 per million take-offs to 0.4 per million take-offs in the most recent 11-year period.
- Leadership and teamwork is reported as a competency issue in 8% of all accidents, which is a reduction from 18% in the previous 11-year period.
- When considering serious incidents, Leadership and teamwork is not reported as a competency issue, implying that effective Leadership can prevent more serious events.

#### Gen3 Jet

- Exposure to an accident or serious incident involving Leadership and teamwork as a competency issue has reduced from 0.23 per million take-offs to 0.08 per million take-offs in the most recent 15year period.
- Leadership and teamwork is reported as a competency issue in 5% of all accidents, which is a reduction from 13% in the previous 15-year period.
- However the trend is reversed for fatal accidents where Leadership and teamwork is reported as a competency issue has risen from 7% to 15% in the most recent 15-year period.
- In serious incidents, where in many cases an accident was prevented by the crew action, Leadership and teamwork is conspicuously not reported as a competency issue providing evidence for research that effective Leadership could well have prevented an accident.

#### Gen2 Jet

- Exposure to an accident or serious incident involving Leadership and teamwork as a competency issue has increased from 0.11 per million take-offs to 0.19 per million take-offs in the most recent 15-year period.
- Leadership and teamwork is reported as a competency issue in 4% of all accidents.
- The percentage of fatal accidents with a Leadership and teamwork as a competency issue has risen from 4% to 7% in the most recent 15-year period.
- In serious incidents, Leadership and teamwork as a competency issue is only reported at 3%, providing evidence for research that effective Leadership could prevent more serious events.

#### Gen3 Turboprop

#### Note, there was no available exposure data for this generation

- Leadership and teamwork is reported as a competency issue in 8% of all accidents.
- When considering serious incidents, Leadership and teamwork as a competency issue has risen from 3%, to 7% over the last 15-years.

#### Gen2 Turboprop

#### Note, there was no available exposure data for this generation

 Leadership and teamwork is reported as a competency issue in 38% of all accidents, and this has risen from a previous figure of 17%.

#### **2.6 MANUAL AIRCRAFT CONTROL** (FLIGHT PATH MANAGEMENT – MANUAL)

#### Gen4 Jet

- Of the 9 competencies analyzed, the competency most reported as a problem is Manual Aircraft Control, it is a competency issue in 22% of accidents over the most recent period. It does show improvement from the previous 11-year study, where it was at more than 35%.
- For the period up to 2000, more than 0.8 accidents per million take-offs showed manual aircraft control as a competency issue, which then declined to 0.3 in the period 2000-2010.
- For accident with a high training effect, manual aircraft control remains the highest competency issue from data over the last 11 years as well as in the previous period.
- There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.

#### Gen3 Jet

- The exposure to accidents with manual aircraft control as a competency issue is stable over time, at approximately 30%. This is more than double the percentages of the other competencies.
- There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.
- For accidents with a high training effect, manual aircraft control remains the highest competency issue from data over the last 15-years as well as in the previous period.
- Manual aircraft control, as a competency issue stands at 40% in fatal accidents more than 15-years ago, as compared to over 50% in the most recent 15-year period.

- Of the 9 competencies analyzed, the competency at issue most often is Manual Aircraft Control, a competency issue in 40% of accidents over the period 1995-2010. This has increased by a magnitude of 3 times from the previous 15-year period.
- There are 4 accidents per million take-offs, 50% of them showing manual aircraft control as a competency issue.
- Manual aircraft control has always been amongst the top ranked competency issues in fatal accidents, but has risen in the most recent 15-year period to 60%.
- There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.
- For accidents and serious incidents with a high training effect, manual aircraft control is now considered a competency issue in 80% of events, an increase of 100% over the previous 15-year period.
- Exposure data indicates an increase in manual aircraft control as a competency issue, from of 0.2 to 0.7 for accidents with a high training effect, over the most recent 15-year period.



#### Gen3 Turboprop

#### Note, there was no available exposure data for this generation

- Manual aircraft control as a competency issue in all accidents has risen from 13% to 16% in the most recent 15-year period.
- Manual aircraft control is now ranked as the number 1 competency issue in accidents. There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.

#### Gen2 Turboprop

#### Note, there was no available exposure data for this generation

- Manual aircraft control shows an increase from 27% to 38% as a competency issue in all aircraft accidents, and is now ranked 2.
- There is a significant difference in the rate of manual aircraft control as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through effective manual control strategies.

#### 2.7 SURPRISE (SITUATION AWARENESS)

Little information can be directly inferred from accident and incident reports with respect to unexpected or surprise events being considered as competency issues. Surprise was not considered directly as a competency issue. It can however be indirectly inferred, that when there is a reported breakdown in situation awareness, there is a greater likelihood of unexpected events, and the management of surprises is more difficult. For this reason, situation awareness is considered as a competency issue affecting surprise.

#### Gen4 Jet

- For all accident data, Situation Awareness is among the top 3 ranked competency issues, the rate rising from 18% to 22% in the last 11-years, when compared with the previous time period.
- Situation Awareness is the number 1 competency, alongside Manual Aircraft Control, when analyzing competency issues in accidents and incidents.
- When analyzing incidents alone, Situation Awareness is the highest ranked competency issue at over 20%.
- Gen3 Jet
  - For all accident data, Situation Awareness is among the top 3 ranked competency issues, with the rate rising from 13% to 28% in the last 15-years, when compared with the previous period.
  - Situation Awareness is now ranked 2<sup>nd</sup> as the most significant competency issue, after Manual Aircraft Control.
  - When considering fatal accidents, Situation Awareness is ranked 2<sup>nd</sup>, in 29% of fatal accidents.
  - There is a significant difference in the rate of Situation Awareness as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through the maintenance or regaining of Situation Awareness.

- For all accident data, Situation Awareness is among the top 3 ranked competency issues with, the rate rising from 16% to 24% in the last 15-years, when compared with the previous period.
- When considering fatal accidents, Situation Awareness is ranked 2<sup>nd</sup> as a competency, contributory to 21% of fatal accidents, with a slight reduction from 23% in the previous period.

• There is a significant difference in the rate of Situation Awareness as a competency issue, between fatal accidents and serious incidents, this and the fact that analysts noted that in many cases in serious incidents that crew actions prevented an accident from occurring provides evidence that accidents are avoided through the maintenance or regaining of Situation Awareness.

#### Gen3 Turboprop

#### Note, there was no available exposure data for this generation

- For all accident data, Situation Awareness is ranked among the top 3 competency issues with, the rate decreasing from 17% to 14% in the last 15-years, when compared with the previous period.
- Situation Awareness is now ranked 3<sup>rd</sup> after Manual Aircraft Control and Application of Procedures and Knowledge.
- When considering incidents alone, Situation Awareness is the highest ranked competency issue at 18%.

#### • Gen2 Turboprop

#### Note, there was no available exposure data for this generation

• For all accident data, Situation Awareness is currently ranked 4<sup>th</sup>, with the rate rising from 15% to 17% in the last 15-years, as compared with the previous period.

#### 2.8 SYSTEM MALFUNCTION

#### Gen4 Jet

- System malfunction is ranked 5<sup>th</sup> as a factor and present in 15% of all accidents over the latest 11-year period.
- As a factor all accidents, system malfunction has increased from below 10% to above 15% from the previous period.
- For accidents with high training effect, system malfunction has decreased in occurrence from 25% of accidents to 5%. Although the available volume of data is relatively small, it seems reasonable to infer that training is an effective remediation tool.

#### Gen3 Jet

- System malfunction is ranked 3<sup>rd</sup> as a factor and present in 19% of accidents over the latest 15year period.
- As a factor system malfunction has increased from 14% to 19% in the last 15-year period.
- For fatal accidents, system malfunction is ranked 2<sup>nd</sup> and stable at 30% over the 2 time periods analyzed.
- For accidents with high training effect, system malfunction is ranked 6<sup>th</sup> and present in 18% of accidents over the last 15-years. Prior to this the figure was 27%, and therefore it seems reasonable to infer that training is an effective remediation tool.

- System malfunction is ranked number 1 as a factor and is present in 45% of accidents over the latest 15-year period.
- As a factor system malfunction has increased from 25% to 45% in the last 15-year period and has gone from 3<sup>rd</sup> to 1<sup>st</sup> in ranking.
- For fatal accidents, system malfunction is ranked 3<sup>rd</sup> occurring more than 50% of the time compared to the previous time period when it ranked 5<sup>th</sup> and only occurred at 20%.
- For accidents with high training effect, system malfunction is ranked 4<sup>th</sup> and present in over 40% of accidents over the last 15-years. This is up from an occurrence rate of about 20%.



#### Gen3 Turboprop

#### Note, there was no available exposure data for this generation

- System malfunction is ranked 3<sup>rd</sup> as a factor and is present in 22% of accidents over the latest 15year period.
- As a factor system malfunction has decreased as a percentage from 42% to 22% in the last 15year period with a ranking down from 1<sup>st</sup> to 3<sup>rd</sup>.
- For accidents with high training effect, system malfunction is present in 17% of accidents over the last 15-years.

#### • Gen2 Turboprop

#### Note, there was no available exposure data for this generation

- System malfunction is ranked number 1 as a factor and is present in 50% of accidents over the latest 15-year period.
- As a factor system malfunction is stable at 50% and remains number 1 for all flights analyzed.
- For accidents with high training effect, system malfunction is ranked 3<sup>rd</sup> and present in over 70% of accidents over the last 15-years. The rate went from 50% to over 70% in the latest period, although the available data set is small.

#### 2.9 TERRAIN

#### Gen4 Jet

- Terrain as a threat generally ranks low according to Gen4 Jet accident and incident data.
- As a contributory factor in accidents, terrain has reduced from 5% to 1% when comparing older data to that from the last 11-year period.
- When considering accidents with a high training effect, there has been a reduction in accidents including terrain as a factor, from 13% to 5% over the 2 periods analyzed.

#### Gen3 Jet

- Terrain as a threat generally ranks low according to Gen3 Jet accident and incident data, currently it is a factor in 2% of all accidents in the most recent 15-year period, compared to 3% previously.
- When considering fatal accidents, terrain ranks 6<sup>th</sup> overall but has decreased in the rate of occurrence from 21% to 15%.
- When considering accidents with a high training effect, the rate is low at 3% overall.

#### Gen2 Jet

- Terrain as a threat generally ranks 11th according to Gen2 Jet accident and incident data, but has increased in the most recent 15-year period to 11%, from 3% previously.
- When considering fatal accidents only, terrain ranks 8th overall but has increased in the rate of occurrence from 16% to 23% in the most recent 15-year period.
- When considering accidents with a high training effect, the rate of accidents with terrain as a contributory factor is at 14% overall.

#### Gen3 Turboprop

#### Note, there was no available exposure data for this generation

• Terrain as a threat generally ranks low according to Gen3 Turboprop accident data.

#### Gen2 Turboprop

#### Note, there was no available exposure data for this generation

• Terrain as a threat generally ranks low according to Gen2 Turboprop accident and incident data.

## 2.10 TURBOPROP GENERATION 2 ANALYSIS

#### 2.10.1 Data Statistics

#### 2.10.1.1 Demographics



Figure A2.10.1.1



#### **Demographics Continued**



Figure A2.10.1.1a



Figure A2.10.1.1b

#### 2.10.2 Global Accidents (Last 15 Years versus Before)

#### 2.10.2.1 Ranking of Factors for All Accidents (Turboprop Generation 2)

Ranking of factors as a percentage of fatal accidents, last 15Y vs. older (last 15 years in blue, earlier times in black).



Figure A2.10.2.1


#### 2.10.3 Global Fatal Accidents (Last 15 Years)

#### 2.10.3.1 Ranking of Factors for Fatal Accidents (Turboprop Generation 2)

Ranking of factors as a percentage of fatal accidents, last15Y vs. older



Figure A2.10.3.1

#### 2.10.4 Distribution by Flight Phase

#### 2.10.4.1 Distributions by Flight Phase (Turboprop Generation 2)

Number of accidents per Flight Phase last 15 years.



Figure A2.10.4.1

#### 2.10.4.2 Distribution of Specific Factors by Flight Phase (Last 15 Years)

Distribution of factors in accidents by Flight Phase (Turboprop Generation 2)

Figure A2.10.4.2





## 2.10.4.3 Distribution of Specific Factors by Flight Phase (Older)

Distribution of factors in accidents by Flight Phase (Turboprop Generation 2)



## 2.10.4.4 Distribution of Specific Factors by Flight Phase (Last 15 Years, Fatal Accidents only)

Distribution of factors in accidents by Flight Phase (Turboprop Generation 2)





## 2.10.4.5 Distribution of Specific Factors by Flight Phase (Older, Fatal Accidents only)

Distribution of factors in accidents by Flight Phase (Turboprop Generation 2)



## 2.10.4.6 Proportional Distributions of Specific Factors by Flight Phase

Proportional Distributions of Factors by Flight Phase (Last 15 years) (Turboprop Generation 2)

Figure A2.10.4.6





#### 2.10.5 Training Effect

## 2.10.5.1 Training Effect (Turboprop Generation 2)

Training effect for Turboprop Generation 2 aircraft (All Accidents) by flight phase



Figure A2.10.5.1





Figure A2.10.5.2

## 2.10.5.3 Training Effect, Previous Period (All Generations)



Figure A2.10.5.3





#### 2.10.5.4 Training Effect Most Recent Period (All Generations)

Figure A2.10.5.4

## 2.10.5.5 Training Effect, All Times (All Generations)



Figure A2.10.5.5



## 2.10.5.6 Training Effect, Previous Period (All Generations)



## 2.10.5.7 Training Effect, Most Recent Period (All Generations)



#### Figure A2.10.5.7



#### 2.10.6 Competencies in Accidents

## 2.10.6.1 Distributions of Deficient Competencies in Accidents (Turboprop Generation 2)

Deficient competencies in accidents comparing most recent to previous period



Figure A2.10.6.1

## 2.10.7 Competencies in Fatal Accidents

## 2.10.7.1 Distributions of Deficient Competencies in Fatal Accidents (Turboprop Gen 2)

Deficient competencies in fatal accidents comparing most recent to previous period



Figure A2.10.7.1



#### 2.10.8 Competencies in Incidents

## 2.10.8.1 Distributions of Deficient Competencies in Incidents (Turboprop Generation 2)

Deficient competencies in incidents comparing most recent to previous period



Figure A2.10.8.1

#### 2.10.9 Relative Risk Rank

## 2.10.9.1 Relative Risk Rank Table (Turboprop Generation 2)

	Frequency									
	% of event	s (all times	5)	Frequ	ency c (% *	ontribution	Sepa	arately at 3 Se	ev levels	
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	Total risk
CRM	80%	50%	0%	4.00	2.50	0.00	20.00	7.50	0.00	27.50
Adverse Weather/Ice	20%	21%	33%	1.00	1.04	1.67	5.00	3.13	1.67	9.79
Syst mal	40%	50%	83%	2.00	2.50	4.17	10.00	7.50	4.17	21.67
Eng Fail	40%	21%	0%	2.00	1.04	0.00	10.00	3.13	0.00	13.13
Poor Visibility	0%	13%	0%	0.00	0.63	0.00	0.00	1.88	0.00	1.88
Compliance	40%	38%	0%	2.00	1.88	0.00	10.00	5.63	0.00	15.63
Mis A/C State	60%	38%	0%	3.00	1.88	0.00	15.00	5.63	0.00	20.63
Upset	20%	4%	0%	1.00	0.21	0.00	5.00	0.63	0.00	5.63
Fatique	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Workload Distraction Pressure	40%	13%	0%	2.00	0.63	0.00	10.00	1.88	0.00	11.88
Mis-AFS	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Ground equipment	0%	4%	0%	0.00	0.21	0.00	0.00	0.63	0.00	0.63
Ground manoeuvring	0%	4%	0%	0.00	0.21	0.00	0.00	0.63	0.00	0.63
Ops/Type Spec	20%	4%	8%	1.00	0.21	0.42	5.00	0.63	0.42	6.04
Def Manuals	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Mis-Sys	40%	25%	0%	2.00	1.25	0.00	10.00	3.75	0.00	13.75
Def-Ops data	20%	4%	0%	1.00	0.21	0.00	5.00	0.63	0.00	5.63
MEL	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Physio	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Birds	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Fire	0%	4%	0%	0.00	0.21	0.00	0.00	0.63	0.00	0.63
Runway/Taxi condition	0%	4%	0%	0.00	0.21	0.00	0.00	0.63	0.00	0.63
Traffic	40%	8%	0%	2.00	0.42	0.00	10.00	1.25	0.00	11.25

Figure A2.10.9.1

## Relative Risk Rank Table (Continued)

	Frequency									
	% of event	s (all times	5)	Frequ	ency c (% °	ontribution	Separately at 3 Sev levels			
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	Total risk
Def-Proc's	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Crosswind	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ATC	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Cabin	0%	4%	8%	0.00	0.21	0.42	0.00	0.63	0.42	1.04
Def-Chk lists	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
R/W Incursion	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Terrain	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Wake Vortex	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Windshear	0%	8%	0%	0.00	0.42	0.00	0.00	1.25	0.00	1.25
D.G	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Def-DBs	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Def-Charts	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LF.P	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
NAV	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Pilot Incap	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Loss of comms	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Communication	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
SA	20%	17%	0%	1.00	0.83	0.00	5.00	2.50	0.00	7.50
Leadership and Teamwork	80%	38%	0%	4.00	1.88	0.00	20.00	5.63	0.00	25.63
Workload Management	20%	8%	0%	1.00	0.42	0.00	5.00	1.25	0.00	6.25
Problem Solving Decision Making	40%	29%	0%	2.00	1.46	0.00	10.00	4.38	0.00	14.38
Knowledge	40%	17%	0%	2.00	0.83	0.00	10.00	2.50	0.00	12.50
Application of Procedures & Knowledge	40%	42%	0%	2.00	2.08	0.00	10.00	6.25	0.00	16.25
Flight Management, Guidance and Automation	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Manual Aircraft Control	60%	38%	0%	3.00	1.88	0.00	15.00	5.63	0.00	20.63

Figure A2.10.9.1(cont)

## 2.10.9.2 Relative Risk Rank Priority

Relative Risk Ranking Priority for Prop Generation 2 (Turboprop Generation 2)

Factor	Priority
CRM	27.50
Syst mal	21.67
Mis A/C State	20.63
Compliance	15.63
Mis-Sys	13.75
Eng Fail	13.13
Workload Distraction Pressure	11.88
Traffic	11.25
Adverse Weather/Ice	9.79
Ops/Type Spec	6.04
Upset	5.63
Def-Ops data	5.63
Poor Visibility	1.88
Windshear	1.25
Cabin	1.04
Ground equipment	0.63
Ground manoeuvring	0.63
Fire	0.63
Runway/Taxi condition	0.63
Fatique	0.00
Mis-AFS	0.00
Def Manuals	0.00
MEL	0.00
Physio	0.00
Birds	0.00
Def-Proc's	0.00
Crosswind	0.00
ATC	0.00
Def-Chk lists	0.00
R/W Incursion	0.00
Terrain	0.00
Wake Vortex	0.00
D.G	0.00
Def-DBs	0.00
Def-Charts	0.00
L.F.P	0.00
NAV	0.00
Pilot Incap	0.00
Loss of comms	0.00

Figure A2.10.9.2



## 2.10.9.3 Relative Risk Rank Chart

Relative Risk Ranking for Turboprop Generation 2



Figure A2.10.9.3

## 2.10.10 Global Rank Priority for Clustering of Factors for Turboprop Generation 2 (All Accidents)



2.10.10.1 Priority Table

Figure A2.10.10.1



## 2.10.11 High Training Impact

## 2.10.11.1 Factors with a High Training Impact (Turboprop Generation 2)



Figure A2.10.11.1

## 2.10.12 Priority Ranking for Factors Turboprop Generation 2

## 2.10.12.1 Priority Table

Level	Factor	Rank	Tr
А	CRM	8	Α
	Mis A/C State	7	Α
	Mis-Sys	7	В
	Compliance	7	С
в	Syst mal	6	Α
	Workload Distraction Pressure	6	С
	Eng Fail	5	Α
	Adverse Weather/Ice	3	С
с	Traffic	3	С
	Upset	2	С
	Poor Visibility	1	Α
	Ops/Type Spec	1	В

Figure A2.10.12.1

## 2.11 TURBOPROPS GENERATION 3 ANALYSIS

#### 2.11.1 Global Accidents (Last 15 Years)

#### 2.11.1.1 Ranking of Factors for All Accidents (Turboprop Generation 3)

Ranking of factors based on how present they are in accidents (as a percentage of all Prop Generation 3 accidents – last 15 years in blue, earlier times in black)





## 2.11.2 Global Fatal Accidents (Last 15 Years)

#### 2.11.2.1 Ranking of Factors for Fatal Accidents (Turboprop Generation 3)

Ranking of factors as a percentage of fatal accidents, L15Y vs. older



Figure A2.11.2.1

#### 2.11.3 Distribution by Flight Phases

#### 2.11.3.1 Distributions by Flight Phase (Last 15 Years) (Turboprop Generation 3)

Number of accidents per Flight Phase



Figure A2.11.3.1

## 2.11.3.2 Distributions by Flight Phase (Older) (Turboprop Generation 3)

Number of accidents per Flight Phase



Figure A2.11.3.2



## 2.11.3.3 Distribution of Specific Factors by Flight Phase (Last 15 Years) (Turboprop Generation 3)

Distribution of factors in accidents by Flight Phase



## 2.11.3.4 Distribution of Specific Factors by Flight Phase (Previous Time Period) (Turboprop Generation 3)

Distribution of factors in accidents by Flight Phase





#### 2.11.3.5 Distribution of Specific Factors by Flight Phase (Last 15 Years, Fatal Accidents Only) (Turboprop Generation 3)

Distribution of factors in accidents by Flight Phase



## 2.11.3.6 Distribution of Specific Factors by Flight Phase (Previous Period, Fatal Accidents Only) (Turboprop Generation 3)

Distribution of factors in accidents by Flight Phase





#### 2.11.3.7 Proportional Distributions of Specific Factors by Flight Phase (Last 15 Years) (Turboprop Generation 3)

Proportional distribution of factors by Flight Phase



#### 2.11.3.8 Proportional Distributions of Specific Factors by Flight Phase (Last 15 Years) (Turboprop Generation 3)

Proportional distribution of factors by Flight Phase (Fatal Accidents only)





## 2.11.4 Trainability

## 2.11.4.1 Training Effect (Turboprop Generation 3)

Training Effect by Flight Phase, all accidents, L15 Years



Figure A2.11.4.1

## 2.11.5 Competencies in All Accidents

### 2.11.5.1 Comparison of Distributions of Deficient Competencies During Accidents in Current to Previous Period (Turboprop Generation 3)

Deficient competencies in accidents





#### 2.11.6 Competencies in Fatal Accidents

#### 2.11.6.1 Comparison of Distributions of Deficient Competencies during Fatal Accidents Current to Previous Period (Turboprop Generation 3)



Deficient competencies in fatal accidents

Figure A2.11.6.1

## 2.11.7 Competencies in Incidents

#### 2.11.7.1 Comparison of Distributions of Deficient Competencies during Incidents in Current to Previous Period (Turboprop Generation 3)





Figure A2.11.7.1

## 2.11.8 Competency Footprint

# 2.11.8.1 Distributions of Deficient Competencies in Incidents and Fatal Accidents (Turboprop Generation 3)



Deficient competencies in Incidents vs. Fatal Accidents





#### 2.11.9 Relative Risk Rank

## 2.11.9.1 Relative Risk Rank Table for Turboprop Generation 3

	Frequency							Freq*Sev			
	% of even	ts (all times)		Frequer	ncy cont	ribution (% * 5)	Separate	ely at 3 Se	v levels		
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	Total risk	
CRM	60%	26%	20%	3.00	1.28	1.00	15.00	3.85	1.00	19.85	
Adverse Weather/Ice	50%	39%	9%	2.50	1.96	0.44	12.50	5.88	0.44	18.82	
Syst mal	40%	22%	69%	2.00	1.08	3.44	10.00	3.24	3.44	16.69	
Eng Fail	30%	12%	24%	1.50	0.61	1.22	7.50	1.82	1.22	10.55	
Poor Visibility	30%	14%	7%	1.50	0.68	0.33	7.50	2.03	0.33	9.86	
Compliance	30%	11%	11%	1.50	0.54	0.56	7.50	1.62	0.56	9.68	
Mis A/C State	30%	8%	4%	1.50	0.41	0.22	7.50	1.22	0.22	8.94	
Upset	30%	4%	4%	1.50	0.20	0.22	7.50	0.61	0.22	8.33	
Fatique	20%	4%	0%	1.00	0.20	0.00	5.00	0.61	0.00	5.61	
Workload Distraction Pressure	20%	3%	2%	1.00	0.14	0.11	5.00	0.41	0.11	5.52	
Mis-AFS	20%	3%	0%	1.00	0.14	0.00	5.00	0.41	0.00	5.41	
Ground equipment	10%	16%	9%	0.50	0.81	0.44	2.50	2.43	0.44	5.38	
Ground manoeuvring	10%	14%	9%	0.50	0.68	0.44	2.50	2.03	0.44	4.97	
Ops/Type Spec	10%	1%	7%	0.50	0.07	0.33	2.50	0.20	0.33	3.04	
Def Manuals	10%	3%	2%	0.50	0.14	0.11	2.50	0.41	0.11	3.02	
Mis-Sys	10%	1%	4%	0.50	0.07	0.22	2.50	0.20	0.22	2.92	
Def-Ops data	10%	3%	0%	0.50	0.14	0.00	2.50	0.41	0.00	2.91	
MEL	10%	1%	2%	0.50	0.07	0.11	2.50	0.20	0.11	2.81	
Physio	10%	1%	0%	0.50	0.07	0.00	2.50	0.20	0.00	2.70	
Birds	0%	9%	0%	0.00	0.47	0.00	0.00	1.42	0.00	1.42	
Fire	0%	4%	11%	0.00	0.20	0.56	0.00	0.61	0.56	1.16	
Runway/Taxi condition	0%	4%	2%	0.00	0.20	0.11	0.00	0.61	0.11	0.72	
Traffic	0%	4%	2%	0.00	0.20	0.11	0.00	0.61	0.11	0.72	
Def-Proc's	0%	1%	4%	0.00	0.07	0.22	0.00	0.20	0.22	0.42	

## Relative Risk Rank Table (Continued)

	Frequency							Freq*Sev		
	% of even	ts (all times)		Frequen	icy cont	ribution (% * 5)	Separate	ely at 3 Se	v levels	Total rick
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	Total HSK
Crosswind	0%	3%	0%	0.00	0.14	0.00	0.00	0.41	0.00	0.41
ATC	0%	0%	7%	0.00	0.00	0.33	0.00	0.00	0.33	0.33
Cabin	0%	1%	2%	0.00	0.07	0.11	0.00	0.20	0.11	0.31
Def-Chk lists	0%	1%	2%	0.00	0.07	0.11	0.00	0.20	0.11	0.31
R/W Incursion	0%	0%	4%	0.00	0.00	0.22	0.00	0.00	0.22	0.22
Terrain	0%	1%	0%	0.00	0.07	0.00	0.00	0.20	0.00	0.20
Wake Vortex	0%	1%	0%	0.00	0.07	0.00	0.00	0.20	0.00	0.20
Windshear	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
D.G	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Def-DBs	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Def-Charts	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LF.P	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
NAV	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Pilot Incap	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Loss of comms	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Communication	0%	3%	4%	0.00	0.14	0.22	0.00	0.41	0.22	0.63
SA	30%	14%	18%	1.50	0.68	0.89	7.50	2.03	0.89	10.42
Leadership and Teamwork	20%	8%	7%	1.00	0.41	0.33	5.00	1.22	0.33	6.55
Workload Management	0%	3%	4%	0.00	0.14	0.22	0.00	0.41	0.22	0.63
Problem Solving Decision Making	40%	12%	4%	2.00	0.61	0.22	10.00	1.82	0.22	12.05
Knowledge	30%	5%	11%	1.50	0.27	0.56	7.50	0.81	0.56	8.87
Application of Procedures & Knowledge	50%	15%	7%	2.50	0.74	0.33	12.50	2.23	0.33	15.06
Flight Management, Guidance and Automation	10%	1%	2%	0.50	0.07	0.11	2.50	0.20	0.11	2.81
Manual Aircraft Control	50%	16%	4%	2.50	0.81	0.22	12.50	2.43	0.22	15.15

Figure A2.11.9.1 (cont)



## 2.11.9.2 Relative Risk Rank Priority

Relative Risk Ranking Priority for Turboprop Generation 3

Factor	Priority
CRM	19.85
Adverse Weather/Ice	18.82
Syst mal	16.69
Eng Fail	10.55
Poor Visibility	9.86
Compliance	9.68
Mis A/C State	8.94
Upset	8.33
Fatique	5.61
Workload Distraction Pressure	5.52
Mis-AFS	5.41
Ground equipment	5.38
Ground manoeuvring	4.97
Ops/Type Spec	3.04
Def Manuals	3.02
Mis-Sys	2.92
Def-Ops data	2.91
MEL	2.81
Physio	2.70
Birds	1.42
Fire	1.16
Runway/Taxi condition	0.72
Traffic	0.72
Def-Proc's	0.42
Crosswind	0.41
ATC	0.33
Cabin	0.31
Def-Chk lists	0.31
R/W Incursion	0.22
Terrain	0.20
Wake Vortex	0.20
Windshear	0.00
D.G	0.00
Def-DBs	0.00
Def-Charts	0.00
LF.P	0.00
NAV	0.00
Pilot Incap	0.00
Loss of comms	0.00

Figure A2.11.9.2

## 2.11.9.3 Relative Risk Rank Chart

Relative Risk Ranking for Turboprop Generation 3




# 2.11.10 Clustering



# 2.11.10.1 Global Ranking for Clustering of Factors for Turboprop Generation 3 (All Accidents)

Figure A2.11.10.1

#### 2.11.11 High Training Impact

# 2.11.11.1 Comparison of Factor Occurrence in Accidents with High Training Effect



Figure A2.11.11.1





# 2.11.12 Global Priority Ranking for Factors Turboprop Generation 3

# 2.11.12.1 Priority Table

Priority table of factors for Turboprop Generation 3

Level	Factor	Rank	Tr
A	СКМ	8	Α
	Mis A/C State	7	Α
	Compliance	7	С
	Poor Visibility	6	Α
	Adverse Weather/Ice	5	С
	Upset	5	С
В	MEL	4	В
	Mis-AFS	4	В
	Mis-Sys	4	В
	Workload Distraction Pressure	4	С
	Syst mal	3	Α
	Eng Fail	2	Α
	Ops/Type Spec	2	В
	Runway/Taxi condition	1	С

Figure A2.11.12.1

# 2.12 JET GENERATION 2 ANALYSIS

#### 2.12.1 Global Accidents (Last 15 Years)

#### 2.12.1.1 Ranking of Factors for All Accidents (Generation 2)

Ranking of factors based on how present they are in accidents (as a percentage of all Gen4 accidents – last 15 years in blue, earlier times in black)



Figure A2.12.1.1



#### 2.12.1.2 Ranking of Factors for All Accidents per One Million Takeoffs (Generation 2)

Comparison of the ranking of factors (normalized by the number of takeoffs) for all accidents in current versus previous time period



Figure A2.12.1.2

# 2.12.2 Global Fatal Accidents (Last 15 Years)

#### 2.12.2.1 Ranking of Factors for Fatal Accidents

Ranking of factors as a percentage of fatal accidents, L15Y vs. older



Figure A2.12.2.1



#### 2.12.2.2 Ranking of Factors for Fatal Accidents per One Million Takeoffs (Generation 2)

Comparison of the ranking of factors (normalized by the number of takeoffs) for fatal accidents in the current versus previous time period



Figure A2.12.2.2

# 2.12.3 Distribution by Flight Phases (Generation 2)

# 2.12.3.1 Distributions of accidents by Flight Phase

Number of accidents per Flight Phase (Last 15 Years)



Figure A2.12.3.1

Number of accidents per Flight Phase (Older)



Figure A2.12.3.1a



#### 2.12.3.2 Distribution of Specific Factors by Flight Phase (Last 15 Years)

Distribution of factors in all accidents by Flight Phase (Generation 2)



# 2.12.3.3 Distribution of Specific Factors by Flight Phase (Older)

Distribution of factors in all accidents by Flight Phase (Generation 2)





#### 2.12.3.4 Distribution of Specific Factors by Flight Phase (Last 15 Years, Fatal Accidents Only)

Distribution of factors in accidents by Flight Phase (Generation 2)



#### 2.12.3.5 Distribution of Specific Factors by Flight Phase (Older, Fatal Accidents Only)

Distribution of factors in accidents by Flight Phase (Generation 2)





### 2.12.3.6 Proportional Distributions of Specific Factors by Flight Phase

Distribution of factors in all accidents by Flight Phase (Generation 2)



# 2.12.3.7 Proportional Distributions of Specific Factors by Flight Phase

Distribution of factors by Flight Phase (Fatal Accidents only) (Generation 2)



Factors as % of Fatal accidents in each Flight Phase (Last 15Y)

۰



# 2.12.4 Trainability

# 2.12.4.1 Training Effect

Training Effect by Flight Phase, all accidents, L15 Years (Generation 2)



# 2.12.5 Competencies in Accidents

# 2.12.5.1 Distributions of Deficient Competencies in Accidents

Deficient competencies in accidents (Generation 2)







#### 2.12.5.2 Distributions of Deficient Competencies in Accidents per One Million Takeoffs (Generation 2)

#### 2.12.6 Competencies in Fatal Accidents

#### 2.12.6.1 Distributions of Deficient Competencies in Fatal Accidents

Deficient competencies in fatal accidents (Generation 2)





#### 2.12.6.2 Distributions of Deficient Competencies in Fatal Accidents per One Million Takeoffs (Generation 2)



#### 2.12.7 Competencies in Incidents

#### 2.12.7.1 Distributions of Deficient Competencies in Incidents

Comparison of deficient competencies in incidents during current versus previous time period (Generation 2)





#### 2.12.8 Competency Footprint

# 2.12.8.1 Distributions of Deficient Competencies in Incidents and Fatal Accidents

Deficient competencies in Incidents vs. Fatal Accidents (Generation 2)



#### 2.12.9 Relative Risk Rank

# 2.12.9.1 Relative Risk Rank Table (Generation 2)

	Frequency						F	req*Sev			
	% of events in th	ie last 15	γ	Fre contribi	equenc ution (¢	sy % * 5)	Separate	ly at 3 Se	v levels	Total risk	
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	10141-1151	
Syst mal	53%	44%	64%	2.64	2.21	3.18	13.21	6.62	3.18	23.01	
Adverse Weather/Ice	60%	35%	20%	3.00	1.76	1.01	15.00	5.28	1.01	21.29	
Poor Visibility	59%	25%	12%	2.93	1.23	0.62	14.64	3.69	0.62	18.95	
Eng Fail	49%	27%	42%	2.43	1.37	2.09	12.14	4.11	2.09	18.34	
Fire	50%	27%	31%	2.50	1.37	1.55	12.50	4.11	1.55	18.16	
Mis A/C State	33%	28%	16%	1.64	1.40	0.78	8.21	4.19	0.78	13.18	
CRM	27%	26%	16%	1.36	1.28	0.81	6.79	3.85	0.81	11.45	
Crosswind	34%	14%	1%	1.71	0.70	0.04	8.57	2.09	0.04	10.71	
Terrain	23%	11%	1%	1.14	0.53	0.04	5.71	1.59	0.04	7.35	
Windshear	20%	9%	0%	1.00	0.45	0.00	5.00	1.34	0.00	6.34	
Ground manoeuvring	13%	15%	11%	0.64	0.73	0.54	3.21	2.18	0.54	5.94	
Compliance	7%	13%	5%	0.36	0.64	0.27	1.79	1.93	0.27	3.98	
Ground equipment	7%	11%	5%	0.36	0.53	0.27	1.79	1.59	0.27	3.65	
Runway/Taxi condition	6%	7%	4%	0.29	0.36	0.19	1.43	1.09	0.19	2.71	
ATC	4%	3%	2%	0.21	0.17	0.12	1.07	0.50	0.12	1.69	
Mis-Sys	4%	3%	3%	0.21	0.14	0.16	1.07	0.42	0.16	1.65	
Workload Distraction Pressure	4%	3%	0%	0.21	0.14	0.00	1.07	0.42	0.00	1.49	
Def Manuals	4%	2%	1%	0.21	0.11	0.04	1.07	0.34	0.04	1.45	
Fatique	4%	2%	0%	0.21	0.11	0.00	1.07	0.34	0.00	1.41	
Upset	3%	2%	2%	0.14	0.08	0.08	0.71	0.25	0.08	1.04	
Birds	1%	2%	1%	0.07	0.11	0.04	0.36	0.34	0.04	0.73	
Traffic	1%	2%	2%	0.07	0.08	0.08	0.36	0.25	0.08	0.69	

# Relative Risk Rank Table (Continued)

			F							
	% of events in th	ne last 15	δY	Fre contrib	equenc ution ( <sup>1</sup>	cy % * 5)	Separately at 3 Sev levels			Total risk
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	
Def-Ops data	1%	2%	1%	0.07	0.08	0.04	0.36	0.25	0.04	0.65
Cabin	0%	4%	1%	0.00	0.20	0.04	0.00	0.59	0.04	0.63
Ops/Type Spec	1%	1%	2%	0.07	0.06	0.08	0.36	0.17	0.08	0.60
LF.P	1%	1%	1%	0.07	0.06	0.04	0.36	0.17	0.04	0.56
MEL	1%	1%	0%	0.07	0.06	0.00	0.36	0.17	0.00	0.52
D.G	1%	1%	0%	0.07	0.06	0.00	0.36	0.17	0.00	0.52
Def-Proc's	0%	1%	0%	0.00	0.06	0.00	0.00	0.17	0.00	0.17
Mis-AFS	0%	1%	0%	0.00	0.06	0.00	0.00	0.17	0.00	0.17
Wake Vortex	0%	1%	0%	0.00	0.03	0.00	0.00	0.08	0.00	0.08
Def-Chk lists	0%	0%	1%	0.00	0.00	0.04	0.00	0.00	0.04	0.04
Pilot Incap	0%	0%	1%	0.00	0.00	0.04	0.00	0.00	0.04	0.04
Loss of comms	0%	0%	1%	0.00	0.00	0.04	0.00	0.00	0.04	0.04
R/W Incursion	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Physio	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Def-DBs	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Def-Charts	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
NAV	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Communication	6%	3%	2%	0.29	0.17	0.08	1.43	0.50	0.08	2.01
SA	21%	14%	9%	1.07	0.70	0.43	5.36	2.09	0.43	7.88
Leadership and Teamwork	4%	4%	3%	0.21	0.22	0.16	1.07	0.67	0.16	1.90
Workload Management	3%	1%	1%	0.14	0.06	0.04	0.71	0.17	0.04	0.92
Problem Solving Decision Making	3%	9%	6%	0.14	0.47	0.31	0.71	1.42	0.31	2.45
Knowledge	0%	2%	1%	0.00	0.08	0.04	0.00	0.25	0.04	0.29
Application of Procedures & Knowledge	11%	13%	9%	0.57	0.64	0.47	2.86	1.93	0.47	5.25
Flight Management, Guidance and Automation	3%	2%	1%	0.14	0.11	0.04	0.71	0.34	0.04	1.09
Manual Aircraft Control	61%	37%	27%	3.07	1.87	1.36	15.36	5.61	1.36	22.33

# 2.12.9.2 Relative Risk Rank Priority

Relative Risk Ranking Priority for Jet Generation 2

Factor	Priority
Syst mal	23.01
Adverse Weather/Ice	21.29
Poor Visibility	18.95
Eng Fail	18.34
Fire	18.16
Mis A/C State	13.18
CRM	11.45
Crosswind	10.71
Terrain	7.35
Windshear	6.34
Ground manoeuvring	5.94
Compliance	3.98
Ground equipment	3.65
Runway/Taxi condition	2.71
ATC	1.69
Mis-Sys	1.65
Workload Distraction Pressure	1.49
Def Manuals	1.45

# **Relative Risk Rank Priority (Continued)**

Relative Risk Ranking Priority for Jet Generation 2

Factor	Priority
Fatique	1.41
Upset	1.04
Birds	0.73
Traffic	0.69
Def-Ops data	0.65
Cabin	0.63
Ops/Type Spec	0.60
LF.P	0.56
MEL	0.52
D.G	0.52
Def-Proc's	0.17
Mis-AFS	0.17
Wake Vortex	0.08
Def-Chk lists	0.04
Pilot Incap	0.04
Loss of comms	0.04
R/W Incursion	0.00
Physio	0.00
Def-DBs	0.00
Def-Charts	0.00
NAV	0.00

# 2.12.9.3 Relative Risk Rank Chart

Relative Risk Ranking for Jet Generation 2





# 2.12.10 Takeoff Data

# 2.12.10.1 Takeoff Data Table

GLOBAL VALUES		1950	1960	1970	1980	1990	2000	2010	Before last 15Y	Last 15Y	Total/Gen
	Gen1	49279	3654782	6978479	2248452	567284	113441	1213	13361467	251463	13612930
	Gen2	0	7685689	55683176	81876860	57656778	20350718	571250	182355441	41469030	223824471
	Gen3	0	0	0	11881889	70034723	127321496	13391504	47286029	175343583	222629612
	Gen4	0	0	0	73214	9455296	50784434	9443295	3266023	66490216	69756239
				9528510			60227	729			
	ALL GEN	49279	11340471	62661655	96080415	137714081	198570089	23407262	246268960	283554292	

Grand total 529823252

# 2.12.11 Clustering



# 2.12.11.1 Clustering of Factors Graph (Generation 2)



#### 2.12.12 HIGH TRAINING EFFECT





# 2.12.13 Global Priority Ranking for Factors Jet Generation 2

# 2.12.13.1 Priority Table

Priority table of factors for Jet Generation 2

Level	Factors	Rank	Tr
A	CRM	7	Α
	Poor Visibility	7	Α
	Mis A/C State	6	Α
	Syst mal	6	Α
	Adverse Weather/Ice	6	С
в	Fire	5	Α
	Eng Fail	5	Α
	Windshear	5	В
	Crosswind	4	Α
	Compliance	4	С
	Runway/Taxi condition	2	С
C	Terrain	2	С



# 2.13 GENERATION 3 ANALYSIS

#### 2.13.1 Global Accidents (Last 15 Years)

#### 2.13.1.1 Ranking of Factors for All Accidents

Ranking of factors based on how present they are in accidents in Generation 3 (as a percentage of all Gen4 accidents – last 15 years in blue, earlier times in black)



# 2.13.1.2 Ranking of Factors for All Accidents per One Million Takeoffs (Generation 3)

Ranking of factors normalized by the number of takeoffs for all accidents





# 2.13.2 Global Fatal Accidents (Last 15 Years)

#### 2.13.2.1 Ranking of Factors for Fatal Accidents

Comparison of the ranking of factors as a percentage of fatal accidents, L15Y vs. older (Generation 3)



# 2.13.2.2 Ranking of Factors for All Fatal Accidents per One Million Takeoffs (Generation 3)

Comparison of factor rankings, normalized by the number of takeoffs. Fatal accidents. (Generation 3)





# 2.13.3 Distribution by Flight Phases

# 2.13.3.1 Distributions of accidents by Flight Phase

Number of accidents per Flight Phase during the last 15 Years (Generation 3)



Number of accidents per Flight Phase during previous time period (Generation 3)



#### 2.13.3.2 Distribution of Specific Factors by Flight Phase (Last 15 Years)

Distribution of factors in all accidents by Flight Phase (Generation 3)




## 2.13.3.3 Distribution of Specific Factors by Flight Phase (Older)

Distribution of factors in all accidents by Flight Phase (Generation 3)



#### 2.13.3.4 Distribution of Specific Factors by Flight Phase (Last 15 Years, Fatal Accidents Only)

Distribution of factors in accidents by Flight Phase (Generation 3)





## 2.13.3.5 Distribution of Specific Factors by Flight Phase (Older, Fatal Accidents Only)

Distribution of factors in accidents by Flight Phase (Generation 3)



## 2.13.3.6 Proportional Distributions of Specific Factors by Flight Phase

Distribution of factors by Flight Phase for all accidents (Generation 3)





## 2.13.3.7 Proportional Distributions of Specific Factors by Flight Phase

Distribution of factors by Flight Phase for Fatal Accidents only (Generation 3)



# 2.13.4 Trainability

# 2.13.4.1 Training Effect

Training Effect by Flight Phase, all accidents, L15 Years (Generation 3)





## 2.13.5 Competencies in Accidents

#### 2.13.5.1 Distributions of Deficient Competencies in Accidents

Comparison of competency issues in accidents during current versus previous time period (Generation 3)





#### 2.13.5.2 Comparison Distributions of Competency Issues in Accidents per One Million Takeoffs during Current versus Previous Time Period (Generation 3)



## 2.13.6 Competencies in Fatal Accidents

#### 2.13.6.1 Distributions of Deficient Competencies in Fatal Accidents

Comparison of competency issues in fatal accidents during current versus previous time period (Generation 3)





#### 2.13.6.2 Comparison of Distributions of Competency Issues in Fatal Accidents per One Million Takeoffs during Current versus Previous Time Period (Generation 3)



## 2.13.7 Competencies in Incidents

# 2.13.7.1 Distributions of Competency Issues in Incidents

Comparison of deficient competencies in incidents during current versus previous time period (Generation 3)



## 2.13.8 Competency Footprint

# 2.13.8.1 Distributions of Competency Issues in Incidents and Fatal Accidents

Comparison of deficient competencies in Incidents vs. Fatal Accidents (Generation 3)





## 2.13.9 Relative Risk Rank

# 2.13.9.1 Relative Risk Rank Table (Generation 3)

	Frequency							Freq*Sev			
	% of events	in the last 15	ōΥ	Freque	ncy cc	ontribution (% * 5)	Separately at 3 Sev levels				
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	Total risk	
Mis A/C State	56%	32%	17%	2.79	1.62	0.83	13.97	4.87	0.83	19.67	
CRM	47%	30%	12%	2.35	1.52	0.59	11.76	4.57	0.59	16.93	
Syst mal	29%	19%	55%	1.47	0.93	2.75	7.35	2.80	2.75	12.90	
Adverse Weather/Ice	21%	41%	8%	1.03	2.05	0.41	5.15	6.15	0.41	11.70	
Compliance	21%	14%	7%	1.03	0.72	0.36	5.15	2.16	0.36	7.67	
Poor Visibility	18%	9%	3%	0.88	0.46	0.15	4.41	1.38	0.15	5.94	
Fire	12%	5%	18%	0.59	0.26	0.88	2.94	0.79	0.88	4.61	
Mis-Sys	15%	4%	1%	0.74	0.20	0.05	3.68	0.59	0.05	4.32	
Ground manoeuvring	3%	18%	14%	0.15	0.90	0.69	0.74	2.70	0.69	4.14	
Terrain	15%	2%	0%	0.74	0.10	0.02	3.68	0.30	0.02	3.99	
Crosswind	12%	5%	2%	0.59	0.25	0.08	2.94	0.74	0.08	3.76	
ATC	9%	5%	11%	0.44	0.26	0.54	2.21	0.79	0.54	3.54	
Workload Distraction Pressure	12%	3%	1%	0.59	0.16	0.07	2.94	0.49	0.07	3.50	
Ground equipment	6%	10%	4%	0.29	0.49	0.22	1.47	1.48	0.22	3.17	
Def-Proc's	9%	4%	2%	0.44	0.18	0.08	2.21	0.54	0.08	2.83	
Upset	9%	2%	2%	0.44	0.08	0.08	2.21	0.25	0.08	2.54	

# Relative Risk Rank Table (Continued)

		Fr	equency		_		Freq*Sev					
	% of events	ïΥ	Freque	ncy cc ;	ntribution (% * 5)	Se	v levels					
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	Total risk		
Eng Fail	3%	3%	13%	0.15	0.15	0.64	0.74	0.44	0.64	1.82		
Cabin	3%	4%	3%	0.15	0.20	0.14	0.74	0.59	0.14	1.46		
Windshear	6%	2%	1%	0.29	0.08	0.03	1.47	0.25	0.03	1.75		
Runway/Taxi condition	3%	5%	3%	0.15	0.26	0.17	0.74	0.79	0.17	1.69		
Traffic	3%	3%	5%	0.15	0.15	0.25	0.74	0.44	0.25	1.43		
Ops/Type Spec	3%	3%	4%	0.15	0.15	0.19	0.74	0.44	0.19	1.36		
MEL	3%	2%	2%	0.15	0.10	0.08	0.74	0.30	0.08	1.12		
Wake Vortex	3%	1%	1%	0.15	0.05	0.07	0.74	0.15	0.07	0.95		
D.G	3%	0%	0%	0.15	0.02	0.00	0.74	0.05	0.00	0.78		
Def-DBs	3%	0%	0%	0.15	0.02	0.00	0.74	0.05	0.00	0.78		
Def-Charts	3%	0%	0%	0.15	0.02	0.00	0.74	0.05	0.00	0.78		
Def-Ops data	0%	3%	2%	0.00	0.13	0.08	0.00	0.39	0.08	0.48		
Mis-AFS	0%	3%	1%	0.00	0.15	0.03	0.00	0.44	0.03	0.48		
Def Manuals	0%	2%	1%	0.00	0.11	0.07	0.00	0.34	0.07	0.41		



# Relative Risk Rank Table (Continued)

	Frequency									
	% of events	in the last 15	jγ	Frequer	ncy co	ntribution (% * 5)	Separately at 3 Sev levels			<b>-</b>
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	Total risk
R/W Incursion	0%	0%	6%	0.00	0.02	0.32	0.00	0.05	0.32	0.37
Birds	0%	1%	2%	0.00	0.05	0.08	0.00	0.15	0.08	0.23
LF.P	0%	1%	1%	0.00	0.03	0.03	0.00	0.10	0.03	0.13
Def-Chk lists	0%	1%	0%	0.00	0.03	0.02	0.00	0.10	0.02	0.12
Fatique	0%	0%	0%	0.00	0.02	0.02	0.00	0.05	0.02	0.07
Physio	0%	0%	0%	0.00	0.02	0.02	0.00	0.05	0.02	0.07
NAV	0%	0%	0%	0.00	0.02	0.02	0.00	0.05	0.02	0.07
Pilot Incap	0%	0%	1%	0.00	0.00	0.03	0.00	0.00	0.03	0.03
Loss of comms	0%	0%	1%	0.00	0.00	0.03	0.00	0.00	0.03	0.03
Communication	0%	4%	2%	0.00	0.21	0.08	0.00	0.64	0.08	0.72
SA	29%	18%	9%	1.47	0.92	0.46	7.35	2.75	0.46	10.56
Leadership and Teamwork	15%	5%	0%	0.74	0.23	0.02	3.68	0.69	0.02	4.38
Workload Management	3%	1%	1%	0.15	0.05	0.03	0.74	0.15	0.03	0.92
Problem Solving Decision Making	18%	12%	5%	0.88	0.62	0.25	4.41	1.87	0.25	6.53
Knowledge	9%	4%	1%	0.44	0.21	0.05	2.21	0.64	0.05	2.90
Application of Procedures &	21%	16%	7%	1.03	0.82	0.34	5.15	2.46	0.34	7.95
and Automation	9%	4%	0%	0.44	0.20	0.02	2.21	0.59	0.02	2.81
Manual Aircraft Control	53%	32%	14%	2.65	1.59	0.69	13.24	4.77	0.69	18.70

# 2.13.9.2 Relative Risk Rank Priority

Relative Risk Ranking Priority for Jet Generation 3

Factor	Priority
Mis A/C State	19.67
CRM	16.93
Syst mal	12.90
Adverse Weather/Ice	11.70
Compliance	7.67
Poor Visibility	5.94
Fire	4.61
Mis-Sys	4.32
Ground manoeuvring	4.14
Terrain	3.99
Crosswind	3.76
ATC	3.54
Workload Distraction Pressure	3.50
Ground equipment	3.17
Def-Proc's	2.83
Upset	2.54
Eng Fail	1.82
Cabin	1.46
Windshear	1.75
Runway/Taxi condition	1.69
Traffic	1.43
Ops/Type Spec	1.36
MEL	1.12
Wake Vortex	0.95
D.G	0.78
Def-DBs	0.78
Def-Charts	0.78
Def-Ops data	0.48
Mis-AFS	0.48
Def Manuals	0.41
R/W Incursion	0.37
Birds	0.23
L.F.P	0.13
Def-Chk lists	0.12
Fatique	0.07
Physio	0.07
NAV	0.07
Pilot Incap	0.03
Loss of comms	0.03



# 2.13.9.3 Relative Risk Rank Chart

Relative Risk Ranking for Jet Generation 3





# 2.13.10 Takeoff Data

## 2.13.10.1 Takeoff Data Table

GLOBAL VALUES		1950	1960	1970	1980	1990	2000	2010	Before last 15Y	Last 15Y	Total/Gen
	Gen1	49279	3654782	6978479	2248452	567284	113441	1213	13361467	251463	13612930
_											
	Gen2	0	7685689	55683176	81876860	57656778	20350718	571250	182355441	41469030	223824471
-				•					•		
Γ	Gen3	0	0	0	11881889	70034723	127321496	13391504	47286029	175343583	222629612
-				•			•		•		
	Gen4	0	0	0	73214	9455296	50784434	9443295	3266023	66490216	69756239
_				9528510			60227	7729			
	ALL GEN	49279	11340471	62661655	96080415	137714081	198570089	23407262	246268960	283554292	

Grand total 529823252



# 2.13.11 Clustering of Factors



# 2.13.11.1 Clustering of Factors Graph (Generation 3)

## 2.13.12 High Training Impact







# 2.13.13 Global Priority Ranking for Factors Jet Generation 3

# 2.13.13.1 Priority Table

Priority table of factors for Jet Generation 3

Level	Factors	Rank	Tr
	CRM	7	Α
A	Mis A/C State	7	Α
	Compliance	7	С
	Poor Visibility	6	Α
	Crosswind	5	Α
	Mis-Sys	5	В
В	Adverse Weather/Ice	5	С
	Workload Distraction Pressure	5	С
	Syst mal	4	Α
	Windshear	4	В
	Runway/Taxi condition	3	С
	ATC	3	С
	Fire	2	Α
	Terrain	2	С
	Upset	2	С
	Eng Fail	1	Α

# 2.14 GENERATION 4 ANALYSIS

## 2.14.1 Global Accidents (Last 11 Years)

## 2.14.1.1 Ranking of Factors for All Accidents (Generation 4)

Ranking of factors based on how present they are in accidents (as a percentage of all Gen4 accidents – last 11 years in blue, earlier times in black)



## 2.14.1.2 Ranking of Factors for All Accidents Per One Million Takeoffs (Generation 4)

Comparison of ranking of factors normalized by the number of takeoffs for all accidents during current versus previous time period (Generation 3)





# 2.14.2 Global Fatal Accidents (Last 11 Years)

## 2.14.2.1 Ranking of Factors for Fatal Accidents

Comparison of the ranking of factors as a percentage of fatal accidents, L11Y vs. older (Generation 4)



## 2.14.2.2 Ranking of Factors for All Fatal Accidents per One Million Takeoffs (Generation 4)

Comparison of the ranking of factors (normalized by the number of takeoffs) for fatal accidents only during current versus previous time period (Generation 4)



# 2.14.3 Distribution of Factors in Flight Phases

# 2.14.3.1 Distributions by Flight Phase

Number of accidents per Flight Phase (Generation 4)





## 2.14.3.2 Distribution of Specific Factors by Flight Phase (Last 11 Years)

Distribution of all accidents with a specific factor by Flight Phase (Generation 4)



## 2.14.3.3 Distribution of Specific Factors by Flight Phase (Older)

Distribution of accidents with a specific factor by Flight Phase during previous time period (Generation 4)





## 2.14.3.4 Distribution of Specific Factors by Flight Phase (Last 11 Years, Fatal Accidents Only)

Distribution of accidents with a specific factor by Flight Phase in current time period (Generation 4)



# 2.14.3.5 Distribution of Specific Factors by Flight Phase (Older, Fatal Accidents Only)

Distribution of accidents with a specific factor by Flight Phase





## 2.14.3.6 Proportional Distributions of Specific Factors by Flight Phase

Proportional distribution of factors by Flight Phase (Generation 4)



# 2.14.4 Trainability

## 2.14.4.1 Training Effect

Training Effect by Flight Phase, all accidents, L11 Years (Generation 4)





## 2.14.5 Competencies in Accidents

### 2.14.5.1 Distributions of Deficient Competencies in Accidents

Comparison of deficient competencies in accidents during current versus previous time period (Generation 4)



#### 2.14.5.2 Comparison of the Distributions of Deficient Competencies in Accidents (Per One Million Takeoffs) During Current versus Previous Time Period (Generation 4)





## 2.14.6 Competencies in Fatal Accidents

#### 2.14.6.1 Distributions of Deficient Competencies in Fatal Accidents

Comparison of deficient competencies in fatal accidents during current versus previous time period (Generation 4)





#### 2.14.6.2 Comparison of the Distributions of Deficient Competencies in Fatal Accidents (Per One Million Takeoffs) during Current versus Previous Time Period (Generation 4)



## 2.14.7 Competencies in Incidents

# 2.14.7.1 Distributions of Deficient Competencies in Incidents

Deficient competencies in incidents (Generation 4)



# 2.14.8 Competency Footprint

# 2.14.8.1 Distributions of Deficient Competencies in Incidents and Fatal Accidents

Deficient competencies in Incidents vs. Fatal Accidents (Generation 4)




#### 2.14.9 Relative Risk Rank

# 2.14.9.1 Relative Risk Rank Table (Generation 4)

		Freq	uency				Fi	req*Sev		
	% of events in th	ne last 1	1Y	F contri	requen	cy (% * 5)	Separatel	y at 3 Sev	/ levels	Total risk
	% of recent fatal acc	% of recent acc	% of recent inc	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	
Adverse Weather/Ice	44%	46%	11%	2.22	2.30	0.53	11.11	6.90	0.53	18.53
CRM	44%	30%	24%	2.22	1.49	1.18	11.11	4.48	1.18	16.78
Compliance	44%	23%	11%	2.22	1.15	0.53	11.11	3.45	0.53	15.09
Mis A/C State	44%	22%	13%	2.22	1.09	0.66	11.11	3.28	0.66	15.04
Ground manoeuvring	0%	21%	12%	0.00	1.03	0.59	0.00	3.10	0.59	3.70
Syst mal	0%	16%	42%	0.00	0.80	2.11	0.00	2.41	2.11	4.52
Cabin	0%	7%	1%	0.00	0.34	0.07	0.00	1.03	0.07	1.10
Ground equipment	22%	10%	5%	1.11	0.52	0.26	5.56	1.55	0.26	7.37
Fire	11%	9%	9%	0.56	0.46	0.46	2.78	1.38	0.46	4.62
Mis-Sys	11%	8%	7%	0.56	0.40	0.33	2.78	1.21	0.33	4.31
Crosswind	11%	7%	3%	0.56	0.34	0.13	2.78	1.03	0.13	3.94
Runway/Taxi condition	22%	7%	7%	1.11	0.34	0.33	5.56	1.03	0.33	6.92
ATC	0%	7%	17%	0.00	0.34	0.86	0.00	1.03	0.86	1.89
Traffic	0%	7%	5%	0.00	0.34	0.26	0.00	1.03	0.26	1.30
Workload Distraction Pressure	11%	6%	9%	0.56	0.29	0.46	2.78	0.86	0.46	4.10
Ops/Type Spec	0%	6%	4%	0.00	0.29	0.20	0.00	0.86	0.20	1.06
Poor Visibility	11%	5%	3%	0.56	0.23	0.13	2.78	0.69	0.13	3.60
Eng Fail	0%	5%	28%	0.00	0.23	1.38	0.00	0.69	1.38	2.07

## Relative Risk Rank Table (Continued)

		Freq	uency				Fr	eq*Sev		
	% of events in th	ne last 1 <sup>.</sup>	1Y	Fi contril	requen bution (	cy (% * 5)	Separately	vat 3 Sev	levels	Total risk
	% of recent fatal acc	% of recent	% of recent	F acc	Acc	Inc	F Acc (5)	Acc (3)	Inc (1)	
Def-Proc's	0%	3%	3%	0.00	0.17	0.13	0.00	0.52	0.13	0.65
Def-Ops data	0%	2%	3%	0.00	0.11	0.13	0.00	0.34	0.13	0.48
Mis-AFS	0%	2%	0%	0.00	0.11	0.00	0.00	0.34	0.00	0.34
MEL	11%	2%	1%	0.56	0.11	0.07	2.78	0.34	0.07	3.19
Def-Chk lists	0%	2%	0%	0.00	0.11	0.00	0.00	0.34	0.00	0.34
Terrain	11%	1%	1%	0.56	0.06	0.07	2.78	0.17	0.07	3.02
Windshear	0%	1%	1%	0.00	0.06	0.07	0.00	0.17	0.07	0.24
Def Manuals	0%	1%	0%	0.00	0.06	0.00	0.00	0.17	0.00	0.17
Upset	0%	1%	1%	0.00	0.06	0.07	0.00	0.17	0.07	0.24
Birds	0%	1%	3%	0.00	0.06	0.13	0.00	0.17	0.13	0.30
Fatique	0%	1%	0%	0.00	0.06	0.00	0.00	0.17	0.00	0.17
R/W Incursion	0%	1%	9%	0.00	0.06	0.46	0.00	0.17	0.46	0.63
Physio	11%	1%	1%	0.56	0.06	0.07	2.78	0.17	0.07	3.02
LF.P	0%	0%	1%	0.00	0.00	0.07	0.00	0.00	0.07	0.07
Wake Vortex	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
D.G	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Def-DBs	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Def-Charts	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
NAV	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Pilot Incap	0%	0%	0%	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Loss of comms	0%	0%	4%	0.00	0.00	0.20	0.00	0.00	0.20	0.20
Communication	0%	6%	5%	0.00	0.29	0.26	0.00	0.86	0.26	1.13
SA	33%	22%	21%	1.67	1.09	1.05	8.33	3.28	1.05	12.66
Leadership and Teamwork	0%	8%	0%	0.00	0.40	0.00	0.00	1.21	0.00	1.21
Workload Management	0%	0%	1%	0.00	0.00	0.07	0.00	0.00	0.07	0.07
Problem Solving Decision Making	0%	9%	9%	0.00	0.46	0.46	0.00	1.38	0.46	1.84
Knowledge	0%	0%	3%	0.00	0.00	0.13	0.00	0.00	0.13	0.13
Application of Procedures & Knowledge	44%	21%	14%	2.22	1.03	0.72	11.11	3.10	0.72	14.94
Flight Management, Guidance and Automation	0%	1%	1%	0.00	0.06	0.07	0.00	0.17	0.07	0.24
Manual Aircraft Control	44%	22%	12%	2.22	1.09	0.59	11.11	3.28	0.59	14.98



# 2.14.9.2 Relative Risk Rank Priority

Relative Risk Ranking Priority for Jet Generation 4

Factor	Priority
Adverse Weather/Ice	18.53
CRM	16.78
Compliance	15.09
Mis A/C State	15.04
Ground equipment	7.37
Runway/Taxi condition	6.92
Fire	4.62
Syst mal	4.52
Mis-Sys	4.31
Workload Distraction Pressure	4.10
Crosswind	3.94
Ground manoeuvring	3.70
Poor Visibility	3.60
MEL	3.19
Physio	3.02
Terrain	3.02
Eng Fail	2.07
ATC	1.89
Traffic	1.30
Cabin	1.10
Ops/Type Spec	1.06
Def-Proc's	0.65
R/W Incursion	0.63
Def-Ops data	0.48
Def-Chk lists	0.34
Mis-AFS	0.34
Birds	0.30
Upset	0.24
Windshear	0.24
Loss of comms	0.20
Def Manuals	0.17
Fatique	0.17
LF.P	0.07
D.G	0.00
Def-Charts	0.00
Def-DBs	0.00
NAV	0.00
Pilot Incap	0.00
Wake Vortex	0.00

### 2.14.9.3 Relative Risk Rank Chart

Relative Risk Ranking for Jet Generation 4





#### 2.14.10 Takeoff Data

#### 2.14.10.1 Takeoff Data Table

7	GLOBAL VALUES		1950	1960	1970	1980	1990	2000	2010	Before last 11Y	Last 11Y	Total/Gen
		Gen1	0	0	0	0	0	0	0	0	0	0
		Gen2	0	7685689	55683176	81876860	57656778	20350718	571250	182355441	41469030	223824471
		Gen3	0	0	0	11881889	70034723	127321496	13391504	47286029	175343583	222629612
		Gen4	0	0	0	73214	9455296	50784434	9443295	3266023	66490216	69756239
					9528510			60227	729			
		ALL GEN	0	7685689	55683176	93831963	137146797	198456648	23406049	232907493	283302829	

Grand total 516210322

### 2.14.11 Clustering







#### 2.14.12 High Training Impact

#### 2.14.12.1 Comparison of Factors with a High Training Impact During Current Versus Previous Time Period (Generation 4)



#### 2.14.13 Global Priority Ranking for Factors Jet Generation 4

#### 2.14.13.1 Priority Table

Priority table of factors for Jet Generation 4

Level	Updated Gen4 ranking (acc study)	Rank	Tr
	CRM	8	Α
	Mis A/C State	8	Α
	Compliance	8	С
	Crosswind	6	Α
	Mis-Sys	6	В
	Runway/Taxi condition	6	С
	Adverse Weather/Ice	5	С
	Poor Visibility	4	Α
	MEL	4	В
	Workload Distraction Pressure	4	С
	Terrain	4	С
	Fire	2	Α
	Syst mal	2	Α
	ATC	2	С
	Eng Fail	1	Α



# APPENDIX 3 EVIDENCE-BASED TRAINING MATRIX

# INTRODUCTION

This appendix contains the EBT accident-incident matrix stage 1. These are the data that formed the basis for the factor analysis. In addition the exact guidance to the analysts is provided in section 3.2.

# 3.1 EVIDENCE-BASED TRAINING ACCIDENT-INCIDENT MATRIX

		Ac	cident	s			Lactors ay Taxi condition ay Taxi condition ay Taxi condition AT C Nucleshear AT C Nucleshear																			Fac	ctors	i (No	on-Te	echı	nical	)								Cor	npe	tenc	cies				Va	ilidati	on		
Date	Severity	Info Source Link	Phase	Generation	Regior	і Туре	Ground equipment	Ground manoeuvring	Adverse Weather/Ice	Windshear	Crosswind	ALC	Loss of comms	Traffic	R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds	Eng Fail	MEL	Syst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data	Def-Charts	Def-Chk lists Def-DBs	Def-Proc's	Fatique	CRM Dhusio	Prysio Workload Distraction	Pressure	L.E.P	Mis-AFS	Mis A/C State	Mis-Sys	Pilot Incap	Communication SA	Leadership and	leamwork Workload Management	Problem Solving	Knowledge	Application of	Procedures & Knowledge	Flight Management, Guidance and	Automation Manual Aircraft Control	Improved Training	Analyst	Checker VEAD (nh)	
11/03/2010	N	http://www.ntsb.g	DES	4	NA	A319			1														Π																								-	N	JPB J	JE 2	010
10/01/2010	N	http://www.ntsb.g	LDG	4	NA	A319																1		1																								N	JPB J	JE 2	010
05/04/2010	1	http://www.ntsb.g	то	4	NA	A320																1																									-	N	IG J	JE 2	010
15/06/2010	1	http://www.ntsb.g	то	4	NA	A330								-				+	-	1	1	1			+						-				+	-											-	N	MN [	DS 2	010
05/06/2010	N	http://www.ntsb.g	GRD	4	NA	A330		1						-				-													-				-	-			1					1			-	M	MN [	DS 2	010
12/05/2010	F	http://www.ntsb.g	LDG	4	AFR	A330								1								-			+										-	1											+	N	MN [	DS 2	010
13/04/2010		http://www.ntsb.g	APR	4	ASIA	A330								+			-		1	1		1			+						+			-	+	+				+							+	N	MN [	DS 2	010
03/04/2010	N	http://www.ntsb.g	CRZ	4	NA	EMB-170		-	1					+			-	+	+		-		$\square$		+						+	+			+	+			+	+	-	-					+	t	MS	ML 2	010
14/11/2009		http://www.ntsb.g	CLB	4	NA	A319		-		-				-				+	1	1	-	1			+						+	-	-		+	+			-	-	+	-					+	N	JPB	JE 2	009
17/09/2009		http://www.ntsb.g	CLB	4	FUR	A319		-						+		-			1	1	-	1			+						-	-	-	-	+	-			-		+	-					+	N	JPB.	JF 2	009
05/11/2009	-	http://www.ntsb.g	CRZ	4	NA	A320					1		1					-			-		+		+					1	1	-			+	-			1		-	-		1			+	Н	IG .	JF 2	009
21/10/2009	+	http://www.ntsb.g	CRZ	4	NA	A320		-		-			1					+	-		-	+	+		+					1	1	-			+	+			1	-	+	-		1			+	M	IG .	IF 2	009
05/08/2009	+	http://www.ntsb.g	GRD	4	FUR	A320		1								-	-	+	+		1	1		-	+			-				-	-		+	+		-	-	-	+	-		-			+	1	IG .	IF 2	009
10/07/2009	N	http://www.ntsb.g	DES	4	NA	A320			1					+			-	+	-				+		+						+	-		-	+	+			-	+	+	-					+	N	IG .	IF 2	009
18/06/2009	1	http://www.ntsb.g	GRD	4	NA	A320	1	-						+				-	-		-	+	+		-						-				-	+		-	-	-							+	N	IG	IF 2	009
04/05/2009	N	http://www.ntsb.g	LDG	4	NA	A320		-	1		1		-	-				+	-		-	+	1	1	-					1	1	-			1	1			-	-	+	-		1		1	1	н	IG .	JF 2	009
15/01/2009	N	http://www.ntsb.g	CLB	4	NA	A320		-					-	-		-	-	+	1	1	-	+	-					-				-	_		-				+	+	-	-		-			-	M	IG	IE 2	009
28/10/2009	1	http://www.ntsb.g	CRZ	4	AUS	A330		-						+			-	+			-	1			+						+	-			+	+			+	+	+	-					+	N	MN F	05 2	009
23/06/2009	-li-	http://www.ntsb.g	CRZ	4	ASIA	A330								-			-	-				1			-										-	+		-	-	-				-			+	N	MN F	05 2	009
01/06/2009	F	http://www.ntsb.g	CRZ	4	FUR	A330		-	1					+		-	-	+	+		-		+		+						+	+		-	+	+			+	+	+	-					+	N	MN F	05 2	009
21/05/2009	+i-	http://www.ntsb.g	CRZ	4	NA	A330		-				-	-	+		_	-	+	+		-	1		-	+			-	+ +		+	+	-	-	+	+		-	+	-	+	-					+	N	MN F	05 2	009
18/11/2009	N	http://www.ntsb.g	CRZ	4	NA	B777		-	1			-	-	+		-	+	+	+		-		+		+			-			-	+	-	-	+	+		-	+	-	+	-						tu t	SF	G 2	009
05/03/2009	N	http://www.ntsb.g	CRZ	4	ASIA	B777			1					-								-													-	-											-	U	SF I	G 2	009
06/01/2009	1	http://www.ntsb.g	CLB	4	ASIA	B777														1	1																											Ν	SF I	G 2	009
27/07/2009	N	http://www.ntsb.g	CLB	4	NA	EMB-170			1																																							L	MS N	VIL 2	J09
11/07/2009	N	http://www.ntsb.g	APR	4	NA	EMB-170		$\rightarrow$	1		$ \rightarrow $			1				+	-	$\square$		1		-			$ \rightarrow $	_	+	$\vdash$	-+	-			-	+	1	-	-		+	+		1			+	L.	MS N	VL 2	009
23/07/2008		mup://www.mtsb.g	ICLB	4	INA	M319		1		1				1	1 I	1	1	1		1	1		4	11		1			1 1					- 1		1		1	- 11			1	- 1	T			1	INI	JPB J	JE 12	JUB





Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runwav/Taxi condition	Adverse Weather/Ice	Windshear Crosswind	ATC	NAV Loss of comms	Traffic	R/W Incursion Poor Visibility	Upset	Wake Vortex Terrain	Birds	eng Fail MEL	Fire C	syst mai Ops/Type Spec	Cabin	Compliance	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs	Def-Proc's Fatique	CRM Physio	Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation Manual Aircraft Control	Improved Training	Analyst	Checker	YEAK (nb)
17/02/2008	Ν	http://www.ntsb.g	GRD	4	NA	A319		1					1																											N	JPB	JE 2	2008
10/01/2008	Ν	http://www.ntsb.g	CLB	4	NA	A319									1						1																			L	JPB	JE 2	2008
09/01/2008	Ν	http://www.ntsb.g	LDG	4	NA	A319													1			1						1								1	1	1		M	JPB	JE 2	2008
27/11/2008	F	http://www.ntsb.g	APR	4	EUR	A320																																		U	IG	JE 2	2008
20/10/2008	Ν	http://www.ntsb.g	LDG	4	NA	A320																1					1				1		1				1	1	1	Н	IG	JE 2	2008
30/05/2008	F	http://aviation-	LDG	4	SA	A320		1	1	1												1					1				1		1				1	1	1	Н	IG	JE 2	2008
15/04/2008	1	http://www.ntsb.g	CRZ	4	NA	A320			1																															L	IG	JE 2	:008
25/02/2008	1	http://www.ntsb.g	LDG	4	NA	A320		1											1																					L	IG	JE 2	:008
25/01/2008	1	http://www.ntsb.g	то	4	NA	A320			_			1							1															_						M	IG	JE 2	:008
04/05/2008	1	http://aviation-	LDG	4	ASIA	A321			_											_											1								1	н	DS	JE 2	.008
30/03/2008	1	http://www.ntsb.g	CLB	4	ASIA	A321																								_				_						N	DS	JE 2	800.
08/01/2008	1	http://aviation-	LDG	4	EUR	A321			_											_		1	_		_		1 1	1			1					1	1	1	1	н	DS	JE 2	800.
07/10/2008	N	http://www.ntsb.g	CRZ	4	AUS	A330			_		_		4	4				_	1			_	_		_		_	_		_				_			_			N	MN		800.
02/07/2008	1	http://www.ntsb.g	GRD	4	INA	A330			_	+	_		1	1				_		4		-	_		-	+	_	_		_	-			_						IN		28 2	.008
16/09/2008	I NI	http://www.nisb.g	CRZ	4	N/A	D///	1	1	_		-		-						$\vdash$	-		-			+		+	-		_	-	-		-			-			IN N	OF		.000
02/07/2008		http://www.nisb.g	DES	4		D///	'	1	1		-	-								_		-	-		+		-	-		_	-			-			-				OF OF		2008
20/03/2008		http://www.ntsb.g	CP7	4		D777					-							_		_		-	-		+		-	-		_	-			-			-			N	0	10 2	2000
25/02/2008		http://www.nisb.g	GPD	4	NA	D777	1	1	-		-									_		-	_		-		1	-		_		_	1			1	_				0	10 2	2008
17/01/2008	N	http://www.ntsb.g	APR	4	FUR	B777			1		-								1	1		-			-			-									-			li l	SE	16 2	2008
26/12/2008	N	http://www.ntsb.g	DES	4	NA	EMB-170			1		-											-			+		-	-			-			-	+ +		-			Li I	MS	MIZ	2008
17/02/2008	N	http://www.ntsb.g	GRD	4	NA	EMB-170		1			+						+ +			-		-			+		1	-		_	1	-	1		+ +		-		1	Ŭ,	MS	MI 2	2008
22/04/2007	N	http://www.ntsb.g	TO	4	NA	A319			-		-						+ +	_	1			1	-		+			-							+ +		1	1		M	IPB	JE 2	2007
16/02/2007	N	http://www.ntsb.g	CLB	4	NA	A319			1		-							-					-		-		-	-		_				-						N	JPB	JF 2	2007
05/01/2007	1	http://www.ntsh.g	LDG	4	NA	A319	1	1 1	1		1		1	1 1								1			+		-	-					1 1		+ +					M	IPB	JE 2	2007
17/12/2007	i	http://www.ntsb.g	CRZ	4	SA	A320	· I		- ·		· ·						1		1						-		-										-			1	IG	JE 2	2007
02/12/2007	i	http://www.ntsb.g	IDG	4	NA	A320					1											-			-			-												N	IG	JE 2	2007
26/10/2007	i	http://aviation-	IDG	4	ASIA	A320					· ·											-			+		-	-			1			-					1	M	IG	JF 2	2007
20/10/2007		http://www.ntsb.g	LDG	4	NA	A320					-								1			-			-		1	-					1							L	IG	JE 2	2007
09/10/2007	1	http://www.ntsb.g	LDG	4	NA	A320													1			-			+			-												N	IG	JE 2	2007
16/08/2007	1	http://www.ntsb.g	GRD	4	NA	A320					1																1										1	1		N	IG	JE 2	2007
17/07/2007	F	http://www.ntsb.g	LDG	4	SA	A320		1	1							1		1				1					1				1	1					1	1	1	Н	IG	JE 2	2007
11/07/2007	I	http://www.ntsb.g	GRD	4	NA	A320								1								1					1						1							M	IG	JE 2	2007
10/02/2007	I	http://www.ntsb.g	CLB	4	NA	A320													1		1																			N	IG	JE 2	2007
25/12/2007	Ν	http://www.ntsb.g	CRZ	4	NA	A330			1																															N	MN	DS 2	2007
04/10/2007	I	http://www.ntsb.g	CLB	4	EUR	A330											1		1																					N	MN	DS 2	2007
23/07/2007	I I	http://www.ntsb.g	CRZ	4	ASIA	A330											1		1																					N	MN	DS 2	2007
14/12/2007	Ν	http://www.ntsb.g	APR	4	NA	B777											1		1		1																			U	SF	IG 2	2007
12/07/2007	N	http://www.ntsb.g	GRD	4	NA	B777		1																																N	SF	IG 2	:007
27/06/2007	N	http://www.ntsb.g	GRD	4	NA	B777		1	1					1													1						1							L	SF	IG 2	:007
13/05/2007	1	http://www.ntsb.g	TO	4	ASIA	B777													1																					N	SF	IG 2	:007
11/03/2007	N	http://www.ntsb.g	TO	4	SA	B777													1																					U	SF	1G 2	.007
26/02/2007	N	http://www.ntsb.g	GRD	4	EUR	B777													1 1									_						_						N	SF	iG 2	:007
23/02/2007	N	http://www.ntsb.g	CRZ	4	INA	B777			1						1						1																			N	SF	IG 2	:007

		A	ccident	ts									Fa	ctors											Fac	ctors	(Non-	Techn	ical)							Comp	oeter	ncies			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear	Crosswind ATC	NAV Loce of comme	Traffic	R/W Incursion	Upset	Wake Vortex	Birds	Eng Fail	MEL Fire	Syst mal	Ops/lype spec Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts	Def-Chk lists Def-DBs	Def-Proc's	ratique CRM	Physio Workload Distraction	Pressure D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Dilot Incen	Communication	SA	Leadership and Teamwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
26/05/2007	1	http://www.ntsb.g	TO	4	NA	EMB-170					1			1																								_		N	MS MI
27/03/2007	N	http://www.ntsb.g	DES	4	AFR	EMB-170			1				-			-+		++			_		_		_					1		-									MS MI
18/02/2007	N	http://www.ntsb.g	LDG	4	NA	EMB-170		1	1				-	1		-	-	++			-	1	1		_	1	1				1	-	-				-	1		1 1	MS MI
14/12/2007	N	http://www.ntsh.g	GRD	4	NA	EMB-190	1	1 1					-			-					-	·										-	-								MS MI
23/10/2006	1	http://www.ntsb.g	LDG	4	NA	A319							-			-		++		1			_		_	+ +		1			-	1	-	1			1			- H	JPB JE
08/09/2006	N	http://www.ntsb.g	GRD	4	NA	A319	1	1			1		1			-	-	+					_	+ +	_	++	1	1			1		-	1	1					1 M	JPB JE
07/07/2006	N	http://www.ntsb.g	DES	4	NA	A319			1							-	-	+					_									-	_							N	JPB JF
21/03/2006	1	http://www.nteb.g	GRD	4	ΝΔ	A310					1		1	1		-	-	+			_							1				-	-	1	1						IPB IF
29/01/2006	N	http://www.ntsb.g	TO	4	NΔ	A310		_		$\vdash$						-	-	++			_		_		_	+ +					1	-	-	1						1 1	IPB IF
07/11/2006		http://www.ntsb.g	GRD	4	NΔ	A320	1	1		+	1		+			-+-	-	++			_		-		-	+ +	1					-	-	1						M	
02/08/2006	-li	http://www.ntsb.g	CLB	4	ASIA	A320				$\vdash$			-			-	-	1			-				-			_	-		-	-	_	<u> </u>						N	IG JE
24/07/2006	-li	http://www.ntsb.g	CLB	4		A320	-						-			-		1			-				-						-	-	-							N	
05/05/2006	N	http://aviation-	GRD	4	FUR	A320	1			$\vdash$			-			-+-	-		1		_		_			+ +		_			-	-	-	+ +							
05/05/2006	N	http://aviation-	GRD	4	FUR	A320	1			$\vdash$	-		+			-+-	-	++	1		_		-		-	+ +						-	-								
05/05/2006	N	http://aviation	CPD	4		A320	1	_		+			-				-	+	1		-		_		_			_				-	-								
03/05/2006		http://aviation=		4		A320			1		-		-	1		-	-	+			-	1	_		_		1	1 1			1	-	_	1						1 1	
23/03/2006	- <u> -</u>	http://www.nteb.a	GRD	4	NA	A320					1		-	1		-+-	-	++	-		_				-	+ +		<u></u>				-	-							N	
05/03/2006	- <u> -</u>	http://www.ntsb.g		4	FUR	A320				+			+			-+-	-	++	1	1	_		-		-	+ +						-	-								
25/04/2006	N	http://www.ntob.g	DES	4	NA	D777		_	1				-				-	+		1.	-		1		_			_				-	-								SE IG
19/04/2006	N	http://www.ntsb.g	DES	4		D777					-		1			-	_	+			-		- 1'		_						-	-	_								SE IG
19/01/2006		http://www.ntsb.g	CPD	4	NA	D777	1	_		$\vdash$	_	+ +	-		-	-	-	++		+ +			_	+	_	++		_	_		-	-	-								
08/09/2006	N	http://www.ntsb.g	GRD	4	NA	EMP 170	1	1	-	$\vdash$	1		-			$\rightarrow$	_	++	_		_		_	+ +	_			_	_		-	-	_								MS MI
30/05/2008	N	http://www.ntsb.g	GRD	4	NA	EMP 170				$\vdash$			-			-	_	++		1	-		_		1			_	_			-	_								MS MI
10/10/2005	N	http://www.ntsb.g	CPD	4	NA	A210	1 1	1 1	1		-		-	1		-	-	+		<u> </u>		1	_					1			-	-	1	1						M	
10/06/2005	N	http://www.ntsb.g	DES	4	NA	A315			1		_	+ +	-			-+-	_	++		+ +	1	1		+	_	++					-	-									
10/05/2005	N	http://www.ntsb.g	GPD	4	NA	A313		1			_		1			$\rightarrow$	_	++	_	1		1	_		1	1		_	_		-	1	_	1		1					
21/00/2005		http://www.msb.g	LDC	4	N/A	A313				$\vdash$						-		++		1	_	1	_					_					_	<u> </u>		1				-	
21/09/2005		http://aviation-	CPD	4		A320	4	1								-		+		-	-		_		-		1	_	_		1	_	-	1							
18/09/2005	N	http://www.ntsb.g	LDG	4	NA	A320					1	+ +	-	+		-+-	_	++		1	_	1	_	+ +	_	++	1	_	_		1	1	-		1						
20/08/2005	N	http://www.ntsb.g	CPD	4	NA	A321		1	-				-			-	_	++	_			'	_	+ +	_		1	_	_				_	1						M	MN DS
00/06/2005		http://www.ntsb.g	TO	4	NA	A330					1		1	1		-	_	+			-				-			_	_			_	_								MNI DS
06/11/2005	N	http://www.ntsb.g	GPD	4		A330	4	1		+			-	· ·		-	-	++					_		_	+ +		_	_			-	-	1							MNI IE
00/11/2005	N	http://www.ntsb.g	LDG	4	EUR	A340		1	1		1		-		-	-	-	++	1		_	1	_	+ +	-		1	_	_		1	-	_	-		1					MNI JE
06/11/2005	N	http://www.ntsb.g	CPD	4		P777		1					-			-	_	++			_	'	_	+ +	_			_	_			-	_			1					SE IG
00/11/2005		http://www.ntsb.g		4	AUG	D777				$\vdash$			-		1	-		++		1 1	_		_		_			_			-	-	_								
02/08/2005	-	http://www.nisb.g		4	AUS	D///		_		$\vdash$			-		1		-	1		<u>      </u>			_		_			_			-		_								
23/00/2005	N	http://www.nisb.g		4	ASIA	D///		_	1				+			$\rightarrow$	-	-			_	1		+	-	1	1	_	_		1	1	_	1						1	
03/10/2005	N	http://www.ntsb.g		4	NA	EMP 170						-	1			-	-	+		+		1	-	+	-		1	_			1		-	-							MS MI
03/10/2003		http://www.ntsb.g		4	N/A	EMD 170	1			$\vdash$			1					+				1			-	+	1	_			1	-									MC MI
17/07/2005	N	http://www.msb.g	DES	4	NA	A210	1	-	1	$\vdash$		+	-	+				++		+	-	$\vdash$		+		++	1	_		+	-		1		1						
30/06/2004	N	http://www.ntsb.g	GPD	4	NA	A315		-			_	+ +	1		-	-		+	_				-+	+	-	+	-	_	_	-	-	-	-	1		1				-+	
18/10/2004		http://www.msb.g	LDG	4		A320			1	1		+	-			+				+	_	1		+		+	1	1		+	1	1	1	-		-					
13/07/2004	1	http://www.ntch.o	TO	4	NA	A320										-		<sup>1</sup>			-	1		+			- 1				1		1					1		<u> </u>	
05/03/2004	1	http://www.ntsb.g	GRD	4	NA	A320	1	1	+									++			-	1			-		1				1	-	1	1	-					1 M	IG JE
											1				1				1	1 1																					

05/03/2004	1	http://www.ntsb.g	GRD	4 N	NA	A320		1															1						1				1		1 1						1 M	IG	JE
		A	ccidents	;										Facto	ors											Fa	actors	5 (N	on-Tec	hnica	ıl)							Compe	tencies			Vali	idation
Date	Severity	Info Source Link	Phase	Generation 		Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind	ATC NAV	Loss of comms	Iramic R/W Incursion	Poor Visibility	Upset Moto Votes	Torrain	Birds	Eng Fail	MEL Fire	Syst mal Ons/Type Spec	Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts	Def-Chk lists	Def-DBs Def-Proc's	Fatique	CRM Physio	Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	knowledge Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
22/01/2004	N	http://www.ntsb.g	APR	4 E	EUR	A320														1	1																				N	IG	JE
07/06/2004	1	http://www.ntsb.g	GRD	4 N	NA	A340																									1										U	MN	JE
11/08/2004	1	http://www.ntsb.g	TO	4 N	NA	B777													1	1	1																				N	SF	IG
16/10/2003	N	http://www.ntsb.g	GRD	4 N	NA	A319		1													1	1																			L	JPB	JE
02/06/2003	N	http://www.ntsb.g	APR	4 N	NA	A319			1	1																															N	JPB	JE
05/04/2003	N	http://www.ntsb.g	CLB	4 N	NA	A319			1	1																															N	JPB	JE
29/11/2003	1	http://www.ntsb.g	CLB	4 E	EUR	A320															1																				N	IG	JE
06/11/2003	li –	http://aviation-	LDG	4 5	SA	A320			1	1	1																						1								1 M	IG	JE
05/06/2003	N	http://www.ntsb.g	CLB	4 N	NA	A320			1	1							+									-			1						1	1					M	IG	JE
26/05/2003	1	http://aviation-	CRZ	4 E	EUR	A321			1	1		_					+	-		_	1					-	1		1									1		-	L	JE	MS
21/03/2003	N	http://aviation-	IDG	4 A	ASIA	A321	1					1		1															1						1 1							JE	MS
05/10/2003	1	http://www.ntsb.g	CLB	4 1	NA	A330								-			-		1		1																				- N	MN	DS
09/08/2003	i -	http://www.ntsb.g	CRZ	4 F	=UR	A330			-					-			+	-	1	_	1					-										-					N	MN	DS
18/08/2003	ti -	http://www.ntsb.g	TO	4	NA	A340	_		-			_		-			+	-		_	1	-	+			-	-									+			-	-	1 U	MN	JF
06/08/2003	N	http://www.ntsh.g	CRZ	4 1	NA	A340			1	1							+	-					1			-			1							1		1	1		H H	MN	LIE
07/10/2003	N	http://www.ntsb.g	GRD	4 N	NA	B777		1	- 1			1					+	-				-				-										1	-					SE	IG
07/10/2003	N	http://www.ntsb.g	GRD	4 N	NA	B777		1	-			1		-	-		+	+	-	_		-	+ +		+ +	-	_		1				1	-	1	-	-		-	-	1 1	SF	lig
28/09/2003		http://www.ntsb.g	CRZ	4 A		B777	-		-	_				-			+	-		1		-		_	+ +	-	_							-			-		-	-		SE	
17/07/2003	N	http://www.ntob.g		4 1		D777	-		-	1				-	-		-					-		_	+ +	-	-		1					-	1							SE.	
25/02/2003	N	http://www.ntsb.g	DES	4		D777	-			1				-	-		-	-		_		_		_	+ +	-	-							-			-				M	SI	
21/11/2002	N	http://www.ntsb.g	LDC	4		A210	_		- 1		+ +	_	+ +	-	-		-	-		_	1	_		_	+ +	-	-	+						-		-	-		-				
21/11/2002	N	http://www.nisb.g	DES	4 1		A319	_		-			_		-	-		+	-	-	_	1	_	+	_	+ +	-	_	$\vdash$						_		+	-		-	-		JPB	
15/04/2002	IN	http://www.nisb.g	DES	4 1		A319	_		- 1			_		_	-		_	_		_		4		_	+ +	-	_	+ +						_		-			-			JPB	
28/11/2002	IN	http://www.ntsb.g	ULB	4 1		A320	_		_	_		_		_	_		_	_		4		1	4			-	_		4				4		4	4						IG	JE
28/08/2002	N	http://www.ntsb.g	LDG	4 1	NA	A320			_	_		_		_	_		+	_		1			1 1	1		_	_		1				1 1		1	1					1 H	IG	JE
06/07/2002	-	http://www.ntsb.g	10	4 E		A320			_	_				_			-		1	_		_		_	-	_	_							_						-		IG	JE
17/12/2002	1	http://www.ntsb.g	APR	4 <i>P</i>	ASIA	A330				_		1			1		1							_					1				1		1				1	1	н	MN	DS
25/01/2002		http://www.ntsb.g	GRD	4 N	NA	A340		1 1		_		_										_		_			1		1	1					1				1		M	MN	JE
02/11/2001	1	http://www.ntsb.g	CRZ	4 N	NA	A319				_		_					$\rightarrow$				1			_									1					1			M	JPB	JE
20/08/2001	N	http://www.ntsb.g	CRZ	4 N	NA	A320			1	1																			_												N	IG	JE
15/06/2001	N	http://www.ntsb.g	DES	4 N	NA	A320						1																	1				1			1		1			1 H	IG	JE
19/04/2001	N	http://www.ntsb.g	CRZ	4 N	NA	A320			1	1				_															1							1		1			н	IG	JE
20/03/2001	1	http://aviation-	то	4 E	EUR	A320			1	1											1																				N	IG	JE
17/03/2001	N	http://www.ntsb.g	TO	4 N	NA	A320			1	1											1		1						1	1			1 1	1	1				1		1 H	IG	JE
07/02/2001	Ν	http://aviation-	LDG	4 E	EUR	A320			1	1 1	1										1		1				1		1				1 1	1				1	1		1 M	IG	JE
21/01/2001	1	http://www.ntsb.g	LDG	4 1	NA	A320		1	1	1	1	1											1	1					1				1					1	1		1 M	IG	JE
24/08/2001	1	http://www.ntsb.g	CRZ	4 E	EUR	A330													1		1								1				1	1				1 1	1		н	MN	DS
25/07/2001	1	http://www.ntsb.g	CLB	4 E	EUR	A330													1		1																				N	MN	DS
05/09/2001	F	http://www.ntsb.g	GRD	4 N	NA	B777	1													1																					H	SF	IG
07/08/2001	1	http://www.ntsb.g	GRD	4 E	EUR	B777		1																																	U	SF	IG
06/06/2001	1	http://www.ntsb.g	CRZ	4 A	ASIA	B777															1																				N	SF	IG
30/01/2001	1	http://aviation-	TO	4 A	AUS	B777													1																						N	SF	IG
23/08/2000	F	http://www.ntsb.g	GA	4 A	ASIA	A320																	1						1				1		1				1		1 H	IG	JE
12/06/2000	N	http://www.ntsb.g	TO	4 N	NA	A320															1	1													1						N	IG	JE
11/04/2000	N	http://aviation-	GRD	4 N	NA	A320	1																												1 1						N	IG	JE





		A	ccident	ts								Fa	actors	;										Facto	rs (No	on-Teo	chnica	al)						(	Comp	etencies			Valio	dation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment Ground mangeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility Upset	Wake Vortex	Terrain Birds	Eng Fail	Fire	Syst mal Ons/Type Spec	Cabin	Def Manuals	Def-Ops data	Def-Chk lists Def-Chk lists	Def-DBs Daf-Dmo'e	Fatique	CKM Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State Mis-Svs	Pilot Incap	Communication SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
25/01/2010	F	http://www.ntsb.go	TO	3	ME	B737G3									1	1																						U	DS	SD
19/01/2010	I I	http://www.ntsb.go	LDG	3	ASIA	B737G3	1																							1								1 U	DS	SD
04/01/2010	I I	http://www.ntsb.go	GRD	3	EUR	B737G3	1											1	1																			N	DS	SD
03/01/2010	1	http://www.ntsb.go	TO	3	EUR	B737G3	1	1	1				1	1					1											1								1 M	DS	SD
03/02/2010	1	http://www.ntsb.go	TO	3	ASIA	B747G3											1	1	1		_																	N		_
31/05/2010	1	http://www.ntsb.go	GRD	3	EUR	B747G3					_								1		_										_							U		_
21/09/2010	1	http://www.ntsb.go	GRD	3	ASIA	B747G3													1																			U		_
21/01/2010	N	http://www.ntsb.go	LDG	3	EUR	B747G3	1			1			1							_																		N		_
10/10/2010	N	http://www.ntsb.go	APR	3	INA	B747G3					_					_			1			+			+	_	<u> </u>				_							N	<u> </u>	_
08/04/2010	N	nttp://www.ntsb.go	GRD	3	EUR	B/4/G3			_		-		+	_	$ \rightarrow $			1	1		_	+	_			_					_		-			_		N		_
10/10/2010	<u> </u>	nttp://www.ntsb.go	TO	3	ASIA	B/4/G3			_		-			_			1		1		_		_			_				1	-		-			_	-	IN N	<u> </u>	-
11/06/2010		http://www.ntsb.go		2	AUS	D747G3			_		-			_		_	1		1		_		-							1	-						-	I IVI		
20/07/2010	<u> </u>	http://www.nisb.go		3	NA	D747G3			_		+		+ +	-		-			1		_	+ +				-					-		-			_			<u> </u>	-
04/02/2010	I NI	http://www.nisb.go		3	IN/A	D747G3			_		-		+ +	-	$\rightarrow$	-			1		_	+ +	_			-				1	-		-			_	-	1 14		-
5/16/2010	IN	http://www.ntsb.go		2	IN/A	D747G3			_		-			_		_	1	1	1 1		_		_							1	-							I IVI		-
5/16/2010		http://www.ntsb.go		3		B/3/			_		-			-		_	1	1	1 1		_		_							_	-		-							-
0/12/2010	<u> </u>	http://www.nisb.go		3		D/3/			1		+		+ +	-		-	+		1	-	_	+ +	-			-	-				-		-			_	-			-
10/26/2010	I N	http://www.ntsb.go		2		D/0/ D757					+			-		_			1		_	+ +			++	_	-			_	-		-				-			-
8/30/2010		http://www.ntsb.go		2		D757			1		-			-		_			1	-	_		-			-					-									-
6/16/2010		http://www.ntsb.go		2	ELID	D/0/ D767					-					_		1	1	-	_	+ +			++	_	-				-		-						QE.	
4/20/2010	I N	http://www.ntsb.go		2		D/0/ D767			1		+			-	+	-				-	_						-			_	-	1	-		1		-			- 06
4/23/2010	IN	http://www.ntsb.go		3		D707					-			-	+	_	+	1	1	1	_		-								-		-			_				-
7/15/2010	I N	http://www.ntsb.go		2		D/0/ D767			1		-			-		_		1	1	-	_				++	_					-		-							-
17/04/2010	N	http://www.ntsb.go		3	NA				1		+		+ +		+	-	+				_	+	_	-		_	<u> </u>	+			-								ml	MS
28/06/2010	N	http://www.ntsb.go	CRZ	3		EMB-145			1		+		+ +	-		-					_	+ +	-		+	-	-			_	-		-						MS	MI
16/06/2010	N	http://www.ntob.go		2	NA	EMD 145		1			-		+ +						1		-	+ +					-			1	-		-						MS	MI
12/03/2010		http://www.ntsb.go	APR	3		EMB-145			1		+		+ +			-			1		-	+ +			+		<u> </u>				-		-			-			MS	MI
9/18/2010	li l	http://www.ntsb.go	GRD	3	FUR	MD11				1			1	-		-	+ +				-	+ +	-			-	-				+		-						1110	- IVIL
7/27/2010	N	http://www.nteb.go		3	AFR	MD11					-					-	+		1		-	+ +					-			1	+		-			-		1 M	<u> </u>	-
3/23/2010		http://www.ntsb.go	CRZ	3	FUR	MD11			-		-			-					1		-										-							N		-
29/06/2009	F	http://aviation-safe	APR	3	AFR	A310			1	1	+			-	+	-					_	+ +			+ +		-			1	+		-			_		1 H	FV	AAD
22/12/2009	N	http://www.ntsh.go	NI DG	3	SA	B737G3	1	1	1		+		1	1		-	+				-	+ +				_	-				+		-		1	1		1 M	DS	ISD
30/10/2009	1	http://www.ntsb.go	TO	3	ASIA	B737G3													1		-									1								. N	DS	SD
19/10/2009	i	http://www.ntsb.go	DG	3	AUS	B737G3	1				+		+				++		1		+	+			++	-	-				+		1				-		DS	SD
02/10/2009	li l	http://www.ntsb.go	IDG	3	ASIA	B737G3	1		_		+		+ +			-	++		1		_	+ +				_					-		-			-	-		DS	ISD
08/09/2009	i l	http://www.ntsb.go	DG	3	NA	B737G3	1				+		+				+		1			+			++	-					+		1						DS	SD
21/08/2009	li l	http://www.ntsb.go	TO	3	AUS	B737G3			-		1								1								1				+		1				1		DS	SD
10/08/2009	N	http://www.ntsb.go	TO	3	ASIA	B737G3	1		-		+		+		+	-	++				-	+			++	-	1			1	+		1			1		1 H	DS	SD
17/07/2009	1	http://www.ntsb.go	GRD	3	EUR	B737G3	1		+		+					-	++				-		-		+ +	+	-				+		1					N	DS	SD
15/07/2009		http://www.ntsb.go	GRD	3	NA	B737G3					1								1												-						1		DS	SD
13/07/2009	1	http://www.ntsb.go	CRZ	3	NA	B737G3													1												-							N	DS	SD
14/06/2009	1	http://www.ntsb.go	LDG	3	ME	B737G3					+								1												+							N	DS	SD
12/06/2009	1	http://www.ntsb.go	LDG	3	ME	B737G3	1												1								1						1				1	U	DS	SD





		Ac	ccident	ts										Fac	tors	S											Fa	actors	s (N	on-Te	chnic	al)							(	Compet	encies			Validatio	on
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind	ATC	Loss of comms	Traffic	R/W Incursion	Poor Visibility	Wake Vortex	Terrain	Birds	eng Fail MEL	Fire	Syst mal	Cabin Cabin	Compliance	Def Manuals Def-Ons data	Def-Charts	Def-Chk lists	Def-DBs Def-Proc's	Fatique	CRM Physio	Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and	Manual Aircraft Control Improved Training	. Analyst Checker	
28/08/2008	1	http://www.ntsb.go	CRZ	3	SA	B737G3						1		1																						1							N	DS SD	,
16/08/2008	1	http://www.ntsb.go	TO	3	EUR	B737G3		1																1									1				1						н	DS SD	)
23/07/2008	1	http://www.ntsb.go	GRD	3	ASIA	B737G3																1																					N	DS SD	)
05/07/2008	1	http://www.ntsb.go	APR	3	NA	B737G3					1			1																													N	DS SD	<u>ر</u>
02/07/2008	1	http://www.ntsb.go	GRD	3	NA	B737G3		1							1									1													1 1	1					H	DS SD	)
06/04/2008	Ν	http://www.ntsb.go	DES	3	NA	B737G3			1															1																			L	DS SD	)
27/03/2008	1	http://www.ntsb.go	LDG	3	NA	B737G3		1												1														1							1		1 H	DS SD	נ
21/03/2008	I	http://www.ntsb.go	LDG	3	EUR	B737G3		1																													$\square$						U	DS SD	)
10/03/2008	Ν	http://www.ntsb.go	LDG	3	ASIA	B737G3		1														1															$\square$						U	DS SD	)
01/03/2008	1	http://www.ntsb.go	GRD	3	NA	B737G3		1			_													1													1						н	DS SD	)
24/02/2008	1	http://www.ntsb.go	DES	3	NA	B737G3			1																												$\vdash$						U	DS sd	
22/02/2008	N	http://www.ntsb.go	DES	3	NA	B737G3			1														_														$\vdash$						U	DS sd	
13/02/2008	1	nttp://www.ntsb.go	LDG	3	EUR	B/3/G3					-		_		_	_	_					_		-						_	-	+		1	-		$\mapsto$						1 0	DS SD	)
10/02/2008	IN	http://www.ntsb.go		3	ASIA	B/3/G3	4		1		+		_		_	_	_	-				_	_	-						_	-	+			$\rightarrow$	_	$\mapsto$					_		05 50	-
31/01/2008	F	http://ntsb.gov/ntst		3	INA	B/3/G3	1			_	-					_	_					_		-		_				_	-					-	$\mapsto$					-	IN IN	05 50	<u>,</u>
14/01/2008	F	http://ntsb.gov/ntst		3		B/3/G3		4		_	-		_			_	_	1				-	1							_	-			1			++				-	-	1 1	DS SD	-
03/01/2008	N	http://www.ntsb.go		2		B737G3		1	1		+		_		-	-	_	+				-				-			+ +	_	-	+		1	-	-	++					_		03 30	<u></u>
02/10/2008		http://www.ntsb.go		2	ASIA	D747G3					+		_		-	-	_	+				1	_	-		-				_	-	+			-	-	$\mapsto$					-		-	
25/03/2008	l l	http://www.ntsb.go		2		B747G3				-	-		_		_	-	_			-	1	1	_	-						_	-						$\vdash$				-	-			
25/07/2008	N	http://www.ntsb.go		2		B747G3				-	+		_		-	-	_	-				1	_	-		-				_	-		_		-	-	++				-	-			
26/08/2008		http://www.ntsb.go		3	NA	B747G3				-	+		_		-	-	-	+		-			_	+		-				_	-	+	_	1	-	-	++		-			-	1 M		-
0/22/2008	li li	http://www.ntsb.go		2	NA	D74703				_	-		1		-	-	_					1	_	-	1	_		1		1	-			1	-		++		- 1	1	1		1 1		
9/18/2008	li l	http://www.ntsb.go	CRZ	3	FUR	B757					-				-		-				1	1	-	-													$\vdash$				1		N		-
8/6/2008	li l	http://www.ntsb.go	TO	3	NA	B757				-	+		-		-	-	-	+ +	1			1	-	-						-	-	+			-	-	$\vdash$			-	-	-	N		-
3/22/2008	li l	http://www.ntsb.go	CBZ	3	NA	B757					+		_		-	-	_	+ +				1	-	-		-				-	-				-	-	$\vdash$		-			-		-	
1/13/2008	N	http://www.ntsb.go	GRD	3	ΝΔ	B757		1			-	1	-			-	_			-		<u> </u>	_	-				_			-					-	$\vdash$						N	-	
12/28/2008	N	http://www.ntsb.go	GRD	3	NA	B757		1		-	+		_		-	-	-	+				-		+		-				_	-				-		$\vdash$	-	-						
1/30/2008	i i	http://www.ntsb.go	CRZ	3	NA	B757				-	+		_		-	-	-	-		-	1	1 1		+						_	-	+	_		-	-	$\vdash$				-	-	- N		-
7/5/2008	li l	http://www.ntsb.go	TO	3	NA	B767					+	1		1	1	-	-					· · ·		-													$\vdash$	-					1 10		-
6/28/2008	N	http://www.ntsb.go	GRD	3	NA	B767					-					-					1	1		-													$\vdash$						N		-
26/12/2008	N	http://www.ntsb.go	GRD	3	NA	DC9-8x		1			+					-								1						_	-				-		$\vdash$				-		H	ml MS	s
11/12/2008	i.	http://www.ntsb.go	DG	3	NA	EMB-145					+		_		-	-	-	+ +			1	1									-				-	-	+			-			1 U	DS MS	ŝ
14/08/2008	N	http://www.ntsb.go	DG	3	NA	EMB-145				-	-					-								1						1	-			1			$\vdash$		1	1	1		1 H	DS MS	s
21/07/2008	i.	http://www.ntsb.go	TO	3	NA	EMB-145					+	1		1	-									·													$\vdash$						N	DS MS	ŝ
27/05/2008	N	http://www.ntsb.go	CRZ	3	NA	EMB-145			1		-													-																_	-		L	MS ML	
15/02/2008	N	http://www.ntsb.go	CLB	3	NA	EMB-145					-				-					-			1								1					1							N	DS MS	s
4/27/2008	1	http://www.ntsb.go	GRD	3	ASIA	MD11					1											1									1					1	-+						N		-
23/01/2007	1	http://www.ntsb.go	CLB	3	ASIA	A306					1								1		1	1		1							1					1	$\square$				1	1	N	EV AA	AD
12/03/2007	N	http://aviation-safe	TO	3	ASIA	A310					1											1		1							1					1	$\square$				1		U	EV AA	AD
28/01/2007	1	http://www.ntsb.go	CRZ	3	EUR	A310																1		1																			U	EV AA	٨D
25/11/2007	1	http://www.ntsb.go	TO	3	NA	B737G3		1														1															$\square$						N	DS SD	5
21/11/2007	1	http://www.ntsb.go	CLB	3	ASIA	B737G3																																					N	DS SD	5
17/11/2007	1	http://www.ntsb.go	CLB	3	NA	B737G3													1				1	1																			N	DS SD	5





		A	ccident	ts								Fa	ctors										F	actors	; (Non	-Techr	ical)							Com	pete	ncies			Vali	dation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss or comms Traffic	R/W Incursion	Upset	Terrain	Birds	eng rail MEL	Fire Svet mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data	Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure D.G	LF.P	Mis-Ar S Mis A/C State	Mis-Sys Dilot Incen	Communication	SA Leadershin and	Teamwork	Workload Management Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
19/10/2006	1	http://www.ntsb.go	CRZ	3	NA	B737G3												1																				N	DS	SD
29/09/2006	F	http://www.ntsb.go	CRZ	3	SA	B737G3				1																												U	DS	SD
16/09/2006	Ν	http://www.ntsb.go	CRZ	3	NA	B737G3			1			1																										N	DS	SD
12/09/2006	I I	http://www.ntsb.go	LDG	3	AUS	B737G3												1																				N	DS	SD
03/09/2006	1	http://www.ntsb.go	LDG	3	ME	B737G3												1																				N	DS	SD
31/08/2006	I I	http://www.ntsb.go	LDG	3	NA	B737G3	1											1					1						1									1 H	DS	SD
21/08/2006	1	http://www.ntsb.go	GRD	3	NA	B737G3	1 1																															N	DS	SD
27/07/2006	Ν	http://www.ntsb.go	GRD	3	NA	B737G3	1																										$\rightarrow$					N	DS	SD
23/07/2006	1	http://www.ntsb.go	TO	3	NA	B737G3				1		1	1										_								_		_	_				N	DS	SD
07/07/2006	1	http://www.ntsb.go	CRZ	3	EUR	B737G3												1			_		_			$\rightarrow$	_		<u> </u>		_		$\rightarrow$	-		-		N	DS	SD
15/06/2006	!	http://www.ntsb.go	LDG	3	EUR	B737G3			1	1		_	1	4		_	_				_	1	_		1		_	1	1		_		$\rightarrow$	1		1	1	1 0	DS	SD
08/06/2006		http://www.ntsb.go	DES	3	EUR	B737G3								1		_							_				_		_					_				L	DS	SD
08/06/2006	IN	http://www.ntsb.go	JTO	3	INA	B737G3	1		_			-	4				_		_		_	+	_				_		_		_		$\rightarrow$	_				IN	DS	SD
23/03/2006		http://www.ntsb.go		3		B/3/G3	1		_	1		1	1			1		1 1			_	+	_			++	_		_		_		$\rightarrow$	_				IN N	DS	SD
13/02/2008	1	http://www.nisb.go		0	ISA NA	D737G3			_	4		1	4					1 1			_	+	_				_		_		_		$\rightarrow$	_				IN	03	30
23/07/2006		http://www.ntsb.go		3	INA	B747G3	1 4			1		1	1			_	-		-			+	_		1		_		1		_	1	$\rightarrow$	_				1		
23/04/2006	<u> </u>	http://www.nisb.go		2		D747G3	1 1		-			-	+			1			-		-	+	-				-		- 11		_		$\rightarrow$	-	+			I L	-	
2/1/2000		http://www.ntsb.go		2		D747G3						-		_				1				+	-				_		_		_		$\rightarrow$	-				IN N		
26/12/2006	li l	http://www.ntsb.go		2	NA	B747G3	1		-							_	-						-		1		_		1		_	1	-+	-				1 M		
31/10/2006	N	http://www.ntsb.go		3		B747G3	1					-	1			-	-					+	-		1		_		1		_	1	-+					1 M		
09/10/2006		Eactual	CPD	2		B747G3	1		-	-		_				1		1 1			-	+ +	_				_				_		$\rightarrow$	_	+ +			I IVI		
12/31/2006		http://www.ptch.go		2		D74703												1 1			_	+	_				_		_		_		$\rightarrow$	-					ee.	DP
2/25/2006	N	http://www.ntsb.go		2	NA	D757	1					-	$\vdash$			-						+	-						-		_		$\rightarrow$	-				U	31	00
1/27/2006		http://www.ntsb.go		3		B757				1		1	1			-	+		-		-	+	_			++			+	-	_		-+		+ +			N		
10/28/2006	li l	http://www.ntsb.go		3	ΝΔ	B757			-	1			1			-			-	1		+	-		1	1			1		_	1	-+	-		1		M		
3/15/2006	N	http://www.ntsb.go	CRZ	3	ΝΔ	B757			1			-				-	-		-			1									_					-				
5/17/2006		http://www.ntsb.go	GRD	3	NΔ	B757						-				-	-	1					-						_		_		-+	-				N		
9/5/2006	N	http://www.ntsb.go		3	ΝΔ	B757			-		1	-				-	-					+ +	-		1		-		1	1	_	1	-	-		1		1 H		
12/30/2006	1	http://www.nteb.go		3	AUS	B767										-		1 1				+	-								-		_	-		<u> </u>				
11/8/2006	li l	http://www.ntsb.go	GRD	3	FUR	B767						-				-	-	1											-									N		
7/24/2006	li l	http://www.ntsb.go	CRZ	3	NA	B767			1			-				-	-					+ +	-				-		+		_			-	+ +				-	
6/17/2006	N	http://www.ntsb.go	GRD	3	NA	B767	1					-				-			-			+	_				_		-		_		-		+			N		
6/2/2006	1	http://www.ntsb.go	GRD	3	NA	B767										1		1													-							N		
9/17/2006	li l	http://www.ntsb.go	CRZ	3	SA	B767										-		1 1				+									_		-+					N	-	
20/08/2006	li l	http://www.ntsb.go	GRD	3	NA	DC9-8x						-				-	-	1 1				+	_						-		_		-					N	Ben	ml
20/06/2006	N	http://www.ntsb.go	DG	3	NA	DC9-8x						-				-	-	1					+				-		-		-1		+					N	Ben	ml
21/03/2006	li l	http://www.ntsb.go	DG	3	NA	DC9-8x											-			1			-		1		-		1		-1	1	-+	-				1 M	Ben	ml
24/07/2006	N	http://www.ntsb.go	GRD	3	NA	EMB-145	1 1					+				-	-			1		+	+		1		-		- <u> </u>		1		+			1		M	MS	ML
13/05/2006	N	http://www.ntsb.go	DES	3	NA	EMB-145			1			+				-	-						+				-		+				+					L	MS	ML
12/05/2006	N	http://www.ntsb.go	GRD	3	NA	EMB-145	1						1																				+					N	MS	ML
21/03/2006	1	http://www.ntsb.go	GRD	3	NA	EMB-145				1		1	1																				+					U	DS	MS
11/7/2006	1	http://www.ntsb.go	LDG	3	EUR	MD11										-		1					-										+					N		<u> </u>
9/14/2006	1	http://www.ntsb.go	LDG	3	ASIA	MD11													1										1									1 M	1	





		A	ccident	ts								Fa	acto	rs										Fa	ctors	s (No	n-Tec	chnica	al)						C	ompet	encies			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Svst mal	Ops/Type Spec	Cabin	Compliance Def Manuals	Def-Ops data Def-Charts	Def-Chk lists Dof-Dec	Def-Proc's	Fatique C.P.M	Physio	Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State Mis-Sys	Pilot Incap	Communication SA	Leadership and Teamwork	Workload Management Problem Solving	Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
11/10/2004	1	http://www.ntsb.go	TO	3	AUS	B737G3																									1							1	1 M	DS ML
13/09/2004	Ν	http://www.ntsb.go	APR	3	NA	B737G3									1																							1	N	DS ML
01/09/2004	I	http://www.ntsb.go	TO	3	EUR	B737G3													1																				N	DS ML
19/08/2004	I	http://www.ntsb.go	TO	3	NA	B737G3				1		1	1																										N	DS ML
07/08/2004	I I	http://www.ntsb.go	TO	3	NA	B737G3				1																													N	DS ML
04/06/2004	Ν	http://www.ntsb.go	CRZ	3	NA	B737G3			1																														U	DS ML
14/04/2004	N	http://www.ntsb.go	CRZ	3	NA	B737G3			1																													<u> </u>	U	DS ML
10/04/2004	N	http://www.ntsb.go	CRZ	3	NA	B737G3			1																	1							1						M	DS ML
24/02/2004		http://www.ntsb.go	LDG	3	NA	B737G3			_				_	1												1							1		_		1	<u> </u>		DS ML
03/01/2004	F	http://www.ntsb.go	10	3	ME	B737G3		_			-		-	1	1	-				-		_			_	1				_	1		1	1	-			1	пн	DS ML
8/31/2004	IN	http://www.ntsb.go		3	ASIA	B/4/G3			1				-	+				-		_		_			_			<u> </u>							_		<u> </u>	+		
1/24/2004		http://www.nisb.go		2		D757			_		-		-	+		-			1	1						1				_			_		1			+		SF DB
3/1/2004	N	http://www.ntsb.go		3	NA	B757			1		-		-	+		-			· · ·			-			-			<u> </u>		-		-	-		-		<u> </u>	+		
8/27/2004		http://www.ntsb.go	CLB	3	NA	B757					-		-	+		-	1	-	-	-		-			_		-			-		-	-	-	-	_		+		
10/19/2004	i l	http://www.ntsb.go	CLB	3		B757							-			-	. 1		1						_					_			_			_	<u> </u>	+		
9/29/2004	N.	http://www.ntsb.go	CRZ	3	NA	B767			1				-																								<u> </u>	+	t lu	
11/7/2004	i i	http://www.ntsb.go	GRD	3	EUR	B767	1				+		-			+			-						_					_					-	_		+	ŤŪ	
2/19/2004	1	http://www.ntsb.go	LDG	3	NA	B767					-					-			1																			+	N	
7/28/2004	N	http://www.ntsb.go	TO	3	EUR	B767											1		1 1																			1	N	
8/7/2004	Ν	http://www.ntsb.go	LDG	3	SA	B767																									1								1 M	
21/11/2004	I	http://www.ntsb.go	APR	3	NA	DC9-8x								1		1					1					1		1			1				1		1		1 H	Ben ml
16/09/2004	I	http://www.ntsb.go	CLB	3	NA	DC9-8x											1 1		1																				L	Ben ml
15/07/2004	Ν	http://www.ntsb.go	DES	3	NA	DC9-8x			1																	1							1						M	Ben ml
26/05/2004	I	http://www.ntsb.go	DES	3	NA	DC9-8x			1												1																		L	Ben ml
20/02/2004	Ν	http://aviation-safe	TO	3	SA	DC9-8x													1																				N	Ben ml
29/08/2004	N	http://www.ntsb.go	CRZ	3	NA	EMB-135			1					$ \downarrow \downarrow$																_			_					<u> </u>	L	MS ML
11/06/2004	1	http://www.ntsb.go	LDG	3	NA	EMB-135			_				-	$\vdash$					1	1					1			<u> </u>			1		_				<u> </u>	<u> </u>	1 M	MS ML
19/01/2004	1	http://www.ntsb.go	10	3	NA	EMB-135			_				_	+					1											_					_		<u> </u>		N	ML JS
0/10/2004	I NI	http://www.ntsb.go		3	INA NA	MD11 MD11			_		-		-	+		-	1	1	1			1	1		_	1					1		_		1	1	1			SF DB
1/26/2004	IN	http://www.nisb.go	LDG	2	NA	MD11		-	_		-		-	+		-		-	-	-					_					_	1	-	_		- 1	_	+	4		
10/04/2003	li l	http://www.ntsb.go	CLB	3		A306			_		-		-	+		+			1 1			_			_		-	<u> </u>		_		-	_		-	_	<u> </u>	+	N	
19/12/2003	N	http://www.ntsb.go		3	AFR	B737G3			1		-		-	+		-			· .							1					1	-			1			-	1 M	
29/11/2003		http://www.ntsb.go	IDG	3	NA	B737G3					-		-	+		-			1						_			-		_		-	_		-	_	<u> </u>	+	N	DS MI
01/11/2003	N	http://www.ntsb.go	DES	3	NA	B737G3			1		-		-	+	-	-			-1'			-			+	++	-		+			1	-	+ +		_	<u> </u>	+	Hü	DS ML
06/10/2003	i l	http://www.ntsb.go	UNK	3	ASIA	B737G3					-		-	+		-			+							++	-				1	1	-	+ +			<u> </u>	+	1 1	DS ML
04/10/2003	N	http://www.ntsb.go	GRD	3	NA	B737G3	1						1												1												1	1	N	DS ML
16/08/2003	N	http://www.ntsb.go	CRZ	3	NA	B737G3			1																1												<u> </u>	+	U	DS ML
24/05/2003	N	http://www.ntsb.go	LDG	3	NA	B737G3			1					1												1					1				1		1		1 H	DS ML
06/04/2003	Ν	http://www.ntsb.go	CRZ	3	NA	B737G3			1																														U	DS ML
01/02/2003	N	http://www.ntsb.go	LDG	3	NA	B737G3																				1					1		1						1 M	DS ML
16/01/2003	1	http://www.ntsb.go	GRD	3	NA	B737G3	1																																N	DS ML
3/12/2003	U	http://www.ntsb.go	TO	3	AUS	B747G3		IT						ΙT				1 T						ΙĒ		1			ιГ		1	17	1	I T			1		1 H	





		Ac	ccident	ts										Facto	ors											Fa	actors	s (No	on-Teo	chnica	al)							Compet	encies			Vali	idation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition	Windshear	Crosswind	ATC NAV	Loss of comms	Traffic R/W Incursion	Poor Visibility	Upset	Wake Vortex Terrain	Birds	Eng Fail	Fire	Syst mal	Ops/Type Spec	Compliance	Def Manuals	Def-Charts	Def-Chk lists	Def-Proc's Def-Proc's	Fatique	CRM Physio	Workload Distraction Pressure	D.G	LF.F Mis-AFS	Mis A/C State Mis-Svs	Pilot Incap	Communication	Leadership and Teamwork	Workload Management	Problem Solving Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and	Manual Aircraft Control Improved Training	Analyst	Checker
7/2/2002	1	http://www.ntsb.go	CRZ	3	SA	B767														1																					N	SF	DB
4/5/2002	N	http://www.ntsb.go	CLB	3	NA	B767															1							1	1						1						N		-
4/22/2002	N	http://www.ntsb.go	CRZ	3	NA	B767			1																											-	++			1	1 U		-
10/19/2002	1	http://www.ntsb.go	CLB	3	NA	B767												1	1		1															-	+				N	-	
12/8/2002	1	http://www.ntsb.go	CLB	3	AUS	B767													1		1													-		-	+				N	-	
10/21/2002	1	http://www.ntsb.go	TO	3	SA	B767															1															-	+				N		-
8/24/2002	1	http://www.ntsb.go	GRD	3	SA	B767		1													1															-	+				N	-	
4/15/2002	F	http://www.ntsb.go	APR	3	ASIA	B767											1						1						1				1	-	1		++	1	1		1 H		
6/26/2002	N	http://www.ntsb.go	LDG	3	ASIA	B767																		1			1	•	1				1		1		++	1			1 H	-	-
16/06/2002	N	http://www.ntsb.go	LDG	3	NA	DC9-8x																	1						1				1		1		+	1			1 H	Ben	ml
26/03/2002	1	http://www.ntsb.go	APR	3	NA	EMB-145			1									-			1													-		-	+			-	N	DS	ML
3/17/2002	N	http://www.ntsb.go	GRD	3	NA	MD11		1	1 1						1								1					1 1	1				1	-	1	-	++		1		1 N	SF	DB
3/31/2002	N	http://www.ntsb.go	CRZ	3	NA	MD11														1	1															-	++				N	-	-
2/3/2002	1	http://www.ntsb.go	LDG	3	EUR	MD11			1 1		1												-											-		+	+			-		-	
5/31/2002	1	http://www.ntsb.go	GRD	3	NA	MD11												-		1	1		-											-		+	++			-		-	
6/3/2002	N	http://www.ntsb.go	UNK	3	ASIA	MD11															1															+	++				N	-	
6/2/2002	N	http://www.ntsb.go	APR	3	ASIA	MD11															1		-											-		-	++					-	
28/11/2001	1	http://www.ntsb.go	CLB	3	SA	A306						-					-	-			<u> </u>		+											-		+	++			-	+ 10	FV	AAD
12/11/2001	F	http://www.ntsb.go	CLB	3	NA	A306						-			-						+		+				1	•	1				1	+		+-	++	1 1			1 H	EV	MS
30/07/2001	1	http://www.ntsb.go	DG	3	NA	A306													1	1																-	+				N	FV	AAD
18/05/2001	N	http://aviation-safe	CRZ	3	MF	A306													1				+											-		+	++					FV	AAD
08/07/2001	1	http://www.ntsb.go	GRD	3	FUR	A310						-			-		-	-			+		+		-					-			_	+		+	++		-	-	+ 10	MS	AAD
28/12/2001	li	http://www.ntsh.go	DES	3	NA	B737G3									-								-					+ +						-		+	+			-		DS	MI
13/12/2001	li –	http://www.ntsb.go	DES	3	NA	B737G3						-			-		i	-					-					+ +						-		+	+			-		DS	MI
10/10/2001	-li-	http://www.ntsb.go	TO	3	NA	B737G3			-	-		-		-	-		-	-		_	1	-	+		_			+			++		_	-		+	+		-	+		DS	MI
25/08/2001	N	http://www.ntsb.go		3	NA	B737G3			1			-		-	1		-	-		_	· ·	-	1		_				1		$\vdash$		1	+		+	+	1	1		1 H	DS	MI
16/08/2001	1	http://www.ntsb.go	TO	3	NA	B737G3								1				-		-																+	+-				- N	DS	MI
09/08/2001	N	http://www.ntsb.go	CRZ	3	NA	B737G3			1			-		-			-	-		-	+		-						1				_	-	1	<u> </u>	+	1	-	+	+ #	DS	MI
22/07/2001	N	http://www.ntsb.go	IDG	3	AFR	B737G3			-			-		-	-		-	-		_	+	-	+		_				1				1	-	1	<u> </u>	+		-	-	1 M	DS	MI
28/05/2001	N	http://www.ntsb.go	CRZ	3	NA	B737G3			1						-			-					-		-									-		+	++				+ <u>u</u>	DS	MI
09/04/2001	N	http://www.ntsb.go	GRD	3	NA	B737G3		1				-			-			-					-					+ +		<u> </u>				-		+	+			-		DS	MI
25/03/2001	1	http://www.ntsb.go	CRZ	3	ME	B737G3			-	-		-		-	-		-	-		_	1		+		_			+			++		_	-		+	+		-	+		DS	MI
17/03/2001	-li	http://www.ntsb.go	IDG	3	FUR	B737G3			1	-		-		-	-		-	-		_	· ·	-	+		_				-		$\vdash$		1	+		+-	+			-		DS	MI
04/03/2001	-i	http://www.nteb.go		3	NA	B737G3						-		-	-		-	-		-		-	1						1				1	-		+	+	1	1		1 H	00	MI
03/03/2001	F	http://www.ntsb.go	GRD	3		B737G3			-			-		-	-		-	-		1		-	- <u> '</u>		-					-	$\vdash$			+		+-	+-						MI
03/02/2001	N	http://www.ntsb.go	GRD	3	NA	B737G3	1	1	-	-		-		-	-		-	-				_	+		-			+ +		-				+		+	+		-	+			MI
5/21/2001	N	http://www.ntsb.go	CRZ	3	ASIA	B747G3			1						-			-	$\vdash$		+	_	-					+			$\vdash$			-		+	+ +		1	-	$+\frac{1}{10}$		
6/5/2001	1	http://www.ntsb.go		3		B747G3						-		-	-		-				1	-	-											-		+	+					-	
6/5/2001	li –	http://www.ntsb.go	IDG	3	NA	B757			-	-	+	-	+ +		+		-	+	$\vdash$	+	r	-+-	+	++	-	$\vdash$	_	+		<u> </u>	$\vdash$		1	+	++	+	+ +	$\vdash$		+	1 1	+	+
6/28/2001	li –	http://www.ntsb.go	GRD	3	NA	B757			-	-	+	-	+		+		-	+	$\vdash$	+	1		+	++	-	$\vdash$	_	+	-		$\vdash$			+		+	+ +	$\vdash$	-	+		+	+
10/29/2001	N	http://www.ntsb.go	GRD	3	NA	B757				-	+	-	+	-	+		-	-	$\vdash$		<u> </u>	1	-	+		$\vdash$	_		1					+		1	+	1	-	-	+ +	+	+
9/23/2001	N	http://www.ntsb.go	GRD	3	NA	B757	1	1							+		-	-	$\vdash$	+	+	- 1	1			$\vdash$		+ +	1	<u> </u>	$\vdash$		1	+	1	+	4-1		1			+	+
6/5/2001	N	http://www.ntsh.go	CRZ	3	NA	B757			1		+	-	+ +		+		-	+	$\vdash$	+	+	-		++	-	$\vdash$				<u> </u>	++			+		+	+ +				+ 10	+	+
7/11/2001	N	http://www.ntsb.go	CRZ	3	NA	B757			- 1				1 1		+		-	+	$\vdash$	+	+	-	+	++		$\vdash$	_			1		1	1	+	1	+	11		1	1	11 M	+	+

		Ac									Fact	ors												Factor	rs (No	n-Teo	chnica	al)							С	ompr	eten	ncies			Valio	dation			
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear	Crosswind	NAV	Loss of comms	Traffic B/W Incursion	Poor Visibility	Upset	Wake Vortex	Terrain Birds	Eng Fail	MEL	Fire Syst mal	Ops/Type Spec	Cabin	Compriance Def Manuals	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State	Mis-Sys Pilot Incan	Communication	SA	Leadership and Teamwork	Workload Management Problem Solving	Decision Making	Knowledge Annlication of	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
4/9/2001	N	http://www.ntsb.go	GRD	3	NA	B767		1							1													1					1			1		1					1 U		
9/7/2001	N	http://www.ntsb.go	APR	3	SA	B767			1																														_				U		
12/4/2001	1	http://www.ntsb.go	CLB	3	EUR	B767															1																						N		
11/27/2001	1	http://www.ntsb.go	CLB	3	AUS	B767													1		1																		-				N		
3/27/2001	1	http://www.ntsb.go	APR	3	EUR	B767			1												1	1																	-				L		
3/16/2001	N	http://www.ntsb.go	CRZ	3	NA	B767															1																						N		
4/23/2001	1	http://www.ntsb.go	APR	3	EUR	B767															1	1																	_				N		
30/11/2001	N	http://www.ntsb.go	CRZ	3	NA	DC9-8x			1														1																				N	Ben	ml
30/08/2001	N	http://www.ntsb.go	DES	3	NA	EMB-135			1																																		M	ML	JS
12/04/2001	N	http://www.ntsb.go	GRD	3	NA	EMB-135	1 1	1																																			N	ML	JS
16/10/2001	N	http://www.ntsb.go	APR	3	NA	EMB-145																	1	1				1					1				1			1			1 H	DS	ML
25/04/2001	1	http://www.ntsb.go	CRZ	3	NA	EMB-145															1																						N	ML	JS
11/20/2001	U	http://www.ntsb.go	LDG	3	ASIA	MD11																						1					1										1 M		-
20/11/2000	F	http://www.ntsb.go	GRD	3	NA	A306															1		1 1			1	1	1		1			1			1				1			H	EV	AAD
28/03/2000	1	http://www.ntsb.go	APR	3	NA	A306															1 1																		-				N	EV	AAD
12/07/2000	N	http://aviation-safe	APR	3	EUR	A310													1		1		1			1	1	1		1			1			1		1	1	1		1	Н	EV	MS
30/01/2000	F	http://aviation-safe	TO	3	AFR	A310										1							1					1					1			1				1			1 H	EV	AAD
13/11/2000	N	http://www.ntsb.go	DES	3	NA	B737G3			1																																		M	DS	ML
15/09/2000	N	http://www.ntsb.go	GRD	3	NA	B737G3	1 '	1																															-				N	DS	ML
31/07/2000	N	http://www.ntsb.go	DES	3	NA	B737G3								1																			1										1 L	DS	ML
02/07/2000	N	http://www.ntsb.go	GRD	3	NA	B737G3	1 1	1															1					1					1			1			-	1			1 H	DS	ML
20/05/2000	N	http://www.ntsb.go	GRD	3	NA	B737G3																	1																-				N	DS	ML
05/03/2000	N	http://www.ntsb.go	LDG	3	NA	B737G3					1												1					1					1					1		1			1 H	DS	ML
03/03/2000	N	http://ntsb.gov/ntsb	CRZ	3	NA	B737G3			1																														_				U	DS	ML
27/02/2000	N	http://www.ntsb.go	LDG	3	SA	B737G3		1	1						1							-						1		<u> </u>			1					1					1 M	DS	ML
13/01/2000	1	http://www.ntsb.go	GRD	3	EUR	B737G3															1																		-				N	DS	ML
8/6/2000		http://www.ntsb.go	то	3	NA	B747G3					1			1																													U		
12/12/2000	1	http://www.ntsb.go	CRZ	3	NA	B747G3			1		1																																U		-
10/31/2000	F	http://www.ntsb.go	TO	3	ASIA	B747G3	1		1		1				1								1					1		1			1				1	1					1 H		-
11/15/2000	1	http://www.ntsb.go	APR	3	EUR	B757			1											-	1	-																	_				N		-
4/2/2000	N	http://www.ntsb.go	CRZ	3	NA	B757			1																																		U		
8/23/2000	N	http://www.ntsb.go	CRZ	3	NA	B757			1																1																		U		-
1/11/2000	N	http://www.ntsb.go	CRZ	3	NA	B757			1																			1							1				-				L		-
2/12/2000	N	http://www.ntsb.go	LDG	3	SA	B757			1		1				1													1					1					1					1 H		
6/18/2000	1	http://www.ntsb.go	CRZ	3	AFR	B767													1		1									1									_				U	SF	DB
9/20/2000	N	http://www.ntsb.go	DES	3	NA	B767		-	1																									+	1				-+				U		
12/27/2000	N	http://www.ntsb.go	GRD	3	NA	B767	1															1								1					1				$\rightarrow$				N	1	
11/26/2000	N	http://www.ntsb.go	DES	3	NA	B767			1								- 1					1													1				-				Ú	1	
2/22/2000	N	http://www.ntsb.go	LDG	3	AFR	B767			1						-																		1						-				1 H	1	1
6/7/2000	1	http://www.ntsb.go	CRZ	3	NA	B767		-													1	1												+	1				-+				N		
3/30/2000	1	http://www.ntsb.go	CLB	3	NA	B767			1							1	- 1											1		1			1		1	1			-				1 M	1	
11/4/2000	N	http://www.ntsb.go	DES	3	NA	B767			1																														-+				U	1	
5/24/2000	N	http://www.ntsb.go	GRD	3	NA	B767		1				-		-	-																			-					-+				L	1	1
29/11/2000	1	http://www.ntsb.go	CLB	3	NA	DC9-8x			1											-	1	1																	-				N	Ben	ml



		A	ccident	ts									Fact	ors										Factors	s (No	n-Tec	hnica	ul)							Comp	etencie	es			Vali	dation.
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	windsnear Crosswind	ATC	NAV Loss of comms	Traffic D/M Incursion	Poor Visibility	Upset Wake Vortex	Terrain Birds	Eng Fail MEL	Fire	syst mai Ops/Type Spec	Cabin	Compriance Def Manuals	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique	Physio	Workload Distraction Pressure	D.G	Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge Application of Procedures & Knowledge		Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
10/10/2000	1	http://www.ntsb.go	APR	3	NA	DC9-8x									1																								N	Ben	ml
27/12/2000	1	http://www.ntsb.go	TO	3	NA	EMB-135												1	1					1															M	ML	JS
11/25/2000	1	http://www.ntsb.go	CLB	3	NA	MD11												1																					N		_
9/29/2000	1	http://www.ntsb.go	TO	3	ASIA	MD11											1	1																		_			N		
15/07/1999	N	http://www.ntsb.go	LDG	3	NA	A306				1																				1		1			1				<u>1 H</u>	EV	AAD
11/05/1999	1	http://www.ntsb.go	APR	3	NA	A306												1								_							_						U	EV	AAD
24/03/1999	N	http://aviation-safe	LDG	3	ASIA	A306		1	1								1	1		1										1					1	1 1			<u>1 H</u>	EV	AAD
27/12/1999	N	http://www.aaiu.ie/	LDG	3	EUR	A310				1										1					1					1		1	1		$\rightarrow$	1			<u>1 H</u>	EV	AAD
28/06/1999	N	http://www.ntsb.go	LDG	3	ASIA	A310				_																_				1	_					_			1 U	EV	AAD
24/12/1999	1	http://www.ntsb.go	GRD	3	NA	B737G3				_							++	1											_		_		-		$\rightarrow$				N	DS	ML
11/11/1999	-	http://www.ntsb.go	UCLB	3	INA	B/3/G3				_								1								_					_	1 1		+		_				05	IVIL
12/00/1000	I N	http://www.nisb.go	CDD	2		D737G3	1 1			-				-											1							1 1				_				03	IVIL NAL
12/09/1999	N	http://www.ntsb.go		2	IN/A	D737G3				-							1		-									$\vdash$	_				-	+		+				03	
12/09/1999	N	http://www.ntsb.go		2	IN/A	D737G3				-				-	1		-		-		_					-			_		-		-	+		+-				03	MI
02/09/1999	IN N	http://www.nisb.go		2		D737G3			1					_	1											_			_		_		-						<u> </u>	03	IVIL NAL
08/07/1999	IN N	http://www.ntsb.go		3		B/3/G3			1	-				-			++									_			_		_		-							05	MIL
25/06/1999	N	http://www.ntsb.go		2	IN/A	D737G3			1	-				-			++		-		_					-		$\vdash$	_		-		-	+		+-				03	MIL
25/05/1999		http://www.nisb.go		2	ME	B737G3			1	-							+	1		1					1	_	1		_	1	1	1		+		1				03	MI
17/03/1000	N	http://www.ntsb.go		2		B737G3	1							-											· ·		1		_	1					-	<u> </u>				03	MI
0/23/1000		Factual		2		B737G3		1	1	-	1			1		+	++		-			1			1				_	1	1	1	1		$\rightarrow$	+-					IVIL
6/6/1000	N	http://www.ptch.go	CPD	2	NA	B747G3	1			-	1					+	++		-		_				1				_	1		1	1		$\rightarrow$	+			M		-
0/0/1333	N	http://www.ntsb.go		2	NA	D74703				_								1						1					_	1	_				$\rightarrow$	+			1 1	ee.	DP
10/28/1000		http://www.ntsb.go	CP7	2	NA	D757				-				-			++									-			-				-		$\rightarrow$					- 31	-00
2/7/1000	N	Probable Cause		2	NA	D757			1	-						+	++	-								_			_		_		+	+	$\rightarrow$	+					
2/22/1999	N	http://www.ptsb.go		3		B757								-		1			-							_		$\vdash$	_		-		-	+	$\rightarrow$	+	-				-
0/14/1000	N	http://www.ntab.go		2		D757		1	1	-				1		- · ·					_				1		1			1	-	1			1		-		1 1		-
7/24/1999	N	http://aviation=sale	GRD	3	NA	B757	1										++		-	1					1		1		-		-	1				1			- H	-	+
6/2/1999	N	http://www.ntsb.go		3	ΝA	B757				-				-			1		-										-	1	-		+	+	$\rightarrow$	- <u> '</u>			1 M		-
6/9/1999		http://www.ntsb.go	UDG	3	SA	B757				-									-							_				1			-				-		1 1	-	-
9/27/1999	N	http://www.ntsb.go	APR	3	NA	B767			1		1		1	1			++	+ +	-												-		-		$\rightarrow$		-		<u></u>	-	+
10/31/1999	F	http://www.ntsb.go	CRZ	3	NA	B767				-								+	-						1				_	1	-		1				-		1 1	-	-
6/29/1999	li l	http://www.ntsb.go	GRD	3	NA	B767	1			-	1			-				+	-		-				1				_	1	-	1				-	-		1 1	-	-
8/24/1999	li l	http://www.ntsb.go		3	FUR	B767				-				-					-																	-	-		<u> </u>	-	+
11/20/1999	li l	http://www.ntsb.go	APR	3	NA	B767				-							++	1							1						-		-		$\rightarrow$		-				+
1/15/1999	N	http://www.ntab.go		3	FUR	B767				-				-			++				1			1	1				-	1	-	1		+	$\rightarrow$	+			H		-
12/6/1999	1	http://www.nteb.go	TO	3	NA	B767											++	1						· ·												+				-	-
25/06/1999	li -	http://www.ntsb.go	TO	3	NA	DC9-8x			+		1		++				1			+ +					++	_	-	$\vdash$					1	+		+	-			Ben	ml
24/08/1999	i	http://www.ntsb.go	TO	3	NA	EMB-135				-				-				++	1			+			+	-		$\vdash$	-	1			+	+	$\rightarrow$	+-	-+		1	MI	JS
8/23/1999	N	http://www.ntsb.go		3	ASIA	MD11			$\vdash$	-	+						++	++	-1'-			+				-		$\vdash$		1	-		+	+	$\rightarrow$	+	-+		1 M		+
6/30/1999	N	http://www.ntsb.go	APR	3	ASIA	MD11					1	$\vdash$		-			++	1		+ +					++	-		$\vdash$		1			1	+			-		1 1	+	+
10/5/1999	N	http://www.ntsb.go	DG	3	NA	MD11								-								+				-		$\vdash$					+	+	-+	+-	-			+	+
8/8/1999	N	http://www.ntsb.go	IDG	3	ASIA	MD11				-				-						+ +		+				-		$\vdash$	-	1	-		+	+	$\rightarrow$	+	-+		1 M	+	+
4/15/1999	F	http://www.ntsb.go	CLB	3	ASIA	MD11			$\vdash$					+			++	1 1		+		+	$\vdash$					$\vdash$				++	1	+		-	-		U	+	+

		A								Fac	tors										Fa	actor	rs (Non	-Techn	ical)							Compe	tencies			Validatio	bn .			
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear Crosswind	ATC	NAV Loss of comms	Traffic	R/W Incursion Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Svst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Application of Procedures & Knowledge	Flight Management, Guidance and	Manual Aircraft Control Improved Training	Analyst Checker	
9/18/1999	1	http://www.aaiu.ie/	LDG	3	EUR	MD11		1	1	1										1						1				1	1				1	1		1 H		
10/17/1999	N	http://www.ntsb.go	LDG	3	ASIA	MD11														1						1				1						1		1 H		
27/11/1998	1	http://www.ntsb.go	UNK	3	ASIA	A306													1																			U	EV AAD	Б
28/09/1998	1	http://www.ntsb.go	TO	3	EUR	A306																																U	EV AAD	Ъ
09/07/1998	1	http://www.ntsb.go	CLB	3	NA	A306											1		1			1				1	1							1		1		Н	EV AAD	5
20/04/1998	1	http://www.ntsb.go	CRZ	3	OTH	A306													1																			N	EV AAD	б
16/02/1998	F	http://aviation-safe	GA	3	ASIA	A306								1	1						1					1				1			1				1	1 H	EV AAD	Б
11/12/1998	F	http://aviation-safe	APR	3	ASIA	A310			1					1																								U	EV AAD	5
13/12/1998	N	http://www.ntsb.go	CRZ	3	NA	B737G3			1																													N	DS ML	
06/11/1998	1	http://www.ntsb.go	LDG	3	NA	B737G3													1																			N	DS ML	
16/09/1998	N	http://www.ntsb.go	LDG	3	NA	B737G3		1	1	1				1												1				1					1			1 L	DS ML	
14/08/1998	N	http://www.ntsb.go	LDG	3	NA	B737G3																				1				1						1		1 H	DS ML	
07/08/1998	1	http://www.ntsb.go	CLB	3	NA	B737G3									1																							N	DS ML	
07/07/1998	1	http://www.ntsb.go	APR	3	NA	B737G3													1		EL	JŔ																N	DS ML	
02/07/1998	1	http://www.ntsb.go	CRZ	3	SA	B737G3													1																			N	DS ML	
27/06/1998	1	http://www.ntsb.go	LDG	3	EUR	B737G3													1																			N	DS ML	
20/06/1998	1	http://www.ntsb.go	UNK	3	EUR	B737G3													1																			N	DS ML	
17/06/1998	N	http://www.ntsb.go	GRD	3	NA	B737G3	1 1	1													1					1					1					1		L	DS ML	
11/11/1998	N	http://www.ntsb.go	GRD	3	NA	B747G3	1	1 1	1																					1								1 M	SF DB	
7/31/1998	1	http://www.ntsb.go	UNK	3	EUR	B747G3											1		1 1																			U		
11/30/1998	N	http://www.ntsb.go	GRD	3	NA	B747G3	1 1	1																		1						1						M		
11/28/1998	1	http://www.ntsb.go	CRZ	3	EUR	B747G3													1 1																			U		
8/5/1998	N	http://www.ntsb.go	LDG	3	ASIA	B747G3		1	1					1												1				1					1			1 M		
3/17/1998	1	http://www.ntsb.go	UNK	3	SA	B757															1																	N		
2/17/1998	1	http://www.ntsb.go	GRD	3	EUR	B757	1	1											1																			N		
9/20/1998	N	http://www.ntsb.go	LDG	3	SA	B757																								1			_	+				1 M		
6/22/1998	1	http://www.ntsb.go	CRZ	3	EUR	B757													1 1																			N		
1/6/1998	N	http://www.ntsb.go	CRZ	3	NA	B757			1																													U		
1/1/1998	N	http://www.aaib.go	LDG	3	NA	B757			1					1							1					1	1 1			1			1		1			1 M		
11/29/1998	1	http://www.ntsb.go	LDG	3	NA	B757					1		1	1																								U		
5/24/1998	N	http://www.ntsb.go	CRZ	3	NA	B757			1																													U		
5/12/1998	N	http://www.ntsb.go	TO	3	AFR	B767							1 1	1																								U		
9/11/1998	N	http://www.ntsb.go	LDG	3	NA	B767		1	1	1				1									1			1				1			_		1	1		1 H		
4/4/1998	1	http://www.ntsb.go	CRZ	3	EUR	B767													1 1																			N		
11/25/1998	N	http://www.ntsb.go	CRZ	3	NA	B767																							1									N		
1/9/1998	N	http://www.ntsb.go	CLB	3	EUR	B767													1 1																			N		
7/22/1998	N	http://www.ntsb.go	CLB	3	NA	B767			1												1													+				U	1	
10/4/1998	N	http://www.ntsb.go	APR	3	SA	B767			1																					1								U	1	
9/12/1998	1	http://www.ntsb.go	TO	3	ASIA	B767															1									1			_					1 M		
29/07/1998	N	http://www.ntsb.go	TO	3	NA	EMB-135														1										1								1 L	ML JS	
28/12/1998	N	http://www.ntsb.go	LDG	3	SA	EMB-145																								1		1						1 U	ML JS	
11/02/1998	N	http://www.ntsb.go	TO	3	NA	EMB-145										1					1					1				1						1		1 H	MS ML	
11/8/1998	1	http://www.ntsb.go	GRD	3	NA	MD11													1																			U		
10/21/1998	1	http://www.ntsb.go	TO	3	NA	MD11													1																			l lu		_



		A	ccident	ts									Fac	ctors										Fa	actors	s (Non	-Techr	nical)						C	Compet	encies			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear	Crosswind ATC	NAV Loss of comms	Traffic	R/W Incursion Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Svst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	مح Leadership and Teamwork	Workload Management	Problem Solving Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
6/14/1998	N	http://www.ntsb.ac	LDG	3	SA	MD11		1																						1						1		1 M	
9/2/1998	F	http://www.ntsb.go	CRZ	3	NA	MD11													1 1							1							+ +	1		1		M	
7/5/1998		http://www.ntsb.go	OTO	3	EUR	MD11													1														+ +					N	
11/11/1998	N	http://www.ntsb.go	LDG	3	NA	MD11		-																	_	1			1 1	1		1		-+		1	1	1 H	
12/25/1998		http://www.ntsb.go	LDG	3	ASIA	MD11		_																						1			+ +	-+		-		1 U	
9/10/1998		http://www.ntsb.go	LDG	3	ASIA	MD11													1														+			1		N	1
10/8/1998	1	http://www.ntsb.go	CRZ	3	EUR	MD11													1														+ +	-+		+		N	
11/27/1998		http://www.ntsb.go	CLB	3	Asia	MD11					_								1						_								+-+	-+		+		U	
26/09/1997	N	http://www.ntsb.gc	DES	3	NA	A306			1											-													++	$\vdash$		+		N	EV AAD
30/06/1997	1	http://www.ntsb.gc	TO	3	ASIA	A306																	1										++	$\vdash$		+		l lu	EV AAD
12/05/1997	N	http://www.ntsb.gc	DES	3	NA	A306			1		_			1	1				-	-	1				_	1		-	1	1		1				+	1	1 H	EV AAD
07/01/1997	N	http://www.ntsb.gc	DICRZ	3	NA	A306		-	1		_									-	1				-				-		-		+ +	-+	-+	+		N	EV AAD
25/12/1997	1	http://www.ntsb.gc	GRD	3	NA	B737G3			-										1		. 1					1							+ +	1		1		M	DS MI
27/09/1997	i	http://www.ntsb.gc	TO	3	NA	B737G3					_					+ +			. 1						_						-		++		_	+			DS MI
21/08/1997	i	http://www.ntsb.gc	DES	3	NA	B737G3		-		+	_					1			-						_			-			-		+-+		-+	+		N	DS MI
20/06/1997	i	http://www.nteb.go	APR	3	ΝΔ	B737G3				+									1	-			_		_						-		++	$\vdash$	-+	+			DS ML
08/06/1997	N	http://www.ntsb.gc		3	NΔ	B737G3							1			+ +															-		++	$\vdash$	-+	+			DS MI
11/05/1997	1	http://www.ntsb.gc	APR	3	NΔ	B737G3		-	-	+	1					+ +	-	+ +	-	-	1		-		_	1					-	1	+	+	-+	1		H	DS MI
08/05/1997	F	http://www.ntsb.gc	APR	3	ASIA	B737G3		1	1					_		+ +			1 1				_		_			-		1	-			$\vdash$	-+	+ <del>`</del>		1 H	DS MI
18/04/1997	N	http://www.nteb.go		3	NA	B737G3			· ·		1		1								1				-	1			1				1		-+	+	1		DS ML
16/04/1997	1	http://www.ntsb.gc	APR	3	NΔ	B737G3		-	-	+							-		1 1							- ·					-		+	+	-+	+		N	DS MI
18/01/1997	N	http://www.ntsb.gc		3	SA	B737G3			-	+	_					-	-		1				-		_	+		-		-	-	-	+	+	-+	+			DS MI
4/12/1997	N	http://www.ntob.go		2	NA	B747C2																	_		-						-		++	$\vdash$	-+	+			
9/14/1997	N	http://www.ntsb.gc		2	NA	B747G3			1										-	-			-		-								++	$\vdash$	-+	+			51 00
5/14/1997	N	http://www.ntsb.gc	GRD	3	FUR	B747G3		1			_					+ +	-	+ +	-	-	1		-		_	+					-	-	++	+	-+	+			
12/24/1997	N	http://www.ntsb.gc		3	FUR	B757			-	+	_					+ +	-		1				-		_	+				-	-		+	$\vdash$	-+	+		Hŭ	SE DB
1/31/1007	1	http://www.ntob.go		2	NA	D757		-			_						1		1						-						-		+ +	$\vdash$		+			01 00
3/2/1007	N	http://www.ntsb.gc		2		D757			1							+ +	-						_	+ +	_	+					-		++	$\vdash$	-+	+			
3/1/1997	1	http://www.ntsb.gc	GRD	3	NΔ	B757		1			1					-	-		-	-	1		-		_	1		-		1	-	1	+	1	-+	+		1 M	
7/10/1997	i i	http://www.ntob.go		2	NA	D757			1							+ +	-		-	-			1		-	1					-		++	H I		+			
8/2/1007	- -	http://www.ntsb.gc		2		D757										+ +			-	-					-								++	H-H-		+			
10/16/1997	1	http://www.ntsb.gc		2	NA	D757				+	_			_		+ +	-	+ +	1				_	+ +	_	+					-	-	++	$\vdash$	-+	+			
6/3/1997	N	http://www.ntsb.gc		3	SA SA	B767		-	1		_					+	-						_		_			-			-		++	$\vdash$	-+	+			SE DB
3/27/1007	1	http://www.ntob.go		2	NA	D767		-									-		1						-						-		+ +	++		+			01 00
5/22/1007	N	http://www.ntsb.gc		2	NA	D/0/ D767		-	1	1	1 1					+ +	-		- 1				1			1		_		1	_	1	+		<u> </u>	+			
3/22/1997	IN N	http://www.nisb.gc		2	IN/A	D/0/		_	1	<u> </u>	1 1		-			-	_	+ +	-	-					_					1	_			<b>⊢</b> ₽'		+	-		
2/23/1997	IN N	http://www.nisb.gc		2	IN/A			-	1								_			-					_	1		_			_	1	+	$\vdash$		+	-		ml do
25/00/1007	IN	http://www.htsb.gc		3	NA			1	1							+		+	_	-		+		+						+			+	$\vdash$		+	-		mi de
01/00/1007	N	http://www.nisb.go	NLDG	3	NA	DC0 8v	$\vdash$	- 1	-	+	_			$\vdash$		+	-	+	4	1		+		+ +	+	+	++		++	+	-	+	+	$\vdash$	-+	+	-		mi us
14/03/1997	N	http://www.nisb.go		3	NA	DC0 8v	$\vdash$	-	1		_			1		+	1		-	-	1		_	+ $+$		+	+		+	+	_	+	+	$\vdash$	-+	+			mi us
05/02/1007	IN N	http://www.nisb.go		3	N/A	DC0-0X			1		1					+	- 1		_			1		+ $+$	_				-		_	+	+	⊢+-	$ \rightarrow $				mi us
6/01/1997	N	http://www.htsb.gc		3		DC9-0X		1	-		1		-			+			-	-	1	1	_	+	+				1	1	_		+	H	<u> </u>	-			iiii as
10/24/1007		http://www.htsb.go	LDG	3	INA SA	MD11		-	-	+		-			-	++	-	+	-	-				+ +	+			-		1	-	+	+	⊢ <del>I</del> '		+		1 H	
6/8/1007	N	http://www.msb.gc		3	- SM	MD11	$\vdash$	-	1		1			$\vdash$		+		+				1		+ $+$	4	1			-	1		+	+	⊢+-	-+	+	1	1 1/1	
0.0/100/	IN	mup.//www.mill.go.	.IDEO	10	NOM	ווטאון		1		11			1		1 1	1 1	1	1	1	1		11		1 1		1 11	I I .						1 1	4 IV	- 117	4	11	11 IT	4





		A	ccident	ts								Fa	actors	5											Facto	ors (N	lon-T	echnic	al)							Comp	beter	ncies			Vali	dation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility Inset	Wake Vortex	Terrain	Birds Eng Fail	MEL	r ire Syst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data	Def-Chk lists	Def-DBs	Def-Proc's Fatique	CRM	Pnysio Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA Leadership and	Teamwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
13/04/1995	Ν	http://www.ntsb.go	LDG	3	NA	B737G3			1												1						1				1			1			1	1		1 M	DS	ML
23/01/1995	1	http://www.ntsb.go	TO	3	NA	B737G3											_		1																		$\square$			N	DS	ML
01/01/1995	1	http://www.ntsb.gc	DES	3	NA	B737G3					_			_	1																	$\rightarrow$		$\rightarrow$	_		$\vdash$			L	DS	ML
10/17/1995	N	http://www.ntsb.go	CRZ	3	OTH	B747G3																	_									_		_	_		$\vdash$			U		_
12/20/1995	F	http://www.ntsb.gc	DES	3	SA	B/5/			_		_			1		1	_				1			_	1		1	1		1	1			1		1	++		1	1 H		_
8/4/1995	N	http://www.ntsb.go		3	NA NA	B/5/		_			-			_		+	_		_		1		_	_			4	_			4	+		—	_		++					-
4/11/1995	IN N	http://www.ntsb.go		3	INA NA	B/3/			_		-		1	_		+	_		_		1		_	_			1	_	+		1	-		+	$\rightarrow$	<u> </u>		1		1 IVI		-
6/20/1995	N	http://www.ntsb.go		3	INA	B/0/	4				-		1	_			_			-				_				_				—		+	_	<u> </u>	++			0		-
3/19/1995	!	http://www.ntsb.go		3	INA NA	B/0/	1		_	1			+ +	_	_	+			_				_	_				_				-			-+		$\vdash$			U		-
4/2/1005	I N	http://www.ntsb.gc	CPD	2	NA	MD11		-	_		-		-	-	_	+	_	1		-			-	_	+ +			_				+		+	+	+	$\mapsto$			IN N	+	-
10/08/1994	N	http://www.msb.gc		3		A306					+		+ +	-		+	_	1			1		-	_			1	-	+ +		1	+		+	+	1	<del>ا ا</del>	1		1 H	FV	
26/04/1994	F	http://aviation-safe	APR	3		A306					-		+ +	1			-			1	1	1	-	-	1	1	1	-	+ +	1	1	+				1	1		1	1 H	AB	
28/01/1994	N	http://www.ntsb.ac	CRZ	3	NA	A306		-			-		+ +			+	-		+			·	-	-				_	+		<u> </u>	-		-	+	+	<u>+</u> +		•	. N	AB	AAD
24/09/1994	N	http://aviation-safe	APR	3	FUR	A310					+		+ +	1		+	-		+	1	1		-				1	-		1	1	-		1	-	+	1		1	1 H	FV	MS
23/03/1994	F	http://aviation-safe	CR7	3	ASIA	A310					+			1					-		1						1		+ +	1	1	+		1		+	1		1	1 N	FV	MS
29/12/1994	F	http://www.ntsb.ac	APR	3	ME	B737G3								1		1					1						1				1	-		1	_			1		M	DS	ML
11/12/1994	N	http://www.ntsb.go	CLB	3	NA	B737G3					-								1													-			_	+				N	DS	ML
19/09/1994	N	http://www.ntsb.go	DES	3	ОТН	B737G3		1			-																					_		-	_	+	$\square$			L	DS	ML
08/09/1994	F	http://www.ntsb.gc	APR	3	NA	B737G3								1					1	1															_					N	DS	ML
01/07/1994	1	http://www.ntsb.go	APR	3	NA	B737G3				1		1																				-		_	_					L	DS	ML
2/12/1994	Ν	http://www.ntsb.go	CRZ	3	ОТН	B747G3		1	1																							-								U		
8/19/1994	Ν	http://www.ntsb.go	GRD	3	NA	B757	1																											_						N		
11/6/1994	Ν	http://www.ntsb.go	GRD	3	NA	B757	1														1						1				1					1				1 M		
11/25/1994	Ν	http://www.ntsb.gc	LDG	3	NA	B757																					1				1					1				1 H		
6/29/1994	Ν	http://www.ntsb.go	CRZ	3	NA	B767			1																		1							1		1				M		
1/1/1994	1	http://www.ntsb.go	GRD	3	NA	B767	1														1																			N		
22/11/1994	F	http://www.ntsb.go	TO	3	NA	DC9-8x							1	1																										N	ml	ds
11/4/1994	Ν	http://www.ntsb.gc	LDG	3	NA	MD11														1							1				1	$ \rightarrow $		1			1 1	1		1 H	SF	DB
9/28/1994	1	http://www.ntsb.gc	APR	3	NA	MD11					_								1				_									+		_	_		$\vdash$			N	SF	DB
6/29/1994	N	http://www.ntsb.go	CRZ	3	SA	MD11					_												_	_			1	_	+		1	_	1	1			$\vdash$			1 M		_
8/19/1994	N	http://www.ntsb.go	LDG	3	NA	MD11			_		-			_	_	+			-	1			_	_				_		_	1	+	-	$\rightarrow$	_		++			1 H		_
10/13/1994	!	http://www.ntsb.gc	UCLB	3	INA	MDTT			_		-						_		1				_	_				_							_	+	$\vdash$			N	-	
08/12/1993	1	http://www.ntsb.go	LDG	3	NA NA	B737G3			_		-			1		+			_	-	1		_	_			1	_				+		—	_	1	<b>⊢</b> ₽	1		H	DS	ML
21/09/1993	1	http://www.ntSb.gc		3	NA NA	B737G3	$\vdash$	+	_	+	+	$\vdash$	+	-	-	+	+	+	1			+	_	+	+		<u> </u>		+	_	+	+	+	+	+	+'	++				100	MI
23/04/1002	l l	http://www.msb.go	APR	2	NA	B737G3					+	$\vdash$	+		1		_	+	-			+		_	+		1	-	+		+	+	+	+	+	1	┢╋	1			00	MI
23/04/1993	N	http://www.niSD.gc	CLB	3	NA	B757				+ +	1		+		1			+	-	-		+		_	+		1	_	+		+	+	+	1	-	1	┢╋				-00	IVIL
6/24/1993	N	http://www.htsb.gc	IDES	3	NA	B757		-		+ +	+		+	-		+	+		+	-		+	-	+	+				+		+ +	+		+-	_	+	++	$\rightarrow$		N	+	+
8/2/1993	N	http://www.ntsb.gc	UDG	3	NA	B757		+ +			+		+	-	-	+	-		-				-	-			1		+		1	+		1	-	+	++	$\rightarrow$		1 H	+	+
10/4/1993	1	http://www.ntsb.gc	TO	3	NA	B757					1		+			+	-		-	-	1			-			1		+		1	+	1 1	- <u> </u> -	-	+	H.	1		1 H	+	+
2/23/1993	N	http://www.ntsb.gc	DG	3	NA	B757					+		+				1		1		l l'		-	-	1			-	+		1	+	1	+	+	+	H P			1 H	+	+
2/13/1993		http://www.ntsb.go	CRZ	3	NA	B757					+		+ +	-			-		1				-	-	1			-	++		1	+	1	+	+	+	++			N	+	+
4/7/1993	1	http://www.ntsb.go	CRZ	3	NA	B757		1	1		1								1												1	-	1	+	-	1	++			1 L	1	1





		A	ccident	ts								E.	actors											Facto	ors (No	n-Tec	hnica	al)						(	Comp	etencies			Vali	dation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility Upset	Wake Vortex	Birds	Eng Fail MFL	Fire	Syst mal Ops/Type Spec	Cabin Cabin	Def Manuals	Def-Ops data	Def-Chk lists	Def-DBs	Def-Proc's Fatique	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State Mis-Svs	Pilot Incap	Communication SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
5/4/1991	Ν	http://www.ntsb.go	CRZ	3	NA	B767		1	1																1					1				1	1	1		M		
27/12/1991	Ν	http://www.ntsb.go	TO	3	EUR	DC9-8x		1	1								1		1		1			1	1				1			1			1	1	1	н	ml	MS
23/12/1991	1	http://www.ntsb.go	TO	3	NA	DC9-8x				1			1								_				1							1 1						L	ml	ds
23/09/1991	N	http://www.ntsb.go	GRD	3	NA	DC9-8x	1 1							_							_				1							1		1	1	_		M	ml	ds
12/08/1990	N	http://www.ntsb.go	UNK	3	EUR	A310			_							_					_																	U	MS	AAD
21/08/1990	1	http://www.ntsb.go	APR	3	NA NA	B/3/G3										_			1		_	+	_									_				_		N	DS	ML
09/08/1990	N	http://www.ntsb.go		3	NA	B737G3		_						_	_	_	4	-	-		_		_									_				<u> </u>		M	DS	ML
17/03/1990	I NI	http://www.ntsb.go		3	INA	B/3/G3			_					_		_	1	1	1		_									4		4				-		IN III	DS	NIL
16/03/1990	IN	http://www.ntsb.go		3	INA	B/3/G3		1 /	_				+ +	_		_			_	1			_		1					1		1				1		1 H	DS	IVIL
2/14/1990		http://www.nisb.go		2	NA	B737G3					-	_		_		-			1		_		-								-	-	-						03	IVIL
1/16/1990	N	http://www.ntsb.go		3		B74703			-		-			_		-				1	-		-		1					1	-	1	1					1 M	-	-
12/07/1989	E	http://www.ntob.go		2	NA	A306	1							-						-													P					I IVI	۸D	
15/05/1989	1	http://www.ntsb.go	DES	3	NΔ	A310				1		1		_		-			-		-										-								EV	
07/01/1989	i i	http://www.ntsb.go	UNK	3	FUR	A310			-					_		-			-		_		-							-	+	-						- U	MS	AAD
27/10/1989	i l	http://www.ntsb.go	CLB	3	NA	B737G3												1	1											-		_							DS	MI
20/09/1989	F	http://www.ntsb.go	TO	3	NA	B737G3														1					1					1				1	1	1		1 H	DS	MI
02/08/1989	i l	http://www.ntsb.go	APR	3	NA	B737G3		+ +	-							-			-	1					-						-	-	-						DS	MI
17/03/1989	N	http://www.ntsb.go	GRD	3	NA	B737G3													1	-											-							N	DS	ML
12/15/1989	N	http://www.ntsb.go	DES	3	NA	B747G3		-											1	1		1	1		1											1 1		м	SF	DB
1/19/1989	1	http://www.ntsb.go	CLB	3	NA	B757													1	-			-										-			-		N		
9/13/1989	1	http://www.ntsb.go	LDG	3	NA	B757																								1	-		-			-		1 H		-
11/6/1989	N	http://www.ntsb.go	GRD	3	NA	B757	1																													-		N		-
10/9/1989	1	http://www.ntsb.go	DES	3	NA	B757													1																			N		
12/21/1989	N	http://www.ntsb.go	LDG	3	NA	B757																			1					1			1					1 H		
9/5/1989	1	http://www.ntsb.go	CRZ	3	NA	B767		1		1			1												1					1		1 1						M		-
4/3/1989	N	http://www.ntsb.go	GRD	3	NA	B767														1																		Н		
11/12/1989	1	http://www.ntsb.go	GRD	3	NA	DC9-8x		1												1					1					1		1						1 M	ml	ds
02/05/1989	1	http://www.ntsb.go	CRZ	3	NA	DC9-8x													1																			N	ml	ds
01/03/1989	1	http://www.ntsb.go	APR	3	NA	DC9-8x				1		1													1							1 1						N	ml	ds
27/11/1988	1	http://www.ntsb.go	CLB	3	NA	A306											1	1	1																			U	AB	AAD
24/10/1988	I	http://www.ntsb.go	TO	3	NA	A306											1	1	1																			U	AB	AAD
30/08/1988	I	http://www.ntsb.go	CRZ	3	NA	B737G3		1	1											1					1							1				1		M	DS	ML
26/07/1988	1	http://www.ntsb.go	DES	3	NA	B737G3		1									1			1					1									1	1	1		M	DS	ML
24/05/1988	1	http://www.ntsb.go	DES	3	NA	B737G3		1	1								1								1									1	1	1		U	DS	ML
18/03/1988	1	http://www.ntsb.go	CLB	3	NA	B737G3				1		1																										N	DS	ML
10/03/1988	1	http://www.ntsb.go	CRZ	3	NA	B737G3				1		1																										U	DS	ML
9/29/1988	N	Factual	UNK	3	SA	B757																														_		U	SF	DB
3/22/1988	1	Probable Cause	UNK	3	NA	B757																									1							N		
4/16/1988	N	http://www.ntsb.go	UNK	3	SA	B757																											1			_		U	1	
1/25/1988	N	Probable Cause	UNK	3	NA	B767												+							$\rightarrow$							_						U		$\perp$
8/26/1988	N	Probable Cause	UNK	3	NA	B767							1							1					$\rightarrow$					_		_	-			<u> </u>		M	-	
1/19/1988	N	Probable Cause	UNK	3	NA	B/67								_						1		+											-					M	-	+
3/24/1988		Probable Cause	JUNK	3	INA	B767		1 1										1			1								1				1				1	I U	1	1





		Ac									Facto	ors											Fac	ctors	(No	n-Tec	hnica	al)							Co	ompete	encies			Validation	n.			
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition	Adverse weatner/Ice Windshear	Crosswind	ATC NAV	Loss of comms	Traffic R/W Incursion	Poor Visibility	Upset	Wake Vortex Terrain	Birds	Eng Fail	MEL Fire	Syst mal	Ups/ Iype Spec Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts	Def-Chk lists Def-DBs	Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State	mis-sys Pilot Incap	Communication	SA Leadership and	Teamwork	Workload Management Problem Solving	Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker	
14/06/2010	1	http://www.ntsb.go	GRD	2	NA	DC9													1																							N	ml MS	
29/04/2009	F	http://www.ntsb.go	CRZ	2	AFR	B7312											1																									U	SD	
27/04/2009	Ν	http://www.ntsb.go	LDG	2	NA	B7312		1													1																					N	SD	
17/12/2009	I	http://www.ntsb.go	CLB	2	ASIA	B747G2													1		1																_					U		
5/6/2009	Ν	http://www.ntsb.go	LDG	2	NA	DC10																						1 1					1			1				1		1 H	SF rs	
3/26/2009	1	http://www.ntsb.go	CLB	2	SA	DC10													1		1																					N	SF rs	
24/08/2008	F	http://www.ntsb.go	CLB	2	ASIA	B7312											1				1																					U	SD	
23/08/2008	F	http://ntsb.gov/ntst	APR	2	SA	B7312			1								1																									U	SD	
14/07/2008	1	http://www.ntsb.go	LDG	2	AFR	B7312		1	1																																	U	SD	
06/06/2008	1	http://www.ntsb.go	TO	2	SA	B7312															1																					N	SD	
22/05/2008	Ν	http://www.ntsb.go	CLB	2	NA	B7312													1	1																						N	SD	
03/03/2008	1	http://www.ntsb.go	TO	2	SA	B7312		1											1																		_					Н	SD	
10/02/2008	1	http://www.ntsb.go	TO	2	SA	B7312		1											1																							N	SD	
30/01/2008	F	http://www.ntsb.go	APR	2	SA	B7312											1																									U	SD	
08/01/2008	1	http://www.ntsb.go	GRD	2	NA	B7312		1													1																_					N	SD	
26/08/2008	1	http://www.ntsb.go	TO	2	SA	B747G2													1		1																_					N		
07/07/2008	F	http://www.ntsb.go	TO	2	SA	B747G2											1		1	1	1									1							_					U		
27/10/2008	1	http://www.ntsb.go	TO	2	EUR	B747G2																	1					1				1	1				_	1		1		1 M		
25/05/2008	N	http://www.ntsb.go	TO	2	EUR	B747G2												1	1		1							1				1				1	_			1	1	н		-
19/04/2008		http://www.ntsb.go	CLB	2	NA	B747G2													1	1	1																					N		_
23/12/2008	N	http://www.ntsb.go	GRD	2	NA	B747G2		1																													_					L		_
5/19/2008	N	http://www.ntsb.go	CRZ	2	UNK	DC10			1									-		_		_			+ +															<u> </u>		N	SF rs	-
03/12/2008	N	http://www.ntsb.go	GRD	2	NA	DC9		1	1													_			+ +																	N	ml MS	-
06/07/2008	F	http://www.ntsb.go	APR	2	NA	DC9																																				U	Ben ml	-
15/04/2008	F	http://aviation-safe	TO	2	AFR	DC9								_			-	-	1	_	+	_												-		-	-			+	-	M	Ben ml	-
12/02/2008	ti -	http://aviation-safe	GRD	2	SA	DC9		1		-	-	-		_	-		-	-		_	1	_			+ +	-		-	-					-		-	+	-		<u>+</u>		N	Ben ml	-
28/01/2008	li l	http://aviation-safe	GRD	2	NA		1			-		-		-	-		-	-		-		_				-		-						-	+ +	-	$\rightarrow$	-	-	+		N	Ben ml	-
23/03/2007	N	http://aviation-safe		2	ME	A300				-	-	-		-	-		-	-		_	+	_			+	-	+ +	-					1	-		-	+	-	-	<u> </u>		1 1	EV AAD	5
10/02/2007	i i	http://www.ntsb.go	CLB	2	ASIA	A300	_			-	-	-		_	-		-	-	1	_	1	_			+ +	-		-	-					+		-	+	-	-	+		. 0	EV AAD	÷
07/11/2007	N	http://www.nteb.go	CLB	2	AFR	B7312				-	-	-			-		-	-	1	-		_			+ +			-						-		-	+	-		<u>+</u>		N		-
14/09/2007	N	http://www.ntsb.go	IDG	2	NA	B7312		1		-		-			-		-	-		-	1	_					+ +	-						-		-	-+	-		<u> </u>			SD	-
10/07/2007	F	http://www.ntsb.go	GRD	2	NA	B7312	1					-		_	-		-	+		_		_			+ +	-		-						-		-	+	-		<u>+</u>		N	SD	-
28/06/2007	F	http://www.ntsb.go		2	AFR	B7312					-			-	-		1		+	_	+	_			+ +	-	+ +	-						-		1	-+	-				1 H	SD	-
16/12/2007	li l	http://www.nteb.go	GRD	2	AFR	B747G2		1		-		-		-	-					-		_				-		1						-		1	$\rightarrow$	-	-	+		. M	00	-
19/04/2007	li l	http://www.ntsb.go		2		B747G2						-			-		-	-		1		_			+		+ +										$\rightarrow$	-		<u> </u>	-	N		-
10/02/2007	li -	http://www.ntsb.go		2		B747G2				-	-	-		-	-		-	-	1		1	_			+ +			-						-		-	-+	-	-	+	-		<b></b>	-
21/03/2007	li l	http://www.ntsb.go	CLB	2		B747G2				-			+		+		-								+		+	-			+			-	+		+			<u>+</u>	-		<b>I</b> → →	-
6/25/2007	N	http://www.ntsb.go	IDES	2	NA	DC10	-			-		-	+		+		1		<b>'</b>		r				+		+	1			+		1	-	+		+			<u> </u>		1 4	SF rc	-
5/2/2007		http://www.ntsb.go	DES	2	NA	DC10	-		$\vdash$	+	+	-	+		+	+	-		++				+		++	-	++	-		-	+	_		+	+	-	+			<u>+</u>	+	- 11 N	SF IC	-
18/05/2007	N	http://www.ntsb.go	CLB	2	NA		1		$\vdash$	-	+	-	+		+	+	-	-	++			-			+		+				+	_		-	+		+		_	+		N	Ben ml	_
01/05/2006	-	http://www.ntsb.go	ADD	2	NA	A 300	Ľ			-	-			_	-		-	-		_	1	_			+	-	+	-							+	-	-		_	<u> </u>		N		<u> </u>
30/10/2006	-	http://www.ntsb.go		2	NA	P7212				+	-	1		_	-		-	-			-	_	-		+	-	+	_	-						1	1	$\rightarrow$		_	+				-
29/10/2006	F	http://www.ntsb.go	CLB	2	AFR	B7312			$\vdash$	-	+		+		+	+	1		++	1	$\vdash$				+	-	+	-+	+	-	+	_		+	-	-	+			<u>+</u>				_
12/06/2006	-	http://www.ntsb.go		2		B7312				+	-	-			-			1		-	$\vdash$	_	-		+		+	-	+		+			-	+	-	$\rightarrow$		_	<u> </u>			50	_
	12	mup.//www.msb.go	0.0	14	TUT IV	01012		1					- I		1	1				- 1				1 I					1		1 I.	1	. I.						1	1	1	1 D N	. 30	





		A	ccident	ts										Facto	rs											Fac	ctors	(Noi	1-Tec	hnica	1)							Compet	encies			Validation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	kunway/Iaxi condition Adverse Weather/Ice	Windshear	Crosswind	ALC NAV	Loss of comms	Iraffic R/W Incursion	Poor Visibility	Upset Make Marter	Terrain	Birds	Eng Fail MFI	Fire	Syst mal	Ops/Type Spec Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts	Def-Chk lists Def-DBs	Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State Mis-Svs	Pilot Incap	Communication SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
10/2/2003	1	http://www.ntsb.go	CRZ	2	EUR	B747G2														1	1																				N	
2/13/2003	1	http://www.ntsb.go	CRZ	2	ASIA	B747G2													1		1																				U	
7/6/2003	N	http://www.ntsb.go	LDG	2	SA	DC10		1																									1				$\square$				1 M	SF rs
12/10/2003	1	http://www.ntsb.go	TO	2	NA	DC10															1																$\square$				N	SF rs
18/12/2003	F	http://aviation-safe	DES	2	SA	DC9																																			U	Ben ml
12/09/2003	F	http://www.ntsb.go	GRD	2	NA	DC9	1																																		N	Ben ml
18/04/2003	N	http://aviation-safe	CLB	2	AFR	DC9															1																$\square$				U	Ben ml
17/02/2002	N	http://www.ntsb.go	UNK	2	SA	B7312															1																$\square$				N	ML
11/02/2002	N	http://www.ntsb.go	CRZ	2	SA	B7312			1																												$\square$				U	ML
1/3/2002	1	http://www.ntsb.go	LDG	2	NA	B747G2															1																				U	
8/11/2002	N	http://www.ntsb.go	CLB	2	NA	B747G2													1	1	1															+	+		-		N	
5/25/2002	F	http://www.ntsb.go	CRZ	2	ASIA	B747G2															1		1													1	+		-		U	
6/13/2002	1	http://www.ntsb.go	LDG	2	EUR	B747G2													1		1																				U	
8/10/2002	1	http://www.ntsb.go	APR	2	NA	DC10															1															1	+				N	SF rs
4/27/2002	N	http://www.ntsb.go	TO	2	SA	DC10		1													1												1			+	+		-		1 M	SF rs
3/22/2002	N	http://www.ntsb.go	CRZ	2	отн	DC10			1																			1					1	-		1			1		1 H	SF rs
31/10/2002	N	http://www.ntsb.go	LDG	2	NA	DC9		1	1						1																		1								1 M	Ben ml
22/09/2002	N	http://www.ntsb.go	GRD	2	NA	DC9		1													1															+	+		-		N	Ben ml
14/06/2002	N	http://aviation-safe	LDG	2	SA	DC9											1						1					1						-	1		+		1		M	Ben ml
03/06/2002	N	http://www.ntsb.go	LDG	2	NA	DC9															1																+				N	Ben ml
24/01/2002	N	http://www.ntsb.go	GRD	2	NA	DC9		1												1	1	1												-		+	+		-		N	Ben ml
20/01/2002	N	http://www.ntsb.go	GRD	2	NA	DC9	1	1 1		-															+ +			_			_			-		+	++				N	Ben ml
17/10/2001	N	http://aviation-safe	IDG	2	MF	A300															1	_											_			+	++		-			EV AAD
7/13/2001	F	http://www.ntsb.go	APR	2	EUR	B727			1	1	1				1				1	1	1															+	++		-		1 N	IG AP
5/25/2001	F	http://www.ntsb.go	APR	2	NA	B727		-	1	1	1				1		-		1	1	1	_	+				+ +						_	-		+	++		+		1 N	IG AP
3/23/2001	F	http://www.ntsb.go	APR	2	NA	B727	1	-	1	1	1				1		-		1	1	1	_	-		+ +		+ +	-			-			+		+	++		+		1 N	IG AP
3/11/2001	F	http://www.ntsb.go	APR	2	NA	B727			1	1	1				1				1	1	1												1			-	++		-		1 H	IG AP
1/9/2001	F	http://www.ntsb.go	APR	2	NA	B727		-	1	-	1				1		-		1	1	1		-											-		+	++				1 N	IG AP
1/6/2001	F	http://www.ntsb.go	APR	2	NA	B727			1		1				1				1	1	1		-		+ +			_			_			-		+	++				1 U	
17/04/2001	N	http://www.ntsb.go	CLB	2	NA	B7312			1													_		1									_	-		+	++		-		N	MI
12/28/2001	N	http://www.ntsb.go	TO	2	NA	B747G2																	1	· ·				1					1		1 1		++		1		M	SF DB
1/5/2001	1	http://www.ntsb.go	CRZ	2	NA	B747G2														1	1													-		-	++				N	
11/23/2001		http://www.ntsb.go	CRZ	2	ASIA	B747G2		-		-							-		1		1		-											-		+	++					
2/4/2001	1	http://www.ntsb.go	DG	2	NA	B747G2													1		1															-	++		-		U U	
11/27/2001	Ū.	http://www.ntsb.go	APR	2	AFR	B747G2		-							1								1					1				1	1	-	1	-	++		1	1	1 H	
3/6/2001	1	http://www.ntsb.go	TO	2	NA	DC10		+	1						-		-		1	1			r i		+ +		+ +	-			-			+		+	++		-		M	SF rs
25/07/2001	N	http://www.ntsb.go	DES	2	NA	DC9		-	-													1					+	-					-	-		+	++		+		N	Ben ml
01/05/2001	N	http://www.ntsb.go	GRD	2	NA	DC9	1	-																	+									+		+	++		+		N	Ben ml
12/02/2000	N	http://aviation-safe	GRD	2	ME	A300		1	-	-							-		-		1		-		+ +		+ +		+		-	+ +		+		+	++	_	+		N	EV AAD
10/23/2000	F	http://www.ntsb.go	APR	2	NA	B727		1	1		1				1		-		1	1	1		-				+	1					1	-	1	<u> </u>	+	1	+		1 H	IG AP
10/17/2000	F	http://www.ntsb.go	APR	2	NA	B727			1		1				1				1	1	1		-	1	+									-		1			+		1 N	IG AP
9/10/2000	F	http://www.ntsb.go	APR	2	NA	B727		1	1		1				1				1	1	1			1										-		+	++		+		1 N	IG AP
8/16/2000	F	http://www.ntsb.go	APR	2	NA	B727		1	1		1				1		-		1	1	1		-	1	+							+		+		+	++		<u> </u>		1 N	IG AP
7/28/2000	F	http://www.ntsb.go	APR	2	NA	B727			1		1				1				1	1	1		1					1							1		1		1		1 H	IG AP





		A	ccident	ts									acto	rs									F	actors	i (Noi	n-Tec	hnicaľ	)						Co	mpet	encies			Val	idation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment Ground manostrucing	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind	AIC NAV	Loss of comms	Iramic R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain Birds	Eng Fail MEL	Fire Svet mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G	Mis-AFS Mis A/C State	Mis-Sys	Pilot Incap Communication	SA Loodorshin and	Leadersnip and Teamwork	Workload Management Problem Solving	Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
7/29/1999	Ν	http://www.ntsb.go	CLB	2	NA	B747G2											1	1	1																			N	SF	DB
1/19/1999	1	http://www.ntsb.go	GRD	2	NA	B747G2											1	1 1																				N		
6/6/1999	Ν	http://www.ntsb.go	GRD	2	NA	B747G2	1			1														1	1				1			1						L		
3/5/1999	Ν	http://www.ntsb.go	LDG	2	ASIA	B747G2												1 1							1									1		1		M		
6/9/1999	Ν	http://www.ntsb.go	CRZ	2	OTH	B747G2														1																		N		
1/20/1999	1	http://www.ntsb.gc	CRZ	2	OTH	B747G2		1	1					1											1							1		1				M		
12/22/1999	F	http://www.ntsb.go	CLB	2	EUR	B747G2								1	1			1							1				1	1	1	1						1 H		
9/2/1999	I	http://www.ntsb.go	LDG	2	ASIA	B747G2																							1									1 L		
8/7/1999	Ν	http://www.ntsb.go	APR	2	NA	DC10												1																				N	SF	rs
6/24/1999	1	http://www.ntsb.gc	APR	2	EUR	DC10				_										1					1			_				1				1		<u> </u>	SF	rs
3/2/1999	1	http://www.ntsb.gc	CRZ	2	NA	DC10				1		1 1																										N	SF	rs
12/21/1999	F	http://www.ntsb.go	LDG	2	SA	DC10		1																				_	1			$\square$		_	_			1 H	SF	rs
12/18/1999	N	http://www.ntsb.gc	TO	2	EUR	DC10											1											_				$\vdash$				<u> </u>		N	SF	rs
11/7/1999	N	http://www.ntsb.gc	CLB	2	NA	DC10						1			1														1					_	_			1 M	SF	rs
09/11/1999	F	http://aviation-safe	TO	2	NA	DC9								1	1					1					1		1		1			1	1	1		1		1 H	Ben	ml
14/10/1999	1	http://www.ntsb.gc	TO	2	NA	DC9					_							1	1									_						_	_			N	Ben	ml
09/09/1999	1	http://www.ntsb.gc	LDG	2	NA	DC9																			1			_	1			1			_	1		1 H	Ben	ml
02/07/1999	N	http://www.ntsb.gc	GRD	2	NA	DC9	1																															N	Ben	ml
09/04/1999	1	http://www.ntsb.go	CRZ	2	NA	DC9		1																														L	Ben	ml
21/03/1999	1	http://www.ntsb.gc	CRZ	2	NA	DC9		1	1																			_				$\vdash$				<u> </u>		L	Ben	ml
04/03/1999	N	http://www.ntsb.gc	APR	2	NA	DC9										1	1											_				$\vdash$			_			N	Ben	ml
08/02/1999	Ν	http://aviation-safe	GRD	2	EUR	DC9	1																															U	Ben	ml
15/01/1999	Ν	http://www.ntsb.go	DES	2	NA	DC9									1					1																		L	Ben	ml
11/12/1998	F	http://aviation-safe	LDG	2	ASIA	A300		1	1					1																								U	EV	AAD
09/07/1998	I	http://www.ntsb.gc	LDG	2	EUR	A300											1	1																				N	EV	AAD
12/21/1998	F	http://www.ntsb.gc	APR	2	ASIA	B727	1	1 1	1					1			1	1 1																				1 H	IG	AP
10/20/1998	F	http://www.ntsb.go	APR	2	ASIA	B727		1	1					1			1	1 1							1							1				1		1 H	IG	AP
10/7/1998	F	http://www.ntsb.gc	APR	2	ASIA	B727		1	1	1				1			1	1 1																				1 N	IG	AP
10/2/1998	F	http://www.ntsb.gc	APR	2	ASIA	B727		1	1	1				1			1	1 1							1				1			$\square$						1 H	IG	AP
8/31/1998	F	http://www.ntsb.gc	APR	2	EUR	B727		1	1	1 1				1			1	1 1																				1 N	IG	AP
8/8/1998	F	http://www.ntsb.gc	APR	2	EUR	B727	1	1 1	1	1				1			1	1 1							1						1	1						<u>1 H</u>	IG	AP
5/7/1998	F	http://www.ntsb.gc	APR	2	EUR	B727		1	I 1	1				1		1	1	1 1																				1 U	IG	AP
4/20/1998	1	http://www.ntsb.gc	APR	2	NA	B727		1	1					1		1	1	1 1																				1 H	IG	AP
4/19/1998	1	http://www.ntsb.go	APR	2	NA	B727		1	1					1			1	1 1		1																		1 L	IG	
3/30/1998	1	http://www.ntsb.gc	APR	2	NA	B727		1	1					1			1	1 1																				1 N	IG	
2/9/1998	1	http://www.ntsb.gc	APR	2	NA	B727		1						1			1	1 1							1				1			$\square$		1			1	1 H	IG	_
1/6/1998	1	http://www.ntsb.go	APR	2	NA	B727	1 1	1						1			1	1 1														$\square$						1 N	IG	_
15/12/1998	1	http://www.ntsb.gc	APR	2	NA	B7312												1				+	_									$\square$						N		ML
08/12/1998	1	http://www.ntsb.gc	APR	2	NA	B7312						1			1																	$\vdash$				<u> </u>		N	1	ML
01/11/1998	N	http://www.ntsb.go	APR	2	NA	B7312											1	1 1														$\square$						N	1	ML
13/08/1998	1	http://www.ntsb.gc	APR	2	EUR	B7312												1				+	_									$\square$				<u> </u>		N		ML
05/05/1998	F	http://www.ntsb.gc	APR	2	SA	B7312		1						1															1			$\vdash$		_		+		U	-	ML
04/05/1998	N	http://www.ntsb.gc	PLDG	2	SA	B7312		1 1	1					1	1					1					1				1			$\vdash$		1		1		1 H		ML
12/04/1998	N	http://www.ntsb.go	LDG	2	IEUR	B7312		1 1				1 1		1				1 1		1									1			1				1	1	1  L	1	IML




		A	ccident	ts								Fa	ctors										Fac	ctors	(Non-	Techni	cal)							Comp	etencies			Valio	dation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Syst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists Def-DBs	Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA Leadership and	Workload Management	Problem Solving Decision Making	Knowledge Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
6/9/1997	1	http://www.ntsb.go	GRD	2	NA	DC10	1																														N	SF	rs
5/11/1997	Ν	http://www.ntsb.go	GRD	2	NA	DC10												1 1																			N	SF	rs
4/9/1997	Ν	http://www.ntsb.go	CRZ	2	NA	DC10																															N	SF	rs
2/1/1997	N	http://www.ntsb.gc	CRZ	2	SA	DC10																															N	SF	rs
07/12/1997	N	http://www.ntsb.go	GRD	2	NA	DC9														1																	N	ml	ds
21/11/1997	N	http://www.ntsb.gc	TO	2	NA	DC9														1								1									н	ml	ds
10/10/1997	F	http://www.ntsb.gc	DES	2	SA	DC9		1	1				1																								U	ml	MS
12/07/1997	1	http://www.ntsb.gc	APR	2	NA	DC9								1				1																			N	ml	ds
05/07/1997	1	http://www.ntsb.go	CRZ	2	NA	DC9												1 1																			N	ml	ds
18/03/1997	1	http://www.ntsb.gc	TO	2	NA	DC9										1		1 1																			N	ml	ds
20/02/1997	1	http://www.ntsb.go	CRZ	2	NA	DC9											1	1 1																			N	ml	ds
28/01/1997	N	http://www.ntsb.go	LDG	2	NA	DC9		1	1											1																	M	ml	ds
15/08/1996	1	http://www.ntsb.go	CLB	2	NA	B727										1		1 1																			1 N	IG	AP
14/08/1996	1	http://www.ntsb.gc	CLB	2	NA	B727										1		1 1																			1 N	IG	AP
14/06/1996	I	http://www.ntsb.go	CLB	2	NA	B727										1	1	1 1							1						1				1		1 M	IG	AP
12/05/1996	1	http://www.ntsb.go	CLB	2	NA	B727										1	1	1 1		1					1					1	-				1		1 H	IG	AP
28/04/1996	1	http://www.ntsb.go	CLB	2	NA	B727		1	1							1	1	1 1																			1 N	IG	AP
27/03/1996	1	http://www.ntsb.go	CLB	2	NA	B727	1 1			1						1	1	1 1			1				1				1		1						1 L	IG	AP
18/11/1996	N	http://www.ntsb.go	GRD	2	NA	B7312										1	1	1 1																			N		ML
09/09/1996	1	http://www.ntsb.go	DES	2	NA	B7312								1				1	1																		N		ML
08/07/1996	N	http://www.ntsb.go	TO	2	NA	B7312										1 1		1 1		1					1	1			1					1	1		M		ML
22/06/1996	N	http://www.ntsb.go	DES	2	NA	B7312		1	1																							_					N		ML
20/03/1996	N	http://www.ntsb.gc	GRD	2	NA	B7312												1														_					N		ML
29/02/1996	F	http://www.ntsb.go	APR	2	SA	B7312									1														1								U		ML
20/02/1996	1	http://www.ntsb.go	LDG	2	NA	B7312		1 1	1									1		1					1				1			-		1	1		1 H		ML
7/17/1996	F	http://www.ntsb.go	CLB	2	NA	B747G2												1 1														+					U		-
12/5/1996	1	http://www.ntsb.go	GRD	2	ASIA	B747G2												1																			N		-
6/17/1996	1	http://www.ntsb.go	CRZ	2	NA	B747G2												1 1																			N		-
5/19/1996	1	http://www.ntsb.go	CRZ	2	NA	B747G2												1														+					U		-
1/5/1996	1	http://www.ntsb.go	GRD	2	NA	B747G2										1		1																			N		-
1/23/1996	N	http://www.ntsb.gc	GRD	2	NA	B747G2	1			1		1																1	1		-			1		1	1 M		
11/12/1996	F	http://www.ntsb.go	CLB	2	ASIA	B747G2						1																				_					U		-
9/5/1996	N	http://www.ntsb.go	CRZ	2	NA	DC10												1		1					1		1					1					M	SF	rs
12/22/1996	N	http://www.ntsb.go	GRD	2	NA	DC10	1 1																														N	SF	rs
08/08/1996	1	http://www.ntsb.go	LDG	2	NA	DC9												1														+					N	ml	ds
14/05/1996	N	http://www.ntsb.go	APR	2	NA	DC9		+ +				_				1		1												-		+				-	tυ	ml	MS
11/05/1996	F	http://www.ntsb.gc	CLB	2	NA	DC9																					1					+					N	ml	ds
28/02/1996	1	http://www.ntsb.ac	LDG	2	NA	DC9														1					1				1			-		1	1		M	ml	ds
19/02/1996	N	http://www.ntsb.ac	LDG	2	NA	DC9														1					1	1			1			+	-	1	1		M	ml	ds
01/02/1996	N	http://www.ntsb.ac	LDG	2	NA	DC9												1						++								+	+				N	ml	ds
07/01/1996	N	http://www.ntsb.gc	CLB	2	NA	DC9												1		1					1				1						1 1		I H	ml	ds
07/12/1995	1	http://www.ntsb.ac	CLB	2	NA	B727			1							1		1 1							1				1					1			1 H	IG	AP
07/11/1995	1	http://www.ntsb.ac	CLB	2	NA	B727										1		1						++			1					-	-			1	1 N	IG	AP
04/07/1995	1	http://www.ntsb.gc	CLB	2	NA	B727										1		1													1	-				1	1 N	IG	AP





		A	cciden	ts									Fac	ctors										Fa	ictor	s (Non	-Tech	nical	)					(	Compet	tencies			Vali	dation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runwav/Taxi condition	Adverse Weather/Ice	Windshear	Crosswind ATC	NAV Loss of comms	Traffic	R/W Incursion Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Svst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure	u.c LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	ъА Leadership and Teamwork	Workload Management	Problem Solving Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
3/1/1994	Ν	http://www.ntsb.go	TO	2	ASIA	B747G2													1 1																			U		
4/7/1994	N	http://www.ntsb.go	UNK	2	NA	DC10																																U	SF	rs
05/07/1994	N	http://www.ntsb.go	CLB	2	NA	DC9			1																													M	ml	ds
02/07/1994	F	http://www.ntsb.go	APR	2	NA	DC9			1	1	1										1					1				1			-		1	1		1 H	ml	MS
08/05/1994	1	http://www.ntsb.go	LDG	2	SA	DC9																								1			-					U	ml	ds
05/05/1994	1	http://www.ntsb.go	TO	2	NA	DC9											1																					N	ml	ds
28/01/1994	1	http://www.ntsb.go	TO	2	NA	DC9		1																						1								1 M	ml	ds
06/12/1993	1	http://www.ntsb.go	LDG	2	NA	A300													1														-	$\square$				N	AB	AAD
15/11/1993	N	http://aviation-safe	APR	2	ASIA	A300			1					1					1		1					1					1	-			1			н	AB	AAD
19/10/1993	1	http://www.ntsb.go	CLB	2	NA	A300											1		1																			N	AB	AAD
15/11/1993	1	http://www.ntsb.go	CLB	2	NA	B727							1								1					1	1				1	1				1		1 H	IG	AP
22/03/1993	1	http://www.ntsb.go	CLB	2	NA	B727					1		1								1					1						1 1						1 M	IG	AP
15/03/1993	1	http://www.ntsb.go	CLB	2	NA	B727							1													1												1 M	IG	AP
09/03/1993	1	http://www.ntsb.go	CLB	2	NA	B727					1		1																									1 N	IG	AP
11/02/1993	1	http://www.ntsb.go	CLB	2	NA	B727		1						1							1					1	1			1		1				1		1 H	IG	AP
06/06/1993	1	http://www.ntsb.go	GRD	2	NA	B7312													1																			N		ML
15/03/1993	1	http://www.ntsb.go	TO	2	NA	B7312													1																			N		ML
13/02/1993	1	http://www.ntsb.go	LDG	2	NA	B7312		1	1												1									1			-		1	1		1 M		ML
4/12/1993	1	http://www.ntsb.go	CLB	2	NA	B747G2													1														-					N	SF	DB
9/25/1993	1	http://www.ntsb.go	TO	2	NA	B747G2											1 1		1																			L	SF	DB
3/31/1993	N	http://www.ntsb.go	CLB	2	NA	B747G2			1								1		1																			N	SF	DB
7/25/1993	N	http://www.ntsb.go	GRD	2	NA	B747G2		1																		1				1		1		1				1 H		
8/27/1993	1	Factual	UNK	2	EUR	B747G2																														-		U		
9/11/1993	1	http://www.ntsb.go	CLB	2	NA	B747G2													1														-			-		N		-
7/10/1993	1	http://www.ntsb.go	CLB	2	NA	DC10													1														-			-		N	SF	rs
4/14/1993	N	http://www.ntsb.go	LDG	2	NA	DC10		1			1															1				1			-					1 H	SF	rs
11/26/1993	N	http://www.ntsb.gc	LDG	2	SA	DC10		1			1																			1								1 M	SF	rs
11/03/1993	N	http://www.ntsb.go	LDG	2	NA	DC9															1					1								1	1	1		H	ml	MS
28/09/1992	F	http://aviation-safe	APR	2	ASIA	A300			1		1			1		1					1		1			1						1				1		н	AB	AAD
17/12/1992	1	http://www.ntsb.go	CLB	2	NA	B727													1																			1 N	IG	AP
27/11/1992	1	http://www.ntsb.go	CLB	2	NA	B727																				1					1		1			1		1 L	IG	AP
01/10/1992	1	Factual	CLB	2	NA	B727																																1 U		
02/07/1992	1	http://www.ntsb.go	CLB	2	NA	B727			1												1					1						1		$\square$		1		1 H	IG	AP
09/02/1992	1	http://www.ntsb.go	CLB	2	NA	B727													1		1					1					1				1	1		1 H	IG	AP
08/10/1992	1	http://www.ntsb.go	APR	2	NA	B7312					1		1																									N		ML
26/08/1992	N	http://www.ntsb.go	GRD	2	NA	B7312													1 1														-					N		ML
06/08/1992	Ν	http://www.ntsb.go	GRD	2	NA	B7312	1	1																												1		N	1	ML
15/07/1992	1	http://www.ntsb.go	APR	2	NA	B7312													1																			N		ML
14/05/1992	N	http://www.ntsb.go	DES	2	NA	B7312			1																													M		ML
07/01/1992	1	http://www.ntsb.go	CLB	2	NA	B7312													1																			N	1	ML
8/23/1992	F	http://www.ntsb.go	GRD	2	NA	B747G2	1	1																														U		1
3/19/1992	1	http://www.ntsb.go	GRD	2	NA	B747G2	1	1													1					1						1		1				M		
1/9/1992	N	Factual	UNK	2	ASIA	B747G2																																U		
8/11/1992	N	http://www.ntsb.go	GRD	2	NA	B747G2		1			1														1	1				1		-						1 M	1	

		Ac	ccident	S										acto	ors											F	actors	s (No	n-Tec	hnic	al)							C	ompe	tencie	s			Validation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runwav/Taxi condition	Adverse Weather/Ice	Windshear	Crosswind ATC	NAV	Loss of comms	Iramic R/W Incursion	Poor Visibility	Upset	vvake vortex Tarrain	Birds	Eng Fail MEI	Fire	Syst mal	Ops/Type Spec	Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State	MIS-Sys Pilot Incap	Communication	SA	Leadersnip and Teamwork	Workload Management Problem Solving	Decision Making	Anoweage Application of Procedures & Knowledge	Flight Management,	Guidance and Automation	Manual Aircratt control Improved Training	Analyst Checker
9/19/1992	1	Factual	UNK	2	SA	B747G2																															-		_				U	
9/23/1992	1	http://www.ntsb.go	CLB	2	NA	DC10													1																		-		-				N	SF rs
3/3/1992	1	http://www.ntsb.go	LDG	2	NA	DC10															1																		-				N	SF rs
12/21/1992	F	http://www.ntsb.go	UNK	2	EUR	DC10		1	1	1	1 1												1					1								1			-				U	SF rs
21/10/1992	N	http://www.ntsb.go	GRD	2	NA	DC9	1	1							1						+																		-				N	ml ds
08/04/1992	F	http://www.ntsb.go	GRD	2	NA	DC9		1																													-						N	ml ds
18/01/1992	N	http://www.ntsb.go	LDG	2	NA	DC9			1								-																						-				U	ml ds
13/12/1991	1	http://www.ntsb.go	CLB	2	NA	B727			1			-			-		-									_		1					1			1	-+	-	-+			1	H H	IG AP
02/11/1991	1	http://www.ntsb.go	CLB	2	NA	B727																	1														-+	_	-+			1	N	IG AP
05/10/1991	li	http://www.ntsb.go	CLB	2	NA	B727			1								-				+							1								1			-+	1		1	H	IG AP
20/09/1991	1	http://www.ntsb.go	CLB	2	NA	B727									-		+				1					-											-	-	-+			1	N	IG AP
02/07/1991	1	http://www.ntsb.go	CLB	2	NA	B727						-					-				1					_								-			-+	-	-+			1	N	IG AP
06/06/1991	1	http://www.ntsb.go	CLB	2	NA	B727																																	-+			1	N	IG AP
15/05/1991	1	http://www.ntsb.go	CLB	2	NA	B727			1								-						1					1					1			1			-			1	H	IG AP
03/05/1991	1	http://www.ntsb.go	CLB	2	NA	B727						-			-		+									_											-+	-	-+			1	U	IG AP
25/04/1991	li –	http://www.ntsh.go	CLB	2	NA	B727		1				-					+				+					-										-+			-+			1	M	IG AP
23/03/1991	li	http://www.ntsb.go	CLB	2	NA	B727			1												+															-			-+			1		IG AP
25/01/1991	li –	http://www.ntsb.go	CLB	2	NA	B727		1	-			-			-	1					+	_	1			-		1						-	1	1		_	+			1	H	IG AP
20/01/1991	li –	http://www.ntsb.go	CLB	2	NA	B727		1				-			-					-	1	_				-						-				Ē		-	-+			1	U U	IG AP
01/03/1991	li	http://www.ntsh.go	CLB	2	NA	B727						-			-		-				1	1													-	-+			-+			1	Ū.	IG AP
30/11/1991	N.	http://www.ntsb.go	APR	2	NA	B7312		-	-		-	-		-	1		+	1			<u> </u>	-				-			-	<u> </u>	++				-	$\pm$	-+	-	-+	-	-		- U	MI
16/10/1991	N	http://www.ntsb.go	GRD	2	NA	B7312		1	-		1		1				+				+	_				-		1				-		-		1	-	1	-+	-	-		M	MI
09/04/1991	1	http://www.ntsh.go	CLB	2	NA	B7312					-						+		1	1						-										<u> </u>	-		-+				N	MI
03/03/1991	F	http://www.ntsb.go	APR	2	NA	B7312		-				-			-		+				1	-				-										-+	-+	-	-+				- <u>ii</u>	ML
13/02/1991	li –	http://www.ntsb.go	APR	2	NA	B7312		-	-	1	-	+		-	-		+	-		-	· ·	_	+			-			-	<u> </u>		-	1	-	-	-+	-+	-	-+	-		1	M	ML
4/29/1991	li –	http://www.ntsb.go	CRZ	2	NA	B747G2		-	-		-	+		-	-	-	+	-	1	-	1	-	-			-				-		-		-	-	-+	-+	-	+		_		- <u>U</u>	
10/24/1991	li –	http://www.nteb.go	CRZ	2	ΝΔ	B747G2		-	-		-	-		-	-		-	-		-	1	-	-			-						-		-	-	-+		_	$\rightarrow$					
10/17/1991	li –	http://www.ntsb.go	IDG	2	NA	B747G2		-				-		-	-		+	-		1	<u> </u>	_	1			-		1		<u> </u>	++		1		-	1		-	-+	1		1	H H	
8/12/1991	li –	http://www.ntsb.go	TO	2	NA	B747G2		-	-		1		1		1		+	-				_	- <u>-</u>			-				<u> </u>		-		+	-	-ť	-	-	-+					
12/12/1991	li –	Factual	CRZ	2	ΝΔ	B747G2		-	-	-	-					1	+	-		-	1	_	-			-		1				-	1	-	-	1			-+			1	- Ŭ	
8/22/1991	li –	http://www.nteb.go		2	NΔ	B747G2		-				-		-			+		1	1	1	1				-										<u> </u>		-	$\rightarrow$			— <u> </u>	N	
12/29/1991	F	Factual	CLB	2		B747G2		-	-	-	-	+		-	-		1		1		1					-			-	<u> </u>	++	-		-	-	-+		-	+	-	-	-+		
7/13/1991	li –	http://www.ntsh.go	CLB	2	NA	DC10		-	-	+ +	_	-	+	-	+		- 1.				1	_	-			+			-	-	+	-		-	1	-+	-+	-	-+	-	-			SE rs
12/23/1991	li –	http://www.nteb.go	TO	2	ΝΔ	DC10		-			1			1			-			-		-	-			-		1				-		-	1	-+		_	$\rightarrow$					SF re
10/30/1991	li –	http://www.ntsb.go		2	NΔ	DC10		1			1						+	-		-	+	_	-			-		1				-	1	-		-+		-	+		-		HH H	SF re
10/28/1991	li –	http://www.ntsb.go	CLB	2	NΔ	DC10						+		-	-		+	-		-	1	_				-				<u> </u>		-		-	-	+	-+	-	-+	-	-	— <del> </del>	N	SF re
29/05/1991	li –	http://www.ntsb.go	CRZ	2	NA				1		-+-		+	-	+		-	+				4		+		+			-	-	+	+		-	1	+	$\rightarrow$	+	-+		-	-+		ml de
17/02/1991	F	http://www.ntsb.go	TO	2	NA	003		-	1			-	+		-		-							1		-	1	1		<u> </u>		-			1	1	-+	1	-	-				mi de
19/12/1990	li –	http://www.ntsb.go	CLB	2	NA	B727					-+-	-	++	-	+		+	+		+	+	-	+			+				<u> </u>	++	+		+	1	-	$\rightarrow$		-	-	-	- 1		IG AP
05/12/1990	li –	http://www.ntsb.go	CLB	2	NA	B727		-	+	+ +	_	-	+	-	+		+	-	+			1	-			+	1		-	-		-		-	1	-+	-+	-	-+	-	-			IG AP
16/11/1990	i -	Factual	CLB	2	NA	B727			-		-	-	+	-	-		+	-					+	+		-	<u> </u>		-			-		-	1	+	$\rightarrow$	-	$\rightarrow$	-				
09/09/1990	li –	http://www.nteb.go	CLB	2	NA	B727		-	-			-	+	-	-		+	-		-	+	1				+		$\vdash$	-	-	+	-			+	-+	$\rightarrow$	-	-+	-				
28/09/1990	lí –	http://www.ntsb.go	CLB	2	NA	B727			-		-+-	-	+	-	+		+	+			+	- 1			$\vdash$	+		1		-	+	+		+	1	-+	$\rightarrow$	+	-+	1			HH H	IG AP
03/12/1990	li –	http://www.ntsb.go	CLB	2	NA	B727		-	1		1			1			+	+			+		+	1		+				<u> </u>	++	+	+	+	1	+	$\rightarrow$	-	+			- 1		IG AP
	11		, 010	-		1											_	_	1 I I				_			_					<u> </u>			_		_				_				



		A	ccident	ts									F	acto	rs											F	acto	ors (	Non-	Techr	nical	)						(	Compe	tenc	cies			Vali	dation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runwav/Taxi condition	Adverse Weather/Ice	Windshear	Crosswind ATC	NAV	Loss of comms	R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds	eng raii MEL	Fire	Systmal Ons/Type Spec	Cabin Cabin	Compliance	Def Manuals	Def-Charts Def-Charts	Def-Chk lists	Def-DBs	Def-Proc's Fatique	CRM	Physio Workload Distraction	Pressure	D.G LF.P	Mis-AFS	Mis A/C State Mis-Sys	Pilot Incap	Communication sA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making Knowlodzo	Application of	Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
12/08/1990	1	http://www.ntsb.go	CLB	2	NA	B727																																		—			1 N	IG	AP
18/07/1990	1	http://www.ntsb.go	CLB	2	NA	B727			1															1																			1 U	IG	AP
21/06/1990	1	http://www.ntsb.go	CLB	2	NA	B727															1																						1 L	IG	AP
13/03/1990	I	http://www.ntsb.go	CLB	2	NA	B727					1																																1 N	IG	AP
17/02/1990	1	http://www.ntsb.go	CLB	2	NA	B727															1																						1 N	IG	AP
12/02/1990	1	http://www.ntsb.go	CLB	2	NA	B727														1	1																						1 N	IG	AP
31/01/1990	1	http://www.ntsb.go	CLB	2	NA	B727	1																1																				1 N	IG	AP
18/01/1990	1	http://www.ntsb.go	CLB	2	NA	B727					1		1	1																													1 L	IG	AP
04/01/1990	1	http://www.ntsb.go	CLB	2	NA	B727															1																						1 N	IG	AP
22/02/1990	1	http://www.ntsb.go	GRD	2	NA	B7312		1 1	1													_			_						_			1		1							1 H		ML
19/09/1990	1	http://www.ntsb.go	GRD	2	NA	B7312														1	1		1						1		_							_		1			M		ML
22/07/1990	N	http://www.ntsb.go	010	2	NA	B7312			_												1				_	_		_		_	_		_	_	_			_					N		ML
02/06/1990	N	http://www.ntsb.go		2	NA	B7312			4				_	_					_			_	1		_	-		_	1	_	_		_	1	-	1	1	-		1			<u>1 H</u>	_	ML
1/105/1990	IN	http://www.ntsb.go	DES	2	INA NA	B7312		_	1			-	_	_				_	_	1	_	_			_	-		_	-	_	_		-	_	-	_		-		+				_	IVIL
6/16/1000	I NI	http://www.nisb.go		2	IN/A	D747G2		1	_				-	-				-		1		_			_	-		_	1	1			-		-			1 1		+					
8/27/1000		http://www.nisb.go		2	NA NA	B747G2			-				-	-					_		1	_		1	_	1		_	1	- 1			-		-		-			+				-	
7/14/1990	N	http://www.ntsb.go		2	ΝΔ	B747G2		-	1			-	-				+ +	-	-			-			-			-	1	-	-+		-	_	+	1		-		+			-##	-	
8/3/1990	N	http://www.ntsb.go	DEC RZ	2	NA	DC10		-				-	-	-			+ +	-	-		-	1			-	-				-	-		-		+			-+		+				SE	rs
7/27/1990	N	Factual		2	ASIA	DC10																				-					-		-					-		+				SF	rs
4/18/1990	N	http://www.ntsb.go	DIDG	2	NA	DC10																	1					-	1		-		-	1	+		-	-	-	+			1 H	SF	rs
20/01/1990	N	http://www.ntsb.go	DES	2	NA	DC10			1		_								-			-				-					-		-		+		-	-		+			N	SF	rs
02/01/1990	N	http://www.ntsb.go	CRZ	2	NA	DC10														1	1	_											-		-			-		+			N	SF	rs
03/12/1990	F	http://www.ntsb.go	GRD	2	NA	DC9					1			1	1														1						1	1 1				+			H	ml	ds
29/10/1990	N	http://www.ntsb.go	GRD	2	NA	DC9		1											-							-			1				-		-	1		-		+			L	ml	ds
03/10/1990	F	http://www.ntsb.go	CRZ	2	NA	DC9			1													1	1						1						-	1	1			+			Н	ml	ds
29/06/1990	1	http://www.ntsb.go	LDG	2	NA	DC9			1														1																				н	ml	ds
21/06/1990	1	http://www.ntsb.go	TO	2	NA	DC9															1																						N	ml	ds
07/06/1990	I	http://www.ntsb.go	TO	2	NA	DC9												1			1																						N	ml	ds
31/05/1990	1	http://www.ntsb.go	CLB	2	NA	DC9															1																						N	ml	ds
13/03/1990	1	http://www.ntsb.go	TO	2	NA	DC9														1	1																						N	ml	ds
31/01/1990	1	http://www.ntsb.go	GRD	2	NA	DC9															1																						N	ml	ds
18/01/1990	1	http://www.ntsb.go	DTO	2	NA	DC9																	1						1					1		1				1			н	ml	ds
10/05/1989	N	http://www.ntsb.go	DES	2	NA	A300			1																						_				_		_	_		+			N	AB	AAD
27/12/1989	1	http://www.ntsb.go	CLB	2	NA	B727																			_															$\perp$			1 U	IG	AP
08/12/1989	-	nttp://www.ntsb.go	DICLB	2	NA	B/2/												_			1			$\vdash$	_	_		_	+		_				-			_		+			1 N	IG	AP
15/12/1989	-	nttp://www.ntsb.go		2	NA NA	B/2/			-		1		1					_		+		_	4		_	-		_	4	_	_		_	_	-			-		+				IG	AP
21/10/1989	1	Factual	ICLB	2	NA	B/2/		_	-	+		+	+	_	+	$\vdash$	+	$\rightarrow$	-		1	_	1	$\vdash$	_	-	$\left  \right $	_	1		-		-		1	1		+		+			H	IG IC	
20/11/10/1989	-	http://www.ntsb.go		2	NA	D121 D727	$\vdash$	_	_	+	_	+	+	_	+	$\vdash$	+	$\rightarrow$	-		1	_	+	$\vdash$		-	+	_	+	_	$\rightarrow$				+	$\vdash$	+ +	+		+				IG	
25/08/1020	1	http://www.msb.go	CB7	2	NA	B727			-				-		+		+		-				1	1	_	-		1	1		-	1	_	1 1	1	$\vdash$	1	+		1				IG	
10/08/1989	1	http://www.msb.go		2	NA	B727				+			-	-	+		+	-	-		1	_	1	1		-			1	_	-	-	_	1 1	-		-	+		+-				IG	
10/08/1989	-	http://www.nisb.go	CRZ	2	NA	B727				+		+	+	-	+		+	+	+		1	-		$\vdash$	-	-	+	-	+		+		-		+	$\vdash$	+ +	+		+	-+		- IN	IG	
24/05/1989	i	http://www.ntsb.go	CRZ	2	NA	B727						1	+		1			+	+		1			$\vdash$							-		-		1	$\vdash$		+		+				IG	AP





		A	ccident	ts										Facto	ors											Fac	tors	(Nor	I-Tec	hnica	I)							Com	ieter	ncies			Valio	dation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition	Adverse weather/ice Windshear	Crosswind	ATC NAV	Loss of comms	Traffic R/W Incursion	Poor Visibility	Upset	wake vortex Terrain	Birds	Eng Fail MEI	Fire	Syst mal	Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts	Def-Chk lists Def-DBs	Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G	Mis-AFS	Mis A/C State	Pilot Incap	Communication	Contraction Leadership and	Teamwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
5/9/1988	N	http://www.ntsb.go	APR	2	NA	B747G2															1																					N		
2/19/1988	1	Probable Cause	TO	2	NA	B747G2						1		1																							T		$\square$			U		
6/17/1988	1	Factual	UNK	2	SA	B747G2																																				U		
9/21/1988	1	http://www.ntsb.go	CRZ	2	SA	B747G2			1													1																				N		
6/1/1988	1	http://www.ntsb.go	LDG	2	NA	B747G2			1	1					1													1					1		1							1 H		
12/21/1988	F	Factual	CRZ	2	EUR	B747G2																																				U		
3/3/1988	N	Probable Cause	LDG	2	NA	B747G2																	1					1				1	1						1		1	1 H		
1/9/1988	1	Probable Cause	CRZ	2	NA	B747G2															1																					U		
5/2/1988	1	Probable Cause	LDG	2	ASIA	B747G2													1		1							1					1 1						1 1			Н		
4/14/1988	1	Factual	UNK	2	EUR	B747G2																																	$\square$			U		
12/16/1988	N	Factual	UNK	2	OTH	B747G2																																				U		
9/12/1988	N	Probable Cause	LDG	2	NA	DC10															1							1					1		1							1 M	SF	rs
5/21/1988	N	Probable Cause	TO	2	NA	DC10															1																					N	SF	rs
5/11/1988	1	Probable Cause	TO	2	NA	DC10						1		1																									$\square$			N	SF	rs
3/30/1988	1	http://www.ntsb.go	GRD	2	NA	DC10														1	1																		$\square$			N	SF	rs
2/10/1988	1	http://www.ntsb.go	LDG	2	NA	DC10	1							1																									$\square$			N	SF	rs
12/30/1988		Probable Cause	CRZ	2	отн	DC10						1		1																						-	-		$\square$			N	SF	rs
10/01/1988	N	http://www.ntsb.go	GRD	2	NA	DC10																1				_						_		-		-	-	-	$\leftarrow$			N	SF	rs
15/11/1988		http://www.ntsb.go	TO	2	NA	DC9													1		1																-		$\square$			N	ml	ds
30/10/1988	N	http://www.ntsb.go	GRD	2	NA	DC9	1	1																													-		-+			N	ml	ds
20/08/1988	1	http://www.ntsb.go	DG	2	NA	DC9								_		1			-		-										-	-		+		-	+		$\sim$			U.	ml	ds
05/08/1988	i	http://www.ntsb.go	TO	2	NA	DC9								-					1		1	_								_	-	-		+		+	+	-	( <del> </del>			N	ml	ds
05/08/1988	i i	http://www.ntsh.go	GRD	2	NA	DC9		1																										-		-	-		( <del> </del>	$\rightarrow$		N	ml	ds
10/05/1988	li l	http://www.ntsb.go	TO	2	NA	DC9						1		1					-												-					-	+		( <del> </del>	-+			ml	ds
21/09/1987	F	http://aviation_safe		2	ME	A300				-							-		-		-	_	1			-	+ +	1			-	_	1	+	1	-	+	1	$\vdash$	$\rightarrow$		1 1	ΔB	
03/08/1987	li l	http://www.nteb.go	TO	2	NΔ	A300				-				-			-		1		1	_	1					1			-	_		+	1		+	1	$\vdash$	$\rightarrow$		M	AB	
20/03/1087	N	http://www.ntob.go		2	NA	A300	-		1					_								_									-						+		+					
05/12/1087	N	http://www.msb.go		2	NA	P7212	-							_			-		1		1	_						-			-	_		-		-	+	-	+				ль	MI
19/11/1097	N	http://ntsb.gov/ntsi		2	NA	D7312			1					_			-					_	-	-	+ +			_			-	_		+		-	+	-	⊢	$\rightarrow$				MI
10/11/1987	N	http://ntsb.gov/ntsi		2	NA	D7312						_		_	1		-		-		-	_		_	+ +	_	+ +	_			-	_		-		-	+	-	⊢				-	MI
11/09/1097	IN	http://nisb.gov/nisi		2	N/A	D7312						1		1			-		-		_	_		-		-		-			-	_				_	+	-	⊢					NAL NAL
07/07/1987	-	http://www.nisb.go		2	NA	D7312 D7212						1			1		-		-		_	-	1			-		1			-				1 1	-	-	-					-	MI
07/07/1987	I NI	http://www.ntsb.go	CDD	2	IN/A	D7312		1		-	-			-	1		-		-		-	_	1		+	-		- 1		-	-	_		+		-	+	-	⊢₽					- IVIL
19/06/1987	IN	http://www.ntsb.go		2	IN/A	D7312		1		_		1		1 1	4		-		-		-	_		_	+	_		_			-	_		-		-	+	-	⊢	$\rightarrow$			_	IVIL NAL
10/00/1987		http://www.ntsb.go		2		D7312		-		_				1 1	1		_		_			_				_		_			_	_		_		_	—		$\vdash$					IVIL
11/06/1987	-	nttp://www.ntsb.go		2	INA	B/312		-			4	_		_	-				_	-	1	_	-		+	_					_	_	4	-		_	+		⊢				-	IVIL
23/02/1987	-	http://www.ntsb.go	DEG	2	NA	D7312	-	-	1		1		+	_			-	+		+	1	_		_	+		+	_	+ +		-	+	1	+	+	-	+	+	⊢			- M	-	INIL
12/16/1087	-	Teetuel	UNK	2	INA CA	D7312	_	-	$\vdash$	_	+		+	_				+	_	+	1	_		_	+		+	_	+		-	-		+	++		+	-	$\mapsto$			-H-	-	IVIL
12/10/1987	U	Pacitial Deskable One	UNK	2	SA	D747G2		-		_		_	+					+		+	_	_			+	_	+	_	+		-			-	++		+		$\mapsto$				I	+
5/29/1987	1	Probable Cause	URZ OPP	2	SA	B747G2		-		_	+		+	_				+	_		4	4			+		+		+		1	-		-	+	_	+		$\mapsto$				I	+
2/11/1987	N	Probable Cause	GRD	2	NA	B747G2		-	+ +	_	+	-	+	_	1		_	+	_	+	1	1			+	_	+	-			-	_	4	+			+	4	$\mapsto$			N	I	+
8///198/	1	Probable Cause	APR	2	NA	B747G2		-			+	1	+	_	1			+		+	_	_			+		+	1			_	_	1	+	1		+	1	$\mapsto$			M	I	+
0/22/1987	N	nttp://www.ntsb.go	GRD	2	INA	B747G2		1					+					+			_				+				+		_			_			+	-	$\mapsto$				I	+
2/26/1987	N	Probable Cause	GRD	2	NA	B/4/G2				_				_				+	_			1		_	+	_	1				_			-			+		$\mapsto$		-	N		+
//24/1987	N	Probable Cause	IGRD	2	INA	B/4/G2	1	11			1		1 1					1 1			1		11				1 1	1				1	1		1			1	(  ľ	( )	1	a H		1

		A	ccident	ts										Fac	tors	3												Factor	rs (N	lon-1	Tech	nical	)								Comp	oetei	ncies			Va	idation.
Date	Severity	Info Source Link	Phase	Generation	Region	1 Туре	Ground equipment	Ground manoeuvring	Adverse Weather/Ice	Windshear	Crosswind	ATC	Loss of comms	Traffic	R/W Incursion	Poor Visibility Upset	Wake Vortex	Terrain	Birds :	eng Fail MEL	Fire	Syst mal One/Tyne Sner	Ops/Type opec Cahin	Compliance	Def Manuals	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique	CRM	Physio Workload Distraction	Prorivad Distraction	D.G LF.P	Mis-AFS	Mis A/C State	Mis-Sys Dilot Incen	Communication	SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control	Analyst	Checker
8/9/1987	I I	Probable Cause	APR	2	NA	B747G2						1		1	1	1																													N		
8/11/1987	F	Probable Cause	GRD	2	NA	B747G2	1																																						N		
8/2/1987	I I	Probable Cause	TO	2	NA	DC10									1																														N	SF	rs
7/9/1987	I	Probable Cause	CRZ	2	OTH	DC10						1		1																															N	SF	rs
6/6/1987	I I	Probable Cause	APR	2	NA	DC10																1																							N	SF	rs
6/26/1987	I I	Probable Cause	DES	2	NA	DC10																1																							N	SF	rs
3/26/1987	I I	Probable Cause	CRZ	2	NA	DC10													1																										N	SF	rs
3/25/1987	Ν	Probable Cause	GRD	2	NA	DC10														1	1																								N	SF	rs
11/7/1987	1	Factual	UNK	2	NA	DC10							_		_		_								_																				U	SF	rs
11/21/1987	1	Probable Cause	LDG	2	NA	DC10			_				_		_	_							_	_	_	+			_					_	1	1									1 N	SF	rs
10/5/1987	1	Probable Cause	CLB	2	NA	DC10							_		_							1															_			$\square$					N	SF	rs
10/28/1987	1	Probable Cause	CRZ	2	NA	DC10							_		_		_					1	_						_																N	SF	rs
27/12/1987	N	http://www.ntsb.go	LDG	2	NA	DC9			1			_	_		_	_	_					_	_	1		+			_	1		_	_	_	1		_	1							1 H	ml	ds
05/12/1987	1	http://www.ntsb.go	CLB	2	NA	DC9	_		_	_		1	_	1	-	_	_			_		-	_	+	_		_		-		_		_	_		$\rightarrow$	_	-		$ \rightarrow $		$\vdash$				mi	ds
15/11/1987		nttp://www.ntsb.go	DES	2	INA	DC9							_		_		_					1			_		_		_					_											IN IN	mi	ds
15/11/1987	F	http://www.ntsb.go	10	2	NA	DC9			1				_			_	_			_		_		1	_				_	1	_		_	_	1	_				$\left  \right $			1		11 H	mi	ds
20/08/1987	N	http://www.ntsb.go		2		009	_		1			1	_		1	1	_	-	1 1		+ +	-	_	1	-	+	_		-	1	-		_	_	1	$\rightarrow$	_				1		1				
13/07/1986	N	http://aviation-sale		2	NA	A300			1				-		-		_	-	1 1			-	_	-			-		-	1	-			-	1	-+	_				1		<u> </u>				
25/10/1986	N	http://www.msb.go	HLDG	2	NA	P7212		1	1		1		-		_	-	_					-	_	-	-				-		-		-	-	1		_		1		1				1		MI
30/08/1986	I	http://www.pteb.go		2	ΝΔ	B7312	-					1	-	1	-	-	-	-					-	+	-	+			-	+	-			-	1			1	1			$\vdash$			1 1	-	MI
06/07/1986	1	http://www.ntsb.go	APR	2	NA	B7312			-	-			-		-	-	-	+ +		-			-	+	-		-		+		1	-		-		1				+		$\vdash$				-	MI
04/05/1986	N	http://ntch.gov/ntcl		2	NA	D7012			1				-		-		-							-	-		-		-					-												-	MI
08/04/1986	N	http://ntsb.gov/ntsi		2	NA	B7312								$\vdash$	-	-				-		1		-					-		-	-				-	-									+	MI
21/03/1986		http://www.ntsh.go	DES	2	NA	B7312			-	-		-	-	1	-	-	-	+ +		-			-	+	-		-		+	$\vdash$	-		-	-		-	-			+		$\vdash$				-	MI
03/01/1986	i i	http://www.ntsb.go	TO	2	NA	B7312	-		-	-		-	-		-	-	-	+ +		-		1	-	+	-		_		+	$\vdash$	-	-		-		-	-	-		+		+				-	MI
3/3/1986	N	Probable Cause	CRZ	2	NA	B747G2			1						-		-								-	1						-														-	
12/21/1986	1	Probable Cause	GRD	2	NA	B747G2			-				+		-		+			+				+	1				+		-	-				1				+		$\vdash$			T N	1	+
1/27/1986	i	Probable Cause	CLB	2	NA	B747G2				-			-		-		-			-	1	1		+					-		-	-		-		-									I N	-	-
6/24/1986	1	Probable Cause	CR7	2	ASIA	B747G2									-							1	1																							-	-
5/23/1986	N	Factual	UNK	2	AUS	B747G2																																							ΤŪ		-
8/10/1986	1	Probable Cause	GRD	2	NA	DC10				-					-						1			-					-		-	1	1												N	SF	rs
5/7/1986	1	Probable Cause	GRD	2	NA	DC10									-									1					-	1	-					-							1		Н	SF	rs
4/7/1986	N	Probable Cause	CRZ	2	NA	DC10			1																																					SF	rs
3/2/1986	1	Probable Cause	CRZ	2	NA	DC10			- F																1				-			-				1										SF	rs
11/7/1986	N	Probable Cause	CRZ	2	NA	DC10				-					-	1				-		1	1						-		-	-										$\square$			N	SF	rs
11/10/1986	1	Probable Cause	CRZ	2	NA	DC10						1	1	1											1																				N	SF	rs
10/5/1986	1	Probable Cause	GRD	2	NA	DC10																1																							N	SF	rs
02/01/1986	1	Probable Cause	LDG	2	NA	DC10		1																					+	1		-			1				1						1 H	SF	rs
01/12/1986	1	http://www.ntsb.go	GRD	2	NA	DC9		1	1		1																								1										L	ml	ds
25/09/1986	I	http://www.ntsb.go	LDG	2	NA	DC9										1								1						1					1			1							1 H	ml	ds
31/08/1986	F	http://www.ntsb.go	DES	2	NA	DC9						1		1																															N	ml	ds
21/07/1986	Ν	http://www.ntsb.go	CRZ	2	NA	DC9			1														1	1						1											1		1		N	ml	ds
30/05/1986	1	http://www.ntsb.go	DES	2	NA	DC9								1	T				ΙT		IΤ							IT		ΙT	T					T				IΤ					N	ml	ds



		A	ccident	ts								E F	actor	'S										Fac	ctors	(Non-	-Techr	nical)							Comp	tenci	ies			Valid	ation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL Fire	Syst mal	Ops/Type Spec	Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists Def-DBs	Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure	LF.P	Mis A/C State	Mis-Sys	Pilot Incap	SA	Leadership and Teamwork Workload Management	Problem Solving Decision Making	Knowledge Application of	Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training		Checker
17/05/1986	1	http://www.ntsb.go	TO	2	NA	DC9				1			1																										N	ml	ds
13/03/1986	1	http://www.ntsb.go	LDG	2	NA	DC9		1	1	1											1					1				1			1		1				M	ml	ds
21/02/1986	Ν	http://www.ntsb.go	LDG	2	NA	DC9		1	1	1				1							1					1				1					1	1			M	ml	ds
30/12/1985	1	http://www.ntsb.go	TO	2	NA	A300											1		1																				N	AB	AAD
28/05/1985	Ν	http://www.ntsb.go	CRZ	2	NA	A300			1																	1						1		1					M	AB	AAD
03/11/1985	Ν	http://ntsb.gov/ntst	d CLB	2	NA	B7312			1																														N		ML
25/09/1985	Ν	http://ntsb.gov/ntst	bLDG	2	NA	B7312		1	1 1	1				1								1			1	1				1				1	1			1	M		ML
27/06/1985	1	http://www.ntsb.go	CRZ	2	NA	B7312													1																				N		ML
16/06/1985	Ν	http://ntsb.gov/ntst	bCRZ	2	NA	B7312		1	1																					1		1			1				н		ML
12/04/1985	1	http://www.ntsb.go	TO	2	NA	B7312	1											1	1																				N		ML
23/02/1985	1	http://www.ntsb.go	CLB	2	NA	B7312																					1				1								N		ML
12/15/1985	Ν	Probable Cause	APR	2	NA	B747G2													1	1																			N		
4/25/1985	I	Probable Cause	GRD	2	NA	B747G2												1	1							1								1	1				M		
11/28/1985	I	Probable Cause	CLB	2	NA	B747G2											1	1	1																				N		
9/15/1985	1	Probable Cause	LDG	2	NA	B747G2																				1				1			1					ŕ	I H		
2/19/1985	Ν	Probable Cause	CRZ	2	NA	B747G2			1 1					1 1	1											1	1			1				1		1		i i i	I H		
9/8/1985	I	Probable Cause	GRD	2	NA	DC10	1 1																																N	SF	rs
9/3/1985	1	Probable Cause	CRZ	2	NA	DC10											1	1																					N	SF	rs
8/7/1985	1	Probable Cause	CLB	2	NA	DC10											1																						N	SF	rs
6/27/1985	Ν	Probable Cause	TO	2	NA	DC10		1											1																				N	SF	rs
6/2/1985	I	Probable Cause	CRZ	2	NA	DC10													1																				N	SF	rs
5/28/1985	Ν	Probable Cause	CLB	2	NA	DC10													1																				N	SF	rs
19/10/1985	1	http://www.ntsb.go	CLB	2	NA	DC9											1		1																				N	ml	ds
06/09/1985	F	http://www.ntsb.go	TO	2	NA	DC9											1		1		1					1				1			1			1		i i i	I H	ml	ds
02/07/1985	1	http://www.ntsb.go	CLB	2	NA	DC9																					1												N	ml	ds
26/03/1985	1	http://www.ntsb.go	CLB	2	NA	DC9													1																				N	ml	ds
15/03/1985	1	http://www.ntsb.go	APR	2	NA	DC9				1																													M	ml	ds
10/02/1985	I	http://www.ntsb.go	APR	2	NA	DC9			1					1												1				1			1		1			1	M	ml	ds
05/02/1985	Ν	http://www.ntsb.go	GRD	2	NA	DC9			1								1			1	1					1				1					1			í	Н	ml	ds
31/01/1985	1	http://www.ntsb.go	TO	2	NA	DC9		1	1								1				1										1				1	1			M	ml	ds
29/08/1984	1	http://www.ntsb.go	CLB	2	NA	B7312											1																						N		ML
09/07/1984	I	http://www.ntsb.go	CLB	2	NA	B7312													1																				N		ML
27/06/1984	1	http://www.ntsb.go	UNK	2	NA	B7312													1		1					1									1				M		ML
08/03/1984	1	http://www.ntsb.go	LDG	2	NA	B7312			1	1			1	1																									N		ML
1/1/1984	1	Probable Cause	CRZ	2	NA	B747G2				1		1																											N		
11/16/1984	N	Probable Cause	то	2	NA	B747G2													1		1					1						1							М		
1/18/1984	1	Probable Cause	TO	2	NA	B747G2	1	1	1				1	1																						_			N		
11/1/1984	1	Probable Cause	GRD	2	NA	B747G2	1			1				1												1					+		1			_			L		1
5/11/1984		Probable Cause	10	2	NA	B747G2											1		1																	$\rightarrow$			N		
4/14/1984	1	Probable Cause	CLB	2	NA	B747G2													1																				N		
12/20/1984	1	Probable Cause	APR	2	NA	B747G2						1			1							1	1 1																U		
6/11/1984		Probable Cause	APR	2	NA	B747G2													1							1					+		1			_			M		1
9/29/1984		Probable Cause	CLB	2	NA	B747G2											1		1																				N		
9/15/1984		Probable Cause	IDES	2	INA	IDC10													1			1									1								N	SF	rs





		A	ccident	ts									Facto	ors										Fa	ictors	s (Non-	-Techr	nical)							Comp	eten	icies			Vali	dation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Crosswind	ATC	Loss of comms	Traffic R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Syst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Dilot Incen	Communication	SA Loodorobin cond	Leadersnip and Teamwork Workload Management	Problem Solving Decision Making	Knowledge Asselication of	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
20/12/1983	F	http://www.ntsb.go	LDG	2	NA	DC9	1		1		1			1																							_		N	ml	ds
18/12/1983	1	http://www.ntsb.go	TO	2	NA	DC9											1		1 1																		_		N	ml	ds
09/11/1983	1	http://www.ntsb.go	LDG	2	NA	DC9		1			1			1							1					1				1			1		1				M	ml	ds
25/06/1983	1	http://www.ntsb.go	GRD	2	NA	DC9	1	1										1	1															_					N	ml	ds
21/06/1983	N	http://www.ntsb.go	GRD	2	NA	DC9	1																														_		N	ml	ds
02/06/1983	F	http://www.ntsb.go	CRZ	2	NA	DC9												1	1 1		1					1						1			1		_		н	ml	ds
28/05/1983	1	http://www.ntsb.go	DES	2	NA	DC9											1				1					1					1					1 1			H	ml	ds
17/03/1983	1	http://www.ntsb.go	CLB	2	NA	DC9			1																												_		N	ml	ds
17/03/1983	1	Probable Cause	CLB	2	NA	DC9													1																		_		N	SF	rs
07/02/1983	1	http://www.ntsb.go	LDG	2	NA	DC9			1					1							1					1				1			1		1		_		н	ml	ds
17/04/1982	N	http://aviation-safe	GRD	2	ME	A300											1		1 1															_					N	AB	AAD
28/12/1982	1	http://www.ntsb.go	APR	2	NA	B7312								1							1					1				1			1			1			1 H		ML
09/12/1982	N	http://ntsb.gov/ntsl	bGRD	2	NA	B7312	1	1													1					1				1						1			1 H		ML
05/12/1982	1	http://www.ntsb.go	APR	2	NA	B7312		1	1																	1				1					1				1 M		ML
02/11/1982	N	http://ntsb.gov/ntsl	bCLB	2	NA	B7312		1	1																														U		ML
12/08/1982	1	http://www.ntsb.go	APR	2	NA	B7312								1												1				1			1				_		1 H		ML
05/08/1982	1	http://www.ntsb.go	TO	2	NA	B7312													1																				N		ML
15/02/1982	1	http://www.ntsb.go	APR	2	NA	B7312			1	1	1			1		1			1		1					1				1			1			1			1 H		ML
13/01/1982	F	http://ntsb.gov/ntsl	ЬΤΟ	2	NA	B7312		1	1					1							1					1				1	1		1			1			1 H		ML
8/21/1982	1	Probable Cause	TO	2	NA	DC10											1	1	1																				N	SF	rs
7/16/1982	N	Probable Cause	CRZ	2	NA	DC10			1																														N	SF	rs
5/26/1982	N	Probable Cause	GRD	2	NA	DC10	1																														_		N	SF	rs
2/3/1982	N	Probable Cause	TO	2	NA	DC10												1	1		1					1				1						1			1 H	SF	rs
12/30/1982	1	Probable Cause	CLB	2	NA	DC10			1																														N	SF	rs
11/18/1982	N	Probable Cause	GRD	2	NA	DC10																																	N	SF	rs
23/01/1982	F	Probable Cause	LDG	2	NA	DC10		1			1															1				1						1			1 H	SF	rs
18/12/1982	1	http://www.ntsb.go	LDG	2	NA	DC9		1	1																														U	ml	ds
01/12/1982	1	http://www.ntsb.go	CRZ	2	NA	DC9																					1												N	ml	ds
18/10/1982	I	http://www.ntsb.go	TO	2	NA	DC9													1																				N	ml	ds
05/07/1982	1	http://www.ntsb.go	TO	2	NA	DC9													1																				N	ml	ds
22/05/1982	N	http://www.ntsb.go	DES	2	NA	DC9			1												1																		N	ml	ds
02/06/1981	1	http://www.ntsb.go	CRZ	2	NA	A300			1																														N	AB	AAD
06/02/1981	F	http://www.ntsb.go	GRD	2	NA	A300																																	U	AB	AAD
23/10/1981	1	http://www.ntsb.go	GRD	2	NA	B727									1 1																								L	IG	AP
13/10/1981	1	http://www.ntsb.go	GRD	2	NA	B727															1																		N	IG	AP
12/10/1981	1	http://www.ntsb.go	GRD	2	NA	B727	1 1	1													1					1				1			1						M	IG	AP
11/09/1981	1	http://www.ntsb.go	GRD	2	NA	B727															1																		N	IG	AP
25/08/1981	1	http://www.ntsb.go	GRD	2	NA	B727			1																	1				1			1			1	_		Н	IG	AP
17/08/1981	1	http://www.ntsb.go	GRD	2	NA	B727			1												1					1				1					1				н	IG	AP
27/06/1981	1	http://www.ntsb.go	GRD	2	NA	B727													1																				N	IG	AP
05/06/1981	1	http://www.ntsb.go	GRD	2	NA	B727			1																														N	IG	AP
03/06/1981	1	http://www.ntsb.go	GRD	2	NA	B727	1	1													1					1													U	IG	AP
04/05/1981	1	http://www.ntsb.go	GRD	2	NA	B727	1	1													1					1				1			1			1	1		М	IG	AP
14/04/1981	1	http://www.ntsb.gc	GRD	2	NA	B727	1 1	1													1											T							L	IG	AP

		Ac	ccident	ts										Facto	ors											F	Factors	s (No	n-Tec	hnica	al)							Comp	beter	ncies			Valio	dation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear	Crosswind ATC	NAV	Loss of comms	Iraffic R/W Incursion	Poor Visibility	Upset	vvake vortex Touroin	Birds	Eng Fail	MEL Fire	Syst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State	Pilot Incap	Communication	حم Leadership and Teamwork	leanwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
09/04/1981	1	http://www.ntsb.go	GRD	2	NA	B727															1		1														_			1		M	IG	AP
08/04/1981	1	http://www.ntsb.go	GRD	2	NA	B727															1															-	-					N	IG	AP
12/02/1981	1	http://www.ntsb.go	GRD	2	NA	B727	1																													-						N	IG	AP
31/01/1981	1	http://www.ntsb.go	GRD	2	NA	B727															1																					N	IG	AP
14/01/1981	1	http://www.ntsb.go	GRD	2	NA	B727	1		1														1					1							1							M	IG	AP
2/11/1981	N	http://www.ntsb.go	GRD	2	NA	B747G2	1																					1				1	1		1						1	1 M		
12/18/1981	1	http://www.ntsb.go	CRZ	2	NA	B747G2													1		1		1					1					1			1			1	1		н		
7/5/1981	1	http://www.ntsb.go	CRZ	2	NA	B747G2													1		1												1									U		
7/9/1981	1	http://www.ntsb.go	APR	2	NA	B747G2															1																					N		
9/7/1981	F	http://www.ntsb.go	GRD	2	NA	DC10																																				N	SF	rs
9/22/1981	N	http://www.ntsb.go	TO	2	NA	DC10													1																							N	SF	rs
9/20/1981	F	http://www.ntsb.go	CRZ	2	отн	DC10																																				N	SF	rs
5/20/1981	F	http://www.ntsb.go	GRD	2	NA	DC10																																	$\square$			N	SF	rs
4/3/1981	N	http://www.ntsb.go	CRZ	2	NA	DC10			1																														$\square$			N	SF	rs
11/17/1981	1	http://www.ntsb.go	то	2	NA	DC10													1																				$\square$			N	SF	rs
10/17/1981	1	http://www.ntsb.go	CLB	2	NA	DC10			_					_																				1			_		$\square$			N	SF	rs
01/10/1981	1	http://www.ntsb.go	CLB	2	NA	DC10			_												1					_										_	_		++			N	SF	rs
31/01/1981		http://www.ntsb.go	CLB	2	NA	DC10													1																	_	+	+	$\vdash$				SF	rs
07/10/1981	1	http://www.ntsb.go	LDG	2	INA	DC9								_																						_	—	+	$\mapsto$				mi	ds
13/08/1981	N	http://www.ntsb.go	GRD	2	INA NA	DC9	1 1		-	+	_	_		_			+	_			4	_				_			_					_		—	+	+	++				mi	ds
18/06/1981	N	http://www.ntsb.go		2	INA NA	009		_	1			-	+	_	-		-	_			1			_	+	_		+				-		_		+	+	+	$\mapsto$				mi	ds
18/05/1981	IN	http://www.ntsb.go		2	INA	009			1			_		_			-	_				1		_		_		4				_	4			-	_	+	++				mi	ds
21/11/1980	-	http://www.ntsb.go		2	INA	B/2/		-	1		_	-		_	-		-		+		+ +	_	1			-							1	_	1	-	+	+	⊢			H	IG IC	AP
02/00/1080	-	http://www.ntsb.go		2	IN/A	D/2/		-	1		-	+	+	-	-		+	-		_	+ +	_	- 1		+	_						-	1	+	1	+	+	1	++				IG	
03/09/1980		http://www.ntsb.go	GRD	2	NA	D/2/ D727			1		_	-		-	-		-	-	+		+ +	_				_						-	1	-		—	+	+	$\vdash$				IG	
11/04/1980	<u>-</u>	http://www.ntsb.go	CPD	2	NA	D727						-		-			-	-			1	_				-										—	+	+	$\vdash$				IG	
15/01/1980	1	http://www.ntsb.go	GRD	2	ΝA	B727			1			-			-		+				1	-			+ +	-		+					1			+	+	+	++				IG	
9/2/1980	i -	http://www.ntsb.go	GRD	2	NA	B747G2	1 1	1			_	+		-	-		+	-		-	+ +	-	-	_		-		1				-	1	+	1	+	+	+ +	++				10	
12/15/1980	i -	http://www.nteb.go	TO	2	NΔ	B747G2					-	-		-			+	1	1		+ +	-	-											+		—	-	+ +	++					
9/16/1980	N	http://www.ntsb.go	TO	2	FUR	DC10		-	-			-					-			1		-												-		+	+	+ +	++				SE	rs
7/24/1980	i.	http://www.ntsb.go	CRZ	2	NA	DC10			-			-			-		+				1	-						++						-		+-	+	+ +	++				SF	rs
10/09/1980	ti -	http://www.ntsb.go	CLB	2	NA	DC9			-			-					+			-		_	-									-	1	+		+-	+	+ +	$\vdash$			1 N	ml	ds
15/07/1980	N	http://www.ntsb.go	DES	2	NA	DC9			1								-					1														+	+	+ +	$\vdash$			. U	ml	ds
07/06/1980	N	http://www.ntsb.go	GRD	2	NA	DC9	1					-					-																			+	+	+ +	$\vdash$			Ū	ml	ds
02/05/1980	N	http://www.ntsb.go	LDG	2	NA	DC9			-			-					+						1	1			1	1					1	-	1		+	1	$\square$			1 M	ml	ds
04/04/1980	N	http://www.ntsb.go	DES	2	NA	DC9			1						-							1										1					+		$\square$			U	ml	ds
20/03/1980	1	http://www.ntsb.go	CRZ	2	NA	DC9															1																					N	ml	ds
17/03/1980	N	http://www.ntsb.go	LDG	2	NA	DC9		1	1		1												1					1					1					1		1		M	ml	ds
21/02/1980	1	http://www.ntsb.go	TO	2	NA	DC9																											1									N	ml	MS
01/10/1979	1	http://www.ntsb.go	GRD	2	NA	B727																												1								N	IG	AP
15/09/1979	1	http://www.ntsb.go	GRD	2	NA	B727																1																				N	IG	AP
07/08/1979	1	http://www.ntsb.go	GRD	2	NA	B727															1																					N	IG	AP
21/06/1979	1	http://www.ntsb.go	GRD	2	NA	B727	1 1										T		IT									1					1		1				( T			M	IG	AP



		A	ccident	ts									F	acto	rs											Facto	ors (N	on-Te	echnic	al)						(	Compe	tencies			Val	dation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition Adverse Weather/Ice	Windshear	Crosswind ATC	NAV	Loss of comms	Iranic R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds	ciig raii MEL	Fire	Syst mal Ops/Type Spec	Cabin Cabin	Def Manuals	Def-Ops data	Def-Chk lists	Def-DBs	Def-Proc's Fatique	CRM Physio	Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA Leadership and Teamwork	Workload Management	Problem Solving Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and	Manual Aircraft Control Improved Training	Analyst	Checker
19/04/1979	1	http://www.ntsb.go	GRD	2	NA	B727			1																							1								H	IG	AP
04/04/1979	1	http://www.ntsb.gc	GRD	2	NA	B727														1	1	1						1	1			1				1		1		M	IG	AP
02/03/1979	1	http://www.ntsb.go	GRD	2	NA	B727														1	1																			N	IG	AP
23/02/1979	1	http://www.ntsb.go	GRD	2	NA	B727			1													1						1						1				1		н	IG	AP
15/02/1979	1	http://www.ntsb.go	GRD	2	NA	B727														1	1							1				1			1 1					Н	IG	AP
15/02/1979	1	http://www.ntsb.gc	GRD	2	NA	B727		1			1		1	1														1							1 1					H	IG	AP
08/01/1979	1	http://www.ntsb.go	GRD	2	NA	B727														1	1																			N	IG	AP
17/11/1979	1	Probable Cause	GRD	2	NA	B727			1													1						1				1			1	1	1			н	IG	AP
07/11/1979		Probable Cause	GRD	2	NA	B727		1					1	1																										U	IG	AP
6/1/1979		http://www.ntsb.go	CRZ	2	ASIA	B747G2														1	1																			Ú	SF	DB
2/15/1979	N	http://www.ntsb.go	LDG	2	NA	B747G2					1		1																											U		
3/14/1979	1	http://www.ntsb.go	CRZ	2	NA	B747G2																											1							U		
9/16/1979	1	http://www.ntsb.gc	LDG	2	EUR	B747G2																						1				1			1 1					1 H		-
4/16/1979	N	http://www.ntsb.go	TO	2	EUR	B747G2		1	1											1	1							1				1 1						1		1 H		
8/29/1979	1	http://www.ntsb.go	TO	2	NA	B747G2														1	1										1									U		
12/27/1979	N	http://www.aaib.go	LDG	2	EUR	B747G2			1		1							1		1 1	1											1								1 M		
9/9/1979	1	http://www.ntsb.go	TO	2	NA	B747G2												1		1 1	1																			N		
9/30/1979	1	http://www.ntsb.go	DES	2	OTH	B747G2																											1							U		
5/25/1979	F	http://www.ntsb.go	CLB	2	NA	DC10												1		1	1																			N	SF	rs
11/11/1979	1	http://www.ntsb.go	CLB	2	EUR	DC10														1	1	1						1				1						1		1 H	SF	rs
10/31/1979	F	http://www.ntsb.go	LDG	2	NA	DC10	1	1	1		1				1							1						1				1			1			1		1 H	SF	rs
20/01/1979	1	http://www.ntsb.go	CRZ	2	NA	DC10												1																						N	SF	rs
30/08/1979	1	http://www.ntsb.go	GRD	2	NA	DC9	1	1														1						1							1	-	1			U	ml	ds
21/04/1979	N	http://www.ntsb.go	LDG	2	NA	DC9																1						1				1			1					1 M	ml	ds
09/04/1979	N	http://www.ntsb.go	CRZ	2	NA	DC9																1																		N	ml	ds
22/03/1979	1	http://www.ntsb.go	LDG	2	NA	DC9		1	1 1						1							1						1				1			1		1			1 M	ml	ds
09/02/1979	N	http://www.ntsb.go	CLB	2	NA	DC9																1						1				1			1					1 H	ml	ds
28/03/1978	F	http://www.ntsb.go	GRD	2	NA	A300		1																																U	MS	AAD
04/10/1978	1	http://www.ntsb.gc	GRD	2	NA	B727	1	1																																N	IG	AP
25/09/1978	1	http://www.ntsb.go	GRD	2	NA	B727					1		1									1						1				1			1			1		Н	IG	AP
17/09/1978	1	http://www.ntsb.gc	GRD	2	NA	B727					1		1	1														1						1						M	IG	AP
07/09/1978	1	http://www.ntsb.gc	GRD	2	NA	B727					1		1	1																										N	IG	AP
15/07/1978	1	http://www.ntsb.gc	GRD	2	NA	B727																											1							N	IG	AP
27/06/1978	1	http://www.ntsb.go	GRD	2	NA	B727		1			1		1	1																										U	IG	AP
21/05/1978	1	http://www.ntsb.gc	GRD	2	NA	B727																1																		N	IG	AP
08/05/1978	I	http://www.ntsb.go	GRD	2	NA	B727			1													1						1							1			1		H	IG	AP
19/04/1978	1	http://www.ntsb.gc	GRD	2	NA	B727			1																															U	IG	AP
03/09/1978	I	http://www.ntsb.gc	GRD	2	NA	B727																																		N	IG	AP
27/01/1978	1	http://www.ntsb.gc	GRD	2	NA	B727																1						1				1						1		H	IG	AP
18/01/1978	I	http://www.ntsb.go	GRD	2	NA	B727														1	1																			N	IG	AP
9/11/1978	1	http://www.ntsb.gc	CRZ	2	UNK	B747G2			1						1																									U		
11/7/1978	1	http://www.ntsb.go	GRD	2	NA	B747G2									1													1				1			1					1 M		
4/16/1978	I	http://www.ntsb.go	DES	2	NA	B747G2												1		1 1	1																			N		
8/8/1978	N	http://www.ntsb.gc	GRD	2	NA	DC10													T																					N	SF	rs

		Acc	cidents									Fa	ictor	s											Facto	ors (	Non-T	echni	cal)							Comp	eten	icies			Vali	dation
Date	Severity	Info Source Link	Phase	Generation Beau Generation	1 Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition Adverse Weather/Ice	Windshear	Crosswind	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility Incet	upset Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Svst mal	Ops/Type Spec	Cabin	Compliance Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-DBs	Def-Proc's Fatique	CRM	Workload Distraction	Pressure D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge Application of	Apprication of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
8/29/1978	1	http://www.ntsb.go	CLB :	2 NA	DC10												1																							N	SF	rs
5/9/1978	1	http://www.ntsb.go	GRD :	2 NA	DC10	1	1																																	N	SF	rs
5/27/1978	Ν	http://www.ntsb.go	CRZ :	2 OTH	DC10			1																																N	SF	rs
4/11/1978	I.	http://www.ntsb.go	TO :	2 NA	DC10														1																					N	SF	rs
3/1/1978	F	http://www.ntsb.go	TO :	2 NA	DC10														1																					N	SF	rs
27/11/1978	1	http://www.ntsb.go	CLB :	2 NA	DC9			1													1						1							1			1			M	ml	ds
12/08/1978	I.	http://www.ntsb.go	CLB :	2 NA	DC9														1																					N	ml	ds
26/07/1978	I	http://www.ntsb.go	CRZ	2 NA	DC9							1																												U	ml	ds
21/07/1978	1	http://www.ntsb.go	LDG :	2 NA	DC9			1		1											1	1					1				1					1	1			M	ml	ds
05/04/1978	N	http://www.ntsb.go	CRZ	2 NA	DC9			1											-		1													_			_			U	ml	ds
10/02/1978		http://www.ntsb.go		2 NA	DC9														1 1		1													_			<u> </u>				ml	ds
31/12/1977	!	http://www.ntsb.go	GRD	2 NA	B/2/														1		1											_		_						N	IG	AP
17/11/19/7	1	nttp://www.ntsb.go	GRD	2 NA	B/2/			1							_			-	1					-		-						_		_	_		_				IG	AP
21/09/1977	1	http://www.ntsb.go	GRD .		B/2/			1				_			_		_		- 1			_		-		+		_	_			_		_	-		-					AP
13/07/1977		http://www.ntsb.go	GRD .		B/2/			4							_		_		1			_						_	_			_		_			-				IG	AP
09/06/1977		http://www.ntsb.go		2 INA 2 NA	B/2/			1				-			_		_	-				_		-			1	-	_		1	_		1		1	<u> </u>				IG	AP
25/05/1977	-	http://www.ntsb.gor	GRD .	2 INA 2 NA	B/2/ B727			1				-	-		_	+ +	_	-		-				-		-	1	-	-		1	-		1		1					IG	
04/03/1977	li –	http://www.ntsb.gol	GRD	2 NA	B727			1				-			_	+ +		-	-					-		-		-	-			-		-	-		_+ <u>+</u> -	_			IG	
11/02/1977	li –	http://www.ntsb.go		2 NA	B727			1				-							-			-		-				-	-			-		-	-		_				IG	
28/01/1977	1	http://www.ntsb.go	GRD	2 ΝΔ	B727			1							-	+ +	-	-	_	-				-		-	1	-			1	-	1		-	1	-+				IG	
25/01/1977	i i	http://www.ntsb.gol	GRD	2 NA	B727		1	1 1				1			_	+ +	-	+	-	-				-		+	1	-	-		1	-	1		-	1	-			M	IG	AP
10/12/1977	i.	http://www.ntsb.go		2 NA	B747G2					1		1			_														-						-		-			<del>- 10</del>		
9/3/1977	i.	http://www.ntsb.gov(		2 NA	B747G2					· ·							1		1													-		-							-	+
8/13/1977	F	http://www.ntsb.go	GRD	2 NA	B747G2	1	1		-		+ +				-	+ +								-		-		-	-			-		-	-		$\pm$			- tū		+
11/17/1977	N	http://www.ntsb.gov1	DG	2 NA	B747G2			1 1		1				1	-	+ +								-		+	1				1	-	1		-	1				1 M	-	+
3/24/1977	1	http://www.ntsb.gov	TO	2 FUR	B747G2														1																					N	-	-
3/27/1977	F	http://www.ntsb.gov(	GRD	2 AFR	B747G2		1	1		1		1		1				+	-					1			1						1	-	-					- lu	-	-
3/27/1977	F	http://www.ntsb.go	то	2 AFR	B747G2			1		1		1		1							1					-	1						1	1			-			H		
8/19/1977	N	http://www.ntsb.gov1	ТО	2 NA	DC10												1																							N	SF	rs
8/1/1977	1	http://www.ntsb.go	CLB	2 NA	DC10			1																																L	SF	rs
7/6/1977	N	Probable Cause [	DES	2 NA	DC10														1											1	1									L	SF	rs
7/28/1977	I	http://www.ntsb.go	TO	2 NA	DC10												1																					_		N	SF	rs
7/10/1977	1	http://www.ntsb.gol	LDG :	2 NA	DC10			1																			1				1									1 H	SF	rs
6/2/1977	1	http://www.ntsb.go	CLB :	2 NA	DC10												1																							N	SF	rs
22/11/1977	I	http://www.ntsb.go	DES	2 NA	DC9																1						1				1		1				1			M	ml	ds
21/08/1977	Ν	http://www.ntsb.go	GRD :	2 NA	DC9	1	1														1						1						1			1				M	ml	ds
04/04/1977	F	http://www.ntsb.go	CRZ	2 NA	DC9			1									1		1								1									1	1			н	ml	ds
27/12/1976	ĺ.	http://www.ntsb.go	GRD :	2 NA	B727														1																					N	IG	AP
07/12/1976	1	http://www.ntsb.go	GRD :	2 NA	B727			1 1																			1				1		1							н	IG	AP
21/11/1976	1	http://www.ntsb.go	GRD	2 NA	B727					1		1	1																											U	IG	AP
02/11/1976	1	http://www.ntsb.go	GRD :	2 NA	B727														1																					N	IG	AP
25/10/1976	1	http://www.ntsb.go	GRD	2 NA	B727			1 1																							1									M	IG	AP
13/10/1976	1	http://www.ntsb.go	GRD	2 NA	B727	1																		1																N	IG	AP



		A	ccident	s								E F	acto	rs										Facto	ors (	Non-Te	echnio	cal)						Compe	tencie	es			Validation
Date	Severity		Phase	Generation		Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL Fire	Syst mal Ons/Type Spec	Cabin	Compliance	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def Dmo's	Def-Proc's Fatique	CRM Physio	Workload Distraction	D.G	LF.P Mis-AFS	Mis A/C State Mis-Sys	Pilot Incap	Communication SA	Leadership and Teamwork Workload Management	Problem Solving Decision Making	Application of Procedures & Knowledge	Flight Management,	Guidance and Automation Manual Aircraft Control	Improved Training	Analyst Checker
08/08/1976	1	http://www.ntsb.go	GRD	2	NA	B727			1																										-			Ν	IG AP
04/08/1976	1	http://www.ntsb.go	GRD	2	NA	B727													1																			N	IG AP
08/02/1976	1	Probable Cause	GRD	2	NA	B727			1											1															-			N	IG AP
12/06/1976	1	http://www.ntsb.go	GRD	2	NA	B727			1																													N	IG AP
25/05/1976	1	http://www.ntsb.go	GRD	2	NA	B727			1																	1				1		1		1				Н	IG AP
18/05/1976	1	http://www.ntsb.go	GRD	2	NA	B727														1																		N	IG AP
27/04/1976	1	http://www.ntsb.go	GRD	2	NA	B727															1					1				1				1	1			Н	IG AP
05/04/1976	1	http://www.ntsb.go	GRD	2	NA	B727		1	1												1					1				1				1	1			Н	IG AP
16/03/1976	1	http://www.ntsb.go	GRD	2	NA	B727		1	1																	1				1		1		1				Н	IG AP
04/03/1976	1	http://www.ntsb.go	GRD	2	NA	B727																				1				1				1	-			Н	IG AP
03/03/1976	1	http://www.ntsb.go	GRD	2	NA	B727			1																													N	IG AP
23/02/1976	1	http://www.ntsb.go	GRD	2	NA	B727				1		1	1																						-			N	IG AP
22/02/1976	1	http://www.ntsb.go	GRD	2	NA	B727			1																													N	IG AP
19/02/1976	1	http://www.ntsb.go	GRD	2	NA	B727													1																			N	IG AP
16/02/1976	1	http://www.ntsb.go	GRD	2	NA	B727			1																										-			N	IG AP
16/02/1976	1	http://www.ntsb.go	GRD	2	NA	B727													1																			N	IG AP
20/01/1976	1	http://www.ntsb.go	GRD	2	NA	B727														1																		N	IG AP
20/01/1976	1	http://www.ntsb.go	GRD	2	NA	B727				1		1																										U	IG AP
17/01/1976	1	http://www.ntsb.go	GRD	2	NA	B727	1													1															-			N	IG AP
5/6/1976	N	http://www.ntsb.go	LDG	2	NA	B747G2															1					1				1			1		1		1	Н	
9/19/1976	N	http://www.ntsb.go	GRD	2	NA	B747G2	1													1															_			U	
12/12/1976	1	http://www.ntsb.go	CLB	2	NA	B747G2													1																+	_		N	
5/27/1976	N	http://www.ntsb.go	GRD	2	NA	DC10	1														1														-			N	SF rs
5/13/1976	1	http://www.ntsb.go	CRZ	2	NA	DC10																									1				-			N	SF rs
3/28/1976	1	http://www.ntsb.go	TO	2	NA	DC10											1																		-	_		N	SF rs
12/26/1976	1	http://www.ntsb.go	LDG	2	NA	DC10		1																		1				1					+		1	H	SF rs
02/01/1976	N	http://www.ntsb.go	APR	2	EUR	DC10											1									1				1					-		1	N	SF rs
17/11/1976	N	http://www.ntsb.go	CRZ	2	NA	DC9				1		1																							-			M	ml ds
16/11/1976	N	http://www.ntsb.go	TO	2	NA	DC9												1	1		1					1				1				1	1		1	H	ml ds
12/11/1976	N	http://www.ntsb.go	GRD	2	NA	DC9	1			1											1					1						1	1		-			М	ml ds
23/06/1976	N	http://www.ntsb.go	LDG	2	NA	DC9			1 1	1				1							1					1								1	1			U	ml ds
01/04/1976	1	http://www.ntsb.go	APR	2	NA	DC9				1		1			1						1					1								1	1			M	ml ds
22/12/1975	1	http://www.ntsb.go	GRD	2	NA	B727			1												1					1								1	1			M	IG AP
12/11/1975	1	http://www.ntsb.go	GRD	2	NA	B727			1												1					1				1				1	1			н	IG AP
11/10/1975	1	http://www.ntsb.go	LDG	2	NA	B727													1																			N	IG AP
23/08/1975	1	http://www.ntsb.go	LDG	2	NA	B727													1																1			N	IG AP
16/08/1975	1	http://www.ntsb.go	LDG	2	NA	B727	1												1	1	1					1				1				1	1			н	IG AP
07/08/1975	1	http://www.ntsb.go	LDG	2	NA	B727			1																	1						1						н	IG AP
24/07/1975	1	http://www.ntsb.go	LDG	2	NA	B727							-						1																+			N	IG AP
24/06/1975	1	http://www.ntsb.go	LDG	2	NA	B727			1	1											1					1						1		1	+		-+	н	IG AP
18/06/1975	1	http://www.ntsb.go	LDG	2	NA	B727							1						1																1			N	IG AP
06/05/1975	1	http://www.ntsb.go	LDG	2	NA	B727	1					1									1					1						1		1	1			Н	IG AP
06/05/1975	N	http://www.ntsb.go	LDG	2	NA	B727	1 1																												1			N	IG AP
04/02/1975	N	http://www.ntsb.go	LDG	2	NA	B727													1																1	_		N	IG AP

		Ac	ccident	ts									Fa	icto	′S											Factor	rs (No	on-Te	chnic	al)							Comr	bete	ncies			Validati	ion
Date	Severity		Phase	Generation	Region	1 Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	vundsnear Crosswind	ATC	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility Inset	Wake Vortex	Terrain	Birds	Eng Fail MEL	Fire	Syst mal Ops/Type Spec	cabin	Compliance	Def Manuals Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique	CRM Physio	Workload Distraction Pressure	D.G	Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA Leadership and	Teamwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker	
08/01/1975	N	http://www.ntsb.go	LDG	2	INA	B727			1		1												1				1					1			1	_			1		Н	IG AP	5
12/14/1975	1	http://www.ntsb.go	CRZ	2	отн	B747G2														1																_	+				N	SF DB	8
12/16/1975	N	http://www.ntsb.go	GRD	2	NA	B747G2	1	1 1	1	1				+																		1			-		+	+			1	SF DB	B
7/12/1975	N	http://www.ntsb.go	DES	2	ОТН	B747G2			1					+			-						_						-		_				-		+	+			Ū		_
10/21/1975	1	http://www.ntsb.go	TO	2	NA	B747G2								+			-			1			-						-		_		-		+	-	+	+			- N		
7/17/1975	fi	http://www.ntsh.go	CRZ	2	NA	B747G2							-	-					-				-														+	+					
9/11/1975	ti –	http://www.ntsb.go	TO	2	FUR	B747G2							-	+		-	-		-				-	_					-		-		-		+	-	+	++					
8/24/1975	ti	http://www.ntsb.go	CBZ	2	OTH	B747G2		_		_			-	+		_	-	1		1 1			-	_			+ +	_	-		-		-		+	-	+	++					_
0/15/1075	N	http://www.ntob.go		2		P747G2			1				-	+		-							-	_				-	-		_		-		+	+	+	+					
0/8/1075	N	http://www.ntsb.go		2	NA	B747G2								+		_			-				-	_					-		_				+	+	+	++					
9/17/1975		http://www.ntsb.go		2	NA	DC10		_	+ +	_			-	+		_	-	1		1			_	_		+ +	+ +	_	-	+	_		-		+	+	+-	++				SE re	
8/25/1975	N	http://www.ntsb.go		2	NΔ	DC10			+ +	-			-	+		-	-	1		1			-	_				-	-		-		-		+	+	+	++			t ti	SF re	_
7/25/1975	1	http://www.ntob.go		2	NA	DC10						-	-	-		-		1					-								_		-			-+	+	+				SE re	_
7/19/1075	-li	http://www.ntsb.go		2	NA	DC10			1	_			-	+		_	-						-	_			+ +		-	+	-		-		+	+	+-	++				SE re	_
7/15/1975	+i	http://www.ntsb.go		2	NA	DC10		_		_			-	+		_	-		-	1	-		_	_				_	-		_		-		+	+	+	++				SE re	
2/12/1075	N	http://www.ntsb.go		2	N/A	0010			1 1					-			-		-		-			_				-	-		_		_		+	-+	+	++				01 13	
3/13/19/3		http://www.ntsb.go		2	IN/A	0010								+		_	-		-				_	_				_	-		_				+	$\rightarrow$	+	+				OF IS	
2/20/19/3	N	http://www.ntsb.go		2	IN/A	0010		_	1	_		-	-	+		_	-		-			-	-					-	-		-		-	-	+	+	+	++					_
11/3/19/3	IN N	http://www.ntsb.go		2	IN/A	0010		_		_	1		1	-		_	-		-		-	-	_	_				_	-		_		_	-	+	+	+	+	·'				
11/20/13/3	N	http://www.ntsb.go		2	N/A	0010				_	<u> </u>		- 1	-		_		1 1					_	_			+	_	-		_				+		+	+				01 13	
10/16/1075	IN N	http://www.ntsb.go		2	IN/A	0010		1		_			-	+		_	-	1 1		1			-	_				_	-		-				+	+	+	++				OF IS	
10/16/1975	IN	http://www.ntsb.go	GRD	2	INA	0010		1	4	_			_	-	4	_	-		_	1	-	-	_	_				_	-		_	4	_		_	$\rightarrow$	-	++	'			SF IS	
31/12/19/5		http://www.ntsb.go	LDG	2		009		-	1	_			_	-		_			_		_			_					-		_	1	_			$\rightarrow$		++				mi us	<u></u>
29/11/19/5	-	http://www.ntsb.go	LDG	2	INA	009		1	1	_			_	-	4	_			_		_		4	- 1					-		_		_			$\rightarrow$	1	4	4			mi as	<u></u>
07/11/19/5	-	http://www.ntsb.go	LDG	2	INA	009		1	1	_			_	-	1	_	-		_			_	1	1					-		_				4	$\rightarrow$	+	+			H H	mi as	-
29/09/1975		http://www.ntsb.go	GRD	2	INA	DC9								-		_				1									-		_				$\rightarrow$	$\rightarrow$	<u> </u>	+	<u> </u>			mi as	<u>,                                     </u>
03/08/1975	1	http://www.ntsb.go	CRZ	2	INA	DC9			1							_																			_	_	1	4	. <u> </u>		н	mi as	1
14/12/1974	N	http://www.ntsb.go	LDG	2	NA	B727			1					-		_				1			1				1					1			_	$\rightarrow$	1	$\square$	1		H	IG AP	2
01/12/1974	N	http://www.ntsb.go	LDG	2	NA	B727			1		1		_	-									1	_	1		1				_		_		<u>+</u>	$\rightarrow$	1	4			HH-	IG AP	2
01/12/19/4	N	http://www.ntsb.go	LDG	2	NA	B/2/								-	1							_	1				1		-			1			_	$\rightarrow$	—	+	1		H	IG AP	
01/12/1974	N	http://www.ntsb.go	LDG	2	NA	B727			1	_				-		_						-		_				_			_				_	$\rightarrow$	<u> </u>	$\vdash$			N	IG AP	2
25/11/1974	N	http://www.ntsb.go	LDG	2	NA	B727	1 1							-		_						_		_					-				_		_	$\rightarrow$		$\vdash$	'		N	IG AP	2
17/11/1974	N	http://www.ntsb.go	LDG	2	NA	B727			1																													$\square$	'		N	IG AP	2
21/09/1974	N	http://www.ntsb.go	LDG	2	NA	B727			1																																N	IG AP	2
03/08/1974	N	http://www.ntsb.go	LDG	2	NA	B727																								1											U	JS AP	2
10/07/1974	N	http://www.ntsb.go	LDG	2	NA	B727														1																					N	IG AP	2
30/04/1974	N	http://www.ntsb.go	LDG	2	NA	B727														1																					N	IG AP	è.
05/04/1974	N	http://www.ntsb.go	LDG	2	NA	B727																								1											N	IG AP	_ د
01/04/1974	Ν	http://www.ntsb.go	LDG	2	NA	B727			1																																N	IG AP	2
04/01/1974	N	http://www.ntsb.go	LDG	2	NA	B727														1																					N	IG AP	د
11/17/1974	1	http://www.ntsb.go	CLB	2	NA	B747G2												1		1 1																					U		
2/2/1974	F	http://www.ntsb.go	CRZ	2	NA	B747G2										L						1																			N		
11/21/1974	Ν	http://www.ntsb.go	GRD	2	NA	B747G2	1	1																			1	1				1			1	_					1 M		
5/4/1974	1	http://www.ntsb.go	CLB	2	NA	B747G2														1																					N		
3/17/1974	1	http://www.ntsb.go	CRZ	2	OTH	B747G2														1 1		1																			U		



		A	ccident	ts									F	acto	rs										Fa	actoi	rs (Non	-Tech	hnica	)						Con	npete	encies			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Adverse Weather/Ice	Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birus Eng Fail	MEL	Fire Svet mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State Mis-Sys	Pilot Incap	Communication SA	Leadership and Teamwork Workload Management	Problem Solving	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
7/11/1974	Ν	http://www.ntsb.go	GRD	2	NA	B747G2	1	1										1		1							1					1		1						1 M	
9/21/1974	N	http://www.ntsb.go	CRZ	2	OTH	B747G2			1																															U	
11/26/1974	N	http://www.ntsb.go	GRD	2	EUR	B747G2														1																				N	
4/16/1974	N	http://www.ntsb.go	GRD	2	NA	B747G2	1																																	U	
7/18/1974	1	http://www.ntsb.go	APR	2	AUS	B747G2														1																				U	
7/8/1974	N	http://www.ntsb.go	CLB	2	NA	DC10												1		1																				N	SF rs
5/14/1974	1	http://www.ntsb.go	DES	2	NA	DC10			1											1																				N	SF rs
10/3/1974	1	http://www.ntsb.gc	DES	2	NA	DC10													1	1		1					1					1			1			1		н	SF rs
19/12/1974	1	http://www.ntsb.go	LDG	2	NA	DC9														1																	+			N	ml ds
21/11/1974	N	http://www.ntsb.go	GRD	2	NA	DC9		1																													+			N	ml ds
05/11/1974		http://www.ntsb.go	DES	2	NA	DC9														1 1		1														-	+			N	ml ds
11/09/1974	F	http://www.ntsb.gc	APR	2	NA	DC9											1					1					1					1				1		1		н	ml ds
01/09/1974	N	http://www.ntsb.go	CRZ	2	NA	DC9			1													1															-			U	ml ds
20/04/1974		http://www.ntsb.go	TO	2	NA	DC9												1		1					+ +									_		-	+			N	ml ds
06/04/1974	1	http://www.ntsb.gc	CRZ	2	NA	DC9																							_	1						-	+			N	ml ds
21/02/1974	N	http://www.ntsb.gc	DES	2	NA	DC9			1													1 1		1			1									1	+	1		M	ml ds
15/02/1974	N	http://www.ntsb.gc	CRZ	2	NA	DC9			1				-			_		-	-	-		1					-		-					_			_	-		1 U	ml ds
22/12/1973	N	http://www.ntsb.gc	DG	2	NA	B727							-					-	+ +	-						_								_		-	+	+		1 Ū	MH AP
20/12/1973	N	http://www.ntsb.gc		2	NA	B727												-		-													1				+	+		N	MH AP
09/12/1973	N	http://www.ntsb.gc	NIDG	2	NA	B727		1										-									1				1			1			+			M	MH AP
07/11/1973	N	Probable Cause	LDG	2	NA	B727			-	+ +	-	-	-				+	-	+ +	-	-	1			+ +	-	1			1		1		1		-	+	1		H H	MH AP
14/08/1973	N	http://www.ptsb.gc	NIDG	2	NA	B727			-		_	-	-		+		+	-	+ +	1						-										-	+	· · · · · · · · · · · · · · · · · · ·		l lü	MH AP
12/08/1973	N	http://www.nteb.gc	NI DG	2	ΝΔ	B727			-									-		1		1							1			1		_		-	+			M	
08/08/1973	N	http://www.ntsb.gc		2	NΔ	B727												-		1																-	+				
27/07/1973	N	http://www.ntsb.gc	NI DG	2	NΔ	B727			-	+ +	1		1		+ +		+	-	+ +			1				_	1			-				_		-	+	1			
10/06/1973	N	http://www.ntsb.gc	NI DG	2	ΝΔ	B727			-	+ +							+	-	-	-	-	1				_	1			-				1 1		-	+	<u> </u>			
10/04/1973	N	http://www.ntob.gc	NLDG	2	NA	D727			1		-		-				1	-				1				_				-		1		1		-	+	1			
17/03/1973	N	http://www.ntsb.gc	NLDG	2	NA	B727			1				-				<u> </u>	-		-	-				+ +											-	+				
03/03/1973	N	http://www.ntsb.gc	UDG	2	NA	B727		1	1		_	-	-	-	+ +		+	-	-	-	-		-		+ +		1			_		1		1		-	+	<u> </u>			
19/01/1973	N	http://www.ntsb.gc	NI DG	2	ΝΔ	B727			-		-	-	-				+	-	-	1		1				_	1			-		1			1	-	+	1			
0/17/1073	1	http://www.ntob.gc	CPD	2	NA	B747C2		1			-		-		1											_				-		1		1		-	+	1		1 M	
0/4/1073	N	http://www.ntsb.gc		2		B747G2			1			-	-				+	-					-		+ +											-	+				
4/26/1073	N	http://www.ntsb.gc		2	NA	B747G2			1		_	-	-	-	+ +		+	-	-	-	-		_		+ +					_				_		-	+	<u> </u>			
4/20/19/3	IN N	http://www.nisb.gc		2	N/A NIA	DC10	_		1				-	-	+		+	_	-	-	-		_				1		1	_				_	1		+	1			SE 69
7/9/10/19/3	IN	http://www.msb.go		2	NA	DC10			_	+			-	-	+			_		1	-	1			+			+						_			+				01 18
7/8/19/3	1	http://www.ntsb.gc		2	INA				_			_	_	_			+	_		1	_	1	_									4				_	-	<u> </u>			SF IS
5/9/19/3		http://www.ntSb.gc		2	NA	DC10			_	+	_		-	_	+		+	+	+	-	-			+	+	_	1	+		_		1	-	_	+	+	-	<del> </del>		I H	
5/7/19/3		http://www.ntSb.gc		2	NA	DC10			_	+				-	+		+	_	+	1			-		+	_	+	+		_				_	+	-	+	<u> </u>			
0///19/3		nup.//www.ntsb.gc	UES I	2	INA	0010				+			_	_	+		+	_		1				$\vdash$	+							-				1	+-	<u> </u>	I	IN IN	
3/19/19/3		nttp://www.ntsb.gc	LDG	2	INA	DC10		1	4				_	-	+			_			-		_		+					_		1		_		1	-	-	<u> </u>	I H	SF IS
12/17/19/3	IN I	nttp://www.ntsb.go	APR	2	INA NA	DC10			1	1	_		-	-	+			-		-	-						1			_		1		_		-	+	1		I M	SF IS
11/3/19/3	F	nttp://www.ntsb.go		12	INA NA	0010			-				_	_	+			1		1			-					+		_				_		-	+	<u> </u>			SF IS
21/12/19/3	IN	nup.//www.ntsb.gc		2	INA	009			1				_	_	+			4		-	-		-	$\square$	+									4		1	+-	<u> </u>	I		IIII OS
17/12/1973	N	nttp://www.ntsb.go	10	2	INA	009		1	1				_	_			+	1		1	_		-		+			$ \rightarrow $						1		1	-	+		H	mi ds
2//11/19/3	IIN	Inttp://www.ntsp.ac	MAPR	12	IINA	IDC9			11	11				- 1			1	1	1			11					1 11		I	1	I	1		11		11		1	1	1 IH	mi ds

		Ac	ccident	S										Fact	ors												Factor	′s (No	n-Tec	hnica	ıl)							Co	mpet	encies			Va	lidation
Date	Severity		Phase	Generation	Region	1 Туре	Ground equipment	Ground manoeuvring Runwav/Taxi condition	Adverse Weather/Ice	Windshear	Crosswind ATC	NAV	Loss of comms	Traffic B/W Incursion	Poor Visibility	Upset	Wake Vortex	Terrain Birds	Eng Fail	MEL	Fire Syst mal	Ops/Type Spec	Cabin	Compriance Def Manuals	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State	Pilot Incap	Communication	SA Leadership and	Teamwork	Workload Management Problem Solving	Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and	Manual Aircraft Control Improved Training	Analyst	Checker
27/11/1973	Ν	http://www.ntsb.go	LDG	2	NA	DC9		1	1		1				1								1					1					1			1				1		Н	ml	ds
13/09/1973	1	http://www.ntsb.go	APR	2	NA	DC9												1					1					1					1			1	_	1				H	ml	ds
31/07/1973	1	http://www.ntsb.go	LDG	2	NA	DC9		1															1					1					1					1		1		Н	ml	ds
31/07/1973	F	http://www.ntsb.go	APR	2	NA	DC9			1						1			1					1					1					1			-	-	1		1		M	ml	ds
22/06/1973	1	http://www.ntsb.go	TO	2	NA	DC9															1															-	-		_			N	ml	ds
01/04/1973	Ν	http://www.ntsb.go	CRZ	2	NA	DC9			1														1																			U	ml	ds
08/01/1973	I	http://www.ntsb.go	TO	2	NA	DC9														1	1 1															-						N	ml	ds
08/11/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727		1													1															_						N	MH	AP
30/10/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727															1																-					U	MH	AP
01/10/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727															1																					U	MH	AP
30/09/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727			1														1																			U	MH	AP
19/08/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727															1																					U	MH	AP
12/08/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727	1	1																																		U	MH	AP
26/07/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727			1		1							1																								U	MH	AP
28/06/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727			1																			1							1							U	MH	AP
24/06/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727	1																1																			U	MH	AP
10/06/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727															1																					U	MH	AP
01/05/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727					1												1					1					1				1	1		1		M	MH	AP
19/04/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727																												1								N	MH	AP
11/04/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727															1		1					1					1			1				1		M	MH	AP
19/02/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727																																				U	MH	AP
10/01/1972	Ν	http://www.ntsb.go	LDG	2	NA	B727			1																																	U	MH	AP
11/1/1972	Ν	http://www.ntsb.go	LDG	2	NA	B747G2															1		1					1								1				1		Н	SF	DB
5/24/1972	1	http://www.ntsb.go	LDG	2	NA	B747G2													1	1	1 1																					N		
9/1/1972	Ν	http://www.ntsb.go	GRD	2	NA	B747G2														1	1 1		1					1					1			1				1		H		
4/18/1972	1	http://www.ntsb.go	LDG	2	NA	B747G2															1																					N		
1/4/1972	Ν	http://www.ntsb.go	CRZ	2	NA	B747G2			1																																	U		
3/8/1972	N	http://www.ntsb.go	GRD	2	EUR	B747G2																															_					U		
6/26/1972	1	http://www.ntsb.go	110	2	EUR	B747G2															1																					U	1	
12/15/1972	N	http://www.ntsb.go	LDG	2	NA	B747G2		1										1	1		1												1					$\perp$			1	1 U	1	
11/22/1972	1	http://www.ntsb.go	GRD	2	NA	B747G2		1																				1					1			1		$\perp$	$\rightarrow$			1 H		$\rightarrow$
5/6/1972	Ν	http://www.ntsb.go	CRZ	2	отн	B747G2			1																																	U		
7/14/1972	1	http://www.ntsb.go	CRZ	2	отн	B747G2			1																											_		_						
4/12/1972	Ν	http://www.ntsb.go	CRZ	2	отн	B747G2			1																																	U		
10/19/1972	1	http://www.ntsb.go	DES	2	NA	B747G2			1												1							1								<u> </u>	$\rightarrow$	$\perp$	1	4	-		1	_
11/21/1972	1	http://www.ntsb.go	CRZ	2	NA	B747G2			_												1															$\perp$	$ \rightarrow $	$\perp$	$\perp$	1		L U	1	
8/4/1972		http://www.ntsb.go	DES	2	NA	DC10				+			+								1															+	$\rightarrow$	$\perp$	$\rightarrow$	4		N	SF	rs
7/27/1972	1	http://www.ntsb.go	CLB	2	NA	DC10			_				+		_				1							-+		+						-		+	$\rightarrow$	+	$\rightarrow$	+			SF	rs
6/12/1972	N	nttp://www.ntsb.go	ICLB	2	NA	0010							+		+						1					_		+						-		+	$\rightarrow$	+	+	+	-		SF	rs
5/2/19/2	1	nttp://www.ntsb.go	URZ	2	INA	0010			_	+			+			-		_	1		1	-	$ \vdash $		$\rightarrow$			+						_		+	$\rightarrow$	+	+	+			SF	rs
4/9/1972	1	nttp://www.ntsb.go	LDG	2	INA	0010			_	-			+			-	_	-	1		1					_		+				-		_		+	$\rightarrow$	+	+	+			SF	rs
10/30/1972	-	nttp://www.ntsb.go	ICLB	2	NA	0010	1	_	_						4		_	1	1	_	$\rightarrow$	-				-+	-	+						+		+	$\rightarrow$	+	+	+			SF	rs
20/12/1972	F	nttp://www.ntsb.go	ICLB	2	INA	DC9			_		1			1	1			_		_		-			+									+		_	$\rightarrow$	+	$\rightarrow$	+		N N	ml	as
28/09/19/2	N	nttp://www.ntsb.go	LDG	12	INA	IDC9				1			1 1			1						1	1					1				1	1		1					1	1	1 M	ml	ds



		A	ccident	ts									Fa	ctors										F	actor	rs (Nor	I-Tech	hnica	l)						Com	peter	ncies			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear	Crosswind ATC	NAV	Loss of connes Traffic	R/W Incursion Poor Visibility	Upset	Terrain	Birds	eng raii MEL	Fire	Syst mal Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State Mis-Sys	Pilot Incap	Communication SA	Leadership and Teamwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
03/07/1972	1	http://www.ntsb.go	CRZ	2	NA	DC9													1																				N	ml ds
01/07/1972	1	http://www.ntsb.go	CLB	2	NA	DC9													1																				N	ml ds
14/06/1972	N	http://www.ntsb.go	LDG	2	NA	DC9															1					1				1	1						1		1 M	ml ds
30/05/1972	F	http://www.ntsb.go	APR	2	NA	DC9									1											1							1						M	ml ds
18/05/1972	N	http://www.ntsb.go	LDG	2	NA	DC9			1					1							1					1									1		1		Н	ml ds
10/05/1972	N	http://www.ntsb.go	GRD	2	NA	DC9													1 1																				N	ml ds
19/03/1972	N	http://www.ntsb.go	TO	2	NA	DC9											1		1 1	1																			N	ml ds
13/02/1972	1	http://www.ntsb.go	TO	2	NA	DC9		1									1		1		1					1				1							1		1 M	ml ds
29/12/1971	N	http://www.ntsb.go	LDG	2	NA	B727			1																														U	MH AP
21/12/1971	N	http://www.ntsb.go	LDG	2	NA	B727			1												1					1			1	1 1			1				1	1	M	MH AP
17/11/1971	N	http://www.ntsb.go	LDG	2	NA	B727																																	U	MH AP
04/09/1971	N	http://www.ntsb.go	LDG	2	NA	B727			1							1					1					1				1	1		1				1	1	М	MH AP
19/07/1971	Ν	http://www.ntsb.go	LDG	2	NA	B727		1											1		1					1	ŀ	1		1	1			1		·	1		Н	MH AP
27/06/1971	N	http://www.ntsb.go	LDG	2	NA	B727		1	1									1			1					1				1							1		н	MH AP
08/06/1971	N	http://www.ntsb.go	LDG	2	NA	B727			1																														U	MH AP
25/05/1971	Ν	http://www.ntsb.go	LDG	2	NA	B727													1																				U	MH AP
14/05/1971	N	http://www.ntsb.go	LDG	2	NA	B727			1														1																U	MH AP
14/04/1971	N	http://www.ntsb.go	LDG	2	NA	B727																																	N	MH AP
01/04/1971	N	http://www.ntsb.go	LDG	2	NA	B727													1	1	1																		U	MH AP
29/03/1971	N	http://www.ntsb.go	LDG	2	NA	B727			1														1																U	MH AP
13/03/1971	N	http://www.ntsb.go	LDG	2	NA	B727													1																				U	MH AP
11/03/1971	N	http://www.ntsb.go	LDG	2	NA	B727													1	1																			U	MH AP
26/02/1971	N	http://www.ntsb.go	LDG	2	NA	B727													1																				U	MH AP
15/02/1971	N	http://www.ntsb.go	LDG	2	NA	B727													1	1																			U	MH AP
07/02/1971	N	http://www.ntsb.gc	LDG	2	NA	B727			1												1					1				1					1		1		M	MH AP
02/01/1971	N	http://www.ntsb.go	LDG	2	NA	B727			1														1																U	MH AP
7/23/1971	N	http://www.ntsb.gc	GRD	2	NA	B747G2													1 1	1	1					1					1		1				1		н	
4/26/1971	1	http://www.ntsb.gc	LDG	2	NA	B747G2		1													1					1				1			1				1		н	
2/24/1971	1	http://www.ntsb.go	GRD	2	NA	B747G2		1			1										1					1				1									н	
1/17/1971	1	Probable Cause	CRZ	2	NA	B747G2							_						1											_									N	
5/13/1971	-	http://www.ntsb.go	10	2	NA	B747G2		_					_		-		1		1 1			_	$\vdash$		_					_			_						N	
11/8/19/1	-	nttp://www.ntsb.go	010	2	NA	B/4/G2		_					_				1		1 1			_								_			_						N	
1/14/19/1	1	nttp://www.ntsb.go	LDG	2	NA	B/4/G2		1	1										1																				N	
1/4/1971	1	http://www.ntsb.go	CLB	2	NA	B747G2													1											_									N	
8/24/1971	-	http://www.ntsb.go	010	2	NA	B747G2	_	_					_				1		1 1			_													-				N	
//21/19/1	-	nttp://www.ntsb.go	GRD	2	NA	B74/G2	1	1	_	+	-+	+	_				+	+			1		+	+		1				1			1		-		1		H	
5/20/1971	1	nttp://www.ntsb.go	DUDG	2	INA	B/4/G2			_				-					-						+			+			_			_						N	
0/29/19/1	N	nttp://www.ntsb.go	GRU	2	EUR	B74/G2			-	+	_	-	-		-		+	-	+	_	1	-		+					1				_		-		4			
10/0/1071	N	http://www.ntsb.go		2	INA	B/4/G2			1		_		-			-	+	-	+	_	1		1	+	_				1	1			4	1	1	$\left  \right $	1		1 H	
0/9/19/1	1	nup.//www.ntsb.gc	LDG	2	INA	D747G2			1			-	-	1		_		_			+		+			+ $1$				- P			T		1				т Н	
9/2/19/1	-	nttp://www.ntsb.go	LDG	2	INA	B74/G2	-		-	+	_	-	-			_	+	-				-	+										_		4		4		N	
6/20/1074	I NI	http://www.ntSb.gc	TO	2	AUS	D747G2	$\mapsto$	-	-	+	-+	+	-	$\vdash$	+	-	+	-	+	_	1	-	+	+		+ $1$			$\rightarrow$	-		$\vdash$	_		1	+	1		1 14	
10/20/19/1	IN	http://www.ntsb.go		2	ASIA	D747G2		1	_	+			-		+		+	+		_	+			+			+						_			+			1 14	
10/20/10/1		mup.//www.msb.gc	10	14	INA	014/02				1 1	1	1			1	1	1		1 1			1	1 1	1 1	1	1 1	1	I		- 12				1	1	1 I			I IVI	4   '

		A	ccident	S										acto	ors												Factor	′s (No	n-Teo	chnica	al)							C	omp	eten	icies			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear • •	Grosswind ATC	NAV	Loss of comms	Iramic R/W Incursion	Poor Visibility	Upset	VVARE VOLIEX Torrain	Birds	Eng Fail	Fire	Syst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State	mis-cys Pilot Incap	Communication	SA Lectorobia and	Leadersmp and Teamwork	Workload Management Problem Solving	Decision Making	Knowledge Annlication of	Apprication of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
2/7/1971	Ν	http://www.ntsb.go	CRZ	2	NA	B747G2			1														1		1			1								1	_	1					M	
8/17/1971	1	http://www.ntsb.go	CLB	2	NA	DC10															1																		_		_		N	SF rs
3/19/1971	I	http://www.ntsb.go	CLB	2	NA	DC10															1																			-			N	SF rs
12/4/1971	I	http://www.ntsb.go	LDG	2	NA	DC10														1	1																-			-			N	SF rs
11/26/1971	1	http://www.ntsb.go	GRD	2	NA	DC10																						1									_			1 1			N	SF rs
04/12/1971	F	http://www.ntsb.go	APR	2	NA	DC9					1		1																														U	ml ds
09/10/1971	Ν	http://www.ntsb.go	GRD	2	NA	DC9	1																																				N	ml MS
24/08/1971	I	http://www.ntsb.go	CLB	2	SA	DC9															1		1					1											1	1 1			M	ml ds
18/08/1971	Ν	http://www.ntsb.go	CLB	2	NA	DC9												1																									N	ml ds
23/06/1971	I	http://www.ntsb.go	TO	2	NA	DC9															1																						N	ml ds
22/06/1971	I	http://www.ntsb.go	APR	2	NA	DC9											1						1					1					1			1				1			н	ml ds
18/06/1971	I	http://www.ntsb.go	DES	2	NA	DC9																							1														N	ml ds
06/06/1971	F	http://www.ntsb.go	CLB	2	NA	DC9					1		1		1								1					1								1				1			M	ml ds
01/06/1971	I	http://www.ntsb.go	LDG	2	NA	DC9													1		1							1					1			1							1 N	ml MS
22/05/1971	Ν	http://www.ntsb.go	CLB	2	NA	DC9															1																						N	ml ds
21/05/1971	1	http://www.ntsb.go	CLB	2	NA	DC9															1																						N	ml ds
12/04/1971	1	http://www.ntsb.go	LDG	2	NA	DC9																	1					1					1			1							1 M	ml ds
19/03/1971	1	http://www.ntsb.go	CLB	2	NA	DC9															1																						N	ml ds
17/02/1971	Ν	http://www.ntsb.go	APR	2	NA	DC9									1								1					1		1							1	1		1			Н	ml ds
11/01/1971	Ν	http://www.ntsb.go	LDG	2	NA	DC9									1								1					1					1			1							1 M	ml ds
28/12/1970	N	http://www.ntsb.go	LDG	2	NA	B727																						1					1					1					н	MH AP
16/12/1970	Ν	http://www.ntsb.go	LDG	2	NA	B727															1																						U	MH AP
20/11/1970	Ν	http://www.ntsb.go	LDG	2	NA	B727			1																											$\square$							U	MH AP
17/11/1970	Ν	http://www.ntsb.go	LDG	2	NA	B727															1																						U	MH AP
08/11/1970	N	http://www.ntsb.go	LDG	2	NA	B727			_												1															$\vdash$		$ \rightarrow$	$\rightarrow$	$\rightarrow$			U	MH AP
04/11/1970	Ν	http://www.ntsb.go	LDG	2	NA	B727	1	1													1															$\perp$							U	MH AP
22/10/1970	Ν	http://www.ntsb.go	LDG	2	NA	B727																												1		$\vdash$							N	MH AP
01/10/1970	N	http://www.ntsb.go	LDG	2	NA	B727												_						_										1		$\vdash$		$\rightarrow$		$\rightarrow$			N	MH AP
23/09/1970	Ν	http://www.ntsb.go	LDG	2	NA	B727			_																													$ \rightarrow $		$\rightarrow$			N	MH AP
22/07/1970	N	http://www.ntsb.go	LDG	2	NA	B727			_		_										1								_			_				$\vdash$	$\rightarrow$	$\rightarrow$	$\rightarrow$	+			U	MH AP
28/06/1970	N	http://www.ntsb.go	LDG	2	NA	B727			_		_							_			+	_		_		_		+				_		_		$\vdash$	$\rightarrow$	$\rightarrow$	$\rightarrow$	$\rightarrow$				MH AP
27/06/1970	N	http://www.ntsb.go	LDG	2	NA	B727															+													1		$\vdash$	$\rightarrow$	$\rightarrow$	$\rightarrow$	$\rightarrow$			N	MH AP
16/06/1970	N	http://www.ntsb.go	LDG	2	INA	B/2/																							_							$\vdash$	$\rightarrow$	_	$\rightarrow$	_			N	MH AP
03/06/1970	N	http://www.ntsb.go	LDG	2	NA	B727			_		_							_			1								_			_				$\vdash$	$\rightarrow$	$\rightarrow$	$\rightarrow$	+			U	MH AP
19/05/1970	N	nttp://www.ntsb.go	LDG	2	NA	B/27							$\vdash$	_				+								_	+	+	+	-	$\vdash$			1		++	$\rightarrow$	$\rightarrow$	$\rightarrow$	+				MH AP
18/05/19/0	N	nttp://www.ntsb.go	LDG	2	INA	B/2/		-	-	$ \vdash $		_	$\vdash$	_			_	+	+	_	1	1		_	+		+	+		<u> </u>	+	_			1	⊢	$\rightarrow$	_	$\rightarrow$	+				MH AP
07/05/1970	N	nttp://www.ntsb.go	LDG	2	INA	B/2/		1	1		_	-		_			-	_			+	_		_				1		-		-	1		-	1	$\rightarrow$	1		+			<u>⊢ M</u>	MH AP
27/03/1970	N	nttp://www.ntsb.go	LDG	2	INA	B/2/		-	-	+ +	_	-	+	_	-		-	+	+	-	+	_	-	-	-	_	+				+	-		1		++	$\rightarrow$	-	$\rightarrow$	-				MH AP
10/03/1970	IN N	http://www.ntsb.go	LDG	2	INA	B/2/		1	1		_	-	+	_			-	+	+	-	+	_	1	_				1		-	$\vdash$		1	+		++	$\rightarrow$	1		1			<u>⊢</u> <u>M</u>	MH AP
23/02/1970	IN	http://www.ntsb.go	LDG	2	INA	D121			1			-	+				_	_	+	_				_	1	_	++				$\vdash$				1			-+	$\rightarrow$	+			+	WIT AP
27/01/19/0	N	nttp://www.ntsb.go	LDG	2	INA	B/2/	1 1		-	+		_	+	_	-		-	+	+	-		_		_	-	_	+	1			$\vdash$	-	1		1		$\rightarrow$	+	$\rightarrow$	+			누분	MH AP
8/26/1070	IN	http://www.ntSb.go	ADD	2	INA NA	D121	-	-	-	+	_	-	+	-	-		-	+	+	-	1	_	-		+	_	+	+	+		+			+	1	++	$\rightarrow$	+	$\rightarrow$	+			누분	WIT AP
0/20/19/0	Ľ	http://www.ntsb.go	APR	2	INA	D747G2	-	-	-	+		-	+	_	-		-	+	+						1	_	++	+	-	<u> </u>	$\vdash$				1	++	$\rightarrow$	+	$\rightarrow$	+			+	╉──┼───
10/20/19/0	P 1	mup.//www.ntsb.go	JUKZ	14	INA	D/4/G2			1	1 I.			1 I.					- 1	1		11	1			1		1 1	1 1		1	1 1				1	1 1		. I.			1		I IN	1 1



		A	ccident	ts								Fa	actors											Fa	ctors	(Non	-Techn	ical)							С	ompr	etencies			Valio	dation .
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion	Upset	Wake Vortex	Terrain Birds	Eng Fail	MEL Fire	Syst mal	Ops/Type Spec Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts	Def-Chk lists Def-DRs	Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure D.G	LF.P Mia AFO	Mis-A/C State	Mis-Sys	Pilot Incap	SA	Leadership and Teamwork	Workload Management Problem Solving	Decision Making	Knowledge Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
11/28/1970	1	http://www.ntsb.go	CRZ	2	NA	B747G2													1																				N		
12/4/1970	1	http://www.ntsb.go	CRZ	2	NA	B747G2													1																				N		
12/18/1970	1	http://www.ntsb.go	LDG	2	NA	B747G2													1																				N		
9/19/1970	1	http://www.ntsb.go	GRD	2	NA	B747G2											1	1	1																				N		
8/25/1970	I I	http://www.ntsb.go	CLB	2	NA	B747G2											1	1	1																				U		
6/26/1970	I I	http://www.ntsb.go	GRD	2	NA	B747G2											1	1	1 1	1	1					1					1					1	1		Н		
6/4/1970	I I	http://www.ntsb.go	TO	2	NA	B747G2		1											1		1					1				1						1	1		1 H		
1/21/1970	1	http://www.ntsb.go	GRD	2	NA	B747G2											1	1	1						1														M		
1/10/1970	1	http://www.ntsb.go	GRD	2	NA	B747G2												1																					N		
10/19/1970	1	http://www.ntsb.go	APR	2	NA	B747G2													1																				N		
12/27/1970	Ν	http://www.ntsb.go	CRZ	2	NA	B747G2														1																			U		
12/13/1970	1	http://www.ntsb.go	CLB	2	EUR	B747G2											1	1	1																				N		
10/27/1970	I I	http://www.ntsb.go	GRD	2	NA	B747G2											1	1	1																				N		
12/29/1970	I I	http://www.ntsb.go	APR	2	NA	B747G2													1																				N		
12/12/1970	1	http://www.ntsb.go	GRD	2	NA	B747G2	1																																U		
10/8/1970	1	http://www.ntsb.go	CRZ	2	NA	B747G2													1																				N		
12/1/1970	I I	http://www.ntsb.go	GRD	2	NA	B747G2													1																				N		
5/24/1970	1	http://www.ntsb.go	APR	2	NA	B747G2													1																				U		
2/9/1970	1	http://www.ntsb.go	CRZ	2	OTH	B747G2											1		1																				N		
11/4/1970	Ν	http://www.ntsb.go	CLB	2	NA	B747G2			1																1	1						1							N		
8/15/1970	1	http://www.ntsb.go	TO	2	NA	B747G2													1							1				1					1		1		1 H		
6/11/1970	I	http://www.ntsb.go	CLB	2	NA	B747G2											1	1	1																				N		
5/26/1970	1	http://www.ntsb.go	APR	2	NA	B747G2											1	1	1																				N		
9/18/1970	1	http://www.ntsb.go	TO	2	NA	B747G2											1	1	1																				N		
8/26/1970	1	http://www.ntsb.go	CLB	2	NA	B747G2											1	1																					N		
8/17/1970	1	http://www.ntsb.go	CRZ	2	NA	B747G2											1		1																				N		
10/2/1970	1	http://www.ntsb.go	CLB	2	NA	B747G2											1	1	1																	_			N		
12/30/1970	1	http://www.ntsb.go	CRZ	2	NA	B747G2													1																				N		
29/12/1970	I	http://www.ntsb.go	LDG	2	NA	DC9		1		1												1																	N	ml	ds
14/11/1970	F	http://www.ntsb.go	APR	2	NA	DC9									1																								U	ml	ds
08/09/1970	Ν	http://www.ntsb.go	LDG	2	NA	DC9									1						1					1				1			1		1				M	ml	ds
02/05/1970	F	http://www.ntsb.go	APR	2	NA	DC9											1				1					1	1				1				1		1		M	ml	ds
19/03/1970	1	http://www.ntsb.go	CRZ	2	NA	DC9																					1									_			N	ml	ds
17/03/1970	1	http://www.ntsb.go	CRZ	2	NA	DC9														1																_			N	ml	ds
11/01/1970	Ν	http://www.ntsb.go	APR	2	NA	DC9							1								1	1				1	1			1					1		1		M	ml	ds
13/12/1969	Ν	http://www.ntsb.go	LDG	2	NA	B727														1																_			U	MH	AP
14/11/1969	Ν	http://www.ntsb.go	LDG	2	NA	B727													1																				N	MH	AP
26/09/1969	N	http://www.ntsb.go	LDG	2	NA	B727																																	U	MH	AP
15/09/1969	N	http://www.ntsb.go	LDG	2	NA	B727														1																			U	MH	AP
29/07/1969	N	http://www.ntsb.go	LDG	2	NA	B727															1					1							1				1		M	MH	AP
29/07/1969	N	http://www.ntsb.go	LDG	2	NA	B727		1	1																					1	1								U	MH	AP
20/07/1969	N	http://www.ntsb.go	LDG	2	NA	B727													1																				U	MH	AP
25/06/1969	N	http://www.ntsb.go	LDG	2	NA	B727	1	1		1																1				1					1				M	MH	AP
04/06/1969	N	http://www.ntsb.go	LDG	2	NA	B727									T				IΤ																				U	MH	AP





		A	ccident	s								F	acto	rs										Fac	tors	(Non-	Techn	ical)						Comp	peter	ncies			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL Fire	Syst mal	Ops/Type Spec	Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists Def-DBs	Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure D.G	LF.P Mis-AFS	Mis A/C State	Pilot Incap	Communication	Leadership and Teamwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
23/06/1968	N	http://www.ntsb.go	LDG	2	NA	B727													1																			U	MH AP
12/06/1968	Ν	http://www.ntsb.go	LDG	2	NA	B727						1																										U	MH AP
08/06/1968	Ν	http://www.ntsb.go	LDG	2	NA	B727		1	1																	1								1				M	MH AP
03/06/1968	Ν	http://www.ntsb.go	LDG	2	NA	B727																				1				1		1		1				M	MH AP
02/04/1968	Ν	http://www.ntsb.go	LDG	2	NA	B727			1																													U	MH AP
23/03/1968	N	http://www.ntsb.go	TO	2	NA	B727													1																			U	MH AP
21/03/1968	Ν	http://www.ntsb.go	TO	2	NA	B727															1					1				1 1				1		1		Н	MH AP
02/03/1968	N	http://www.ntsb.go	TO	2	NA	B727						1																										U	MH AP
16/02/1968	N	http://www.ntsb.go	TO	2	NA	B727																								1								M	MH AP
27/12/1968	Ν	http://www.ntsb.go	CLB	2	NA	DC9			1					1							1					1								1		1		M	ml ds
26/12/1968	1	http://www.ntsb.go	LDG	2	NA	DC9										1					1					1				1		1		1				U	ml ds
18/05/1968	I	http://www.ntsb.go	GRD	2	NA	DC9	1 1												1																			N	ml ds
27/03/1968	F	http://www.ntsb.go	LDG	2	NA	DC9						1									1					1						1				1		М	ml ds
12/11/1967	Ν	http://www.ntsb.go	TO	2	NA	B727																						1										U	MH AP
29/08/1967	N	http://www.ntsb.go	TO	2	NA	B727																																U	MH AP
19/07/1967	Ν	http://www.ntsb.go	TO	2	NA	B727				1		1														1	1					1						U	MH AP
02/07/1967	Ν	http://www.ntsb.go	TO	2	NA	B727																																U	MH AP
09/06/1967	N	http://www.ntsb.go	TO	2	NA	B727			1																													U	MH AP
08/06/1967	N	http://www.ntsb.go	TO	2	NA	B727																								1								М	MH AP
07/06/1967	Ν	http://www.ntsb.go	TO	2	NA	B727																								1								М	MH AP
02/06/1967	Ν	http://www.ntsb.go	TO	2	NA	B727																																U	MH AP
15/05/1967	N	http://www.ntsb.go	TO	2	NA	B727			1																													L	MH AP
29/04/1967	Ν	http://www.ntsb.go	TO	2	NA	B727		1	1																													U	MH AP
19/04/1967	Ν	http://www.ntsb.go	TO	2	NA	B727																																U	MH AP
11/04/1967	Ν	http://www.ntsb.go	TO	2	NA	B727	1 1																			1				1		1						М	MH AP
07/04/1967	N	http://www.ntsb.go	TO	2	NA	B727													1																			U	MH AP
22/03/1967	Ν	http://www.ntsb.go	TO	2	NA	B727													1																			U	MH AP
14/03/1967	N	http://www.ntsb.go	TO	2	NA	B727																								1								М	MH AP
08/03/1967	Ν	http://www.ntsb.go	TO	2	NA	B727											1																					U	MH AP
06/03/1967	N	http://www.ntsb.go	TO	2	NA	B727			1																													U	MH AP
25/02/1967	Ν	http://www.ntsb.go	TO	2	NA	B727			1																	1				1				1				М	MH AP
20/02/1967	Ν	http://www.ntsb.go	TO	2	NA	B727			1												1					1				1				1		1		М	MH AP
09/04/1967	1	http://www.ntsb.go	LDG	2	NA	DC9													1																			N	ml ds
09/03/1967	F	http://www.ntsb.go	DES	2	NA	DC9				1		1									1					1						1				1		M	ml ds
15/11/1966	N	http://www.ntsb.go	TO	2	NA	B727			1																					1								L	MH AP
02/11/1966	N	http://www.ntsb.go	TO	2	NA	B727			1												1					1				1 1		1				1		М	MH AP
25/09/1966	N	http://www.ntsb.go	TO	2	NA	B727													1							1				1 1					1			Н	MH AP
01/09/1966	N	http://www.ntsb.go	OTO	2	NA	B727													1																			U	MH AP
27/08/1966	Ν	http://www.ntsb.go	OTO	2	NA	B727																																U	MH AP
28/07/1966	Ν	http://www.ntsb.go	010	2	NA	B727																								1								н	MH AP
18/06/1966	N	http://www.ntsb.go	OTO	2	NA	B727			1																	1						1						L	MH AP
28/05/1966	N	http://www.ntsb.go	TO	2	NA	B727	1																			1				1		1						M	MH AP
26/05/1966	Ν	http://www.ntsb.go	010	2	NA	B727	1																			1				1		1						м	MH AP
20/05/1966	N	http://www.ntsb.go	OTO	2	NA	B727		1						1								1			1									1				U	MH AP

		Ac	ccident	ts									– Fi	acto	rs											F	actors	) (No	n-Tec	hnica	al)							Co	ompe	tencies	;			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment Ground manageryring	Runway/Taxi condition	Adverse Weather/Ice	Windshear Crosswind	АТС	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility	Upset	vvake vortex Torroin	Birds	Eng Fail	Fire	Syst mal	Ops/Type Spec	Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA Leadershin and	Teamwork	Workload Management Problem Solving	Decision Making	Application of Procedures & Knowledge	Flight Management,	Automation Manual Aircraft Control	Improved Training	Analyst Checker
08/05/1966	N	http://www.ntsb.go	TO	2	NA	B727															1																	_	_				LI	MH AP
20/04/1966	N	http://www.ntsb.go	TO	2	NA	B727																																_	_				UI	MH AP
20/04/1966	N	http://www.ntsb.go	TO	2	NA	B727	1																					1					1			1				-		_	M	MH AP
10/04/1966	N	http://www.ntsb.go	TO	2	NA	B727																																					UI	MH AP
19/03/1966	N	http://www.ntsb.go	TO	2	NA	B727																											1										υI	MH AP
15/03/1966	N	http://www.ntsb.go	TO	2	NA	B727															1		1					1					1 1							1			M	MH AP
05/03/1966	Ν	http://www.ntsb.go	TO	2	NA	B727																	1					1					1					1		1			LI	MH AP
20/02/1966	Ν	http://www.ntsb.go	TO	2	NA	B727															1																						UI	MH AP
09/02/1966	Ν	http://www.ntsb.go	TO	2	NA	B727																																					UI	MH AP
05/01/1966	N	http://www.ntsb.go	TO	2	NA	B727															1																					_	UI	MH AP
01/10/1966	F	http://www.ntsb.go	DES	2	NA	DC9											1											1					1			1		$\perp$	$\rightarrow$			'	Lr	nl ds
04/03/1966	N	http://www.ntsb.go	GRD	2	NA	DC9															1	1														$\rightarrow$		_					N r	nl ds
16/12/1965	N	http://www.ntsb.go		2	NA	B/2/		_		-				-			+	_			1		_	_		_			_					_		+		—	-	<u> </u>	_		UI	VH AP
10/12/1905	N	http://www.ntsb.go		2	INA NA	B/2/		_	1	_				-			-	_		_	+		_	_	+	_			_			-		_		+		+	$\rightarrow$	+	_	<u> </u>		
07/12/1905	IN NI	http://www.ntsb.go		2		D/2/			+	_		_		-		_		_			+		1			_		1					1	_		-	_		$\rightarrow$	1				
08/11/1965	N	http://www.ntsb.go		2		P727			1	-				-			-	-			+		1										1	_		1		—	$\rightarrow$	1			M	
29/09/1965	N	http://www.ntsb.go		2	NA	B727		+		-		-	-	-	+ +	-	+	-	+		+	_	- 1	-	+	-			-					-		-	-	+	-+					
28/09/1965	N	http://www.ntsb.go	TO	2	NA	B727		+	+	-		-	-	-			+	-			+	-	-	-		-			-			-	1	-		+	-	+	+	+	_	-+	M	MH AP
18/08/1965	N	http://www.ntsb.go	TO	2	NA	B727		-						-			-				1		-											-		+			-	-		_	U I	MH AP
18/08/1965	N	http://www.ntsb.go	TO	2	NA	B727		-									-																			-		+	-	+		_	U I	MH AP
16/08/1965	N	http://www.ntsb.go	TO	2	SA	B727		+					-				+				+								-							-		+	-	+		_	UI	MH AP
16/07/1965	N	http://www.ntsb.go	TO	2	SA	B727																																		-		_	υI	MH AP
29/05/1965	N	http://www.ntsb.go	TO	2	SA	B727																																		-			UI	MH AP
26/04/1965	N	http://www.ntsb.go	TO	2	SA	B727																																					UI	MH AP
17/03/1965	N	http://www.ntsb.go	TO	2	SA	B727																																_	_				M	MH AP
06/02/1965	Ν	http://www.ntsb.go	TO	2	SA	B727	1																																				UI	MH AP
12/01/1965	N	http://www.ntsb.go	UNK	2	SA	B727																																					UI	MH AP
06/12/1964	N	http://www.ntsb.go	UNK	2	SA	B727																														$\rightarrow$		$\perp$	$ \rightarrow $				UI	MH AP
02/12/1964	N	http://www.ntsb.go	UNK	2	SA	B727															$\square$			_												$\rightarrow$			_		_		UI	MH AP
21/10/1964	N	http://www.ntsb.go	UNK	2	SA	B727			$ \rightarrow $	_				_			$\rightarrow$	_			+			_	$\vdash$	_			_					_		$\rightarrow$		$\rightarrow$	$\rightarrow$	—	_	_	UI	VH AP
18/10/1964	N	http://www.ntsb.go		2	SA	B/2/		_	+	_				-			_	_	+		+		_	_		_			_					_		+		_	$\rightarrow$		_		UI	VH AP
02/10/1964	IN	http://www.ntsb.go		2	SA	B/2/		_		_				_			-	_	+		+			_		_			_							_		—	_		_			VIH AP
01/07/1964	U	http://www.ntsb.go		2		B/2/		_	+	_		_	-	-	+		+	_	+		+		_	_	+	_			_		$\vdash$	-	1	_		+		+	$\rightarrow$	<u> </u>	_	<u> </u>		
21/10/2009	Ē	Factual	TO	1		B707		-	+	-		_	-	-		-	+	-		-	+	_	-	-					-			-	1	-		+	-	-	$\rightarrow$	+	_	'		
3/19/2005	N	Factual	APR	1	AFR	B707		+	+		+	-+	-	-	1		+	+	+	_	+		-	+				1				1	1		+	+	-	1	+	+	_	1	н	
7/4/2002	F	Factual	IDG	1	AFR	B707		-	+		+ +			-	-		-	+			1			+		-						1	1		1	+	-		-	+			ii i	
3/7/2001	N	Factual	IDG	1	SA	B707		+			+	-	+	-			+	+	++		-	-	+	+				$\vdash$	+			1	1	-	1	+	-	+	+	+		-1	ŭ	
9/21/2000	N	Factual	LDG	1	AFR	B707		+	+				-	-		-	+	+		1	1	-	-	1					+					-		+	-	+	+	+			Ū	
2/3/2000	N	Factual	APR	1	AFR	B707								-		_		-				-		-				1					1			-		1		-		1	H	
2/7/1999	N	Factual	то	1	EUR	B707															1												1					Ť		+		1	М	
11/14/1998	U	Factual	CLB	1	EUR	B707											-				1															-		-		+			Ν	
3/10/1998	F	Factual	TO	1	AFR	B707								1																		1	1		1								U	



		Ac	ccident	ts										– Fa	acto	rs												Facto	ors	(Non-	Tech	hnica	l)								Comp	eten	cies			Va	idation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind	АТС	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility	Upset	vvake vortex Terrain	Birds	Eng Fail	MEL Fire	Syst mal	Ops/Type Spec Cabin	Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-DBs	Def-Proc's Estimo	CRM	Physio	Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incan	Communication	SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge Annlication of	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
12/5/1997	1	Factual	CLB	1	SA	B707																1																							N		
10/22/1996	F	Factual	TO	1	SA	B707															1	1													1										M		
2/22/1996	I	Probable Cause	LDG	1	NA	B707																1							1	1					1							1 1			H		
8/2/1993	I	Probable Cause	CLB	1	NA	B707																1																							N		
4/25/1992	N	Probable Cause	CLB	1	NA	B707																1																							N		
7/8/1991	Ν	Probable Cause	TO	1	NA	B707																1																							N		
9/20/1990	F	Probable Cause	TO	1	NA	B707																		1			1		1	1					1			1			1				1 H		
4/24/1990	I	Probable Cause	TO	1	NA	B707																											1	1											U		_
1/25/1990	F	Probable Cause	APR	1	NA	B707				1 1		1				1								1						1		1			1	1	1				1				H		-
2/8/1989	F	Factual	APR	1	EUR	B707						1						1						1						1					1		1					1			H		
1/22/1989	1	Probable Cause	LDG	1	NA	B707										1								1					1	1					1			1			1				1 U		-
11/16/1988	I	Probable Cause	LDG	1	NA	B707																								1					1				1			1			1 M		
10/12/1988	1	Probable Cause	DES	1	NA	B707						1																																	N		-
1/13/1988	N	Factual	UNK	1	SA	B707																																							U		-
4/30/1987	N	Probable Cause	GRD	1	NA	B707		1																1			-			1							1					1			M		-
4/13/1987	F	Probable Cause	APR	1	NA	B707				1						1		1						1			-			1					1				1			1			1 H		-
2/14/1987	F	Factual	UNK	1	NA	B707															1	1																							N		-
6/23/1984	1	Probable Cause	LDG	1	NA	B707			1	1	-			-	-	1		-	-					1			+			1		1			1					-	1	1			1 H		
12/29/1983	1	Probable Cause	LDG	1	NA	B707					-											1					-			1											1				M		-
4/2/1983	N	Probable Cause	DES	1	NA	B707				1						1														1							1	1							M		-
11/27/1982	N	Probable Cause	то	1	NA	B707					-										1	1	1	-			-																		N		-
11/11/1982	F	Probable Cause	CRZ	1	NA	B707					-			_	-							1		-			+									1				-					U		
3/24/1982	N	Probable Cause	IDG	1	NA	B707					-				-							1		-			+			1					1	1						1			1 M		-
3/8/1982	i i	Probable Cause	GRD	1	NA	B707					-												_	-			+													-					N		-
12/16/1981	N	Probable Cause	IDG	1	NA	B707					+				+			-	-		_	1	_	+			+	+	-									-	-	-					N		
6/20/1981	i i	Probable Cause	GRD	1	NA	B707	1				+			-	-			-	-				_	+			+		-								-	-	-	-					l ü		-
6/3/1981	N	Probable Cause	GRD	1	NA	B707					-				-			-					-	-			-	+ +	-								_	-							- U		
11/12/1980	i i	Probable Cause	CRZ	1	NA	B707					+				+						_			+			+									1		-		-					N		-
10/17/1980	N	Probable Cause	CIB	1	NA	B707				1	+			-	+			-	-		_		_	+		-	+	+ +	-	-				-		-		-	-	-					U U		-
4/21/1980	N	Probable Cause	DES	1	NA	B707				1	+				-								-	+			-		-									-							- u		-
9/18/1979	N	Probable Cause	APR	1	NA	B707					-			-	-			-				1	-	+			-		-									-							N		
4/21/1979	N	Probable Cause	DES	1	SA	B707	-			1	+			-	+	1		-	-		_		_	+		-	+	+ +	-	-				_		-	-	-	-	+		-			1 10	-	
4/10/1979		Probable Cause	TO	1	NA	B707					+			-	+			-	-	+	_	1	-	+		-	+	+ +	-	-						-	_	-	-	-					N	-	
4/6/1979		Probable Cause	GPD	1	ΝΔ	B707	-				-				-			-	-		-	1	-	+		-	-		-							-	-	-							N	-	
9/20/1978	N	Probable Cause	CLB	1	NA	B707				1	+			-	+	1		+	+				_	+	+	-	+	+	-	1	$\vdash$	-				-	+	+	1		1	+					+
8/6/1978		Probable Cause	GRD	1	NA	B707	-	1			+			+	+		-	+	+	+	_	+	_	+	+	-	+	+	-	-	$\vdash$					1	-	+				+					+
10/27/1977		Probable Cause	CLB	1	SA	B707	-				+			-	+	+		-	+	+		1	_	+	+		+	+		-	$\vdash$			-				+	<u> </u>	+		-				-	+
6/22/1977	i l	Probable Cause	LDG	1	NA	B707	-	+	$\vdash$		1	+		-	+	+		-	+	+		1		+	+	-	-		-	-	$\vdash$		+	-		-	-	-	<u> </u>	1		-				1	+
4/5/1977	i i	Probable Cause	CLB	1	NA	B707	-	+ +	$\vdash$		+	+ +		-	+	+	-+	+	+	+		1		+	+	-	+	+	-	-	$\vdash$		+	+	+		-	-	<u> </u>	+	+	-				1	+
1/25/1977	N	Probable Cause	GRD	1	SA	B707		1	1		+			-	+	+	-	+	+	+				+	+	-	+	+	-	1	$\vdash$		+	-	1		-	1		+	<b>⊢</b> +	-				1	+
1/12/1977		Probable Cause		1	NA	B707	-	-			1			-	-	+			+	+				-	+		+				$\vdash$				1		-			1						1	-
4/24/1976	N	Probable Cause	LDG	1	FUR	B707	-				+			-	+	+		+	+	+ +	_	1	_	+	+	-	+	+			$\vdash$			-			+	-	<u> </u>	+		-				-	+
12/22/1975	N	Probable Cause	APR	1	FUR	B707	-				+			+	+	+	-	+	+	+				1		-	+	+	-	1	$\vdash$		+	-	1		-	-	-	+	1	-			1 4	1	+
9/14/1975		Probable Cause	ТО	1	NA	B707					1			-	+	+	-+	-	+	+		1	-			-	+				$\vdash$					-	+			1	-				N	1	+
								1 I												1 I.					- I I			1																			

		A	ccident	ts										Fac	tors												Facto	ors (	Non	-Tecl	hnica	d)							C	Comp	etencie	s			Vali	dation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Kunway/Taxi condition	Auverse weathernce Windshear	Crosswind	ATC	Loss of comms	Traffic	R/W Incursion	Poor Visibility Upset	Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Svst mal	Ops/Type Spec	Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts Dof-Chk lists	Def-DBs	Def-Proc's Fatique	CRM	Physio	Workload Distraction Pressure	D.G	Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge Application of Procedures & Knowledge		Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
8/13/1975	Ν	Factual	CRZ	1	NA	B707			1							1																												U		
8/6/1975	N	Probable Cause	CRZ	1	ASIA	B707			1																																			U		
7/27/1975	Ν	Probable Cause	CRZ	1	NA	B707			1																												$(\Box$							U		
7/12/1975	Ν	Probable Cause	DES	1	NA	B707			1																																			U		
4/7/1975	1	Probable Cause	CRZ	1	NA	B707															1																							N		
2/18/1975	Ν	Probable Cause	LDG	1	NA	B707															1																							N		
12/28/1974	N	Probable Cause	DES	1	NA	B707										1								1					1					1			1							1 M		
12/10/1974	N	Probable Cause	DES	1	NA	B707																							1					1			1		1					1 L		
11/25/1974	N	Probable Cause	TO	1	ASIA	B707													1		1																							N		
10/24/1974	1	Probable Cause	CLB	1	SA	B707																										1												U		
5/13/1974	N	Probable Cause	CRZ	1	NA	B707			1															1					1									1	1					, н		
5/8/1974	1	Probable Cause	TO	1	NA	B707													1		1																							N		
4/22/1974	F	Probable Cause	APR	1	ASIA	B707																		1					1					1				1						1 H		
4/1/1974	N	Probable Cause	CRZ	1	NA	B707			1						1	1													1								1		1	1				M		
3/20/1974	1	Probable Cause	DES	1	NA	B707						1		1																														, U		
2/16/1974	N	Probable Cause	APR	1	NA	B707															1																							N		
1/30/1974	F	Probable Cause	APR	1	ASIA	B707																		1					1		1			1			1		1					1 H		
1/17/1974	N	Probable Cause	LDG	1	NA	B707			1						1	1								1					1					1				1	1	1				1 H		
1/16/1974	N	Probable Cause	LDG	1	NA	B707										1								1					1					1					1		1			1 H		
1/12/1974	N	Probable Cause	LDG	1	NA	B707															1																							N		
1/8/1974	1	Probable Cause	GRD	1	NA	B707		1				1																	1					1		1	1							M		
1/1/1974	N	Probable Cause	GRD	1	NA	B707		1				1			1	1													1					1		1	1							1 M		
12/17/1973	1	Probable Cause	GRD	1	EUR	B707																															$\square$							U		
11/3/1973	F	Probable Cause	CRZ	1	NA	B707									1	1					1 1								1			1		1			$\square$		1	1	1			1 H		
9/5/1973	1	Probable Cause	CRZ	1	NA	B707															1																							N		
8/28/1973	F	Probable Cause	DES	1	NA	B707															1																							N		
8/27/1973	N	Probable Cause	CRZ	1	OTH	B707			1																												$\square$							U		
7/22/1973	F	Probable Cause	CLB	1	ASIA	B707																															$\square$							U		
5/1/1973	1	Probable Cause	CRZ	1	OTH	B707															1 1																$\square$	!	$\square$					N		
4/9/1973	Ν	Probable Cause	GRD	1	NA	B707															1																$\square$							N		
4/6/1973	N	Probable Cause	CLB	1	NA	B707									1																						$\square$							U		
3/5/1973	N	Probable Cause	TO	1	NA	B707			1						-	1		1						1					1					1				1	1	1				1 H		
1/20/1973	N	Probable Cause	CLB	1	NA	B707															1																$\square$		$\square$					N		
12/14/1972	I	Probable Cause	CRZ	1	NA	B707																													1									U		
12/12/1972	N	Probable Cause	APR	1	NA	B707	L									1	1			1				1					1					1			1		1					<u>1 H</u>	1	_
11/1/1972	N	Probable Cause	LDG	1	NA	B707									_						1 1																$\square$		$\square$					N	-	
10/24/1972	N	Probable Cause	CRZ	1	SA	B707			1								1																				$\square$		$\vdash$					U	1	_
9/13/1972	Ν	Probable Cause	ſO	1	NA	B707											1			1	1			1					1					1			$\square$				1			<u>1 H</u>	1	_
9/13/1972	1	Probable Cause	LDG	1	NA	B707													-		1				_											_	$\square$		$\square$	$\rightarrow$				N	4	-
8/13/1972	N	Probable Cause	ſO	1	NA	B707									_		1			1	1					+								1			$\square$	!	$\vdash$	$\rightarrow$				1 N	+	-
7/30/1972	1	Probable Cause	LDG	1	NA	B707						_									1																$\square$	!	$\vdash$	$\rightarrow$					+	_
7/20/1972	1	Probable Cause	CRZ	1	NA	B707						1		1			1																				$\vdash$		$\vdash$					<u> </u>	4	
7/18/1972	N	Probable Cause	CRZ	1	NA	B707	L										1	+		1	1				_	+				+						_	$\vdash$		$\vdash$	$\rightarrow$				<u>N</u>	+	-
5/23/1972		Probable Cause	IGRD	1	INA	B707		1			1			1			1			1	1		1 1			1 1				1		1		1			r L		(					, IN	1	1



		A	ccident	ts									Fac	tors										F	acto	ors (No	n-Tec	chnica	al)						Com	pete	ncies			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear Crosswind	ATC	NAV Loss of comms	Traffic	R/W Incursion Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Syst mal	Ops/Type Spec	Cabin Compliance	Def Manuals	Def-Ops data	Def-Chk lists	Def-DBs Dof Dunc's	Der-Proc's Fatique CPM	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State Mis-Sys	Pilot Incap	Communication SA	Leadership and Teamwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
4/9/1972	1	Probable Cause	GRD	1	NA	B707	1 1	1													1					1							1 1				1		М	
3/20/1972	N	Probable Cause	LDG	1	ASIA	B707																									1								1 M	
3/8/1972	N	Probable Cause	GRD	1	EUR	B707	1	1																															U	
1/14/1972	1	Probable Cause	CRZ	1	NA	B707																										1							U	
12/12/1971	N	Probable Cause	DES	1	NA	B707			1																														U	
11/13/1971	N	Probable Cause	CRZ	1	NA	B707			1																														U	
9/23/1971	Ν	Probable Cause	CLB	1	EUR	B707			1																	1								1	1				М	
8/4/1971	N	Probable Cause	DES	1	NA	B707							1																										U	
7/25/1971	F	Probable Cause	APR	1	ASIA	B707										1					1					1					1			1			1		M	
7/21/1971	1	Probable Cause	TO	1	NA	B707												1	1																				N	
6/20/1971	N	Probable Cause	CRZ	1	OTH	B707			1												1					1								1			1		М	
6/12/1971	1	Probable Cause	GRD	1	NA	B707	1 1	1																		1					1		1						1 M	
6/11/1971	-	Probable Cause	CRZ	1	NA	B707					1		1																										U	
5/8/1971	1	Probable Cause	CRZ	1	OTH	B707																										1							U	
4/7/1971	1	Probable Cause	TO	1	NA	B707													1																				N	
3/8/1971	1	Probable Cause	LDG	1	NA	B707													1						1	1					1 1		1			1			1 M	
1/9/1971	F	Probable Cause	CRZ	1	NA	B707							1																								L'		U	
12/24/1970	N	Probable Cause	CRZ	1	NA	B707			1																														U	
12/18/1970	1	Probable Cause	DES	1	NA	B707															1					1							1 1						н	
12/5/1970	1	Probable Cause	TO	1	NA	B707													1																		L'		N	
11/30/1970	F	Probable Cause	TO	1	ASIA	B707								1																									U	
11/7/1970	N	Probable Cause	CLB	1	отн	B707			1																1												L'		U	
10/28/1970	1	Probable Cause	CLB	1	NA	B707																										1					'		N	
10/20/1970	1	Probable Cause	LDG	1	NA	B707																				1					1		1		1		<u> </u>		1 H	
10/16/1970	1	Probable Cause	GRD	1	NA	B707													1																		L'		N	
9/18/1970	N	Probable Cause	CRZ	1	отн	B707			1																												'		U	
8/22/1970	1	Probable Cause	DES	1	NA	B707																										1					<u> </u>		U	
8/13/1970	N	Probable Cause	DES	1	SA	B707			1																												L'		U .	
6/9/1970	1	Probable Cause	CRZ	1	NA	B707													1																	$\square$	<u> </u>	-	N	
4/22/1970	1	Probable Cause	GRD	1	NA	B707					_							1	1																_	+	<u> </u>		N	
3/28/1970	1	Probable Cause	CRZ	1	NA	B707					_		$ \downarrow \downarrow$											_								1			_	+	<u> </u>		U	
2/11/1970	N	Probable Cause	LDG	1	NA	B707							$\vdash$						-		1					1					1		1	1	_	+	<u> </u>		1 M	
2/10/1970	1	Probable Cause	10	1	NA	B707											_		1																	+	<u> </u>		N	
12/1/1969	N	Probable Cause	10	1	AUS	B707					_		$ \downarrow \downarrow$			1	1		1		1		1	_		1			1		1				1		1		H	
10/14/1969	1	Probable Cause	10	1	ASIA	B707							+	_		-			1									-				-		<b>I</b>	-	+	<u> </u>		N	
10/12/1969	N	Probable Cause	CRZ	1	OTH	B70/			1		_		+			+				+	1					1		<u> </u>			1	+	1	1	-	+	<u> </u>		M	
10/11/1969	N	Probable Cause	CRZ	1	IOTH I	B/0/			1		-		+			+	-		-			+					_									+	<u> </u>	l	U	
8/29/1969	N	Probable Cause	GRD	1	ASIA	B707			4		-	$\square$	+	_		+ +	_	-	_	-		+			$\vdash$		_	-		-		+	_	+ +	-	+	<u> </u>	l	U	
8/26/1969	N	Probable Cause		1	UTH NA	B707			1		-					-	+		+	-		+						-		-		-	_		-	+	<u> </u>		U	
0/3/1909	F	Probable Cause	URZ ODZ	1	INA	D707						$\square$		-		+	_	+				-					_	-	$\vdash$	-	$\vdash$	+		+	-	+	<u> </u>	l	U	
8/2/1969	N	Probable Cause	URZ	1	UTH	B707			1		-	$\square$	+	1		1	_	-	_	-		+					_	-	$\vdash$	-	4	-	_		-	+	<u> </u>			
7/26/1060		Probable Cause	LDG	1	EUR	D707			$\vdash$	-			+	_		+	_	+	+	+		1	-		-			-	$\vdash$		1	+	_	+	1	+	<u> </u>		1 M	
6/5/1060	F	Probable Cause	CDD	1	IN/A	D707			$\vdash$	_	-		+	-		+	+	+	-			1	1								1	+	_	+ $+$	1		<u> </u>			
0.0/1000	1	FIGUADIE Gause	JORD		INA	10101					1	1 1	1	1	1	1	1	1		1		1	I I		I I.		1	1	I I	1		1	1	1	1	1 2	1	. 1		1

		Ac	ccident	ts									Fac	tors	S										F	Factors	) (No	n-Tecl	hnica	al)							Comp	beter	ncies			Validation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear Crosswind	ATC	NAV Loss of comms	Traffic	R/W Incursion	Poor Visibility Upset	Wake Vortex	Terrain	Birds Eng Fail	MEL	Fire Syst mal	Ops/Type Spec	Cabin Comuliance	Def Manuals	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio	Workload Distraction Pressure	D.G LF.P	Mis-AFS	Mis A/C State Mis-Sve	Pilot Incap	Communication	Leadership and	Teamwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
22/04/1969	1	Probable Cause	CLB	1	NA	B707												1		1																					N	
4/19/1969	1	Probable Cause	CLB	1	NA	B707														1																					N	
4/8/1969	N	Probable Cause	CRZ	1	NA	B707			1																																U	
3/20/1969	N	Probable Cause	CRZ	1	NA	B707			1																																U	
2/7/1969	N	Probable Cause	CRZ	1	OTH	B707			1																																U	
2/2/1969	N	Probable Cause	GRD	1	NA	B707	1																																		N	
12/26/1968	F	Probable Cause	TO	1	NA	B707			1						1							1		1			1		1			1 1			1				1		Н	
12/12/1968	F	Probable Cause	APR	1	SA	B707									1							1					1					1		1				1			1 M	
12/10/1968	1	Probable Cause	GRD	1	NA	B707	1																				1					1		1							1 M	
11/23/1968	N	Probable Cause	CRZ	1	SA	B707			1																																U	
11/19/1968	Ν	Probable Cause	CLB	1	NA	B707														1 1																					N	
11/19/1968	1	Probable Cause	DES	1	NA	B707														1																					N	
10/28/1968	N	Probable Cause	CRZ	1	OTH	B707			1																		1							1			1	$\square$			M	
10/5/1968	N	Probable Cause	DES	1	NA	B707																																$\square$			U	
9/14/1968	N	Probable Cause	CRZ	1	OTH	B707			1																		1							1	1			$\square$			M	
8/5/1968	N	Probable Cause	LDG	1	NA	B707														1 1																		$\square$			N	
7/23/1968	N	Probable Cause	CRZ	1	NA	B707			1																													$\square$			U	
6/13/1968	F	Probable Cause	APR	1	ASIA	B707									1							1					1					1			1		1	$\vdash$			1 H	
3/7/1968	1	Probable Cause	CLB	1	NA	B707				_				_						1																		$\vdash$			N	
1/27/1968	N	Probable Cause	10	1	NA	B707		_		_				_		_		_				1			_		1					1	_		1		1	$\mapsto$			1 H	
1/25/1968	N	Probable Cause	CRZ	1	ASIA	B707		_	1	_		_		_	_	_	$\vdash$			_					_													$\mapsto$			U	
1/13/1968	N	Probable Cause	CRZ	1	ОТН	B707			1	_				_	_							1					1							1		_		$\mapsto$			M	
11/21/1967	N	Probable Cause	10	1	INA	B707		_	+	_	4	_		4	_	_	+	_		1			_				1					4	_			_	4	$\mapsto$	4		N	
11/0/1907	F	Probable Cause	10	1	INA	B707		_	+	_	1	_		1	_	_	+	_		1		1			_		1					1	_	1	4		1	$\vdash$	1			
10/17/1067		Probable Cause		1		B/0/		1		_				_	_	_	+	_		1		1	_		_		1					1	_		1	_	1	$\mapsto$			1 1	
0/00/4007	1	Probable Cause		4		D707		1	4	_				_	_	_		_		- 1			_		_								_		-	_		$\mapsto$			0	
9/29/1967	IN	Probable Cause		1	ASIA	B/0/			1	_	+	_		-	_	_	+	_		1 1			-	+	_					$\left  \right $			_		-	_	-	++			U	
9/14/1907	N	Probable Cause		1		B707		-	+	_	+	_	-	-	_	-	+			1 1			-	+	_								-		-		-	++				
9/19/1007	N	Probable Cause		4		D707		-	1	_				-	_	-	+																		-	_		++			0	
7/15/1967		Probable Cause		1	NA	B707		-	1	_				-	1			-		-					_								_		-	_		++			0	
5/19/1967	li -	Probable Cause		1	ΝA	B707		-			+	_	-	-			+	-		1				+ +	-		$\vdash$						-		+	-	-	$\vdash$			N	
4/25/1967	N	Probable Cause	LDG	1	NA NA	B707		-	+	_		_	-	-	_	-	+	-		1				+	-								+		+	_	-	++			- 11	
3/11/1967	N	Probable Cause	DES	1	ΝΔ	B707		-	+		++	-	1		1	-	+						-												-	-		$\vdash$			U U	
1/6/1967		Probable Cause	GRD	1	NΔ	B707	1	-	+ +	_		-		-		-		-	-		-												-		-	-	-	$\vdash$			N	
11/26/1966	N	Probable Cause	IDG	1	NA	B707		-		_		_	-	-	_	-	+	-		1				+ +			1		1			1	-		1		1	$\vdash$			1 H	
11/4/1966	1	Probable Cause	APR	1	NA	B707			+		+			-			+			1			+										-		- <u> </u>		-	$\vdash$			N	
10/18/1966	N	Probable Cause	LDG	1	NA	B707														ľ		1					1					1	-		1			$\square$			1 M	
10/10/1966	1	Probable Cause	CRZ	1	EUR	B707		-			+			-	1					1		L L					l l'				1		-		-		1	$\vdash$			U	
9/26/1966	1	Probable Cause	CLB	1	NA	B707		-	+		+			-+	-		+			1 1				+									+		+	-		$\vdash$			N	
9/9/1966	N	Probable Cause	CRZ	1	NA	B707			1													1					1								1			$\square$			м	
8/30/1966	1	Probable Cause	то	1	NA	B707								-																			-					$\square$			U	
8/9/1966	N	Probable Cause	DES	1	NA	B707			1					-																			-					$\vdash$			U	
6/11/1966	1	Probable Cause	CLB	1	NA	B707										1				1						1												$\square$			N	



		A	ccident	s										E F	acto	rs												Facto	ors (	(Non	-Tec	hnica	ıl)							1	Compe	etencie	es			Val	idation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind	АТС	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds	Eng Fail MEI	Fire	Syst mal	Ops/Type Spec	Compliance	Def Manuals	Def-Ops data	Def-Chk lists Def-Chk lists	Def-DBs	Def-Proc's Fatique	CRM	Physio	Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	knowledge Application of Procedures & Knowledge		Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
6/7/1966	1	Probable Cause	CLB	1	NA	B707			1	1																																			U		
5/5/1966	1	Probable Cause	CRZ	1	ASIA	B707																																							U		
4/30/1966	1	Probable Cause	CRZ	1	OTH	B707					_										_	1																				_			N		
4/24/1966	1	Probable Cause	APR	1	NA	B707				_	_					$ \rightarrow $								1						1					1				1		1	_			1 H		
1/30/1966	N	Probable Cause	DES	1	NA	B/0/			1						_				_																	_									U		_
1/23/1966	N	Probable Cause	LDG	1	NA	B707			1		1			_		1		_	_		_		_		_					1					1	_	_					_			1 M	_	
12/4/1965	F	Probable Cause	CRZ	1	NA	B707		_			_			1		$ \rightarrow $		_	_		_		_		_		_			1						_	_	1				_			1 L		_
11/20/1965	1	Probable Cause		1	NA	B707				_	_								_		_	1	_																						N	_	
10/17/1965		Probable Cause		1	NA	B707					_				_	+ +		_	_		_			-	_			-		4					4	_	_	4			-	_			U	_	
9/1//1965	F	Probable Cause	DES IODZ	1	UIH	B707		_			-			$\rightarrow$	_	$ \rightarrow $		+	-		_		_	1			_	-		1			$\vdash$		1	_	_	1			1	_			н	_	
7/0/1903	IN N	Probable Cause		1		D707		_			-			+	-	+		+	-		_	1			_	+ +	_	-	-	_						_	-			$\vdash$		_				-	_
7/5/1005		Probable Cause		4	N/A	D707		-			-		_		_			-	-		_			-	_				-	-				_		-	_					-	_			-	
7/1/1965	N	Probable Cause		1	NA	B707			1		+			-	+			+	-		_		-	-	_	+ +	-	+ +	-	-	+ +				1		-						-		1 M	-	
6/28/1965	N	Probable Cause	CLB	1	NΔ	B707				-	-		-	-	-	+		+	-	1	1	1	-	+	_	+ +	-	+ +	-	-						-	-			$\vdash$		_	-		I IVI	-	
5/11/1965	N	Probable Cause		1	NA	B707					-		_		-			-	-				-		_	+ +	-			-							-					-			N		
5/9/1965	N	Probable Cause			NΔ	B707			1		-		-		-			-	-		-	<u> </u>	-	1						1							-		1		1	-			M	-	
4/23/1965	N	Probable Cause		1	NΔ	B707					+		-	-	+	+		+	+		_	+	-			+ +		+ +	-				$\vdash$		1	-	-						-		1 M	-	
3/26/1965	N	Probable Cause	LDG	1	ASIA	B707				-	+		-	-	-	+		+	-		-		-	-	_	+ +	-		-	-			$\vdash$		1	-	-			$\vdash$		-			1 M	-	
3/4/1965	1	Probable Cause	TO	1	NA	B707					-		-		-			-	-		-		_	-	-		-	-	-	-					1	-	-								1 11	-	
2/17/1965	N	Probable Cause	GPD		NΔ	B707		1			+		-		+	+		+	+		-		-	-	-			+ +	-	1			$\vdash$		1		-	1	1			-	-		1 M	-	
2/13/1965		Probable Cause	LDG	1	NA	B707				-	+		-	-	-	+		+	-		_		-	+	_	+ +		-	-				$\vdash$		1	-	-			$\vdash$		-	-		1 H	-	
1/31/1965	N	Probable Cause	CRZ	1	ОТН	B707			1		-				-	+		+	-		-		-	1					-	1			$\vdash$		1						1				M	-	
1/17/1965	1	Probable Cause	TO	1	NA	B707					-		-	-	-			+	-			1	-			+ +																	-		N		
12/21/1964	-li	Probable Cause	CLB	1	NA	B707				-	+		-	-	+	+		+	1		_	1	-	+	_	+ +			-	-	+ +		$\vdash$		-	-	-			$\vdash$		-	-		N	-	
12/7/1964	-i	Probable Cause	DES	1	NA	B707				-	+		-	-	-	+		+			-	<u> </u>	-	-	_	+ +	-		-	-	+ +		$\vdash$		-	-	-			$\vdash$		-				-	
11/23/1964	F	Probable Cause	TO	1	FLIR	B707					-		-	-	-			-	-		-	1	-	-	-	+ +			-	1					1	1	-	1					-		1 M	-	
11/12/1964	N	Probable Cause	GRD	1	NA	B707		1		-	+		-	-	+			+	+		_	1	-	-	_	+ +		-	-				$\vdash$				-			$\vdash$		-	-		N	-	
11/11/1964	1	Probable Cause	GRD	1	NA	B707				-	+		-	-	+	+		+	-		_		-	-	_			-	-	-						_	-					-	-		11		
11/10/1964	-li	Probable Cause	CRZ	1	NA	B707					-		-		-			-	-		-			1						-												-	-		U U	-	
9/30/1964	-li	Probable Cause	CRZ	1	NA	B707					-							-	1																								-		N		
9/25/1964	-i	Probable Cause	CRZ	1	NA	B707					+			-	-			+			-	1		-				+ +	-	-				_			-					-	-		N	-	
9/25/1964	-li	Probable Cause	CRZ	1	NA	B707			1		+		-	-	+			+	-		-			-	-			+ +	-	-						-	-					-	-		U	-	
9/20/1964	li	Probable Cause	CRZ	1	NA	B707					-		-		-			-	-			1	-	-					-														-		N		
8/26/1964	N	Probable Cause	APR	1	NA	B707		1		-	+			-	-			-	1		+	· ·		1	+			1	-	1			$\vdash$		1		+	1							1 H	1	+
8/21/1964	1	Probable Cause	LDG	1	NA	B707				-	+		+	+	-	+		+			1		-	- [				++	-	- i -		_	+		1	-	1		_	+			-		1 M		+
8/21/1964	1	Probable Cause	TO	1	NA	B707		1		-	-			-	-			-	1	1	-	1			+			1	-		1 1				1		+						-		1 M	1	-
8/13/1964	1	Probable Cause	GRD	1	NA	B707	1	1					+					-	1		1				-					1					1								-		1 M	1	-
6/14/1964	1	Probable Cause	GRD	1	NA	B707							+	-				-			1				1					- i													-		N		+
6/9/1964	1	Probable Cause	GRD	1	NA	B707		1		+	-			-	-	+		+	1				-	-	+				-	1			$\vdash$		1	-	1	1					-		1 M	1	+
5/29/1964	N	Probable Cause	TO	1	EUR	B707							+		-				1			1		-													1						- 1		N	1	
4/7/1964	N	Probable Cause	LDG	1	NA	B707																		1						1					1				1		1				1 H		
3/5/1964	1	Probable Cause	CRZ	1	EUR	B707							+					-																									-		U	1	-
2/15/1964	1	Probable Cause	CLB	1	EUR	B707		1											1				1					1									1								N	1	-





		Ac	ccident	s								F	actors	3										Fa	actors	। (Non	-Techn	ical)							Con	npet	encies			Valio	dation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion	Poor Visibility Upset	Wake Vortex	Terrain Birds	Eng Fail	MEL Fire	Syst mal	Ops/Type Spec Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts	Def-Chk lists	Def-DBs Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Bilot Incom	Communication	SA · · ·	Leadership and Teamwork	Workload Management Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
5/30/2005	I I	Probable Cause	GRD	P3	NA	DHC8	1 1																			1						1	1	1					н		
5/19/2004	I I	Factual	GRD	P3	EUR	DHC8											1	1	1																				N		
1/19/2004	I I	Probable Cause	LDG	P3	NA	DHC8							1	1												1							1			1			M		
1/8/2003	Ν	Probable Cause	APR	P3	NA	DHC8										1			1																				N		
10/14/2002	Ν	Probable Cause	APR	P3	NA	DHC8										1			1																				L		
3/1/2002	I I	Probable Cause	CRZ	P3	NA	DHC8													1																				N		
8/28/2001	I I	Probable Cause	CLB	P3	NA	DHC8													1																				N		
3/6/2001	Ν	Probable Cause	APR	P3	NA	DHC8											1	1																					N		
3/12/2000	I	Probable Cause	GRD	P3	NA	DHC8													1		1					1					1		1						M		
10/6/1999	Ν	Probable Cause	CRZ	P3	NA	DHC8										1																							N		
9/27/1998	Ν	Probable Cause	APR	P3	NA	DHC8			1																														L		
3/26/1997	Ν	Probable Cause	GRD	P3	NA	DHC8	1 1														1				1	1							1						Н		
2/24/1997	I	Probable Cause	CLB	P3	NA	DHC8													1																				N		
2/20/1997	I	Probable Cause	CLB	P3	NA	DHC8													1	1																			N		
1/22/1997	I	Probable Cause	TO	P3	NA	DHC8													1	1																			N		
12/15/1996	Ν	Probable Cause	LDG	P3	NA	DHC8													1																				U		
4/3/1995	I	Probable Cause	APR	P3	NA	DHC8													1	1																			N		
8/1/1994	Ν	Probable Cause	GRD	P3	NA	DHC8	1																																N		
2/11/1994	1	Probable Cause	APR	P3	NA	DHC8			1																	1							1						M		
3/23/1993	Ν	Probable Cause	APR	P3	NA	DHC8			1													1				1						1	1						M		
1/9/1993	1	Probable Cause	TO	P3	NA	DHC8													1		1					1					1		1		1				1 H		
1/8/1993	1	Probable Cause	TO	P3	NA	DHC8											1			1																			N		-
1/12/1992		Probable Cause	то	P3	NA	DHC8											1	1	1																	-			N		-
10/8/1992		Probable Cause	DES	P3	NA	DHC8				1		1	-	1												1							1						M		
7/16/1991	1	Probable Cause	TO	P3	NA	DHC8													1																				N		
7/25/1990		Probable Cause	TO	P3	NA	DHC8					-		+ +						1	_								_						-	_				L		
4/22/1988		Probable Cause	CRZ	P3	NA	DHC8											1	1	1																	-			N		-
4/15/1988	N	Probable Cause	CLB	P3	NA	DHC8											1	1	1																				L		
6/19/1987		Probable Cause	CLB	P3	NA	DHC8					-		+ +				1		1									_						-	_	-			N		-
12/2/1986	1	Probable Cause	CLB	P3	NA	DHC8					-						1	1	1																	-			N		-
9/11/2009	N	Preliminary	UNK	P3	NA	DHC8																																	U		-
6/26/2009		Probable Cause	GRD	P3	NA	DHC8				1			1																										N		
8/5/2009	N	Factual	CRZ	P3	NA	DHC8			1					1					+	_											-			-	-	+	-		1		-
11/8/2010	N	Preliminary	DES	P3	NA	DHC8					+					1			+	-								-			-	-		-	-	+	-		N		-
24/09/2009	F	actual	TO	P2	AFR	BAE Jetstream 41					-						1		1	-	1					1	1			1	1	-	1 1			+	1		1 H	DS	SE
29/12/2000	N.	Probable Cause	IDG	P2	NA	BAF Jetstream 41					-								1	-	1					1				1	1	-	1			+	1		1 H	DS	SF
07/01/1994	F	Probable Cause	APR	P2	NA	BAE Jetstream 41			1	++	+	++	1	1		-	+		<u> </u>	-	1	1		++	1	1	1			1	1		1		1	1	1		1 H	DS	SF
06/09/1997	N	Probable Cause	CRZ	P3	NA	BAE-ATP			1		-				+	-	+		+	-		-	-				· ·							-		- (*				DS	SF
25/02/1994		Probable Cause	DES	P3	NA	BAE-ATP					1						+	1	1												-			-		-	1		N	DS	SF
19/01/1994	li l	Probable Cause	GRD	P3	NA	BAE-ATP			-		+		+			-	+	1	1					$\vdash$							-			-	-	-	+		N	DS	SF
07/05/1993	N	Probable Cause	GRD	P3	NA	BAE-ATP			+	++	+	++	++	-	+	-	++		<u> </u>	1		+		++			++	-			+		+	-		+	+		N	DS	SF
11/04/1993		Probable Cause	CRZ	P3	NA	BAE-ATP	$\vdash$		1	++	+	++		1	+		1		1				-	$\vdash$			++	-			+	-	+	-	-	+	1		N	DS	SF
08/01/1992	li l	Probable Cause	DES	P3	NA	BAE-ATP	$\vdash$		1	++	1	++	-	1		-		-	1	-				$\vdash$	_			-			-	-	+			+	-		N	DS	SE
27/11/1999	N	Probable Cause	LDG	P2	NA	DeHavilland DH7					+								1	1	1					1					1		1		1	1	1		H	SF	DS

		Ac	cident	S									acto	rs											Facto	ors (N	lon-T	echnie	cal)							Co	ompet	encies			Vali	idation
Date	Severity		Phase	Generation Begion	Туре	Ground equipment	Ground manoeuvring Runway/Taxi condition	Adverse Weather/Ice	Windshear Crosswind	ATC	NAV	Loss of comms	Iramic R/W Incursion	Poor Visibility	Upset Wake Vortex	Terrain	Birds	eng rau MEL	Fire Svet mal	Ops/Type Spec	Cabin	Compriance Def Manuale	Def-Ops data	Def-Charts Def-Chk lists	Def-DBs	Def-Proc's Fatique	CRM 	Physio Workload Distraction	D.G	LF.P Mis-AFS	Mis A/C State	Mis-Sys Bilot Incon	Communication	SA	Leadership and Teamwork	Workload Management Problem Solving	Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
05/03/1993	Ν	Probable Cause	APR	P2 NA	DeHavilland DH7			1																																U	SF	DS
29/07/1990	Ν	Probable Cause	APR	P2 NA	DeHavilland DH7														1		1						1					1				1	1	1		н	SF	DS
11/01/1989	1	Probable Cause	LDG	P2 NA	DeHavilland DH7														1																					N	SF	DS
08/04/1987	I	Probable Cause	APR	P2 NA	DeHavilland DH7					1		1																												N	SF	DS
15/04/1985	Ν	Probable Cause	CRZ	P2 NA	DeHavilland DH7												1		1 1																					N	SF	DS
29/07/1984	1	Probable Cause	то	P2 NA	DeHavilland DH7														1																					N	SF	DS
15/05/1984	I	Probable Cause	APR	P2 NA	DeHavilland DH7														1																					N	SF	DS
22/12/1983	Ν	Probable Cause	APR	P2 NA	DeHavilland DH7										1																									U	MS	DS
10/06/1981	1	http://www.ntsb.go	LDG	P2 NA	DeHavilland DH7			1	_							_			1		1						1	1			1	1			1 1	1		1		M	SF	DS
18/08/1980	1	http://www.ntsb.go	APR	P2 NA	DeHavilland DH7		-		_			_	_	-		_			1									_					_							N	SF	DS
03/03/1979		http://www.ntsb.go	LDG	P2 NA	DeHavilland DH7		1		_	_		_	_	-		+		_	1									_					_				_		_	N	SF	DS
06/12/1977	IN N	http://www.ntsb.go	GRD	PZ NA	Denavilland DH7		_		_	_		_	_	_		_		_	1	_	4	1				1	4	_			4	_		4		-		4			SF	05
03/06/2008	IN	Probable Cause	TO	P2 INA	Dornier 320		_	+	_	-		-	-	-		+	+	-	1	-		_					'	_			1		_	1		- 11		1		IVI N	OF	00
02/09/2003	N	Probable Cause	GRD	P2 NA	Dornier 328		_	+ +		-		-+	-	-		+		-				-						_			-	-	-			-			+		SE	
24/04/2003	N	Probable Cause	CRZ	P2 NA	Dornier 328			1	-	-		-	-	-		-		-		-											-					-					SE	
13/03/2003		Probable Cause	APR	P2 NA	Dornier 328			1				-		-		+		-		-		-									-	-				-					SF	DS
28/07/2002	ti d	Probable Cause	CLB	P2 NA	Dornier 328					-		-	-	-		+		-	1											_	-	-				-		+	+		SF	DS
17/06/2002	li l	Probable Cause	GRD	P2 NA	Dornier 328									-		+		-			1										-	-				-				N N	SF	DS
06/06/2002		Probable Cause	APR	P2 NA	Dornier 328														1																					N	SF	DS
22/05/2002	1	Probable Cause	DES	P2 NA	Dornier 328											-			1																					N	SF	DS
02/05/2002	1	Probable Cause	CRZ	P2 NA	Dornier 328			1								-			1																					N	SF	DS
09/04/2001	Ν	Probable Cause	APR	P2 NA	Dornier 328			1													1																			N	SF	DS
20/03/2000	Ν	Probable Cause	LDG	P2 NA	Dornier 328														1																					N	SF	DS
29/05/1996	I	Probable Cause	CRZ	P2 NA	Dornier 328			1											1	1																				N	SF	DS
31/03/1996	1	Probable Cause	CLB	P2 NA	Dornier 328			1											1																					N	SF	DS
03/08/1995	Ν	Probable Cause	LDG	P2 NA	Dornier 328			1	1													1				1											1			Н	SF	DS
22/03/2010	F	Factual	то	P3 AUS	EMB-120												1		1								1									1		1		1 H	SF	DS
16/02/2010	1	Preliminary	GRD	P3 NA	EMB-120	1	1		_																			_												L	SF	DS
21/02/2009	1	Probable Cause	GRD	P3 NA	EMB-120	1	1		_			_	_	_		_		_		_		_										_	1	1						Н	SF	DS
26/06/2008	-	Factual	APR	P3 AUS	EMB-120		_		_	4		-	-			-	1	_	1	-		_			_			_			-	_	_			_	_	_	_	N	SF	DS
26/05/2007	-	Probable Cause	LDG	P3 NA	EMB-120		_		_	1		_	1	1		-		_		_	1	_					1	_			1	_	_		1 1		_	1		1 1	51	05
20/11/2003	I N	Probable Cause	CDD	P3 INA	EIVID-120	4	1		_			-	_	1		-		-		-							1	_			1	_					_	1			OF	03
16/03/2003	IN	Probable Cause	TO	P3 NA	EMP 120	1	1	1	_	-		-	-	1		-		-		-		_					1	_			-	-	_	1		-	_	-	-		OF OF	03
16/10/2001	N	Probable Cause	APR	P3 NA	EMB-120			1		+		+		1		+	++	+	++	+	1	-	+				1				+	-		1	1 1		-	1		1 M	SF	DS
19/03/2001	N	Probable Cause	CRZ	P3 NA	EMB-120			1		1		+		1		+	++	-	++	-	1		+									-		+	1 1			1		1 M	SF	DS
25/02/2001	N	Probable Cause	DES	P3 NA	EMB-120			1		1		+		+		-	++	-	1				+							_						-		ľ		N	SF	DS
06/12/2000	N	Probable Cause	LDG	P3 NA	EMB-120			1		+		+		1		-	++	+					+				+					-			-	-		+	+		SF	DS
12/08/2000	1	Probable Cause	DES	P3 NA	EMB-120					1		+		1		+	++	-	1			+	+				+					-			-	-		1	-	T N	SF	DS
21/02/2000	1	Probable Cause	DES	P3 NA	EMB-120					1		-		1					1			+																		N	SF	DS
21/05/1997	N	Probable Cause	CRZ	P3 NA	EMB-120												1		1 1																					N	SF	DS
09/01/1997	F	Probable Cause	APR	P3 NA	EMB-120			1															1				1								1	1	1	1		1 H	SF	DS
29/11/1996	1	Probable Cause	APR	P3 NA	EMB-120																																			N	SF	DS



		A	ccident	ts										Fac	tors	;												Factors	s (N	on-Te	chni	ical)								Comp	eter	ncies			Va	lidation
Date	Severity	Info Source Link	Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windshear	Crosswind	ATC	Loss of comms	Traffic	R/W Incursion	Poor Visibility Heet	Wake Vortex	Terrain	Birds	Eng Fail MEL	Fire	Syst mal	ops/rype spec Cabin	Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-DBs Def-Proc's	Fatique	CRM Physio	Workload Distraction	Pressure D.G	LF.P	MIS-AF 3 Mis A/C State	Mis-Sys	Pilot incap Communication	SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
23/06/1996	Ν	Probable Cause	APR	P3	NA	EMB-120																1			1		1																	N	SF	DS
20/02/1996	1	Probable Cause	CLB	P3	NA	EMB-120																1																						N	SF	DS
21/08/1995	F	Probable Cause	CLB	P3	NA	EMB-120													1			1																						M	SF	DS
17/07/1995	Ν	Probable Cause	GRD	P3	NA	EMB-120		1							- 1	1								1						1								1	1		1			L	SF	DS
29/04/1993	Ν	Probable Cause	CRZ	P3	NA	EMB-120			1	1						1								1					1	1	1								1	1	1	1		1 M	SF	DS
09/12/1992	1	Probable Cause	CLB	P3	NA	EMB-120																1																						N	SF	DS
21/07/1992	1	Probable Cause	APR	P3	NA	EMB-120			1	1												1																						N	SF	DS
11/09/1991	F	Probable Cause	DES	P3	NA	EMB-120																1																						N	SF	DS
05/04/1991	F	Probable Cause	APR	P3	NA	EMB-120											_		1			1	_	_												_	_							N	SF	DS
25/08/1990		Probable Cause	CLB	P3	NA	EMB-120							_		_		_		1			1		-							_										_			N	SF	DS
09/04/1990	F	Probable Cause	CLB	P3	NA	EMB-120			_	_		_	_	1			_		_	_		_	_	1			_			1	-					_	1			4	_			M	SF	
09/12/1987	IN	Probable Cause	LDG	P3	INA	EMB-120	_		_	_		_				_	_		_	_		_	_	1		_	_			1	1						_		1	1				IVI	SF	05
13/07/1987	IN	Probable Cause	CLDG	P3	INA NA	EMB-120	_		-	_					-	-	_	-				1	_	1		-	-			1	1		+	_		_	_		1	1	_			IVI	51	05
23/12/1986		Probable Cause		P3 D2	NA NA	EMP 120	_		-	-		-	_		-		_	-	- 1			1	_	+		-	-		+ +		+	_		-		_	-				-				OF OF	- 03
21/10/2007	N	Frobable Gause	TO	F 3	64	Elvid=120	-		-	1		-			-				- 1				_	-		_	-			_	-	_		_		_					-				10	00
27/04/2004	N	Factual		P2	SA SA	FORKELF-27				-		-			-		_		-	-	1	-	_	-		_	-				-	-				_					-				IG	03
10/02/2004		Factual		P2	ASIA	FORKELF-27			-	-		-	_		-	-	_		1			1	_	+		-	-		+ +	_	+	_		-		-	-		+		-				IG	- 03
17/04/2003	N	Probable Cause	DES	P2	NA	Eokkor E 27			-	_	-	-	_		-	-	_	+ +	- 1			1	_	+		-	-		+ +	_	+	_		-		_	-				-				IG	- 03
22/05/2000	N	Frobable Gause	LDG	P2		Eokkor E 27	-		-	_		-	_		-		_		-			1	_	-		_	_			_	-	-				_	_				-				IG	03
05/03/1999	N	Factual	TO	P2	SA SA	Fokker F-27			-	-		-			-		-	-	-	-		1	_	+		-	-		+ +		+	-	+ +			-	-				-			1 11	IG	
01/04/1997	N	Probable Cause	GRD	P2	NA	Fokker F-27	1	1	-			-	-		-		-	+ +	-	-			_	+		-	-		+ +	-	+	-		-	+ +	_	-				-			I N	IG	
04/11/1002		Probable Cause		D2	NA	Eokkor E 27			-			-			-		_		-	-		1	_	-			-		+ +	_	-	-				_	-				-			N	IG	00
23/02/1990	li l	Probable Cause	LDG	P2	NΔ	Fokker F-27			1 1		1	-			-				-	-			-	-						1	-			1		-	1			1	-			M	IG	
30/09/1989	N	Probable Cause	LDG	P2	NΔ	Fokker F-27	-			1 1	1	-	-				-	+ +	-	-		-	_	+	1	1	-		+ +	1	+	-		1		_	1			1	1			1 H	IG	
03/05/1989		Probable Cause	LDG	P2	NA	Fokker E-27			-			-	_		-	-	-	+ +	-	+		1	_	+			-		+ +		+		+ +			-					- 1			N	IG	DS
29/10/1987		Probable Cause	LDG	P2	NΔ	Fokker F-27	-		-	-		1	-	1	-	-				-			_	-		-	-				-					-	-				-			N	IG	00
07/10/1985	N	Probable Cause	LDG	P2	NΔ	Fokker F-27					1	<u> </u>	-		-	-	-	+ +	-	1		1	_	1		-	-		+ +	1	1			1		-	1		1		1			1 H	IG	
09/09/1985	ii I	Probable Cause	TO	P2	NA	Fokker E-27			-	_		-			-	-	_	+ -	1	- <u>-</u>	1	1	_			-	-		+ +				+ +			_									IG	DS
20/03/1985	li l	Probable Cause	GRD	P2	NA	Fokker E-27			-						-						1	1	_	-			-		+ +		-						-				-			N N	IG	DS
13/01/1984	N	Probable Cause	TO	P2	NA	Fokker E-27						-							1			1	-	1						1	-	-					-			1	1 1			H H	IG	DS
18/05/2011	F	Preliminary	CRZ	P3	SA	SAAB 340	-					-			-	1				-							-			1	+	-		1			1			1	· · ·			M	SF	IG
05/04/2010	N	Probable Cause	CRZ	P3	NA	SAAB 340			-			-			-				-	+		-	_	+			-				+										-			U U	SF	IG
04/10/2009	1 1	Factual	CLB	P3	NA	SAAB 340						-							1			1	_	-							-										-			N	SE	IG
30/07/2009	li l	Probable Cause	CRZ	P3	NA	SAAB 340			+	-					-	-	+		- [				1	1		-	+				+	-	+			+	+		+		+				SF	lig
29/07/2008	i l	Probable Cause	GRD	P3	NA	SAAB 340			+	+		-			+	+	+		1			1	1		++		+				+	+	+	-	++		+		+		+			N	SF	liG
16/12/2006	li l	Factual	ТО	P3	AUS	SAAB 340				-						-	+	1	1			1	1	1		-	+		1		+	-				-	+		+ +		-+				SF	IG
13/03/2006	N	Probable Cause	GRD	P3	NA	SAAB 340	1								-									-							-										-			N	SF	liG
02/01/2006	1	Probable Cause	CLB	P3	NA	SAAB 340			-						-	1			-	1		1		1				1		1	-						1	1			1 1		1	H	SF	IG
08/06/2005	1	Probable Cause	LDG	P3	NA	SAAB 340								$\square$	-+	-		-	-			1					+				+	-				-								N	SF	IG
11/02/2005	N	Probable Cause	DES	P3	NA	SAAB 340			1						-		1							1							-										-			U	SF	IG
13/11/2004	N	Probable Cause	GRD	P3	NA	SAAB 340	1												-					1																	-			N N	SF	IG
25/10/2004	N	Probable Cause	GRD	P3	NA	SAAB 340	1	1	+						-									1							-										-+			N	SF	IG
24/02/2004	N	Probable Cause	GRD	P3	NA	SAAB 340		1						1	-	1								1						1						1	1							L	SF	IG

		Ac	ccident	S										Fact	ors												Factor	rs (N	on-T	echni	cal)							(	Comp	eten	ncies			Validation
Date	Severity		Phase	Generation	Region	Туре	Ground equipment	Ground manoeuvring	Adverse Weether/Ice	Windshear	Crosswind	ATC NAV	Loss of comms	Traffic DAM Incrussion	Poor Visibility	Upset	Wake Vortex	Terrain Birde	Eng Fail	MEL	Fire Syst mal	Ops/Type Spec	Cabin Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts Def-Chk lists	Def-DBs Def-Proc's	Fatique	CRM	Workload Distraction	D.G	LF.P Mis.AFS	Mis A/C State	Mis-Sys	Pilot Incap	Communication SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst Checker
01/02/2004	Ν	Probable Cause	GRD	P3	NA	SAAB 340	1																																				N	SF IG
12/11/2003	Ν	Probable Cause	APR	P3	NA	SAAB 340												1																									N	SF IG
21/05/2003	Ν	Probable Cause	GRD	P3	NA	SAAB 340		1						1																													L	SF IG
04/09/2002	I	Probable Cause	CLB	P3	NA	SAAB 340															1																						N	SF IG
21/07/2002	Ν	Probable Cause	GRD	P3	NA	SAAB 340	1																																				N	SF IG
16/07/2002	Ν	Probable Cause	GRD	P3	NA	SAAB 340	1																																				N	SF IG
06/09/2001	Ν	Factual	LDG	P3	NA	SAAB 340													1		1																						U	SF IG
23/05/2001	I	Factual	TO	P3	AUS	SAAB 340													1		1																						N	SF IG
10/01/2001	1	Probable Cause	CRZ	P3	NA	SAAB 340			1										1		1																						N	SF IG
08/11/2000	Ν	Probable Cause	APR	P3	NA	SAAB 340												1					1																				Ν	SF IG
29/09/2000	Ν	Probable Cause	GRD	P3	NA	SAAB 340	1																																				N	SF IG
25/04/2000	Ν	Probable Cause	TO	P3	NA	SAAB 340																																					N	SF IG
21/03/2000	Ν	Probable Cause	LDG	P3	NA	SAAB 340		1	1		1				1			1					1						1				1			1		1	1	1			1 H	SF IG
12/02/2000	1	Probable Cause	GRD	P3	NA	SAAB 340	1																																				N	SF IG
10/01/2000	F	Preliminary	CLB	P3	EUR	SAAB 340			1						1	1							1						1 1	1		1	1			1	1			1		1	1 H	SF IG
08/05/1999	Ν	Probable Cause	LDG	P3	NA	SAAB 340		1	1						1								1					1	1				1				1		1	1			<u>1 H</u>	SF IG
12/04/1999	Ν	Probable Cause	GRD	P3	NA	SAAB 340	1																																				N	SF IG
03/03/1999	Ν	Probable Cause	DES	P3	NA	SAAB 340			1																																		U	SF IG
11/11/1998	I	Factual	APR	P3	AUS	SAAB 340			1							1						1							1				1	1		1		1	1	1			M	SF IG
03/11/1998	F	Probable Cause	GRD	P3	NA	SAAB 340	1																																	_			N	SF IG
18/03/1998	F	Factual	CLB	P3	ASIA	SAAB 340			1						1	1				1	1		1					1	1	1			1	1		1			1	1 1			1 H	SF IG
22/02/1998	I I	Probable Cause	LDG	P3	NA	SAAB 340															1		1	1	1	1	1		1							1		1	1	1			M	SF IG
20/01/1998	1	Factual	CLB	P3	EUR	SAAB 340													1		1 1									_								$\rightarrow$					<u> </u>	SF IG
11/12/1997	Ν	Probable Cause	DES	P3	NA	SAAB 340			1																													$ \rightarrow $					U	SF IG
11/08/1997	1	Probable Cause	GRD	P3	NA	SAAB 340		1													1 1																						N	SF IG
13/05/1997	I I	Probable Cause	CLB	P3	NA	SAAB 340													1		1		1						1	1						1		1		1 1			н	SF IG
20/09/1996	Ν	Probable Cause	GRD	P3	NA	SAAB 340																																					N	SF IG
11/07/1996	Ν	Probable Cause	GRD	P3	NA	SAAB 340																																					N	SF IG
01/07/1996	N	Probable Cause	CLB	P3	NA	SAAB 340													1		1																						N	SF IG
17/11/1995	I I	Probable Cause	CLB	P3	NA	SAAB 340													1		1	1		1	1	1	1																U	SF IG
17/08/1995	N	Probable Cause	GRD	P3	NA	SAAB 340		1													1 1	1		1	1		1											+					N	SF IG
05/07/1995	1	Probable Cause	то	P3	NA	SAAB 340															1																						N	SF IG
12/05/1994	I I	Probable Cause	то	P3	NA	SAAB 340															1		1						1							1		1	1	1 1			н	SF IG
03/05/1994	1	Probable Cause	CRZ	P3	NA	SAAB 340			1										1		1	1																+					U	SF IG
01/02/1994	N	Probable Cause	DES	P3	NA	SAAB 340													1		1	1	1						1					1		1				1			M	SF IG
02/01/1993	N	Probable Cause	LDG	P3	NA	SAAB 340			1						1								1	1	1				1			1	1		1		1			1 1			1 M	SF IG
31/08/1992	1	Probable Cause	CRZ	P3	NA	SAAB 340						_		_					1		1																	+					<u>N</u>	SF IG
21/11/1991	1	Probable Cause	CRZ	P3	NA	SAAB 340													1		1																	+		_			N	SF IG
10/11/1990	1	Probable Cause	CRZ	P3	NA	ISAAB 340						_							_				1						1								1	+	1	1 1			1 H	SF IG
22/11/1989	1	Probable Cause	APR	P3	NA	SAAB 340		_	1	1					1	1							1						1				1			1		+	1	1			1 H	SF IG
24/10/1988	1	Probable Cause	CRZ	P3	NA	SAAB 340			_		+		+	_		-			1		1 1	1	$ \rightarrow $			+				_			-	+	-		L	++					N	SF IG
02/02/1988	1	Probable Cause	LDG	P3	NA	SAAB 340													1		1 1																	+					<u>N</u>	SF IG
09/03/1987	1	Probable Cause	IGRD	P3	INA	ISAAB 340		1	1		1		1								1		1						1					1			1	1	I				U	SF IG



		Ac	ccident	S									Facto	ors												Facto	ors (l	Non-Te	chnic	al)							Compe	tencies	3		Va	lidation
Date	Severity		Phase	Generation Beau	ол Туре	Ground equipment	Ground manoeuvring	Runway/Taxi condition	Adverse vveatner//ce Windshear	Crosswind	ATC NAV	Loss of comms	Traffic R/W Incursion	Poor Visibility	Upset	Wake Vortex Terrain	Birds	Eng Fail	MEL Fire	Syst mal	Ops/Type Spec	Cabin	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-DBs Dof Doc 's	Der-Proc s Fatique	CRM Physio	Workload Distraction Pressure	D.G	LF.P Mis-AFS	Mis A/C State	Pilot Incap	Communication SA	Leadership and Teamwork	Workload Management	Problem Solving Decision Making Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and	Automation Manual Aircraft Control	IIIIproved Training Analyst	Checker
29/10/1985	1	Probable Cause	LDG	P3 NA	SAAB 340															1																				N	I SF	IG
05/02/2006	F	Probable Cause	CRZ	P2 NA	Shorts SD360							1	1															1					-		1		1			1 F	I SF	DS
05/02/2006	F	Probable Cause	CRZ	P2 NA	Shorts SD360							1	1															1					-		1		1	-		1 F	I SF	DS
16/12/2004	N	Factual	LDG	P2 NA	Shorts SD360									1						1		1						1				1			1		1	1		1 F	I SF	DS
09/04/2003	N	Probable Cause	APR	P2 NA	Shorts SD330									1								1						1							1		1	1		1 F	I SF	DS
30/07/2000	N	Probable Cause	CRZ	P2 NA	Shorts SD330																																			N	I SF	DS
25/11/1997	N	Probable Cause	APR	P2 NA	Shorts SD360			1																				1				1			1			1		1 L	SF	DS
09/05/1997	1	Probable Cause	CLB	P2 NA	Shorts SD360															1																				N	I SF	DS
09/07/1996	1	Probable Cause	CLB	P2 NA	Shorts SD360															1													-							N	I SF	DS
02/06/1996	1	Probable Cause	CLB	P2 NA	Shorts SD360															1													-			+		-		N	I SF	DS
12/03/1995	N	Probable Cause	GRD	P2 NA	Shorts SD360		1																										+		-	+		-		N	I SF	DS
18/02/1995	1	Probable Cause	LDG	P2 NA	Shorts SD360															1															-			-		N	I SF	DS
14/06/1993	1	Probable Cause	CRZ	P2 NA	Shorts SD360														1	1																				N	I SF	DS
22/04/1993	1	Probable Cause	CRZ	P2 NA	Shorts SD360			1																1				1					+		1			1		N	1 SF	DS
11/05/1991	N	Probable Cause	GRD	P2 NA	Shorts SD360		1													1													+	-	_			-		N	I SF	DS
02/03/1991	N	Probable Cause	LDG	P2 NA	Shorts SD360															1								1					+		1		1	1		1 F	I SF	DS
11/05/1990	N	Probable Cause	GRD	P2 NA	Shorts SD360		1																1										-					-		F	I SF	DS
19/02/1990	1	Probable Cause	LDG	P2 NA	Shorts SD360													1		1															-	+		-		N	I SF	DS
24/03/1989	1	Probable Cause	CRZ	P2 NA	Shorts SD360			1														1						1					-		1		1	1		F	I SF	DS
07/03/1989		Probable Cause	то	P2 NA	Shorts SD360																							1	1				-	1	1			-			SF	DS
03/06/1988		Probable Cause	APR	P2 NA	Shorts SD360															1													-		_	++		+			I SF	DS
21/05/1986	N	Probable Cause	CRZ	P2 NA	Shorts SD330			1													1								-				+		+	++		+		10	SF	DS
26/04/1984	N	Probable Cause	GRD	P2 NA	Shorts SD330	1	1													1									-				_		+	+		+		1 1	1 SF	DS
21/03/1984	1	Probable Cause	APR	P2 NA	Shorts SD330													1		1								1							+	+	1	1		- N	1 SF	DS
28/10/1983	F	Probable Cause	CLB	P2 NA	Shorts SD330											-		-	_	·	1						-		-				-	+	+	++		-			SF	DS
18/10/1981	N	Probable Cause	CRZ	P2 NA	Shorts SD330			1						-				+	-	+					-		-		-				+		+	+		+			SF	DS
22/06/1981	N	Probable Cause	CRZ	P2 NA	Shorts SD330			1																											+	+		-			SF	DS
11/06/1981	N	Probable Cause	IDG	P2 NA	Shorts SD330			-												1									-				-		+	++		+		- <u></u>	SF	DS
03/06/1980	N	Probable Cause	GRD	P2 NA	Shorts SD330			1						1															-				+		+	++		+			SF	DS
06/08/1979		Probable Cause	TO	P2 NA	Shorts SD330													1		1									-				_		+	+		+			SF	DS
13/02/1979	li l	Probable Cause	IDG	P2 NA	Shorts SD330			1 1												1															+	+		+			SF	DS
10/03/1978	i i	Probable Cause	LDG	P2 NA	Shorts SD330									-		-				1		-			-		-		-				+		+	++		-			SF	DS
04/12/2004	N	Probable Cause	LDG	P2 NA	Convair 580			1 1						1				1	-	1		1			-		-	1	1			1 1	-		+	1	1 1	1		F	is	DS
13/08/2004	F	Probable Cause	APR	P2 NA	Convair 580													1		1	1	1						1	1			1 1			1	1	1	1			lis	DS
03/10/2003	F	Foreign	DES	P2 AUS	Convair 580			1						-	1							-		1	-		-					1	-	-	-	++	1	-			1 JS	DS
06/12/2001	N	Probable Cause	CLB	P2 NA	Convair 580			E P			-			+		+	+	1		1		1					-	1	1			1	-	1	1	++	<u> </u>	1			1 15	DS
02/02/1992	F	Foreign	APR	P2 AFR	Convair 580									1								-			-		-	1	-			1		1		++		-			US	DS
20/11/1991	N	Probable Cause	APR	P2 NA	Convair 600 series												-	+										1	1				+	1		+		1		- <u></u>	JS	DS
18/09/1991	F	Probable Cause	CRZ	P2 NA	Convair 580			1						1	1	-	+	+		+		-					-		1			1	+	1	-	+		1		1 1	1 15	DS
04/08/1989	N	Probable Cause	LDG	P2 NA	Convair 600 series			1						1				1		1		+			-		-	1	1				+	+	+	+	1	+		N	1 JS	DS
03/08/1989	N	Probable Cause	LDG	P2 NA	Convair 600 series									-			-					1						1	1			1	+	1	1	+	1	1		1 1	1 JS	DS
20/01/1989	N	Probable Cause	CRZ	P2 NA	Convair 580											1		1		1	1	1						1	1			1 1		1	1			1		N	1 JS	DS
02/02/1988	N	Probable Cause	LDG	P2 NA	Convair 580			1 1						1		-						-						1				1	-	1		++				1 1	I JS	DS
28/10/1987	N	Probable Cause	DES	P2 NA	Convair 600 series			1										1		1	1	1						1				1 1			1		1	1		F	JS	DS

		Ac	ccident	S								Facto	ors											Fact	ors (	(Non	-Tech	nnica	l)							Con	pet	encies			Val	idation
Date		Info Source Link	Phase	Generation Begor	1 Туре	Ground equipment Ground manoeuvring	Runway/Taxi condition	Adverse Weather/Ice Windeboar	Crosswind	NAV	Loss of comms	Traffic R/W Incursion	Poor Visibility	Upset	Wake Vortex Terrain	Birds	Eng Fail	MEL Fire	Syst mal Ops/Type Spec	Cabin	Compliance	Def Manuals Def-Ops data	Def-Charts Def-Chk lists	Def-DBs	Def-Proc's Fatione	CRM	Physio	Workload Distraction Pressure	D.G L.F.P	Mis-AFS	Mis A/C State	Mis-Sys Pilot Incap	Communication	SA Leadershin and	Teamwork	workioaa management Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
24/03/1987	N	Probable Cause	TO	P2 NA	Convair 580			1	1								1		1		1					1					1			1		1		1		1 H	JS	DS
25/04/1986	N	Probable Cause	CRZ	P2 NA	Convair 580			1																																U	JS	DS
06/11/1983	N	Probable Cause	APR	P2 NA	Convair 580								1			1																								N	JS	DS
09/01/1983	F	Probable Cause	LDG	P2 NA	Convair 580		1						1		1		1		1			1									1									1 M	JS	DS
04/11/1981	N	Probable Cause	TO	P2 NA	Convair 580																					1					1		1							1 M	JS	DS
30/12/1980	I.	Probable Cause	TO	P2 NA	Convair 580														1																					N	JS	DS
07/08/1980	I	Probable Cause	LDG	P2 NA	Convair 580														1 1																					N	JS	DS
31/10/1979	I	Probable Cause	LDG	P2 NA	Convair 580		1	1	1				1																		1									M	JS	DS
26/07/1979	Ν	Probable Cause	CRZ	P2 NA	Convair 580															1																				N	JS	DS
31/05/1979	Ν	Probable Cause	GRD	P2 NA	Convair 600 series													1	1																					U	JS	MS
19/01/1979	Ν	Probable Cause	GRD	P2 NA	Convair 580														1 1																					N	JS	MS
18/11/1978	N	Probable Cause	GRD	P2 NA	Convair 600 series														1 1																					N	JS	MS
03/10/1978	1	Probable Cause	CLB	P2 NA	Convair 600 series													1	1																					N	JS	MS
25/07/1978	Ν	Probable Cause	то	P2 NA	Convair 580											1	1		1		1					1					1			1				1		1 H	JS	MS
20/04/1978	N	Probable Cause	LDG	P2 NA	Convair 580												1		1		1					1					1					1				1 M	JS	MS
18/03/1977	N	Probable Cause	GRD	P2 NA	Convair 580	1											_				1					1	ľ	1	_					1	1			1		1 M	JS	MS
21/12/1976	N	Probable Cause	GRD	P2 NA	Convair 580		_	1				_	1							_			+			_			_				_		_	_	_			N	JS	MS
10/11/19/5	N	Probable Cause	LDG	P2 NA	Convair 580		_	_		_	+	_	_		_		1	1	1	_		_				_	+		_			_			_	_	_				JS	MS
09/07/1975	I NI	Probable Cause	ICLB	P2 NA	Convair 580		_			_		_	_		_		1	1	1							_			_			_			_	_	_			N	12	MS
20/06/1975	IN N	Probable Cause		P2 NA	Convair 580		-	1		-	+	_	-		-		-			_		_	+ $+$			_			_	-		-	-		-		-				12	MS
13/01/1974		Probable Cause	APR CDZ	P2 NA	Convair 560 earles		-	1		+		-	1		1		$\rightarrow$			_	1	_	+			1			_	-	1	-	-	1	-	1	-	1	-		10	MC
27/09/1973		Probable Cause		P2 INA	Convair 500 series		-			-		_	1		- 1		-		1 1		1	_				1			_		1			1		1	-	1			10	IVI S
31/05/1973	IN I	Probable Cause	LDG	P2 NA	Convair 500		-	_		-		_			-		-		1 1							-			_						_	-	-				10	MS
04/12/1972	N	Probable Cause	CP7	P2 NA	Convair 590		-	1		-		-	1		-		-					_	+			-				-		-	-		-	-	-				10	MS
24/11/1972		Probable Cause	GRD	P2 NA	Convair 580	1			1		+ +	1			-		-			-		-				-			-	-		-	-		-	-	+				15	MS
29/06/1972	F	Probable Cause	CRZ	P2 NA	Convair 580			1				1	1				-					-				1		-	-			-	-	1	-						15	MS
08/05/1972	N	Probable Cause	GRD	P2 NA	Convair 600 series		-			+					-		-		1 1			+						-	-			-			-	-	+			Hŭ	JS	MS
23/03/1972	1	Probable Cause	IDG	P2 NA	Convair 600 series		-	-		-		-			-		-		1 1			-				-			-			-			-	+	-			t lu	JS	MS
11/03/1972	N	Probable Cause	I DG	P2 NA	Convair 580												1		1			-				-					1						+			1 H	JS	MS
16/02/1972	N	Probable Cause	IDG	P2 NA	Convair 600 series												1	1	1													-				-	-				JS	MS
20/08/1971	N	Probable Cause	LDG	P2 NA	Convair 580					-					-				1 1			-										-			-	-	-			Ň	JS	MS
07/06/1971	F	Probable Cause	APR	P2 NA	Convair 580			1					1		1		-				1	-				1					1	-	1			1		1		1 H	JS	MS
29/01/1971	1	Probable Cause	то	P2 NA	Convair 580														1												1									1 M	JS	MS
04/01/1971	1	Probable Cause	APR	P2 NA	Convair 580												-		1 1																					N	JS	MS
23/12/1970	N	Probable Cause	LDG	P2 NA	Convair 580														1 1																					U	JS	MS
01/01/1970	I	Probable Cause	LDG	P2 NA	Convair 580														1 1														1							N	JS	MS
10/12/1970	N	Probable Cause	LDG	P2 NA	Convair 600 series			1	1										1												1		1							1 H	JS	MS
03/11/1970	1	Probable Cause	CRZ	P2 NA	Convair 580														1								1													N	JS	AS
20/10/1970	1	Probable Cause	CRZ	P2 NA	Convair 580													1	1																					N	JS	AS
16/09/1970	Ν	Probable Cause	CRZ	P2 NA	Convair 600 series			1																																U	JS	AS
28/06/1970	1	Probable Cause	CRZ	P2 NA	Convair 580																								1			1								U	JS	AS
01/02/1970	1	Probable Cause	LDG	P2 NA	Convair 580		1										T									1					1	1		1		1				1 H	JS	AS
01/02/1970	N	Probable Cause	LDG	P2 NA	Convair 580						ΙT			I T		IT	- E				1				1	1	ιT	Т		1 -	1 T		1 7	1	1		1	1		M	JS	AS


# Evidence-Based Training Accident-Incident Matrix Continued

		A	ccident	5							Fa	ctors						Factors (Non-Technical) Competencies					Valic	lation															
Date	Severity		Phase	Generation oi6aa	n Type	Ground equipment	Browny/Taxi condition	Adverse Weather/Ice Windshear	Crosswind ATC	NAV	Loss of comms Traffic	R/W Incursion Poor Visibility	Upset Wake Vortex	Terrain	Birds Eng Fail	MEL Fire	Syst mal	Ops/Type Spec Cabin	Compliance	Def Manuals	Def-Ops data Def-Charts	Def-Chk lists	Def-Proc's	Fatique CRM	Physio Workload Distraction	Pressure	LF.P	Mis-AF3 Mis A/C State	Mis-Sys	Pilot Incap	Communication SA	Leadership and Teamwork Workload Management	Problem Solving Decision Making	Knowledge	Application of Procedures & Knowledge	Flight Management, Guidance and Automation	Manual Aircraft Control Improved Training	Analyst	Checker
01/08/1969	Ν	Probable Cause	LDG	P2 NA	Convair 600 series												1	1																			N	JS	AS
27/12/1968	F	Probable Cause	APR	P2 NA	Convair 580		1	1				1		1					1					1			1	1				1	1				1 H	JS	AS
24/12/1968	F	Probable Cause	APR	P2 NA	Convair 580		1	1				1							1					1				1				1	1	1	1		Н	JS	AS
12/11/1968	Ν	Probable Cause	LDG	P2 NA	Convair 580												1		1					1				1	1			1 1		1	1		М	JS	AS
04/08/1968	F	Probable Cause	DES	P2 NA	Convair 580		1	1				1					1							1				1				1	1	$\square$			М	JS	AS
25/07/1968	N	Probable Cause	LDG	P2 NA	Convair 580												1																	$\vdash$			N	JS	AS
23/07/1968	1	Probable Cause	CRZ	P2 NA	Convair 580		1	1																1				1			1		1	$\square$			M	JS	AS
24/06/1968	N	Probable Cause	APR	P2 NA	Convair 580		1	1				1		1	1	1	1		1					1	1 1						1	1			i j		н	JS	AS
28/01/1968	N	Probable Cause	CRZ	P2 NA	Convair 600 series		1	1			_	1					-																	$\mapsto$			U	JS	AS
08/09/1967	N	Probable Cause	LDG	P2 NA	Convair 580						_						1	1																$\mapsto$			N	JS	AS
25/04/1967	N	Probable Cause	APR	P2 NA	Convair 600 series						_					1	1	1																$\vdash$			N	JS	AS
27/03/1967		Probable Cause	CRZ	P2 NA	Convair 580						_						_		_							_				1				⊢+			IN	12	AS
24/01/1967	1	Probable Cause	GRD	P2 NA	Convair 580			_		_	_			+ +			_		4		_	+		1		_		1		_	1	1					I H	12	AS
23/01/1967	IN	Probable Cause	APR	P2 NA	Convair 600 series			_			_	++		+ +			-		1		_	+		1		_		1		_	1	1		⊢ <b>₽</b>	-		1 H	12	AS
14/12/1900	I NI	Probable Cause	ADD	P2 INA	Convair 500						_						1		1		-					_		- 11		_	1	1		<u> </u>				10	AS
27/06/1066	IN N	Probable Cause	DEC	P2 INA	Convair 600 series		-				_	1					-		-									-		_	-			$\rightarrow$				10	AS
2//00/1900		Frobable Gause		P2 INA	ATRA2						_			-			-		-		-		_			_		+		_	_			$\rightarrow$				10	AS
11/20/1996		Probable Cause	GRD	P3 NA	ATR42					-	_			+ +			1		+		-					-		+		-	_			$\rightarrow$				15	
4/3/1006	li l	Probable Cause															1		-							-				-				-+			N	16	10
3/4/1995		Probable Cause	DES	P3 NA	ATR42		-	1			_			+ +			-		-			+				-		+		-	-			+				15	45
3/13/1993	i i	Probable Cause	TO	P3 NA	ATR42				1		1						+		-		-		_			-		+		-	_			$\rightarrow$				JS	AS
12/22/1988	i i	Probable Cause	APR	P3 NA	ATR42		-	1					1				+		-					1		-		1	1	-	1							19	AS
1/18/1988	i i	Probable Cause	CRZ	P3 NA	ATR42										1	1	1		-							-				-				Ē				JS	AS
12/18/1986	i i	Probable Cause	APR	P3 NA	ATR42			1						+ +					-	1		+		1		-		+		-							-H	JS	AS
8/6/2000	ti t	Probable Cause	TO	P3 NA	ATR42			-	1		1						+		-									+						Ē			N	JS	AS
6/15/2005	N	Probable Cause	DES	P3 NA	ATR42		-	1									-											-		-				-+			N	JS	AS
3/19/2003	N	Factual	CRZ	P3 SA	ATR42			1									-		-									-		_				-+			N	JS	AS
4/26/2001	N	Probable Cause	CRZ	P3 OTH	ATR42			1									-		-					1				+		1			1	-+			M	JS	AS
7/23/2000	1	Probable Cause	CRZ	P3 NA	ATR42												1		-															-			N	JS	AS
8/13/1999	N	Probable Cause	GRD	P3 NA	ATR42	1																															N	JS	AS
12/17/1998	N	Probable Cause	LDG	P3 NA	ATR42		1 1	1	1															1									1				1 H	JS	AS
10/25/1998	N	Probable Cause	GRD	P3 NA	ATR42	1																		1							1			1			н	JS	AS
9/17/1998	N	Probable Cause	DES	P3 NA	ATR42								1																					1			N	JS	AS
3/10/1998	1	Probable Cause	CRZ	P3 NA	ATR42												1																				N	JS	AS
12/30/1995	Ν	Probable Cause	DES	P3 NA	ATR42		1	1																													N	JS	AS
7/25/1993	Ν	Probable Cause	GRD	P3 NA	ATR42	1																															N	JS	AS
5/4/1993	N	Probable Cause	LDG	P3 NA	ATR42																			1				1					1				1 H	JS	AS
4/4/1993	F	Probable Cause	GRD	P3 NA	ATR42	1											1																	μT			N	JS	AS
3/31/1993	1	Probable Cause	UNK	P3 NA	ATR42											1	1	1																$\square$			N	JS	AS
3/4/1993	1	Probable Cause	APR	P3 NA	ATR42			1											1					1				1	1				1	1	1		M	JS	AS
11/20/1991	1	Probable Cause	DES	P3 NA	ATR42								1																					$\rightarrow$			<u>N</u>	JS	AS
9/14/1991	N	Probable Cause	CRZ	P3 NA	ATR42										1	1	1																	$\rightarrow$			N	JS	AS
7/17/1991	IN	Probable Cause	IAPR	IP3 INA	IATR42										1	1	11			1													1	( L	1		IN	JS	IAS

Figure A3.1 (cont.)

# Evidence-Based Training Accident-Incident Matrix Continued



Figure A3.1 (cont.)



# 3.2 ACCIDENT/INCIDENT SPREAD SHEET – GUIDANCE FOR PILOT-ANALYSTS

The following instructions were given to pilot analysts in order to complete the spreadsheets. For further information see Chapter 3, Methodology.

- Read the Accident/incident Report from the NTSB database carefully and insert information in the spreadsheet based on that information. If the information is sketchy or not sufficient, then you may find that same accident in the ASN database particularly if it is a fatal accident. Use that information as well if the source of the ASN report is an official accident report or refers to an official document. The link to the ASN Accident database is: http://aviation-safety.net/database/
- The first 9 columns are general information and should be filled already except for the **phase** (of flight) column. You should fill out the **Phase** column from the information in the report. Sometime the events occurs over several phases and when that is the situation, use the initial phase where the event occurred (Note there is a pull down menu for the phase column please use it).
- 3. The 10th column begins the Factors (Note the title in blue). Insert the number 1 in the cell if parameter occurred **during** the accident/incident; if it did not occur during the accident/incident, leave the cell blank. The factor should be mentioned or logically implied for you to put a 1 in the cell.
- 4. The next 5 columns after the Factor columns are the non Technical Competencies columns Note that the title cells are magenta. Important: For each accident/incident you are allowed only two insertions in the columns that have magenta highlighted titles. In other words you must choose the two best non-technical competencies of the 5 magenta titled columns.
- 5. The next 4 columns (title cells are highlighted in green) are technical competencies. There is no restriction here so please fill any cell that applies to the accident-incident event.
- 6. The next column is labeled **Improved Training** insert a **letter** grade from the drop down menu. The meaning of each letter is defined by the comment imbedded in the title cell for that column.
- 7. Highlight a cell blue if you are unsure of the response that you made or if you are unsure if a response is required from the report. The reconciliation team will decide the appropriate response.
- 8. The last two columns are for your initials. If you are the primary analyst initial each cell in the Analyst column as you complete the analysis for the accident-incident in that row; if you are the Checker initial each cells in the Checker column.
- 9. If you are the **Checker** and you **disagree** with the response of the **Analyst**, highlight the appropriate cell in red. (Do not change the original response) (Applies to all columns).
- 10. For column labeled **Improved Training** If you are the Checker and you disagree with the analyst, highlight the analyst's choice in red and insert your response in the first open cell to right on the same row. The reconciliation team will decide the appropriate response.
- 11. If you are the **Checker and you think that a cell should have a '1' but the cell does not,** then highlight the empty cell in red. (An empty cell highlighted in red indicates that the checker thinks the cell should have a 1 but the analyst did not put insert a '1'. In the following round (Reconciliation) a decision will be made as to whether or not the factor or competency was merited.
- 12. **Special notes:** Experience has shown that common error occurs so here are a few things to watch:
  - a. Remember, if you have inserted any 1's in magenta labeled columns (non-technical skills), then you must insert a 1 in the column labeled CRM as a non technical skill is part of CRM.
  - b. Pay special attention to Ops/Type Spec. Its comment is not as clear as it should be. The meaning of this parameter is type specific characteristics of the aircraft such as: Side stick and non-moving thrust levers on the FBW (Airbus), deep stall characteristics on some T-tailed aircraft, go-levers, etc. One that comes to mind is the Autopilot override on the A300. If any of these characteristics were a factor in the accident/incident mark a 1 in the applicable cell. Disregard the phrase in the comment "Please state the issue you are grading".



- c. Pay special attention to Mismanaged Aircraft State as it occurs quite frequently e.g. unstable approach, abnormal landing etc. particularly if manual handling or automation is an issue. Do not forget it even though it was noted in those specific cases.
- d. Keep in mind that the factor columns are not mutually exclusive. Some factors are subsets of others. Some examples of this are:
  - i. If there is Adverse Weather than most probably there will be at least one or more factors present e.g. visibility, crosswind etc.
  - ii. If you have inserted a 1 for Eng. Fail, a 1 is required for Sys Mal.
- 13. Please make no other changes to the spreadsheet, as they all must have the same format for the 2<sup>nd</sup> stage of analysis.
- 14. Please work by alone, so as to be able to have an independent check function.
- 15. If you have any question on a response highlight the cell blue For general questions email johnscully@gmail.com
- 16. When finished please save the file exactly as you received it except for the following:
  - Change the version number by one (e.g. v5 becomes v6)
  - Change the date to the current date saved
  - Put your initials after the date if you are the Analyst or after the initials of the Analyst, if you are the Checker.
  - An example of a file name saved by a checker might be: Accident-threats\_t9 DC 9 2010 11-07\_v8 ML\_DS.xlsx

Note: ML is the initials of the analyst and DS are the initials of the checker.



# APPENDIX 4 AIRLINE PILOT PERCEPTIONS OF TRAINING EFFECTIVENESS



# **Airline Pilot Perceptions of Training Effectiveness**

Barbara Holder, PhD Flight Deck Concept Center Boeing Commercial Airplanes barbara.e.holder@boeing.com

#### Introduction

In collaboration with the International Air Transport Association (IATA) and the International Federation of Air Line Pilots Associations (IFALPA), Boeing surveyed the professional pilot community for their perspectives on pilot training and the application of those knowledge and skills presented in training to operational contexts. The results indicate that improvements are needed in the areas of instruction, content, and delivery methods.

We conclude training could be improved to prepare pilots for their actual work by delivering content that is relevant to daily flight operations. Training delivery mechanisms could be modernized, instruction could be improved through instructor qualification, standardization, and calibration. For training change to be successful and sustainable all interacting dimensions of instructors, content, methods, and airline culture must be addressed.

#### Method

The survey explored pilot perceptions of current training and the effectiveness of their application to the operational context of airline flying. It was intended to identify areas where training may be lacking to create targeted interventions or to identify follow-on research activities. Boeing made the survey available to airline pilots through a link on the International Federation of Air Line Pilots Association (IFALPA) website. IATA member airlines were notified of the survey via email. All responses were anonymous.

The results will be added to the International Air Transport Association (IATA) data corpus, which includes data from Line Oriented Safety Audit (LOSA) reports, global accident and incident data, and other surveys. Because this survey was conducted to supplement the IATA Evidence Based Training (EBT) initiative the probe topics were defined by the EBT data team. The were areas where current data was needed on specific topics or where there were gaps in the data corpus.

# **Pilot Demographics**

Nine hundred and sixty-six pilots completed the survey: fifty-six percent captains and forty-four percent first officers. Figure 1 shows the distribution of respondents with majorities based in Europe, North America, and Oceania. We attribute the higher response rates in these regions to the higher IFALPA representation across these regions. Other regions represented were Middle East, Asia, Central and South America, Africa, and the Commonwealth of Independent States (CIS). The lowest response rate came from regions that also have the highest regional safety risk. Regulators could actively promote higher levels of safety in these regions by supporting improvements to global training and, thus, all operators would be training to a higher safety standard.



Figure 1. Global Distribution of Respondents



Figure 2. Pilot Training Delivery and Most Recently Completed Training

Most pilots (94%) are trained by their airline so instituting change in training practices will require motivating airlines to invest in change and their regulators to approve change (Figure 2). The most recently completed training for our respondents was recurrent training (84%), therefore the responses given are likely to be framed in the context of their last recurrent training experience.



Figure 3. Distribution of Aircraft, Base Location, and Pilot Rank—Captains are represented in blue, first officers are represented in red, and aircraft are identified by type.

# Automation

Learning to use the flight management automation in modern airplanes continues to be a challenge for many pilots. Training should enable pilots to develop a functional understanding of the system as well as operational understanding of how to use the system across operational situations.

Pilots were asked: in the first 6 months of flying their current aircraft type, did you encounter a situation where you had difficulty performing particular tasks using the flight management system (FMS)? This question was framed in the last 6 months so that we could get a recent sample of events and issues encountered and most pilots (64%) responded they had difficulty performing tasks with the FMS (Figure 4).



# Figure 4. First 6 Months on Current Aircraft: Difficulty Performing Tasks Using FMS

Next, we asked for an assessment of their comfort level in operating the FMS after the completion of the type-rating course. Comfort is a term pilots frequently use to describe confidence in their ability to perform. The question was framed in terms of time increments following the type course to identify the time by when comfort is acquired. Respondents could choose one of the following categories: on your first aircraft flight, after initial operating evaluation (IOE), after 3 months of operation, after 6 months of operation, and after 12 or more months of operation (Figure 5).

Most pilot (62%) felt comfortable operating the FMS only *after* gaining line experience. A few (15%) were comfortable after their initial operating experience (IOE). Others (41%) reported comfort after three months of line operations, after six months (15%) and after twelve months (7%).

If the type-rating course did in fact prepare pilots for line operations, we would expect their reported comfort level to be highest immediately after completion of training. It appears some training programs do instill pilot confidence on their first aircraft flight after training since a quarter (23%) reported being comfortable operating the FMS on their first flight.



Figure 5. When Pilots Felt Comfortable Operating FMS After Type-Rating Course

These results raise some interesting questions about what is being learned after IOE that enables the feeling of comfort that could be brought into training earlier. We also need to know what specifically constitutes effective learning on the line.

Pilots often report that the learning of the flight management system (FMS) occurs over time. We designed the next question to identify how FMS learning is distributed. Respondents estimated the percentage of learning they acquired between training, line operations, and self-study. The results showed the following distribution:

• FMS learning on the line—42%.

- FMS learning from training—38%.
- FMS learning through self-study—20%.

If it is the case that only thirty-eight percent of learning occurs in training then we are failing our pilot community by unnecessarily forcing learning this important system through other means that may or may not be effective. We need to identify what content is needed in training to address this issue and define effective delivery methods that enable higher retention and understanding.

Line operations may be the best context for the integration of skills and knowledge across operational contexts but we need to ensure that airlines are equipped with the tools and guidance needed to enable effective line learning.

The next question inquired about areas of automation training that could be improved and respondents could check up to three options (Figure 6). Operational situations such as automation surprises (57%), hands-on use in operational situations (52%), and transitions between modes (32%), received the highest response rates. Pilot training needs to include functional operation of systems but clearly operational situations need to be introduced into training to expose pilots to using the system in the context of flight operations.

Pilots also citied basic knowledge of the system and programming as areas for improvement which is surprising because these areas tend to be emphasized in recurrent and type-rating courses and indicate functional training of the system could be improved.



Figure 6. Potential Areas of Improvement for Automation Training

# **Go-Around Maneuvers**

The industry currently regards go-around maneuvers as a safety issue because they are either poorly executed or not executed when they should be. The next set of questions probe the rationale underlying rationale the go around decision to continue to landing when a go-around should have been made. The first question inquires about the teamwork component of the decision. We asked, "Did you encounter situations where there should have been a go-around but the approach was continued to a landing?" If they answered yes, they were presented with three options:

- a. I suggested a go-around, but the other pilot disagreed (20%).
- b. The other pilot suggested a go-around, but I disagreed (8%).
- c. Neither pilot suggested a go-around (72%).

The majority of the reported cases, neither pilot suggested a go-around and in the remaining cases the pilots did not agree to go-around. Pilots were permitted to report up to five go-around cases and in all cases, the main result was: neither pilot suggested a go-around. We asked the pilots to report their rank (captain, first officer) and role (pilot flying, pilot monitoring, and augmented crew).

In the cases when one pilot suggested a go-around and the other pilot disagreed, we correlated their rank to compliance with the suggestion of a go-around (Table 1). These results raise concerns regarding the effectiveness of training team decision making and effective communication because we do see the influence of rank entering the decision making process.

Response Categories	Captain	First Officer
I suggested a go-around, but the other pilot disagreed	13.8%	27.6%
The other pilot suggested a go-around, but I disagreed	12.3%	2.8%
Neither pilot suggested a go-around	73.9%	69.7%

# Table 1. Distribution of Responses by Rank

Although a pilot may feel he can suggest a go-around or even demand one from the pilot flying, the other pilot may not comply. For those cases where neither pilot suggested a go-around, it may be that pilots lack familiarity with the go-around criteria or the skill to recognize the need in time to make the decision across operational contexts. Neither pilot suggesting a go-around may be due to the pilots' ability to make the approach work and apply judgment to maintain safety.

The next question inquires about how assertive a pilot feels he can be while in the role of pilot monitoring across different contexts. We asked, "When you are the Pilot Monitoring, you feel you may without hesitation..." Pilots were asked to indicate their agreement with each of the context categories and the percentages in Table 2 represent the distribution of agreement.

Pilots reported high levels of assertiveness in four of the five categories, with taking control from the pilot flying registering the lowest at forty-nine percent. The level of reported assertiveness appears to be linked to the level of resulting intervention. Tasks such as identifying a deviation (92%) or proposing a checklist (91%) are reportedly more likely to be asserted than tasks such as proposing a go-around (83%) or demanding a go-around (80%). One could argue deviations and checklists are higher to assert because they are routine and do not so much challenge the skill or judgment of the pilot flying.

Response Categories	Distribution
Tell the pilot flying about a deviation	92%
Take control from the pilot flying	49%
Propose a checklist if the pilot flying delays asking for it	91%
Propose a go-around during an unstable approach	83%
Verbally demand a go-around if you think it is required	80%

# Table 2. Distribution of Responses to Assertiveness

We learned from the previous question that pilots do assert themselves in the go around maneuver however at a much lower rate (28%) than the case where neither pilot suggested a go-around (72%). It is possible that a lack of assertiveness is the underlying reason why, in the majority of the cases, neither pilot suggested a go-around and that there is an underlying hesitation to assert oneself as the context shifts to a control or judgment assessment. Half the pilots reported they would not hesitate to take control from the pilot flying yet at what point does it become acceptable to take control? How should this skill be trained and assessed? Taking control away from the pilot flying perhaps crosses the boundaries of judgment with regard to one's partner and oneself. A pilot will need to be very confident in his judgment of the need to take control. How best to train and assess these behaviors on a global scale needs further investigation.

The Line Operations Safety Audit (LOSA) reports database suggests most unstable approaches are continued to landing. We asked the respondents to make a judgment about why another pilot would not initiate a go-around to probe for possible rationales for not doing the maneuver. We asked, "In your opinion what are the reasons for not initiating a Go-Around?" They were presented with the six following options and could choose up to three:

- a. According to the judgment by the pilot, the landing can be performed safely
- b. There is a big psychological barrier to go around because they are so rare events
- c. Operational inconvenience
- d. Embarrassment related to a go around
- e. Pilots are not as familiar with unstable approach criteria as they should be
- f. Making a go-around mandates a report

Pilot judgment was most cited (82%) as the reason a pilot would choose not to go around if the approach was unstable (Table 3). This response is certainly reasonable. One of the primary roles of pilots is to apply judgment and interventions in the moment-to-moment context of activity. However, it is our assessment that most training programs train judgment implicitly and if pilots are going to be relying on judgment we should make sure it is explicitly trained to effectively transition to the operational context.

The next two major category responses were psychological barriers (37%) and operational inconvenience (35%). Psychological barriers may be perceived by pilots do the maneuver infrequently in operations and in training. By providing opportunities to practice the maneuver across contexts (such as all engine go around) is important to building a pilot's confidence in his skills. Operational inconvenience could be a safety concern if pilots are choosing to not go around for the wrong reasons.

Response Categories	Distribution
Pilot judgment	82%
Psychological barrier	37%
Operational inconvenience	35%
Embarrassment	24%
Unfamiliar with criteria	17%
Mandates a report	10%

# Table 3. Reasons for Not Choosing Go-Around

# **Monitoring and Cross-Checking**

The next set of questions was designed to inquire about the pervasiveness of error management in flight training and the perceived value as a skill. Monitoring and cross-checking, two key components of error management, are perceived as important piloting skills (Figure 7). Forty-seven percent of the pilots reported the topic of detecting and managing errors are included in their recurrent training as a specific topic in both theory and practice (Figure 7). However the remaining respondents reported the topic of as implicitly covered, or not covered at all.

Although a majority of pilots believe these are important skills, the training of these tasks is not as wide-spread as previously thought and is evidence that guidance for training monitoring and cross-checking skills is needed. The pilot monitoring role is one of the most important for maintaining high levels of safety and operational efficiency and should be trained explicitly on a global scale.



#### Figure 8. Inclusion of Error Management in Recurrent Training

The LOSA reports identified the *climb phase of flight* as one with the highest rate of poor monitoring performance. We asked why this might be the case and the respondents reported the main causes of degradation in monitoring during the climb to be complacency and secondary task loading (Figure 8). Complacency may be induced by the transition from a high workload flight phase to lower workload flight phase. Monitoring tasks are often dropped for competing secondary task demands. In training, monitoring should be emphasized as one of the most important primary tasks and pilots should be taught how to monitor and when. We should also give pilots strategies for managing their workload in all flight phases so that monitoring is not dropped inappropriately.

Most pilots (93%) believe detecting and managing errors is the most effective strategy for error management (Figure ). A small percentage of pilots (7%) believe that errors should not be committed.



Figure 10. Strategy for Error Management

# Briefings

Briefings present an important opportunity for pilots to construct a team concept and build shared understandings about what to expect, each other's roles, and contingency plans. It is important that briefings be included in training so pilots can practice these skills and receive feedback on their content, duration, and effectiveness.



Figure 11. Approach Briefing Frequency in Training

Approach briefings are included in training (Figure 11) however there were a number of respondents provided comments citing that appropriate briefing content is generally not known or practiced. It is a positive finding that pilots get an opportunity in the training environment to practice briefings and providing guidance on their conduct and content would be a positive step toward improving their effectiveness in operations.

Briefings prior to the simulation sessions are regularly included in training and present a potentially valuable opportunity for focused instruction (Figure 12). These sessions tend to be longer than the debriefing sessions by 20-30 minutes (Figure 13). Because debrief sessions are vulnerable to dismissal due to time constraints or late night sessions, care should be taken to make effective use of the debrief. At minimum, instructors should use the debrief sessions as an opportunity for the trainees to review and reflect on their performance. Instructors have a crucial role in making effective use of briefings and ensuring that all appropriate feedback (positive and negative) is given.







Figure 13. Debriefing Duration After Simulator Session

# **Intentional Deviations**

Part of pilot judgment and expertise involves knowing when to deviate from Standard Operating Procedures (SOP). We were interested in the frequency and conditions under which pilots might deviate from their company's SOPs (Figure 14).



Figure 14. Frequency of Pilot Deviation From SOPs

Figure 14 shows that a majority of the respondents (53%) would deviate if they believe it increases safety and twenty-nine percent would deviate if it resulted in no reduction in safety. Overall, most (83%) pilots would exercise judgment to intentionally deviate from company SOPs with their judgment being the pilot's assessment of safety. Another seven percent reported they would never deviate. In the next series of questions, we asked pilots to identify the specific intentional deviations they have experienced on the flight deck.





Intentional deviations from stable approach criteria were reported to occur at a rate of once per year by 40% of the respondents and more than a few times a year by 38% of the respondents (Figure 15). However, some pilots report intentional deviations from stable approach at a higher rate of every ten flights, or virtually every flight. Further inquiry into stable approach deviations should identify the contexts in which these judgments are made and why they are made. It would seem these rates are indicative of conflict between the criteria and the realities of the operational context.

Intentional deviations from checklists occurred a reported every ten flights by 13% of the respondents, a few times a year by 30% of the respondents, and once a year by 36% of the respondents. Very few (4%) reported a deviation on every flight. Checklist deviations occurring at this high of a rate suggest other factors may be involved not related to compliance. Perhaps the pilot does not know the procedure or policy, or does not understand it and several pilots commented to us they would like to know the underlying rationale of the procedure. Further the procedure may not make operational sense to the pilot, it may not fit into the operational context where it is to be applied, or the procedure



Figure 16. Frequency of Intentional Deviation From Checklist

may be interrupted by competing demands on attention—all of which may result in noncompliance. Finally poorly designed procedures may impose excessive cognitive workload, thereby making them difficult to perform correctly.

Callouts had a high intentional deviation rate with about half the respondents (49%) reporting deviations on every 10 flights and virtually every flight (Figure 17). There are several possible reasons why non-compliance is high, most again not necessarily related to compliance. Callouts serve an important purpose of establishing shared understandings and representations of the situation. If pilots do not understand the purpose of the callout or if the callout does not fulfill the purpose by design then we would expect pilots to not use them. The shear number of callouts to remember may be a reason for not making them; pilots may simply forget to make them in the context of a demanding situation or a lapse in monitoring, or the pilots may not feel they are important. If we are to understand intentional deviations from callouts, we will need to investigate the specific callouts deviated from and the contexts of their occurrence and provide guidance on appropriate training of callout use.



Figure 17. Frequency of Intentional Deviation From Callouts

# **Operational Situations**

It is important that the knowledge and skill acquired in training transfer to operations. We tried to identify areas where knowledge and skill transfer may break down and to identify gaps in training content. We asked, "In the last six months, did you encounter an operational situation where you did not feel comfortable?" Just over half (54%) of the respondents answered yes (Figure 18). Within that category, 57% of the reporting pilots were ranked captain and 43% were ranked first officer.



# Figure 18. Experienced Uncomfortable Operational Situations During Last Six Months

If they answered yes, we then asked the pilots to specify what kind of training might have helped in the situation and to select all areas of training that would have helped (Figure 19).



# Figure 19. Training Identified by Pilots to Deal With Uncomfortable Operational Situations

Adverse weather (30%) and crew resource management (23%) were ranked highest for being helpful in dealing with uncomfortable operational situations, followed by training in non-normal checklists (16%),

flight management (15%), airplane handling (13%), systems (12%), and maneuvers (10%). All of these categories are addressed in recurrent training sessions. These results question the effectiveness of the training and its transfer to the operational contexts where they are encountered.

The pilots were then asked to describe the situation they encountered (Table 4). The responses included flight management specific to operational tasks, such as a late runway change or reroute, knowledge issues related to auto flight mode understanding, and procedural issues associated with the introduction of new procedures or changes driven by mergers that resulted in poor procedure integration. Infrequent non-normal events such as low fuel, bird strike, CDU failure, upset recovery, and volcanic ash were also mentioned. Adverse weather responses specified cold weather operations, de-icing, contaminated runway operations and high altitude turbulence. Also cited were non-precision and visual approaches, energy management in the approach, severe crosswinds, go-around and missed approaches, and aircraft handling and maneuvers, particularly in regions of mountainous terrain. Performance calculations, diversion, minimum equipment list (MEL) items, systems knowledge, and conflict management with a crewmember or a passenger were cited.

Runway closure at destination prompting holding and possible divert in busy European airspace
Visual circle to land in EWR Rwy 29 due to massive crosswind
In everyday ATC requirements of speed and last minute changes, there is no training given
While flying at FL400, encountered stick shaker in turbulence due to momentary severe updraft
Tailwind approach over steep terrain simultaneously intercepting localizer and glide slope
At 37,000 feet, escape maneuver for wake turbulence from heavy aircraft (747)
Procedures and terrain unique to foreign airports
Planning/performance done manually on contaminated runways with MEL items
Winter operations with contaminated runway and related decision making with regard to takeoff and landing
performance
If turns on the runway

#### Table 4. Uncomfortable Operational Situations Described by Pilots

# **Negative Experiences in Training**

A positive social context for training is a key component of training effectiveness. We asked a series of questions to probe for any negative experiences pilots may face in training. The instructor-trainee relationship was a known area of concern. We asked pilots to indicate if their instructor had raised



their confidence during their last training session (Figure 20). Unfortunately, 43% of the responses were negative.

#### Figure 20. Instructor Effect on Pilot's Confidence in Proficiency

We then asked pilots if any negative experiences were encountered in training within the past 5 years (Figure 21). The broad time range was to ensure we captured all possible training cycles. Forty-six percent of the pilots responded yes to having a negative experience in training in the past 5 years and we asked the pilots to specify the cause of the negative experience. Responses were coded and grouped by topic (Table 5) and Table 6 provides specific negative training situations reported by pilots in training. The most frequent source of negative experiences in training was the instructor. The other two categories were course content and delivery.



Figure 21. Pilots Having Negative Training Experiences in Last 5 Years

Frequency	Codes for Open Entry Comments
118	Instructor intimidation
51	Instructor knowledge deficiency
40	Instructor standardization
40	Inappropriate assessment
36	Unrealistic scenarios or task loading by instructor
36	SOPs violated by instructor for scenario
36	Poor syllabus content
35	Time compression
34	Disagreement with instructor
34	Focus on checking
21	Inappropriate training method
14	Inappropriate pairing
12	No opportunity to practice
11	Simulator inaccuracy
4	Poor training manuals
3	Poor brief prior to simulator

Table 5.	Negative	Experiences'	<b>Codes and</b>	Frequency
----------	----------	--------------	------------------	-----------

The results point to some areas to target for immediate improvement in training. Instruction, content, and delivery represent the main concerns. Providing comprehensive guidance for instructor qualification, calibration, and standardization should be a top priority. The training environment should facilitate learning and promote the free exchange of ideas, questions, and discussions. The content and its delivery must be operationally relevant and presented in a way that increases retention so knowledge and skills may be transferred.

#### **Table 6. Some Reported Negative Situations**

I had a instructor that loved to "play" with the flight simulator and I had sessions with 8 multiple faults at the same time, fire, fuel leak, generators' faults, door opens... it wasn't training was more like a massacre.

Training is too geared up to meeting LPC and OPC requirements and so we tend to leave little time for the unusual situations that can arise. Example is engine failure at V1 rarely at V2.

Four-hour recurrent session with too many emergencies. Cognitive overload at the end with little learning.

There are times you will ask a question and all it does is put a target on your back.

Cowboy instructor very nonstandard deviation from tco.

Check pilots who aren't familiar w/ the "real world."

Too much content to cover in the available time leading to nothing being covered adequately.

Instructor not understanding priorities and unable to accept that he was wrong and the Capt under check was right.

Instructors in my company are not able to tell a captain he is bad. Most of the time the first officers are charged with every mistake.

Not teaching, just checking.

Nit-picky witch-hunt atmosphere on last evaluation.

Instructor who thought he was still in the military and felt the need to yell. Not very conducive to learning.

Variations by check pilots on procedures.

Training pilot who would not discuss procedure but demanded we follow his procedure.

# **Anything Else We Should Know**

At the end of the survey, we gave the pilots an opportunity to comment freely about their training experiences and they provided detail on what they perceive to be key barriers to improved training. Regarding content, they want access to definitive technical information from the airplane manufacturers. Pilots feel they do not get all the information they need via training or through bulletins and other means of communication. Explanation of the rationale underlying the standard operating procedures was frequently requested, "Explain why SOPs are written that way." Several wrote that their company's SOPs are not compatible with the operational environment and require "adaptation of the SOPs to make it work." Systems training and knowledge were reported to be "gone" from training and pilot knowledge and crew resource management training was reported

"ineffective" or "absent." Pilots believe that flight management automation is a "crutch" and hand flying should be encouraged.

Regarding training delivery, pilots cited the issue of being time compressed in training courses that do not provide sufficient opportunity to assimilate, think, and reflect on what they are learning. Pilots believe the social interaction of learning in a classroom is superior to distance learning programs and "ineffective" self-study. Pilots suggested training occur more frequently and for a reduced duration to enable maintaining proficiency.

We were delighted to receive a few positive comments about training from pilots reporting their company training is "excellent" and "the best training I have ever had." Pilots expressed their appreciation for the opportunity to participate in the survey and were thankful for being able to share their experiences. Pilots are concerned about their training and want improved training for safety, confidence building, and enhanced performance.

# Conclusion

Introducing change to an existing training program will require investment on the part of the airlines, the regulators, and the manufacturers. As an industry, we need to find a way to motivate operator investments in training improvements and ways to motivate regulators to approve training enhancements, while removing barriers to change. Current training programs focus on fulfilling regulatory requirements sufficient to meet a minimum level of proficiency but as one of the pilots said, "Passing does not equal preparation."

The majority of the survey respondents are from regions where the safety record is high (North America and Europe). Regions with the lowest response rates are the regions currently with the highest safety risk. We need to work on improving communication and engagement in these regions and work with the regulators to actively raise the bar of global safety by supporting changes to training so that all operators will be trained to a higher standard.

The results suggest training is multidimensional and all dimensions must be addressed for interventions to be successful and sustainable. A review of instructional practices, content completeness, and delivery methods represent a good place to start improvement. Pilots believe training should prepare them for their actual work and equip them with a transferable toolkit of resources to draw upon in the conduct of their work. Training content should be operationally relevant to the specific operator and scenario-driven to expose pilots to situations they may face in their operations and to build their confidence.

Flight management training is one of the areas where content and delivery need careful reconsideration. Training will need to address the functional use of the system but it also needs to

integrate functional use with operational use. Continued line training may be appropriate to meet business objectives at the airlines, but if we are going to have pilots training while they fly, we should design such training and assess the training to ensure it is appropriate and effective. Training of functional use could be conducted in the context of the operational demands so that automation surprises and mode transition confusion are substantially reduced.

Approach and go-around were identified as areas where training could be improved, particularly the ability to recognize when a go-around is or is not the safest solution. Pilots need training on risk assessment, judgment making, and functioning together as a team. In 82% of the reported cases where pilots decided not to go-around, they believed there would be no reduction in safety. Training pilots to make judgments will be a challenge but it will be important as less-experienced pilots begin to enter the profession.

Although the constructs for crew resource management and threat and error management have high visibility, their current implementation and training appears to be ineffective. Because technical skills and nontechnical skills must be applied in the conduct of operating an airplane, pilots need to be trained on all skills in an integrated manner. Proper guidance material is needed and perhaps even industry standardization is needed for what constitutes effective Crew Resource Management training and application.

Instructors play an important role in achieving successful training by motivating pilots to improve and to create and maintain a culture of safety. To be effective, instructors must receive qualification and be calibrated with proper validation criteria. Industry needs guidance on how to provide these in an affordable and effective way. Change to the instructor qualification and instructional practices would yield an immediate improvement to training experience and effectiveness.

The industry needs guidance on how to develop and deliver operationally relevant training that transfers to actual operations. Operators may need comprehensive guidance on what to train pilots to do and how to measure training effectiveness in the context of an airline's entire culture. This is a challenging task for any operator, therefore effective guidance and standards are required, and standardization is needed to ensure consistency of delivery. Training delivery methods must advance to deliver an embodied, situated learning environment conducive to skill and knowledge development. To make change happen on a global scale, clear validated guidance for content development and training implementation is needed with regulatory engagement.

# Acknowledgements

I am grateful to IFALPA and IATA for supporting the development and distribution of this survey. Thanks to John Scully and Jari Nisula who collaborated on drafting the survey. I'm grateful to Jerry Preiser, Ray Roberts, and Wiley Moore for helpful reviews of this paper. Special thanks to all the pilots who completed the survey for their time and dedication to advancing pilot training and aviation safety.

# APPENDIX 5 Assessment of Pilot Performance Maneuver grades

Assessment of Pilot Performance Maneuver Grades Timothy E Goldsmith, Peder J Johnson, & Kyunghun Jung University of New Mexico January, 2009 Structural Knowledge Analysis of Aviation Safety Reports Quarterly Progress Report for FAA Grant 07-G-004 October-December, 2008

Our work during the last quarter of 2008 focused on analyzing a very large set of pilot performance data obtained from the Federal Aviation Administration. The data were de-identified maneuver validation (MV) and first look (FL) grades given to pilots during continuing qualification evaluations. The primary purpose of our analyses was to determine if there was any evidence of skill decay over the course of a retention interval. We did not find evidence of skill decay. In addition, we examined several other variables including phase of flight, normal and abnormal maneuvers, and type of aircraft. The results of our analyses are given below.

#### Skill Retention after Training

The Federal Aviation Administration (FAA) requires airlines to perform recurrent training on pilots at standardized intervals to insure pilots retain acceptable levels of performance. Airlines spend large amounts of money to retrain and evaluate pilots. It would be beneficial to find the optimal intervals of retraining for different types of pilots and for different task types. In addition to cost savings, optimal retraining intervals would also help ensure safer flights.

In psychology, several factors have been investigated as causes of skill retention (see Arthur et al., 1998 for a review of skill retention). Among the factors known to affect skill retention, in the current study we focused on: (a) length of retention interval, (b) practice level (normal or frequently performed tasks vs. abnormal or infrequently performed tasks), and (c) task characteristics (perceptual motor tasks vs. cognitive tasks). We examine each of these in pilot performance data we have available.

*Retention interval.* Perhaps the best known factor affecting retention of skill is the amount of time that has elapsed between learning a skill and the subsequent assessment. The overall conclusion regarding retention interval is that as the period of skill nonuse increases, skill decay increases (Annett, 1979; Arthur et al., 1998; Farr, 1987; Gardlin & Sitterley, 1972; Hurlock & Montague, 1982; Naylor &

Briggs, 1961; Prophet, 1976). In the current study pilots' skills were evaluated right after qualification training and then at a first look evaluation after 12 months of flying on the line.

*Practice level.* A second factor affecting retention is practice or rehearsal. A long history of research on learning and forgetting has validated the beneficial role of practice in maintaining performance over a retention interval. The question of practice or rehearsal seems particularly germane to flying. Pilots routinely practice those tasks and maneuvers that regularly occur in the course of flying, whereas other tasks, such as emergency maneuvers, receive little or no rehearsal. Exactly how beneficial to maintaining proficiency is the routine performance of maneuvers? In the current study, we attempted to address this question by examining differences between performance on normal and emergency maneuvers over a retention interval.

*Task type*. Psychologists have distinguished among different types of knowledge and skill including declarative, procedural, verbal, and perceptual-motor. Complex, realistic tasks involve several types of knowledge and this is certainly true of flying. Pilots need to know basic declarative facts (e.g., knowledge of electrical systems), perceptual-motor sequences (e.g., ability to hand fly an ILS), procedural skills (e.g., how to enter coordinates into a flight management system), and even social and interpersonal skills (crew resource management; CRM). Do these distinct components of performance decay at the same rate? If not, what are the implications of different decay rates for retraining pilots?

In a review of decay for general skills, Arthur, Bennett, Stanush, and McNelly (1998) found that type of task was a major variable affecting rate of skill decay. Skills used for physical tasks were generally retained better than mental skills. More specific to piloting, Childs and Spears (1986) reported that cognitive and procedural elements of flying decayed more rapidly than perceptual-motor skills. As an example, flying a radar intercept mission showed little decay even after 24 months of non-practice (Fleishman & Parker, 1962). In contrast, Adams & Hufford (1962) found that cognitive/procedural skills associated with complex tasks declined significantly (85% decline) within 10 months. In the current study, we examined whether pilots' performance decayed differentially across sets of maneuvers that emphasized different types of knowledge or skill.

In the previous section, although we mentioned that a practice can be generally regarded as beneficial for skill retaining, not all practice is equally effective (Schmidt & Bjork, 1992). Practice effects can vary by task similarity between practice and assessment, amount and type of feedback, and individual differences such as motivation level. Further, the nature of practice effects has been shown to vary between different types of learning tasks such as between verbal and motor tasks.

490

In an earlier study based on data collected over a decade ago we found a statistically significant and meaningful decreased in maneuver validation performance as the training interval was increased from either 6- to 12-months or 9- to 12-months. During the ensuing decade with the widespread implementation of AQP throughout the industry there have been a number of improvements in training methods designed to improve skill retention. In this study we conduct a comprehensive large scale investigation using more current data to determine is there continues to exist a meaningful loss in commercial pilots' retention of critical maneuvers over a 12-month interval.

#### Methods

The data analyzed in this study were de-identified maneuvers validation grades from eight carriers involving 25 fleets ranging from long-haul 747, 777, and 757/67 aircraft down to short-haul twin engine turbo aircraft. This data set comprises over two million maneuver grades collected over a nine year period (2000 to 2008). The data represent an extensive range of maneuvers occurring across all phases of flight under both normal and abnormal (e.g., engine-out) conditions. Unlike the previous study the where pilots within the same fleet were assessed at different training intervals (6-, 9- or 12-months), all of the current pilots were on a 12-month training interval. However, each training session began with a first-look (FL) evaluation prior to any re-training, followed by maneuvers validation (MV) training, which allowed us to assess skill retention by comparing grades collected during MV training (0-month retention interval), with FL grades collected 12-months later, (i.e., the decay effect = MV minus FL). This calculation of the decay effect was repeated eight times over the succeeding nine years from 2000 through 2008.

There were 2,098,946 evaluations in the original data. The data come from seven different sub data sets. Table 1 shows the number of evaluations from each sub data set. Each data set presents for different carrier. However, we will not consider the different carrier types in this paper. Table 1. Number of evaluations and proportions from each original data set.

Data name	Number of observation	Proportion
1st	248810	0.12
BLAH	297695	0.14
MSTK	929194	0.44
OLDR	76132	0.04
SEAA	391547	0.19
SIKA	121251	0.06

UHAL	34317	0.02
Total	2098946	1.00

\*Note. Data names was arbitrarily assigned to each sub data set by FAA.

Scale issue

As we mentioned before, the data came from seven different carriers and each data set had a different scale as shown in Table 2.

Table 2. Original scale in each data set and newly assigned scales.

Data	Original	Maaring	New	# of
name	scale	Meaning	scale	observation
	1	Unsafe	1	13
	1	Unsatisfactory	1	1471
	2	Not Proficient	1	658
	2	Satisfactory	2	16249
	3	Competent	2	3157
1ct	3	Standard	3	137328
130	4	CRM/TEM/Policy	Excluded	495
	4	Excellent	4	46786
	5	Not Graded	Excluded	666
	5	Proficient	3	28233
	6	Outstanding	4	13753
	9	N/A	Excluded	1
	1	Unsatisfactory:Red, Additional Train Req	1	82
	2	Unsat:Yellow/Red, Errors Unmitigated	1	2639
	3	Sat:Green/Yellow, Errors Debriefed	2	13678
вілн	3	Satisfactory: Yellow, Errors Debriefed	2	50
DLAIT	4	Sat:Green, Errors Mitigated	3	108292
	4	Satisfactory:Green, Errors Mitigated	3	390
	5	Sat:Green, No Errors	4	171747
	5	Satisfactory:Green, No Errors	4	392

-	7	Additional Training Provided	Excluded	3
-	8	Normal Progress	Excluded	20
-	9	Proficient	Excluded	402
	1	Excellent	4	168710
-	2	Above Average	3	20468
	2	Above Expectations	3	384004
MSTK	3	Average	2	23115
	3	Expected Performance	2	319213
-	4	Meets Minumum Standards	1	11900
-	5	Unsatisfactory	1	1784
	1	UNSAT	1	843
	1	UNSATISFACTORY	1	276
-	2	SAT	2	206
	2	SATISFACTORY	2	51317
OLDK -	3	ABOVE STANDARD	3	648
	3	STANDARD	3	16095
-	4	EXCELLENT	4	721
	4	NOT OBSERVED	4	6026
	0	0-Incomp	Excluded	98
-	1	1-Unsat	1	7434
	1	Unsat	1	97
-	2	2-Min Acc	2	22083
	2	Min Acc	2	87
SEAA	2	Min. Acceptable	2	159
-	3	3-Profic	3	254965
	3	Profic	3	702
	3	Proficient	3	2454
-	4	4-Abv Stnd	3	91047

-

\_

	4	Abv Standard	3	497
	4	Abv Stnd	3	1665
-	5	5-Except	4	9770
	5	Except	4	327
	5	Exceptional	4	162
	1	Unsatisfactory/Repeat	1	3607
	2	Debrief	2	6371
511(4 -	3	Standard	3	98936
-	4	Excellent	4	12337
	1	Not Proficient	1	638
	1	Not Proficient/Unsafe	1	218
	2	Meets Minimum Standards	2	2204
UNAL	2	Satisfactory	2	2077
-	3	Standard	3	28896
-	4	Exceeds Standards	4	284

To create a uniform sale across all the data sets, we assigned a new 1-4 scale to the 1st data set, BLAH, MSTK and SEAA so that all data sets had the same 1 through 4 grade levels. This new scale was derived from the meaning of the original scale labels. For example, in the 1st data set scale, level 1 had two different meanings of 'Unsafe' and 'Unsatisfactory' and level 2 also had two different meanings of 'Not Proficient' and 'Satisfactory'. We grouped level 2 with a meaning of 'Not Proficient' together with level 1 (i.e., we assigned 1 to original level 2 if it has a meaning of 'Not Proficient').

Some of the original grade levels were of a qualitatively different nature. For example, in the first data set, level 4, 5, 9 had meanings of 'CRM/TEM/Policy', 'Not Graded' and 'N/A', respectively. We excluded evaluations under these levels. Excluded evaluations were marked with "Excluded" in the third column of Table #. Finally, among all the 2,098,946 evaluations, 1,685 evaluations were excluded giving 2,097,261 evaluations.

#### Maneuver Names

At this point the data contained 1,944 different maneuver names. Some of these maneuver names occurred infrequently, less than 20 times in each sub data set, and these maneuvers were simply excluded from the data set. A total of 974 evaluations were excluded. Some ambiguous maneuver

names were also excluded, for example, 'approach in direct law', 'Climb/Cruise/Descent Operations', 'EP PERFORM #1 HYDR FLRE PROC.', 'FMS Departures, Transitions, and Approaches'. These ambiguous maneuver names that were excluded had 1458, 29266, 118, and 1397 observations, respectively (32239 in total, 0.0154%). Finally, many of the maneuver names were actually the same maneuver but with slightly different names. We grouped similar maneuver names into a single maneuver name. After this maneuver name change, 1,049 maneuver names were left with 2,064,048 evaluations. We assigned maneuver type and phase of flight on each of these 1,049 maneuver name as described in the following section.

#### Assigning maneuver type, phase of flight and retention interval

Two individuals familiar with the performance data assigned maneuver type (normal or abnormal) and phase of flight (Approach, Automation, Climb, CRM, Cruise, Holding, Landing, Preflight, Takeoff, Taxi, N/A) to each maneuver name. Finally, based on when the evaluation was made, each evaluation was assigned as a maneuver validation (MV, an evaluation made right after pilots' training) or a first-look (FL, an evaluation made 12 months after the qualification training).

#### Results

The statistical analyses revealed that with the large sample sizes used in the present study, exceedingly small differences in mean grades (e.g., 0.02) were highly statistically significant (p < .001), while being meaningless in terms of real world implications. To address this problem we only treated differences having a Cohen's d value of 0.2 (i.e., 0.2 of the standard deviation of the sample) or greater as being meaningful.

The following tables show mean grade, standard deviation, and number of observations for comparing normal with abnormal maneuvers (Table 3), maneuver validation with first-look performance (Table 4), and for crossing each level of maneuver type with each time of evaluation (Table 5).

Table 3.	Number of	f evaluations of	each	maneuver	type and	its mean	and star	idard c	leviation	of ratir	ıg
											~

Maneuver type	# of observation	Mean	Standard deviation
Abnormal	846485	2.87	0.67
Normal	1217563	3.00	0.71

F(1, 2064046)=3946.382 (p<0.000) d=0.187

Table 4. Number of evaluations of each retention interval and its mean and standard deviation of rating.

Potentian Interval	# of observation	Moon	Standard
		Wear	deviation
MV	1770383	2.95	0.70
FL	293665	2.93	0.67

F(1,2064046)=208.1032 (p<0.000) d=0.0287

Table 5.	Cross table	of maneuver	type and	retention	interval.
----------	-------------	-------------	----------	-----------	-----------

Maneuver type	MV	FL
Abnormal	2.87(0.67)	2.84(0.63)
Abhormai	692310	154175
Normal	3.00(0.71)	3.02(0.71)
Normai	1078073	139490

The following tables show the same descriptive statistics for phase of flight (Table 6), phase of flight crossed with maneuver type (Table 7), and phase of flight crossed with retention interval (Table 8).

Phase	# of observation	Mean	Standard deviation
Approach	648812	3.00	0.69
Automation	1014	2.72	0.65
Climb	18853	3.04	0.75
CRM	145170	2.86	0.69
Cruise	2867	3.61	0.55
Holding	44148	3.08	0.64
Landing	338752	2.99	0.67
N/A	394632	2.83	0.70
Preflight	21037	2.86	0.77
Takeoff	421839	2.96	0.69
Taxi	26924	2.96	0.66

Table 6. Number of evaluations of each phase and its mean and standard deviation of rating.

Table 7. Crossing of phase of flight with maneuver type
Normal_count	Abnormal_count
3.04 (0.71)_ 395459	2.93 (0.66)_ 253353
2.72 (0.65)_ 1014	
3.11 (0.74)_ 16033	2.65 (0.69)_ 2820
2.86 (0.69)_ 144962	2.83 (0.72)_ 207
3.61 (0.55)_ 2867	
3.09 (0.64)_ 43354	2.97 (0.36)_ 794
3.05 (0.70)_ 163640	2.94 (0.64)_ 175112
2.91 (0.72)_ 212074	2.74 (0.67)_ 182558
2.86 (0.77)_ 21037	
3.09 (0.69)_ 192763	2.85 (0.67)_ 229076
2.96 (0.67)_ 24359	2.99 (0.62)_ 2565
	Normal_count 3.04 (0.71)_ 395459 2.72 (0.65)_ 1014 3.11 (0.74)_ 16033 2.86 (0.69)_ 144962 3.61 (0.55)_ 2867 3.09 (0.64)_ 43354 3.05 (0.70)_ 163640 2.91 (0.72)_ 212074 2.86 (0.77)_ 21037 3.09 (0.69)_ 192763 2.96 (0.67)_ 24359

Table 8. Cross table of phase and retention interval.

Phase	MV	FL
Approach	3.00 (0.70)_ 538830	2.98 (0.65)_ 109982
Automation	2.72 (0.65)_ 1014	
Climb	3.02 (0.75)_ 17144	3.27 (0.70)_ 1709
CRM	2.86 (0.69)_ 145170	
Cruise	3.61 (0.55)_ 2867	
Holding	3.11 (0.64)_ 38429	2.91 (0.60)_ 5719
Landing	3.00 (0.67)_ 294656	2.95 (0.64)_ 44096
N/A	2.83 (0.71)_ 346488	2.79 (0.65)_ 48144
Preflight	2.83 (0.76)_ 19979	3.43 (0.70)_ 1058
Takeoff	2.97 (0.68)_ 342035	2.90 (0.72)_ 79804
Taxi	2.92 (0.66)_ 23771	3.24 (0.65)_ 3153

There were 119 different simulators represented within the data. To examine whether there were systematic differences in grades as a function of simulator type we selected simulators that had at least 10,000 grades associated with them. Table 9 shows the mean and standard deviation across these simulators.

Table 9. Mean and Standard Deviation associated with particular Simulators.

Fleet	SimID	CountOfRe_MRate AvgOfRe_MRate		StDevOfRe_MRate
	598	43112	3.51	0.66
	613	41106	3.49	0.66
	539	36704	2.96	0.40
A 220	335	27644	2.94	0.39
A-320	299	27296	2.93	0.42
	607	26471	2.95	0.41
	865	12469	2.98	0.44
	643	10856	3.57	0.62
B-727	58	19952	2.87	0.39
	28	197531	2.84	0.79
	616	106220	2.89	0.79
	473	104670	2.83	0.79
	316	101452	2.78	0.78
B-737	303	43131	3.52	0.63
	247	42079	3.50	0.63
	178	30048	3.49	0.62
	591	21505	3.03	0.77
	1004	10646	2.98	0.76
B-747-200	311	28720	2.95	0.30
B-747-400	273	21719	2.95	0.27
D-747-400	317	18824	2.96	0.26
	513	111237	2.64	0.65
	691	111075	2.65	0.65
B-757	297	22807	2.89	0.48
	325	22509	2.92	0.45
	119	17492	2.91	0.43
B-757/767	403	34172	3.18	0.56
D-757/707	46	33819	3.14	0.57

	280	33162	3.17	0.58
	353	32573	3.14	0.58
	45	32450	3.16	0.58
	766	30558	3.09	0.59
	601	27895	3.11	0.58
	671	18468	3.20	0.59
B-767	60	24519	3.51	0.60
B-777	606	136949	2.75	0.72
CR7	846	25519	3.03	0.41
	768	51528	2.98	0.55
CRJ	775	23146	2.98	0.56
	683	13305	2.96	0.55
DC-10	552	21441	2.92	0.34
	148	31177	2.91	0.43
	149	21948	2.88	0.41
DC-9	322	17750	2.92	0.42
	308	12889	2.93	0.43
DH8	393	59790	2.37	0.63

Most of the simulators had a mean grade of around 3. However, seven of the simulators had mean grades around 3.5 and one simulator had an average grade below 2.5. To investigate the simulator effect within each fleet type, we selected only fleets with at least five different simulator IDs (fleets with less than 5 simulator IDs showed almost the same mean rating across the simulators within each fleet type). Table 10 presents the results.

Table 10. Simulator by Fleet S	tatistics.
--------------------------------	------------

Fleet	SimID	# of observation	Mean	Standard deviation
A-330	643	10856	3.57	0.62
A-320	598	43112	3.51	0.66

	613	41106	3.49	0.66
	865	12469	2.98	0.44
	539	36704	2.96	0.40
	607	26471	2.95	0.41
	335	27644	2.94	0.39
	299	27296	2.93	0.42
	303	43131	3.52	0.63
	247	42079	3.50	0.63
	178	30048	3.49	0.62
	591	21505	3.03	0.77
B-737	1004	10646	2.98	0.76
	616	106220	2.89	0.79
	28	197531	2.84	0.79
	473	104670	2.83	0.79
	316	101452	2.78	0.78
	325	22509	2.92	0.45
	119	17492	2.91	0.43
B-757	297	22807	2.89	0.48
	691	111075	2.65	0.65
	513	111237	2.64	0.65
	671	18468	3.20	0.59
	403	34172	3.18	0.56
	280	33162	3.17	0.58
	45	32450	3.16	0.58
B-757/707	46	33819	3.14	0.57
	353	32573	3.14	0.58
	601	27895	3.11	0.58
	766	30558	3.09	0.59

Fleets A-320, B-737 and B-757 showed heavy fluctuation of mean grades across the individual simulators. There was no relation between mean grade and corresponding standard deviation. In fleet

A-320, the standard deviation showed a similar pattern to mean grade, however, this pattern was reversed for the B-737 and B-757 fleets.

We investigated whether simulator effect within these three fleets was confounded with a certain maneuver type, retention interval or phase of flight. That is, although there were significant simulator effects, this result could be due to confounding simulator ID with these other factors. For example, in fleet A-320, the first two simulators showed higher mean grades than the remaining simulators. Perhaps this result occurred because these simulators were used to evaluate MV rather than FL maneuvers, or they were used more for evaluating normal than abnormal maneuvers.

We investigated this question with data from the A-320 simulators. Although these two simulators had fewer observations of abnormal maneuvers than other simulators (see Table 11), within each simulator type, mean grades for the two different maneuver types were almost the same. Regardless of the number of observation of each maneuver type, the first two simulators had higher mean grades from each maneuver type than the other simulators.

SimID	Maneuvertype	# of observation	Proportion	Mean
598	А	6426	0.15	3.41
598	Ν	36686	0.85	3.52
613	А	6325	0.15	3.41
613	Ν	34781	0.85	3.51
539	А	20820	0.57	2.95
539	Ν	15884	0.43	2.96
607	А	14885	0.56	2.94
607	Ν	11586	0.44	2.97
335	А	16051	0.58	2.94
335	Ν	11593	0.42	2.94
299	А	15587	0.57	2.93
299	Ν	11709	0.43	2.93

Table 11. Data from A-320 Simulators broken out by abnormal and normal maneuvers.

As for retention interval, each simulator had a similar number of observations for each retention interval (MV vs. FL). Again, in A-320, the first two simulators had higher mean grades for the two different retention intervals than other simulators (see Table 12).

SimID	Retention interval	# of observation	Proportion	Mean
598	MV	35757	0.83	3.50
598	FL	7355	0.17	3.51
613	MV	33690	0.82	3.49
613	FL	7416	0.18	3.51
539	MV	30246	0.82	2.96
539	FL	6458	0.18	2.93
607	MV	22480	0.85	2.95
607	FL	3991	0.15	2.94
335	MV	22484	0.81	2.94
335	FL	5160	0.19	2.93
299	MV	22609	0.83	2.94
299	FL	4687	0.17	2.92

Table 12. Data from A-320 Simulators broken out by MV and FL maneuvers.

As for different phases of flight across the simulator type, there were similar numbers of observations for each phase. Again, the first two simulators had higher mean rate for each phase than other simulators (see Table 13).

Table 13. Data from A-320 Simulators broken out by Flight Phases.

SimID Phase		# of observation	Proportion	Mean
598	Approach	18401	0.51	3.46
598	Landing	8000	0.22	3.62
598	Takeoff	9971	0.27	3.47
613	Approach	17488	0.50	3.44
613	Landing	7480	0.22	3.61
613	Takeoff	9676	0.28	3.46
539	Approach	13926	0.49	2.94
539	Landing	5328	0.19	3.00
539	Takeoff	9309	0.33	2.95

607	Approach	9756	0.48	2.93
607	Landing	4061	0.20	2.99
607	Takeoff	6440	0.32	2.93
335	Approach	10168	0.48	2.93
335	Landing	3871	0.18	2.98
335	Takeoff	7207	0.34	2.93
299	Approach	10087	0.48	2.91
299	Landing	3937	0.19	2.98
299	Takeoff	6870	0.33	2.92

Up to this point, the simulator effect seemed to be not confounded with any other factors. However, upon further analysis, it appeared that there were two different groups of evaluators with one group being assigned to the first two simulators and the second group assigned to the remaining simulators. Our current analyses are focused on examining how much variability in the grades is associated with particular evaluators, and once evaluator variation is held constant, what effects continue to be or now become meaningfully significant.

#### Discussion

The major finding in our analyses was that the mean difference (0.03) between MV (2.96) and FL(2.93) grades averaged across the entire time interval and all 25 fleets and was not meaningfully significant (Cohens'= .03). Moreover, looking the MV-FL difference from 2000 to 2008 showed no indication of a trend. When we partitioned the maneuvers into Normal (practiced regularly on the line) and Abnormal (rarely performed on the line) we found the mean grade for Normal (3.00) maneuvers was not meaningfully higher than the mean grade of Abnormal maneuvers (2.87), Cohens' d = .19. However, when we looked at this difference across phases of flight it was found that Normal (3.09) maneuvers were performed better than Abnormal (2.85) maneuvers on Takeoffs ,Cohens' d = .24. Importantly, the superior performance for Normal maneuvers over Abnormal maneuvers remained constant across the 0- (MV) to 12-month (FL) retention interval. In sum, these findings suggest that pilots are maintaining proficiency across the standard 12-month retraining interval.

#### References

Adams, J. A. & Hufford, L. E. (1962). Contributions of a part-task trainer to the learning and relearning of a time-shared flight maneuver. *Human Factors, 4*, 159-170.

Advisory Circular 120-54 (1991). Advanced qualification program. U.S. Department of Transportation and Federal Aviation Administration.

Air Transportation Operations Inspector's Handbook, Order 8400.10. Available online at: <u>http://www.faa.gov/library/manuals/examiners\_inspectors/8400/</u>.

Arthur, W., Jr., Bennett, W., Jr., Stanush, P. L, & McNelly, T. L. (1998). Factors that influence skill decay and retention: A quantitative review and analysis. *Human Performance, 11*, 57-101.

Childs, J. M. & Spears, W. D. (1986). Flight-skill decay and recurrent training. *Perceptual and Motor Skills, 62*, 235-242.

Childs, J. M., Spears, W. D., & Prophet, W. W. (1983). *Private pilot flight skill retention 8, 16, and 24 months following certification* (DOT/FAA/CT-83/34). Washington, DC: Federal Aviation Administration.

Conway, M. A., Cohen, G., & Stanhope, N. (1991). On the very long-term retention of knowledge acquired through formal education: Twelve years of cognitive psychology. *Journal of Experimental Psychology: General, 120*, 395-409.

Driskell, J. E., Copper, C., & Moran, A. (1994). Does mental practice enhance performance? *Journal of Applied Psychology*, *79*, 481-492.

Driskell, J. E., Willis, R. P., & Copper, C. (1992). Effect of overlearning on retention. *Journal of Applied Psychology*, *77*, 615-622.

Fleishman, E. A. & Parker, J. F. (1962). Factors in the retention and relearning of perceptualmotor skill. *Journal of Experimental Psychology, 64*, 215-226.

Hays, R. T., Jacobs, J. W., Prince, C., & Salas, E. (1992). Flight simulator training effectiveness: A meta-analysis. *Military Psychology*, *4*, 63-74.

Healy, A. F., Fendrich, D. W., Crutcher, R. J., Wittman, W. T., Gesi, A. T., Ericsson, K. A., & Bourne, L. E., Jr. (1992). The long-term retention of skills. In A. F. Healy, S. M. Kosslyn, & R. M. Shiffrin (Eds.), *From learning processes to cognitive processes: Essays in honor of William K. Estes* (Vol. 2, pp. 87-118). Hillsdale, NJ: Erlbaum. Marmie, W. R. & Healy, A. F. (1995). The long-term retention of a complex skill. In A. F. Healy & L. E. Bourne, Jr. (Eds), *Learning and memory of knowledge and skills: Durability and specificity* (pp. 30-65). Thousand Oaks, CA: Sage Publications.

Mengelkock, R. F., Adams, J. A., & Gainer, C. A. (1971). The forgetting of instrument flying skills. *Human Factors, 4*, 159-170.

Posner, M. I., Snyder, C. R. R., & Davidson, B. J. (1980). Attention and the detection of signals. *Journal of Experimental Psychology: General*, 109, 160-174.

Rubin, D. C. & Wenzel, A. E. (1996). One hundred years of forgetting: A quantitative description of retention. Psychological Review, 103, 734-760.

Ruffner, J. W., Wick, D. T., & Bickley, W. R. (1984). Retention of helicopter flight skills: Is there a "critical period" for proficiency loss? *Proceedings of the Human Factors Society, 28<sup>th</sup> Annual Meeting*, 370-374.

Sauer, J., Hockey, G. R. J., & Wastell, D. (1999). Maintenance of complex performance during a 135-day spaceflight simulation. *Space, Aviation, and Environmental Medicine, 70*, 236-244.

Schendel, J. D. & Hagman, J. D. (1982). On sustaining procedural skills over a prolonged retention interval. *Journal of Applied Psychology*, *67*, 605-610.

Schmidt, R. A. & Bjork, R. A. (1992). New conceptualizations of practice: Common principles in three paradigms suggest new concepts for training. Psychological Science, 3, 207-217.

Talleur, D. A., Taylor, H. L., Bradshaw, G. L., Emanuel, T. W., Rantanen, E., Lendrum, L., et al. (2001). Effectiveness of a personal computer aviation training device (PCATD) for maintaining instrument currency. *Presented at the* 11<sup>th</sup> *International Symposium on Aviation Psychology*, Columbus, OH.

Taylor, H. L., Lintern, G., Hulin, C. L., Talleur, D. A., Emanuel, T. W., & Phillips, S. I. (1999). Transfer of training effectiveness of a personal computer aviation training device. *The International Journal of Aviation Psychology*, *9*, 319-335.

Underwood, B. J. (1957). Interference and forgetting. Psychological Review, 64, 49-60.

Wixted, J. T. (2004). The psychology and neuroscience of forgetting. Annual Review of Psychology, 55, 235-269.

## 1. Score distribution in takeoff.

Takeoff						
	EvalType	1	3	4	Total	
	MV	6017	67167	199427	69424	342035
	FL	3400	14576	48109	13719	79804

EvalType	1&2	3&4	Total
MV	73184	268851	342035
FL	17976	61828	79804
. –			

Takeoff					
1 2 3 4 To					
0.02	0.20	0.58	0.20	1	
0.04	0.18	0.60	0.17	1	

1&2	3&4	Total
0.21	0.79	1
0.23	0.77	1

#### 2. Fleet size.

Fleet	Size	CountOfFleet
A-300	М	4270
A-320	М	219465
A-330	L	25301
B-727	М	23611
B-737	М	677764
B-747-200	L	37316
B-747-400	L	40543
B-757	L	294988
B-757/767	L	247637
B-767	L	32714
B-777	L	139504
CR7	S	25519
CRJ	S	95635
DC-10	L	25700
DC-8	М	7783
DC-9	М	87140
DH8	М	75994

 E-190	S	3164
 Total		2064049

#### 2.5 Mean and standard deviations for different fleet sizes

	# of obcomuction	Maan	Standard
FleetSize		Medi	deviation
S	124318	3.01	0.53
М	1096027	2.96	0.75
L	843703	2.92	0.64

## 3. Retention interval rating across fleet size.

FleetSize	Retention Interval	# of observation	Mean	Standard deviation
s	MV	109918	3.02	0.51
3	FL	14400	2.90	0.68
М	MV	916971	2.96	0.75
	FL	179056	2.96	0.71
L	MV	743494	2.93	0.64
	FL	100209	2.86	0.61

d(S)=0.23

d(M)=0

d(L)=0.11

FleetSize	Maneuver type	# of observation	Mean	Standard deviation
c	A	64523	2.96	0.56
3	Ν	59795	3.06	0.50
М	А	431288	2.83	0.73
	Ν	664739	3.05	0.75
	А	350674	2.90	0.60
L	Ν	493029	2.93	0.67

## 4. Maneuver type rating across fleet size.

## d(S)=0.19

# d(M)=0.30

# d(L)=0.05

Fleet size and phase.

Fleet	Phase	# of observation	Mean	Standard
size	FildSe		wean	deviation
	Approach	52993	3.03	0.53
S	Landing	23659	3.01	0.52
	Takeoff	23800	2.94	0.65
	Approach	363634	2.96	0.75
Μ	Landing	164545	3.09	0.72
	Takeoff	225388	2.95	0.76
	Approach	232185	3.04	0.63
L	Landing	150548	2.89	0.62
	Takeoff	172651	2.97	0.60

Fleet	Dhaca	Maneuver	# of obcomunition	Maan	Standard
size	Phase	type	# OF Observation	Medi	deviation
	Approach	А	16746	2.98	0.57
	Арргоасн	Ν	36247	3.05	0.51
c	Landing	А	16672	2.96	0.53
3	Lanung	Ν	6987	3.13	0.47
	Takeoff	А	10480	2.78	0.79
		Ν	13320	3.08	0.47
	Approach	А	139122	2.91	0.72
М	Арргоасп	Ν	224512	3.00	0.76
	Landing	А	76623	2.96	0.71
	Landing	Ν	87922	3.20	0.71
	Takeoff	А	108394	2.76	0.73

	-	Ν	116994	3.13	0.74
	Approach	А	97485	2.94	0.57
L	Approach	Ν	134700	3.11	0.65
	Landing	А	81817	2.93	0.59
		Ν	68731	2.84	0.65
	Takeoff	А	110202	2.94	0.59
		Ν	62449	3.03	0.62

Fleet	Dhasa	Detention interval	# of	Magin	Standard
size	Phase	Retention Interval	observation	iviean	deviation
	Annroach	MV	46879	3.03	0.53
	Арргоасп	FL	6114	3.01	0.53
c	Landing	MV	21802	3.02	0.50
3	Lanung	FL	1857	2.93	0.69
	Takeoff	MV	18561	2.98	0.60
ľ	Takeon	FL	5239	2.81	0.77
Approad M Landing Takeof	Approach	MV	296836	2.95	0.77
	Арргоасн	FL	66798	3.02	0.68
	Landing	MV	135833	3.10	0.73
		FL	28712	3.00	0.65
	Takeoff	MV	177497	2.95	0.76
		FL	47891	2.94	0.76
	Annroach	MV	195115	3.07	0.62
	Approach	FL	37070	2.90	0.61
	Landing	MV	137021	2.89	0.62
L	Landing	FL	13527	2.84	0.60
	Takeoff	MV	145977	2.99	0.60
	такеот	FL	26674	2.86	0.62

EvalType	Maneuvertype	1	2	3	4	То	tal
N 4) /	А	12954	168331	40562	6 1053	99 692	310
IVIV	Ν	9382	239568	56918	2 2599	41 1078	3073
	А	5693	27240	10691	5 1432	27 154	175
FL	Ν	3389	23422	79440	) 3324	40 139	491
1	2	3	4	Tot	tal		
0.02	0.24	0.59	0.15	1			
0.01	0.22	0.53	0.24	1			
0.04	0.18	0.69	0.09	1			
0.02	0.17	0.57	0.24	1			
EvalType	Maneuvertype	1&2	3&4	Total			
N 4) (	А	181285	511025	69231	0		
IVIV	Ν	248950	829123	107807	73		
ГІ	А	32933	121242	15417	5		
ΓL	Ν	26811	112680	13949	1		
EvalType	Maneuvertyp	e 1&2		3&4	Total		
N 4) /	А	0.26		0.74	1	_	
	Ν	0.23		0.77	1		
	А	0.21		0.79	1	_	
FL	Ν	0.19		0.81	1		
ElectSize	EvalTuna Man	ouvertype	1	2	2	1	Total
TieetSize			1074	2	46022		
	MV	A	18/1	3096	46822	5162	56951
S .		N	//4	2231	42139	/823	52967
	FL	A	690	662	5179	1041	7572
		Ν	281	462	5438	647	6828
М	MV	А	7595	109211	163892	62822	343520
		Ν	6296	127516	271861	167778	573451

	<b>F</b> 1	А	2979	17212	58065	9512	87768
	FL	Ν	2115	15291	47003	26879	91288
	N 4) /	А	3488	56024	194912	37415	291839
I	IVIV	Ν	2312	109821	255182	84340	451655
-		А	2024	9366	43671	3774	58835
	ΓL	Ν	993	7669	26998	5714	41374

FleetSize	EvalType	Maneuvertype	1	2	3	4	Total
	N <i>4</i> \/	А	0.03	0.05	0.82	0.09	1
s		Ν	0.01	0.04	0.80	0.15	1
5	EI	А	0.09	0.09	0.68	0.14	1
	Γ <b>L</b>	Ν	0.04	0.07	0.80	0.09	1
M	N/1\/	А	0.02	0.32	0.48	0.18	1
		Ν	0.01	0.22	0.47	0.29	1
	<b>CI</b>	А	0.03	0.20	0.66	0.11	1
		Ν	0.02	0.17	0.51	0.29	1
	N/1\/	А	0.01	0.19	0.67	0.13	1
L.		Ν	0.01	0.24	0.56	0.19	1
	FI	А	0.03	0.16	0.74	0.06	1
		Ν	0.02	0.19	0.65	0.14	1

FleetSize	Phase	EvalType	Maneuvertype	1	2	3	4	Total
		NA\/	А	508	999	11338	1644	14489
	Annroach	IVIV	Ν	579	1591	25612	4608	32390
Approac	Арргоасн	-	А	70	133	1704	350	2257
		ΓL	Ν	92	213	3189	363	3857
5	Landing	MV	А	416	902	12219	1282	14819
			Ν	56	213	5507	1207	6983
		FL	А	127	139	1333	254	1853
			Ν			3	1	4

		N/1\/	А	712	670	4980	676	7038
	Takooff		Ν	115	378	9345	1685	11523
	Takeon	E1	А	493	390	2122	437	3442
		FL	Ν	70	71	1485	171	1797
		NA)/	А	3083	28788	55117	22865	109853
	Annroach		Ν	3315	46312	86422	50934	186983
	Арргоасн	<b>F</b> 1	А	732	3201	21611	3725	29269
		FL	Ν	957	6486	19536	10550	37529
			А	840	15546	31606	15604	63596
N 4	Landing		Ν	713	9671	35012	26841	72237
IVI	Landing	FI	А	317	2103	9644	963	13027
		FL	Ν	307	2092	8715	4571	15685
		N/1\/	А	2680	24438	41663	11207	79988
	Takaaff		Ν	1022	19470	44967	32050	97509
	Takeon	E1	А	1524	7421	16167	3294	28406
		12	Ν	376	2163	9720	7226	19485
		N // \ /	А	1159	10663	54700	10316	76838
	Approach		Ν	868	15152	69596	32661	118277
	Арргоасп	CI	А	601	2901	15868	1277	20647
		16	Ν	576	2465	10482	2900	16423
			А	683	13805	51679	9875	76042
	Landing		Ν	492	16996	35060	8431	60979
L	Lanung	CI	А	145	951	4036	643	5775
		ΓL	Ν	179	1796	5184	593	7752
		MV	А	1259	13303	62352	12715	89629
	Takooff	IVIV	Ν	229	8908	36120	11091	56348
	TakeUII	E1	А	877	3352	15142	1202	20573
		FL	Ν	60	1179	3473	1389	6101

FleetSize	Phase	EvalType	Maneuvertype	1	2	3	4	Total
		N 4) /	А	0.04	0.07	0.78	0.11	1
	Approach	IVIV	Ν	0.02	0.05	0.79	0.14	1
	Арргоасп	<b>F</b> 1	А	0.03	0.06	0.75	0.16	1
		FL	Ν	0.02	0.06	0.83	0.09	1
		N 4) /	А	0.03	0.06	0.82	0.09	1
c	Landing	IVIV	Ν	0.01	0.03	0.79	0.17	1
3	Lanuing	-	А	0.07	0.08	0.72	0.14	1
		FL	Ν	0.00	0.00	0.75	0.25	1
		N 41 /	А	0.10	0.10	0.71	0.10	1
	Takeoff		Ν	0.01	0.03	0.81	0.15	1
		FL	А	0.14	0.11	0.62	0.13	1
			Ν	0.04	0.04	0.83	0.10	1
		N/1\/	А	0.03	0.26	0.50	0.21	1
	Approach		Ν	0.02	0.25	0.46	0.27	1
	Approach	<b>F</b> 1	А	0.03	0.11	0.74	0.13	1
		FL	Ν	0.03	0.17	0.52	0.28	1
		MV	А	0.01	0.24	0.50	0.25	1
N/	Landing		Ν	0.01	0.13	0.48	0.37	1
IVI	Lanung	<b>F</b> 1	А	0.02	0.16	0.74	0.07	1
		FL	Ν	0.02	0.13	0.56	0.29	1
		N 41 /	А	0.03	0.31	0.52	0.14	1
	Takaoff	IVIV	Ν	0.01	0.20	0.46	0.33	1
	Takeon	<b>F</b> 1	А	0.05	0.26	0.57	0.12	1
		FL	Ν	0.02	0.11	0.50	0.37	1
		N 4) /	А	0.02	0.14	0.71	0.13	1
	Approach	IVIV	Ν	0.01	0.13	0.59	0.28	1
	Approach	<b>F</b> 1	А	0.03	0.14	0.77	0.06	1
L		FL	Ν	0.04	0.15	0.64	0.18	1
	Londing		А	0.01	0.18	0.68	0.13	1
	Landing	MV	Ν	0.01	0.28	0.57	0.14	1

		-	А	0.03	0.16	0.70	0.11	1	
			Ν	0.02	0.23	0.67	0.08	1	
		N 4) /	А	0.01	0.15	0.70	0.14	1	
Та	Takeoff		Ν	0.00	0.16	0.64	0.20	1	
Id		-	А	0.04	0.16	0.74	0.06	1	
		FL	Ν	0.01	0.19	0.57	0.23	1	



# APPENDIX 6 Analysis of global fatal accident data

# **Analysis of Global Fatal Accident Data**

Worldwide fatal accidents have been analysed using the ITQI Intuitive Risk Matrix. The following criteria were applied to the data:

- Fixed-wing jet and turbo-prop aeroplanes with original certified MTWA above 5,700 kg or 12,500 lbs
- Civil passenger and cargo flights only
- Fatalities within 30 days of the accident (as per ICAO Annex 13 definition)
- Occurring between 1 January 1997 and 31 December 2008 (inclusive)
- Excluding violent acts (e.g. sabotage, terrorism, etc.)

Data was also analysed for the following five separate categories:

- All fatal accidents
- Passenger flights only
- Cargo flights only
- Western-built jets only
- Western-built jets on passenger flights only

Other points to note are the inclusion of two extra items at the end: 'Other', which includes possible suicide (e.g. SilkAir B737 and Egyptair B767) and 'Unknown', which signifies that there is an element of uncertainty surrounding the circumstances of an accident (e.g. many accidents in Africa).

#### Data Sources:

Ascend (formally Airclaims) CASE database CAA Fatal accident database

# **Background Supporting Statistics**

Phase of Flight	All Fatal Accidents	Passenger Flights Only	Cargo Flights Only	Western- Built Jets Only	Western- Built Jets on Passenger Flights Only
Pre-Flight and Taxi-					
Out	2	1	1	1	1
Take-Off	36	23	13	12	10
Climb	58	32	26	16	11
Cruise	48	33	15	13	12
Descent	13	8	5	4	3
Approach	108	74	34	32	25
Landing	36	30	6	18	18
Post-Flight	2	2	0	2	2
Total	303	203	100	98	82

# Main Data analysis

		All Fatal Accidents	Passenger Flights Only	Cargo Flights Only	Western- Built Jets Only	Western- Built Jets on Passenger Flights Only
1. GENERA	L OPERATIONAL THREATS		-			
1.1	Deficiency within Manuals	4	3	1	0	0
1.2	Deficiency within Charts	2	2	0	1	1
1.3	Deficiency in Ops Data	9	7	2	5	4
1.4	Deficiency within Database	0	0	0	0	0
1.5	Deficiency within Checklists	0	0	0	0	0
1.6	Compliance failure	100	76	24	43	38
1.7	Mishandled Aircraft	68	43	25	23	20
1.8	Mismanaged Aircraft State	41	33	8	20	18
1.9	Mishandled Auto Flight Systems	10	7	3	6	5
1.10	Other Mishandled system	20	17	3	9	9
1.11	Loading/fuel/Performance	22	8	14	4	2
1.12	Workload/ Distraction/ Pressure	18	14	4	7	7
1.13	Fatigue	18	12	6	7	6
1.14	Procedures	36	24	12	13	9
1.15	Cabin issues	3	3	0	1	1
1.16	Terrorism [Note: not covered by AAG]	0	0	0	0	0
1.17	Physiological	4	3	1	1	1
1.18	Human Factors and CRM	169	122	47	63	53
2. PRE-FLI	GHT & TAXI-OUT	1	1			r
2.1	Ground equipment	0	0	0	0	0
2.2	Ground manoeuvring	0	0	0	0	0
2.3	Runway/Taxi condition	0	0	0	0	0
2.4	Adverse Weather/Ice	0	0	0	0	0
2.5	Wind	0	0	0	0	0
2.6	ATC	1	0	1	0	0
2.7	NAV	0	0	0	0	0
2.8	Loss of comms	0	0	0	0	0
2.9	Traffic	1	0	1	0	0
2.1	R/W incursion	1	0	1	0	0
2.11	Poor Visibility	0	0	0	0	0
2.12	Eng Fail	0	0	0	0	0
2.13	MEL	0	0	0	0	0
2.14	Fire	1	1	0	1	1
2.15	System malfunction	0	0	0	0	0
2.16	Pilot Incapacitation	0	0	0	0	0
2.17	Dangerous goods	0	0	0	0	0

3. TAKE-OF	F					
3.1	Windshear	0	0	0	0	0
3.2	Adverse Weather/Ice	6	5	1	3	3
3.3	Runway/Taxi condition	5	5	0	3	3
3.4	Wind	1	1	0	1	1
3.5	ATC	2	2	0	2	2
3.6	NAV	0	0	0	0	0
3.7	Loss of comms	0	0	0	0	0
3.8	Traffic	1	1	0	1	1
3.9	R/W incursion	1	1	0	1	1
3.10	Poor Visibility	3	3	0	2	2
3.11	Wake vortex	0	0	0	0	0
3.12	Upset	0	0	0	0	0
3.13	Terrain	1	1	0	0	0
3.14	Birds	3	1	2	0	0
3.15	Eng Fail	11	5	6	3	2
3.16	MEL	0	0	0	0	0
3.17	Fire	4	2	2	2	1
3.18	System malfunction	8	5	3	2	2
3.19	Pilot Incapacitation	0	0	0	0	0
3.20	Dangerous goods	0	0	0	0	0
4. CLIMB						
4.1	Windshear	1	0	1	0	0
4.2	Adverse Weather/Ice	13	7	6	4	3
4.3	ATC	1	0	1	1	0
4.4	NAV	0	0	0	0	0
4.5	Loss of comms	0	0	0	0	0
4.6	Traffic	0	0	0	0	0
4.7	Poor Visibility	11	5	6	1	1
4.8	Wake vortex	1	1	0	1	1
4.9	Upset	2	1	1	2	1
4.10	Terrain	3	2	1	1	1
4.11	Birds	2	1	1	0	0
4.12	Eng Fail	17	9	8	1	1
4.13	MEL	1	1	0	0	0
4.14	Fire	3	0	3	0	0
4.15	System malfunction	10	7	3	3	2
4.16	Pilot Incapacitation	0	0	0	0	0
4.17	Dangerous goods	1	0	1	0	0

5. CRUISE						
5.1	Windshear	2	2	0	2	2
5.2	Adverse Weather/Ice	16	10	6	2	2
5.3	ATC	3	2	1	2	1
5.4	NAV	0	0	0	0	0
5.5	Loss of comms	0	0	0	0	0
5.6	Traffic	5	3	2	2	1
5.7	Poor Visibility	6	6	0	0	0
5.8	Wake vortex	0	0	0	0	0
5.9	Upset	2	1	1	1	1
5.10	Terrain	10	10	0	0	0
5.11	Birds	0	0	0	0	0
5.12	Eng Fail	5	2	3	1	1
5.13	MEL	0	0	0	0	0
5.14	Fire	1	1	0	1	1
5.15	System malfunction	11	10	1	5	5
5.16	Pilot Incapacitation	2	2	0	2	2
5.17	Dangerous goods	0	0	0	0	0
6. DESCEN	T					
6.1	Windshear	0	0	0	0	0
6.2	Adverse Weather/Ice	4	2	2	1	1
6.3	ATC	0	0	0	0	0
6.4	NAV	0	0	0	0	0
6.5	Loss of comms	0	0	0	0	0
6.6	Traffic	0	0	0	0	0
6.7	Poor Visibility	4	3	1	1	1
6.8	Wake vortex	0	0	0	0	0
6.9	Upset	1	0	1	0	0
6.10	Terrain	6	5	1	2	2
6.11	Birds	0	0	0	0	0
6.12	Eng Fail	4	2	2	1	1
6.13	MEL	0	0	0	0	0
6.14	Fire	0	0	0	0	0
6.15	System malfunction	1	1	0	0	0
6.16	Pilot Incapacitation	0	0	0	0	0
6.17	Dangerous goods	1	1	0	0	0

7. APPRO	ACH					
7.1	Windshear	2	2	0	1	1
7.2	Adverse Weather/Ice	25	22	3	9	9
7.3	Wind	5	4	1	3	3
7.4	ATC	4	4	0	3	3
7.5	NAV	0	0	0	0	0
7.6	Loss of comms	0	0	0	0	0
7.7	Traffic	1	0	1	0	0
7.8	R/W incursion	1	0	1	0	0
7.9	Poor Visibility	47	36	11	16	15
7.10	Wake vortex	0	0	0	0	0
7.11	Upset	1	1	0	0	0
7.12	Terrain	50	36	14	16	14
7.13	Birds	0	0	0	0	0
7.14	Eng Fail	15	10	5	3	1
7.15	MEL	1	0	1	0	0
7.16	Fire	1	1	0	0	0
7.17	System malfunction	14	8	6	5	3
7.18	Pilot Incapacitation	1	1	0	1	1
7.19	Dangerous goods	1	0	1	1	0
8. LANDING		ſ				
8.1	Windshear	3	3	0	3	3
8.2	Adverse Weather/Ice	13	13	0	12	12
8.3	Runway/Taxiway condition	11	10	1	8	8
8.4	Wind	8	8	0	6	6
8.5	ATC	2	2	0	2	2
8.6	NAV	1	1	0	1	1
8.7	Loss of comms	0	0	0	0	0
8.8	Traffic	1	1	0	0	0
8.9	R/W incursion	1	1	0	0	0
8.10	Poor Visibility	9	8	1	7	7
8.11	Wake vortex	0	0	0	0	0
8.12	Upset	0	0	0	0	0
8.13	Birds	0	0	0	0	0
8.14	Eng Fail	3	2	1	0	0
8.15	MEL	3	3	0	3	3
8.16	Fire	0	0	0	0	0
8.17	System malfunction	7	6	1	6	6
8.18	Pilot Incapacitation	1	1	0	1	1
8.19	Dangerous goods	0	0	0	0	0

9. POST-FLIGHT						
9.1	Ground equipment	0	0	0	0	0
9.2	Ground manoeuvring	0	0	0	0	0
9.3	Runway/Taxi condition	0	0	0	0	0
9.4	Adverse Weather/Ice	0	0	0	0	0
9.5	Wind	0	0	0	0	0
9.6	ATC	0	0	0	0	0
9.7	NAV	0	0	0	0	0
9.8	Loss of comms	0	0	0	0	0
9.9	Traffic	0	0	0	0	0
9.10	R/W incursion	0	0	0	0	0
9.11	Poor Visibility	0	0	0	0	0
9.12	Eng Fail	0	0	0	0	0
9.13	MEL	0	0	0	0	0
9.14	Fire	0	0	0	0	0
9.15	System malfunction	2	2	0	2	2
9.16	Pilot Incapacitation	0	0	0	0	0
9.17	Dangerous goods	0	0	0	0	0
10. OTHER						
10.1	Possible suicide	2	2	0	2	2
11. UNKNO	WN					
11.1	Element of uncertainty about accident scenario	37	18	19	5	3







**Figure 3** Breakdown of all fatal accidents by causal group (for primary causal factors only) for the ten-year period 1997 to 2006 (CAP 776)

Rank	Causal Group	Primary Causal Factor	No. Fatal Accidents	%
1	Flight crew	Omission of action/inappropriate action	63	22.3%
2	Flight crew	Lack of positional awareness – in air	40	14.1%
3	Flight crew	Flight handling	39	13.8%
4	Flight crew	Poor professional judgement/airmanship	16	5.7%
5	Maintenance/ ground handling	Maintenance or repair error/oversight/inadequacy	12	4.2%
6	Environmental	Windshear/upset/turbulence/gusts	6	2.1%
7=	Flight crew	Loading incorrect	5	1.8%
7=	Flight crew	Deliberate non-adherence to procedures	5	1.8%
7=	Maintenance/ ground handling	Loading error	5	1.8%
10=	Aircraft systems	System failure - flight deck information	4	1.4%
10=	Aircraft systems	System failure – other	4	1.4%
10=	ATC/ground aids	ound aids Incorrect or inadequate instruction/advice (ATC)		1.4%
10=	Flight crew	crew Lack of awareness of circumstances in flight		1.4%
10=	Flight crew	Disorientation or visual illusion	4	1.4%

 
 Table 1
 Top-ten primary causal factors allocated for all fatal accidents for the tenyear period 1997 to 2006

# **Table 2**Five most common causal factor groups (CAP 780)

Causal factor	Percent of accidents with factor		
Crew - Omission of action/inappropriate action	36%		
Crew - Flight handling	28%		
Crew - Lack of positional awareness - in air	25%		
Crew - Failure in CRM (cross check/co-ordinate)	22%		
Crew - Poor professional judgement/airmanship	20%		

# Comment

- 1. The global fatal accident data was re-analysed by means of the ITQI Intuitive Threat Matrix.
- 2. Analysis, by phase of flight (Figure 1), clearly shows that the greatest risk is within the approach phase of flight.
- 3. Further analysis to determine the areas of general operational threat it is clear that the major threat is that of the non-technical area of human factors (Figure 2).
- The UK Civil Aviation Authority publications CAP 776 Global Fatal Accident Review 1997 2006 and CAP 780 Aviation Safety Review 2008 both suggest that the main areas of concern are non technical ones by nature (Figure 3).
- 5. Table 1 (CAP 776) demonstrates that the top two primary causal factors, accounting for 36.4% of accidents, are non technical in nature. This is further reinforced by data from the CAP 780 which shows that the top five most common causal factors groups contain a significant component of non-technical elements (Human Factors).
- 6. Table 2 (CAP 780) again demonstrates that the most frequently occurring causal factors are crew related.

# APPENDIX 7 Flight data analysis (FDA)

# INTRODUCTION

This introduction contains data in graphic format of the three formal flight data analysis studies used in the EBT analysis:

- 1. A Study of Normal Operational Landing Performance on Subsonic Civil Narrow Body Jet Aircraft during ILS Approaches NLR The full report can be accessed using the link in section 7.1.
- 2. The EBT Flight Data Analysis A de-identified confidential analysis that was performed by the EBY Data subgroup primarily focusing on unstable approaches.
- 3. Long Aircraft Type/Variant difference on Landing and Takeoff A de-identified confidential report study takeoffs and landings of long body aircraft.

# Landings in NLR StudyAircraft TypeNumber of LandingsG417,474G4212,245G435,952G3112,093Aircraft Types have been de-identified.Subscripts indicate de-identified type.

# 7.1 NLR REPORT

Figure 3.3.3 – Number of Aircraft by Generation and de-identified type in NLR

(See Link for the published NLR Study - http://www.tc.faa.gov/its/worldpac/techrpt/ar077.pdf)

# 7.2 EBT FLIGHT DATA ANALYSIS

	EBT Flight Data Analysis
Event ID	Landing Events
1022	Speed High at Touch Down
1023	Speed Low at Touch down
1024	Speed Above Maximum Tire Speed
1029	Braking Delayed at Landing
1033	Tail wind High at Landing
1035	Braking Questionable at Landing
1105	Pitch Input cycling at Landing (below 100ft)
1108	Pitch High at Touch Down
1109	Pitch Low at Touch Down
1111	Pitch Rate High at Landing
1200	Bank High in Approach (below 100ft)
1205	Roll input cycling (below 200ft)
1210	Bank High during Flare (below 10ft)
1211	Bank Oscillation in Approach (below 100ft)
1219	Roll Spoilers extension at Landing (below 50ft)
1405	Path High at Landing (below 20ft)
1504	Vertical Acceleration High at Touchdown
1505	High Lateral Load at Touch Down
1510	Lateral Acceleration High at Touchdown
1602	Flaps Questionable Setting at Landing
1611	Late Reverser Use at Landing
1619	Reversers High Thrust at Low Speed
1703	Thrust Reduction Late at Landing
1706	Thrust Asymmetry in Reverse
1714	Thrust Low at Landing (50ft)
1807	Heading Deviation at Landing (above 60kts)
1808	Long Flare Time
1812	Height Low at Threshold
1813	Height High at Threshold
1815	Heading Excursion During Landing Roll
1817	Short Flare Distance
1818	Long Flare Distance
1819	Short Flare Time
1820	High Vertical Speed before Touchdown
1821	Localizer Deviation at Landing (threshold)
1822	Aircraft not on center line
1905	Engine Reverser selected in Flight
1906	Bounced Landing
1917	Dual Input
1950	Questionable decrab
2206	Wing Strike Risk at Landing
2207	Hard Landing Risk

Figure 3.3.1.4.4 – Landing Events used in EBT FDA Study by name and number

EBT Flight Data Analysis		
Event ID	Serious Landing Events	
1200	Bank High in Approach (below 100ft)	
1210	Bank High During Flare (below 10ft)	
1211	Bank oscillation in Approach (below 100ft)	
1812	Height Low at Threshold	
1815	Heading Excursion During Landing Roll	
1906	Bounced Landing	
2206	Wing Strike Risk at Landing	
2207	Hard Landing Risk	
1922	GPWS Warning (below 500ft)	

Figure 3.3.1.4.4b – Serious Landing Events used in EBT FDA Study by name and number

EBT Flight Data Analysis		
Event ID	Go Around Events	
1008	Speed Above VLO Retraction	
1009	Speed Above VLE	
1016	Speed Above VLO Extension	
1017	Speed Above VFE	
1025	Speed Above Recommended Turbulence Speed	
1028	Speed Low	
1032	Speed High in Climb (below 1000ft)	
1038	Speed Low in Climb (100ft - 1500ft)	
1100	Pitch High at Take Off	
1101	Pitch Rate High at Take Off	
1102	Pitch Rate Low at Take Off	
1103	Pitch High in Climb	
1104	Pitch Low in Climb	
1206	Bank High in Climb (Take Off - 100ft)	
1207	Bank High in Climb (100ft - 400ft )	
1208	Bank High in Climb (400ft - 1000ft)	
1209	Bank Cycling at Take Off	
1407	Rate Of Climb Low in Climb (below 1000ft AFE)	
1500	Vertical Acceleration High at Take Off	
1501	Vertical Acceleration Hi in Flight	
1600	Flaps Early Retraction at Take Off	
1605	Configuration Change Questionable during Go Around	
1609	Landing Gear Late Retraction	
1613	Speed Brakes Out with Significant Thrust	
1618	Rudder Large Inputs (above 200ft)	
1702	EGT High	
1800	HDG Deviation at Take Off (100kts - Rotation)	
1903	Windshear Warning	
1909	Alpha Floor	
1910	Alternate Law	
1911	Direct Law	
1917	Dual Inputs	
1918	TCAS Resolution Advisory	
1921	GPWS Warning (1000ft - 500ft)	
1922	GPWS Warning (below 500ft)	
1930	Stall Warning	

Figure 3.3.1.4.4a- Go-around Events used in EBT FDA Study by name and number



Unstable Approach Event Set		
2000	Continuously Low during final	
2001	Continuously Slow during final	
2002	Continuously High during final	
2003	Continuously Fast during final	
2004	Continuously Steep during final	
2009	Late Offset in Short Final	
2012	Roll Oscillations prior to Flare	

Figure 3.3.1.4.1 – Events used in EBT FDA Study by name and number to define the set of Unstable Approaches.



Figure 2.3c – Comparison of Stable versus Unstable approaches by the rate of landing events per flight using events of all severity









Figure 2.3e – Comparison of Stable versus Unstable approaches by the percentage rate of landing events per flight using events of high severity















Figure 2.3i – Comparison of Stable versus Unstable approaches by the percentage of high severity events per flight using events occurring in flight phases other than approach and landing

EBT FDA Partitions		
All flights		
All go arounds		
All stable approaches		
All unstable approaches		
Go-arounds from unstable approaches		
Go-arounds from stable approaches		
Landing from unstable approaches		
Landing from unstable appraoches with a detected event at landing (high, medium or low)		
Landing from unstable appraoches with a detected event at landing (high, medium)		
Landing from unstable appraoches with a detected event at landing (high)		
Landing from stable approaches		
Landing from stable approaches with a detected event at landing (high, medium or low)		
Landing from stable approaches with a detected event at landing (high, medium)		
Landing from stable approaches with a detected event at landing (high)		
Events in stable landings (high, medium or low)		
Events in stable landings (high, medium)		
Events in stable landings (high)		
Events in unstable landings (high, medium or low)		
Events in unstable landings (high, medium)		
Events in unstable landings (high)		

Figure 3.3.1.4.2 – Definition of the EBT FDA partitions of the sets for comparison of stable approaches to unstable approaches









Figure 2.3b – Comparison of the percentage flights for the set of stable approaches with at least one event by severity levels




Figure 2.3c – Comparison of the percentage flights for the set of unstable approaches with at least one event by severity levels



Figure A7.1– Average Go-around initiation height by for generation 2, 3, and 4 aircraft for the years 2006, 2007 and 2008 for a set of flights from multiple airlines with a sample size of N = 890,709

# 7.3 LONG AIRCRAFT TYPE/VARIANT DIFFERENCE ON LANDING AND TAKEOFF



Figure 4.2.3.2.1 – Comparison of landing rates of long variant aircraft versus short variant aircraft in terms of maximum vertical acceleration during touchdown in three defined acceleration intervals



Figure 4.2.3.2.1a – Comparison of Long variant aircraft versus short variant aircraft in terms of pitch inputs from 150ft above runway threshold to beginning of flare



Q.

Maximum Vertical G Load (>=1.75)



Figure 4.2.2.2a – Comparison of landing rates of long variant aircraft versus short variant aircraft in terms of maximum vertical acceleration during touchdown with values equal to or greater than 1.75g



# APPENDIX 8 DEFINITIONS OF EVENTS USED IN EBT FDA



# 8.1 INTRODUCTION

All the events below were utilized in the EBT Flight Data Analysis Study and are defined by event number and operational goal.

# 1008 – Speed Above VLO Retraction Operational Goal

When the landing gear is selected to retract/up, this event is raised if the airspeed or Mach number exceeds the Maximum Landing Gear Operating Speed (\_VLO) for more than 3 seconds.

If the landing gear is operated from extend to retract above the Maximum Landing Gear Operating Speed (\_**VLO**) the gear doors may be damaged, with possible damage to the gear assembly.

The event is triggered only in the High severity level.

#### 1009 – Speed Above VLE Operational Goal

This event is raised if the airspeed or Mach number exceeds for more than 3 seconds the Maximum Landing Gear Extended Speed limit (VLE) when the landing gear is extended/down.

Exceeding the VLE limit with the landing gear extended can damage the structure of the **AC** or the landing gear.

The event is triggered only in High severity level.

#### 1016 – Speed Above VLO Extension Operational Goal

While the landing gear is selected to extend/down, this event is raised if the airspeed exceeds the Maximum Landing Gear Operating Speed (VLO) for more than 3 seconds.

If the landing gear is operated above the Maximum Landing Gear Operating Speed (VLO), the gear doors may be damaged with possible consequences to the gear assembly.

The event is triggered in High severity level only.

#### **1017 – Speed Above VFE Operational Goal**

Before the flaps / slats are retracted after take-off, this event detects if the **AC** speed exceeds the Maximum Flap Extended Speed limit (**\_VFE**) for more than 3 seconds.

Exceeding AC structural limit speeds can cause AC damage and any exceedances will generate hearing and visual warnings to alert the crew.

Events to detect these exceedances and **AC** warnings are essential in a Flight Analysis System. The severity levels are Medium and High, with no Low level.

# 1022 – Speed High at Touch Down

# **Operational Goal**

This event is raised if the **AC** airspeed (**\_CAS**) at landing is faster than the Approach Speed (**\_VAPP**). The **AC** flies the approach at the required approach speed **\_VAPP**, and by the landing the airspeed will normally be reduced below **\_VAPP**.

A high speed at landing can cause extra brake and tire wear or lead to over-runs on short or slippery runways.

# 1023 – Speed Low at Touch down Operational Goal

This event detects if the airspeed at landing is more than 5 kts. below the aircraft minimum airspeed (\_VLS).

A low airspeed at landing may result in a heavy, or short landing, or a tail-strike due to the high pitch attitude at low speed.

#### **1024 – Speed Above Maximum Tire Speed Operational Goal**

This event detects if the AC ground speed (\_GS) exceeds the Maximum Tire Limit Speed with the AC on the ground.

The AC tires have a maximum speed limit, which varies according to the aircraft type. If this ground speed is exceeded, damage to the tires can occur, such as treads detaching or tires weakening so it may fail later at normal speeds.

# 1025 – Speed Above Recommended Turbulence Speed Operational Goal

This event detects if AC speed exceeds the Turbulence Target Speed (280 kts or .78 Mach) in turbulent conditions.

In turbulence the AC speed and vertical acceleration fluctuate significantly, and may reach the high and low speed limits in extreme conditions. While flying fast, the maximum speed limit can be exceeded and the probability of passenger injury is increased.

While flying slowly, airspeed may drop below the minimum speed with the likelihood of control difficulties.

The turbulence target speed is chosen to give sufficient margins from both the high and low speed limits.

#### 1028 – Speed Low Operational Goal

This event detects if the airspeed (\_CAS) decreases for more than 3 seconds below the lowest selectable speed (\_VLS), which is the lowest speed permitted in normal operations.

The auto-thrust system should always prevent the airspeed decreasing below VLS.

Any decrease below VLS indicates an abnormal situation, which should have been detected and corrected by the crew.





# 1029 – Braking Delayed at Landing Operational Goal

This event is raised when the **AC** deceleration from high speed is slow by comparing the time to decelerate 50 kts against the Deviation time limits.

Immediately after main landing gear touch down, reverse thrust is normally selected which decelerates the aircraft the most effectively from high speed, and may be augmented by autobrake, with manual braking being used at low speed.

Slow deceleration at high speed indicates a delay in reverse thrust selection when it is the most effective and thus a possible abnormality. However some operators use minimum reverse to keep brake temperatures at optimum, and certain airfields prohibit use of max reverse thrust for noise abatement.

The crew may have elected minimum reverse and braking if they have to continue to the end of a long runway after landing.

# 1032 – Speed High in Climb (below 1000ft) Operational Goal

This event is raised when the AC climb speed is more than 30 kts above V2 and the Pitch attitude is less than 15 degrees when below 1000ft AFE, indicating that the aircraft has accelerated too soon during the initial climb.

The initial profile after take off normally requires a climb speed of V2 plus 10-15 kts to at least 1000ft AFE, and besides being non-standard early acceleration to higher speeds may erode terrain clearance in limiting conditions.

# 1033 – Tail Wind at Landing (below 100ft)

#### **Operational Goal**

This event detects a landing with a tail wind of more than 8 kts A strong tail wind increases the landing speed and the required runway distance.

Most aircrafts have a tail wind limit for landing of 10 kts but this may be increased with an amendment to the Aircraft Flight Manual.

It may be preferable to land at certain airports on runways where the tail wind is the lowest available; however some airport authorities use runways that are preferred for noise abatement with significant tail-winds which may adversely affect safety standards.

#### 1035 – Braking Questionable at Landing Operational Goal

This event detects harsh braking when the **AC** deceleration below 100 kts on runway is at least 0.35G for 3 seconds.

Braking should always be made smoothly for passenger comfort and to minimize wear of aircraft systems.

Harsh braking can indicate poor planning, or execution of the approach and landing, or an external problem, which might point to a possible ground incident. Harsh braking can also indicate unnecessary early runway exit, which may be due to ATC factors.

# 1038 – Speed Low in Climb (100ft – 1500ft) Operational Goal

This event detects if the airspeed (\_CAS) in the initial climb between 100 feet and 1500 feet is below V2 plus 6 kts for more than 3 seconds.

The AC should initially climb at close to V2 + 10 kts with all engines operating.

A lower speed may indicate wind shear or questionable handling technique, and safety margins may be affected if speed falls below V2.

#### 1100 – Pitch High at Take Off Operational Goal

This event detects high pitch attitude at take-off. If the HIGH limit of this event is exceeded, a tail strike may occur.

High pitch at take-off may be linked to a wrong pitch trim setting, an AC balance error, or a questionable rotation technique



# 1101 – Pitch Rate High at Take Off Operational Goal

This event detects a too rapid rotation rate at take-off. If the rotation rate exceeds the relevant triggering values during the MW, the event is raised with the corresponding severity.

The normal rotation rate during take-off is 3° per second, and a very strong rotation can lead to the possibility of a tail strike, a low initial climb speed affecting performance and/or an abnormal G factor.

Higher rotation rates than usual ones might be necessary or explained in abnormal circumstances such as wind shear or take-off roll longer than expected.

#### 1102 – Pitch Rate Low at Take Off

#### **Operational Goal**

This event detects too slow rotation rate at take-off if the rotation rate is less than 2.25° per second.

The normal rotation rate during take-off is 3° per second, and a slow rotation rate can lead to a high initial climb speed reducing obstacle clearance.

Slow rotation rates might be necessary in abnormal circumstances such as wind shear.



# 1103 – Pitch High in Climb

### **Operational Goal**

This event detects if the AC pitch angle is above a defined value in initial climb for longer than 3 seconds. A pitch angle above this value may indicate aircraft mishandling or an abnormal situation such as wind shear.

#### 1104 – Pitch Low in Climb

#### **Operational Goal**

This event detects if the AC pitch angle is less than a defined value in initial climb for more than 3 seconds. A pitch angle below this value can indicate aircraft mishandling or an abnormal situation such as system failure or wind shear. A low pitch may also significantly reduce the obstacle clearance

# 1105 – Side Stick Pitch cycling at Landing (below 200ft) Operational Goal

Side stick pitch cycling has been identified as a contributing factor in high G landings. Nose down input should be avoided below 100ft. Side stick pitch cycling is detrimental to a well-controlled flare and landing.

# 1108 – Pitch High at Touch Down Operational Goal

This event detects if the AC pitch angle exceeds the limit imposed by the geometric configuration of the AC at landing (rear fuselage length, and landing gear extension when compressed).

An excessive pitch angle at landing indicates a possible tail strike.



# 1109 – Pitch Low at Touch Down

#### **Operational Goal**

This event detects a pitch attitude of less than 2,5° during landing.

Low pitch angle during landing can indicate high approach airspeed or under-flare, which could lead to a heavy touch down. In some cases it may even lead to a nose gear harsh touch down.

# 1111 – Pitch Rate High at Landing

# **Operational Goal**

This event detects a rapid rotation rate (more than 2° per second) during the landing flare.

Following a stabilized approach the landing flare should consist of a gentle increase in pitch from the approach attitude to arrest the rate of decent prior to touch down.

A too strong flare may lead to a tail strike or indicate an abnormal approach. Rapid rotations in the flare might be necessary in wind shear or with a down draft close to the runway.

# 1200 – Bank High in Approach (below 100ft)

#### **Operational Goal**

This event detects if the AC bank angle is more than 6° below 100 feet AFE in final approach.

High bank angles at very low altitude could be due to wind shear or a severe crosswind, or could indicate a poor approach technique and may lead to wingtip strike or engine nacelle damage or a runway lateral excursion. It may also lead to poor accuracy at landing resulting in reduced lateral margins from obstacles or other aircraft on ground.

# 1205 – Side Stick Roll cycling (below 200ft)

#### **Operational Goal**

Side stick roll cycling has been identified as contributing factors to high g landings. Side stick roll cycling is detrimental to a well-controlled flare and a wings level landing.

# 1206 – Bank High in Initial Climb (Take Off – 100ft)

#### **Operational Goal**

This event detects if the AC bank angle is more than 6° for longer than 3 seconds below 100 feet AFE in the initial take-off phase.

High bank angles at very low altitude after take-off may indicate directional control problems perhaps after an engine failure or in wind shear or a severe crosswind. It may also be associated to a questionable side stick lateral input during rotation initiation.

# 1207 – Bank High in Initial Climb (100ft – 400ft)

#### **Operational Goal**

This event detects if the AC bank angle is more than 15° for longer than 3 seconds between 100 feet AFE and 400 feet AFE in the initial climb.

High bank angles at low altitude in the initial climb might indicate directional control problems perhaps after an engine failure, which could significantly degrade climb performance, or could simply be required by tight turns in the departure procedure.



# 1208 - Bank High in Initial Climb (400ft - 1000ft)

### **Operational Goal**

This event detects if bank angle is more than 25° between 400 feet AFE and 1000 feet AFE in the initial climb for longer than 5 seconds.

High bank angles in the initial climb might indicate directional control problems perhaps after an engine failure, which could significantly degrade, climb performance, or could simply be required by tight turns in the departure procedure.

# 1209 – Bank Cycling during Initial Climb

#### **Operational Goal**

This event detects abnormal bank oscillations during the initial climb by counting the number of times the AC rolls in opposite directions around the average bank angle taken over a maximum time interval.

Bank oscillations during the initial climb could indicate a control problem due to a system failure or over- controlling by the pilot.

#### 1210 – Bank High during Flare (below 10ft)

#### **Operational Goal**

This event detects bank angles of more than 5° below 10ft Radio Altimeter (RA) and lasts the first 10 seconds of the landing roll.

Bank angles during the flare could be required to align the aircraft with the runway centerline in strong crosswinds, otherwise significant bank angles in the flare and initial landing roll could indicate an abnormal situation possibly leading to a runway lateral excursion and/or wingtip strike or engine nacelle damage.



# 1211 – Bank Oscillation in Approach (below 100ft)

# **Operational Goal**

This event detects large bank angle changes below 100 feet AFE.

Significant bank angles below 100ft may be required for runway alignment during strong cross winds, but large changes in bank angles could indicate an abnormal situation possibly leading to a runway lateral excursion and/or wingtip strike or engine nacelle damage.

# 1219 – Roll Spoilers extension at Landing (below 50ft)

# **Operational Goal**

Except for strong crosswind de-crab techniques, roll spoilers extension during flare may lead to a residual bank at landing and to a possible wing tip /engine nacelle damage or may lead to a runway excursion

# 1405 – Path High at Landing (below 20ft)

# **Operational Goal**

This event detects if the descent slope from 20 feet to the ground is steeper than 2.25. A steep descent slope below 50ft may lead to a hard landing and possible AC damage.

# 1407 – Rate of Climb Low in Initial Climb (below 1000ft)

# **Operational Goal**

This event detects if the climb rate after take-off is less than 1000 feet per minute for longer than 5 seconds. With all engines operating after take-off, rates of climb should normally be higher than 1000 feet per minute.

Lower climb rates may indicate an engine failure or weather conditions such as wind shear or abnormal aircraft handling resulting in early acceleration. Low climb rates may conflict with the obstacle clearance requirements.

# 1500 – Vertical Acceleration High at Take Off

# **Operational Goal**

This event detects if the vertical acceleration for a normal take-off is exceeded. A high acceleration rate during rotation can indicate incorrect operational technique, control system abnormality, aircraft erroneous balance or external influence such as wind shear.

# 1501 – Vertical Acceleration High in Flight

# **Operational Goal**

This event detects abnormalities such as in flight turbulence by monitoring abnormal vertical accelerations during the flight.



# 1504 – Vertical Acceleration High at Touchdown

### **Operational Goal**

This event detects High G landings by monitoring touchdowns, which exceed Vertical Acceleration of 1.5G. A family of High G landings might be associated to local factors (high altitude airports, wind shear, surrounding terrain, uphill runways etc.). A severe High G landing might indicate, but not always, a hard landing as per the maintenance manual.

# 1510 – Lateral Acceleration High at Touchdown

#### **Operational Goal**

High Lateral acceleration may occur with crosswind or engine out landings. It may result in undue fatigue or damage for the landing gear and the AC structure.

#### **1602 – Flaps Questionable Setting at Landing**

#### **Operational Goal**

This event detects an incorrect flap setting on landing (LANDING).

AIRBUS recommendation is to land in CONF FULL except if a possible wind shear can be anticipated. An INFO event is raised if landing is done in CONF 3.

#### 1605 – Configuration Change Questionable during Go Around

#### **Operational Goal**

This event is detected when a Go Around Procedure is carried out incorrectly by monitoring that the flap configuration changes and gear selection are made in the correct sequence and time frame.

#### **1609 – Landing Gear Late Retraction**

#### **Operational Goal**

This event detects if the landing gear is retracted significantly later than normal after take off, missed approach or go-around. In normal operation the gear is retracted as soon as the crew confirms a positive climb from the flight instruments, normally by about 100ft AFE.

If the gear retraction is delayed, the increased aerodynamic drag could reduce terrain clearance during the initial climb especially following an engine failure.

After a touch and go, the gear may be left extended to cool the wheel assembly

# 1611 – Reversers Delayed at Landing

# **Operational Goal**

This event detects late selection of engine thrust reversers after landing.

Reverse thrust is normally selected immediately after main gear touchdown, and late selection of reversers delays the ground spoilers extension back-up logics (when spoilers are not armed); It increases landing distance, which is aggravated with a slippery runway surface; It also affects brake wear.

# 1613 – Speed Brakes Out with Significant Thrust

#### **Operational Goal**

This event detects when the speed brakes, also called airbrakes, are selected out with engines at thrust above 60% N1 (or 1.15 EPR) for longer than 20 seconds.

This condition is normally a result of the crew forgetting to retract the speed brakes, and is accompanied by an ECAM warning.

# 1618 – Rudder Large Inputs (above 200ft)

# **Operational Goal**

This event detects abnormal rudder deflection commands from the crew. Excessive rudder deflection commands can over stress the AC structure and reveals highly abnormal handling of the AC.

#### 1619 – Reversers High Thrust at Low Speed

# **Operational Goal**

This event detects if the thrust reversers are not cancelled at the normal speed during the landing roll.

Thrust reversers are most effective at high speed. At low speed hot airflow from the reverser exhaust can be ingested by engines causing surges or loud explosions as well as possible engine damage from the shock and ingestion of foreign objects.

Reverse thrust should therefore be reduced at 70kts towards idle reverse, which should be cancelled by taxi speed of about 25 knots. However in an emergency, full reverse thrust can be kept until the aircraft has stopped.

Triggering of this event would usually indicate mishandling of reverse thrust, but could indicate an emergency stop.



# 1702 – EGT High

# **Operational Goal**

This event is raised when an engine Exhaust Gas Temperature (EGT) exceeds the manufacturer's limit during a take-off or Go Around for more than 2 seconds.

An excessive EGT may damage the engine hot end section with a likelihood of subsequent failure if maintenance actions are not taken.

This event alerts that an engine inspection is required.

# 1703 – Thrust Reduction Late at Landing

# **Operational Goal**

This event detects if the thrust is reduced late (below 10ft) during landing, both with and without active Auto thrust.

A hard or bounced landing can result if the thrust is not reduced at the correct rate and height above the runway. It may affect the landing distance performance.

If the thrust levers are not retarded to Idle the Auto thrust will still be operative and as the aircraft is flared and the speed tends to decrease this will cause an increase in thrust. An increase in thrust during the flare will cause an increase in flare distance with its associated hazards.

# 1706 – Thrust Asymmetry during Landing Roll Out

# **Operational Goal**

This event detects if thrust asymmetry between right and left engines at landing exceeds a certain threshold with both engines operative in reverse thrust.

With both engines operative reverse thrust asymmetry can be due to crew thrust lever mishandling or an engine malfunction, and can lead to runway excursions especially on a slippery runway surface.



# 1800 – HDG Deviation at Take Off (100kts – Rotation)

# **Operational Goal**

This event detects significant aircraft heading changes during the take-off roll. This can indicate a lateral control problem due to an incorrect control input, a residual rudder trim setting, a crosswind factor or another abnormality causing a deviation from the centerline, which require heading changes to realign the aircraft with the runway.

# 1807 – Heading Deviation at Landing (above 60kts)

#### **Operational Goal**

This event detects if there is a Heading Deviation during the landing roll (LANDING) above 60 kts. This can be due to severe crosswinds, crew mishandling or an abnormal aircraft condition leading to an AC deviation from the runway centerline.

# 1808 – Long Flare Time

#### **Operational Goal**

This event detects if a flare is abnormally long. A flare which is too long consumes excessive runway length, and on short runways, or runways with a slippery surface, this may lead to a hazardous situation.

#### 1812 – Height Low at Threshold

#### **Operational Goal**

This event detects if the AC crosses the runway threshold (THR) at (or below) 35ft after an ILS approach.

The ILS normally guides the AC to cross the THR at 50 feet AFE, and passing the THR significantly lower indicates a landing close to the runway THR, which can lead to land before the runway paved surface (Short Landing).

#### 1813 – Height High at Threshold

#### **Operational Goal**

This event detects if the AC crosses the runway threshold (THR) at (or above) 60ft AFE after an ILS approach.

The ILS normally guides the AC to cross the THR at 50 feet AFE, and passing the THR significantly higher can indicate an abnormal approach perhaps of high energy and may lead to overruns of the runway in limiting conditions.



# 1814 – HDG Significant Change in Approach (below 500ft)

### **Operational Goal**

This event detects a significant heading change during final approach below 500 ft. AFE.

This often indicates a late parallel runway change, but could be a late alignment after a circling or visual approach, or corrections due to a strong cross wind.

#### 1816 – Lateral Deviation at Landing

#### **Operational Goal**

This event detects significant excursions from the runway centerline from Touch Down to 50kts. Large lateral deviations at landing may lead to possible runway lateral excursions due to track size of this category of airplane and to a critical reduction in wing tip clearance to surrounding obstacles. Roll out should be laterally stable and not deviate from the centerline to prevent FOD on external engines (the external engines are high over ground and less prone to FOD than the internal engines on the A380).

#### **1817 – Short Flare Distance**

#### **Operational Goal**

This event detects when the AC lands too close to the runway threshold (THR), by monitoring the distance from THR to the first touch down point (LANDING) after an ILS approach.

AC, which lands short or close after the runway threshold may land in the approach area before the runway paved surface with inevitable AC damage.

#### **1818 – Long Flare Distance**

#### **Operational Goal**

This event detects if the AC lands too far from threshold (THR), by monitoring the distance from THR to the first touch down point (LANDING) after an ILS approach.

The hazard of an AC which lands considerably after the threshold is over-running the runway paved surface when the runway distance is limiting for the conditions, e.g. with slippery runway or tailwind.

#### 1819 – Short Flare Time

#### **Operational Goal**

This event detects when a flare is abnormally short.

A short flare may lead to a hard landing, since the rate of descent may be abnormally high and or the flare maneuver started late by the pilot.

# 1820 – High Vertical Speed before Touchdown

# **Operational Goal**

This event detects when the last part of the flare is performed with a high rate of descent. This can lead to a hard landing.

# 1821 – Heading Deviation at Take-Off

### **Operational Goal**

This event detects significant aircraft heading changes late in the take-off roll during TAKE\_OFF.

This can indicate a wing lifting due to an incorrect control input for a crosswind or other abnormality causing a deviation from the centerline, which require heading changes to realign the aircraft with the runway.

# 1822 – Aircraft not on centerline

#### **Operational Goal**

This event detects significant excursions from the runway centerline from runway threshold to Touch Down. Large lateral deviations at landing may lead to possible runway lateral excursions due to track size of this category of airplane and to a critical reduction in wing tip clearance to surrounding obstacles. Roll out should be laterally stable and not deviate from the centerline to prevent FOD on internal engines.

#### 1903 – Windshear Warning

#### **Operational Goal**

This event is raised if the AC EGPWS system predicts Windshear conditions below 1500ft AFE.

# 1905 – Engine Reverser selected in Flight

#### **Operational Goal**

This event detects if reversers are engaged while aircraft is in flight.

# 1906 – Bounced Landing

# **Operational Goal**

This event detects a bounced landing if the aircraft is airborne 1 second after a touch down.

# 1909 – Alpha Floor

# **Operational Goal**

This event is raised when the Alpha floor high angle of attack protection is activated to apply full engine thrust (TOGA).



# 1910 – Alternate Law

# **Operational Goal**

This event detects if the AC reverts to the Alternate Flight Control Law for 5 seconds.

# 1911 – Direct Law

### **Operational Goal**

This event is raised when the AC reverts to the Direct Flight Control Law for 5 seconds.

# 1917 – Dual Stick Inputs

#### **Operational Goal**

This event detects occurrences of sidestick deflection occurring from both sidesticks at the same time (beyond thresholds in roll or pitch axis) that could affect aircraft trajectory or altitude beyond the path as intended by the PFs inputs. Dual inputs can also cause the PF to be out of the aircraft control loop. The aircraft is designed to be flown manually by one pilot and double stick inputs should not occur.

The thresholds used in the aircraft dual stick input logic have resulted from design and testing to represent the amount of significant sidestick inputs needed to start potentially unsafe trajectory changes. Hence AirFASE needs to monitor this same risk to safe flight.

It is not the intent of this event to monitor SOPs. Therefore for cases where the take-over button is used by the PNF, then event reset conditions are applied (i.e. no event is triggered or the event triggering condition is reset if it was previously triggered)

# 1918 – TCAS Resolution Advisory

# **Operational Goal**

This event detects if the AC TCAS system issued a Resolution Advisory for 3 seconds. A TCAS systems issues a Resolution Advisory to the aircraft (e.g. to climb or descend) to avoid a possible collision with another aircraft. All Resolution Advisories should be investigated.



# 1921 – GPWS Warning (1000ft – 500ft)

# **Operational Goal**

This event detects if the AC GPWS (Ground Proximity Warning System) issues a warning between 1000 feet AFE and 500 feet AFE.

A GPWS Glideslope warning is advisory only.

# 1922 – GPWS Warning (below 500ft)

#### **Operational Goal**

This event detects if the AC GPWS (Ground Proximity Warning System) issues a warning below 500 feet AFE.

#### 2000 – Continuously Low during final

#### **Operational Goal**

This event detects approaches that cross 2 or more of 3 Altitude Gates at a shallow flight path angle, as detected by LEVEL 1 (M1) Path Low events

- 1313 Path Low in Approach (at 1200ft),
- 1315 Path Low in Approach (at 800ft) and
- 1317 Path Low in Approach (at 400ft)

An approach with abnormally low path angle can lead to short landings or possibly infringe obstacle clearance margins.

# 2001 – Continuously Slow during final

#### **Operational Goal**

This event detects approaches that cross 2 or more of 3 altitude gates at low approach speed, as detected by the LEVEL 1 (M1) Events Approach Speed Low

- 1011 Speed Low in Approach (at 1000ft),
- 1013 Speed Low in Approach (at 500ft) and
- 1015 Speed Low in Approach (at 50ft)

AC with abnormally low speed in approach have low energy and may not have sufficient engine thrust response to recover from windshear or downdrafts, leading to short / hard landings, together with risk of tail strikes due to high pitch attitude.



# 2002 – Continuously High during final

#### **Operational Goal**

This event detects approaches that cross 2 or more of 3 altitude gates significantly above the 3° glide path angle to the runway (or the local ILS glidepath angle), as detected by the individual LEVEL 1 (M1) Path High Events

- 1312 Path High in Approach (at 1200ft),
- 1314 Path High in Approach (at 800ft) and
- 1316 Path High in Approach (at 400ft)

Flying significantly above the 3° glide path during approach can lead to final descents on steep approach angles, causing high rates of descent, difficult speed management and unstable approaches with high risk of a runway excursion.

#### 2003 – Continuously Fast during final

#### **Operational Goal**

This event detects approaches that cross 2 or more of 3 altitudes gates with Approach Speed High, as detected by the LEVEL 1 (M1) Approach Speed High events

- 1010 Speed High in Approach (at 1000ft),
- 1012 Speed High in Approach (at 500ft) and
- 1014 Speed High in Approach (at 50ft)

An abnormally fast approach speed can lead to long flares and high risk of runway over-runs on short and/or slippery runways.

#### 2004 – Continuously Steep during final

#### **Operational Goal**

This event detects approaches that pass 2 or more of 3 altitude gates with High Rate of Descent as detected by the LEVEL 1 (M1) High Rate of Descent events

- 1402 Rate Of Descent High in Approach (from 2000ft 1000ft),
- 1403 Rate Of Descent High in Approach (from 1000ft 500ft) and
- 1404 Rate Of Descent High in Approach (below 500ft)

An abnormally steep approach with high rates of descent has a high risk of leading to landing incident such as a hard landing.

# 2009 – Late Offset in Short Final

# **Operational Goal**

This event detects a late runway alignment combined with large bank angles below 400ft AFE using LEVEL 1 (M1) events

- 1814 HDG Significant Change in Approach (below 500ft) and
- 1201 Bank High in Approach (400ft 100ft)

Late runway alignment and large bank angles close to the ground carry a high risk of a landing incident.

# 2012 – Roll Oscillations prior to Flare

#### **Operational Goal**

This event detects abnormal bank oscillations prior to flare from the LEVEL 1 (M1) events

- 1200 Bank High in Approach (below 100ft) and
- 1211 Bank Oscillation in Approach (below 100ft)

Large bank angles and rapid roll movements close to the ground carry a high risk of runway excursion and / or AC damage.



# APPENDIX 9 Advanced qualification program (AQP)

# INTRODUCTION

This appendix provides the comparative, generational results in graphical format of the de-identified EBT AQP study. The figures are briefly described at the bottom of the graphic next to the figure number.



Figure 4.2.4.1.2 – Proportionality of grading criteria per type of training session





Figure 4.2.4.1.3 – Comparing the Non Conforming Grades (NCGs) distributions of maneuver validation exercises for generation 3 versus generation 4 pilot crewmembers in Initial Qualification (IQ) along with weighted averages



Figure 4.2.4.1.3a – Comparing the Non Conforming Grades (NCGs) distributions of maneuver validation exercises for generation 3 versus generation 4 pilot crewmembers in Continuing Qualification (CQ) along with weighted averages



Figure 4.2.4.1.5 – Comparison of the trending of NCGs percentages for generation 3 versus generation 4 crewmembers in the training progression from the first assessment of IQ to annual assessments in line operations







Figure 4.2.4.1.5c – Comparing the Non Conforming Grades (NCGs) distributions of Operational Evaluation 1st Flight (OE) by phase of flight for generation 3 versus generation 4 pilot crewmembers in Initial Qualification (IQ)



Figure 4.2.4.1.5b – Comparing the Non Conforming Grades (NCGs) in Operational Evaluation Certification for phases of flight Ground Operations and Cruise for generation 3 versus generation 4 pilot crewmembers in final assessment of Initial Qualification (IQ)



Figure 4.2.4.1.6a – Comparing the Non Conforming Grades (NCGs) in Operational Evaluation Continuing Qualification (IQ) (i.e. Line Checks) by phases of flight for generation 3 versus generation 4



Figure 4.2.4.1.6 – Comparing the Non Conforming Grades (NCGs) distributions of Line Operational Evaluation (LOE) exercises for generation 3 versus generation 4 pilot crewmembers in Initial Qualification (IQ)

ΙΔΤΔ



Figure 4.2.4.1.7 d – Comparing the Non Conforming Grades (NCGs) distributions of Line Operational Evaluation (LOE) by phase of flight for generation 3 versus generation 4 pilot crewmembers in Initial Qualification (IQ)



Figure 4.2.4.1.7a – Comparing percentages of NCGs by type/generation in annual line assessments (Line Checks)

# APPENDIX 10 Atqp study

# INTRODUCTION

This appendix provides the, generational results in graphical format of generation 3 and 4 aircraft the deidentified study was done and provided by the ATQP airline. The figures are briefly described at the bottom of the graphic next to the figure number



Figure 4.2.4.2.3 – Grading criteria percentage rates for NCGs with respect to the maneuver – Engine Failure at/after V1 – during Recurrent Training for all aircraft types over 1 year cycle

Note: These criteria map into the Competencies (i.e. they are a subset)



Figure 4.2.4.2.3a – Grading criteria percentage rates for NCGs with respect to the maneuver – Non-precision Approach – during Recurrent Training for all aircraft types over 1 year cycle







Figure A10. – Grading criteria percentage rates for failure on first attempt with respect to the maneuver – Engine out Go-around – during Recurrent Training for all aircraft types over 1 year cycle



Figure A10.2 – Grading criteria percentage rates for Pass but with a repeat pertaining to the maneuver – Engine Failure at/after V1 – during Recurrent Training for all aircraft types over 1 year cycle

Ð

Distribution of GA Altitudes by initiation Altitude N = 333



Figure 4.2.4.2.5 – Distribution of Go-around initiation heights above the runway threshold as reported by pilots during a two-year interval during ATQP implementation



# APPENDIX 11 TRAINING CRITICALITY SURVEY (TCS)

# INTRODUCTION

This appendix contains the data and analysis of the TCS. The correlations are shown here, but only a cursory analysis of generation 4 was done as a small example of the potential of the technique. None of the results were used in the overall EBT analysis and conclusions because the data sample was felt to be less than sufficient in terms of size and symmetry. That being the case, the method is very powerful and the technique and data collection will be improved to be an important part of future EBT analysis in the future.

# 11.1 LOGISTICAL AND GENERAL DATA PROVIDED BY EVALUATION PILOTS ON SURVEY FORMS

ID Eval Pilot	Organisation	Operation	Aircraft	Region	Date Survey Processed
836	Qantas	short/medium range	B737 600-800	Australia /Pacific	25-May-11
837	Unknown	short/medium range	A320 FAM	Europe	25-May-11
838	British Airways	longrange	B767	Worldwide	25-May-11
839	WIZZAIR	AIRLINE	A-320	Europe	25-May-11
840	TRTO	short/medium range	CE 550B, CE 560XL/XLS	Worldwide	25-May-11
841	Twinjet Aircraft Ltd	longrange	A320 FAM	Worldwide	25-May-11
842	Air Transat	longrange	A330	Worldwide	25-May-11
843	AIR FRANCE	longrange	A330	Worldwide	25-May-11
844	Aire France	longrange	A380	Worldwide	25-May-11
845	Qatar Airways	longrange	B777	Worldwide	25-May-11
846	EMIRATES (EK)	longrange	A380	Worldwide	25-May-11
847	ANA	short/medium range	B737 300-500	Asia	25-May-11
848	Flight Safety	commuter	Cessna Mustang	Worldwide	25-May-11
849	TRTO	commuter	CE-550B	Europe	25-May-11
850	Flightsafety International	short/medium range	Hawker 800	Europe	25-May-11
851	TRTO	short/medium range	Gulfstream GV	Worldwide	25-May-11
852	Qatar Airways	short/medium range	A320 FAM	Worldwide	25-May-11
853	Emirates	longrange	A330	Worldwide	25-May-11
854	Wizz Air	short/medium range	A320 FAM	Europe	25-May-11
855	EMIRATES AIRLINES	longrange	A330	Worldwide	25-May-11
856	FlightSafety International, Inc.	Training	DA-2000	North America	25-May-11
857	TRTO	commuter	CE560XL	Europe	25-May-11
858	FlightSafety International	longrange	Falcon 900EX	Worldwide	25-May-11
859	FSI	Unknown	C-680/ DHC 8/ Be40	Worldwide	25-May-11
860	FlightSafety Intl	short/medium range	Falcon 2000	Worldwide	25-May-11
861	FlightSafety International	short/medium range	CE525A, B, C	Worldwide	25-May-11
862	FlightSafety International	short/medium range	CE560XLS	Worldwide	25-May-11
863	FlightSafety International	longrange	CE750	Worldwide	25-May-11
864	FlightSafety International	short/medium range	CE560	Worldwide	25-May-11

865	FlightSafety	Traning	Simulators	North America	25-May-11
866	Flight Safety Int KTEB	Training	2000EX EASy	Worldwide	25-May-11
867	FlightSafety	short/medium range	Hawker 850	Europe	25-May-11
868	Emirates Airline	longrange	B777	Worldwide	25-May-11
869	AIRBUS TRAINING	short/medium range	A320 FAM	Worldwide	25-May-11
870	Air France	longrange	B777	Worldwide	25-May-11
871	QATAR AIRWAYS	longrange	A330	Worldwide	25-May-11
872	FlightSafety International	longrange	Gulfstream 450	Worldwide	25-May-11
873	British Airways	short/medium range	B737 300-500	Europe	25-May-11
874	Qatar Airways	freight	A300-600	Worldwide	25-May-11
875	Emirates Airlines	short/medium range	A330	Worldwide	25-May-11
876	LFT	longrange	A340 200/300	Worldwide	25-May-11
877	DLH	short/medium range	B737 300-500	Europe	25-May-11
878	FlightSafety International	short/medium range	ERJ-170/190	Worldwide	25-May-11
879	AIRBUS	short/medium range	A330	Worldwide	25-May-11
880	Lufthansa Flight Training	longrange	A340-300+600/A330- 300	Worldwide	25-May-11
881	FlightSafety International	longrange	Gulfstream 450	Worldwide	25-May-11
882	British Airways	short/medium range	B737 300-500	Europe	25-May-11
883	British Airways	short/medium range	A320 FAM	Europe	25-May-11
884	Airbus Training	short/medium range	A320 FAM	Asia	25-May-11
885	Emirates Airline	short/medium range	A340 MFF200-600	Worldwide	25-May-11
886	British Airways	longrange	B777	Worldwide	25-May-11
887	IFALPA- SNPL	longrange	B777	Worldwide	25-May-11
888	qatar airways	longrange	B777	Worldwide	25-May-11
889	BRITISH AIRWAYS	longrange	B747-400	Worldwide	25-May-11
890	Wizz Air	short/medium range	A320 FAM	Europe	25-May-11
891	Qantas	short/medium range	B737 600-800	Australia/Pac ific	25-May-11
892	Lufthansa Flight Training	short/medium range	A320 FAM,A330,340	Worldwide	25-May-11
893	Emirates	longrange	B777	Worldwide	25-May-11
894	Emirates	longrange	B777	Worldwide	25-May-11
895	Qatar Airways	freight	A300-600	Worldwide	25-May-11

ΔΤΔ

Figure A11.1 cont.



896	British Airways	longrange	B777	Worldwide	25-May-11
897	Qatar Airways	short/medium range	A320 FAM	Worldwide	25-May-11
898	AIR FRANCE	short/medium range	A320 FAM	Worldwide	25-May-11
899	Qantas	longrange	B747-400	Worldwide	25-May-11
900	Wzzair	short/medium range	A320 FAM	Europe	25-May-11
901	Air Transat, Canada	longrange	A310	Worldwide	25-May-11
902	Emirates	longrange	B777	Worldwide	25-May-11
903	Qatar Airways	freight	A300-600	Worldwide	25-May-11
904	Unknown	short/medium range	A320 FAM	Europe	25-May-11
905	Wizz-Air	short/medium range	A320 FAM	Europe	25-May-11
906	GULFAIR	short/medium range	A330	Worldwide	25-May-11
907	Qatar Airways	short/medium range	A320 FAM	Worldwide	25-May-11
908	Airbus Training	short/medium range	A320 FAM	Worldwide	25-May-11
909	Qatar Airways	freight	A300-600	Asia	25-May-11
910	Emirates	longrange	A330	Worldwide	25-May-11
911	WIZZAIR	short/medium range	A320 FAM	Europe	25-May-11
912	Emirates Airline	longrange	A380	Worldwide	25-May-11
913	TUIfly GmbH	short/medium range	B737 600-800	Europe	25-May-11
914	Emirates Airline	longrange	A330	Worldwide	25-May-11
915	Air France	longrange	B777	Worldwide	25-May-11
916	WiZZ AIR Airlines	short/medium range	A320 FAM	Europe	25-May-11
917	GULFAIR	short/medium range	A330	Worldwide	25-May-11
918	Qatar Airways	longrange	B777	Worldwide	25-May-11
919	Air France	short/medium range	A320 FAM	Worldwide	25-May-11
920	Cathay Pacific Airways	short/medium range	B747-400	Worldwide	25-May-11
921	Cathay Pacific Airways	short/medium range	A330	Asia	25-May-11
922	Various	longrange	A330	Worldwide	25-May-11
923	Airbus Training Toulouse	short/medium/long	A320/330/340families	Worldwide	25-May-11
924	Airline	short/medium range	A320 FAM	Europe	25-May-11
925	Delta Air Lines	longrange	B767	Worldwide	25-May-11
926	qatarairways	short/medium range	A330	Worldwide	25-May-11

Figure A11.1 cont.



6		short/medium	İ	1	
927	Cathay Pacific	range	A330	Asia	25-May-11
928	Cathay Pacific Airways	short/medium range	A330/A340	Worldwide	25-May-11
929	Cathay Pacific	short/medium range	A330	Worldwide	25-May-11
930	Wizz Air	short/medium range	A320 FAM	Europe	25-May-11
931	Emirates	longrange	B777	Worldwide	25-May-11
932	WIZZAIR	short/medium range	A320 FAM	Europe	25-May-11
933	Qatar Airways	freight	A300-600	Worldwide	25-May-11
934	EK	short/medium range	B777	Worldwide	25-May-11
935	Wizz Air	short/medium range	A320 FAM	Europe	25-May-11
936	Cathay Pacific Airways	longrange	B777	Worldwide	25-May-11
937	Air Transat	longrange	A330	Worldwide	25-May-11
938	Cathay Pacific Airways	longrange	B747-400	Worldwide	25-May-11
939	Delta Airlines	longrange	B757	Worldwide	25-May-11
940	Delta Air Lines	longrange	B777	Worldwide	25-May-11
941	Lufthansa	longrange	B747-400	Worldwide	25-May-11
942	Emirates Airline	longrange	A340 MFF200-600	Worldwide	25-May-11
943	Emirates Airline	short/medium range	A330	Worldwide	25-May-11
944	Qatar Airways	freight	A300-600	Worldwide	25-May-11
945	QATAR AIRWAYS	short/medium range	A320 FAM	Worldwide	25-May-11
946	GULFAIR	short/medium range	A330	Worldwide	25-May-11
947	Cathay Pacific Airways	longrange	B777	Worldwide	25-May-11
948	Axis Airways	short/medium range	B737 300-500	Worldwide	25-May-11
949	WizzAir	short/medium range	A320 FAM	Europe	25-May-11
950	Emirates Airline	longrange	A380	Worldwide	25-May-11
951	Anonymous	short/medium range	B737 600-800	Europe	25-May-11
952	Airline	short/medium range	A320 FAM	Europe	25-May-11
953	Emirates	longrange	B777	Worldwide	25-May-11
954	Qatar Airways	freight	A300-600	Worldwide	25-May-11
955	Unknown	Enter/Select type	Enter/Select type	Select region	25-May-11
956	Unknown	Enter/Select type	Enter/Select type	Select region	25-May-11
957	FlightSafety	short/medium range	G450	Worldwide	25-May-11
958	LFT	longrange	B747-400	Worldwide	25-May-11


-					
959	Lufthansa Flight Training	short-long	A320/A330/A340	Worldwide	25-May-11
960	Lufthansa	longrange	A340 200/300	Worldwide	25-May-11
961	Austrian Airlines	short/medium range	MD80	Europe	25-May-11
962	FlightSafety International	short/medium range	CE510 Mustang	Worldwide	25-May-11
963	AIR FRANCE	short/medium range	A320 FAM	Europe	25-May-11
964	AIR FRANCE	short/medium range	A320 FAM	Europe	25-May-11
965	FlightSafety International	longrange	Gulfstream 450	Worldwide	25-May-11
966	TRTO	short/medium range	Hawker 400	Europe	25-May-11
967	QATAR AIRWAYS	short/medium range	A320 FAM	Worldwide	25-May-11
968	Qatar Airways	short/medium range	A320 FAM	Worldwide	25-May-11
969	Qatar Airways	longrange	B777	Worldwide	25-May-11
970	Qatar Airways	freight	A300-600	Worldwide	25-May-11
971	Qatar Airways	longrange	B777	Worldwide	25-May-11
972	Qatar Airways	short/medium range	A320 FAM	Worldwide	25-May-11
973	Qatar Airways	short/medium range	A320 FAM	Worldwide	25-May-11
974	Qatar Airways	longrange	A330	Worldwide	25-May-11
975	Qatar Airways	short/medium range	A320 FAM	Worldwide	25-May-11
976	Qatar Airways	short/medium range	A320 FAM	Worldwide	25-May-11
977	Qatar Airways	longrange	B777	Worldwide	25-May-11
978	Qatar Airways	short/medium range	A330	Worldwide	25-May-11
979	Qatar Airways	freight	A300-600	Worldwide	25-May-11
980	easyJet Oxford Aviation Academy	short/medium range	A320 FAM	Europe	25-May-11
981	STL FlightSafety International	short/medium range	EMB 170 190	North America	25-May-11
982	STL FlightSafety International	short/medium range	EMB 170 190	North America	25-May-11
983	AIRBUS training	short and long	AII AIRBUS FBW	Worldwide	25-May-11
984	Qatar Airways	longrange	A330	Worldwide	25-May-11
985	WIZZ AIR	short/medium range	A320 FAM	Europe	25-May-11
986	Emirates Airline	short/medium range	A330	Worldwide	25-May-11
987	QatarAirways	freight	A300	Worldwide	25-May-11
988	QANTAS	longrange	B747-400	Worldwide	25-May-11
989	ALPA-Japan	short/medium range	A320 FAM	Asia	25-May-11



0					
990	FlightSafety	short/medium range	Falcon 900EX EASy	Worldwide	25-May-11
991	AIRBUS	short/medium range	A320 FAM	Worldwide	25-May-11
992	British Airways	short/medium range	B767	Worldwide	25-May-11
993	Etihad Airways	longrange	A340 500/600	Worldwide	25-May-11
994	TRTO	short/medium range	CE 680	Europe	25-May-11
995	FlightSafety International	Part 142 Training Center	L-1329 Lockheed JetStar	North America	25-May-11
996	FSI Savannah	longrange	GIV	Worldwide	25-May-11
997	British Airways	longrange	B747-400	Worldwide	25-May-11
998	Emirates	longrange	B777	Worldwide	25-May-11
999	Qatar Airways	longrange	A330	Worldwide	25-May-11
1000	Air Transat	longrange	A330	Worldwide	25-May-11
1001	British Airways plc	short/medium range	A320 FAM	Europe	25-May-11
1002	British Airways	longrange	B747-400	Worldwide	25-May-11

Figure A11.1 cont.

## 11.2 PAGE 1 OF TRAINING CRITICALITY SURVEY (TCS) COMPLETED BY QUALIFIED VOLUNTEER PILOTS DENOTING THREATS AND ERRORS IN ALL PHASES OF FLIGHT (PHASE Φ)

D Organisation	XYZ Airline				Likelihood					
Aircraft Type	B777-200ER				The probability that over the course of one year a pilot will experience a defined event, requiring intervention to ensure a safe outcome. 1. Rare - once in career or less					
Type of Operation	Long Haul, O	verwater Interr	national							
Area of Operation	De-identified									
	Likelihood	Severity	Training	Result	3. Moderate - once every 3-5 years					
Unique Aircraft elements and characteristics	1	1	1	1	4. Likely - probably once a year 5. Almost Certain - more than once a year					
Deficiency within Manuals	2	2	2	8						
Deficiency within Charts (design & error)	2	2	2	8	]					
Deficiency within Database (design & error)	2	2	2	8	Severity					
Deficiency within Checklists	2	1	1	2	The most likely outcome given that the event has occurred for a pilot not					
Incapacitation	1	3	3	9	trained to manage that defined event	Τ̈́				
Compliance failure	3	3	3	27	1. Negligible – insignificant effect not compromising safety	Ũ				
Miss handling Aircraft including unstable approach	3	3	3	27	2. Minor – reduction in safety margin 3. Moderate – safety compromise	AT S				
Loading/fuel/Performance	2	2	3	12	4. Major – aircraft damage and/or personal injury	0,				
Workload/ distraction/ pressure	5	3	3	45						
Fatigue	5	3	1	15						
Procedures	2	2	1	4	Training Benefit					
Crew issues	1	2	2	4	Consider the effect of training to reduce the severity by one level, e.g. the					
Terrorism	1	2	2	4	most likely result of an engine failure during take off is catastrophic at least					
Physiological	2	2	2	8	1. Unimportant – training has no impact					
CRM (poor) inc. Communications	5	2	3	30	2. Minor - enhances performance in managing an event     3. Moderate – having no training compromises safety					
Black Swan	2	3	1	6	<ol> <li>Significant – Safe outcome is unlikely without effective training</li> <li>Critical – essential to understanding and coping with the event</li> </ol>					
						L				

Figure A11.2



•

# 11.3 PAGE 2 OF TRAINING CRITICALITY SURVEY (TCS) DENOTING THREATS AND ERRORS IN GROUND AND PREFLIGHT FLIGHT PHASES

Organisation	XYZ Airlines				Likelihood The probability that over the course of one year a pilot will experience a defined event, requiring intervention to ensure a safe outcome. 1. Rare - once in career or less			
Aircraft Type	B777-200ER							
Type of Operation	Long Haul, Ov	verwater Interr	national					
Area of Operation	De-identified							
	Likelihood	Severity	Training	Result	3. Moderate - once every 3-5 years			
Ground equipment	3	2	2	12	<ol> <li>Likely - probably once a year</li> <li>Almost Certain - more than once a year</li> </ol>			
Ground manoeuvring	3	3	3	27				
Runway/Taxi condition	5	4	5	100		<b>P</b> R		
Adverse Weather/Ice	5	4	5	100	Severity	Q		
Crosswind	5	4	5	100	The most likely outcome given that the event has occurred for a pilot not			
ATC	3	3	2	18	trained to manage that defined event			
NAV	2	2	2	8	1. Negligible – insignificant effect not compromising safety	Ū		
Loss of comms	2	2	1	4	2. Minor – reduction in safety margin			
Traffic	3	4	5	60	4. Major – aircraft damage and/or personal injury	Ш		
R/W incursion	1	4	4	16	5. Catastrophic - significant damage or hull loss	ا صا		
Poor Visibility	5	3	5	75		Ë		
Terrain	1	5	6	30	Training Benefit			
Birds	1	1	1	1	Consider the effect of training to reduce the severity by one level e.g. the			
Eng Fail	1	1	1	1	most likely result of an engine failure during take off is catastrophic at least			
MEL	5	1	2	10	1. Unimportant – training has no impact			
Fire	1	4	5	20	2. Minor - enhances performance in managing an event			
System malfunction	3	2	3	18	<ul> <li>4. Significant – Safe outcome is unlikely without effective training</li> <li>5. Critical – essential to understanding and coping with the event</li> </ul>			

Figure A11.3

ΙΑΤΑ

0

## 11.4 PAGE 3 OF TRAINING CRITICALITY SURVEY (TCS) DENOTING THREATS AND ERRORS IN TAKE-OFF FLIGHT PHASE

Organisation	XZY Airlines				Likelihood					
organisation	B777-200FR									
Aircraft Type		convetor Interr	otional		The probability that over the course of one year a pilot will experience a defined event, requiring intervention to ensure a safe outcome.					
Type of Operation	Long Haul, O	verwater interr	alional							
Area of Operation	De-identified				1. Rare - once in career or less 2. Unlikely - few times in career					
	Likelihood	Severity	Training	Result	3. Moderate - once every 3-5 years					
Windshear	1	4	5	20	4. Likely - probably once a year 5. Almost Certain - more than once a year					
Adverse Weather/Ice	5	4	4	80						
Crosswind	5	4	3	60						
ATC	3	3	2	18	Severity					
NAV	2	2	2	8	The most likely outcome given that the event has occurred for a pilot	H				
Loss of comms	3	2	2	12	not trained to manage that defined event	Ŗ				
Traffic	3	4	5	60	1. Negligible – insignificant effect not compromising safety	Π				
R/W incursion	1	3	3	9	2. Minor – reduction in safety margin	Ч				
Poor Visibility	5	3	4	60	4. Major – aircraft damage and/or personal injury	П				
Wake vortex	2	3	2	12	5. Catastrophic - significant damage or hull loss					
Upset	1	4	4	16						
Terrain	1	5	5	25	Training Benefit					
Birds	1	4	4	16	Consider the effect of training to reduce the severity by one level, e.g.					
Eng Fail	1	4	5	20	at least in a conventional aircraft. Effective training reduces this					
MEL	5	1	2	10	severity to major.					
Fire	1	4	5	20	2. Minor - enhances performance in managing an event					
System malfunction	3	2	3	18	3. Moderate – naving no training compromises safety 4. Significant – Safe outcome is unlikely without effective training 5. Critical – occontral to understanding and contrary with the current 6. Critical					
					To childar – essential to understanding and coping with the event	1				

Figure A11.4



۰

# 11.5 PAGE 4 OF TRAINING CRITICALITY SURVEY (TCS) DENOTING THREATS AND ERRORS IN CLIMB FLIGHT PHASE

Organisation	XYZ Airlines				Likelihood The probability that over the course of one year a pilot will experience a defined event, requiring intervention to ensure a safe outcome				
Aircraft Type	B777-200ER								
Type of Operation	Long Haul, Ov	verwater Interr	national						
Area of Operation	De-identified				A demee vent, requiring intervention to ensure a sale outcome.     A nare - once in career or less     Unlikely - few times in career     Moderate - once every 3-5 years     Likely - probably once a year     Likely - probably once a year				
	Likelihood	Severity	Training	Result					
Windshear	1	4	5	20					
Adverse Weather/Ice	5	4	4	80					
ATC	3	3	2	18	]				
NAV	AV 2 2 2 8		8	Severity					
Loss of comms	3 2	2	2	12	The most likely outcome given that the event has occurred for a nilot				
Traffic	3	4	5	60	not trained to manage that defined event	2			
Poor Visibility	5	3	4 60 1. Negligible – insignificant effect not compr		1. Negligible – insignificant effect not compromising safety	∣╞			
Wake vortex	2	3	2	12	2. Minor – reduction in safety margin 3. Moderate – safety compromise	B			
Upset	1	4	5	20	4. Major – aircraft damage and/or personal injury				
Terrain	1	5	5	25	<ol> <li>Catastrophic - significant damage or hull loss</li> </ol>				
Birds	1	4	4	16					
Eng Fail	1	4	5	20	Training Benefit				
MEL	5	1	2	10	Consider the effect of training to reduce the severity by one level, e.g.				
Fire	1	4	5	20	the most likely result of an engine failure during take off is catastrophic at least in a conventional aircraft. Effective training reduces this				
System malfunction	3	2	3	18	severity to major.				
					2. Minor - enhances performance in managing an event				
				3. Moderate – having no training compromises safety 4. Significant – Safe outcome is unlikely without effective training					
					5. Critical – essential to understanding and coping with the event				

Figure A11.5

## 11.6 PAGE 5 OF TRAINING CRITICALITY SURVEY (TCS) DENOTING THREATS AND ERRORS IN CRUISE FLIGHT PHASE

Organisation	XYZ Airlines				Likelihood				
Aircraft Type	B777-200ER				The probability that over the course of one year a pilot will				
Type of Operation	Long Haul, Ov	verwater Interr	national		<ul> <li>experience a defined event, requiring intervention to ensure a safe outcome.</li> <li>1. Rare - once in career or less</li> <li>2. Unlikely - few times in career</li> <li>3. Moderate, once event 3.5 years</li> </ul>				
Area of Operation	De-identified								
	Likelihood	kelihood Severity	Training	Result					
Windshear	1	4	5	20	4. Likely - probably once a year				
Adverse Weather/Ice	5	3	3	45	5. Almost Certain - more than once a year				
ATC	3	2	2	12					
NAV	2	2	2	8	Severity				
Loss of comms	3	2	2	12	The most likely outcome given that the event has occurred for a pile				
Traffic	3	4	5	60	not trained to manage that defined event	Ж			
Poor Visibility	5	2	3	30	1. Negligible – insignificant effect not compromising safety	$\subseteq$			
Wake vortex	3	2	2	12	2. Minor – reduction in safety margin 3. Moderate – safety compromise	SE SE			
Upset	1	3	4	12	4. Major – aircraft damage and/or personal injury				
Terrain	1	5	5	25	5. Catastrophic - significant damage or hull loss				
Birds	1	4	4	16					
Eng Fail	1	4	5	20	Training Benefit				
MEL	5	1	2	10	Consider the effect of training to reduce the severity by one level,				
Fire	1	4	5	20	e.g. the most likely result of an engine failure during take off is catastrophic at least in a conventional aircraft. Effective training				
System malfunction	3	2	3	18	reduces this severity to major.				
					2. Minor - enhances performance in managing an event				
					<ol> <li>Moderate – having no training compromises safety</li> <li>Significant – Safe outcome is unlikely without effective training</li> </ol>				
					5. Critical – essential to understanding and coping with the event				

Figure A11.6

0



۰

# 11.7 PAGE 6 OF TRAINING CRITICALITY SURVEY (TCS) DENOTING THREATS AND ERRORS IN DESCENT FLIGHT PHASE

Organisation	XYZ Airlines				Likelihood				
Aircraft Type	B777-200ER				The probability that over the course of one year a pilot will				
Type of Operation	Long Haul, Ov	verwater Intern	national		A specific contract of the course of one year a pilot will     experience a defined event, requiring intervention to ensure a safe     outcome.     A sare - once in career or less     Moderate - once every 3-5 years     A. Likely - probably once a year				
Area of Operation	De-identified								
	Likelihood	Severity	Training 5	Result					
Windshear	1 5	3 3		15					
Adverse Weather/Ice			3	45	5. Almost Certain - more than once a year				
ATC	3	3	3	27					
NAV	NAV 2 2 2 8		8	Severity					
Loss of comms 3		2	2	12	The most likely outcome given that the event has occurred for a pilot				
Traffic	3	4	5	60	not trained to manage that defined event	Э С			
Poor Visibility	Poor Visibility 5 2 3 30 1. Negligible – insignificant effe		<ul> <li>1. Negligible – insignificant effect not compromising safety</li> </ul>	Ĩ					
Wake vortex	3	2	2	12	2. Minor – reduction in safety margin				
Upset	1	3	4	12	4. Major – aircraft damage and/or personal injury				
Terrain	1	5	5	25	5. Catastrophic - significant damage or hull loss				
Birds	1	4	4	16					
Eng Fail	1	4	5	20	Training Benefit				
MEL	5	1	2	10	Consider the effect of training to reduce the severity by one level,				
Fire	1	4	4	16	e.g. the most likely result of an engine failure during take off is catastrophic at least in a conventional aircraft. Effective training				
System malfunction	3	3 2 3		18	reduces this severity to major.				
					2. Minor - enhances performance in managing an event				
			3. Moderate – having no training compromises safety     4. Significant – Safe outcome is unlikely without effective training						
					5. Critical – essential to understanding and coping with the event				

Figure A11.7

## 11.8 PAGE 7 OF TRAINING CRITICALITY SURVEY (TCS) DENOTING THREATS AND ERRORS IN APPROACH FLIGHT PHASE

Organisation	XYZ Airlines				Likelihood				
Aircraft Type	B777-200ER				The probability that over the course of one year a pilot will experience a defined event requiring intervention to ensure a safe outcome				
Type of Operation	Long Haul, Ov	verwater Interr	national						
Area of Operation	De-identified				1. Rare - once in career or less				
	Likelihood	Severity	Training	Result	2. Onlinely - lew limes in career 3. Moderate - once every 3-5 years				
Windshear	2	3	5	30	4. Likely - probably once a year 5. Almost Certain - more than once a year				
Adverse Weather/Ice	5	3	3	45		≥			
Crosswind	5	2	5	50		P			
ATC	3	3	3	27	Severity	R O O			
NAV	2	3	3	18	The most likely outcome given that the event has occurred for a nilot	Ř			
Loss of comms	3	3	3	27	not trained to manage that defined event	Ξ			
Traffic	2	3	5	30	1. Negligible – insignificant effect not compromising safety	8			
R/W incursion	1	4	5	20	2. Minor – reduction in safety margin 3. Moderate – safety compromise	Ö			
Poor Visibility	5	3	4	60	4. Major – aircraft damage and/or personal injury	₽			
Wake vortex	3	3	3	27	5. Catastrophic - significant damage or hull loss	õ			
Upset	1	5	5	25	7	١Ę			
Terrain	1	5	5	25	Training Benefit				
Birds	1	4	4	16	Consider the effect of training to reduce the severity by one level, e.g.				
Eng Fail	1	4	5	20	the most likely result of an engine failure during take off is catastrophic at least in a conventional aircraft. Effective training				
MEL	5	1	2	10	reduces this severity to major.				
Fire	1	4	4	16	2. Minor - enhances performance in managing an event				
System malfunction	3	2	3	18	Moderate – having no training compromises safety     Significant – Safe outcome is unlikely without effective training     Section 2.2 State of the section of the sec				
					5. Critical – essential to understanding and coping with the event				

Figure A11.8

0



۰

## 11.9 PAGE 8 OF TRAINING CRITICALITY SURVEY (TCS) DENOTING THREATS AND ERRORS IN THE LANDING FLIGHT PHASE

Organisation	XYZ Airlines				Likelihood				
Aircraft Type	B777-200ER				The probability that ever the source of one year a pilot will				
Type of Operation	Long Haul, Ov	verwater Interr	national		In the probability that over the course of one year a pliot will     experience a defined event, requiring intervention to ensure a safe     outcome.     I. Rare - once in career or less     Unlikely - few times in career     Moderate - once every 3-5 years				
Area of Operation	De-identified								
	Likelihood	Severity	Training	Result					
Windshear	2	4	5	40	4. Likely - probably once a year				
Adverse Weather/Ice	5	3	3	45	5. Almost Certain - more than once a year				
Crosswind	5	3	5	75					
ATC	3	3	3	27	Severity				
NAV	2	3	3	18	The most likely outcome given that the event has occurred for a nilot				
Loss of comms	3	3	3	27	not trained to manage that defined event	Þ			
Traffic	2	4	5	40	<ul> <li>1. Negligible – insignificant effect not compromising safety</li> </ul>				
R/W incursion	1	4	5	20	2. Minor – reduction in safety margin 3. Moderate – safety compromise	Z			
Poor Visibility	5	3	4	60	4. Major – aircraft damage and/or personal injury	<b>U</b> ,			
Wake vortex	3	3	3	27	5. Catastrophic - significant damage or hull loss				
Upset	1	5	5	25					
Terrain	1	1	1	1	Training Benefit				
Birds	1	2	2	4	Consider the effect of training to reduce the severity by one level,				
Eng Fail	1	3	3	9	e.g. the most likely result of an engine failure during take off is catastrophic at least in a conventional aircraft. Effective training				
MEL	1	1	1	1	reduces this severity to major.				
Fire	Fire 1 4 4 16		16	2. Minor - enhances performance in managing an event					
System malfunction	1	1	1	1	Moderate – having no training compromises safety     Significant – Safe outcome is unlikely without effective training     Critical – essential to understanding and coping with the event				

Figure A11.9

0

## 11.10 PAGE 9 OF TRAINING CRITICALITY SURVEY (TCS) DENOTING THREATS AND ERRORS IN AFTER LANDING AND POSTFLIGHT FLIGHT PHASE

Organisation	XYZ Airlines				Likelihood				
Aircraft Type	B777-200ER								
Type of Operation	Long Haul, Ov	verwater Intern	national						
Area of Operation	De-identified				A defined event, requiring intervention to ensure a safe outcome.     A nare - once in career or less     Unlikely - few times in career     Moderate - once every 3-5 years				
	Likelihood	Severity	Training	Result					
Ground equipment	1	2	2	4	4. Likely - probably once a year 5. Almost Certain - more than once a year				
Ground manoeuvring	1	2	2	4					
Runway/Taxi condition	5	2	3	30		Π			
Windshear	1	1	1	1	Severity				
Adverse Weather/Ice	5	3	4	60	The most likely outcome given that the event has occurred for a nilot	ANDI			
Crosswind	1	1	1	1	not trained to manage that defined event				
ATC	2	2	2 8 1. Negligible – insignificant effect not compromis		1. Negligible – insignificant effect not compromising safety	S			
NAV	1	1 1	1	<ol> <li>Minor – reduction in safety margin</li> <li>Moderate – safety compromise</li> </ol>	2. Minor – reduction in safety margin	Q			
Loss of comms	2	1	1	2	4. Major – aircraft damage and/or personal injury	P			
Traffic	2	2	2	8	5. Catastrophic - significant damage or hull loss	Š			
R/W incursion	2	4	1	8					
Poor Visibility	5	3	3	45	Training Benefit				
Terrain	1	1	1	1	Consider the effect of training to reduce the severity by one level, e.g.	Ľ			
Birds	1	1	1	1	the most likely result of an engine failure during take off is catastrophic at least in a conventional aircraft. Effective training				
Eng Fail	1	1	1	1	reduces this severity to major.				
MEL	1	1	1	1	2. Minor - enhances performance in managing an event				
Fire	re 1 4 4 16		16	<ol> <li>Moderate – having no training compromises safety</li> <li>Significant – Safe outcome is unlikely without effective training</li> </ol>					
System malfunction	System malfunction 1 1 1 1		5. Critical – essential to understanding and coping with the event						

Figure A11.10



## 11.11 THE NUMBER OF RESPONSES PER EVALUATION PILOT FROM THE TOTAL OF 159 SURVEY QUESTIONS

Total Numbe	r of questions per	Average que	estions answered	Evaluation	Pilot Answered
5	survey	per	r survey	Pilot ID	Question Count
	159	147	.0060976	092	154
Evaluation Bilot ID	Pilot Answered	Evaluation Bilot ID	Pilot Answered	983	154
912	67	970	1/12	838	155
856	91	875	142	835	155
936	95	890	143	882	155
869	105	913	143	922	155
902	110	968	143	935	155
973	111	870	144	943	155
988	112	985	145	972	155
885	113	840	146	986	155
860	115	925	146	996	155
872	119	949	146	852	156
927	119	876	147	903	156
930	120	859	148	905	156
899	121	976	148	907	156
880	122	997	148	920	156
868	124	851	149	931	156
854	125	926	149	940	156
910	127	978	149	974	150
937	120	8/8	149	990	150
938	120	850	150	843	150
837	130	857	150	849	157
853	131	878	150	861	157
965	132	892	150	873	157
980	132	901	150	879	157
932	133	937	150	886	157
877	134	991	150	897	157
952	134	841	151	904	157
844	135	911	151	933	157
855	135	881	152	951	157
929	136	896	152	953	157
959	136	923	152	961	157
1001	137	960	152	966	157
977	137	993	152	967	157
919	139	908	153	995	157
903	139	914	153	1002	157
8/17	139	921	153	8/12	150
889	140	836	155	846	158
942	140	858	154	916	150
915	141	884	154	944	154
918	141	888	154	948	154
895	142	891	154	894	158
954	142	975	154	898	158

Figure A11.11



# 11.12 SURVEY QUESTIONS ANSWERED PER FACTOR

Factors	Reponses per factor
Adverse Weather/Ice	1230
ATC	1251
Birds	897
Cabin issues	148
Compliance failure	161
Dangerous goods	1174
Deficiency in Ops Data	148
Deficiency within Charts	156
Deficiency within Checklists	155
Deficiency within Database	153
Deficiency within Manuals	155
Eng Fail	1192
Fatigue	145
Fire	1206
Ground equipment	299
Ground manoeuvring	303
Human Factors and CRM	154
Loading/fuel/Performance	156
Loss of comms	1202
MEL	1214
Mishanded Aircraft	144
Mishandled Auto Flight Systems	157
Mismanaged Aircraft State	156
NAV	1212
Other Mishandled system	157
Physiological	149
Pilot Incapacitation	1218
Poor Visibility	1222
Procedures	151
R/W incursion	748
Runway/Taxi condition	463
System malfunction	1225
Terrain	755
Traffic	1200
Upset	910
Wake vortex	916
Wind	757
Windshear	920
Workload/ Distraction/ Pressure	150

Figure A11.12

## 11.13 SURVEY QUESTIONS ANSWERED PER FACTOR BY GENERATION PROVIDING INSIGHT INTO RELATIVE SIZE OF DATA SAMPLE BY GENERATION

Factoro	Res	ponses/F	actor
Factors	Gen 2	Gen 3	Gen 4
Adverse Weather/Ice	32	284	914
ATC	32	284	935
Birds	24	202	671
Cabin issues	4	35	109
Compliance failure	4	37	120
Dangerous goods	32	273	869
Deficiency in Ops Data	4	37	107
Deficiency within Charts	4	35	117
Deficiency within Checklists	4	36	115
Deficiency within Database	4	35	114
Deficiency within Manuals	4	36	115
Eng Fail	32	276	884
Fatigue	4	31	110
Fire	28	274	904
Ground equipment	4	69	226
Ground manoeuvring	8	70	225
Human Factors and CRM	4	35	115
Loading/fuel/Performance	4	33	119
Loss of comms	32	277	893
MEL	32	280	902
Mishanded Aircraft	4	33	107
Mishandled Auto Flight Systems	4	35	118
Mismanaged Aircraft State	4	35	117
NAV	32	275	905
Other Mishandled system	4	35	118
Physiological	4	35	110
Pilot Incapacitation	32	273	913
Poor Visibility	32	282	908
Procedures	4	35	112
R/W incursion	20	172	556
Runway/Taxi condition	12	103	348
System malfunction	32	286	907
Terrain	20	174	561
Traffic	32	282	886
Upset	24	207	679
Wake vortex	24	214	678
Wind	20	172	565
Windshear	24	213	683

Figure A11.13

# 11.14 THE ANALYSIS

The Methodology Chapter (refer to 3.12) discusses the technique, data and relevance of the Training Criticality Study. In the analysis section, the set of responses from the TCS regarding likelihood of occurrence and severity (risk) is compared and correlated to analogous parameters from the EBT accident-Incident study. (See Chapter 4 for the risk ranking of gen 4, 3 and 2 of the EBT accident-Incident study.)

The TSC analysis is performed in a matrix from left to right. in 4 (see figure fig 5.11.15 next page for the case for gen 3).

The  $2^{nd}$  column of the matrix denotes the sum of the risk ( $\Sigma$  risk) for each threat/error in the generation. The respondents of the Training Criticality Survey assessed the threat/error in terms of its components (likelihood and severity) according to their professional experience for each of the phases of flight for which the risk was relevant. The responses for all the surveys for the particular risk of each threat/error in the respective generation are then summed for a raw risk score and depicted in column 2. (See Chapter 3 Methodology (section 3.11.2) for the definitions and scales of risk, likelihood and severity.)

Not all the questions are answered in any survey, so the parameters in the next two columns are used to correct for this effect. A lack of response would indicate no risk, so that problem is addressed by weighting the sum of the scores. The column labeled *Ans. Count* (3<sup>rd</sup> column) shows the total number of responses for each item while the 4<sup>th</sup> column shows the total number of queries. By dividing the sum of the risk (2<sup>nd</sup> column) by the number of responses, (3<sup>rd</sup> column) times the total number of queries, (4<sup>th</sup> column), the corrected sum of the risk is obtained in 5<sup>th</sup> column.

In the survey, if threat and/or error were present in multiple phases it was considered to be in the in the  $\Phi$  phase (See the Methodology Chapter 3.11.1 for a description of the  $\Phi$  phase, where the risk was only assessed once as a way to shorten the survey. This provided a bias if the total risk of the flight is desired unless the threats/errors are multiplied by the number of phases in which they occur. In order to compensate for this bias all the threats in the  $\Phi$  phase were multiplied by the number of relevant phases for which the threat/error was relevant. The column  $\Phi$  phase depicts these particular phases of flight and the column labeled **X** Phases contains the numerical value for which the associated threats are relevant. By multiplying the values in **X** Phases times the Corrected  $\Sigma$  risk a corrected result was obtained and is depicted in column 10 labeled Corrected for phase.

The sum of all the risk per flight for a given generation resulting from the Training Criticality Study are ranked in descending order of risk as shown in the last amber highlighted column labeled **Rank Value**. The final ranking of the threats/errors themselves are shown in the 1<sup>st</sup> amber column in the ranking number is in the 2<sup>nd</sup> amber column. It is this ordering (array of numbers in the 2nd amber column labeled **Rank No#** that is correlated to the EBT Accident Incident risk ranking.

The columns that are highlighted in red show the risk data resulting from the EBT Accident-Incident Study (See fig 3.2.2.12, Chapter 3) for an example of a chart denoting the analysis producing the ranking of the factors analogous to the TCS threats/errors from the Accident-Incident study. The first red column, **Gen** [i] **Final Rank (Red)** shows the factors ranked by descending risk. The numbers in the 2<sup>nd</sup> red column correspond to the ranking positions in the (amber) TCS outcome but appear in the order of the (red) accident – Incident study. If the arrays were identical the correlation would be 1, If they were random, the correlation would be 0, and if they reversely correlated the correlation would be -1. So in a certain sense the closer the arrays are to each other the closer the correlation is to 1.



# 11.15 THE CORRELATIONS

#### 11.15.1 Generation 4

The correlation generation 4 Training Criticality Study (TCS) risk ranking to the EBT Accident-Incident Analysis is **0.583526383526384**.

See figure 5.11.15, which shows the ranking values by bar height (1 - 36) of each of the threats/errors from the TCS in the order (left to right of the EBT Accident-Incident Study). This depiction provides a graphical notion of the closeness of the ranking as the red line indicates how each threat/error in the TCS compares to its counterpart the other study. It is interesting to see where the risks match well but it is equally interesting to see where they differ as this shows the biases of each study. For example (See figure 5.11.15) the risk rank associated with Adverse WX, CRM, Compliance and Mismanaged A/C State from the TCS all are very close to the red line denoting the order of the accident-incident study. However, the pilot perception or risk reflected in the TCS regarding ATC and Fatigue are much greater than that resulting from the accident-incident study.

Accident-incident reports tend to be quite factual at recording factors that are concrete such as ATC but not so complete about documenting issues like fatigue, especially the older reports. Another example of source bias is the risk associated with birds. The Training Criticality Study was taken not so long after the ditching accident resulting from dual engine failure due to multiple bird ingestions. Perhaps the fact that birds have a much higher risk ranking resulting from the TCS (pilot responses) versus from the accident-incident analysis is that the bird factor was such a topical issue at the time of the survey.

Correlating the results of data sources such as was done in this report can be a powerful tool to provide perspective and insight into the results of the analyses. In addition to these attributes, all sources except the collective expertise of our flight crews are limited in terms of scope. While the perceptions of pilots are not always unbiased, they are open to almost any question.



e Gen	Σ risk	Ans count	s_b	Correcte d Σ risk	Gen 4 Amber Rank	Corrected Σ of risk	0 phase	x Phases	Corrected for phase	Gen 4 Final Rank (Amber)	Rank no#	Rank value	Gen 4 Final Rank (Red)	Rank no#	Rank value
4	10409	848	984	12078.4	Adverse Weather/Ice	12078.37	Cabin issues	1	12078.37	Adverse Weather/Ice	1	12078	Adverse Weather/Ice	1	36
4	8279	848	984	9606.76	ATC	9606.764	Compliance failure	1	9606.764	Mismanaged Aircraft State	2	11279	CRM	4	33
4	6673	848	984	7743.2	Poor Visibility	7743.198	Deficiency in Ops Data	1	7743.198	Compliance failure	3	10462	Compliance	3	34
4	6081	848	984	7056.25	Traffic	7056.255	Deficiency within Charts	1	7056.255	Human Factors and CRM	4	9997.8	Mis A/C State	2	35
4	5456	848	984	6331.02	Wind	6331.019	Deficiency within Checklists	1	6331.019	ATC	5	9606.8	Man handling	8	29
4	5334	848	984	6189.45	MEL	6189.453	Deficiency within Database	1	6189.453	Workload/ Distraction/ Pressure	6	9204.1	Runway/Taxi condition	24	13
4	5241	848	984	6081.54	System malfunction	6081.538	Deficiency within Manuals	1	6081.538	Poor Visibility	7	7743.2	Fire	21	16
4	4795	848	984	5564.01	Windshear	5564.009	Fatigue	1	5564.009	Mishanded Aircraft	8	7574.9	Syst mal	14	23
4	4527	848	984	5253.03	Birds	5253.028	Human Factors and CRM	1	5253.028	Fatigue	9	7100.8	Mis-Sys	10	27
4	4345	848	984	5041.84	Dangerous goods	5041.84	Loading/fuel/ Performance	0	0	Other Mishandled system	10	7045.8	Workload Distraction Pressure	6	31
4	4188	848	984	4859.66	Loss of comms	4859.66	Mishanded Aircraft	1	4859.66	Traffic	11	7056.3	Crosswind	12	25
4	4176	848	984	4845.74	Wake vortex	4845.736	Mishandled Auto Flight Systems	1	4845.736	Wind	12	6331	Poor Visibility	7	30
4	3930	848	984	4560.28	Fire	4560.283	Mismanaged Aircraft State	1	4560.283	MEL	13	6189.5	MEL	13	24
4	3504	848	984	4065.96	NAV	4065.962	Other Mishandled system	1	4065.962	System malfunction	14	6081.5	Physio	32	5
4	3396	848	984	3940.64	R/W incursion	3940.642	Physiological	1	3940.642	Windshear	15	5564	Terrain	28	9
4	3175	848	984	3684.2	Runway/Taxi condition	3684.198	Procedures	1	3684.198	Birds	16	5253	Eng Fail	29	8
4	3039	848	984	3526.39	Upset	3526.387	Workload/ Distraction/ Pressure	1	3526.387	Mishandled Auto Flight Systems	17	5221.7	ATC	5	32
4	2794	848	984	3242.09	Terrain	3242.094		1	3242.094	Loss of comms	18	4859.7	Traffic	11	26
4	2785	848	984	3231.65	Eng Fail	3231.651		1	3231.651	Wake vortex	19	4845.7	Cabin	33	4
4	2778	848	984	3223.53	Pilot Incapacitation	3223.528		1	3223.528	Procedures	20	4790	Def-Proc's	20	17
4	1666	848	984	1933.19	Ground manoeuvring	1933.189		1	1933.189	Fire	21	4560.3	R/W Incursion	23	14
4	1661	848	984	1927.39	Ground equipment	1927.387		1	1927.387	NAV	22	4066	Def-Ops data	31	6
4	1464	541	656	1775.2	Fatigue	1775.201		4	7100.806	R/W incursion	23	3940.6	Def-Chk lists	35	2

Figure A5.11.14 – Analysis of generation 4 aircraft from the TCS (Amber Study) with resultant ranking of factors in terms of risk and a correlation with the EBT Accident Study (Red Study) risk ranking of gen 4 aircraft.



_														
4	1322	848	984	1534.02	Workload/ Distraction/ Pressure	1534.019	6	9204.113	Runway/Taxi condition	24	3684.2	Mis-AFS	17	20
4	1215	848	984	1409.86	Mismanaged Aircraft State	1409.858	8	11278.87	Upset	25	3526.4	Birds	16	21
4	1127	848	984	1307.75	Compliance failure	1307.745	8	10461.96	Deficiency within Charts	26	3439.4	Upset	25	12
4	1125	848	984	1305.42	Mishandled Auto Flight Systems	1305.425	4	5221.698	Deficiency within Manuals	27	3430.1	Windshear	15	22
4	1110	848	984	1288.02	Loading/fuel/ Performance	1288.019	1	1288.019	Terrain	28	3242.1	Loss of comms	18	19
4	1077	848	984	1249.73	Human Factors and CRM	1249.726	8	9997.811	Eng Fail	29	3231.7	Def Manuals	27	10
4	816	848	984	946.868	Mishanded Aircraft	946.8679	8	7574.943	Pilot Incapacitation	30	3223.5	Fatique	9	28
4	759	848	984	880.726	Other Mishandled system	880.7264	8	7045.811	Deficiency in Ops Data	31	3211.9	LF.P	36	1
4	741	848	984	859.84	Deficiency within Charts	859.8396	4	3439.358	Physiological	32	3003.1	Def-Charts	26	11
4	739	848	984	857.519	within Manuals	857.5189	4	3430.075	Cabin issues	33	2863.8	Def-DBs	34	3
4	692	848	984	802.981	Deficiency in Ops Data	802.9811	4	3211.925	Deficiency within Database	34	2757.1	NAV	22	15
4	647	848	984	750.764	Physiological	750.7642	4	3003.057	Deficiency within Checklists	35	2659.6	Pilot Incap	30	7
4	617	848	984	715.953	Cabin issues	715.9528	4	2863.811	Loading/fuel/P erformance	36	1288	Wake Vortex	19	18
4	594	848	984	689.264	Deficiency within Database	689.2642	4	2757.057	Ground manoeuvring		1933.2	Removed GRD because of q bias		
4	573	848	984	664.896	Deficiency within Checklists	664.8962	4	2659.585	Ground equipment		1927.4	Removed D.G. because of NTSB db bias		
4	516	848	984	598.755	Procedures	598.7547	8	4790.038	Dangerous goods		0	Op Spec removed due to lack of responses	Corre- lation	0.58

Legend

0 Phase

Amber Study (TCS) Red Study (EBT Accid Study

Figure A5.11.14 cont.







## 11.15.2 Gen3 Jet

The correlation generation 3 Training Criticality Study (TCS) risk ranking to the EBT Accident-Incident Analysis is 0.636808237.

Gen	Σ risk	Ans count	s_b	Correcte d Σ risk	Gen 4 Amber Rank	Corrected Σ of risk	Φ phase	x Phases	Corrected for phase	Gen 4 Final Rank (Amber)	Rank no#	Rank value	Gen 4 Final Rank (Red)	Rank no#	Rank value
4	10409	848	984	12078.4	Adverse Weather/Ice	12078.37	Cabin issues	1	12078.37	Adverse Weather/Ice	1	12078	Adverse Weather/Ice	1	36
4	8279	848	984	9606.76	ATC	9606.764	Compliance failure	1	9606.764	Mismanaged Aircraft State	2	11279	CRM	4	33
4	6673	848	984	7743.2	Poor Visibility	7743.198	Deficiency in Ops Data	1	7743.198	Compliance failure	3	10462	Compliance	3	34
4	6081	848	984	7056.25	Traffic	7056.255	Deficiency within Charts	1	7056.255	Human Factors and CRM	4	9997.8	Mis A/C State	2	35
4	5456	848	984	6331.02	Wind	6331.019	Deficiency within Checklists	1	6331.019	ATC	5	9606.8	Man handling	8	29
4	5334	848	984	6189.45	MEL	6189.453	Deficiency within Database	1	6189.453	Workload/ Distraction/ Pressure	6	9204.1	Runway/Taxi condition	24	13
4	5241	848	984	6081.54	System malfunction	6081.538	Deficiency within Manuals	1	6081.538	Poor Visibility	7	7743.2	Fire	21	16
4	4795	848	984	5564.01	Windshear	5564.009	Fatigue	1	5564.009	Mishanded Aircraft	8	7574.9	Syst mal	14	23
4	4527	848	984	5253.03	Birds	5253.028	Human Factors and CRM	1	5253.028	Fatigue	9	7100.8	Mis-Sys	10	27
4	4345	848	984	5041.84	Dangerous goods	5041.84	Loading/fuel/ Performance	0	0	Other Mishandled system	10	7045.8	Workload Distraction Pressure	6	31
4	4188	848	984	4859.66	Loss of comms	4859.66	Mishanded Aircraft	1	4859.66	Traffic	11	7056.3	Crosswind	12	25
4	4176	848	984	4845.74	Wake vortex	4845.736	Mishandled Auto Flight Systems	1	4845.736	Wind	12	6331	Poor Visibility	7	30
4	3930	848	984	4560.28	Fire	4560.283	Mismanaged Aircraft State	1	4560.283	MEL	13	6189.5	MEL	13	24
4	3504	848	984	4065.96	NAV	4065.962	Other Mishandled system	1	4065.962	System malfunction	14	6081.5	Physio	32	5
4	3396	848	984	3940.64	R/W incursion	3940.642	Physiological	1	3940.642	Windshear	15	5564	Terrain	28	9
4	3175	848	984	3684.2	Runway/Taxi condition	3684.198	Procedures	1	3684.198	Birds	16	5253	Eng Fail	29	8
4	3039	848	984	3526.39	Upset	3526.387	Workload/ Distraction/ Pressure	1	3526.387	Mishandled Auto Flight Systems	17	5221.7	ATC	5	32
4	2794	848	984	3242.09	Terrain	3242.094		1	3242.094	Loss of comms	18	4859.7	Traffic	11	26
4	2785	848	984	3231.65	Eng Fail	3231.651		1	3231.651	Wake vortex	19	4845.7	Cabin	33	4
4	2778	848	984	3223.53	Pilot Incapacitation	3223.528		1	3223.528	Procedures	20	4790	Def-Proc's	20	17
4	1666	848	984	1933.19	Ground manoeuvring	1933.189		1	1933.189	Fire	21	4560.3	R/W Incursion	23	14

Figure A5.11.16 – Analysis of generation 3 aircraft from the TCS (Amber Study) with resultant ranking of factors in terms of risk and a correlation with the EBT Accident Study (Red Study) risk ranking of Gen3 Jet aircraft.



<b>—</b>														
3	471	916	984	505.9651	Ground equipment	505.9651	0	0	NAV	1187	22	Wake Vortex	21	16
3	384	916	984	412.5066	Workload/ Distraction/ Pressure	412.5066	6	2475.039	Birds	1181	23	Def-DBs	35	2
3	378	606	656	409.1881	Fatigue	409.1881	4	1636.752	Eng Fail	1046	24	Def-Charts	33	4
3	314	916	984	337.31	Human Factors and CRM	337.31	8	2698.48	Deficiency within Manuals	1040	25	Def-Ops data	27	10
3	300	916	984	322.2707	Mismanaged Aircraft State	322.2707	8	2578.166	Cabin issues	973	26	Mis-AFS	18	19
3	296	916	984	317.9738	Mishandled Auto Flight Systems	317.9738	4	1271.895	Deficiency in Ops Data	967	27	Def Manuals	25	12
3	291	916	984	312.6026	Compliance failure	312.6026	8	2500.821	Deficiency within Checklists	963	28	R/W Incursion	20	17
3	242	916	984	259.9651	Deficiency within Manuals	259.9651	4	1039.86	Upset	943	29	Birds	23	14
3	225	916	984	241.7031	Deficiency in Ops Data	241.7031	4	966.8122	Terrain	893	30	LF.P	36	1
3	224	916	984	240.6288	Deficiency within Checklists	240.6288	4	962.5153	Runway/Taxi condition	836	31	Def-Chk lists	28	9
3	197	916	984	211.6245	Loading/fuel/ Performance	211.6245	1	211.6245	Physiological	834	32	Fatique	12	25
3	196	916	984	210.5502	Mishanded Aircraft	210.5502	8	1684.402	Deficiency within Charts	821	33	Physio	32	5
3	194	916	984	208.4017	Physiological	208.4017	4	833.607	Pilot Incapacitation	794	34	NAV	22	15
3	191	916	984	205.179	Deficiency within Charts	205.179	4	820.7162	Deficiency within Database	653	35	Pilot Incap	34	3
3	191	916	984	205.179	Other Mishandled system	205.179	8	1641.432	Loading/fuel/ Performance	212	36	Loss of comms	16	21
3	154	916	984	165.4323	Procedures	165.4323	8	1323.459	Dangerous goods	0		Removed GRD because lack of response		
3	152	916	984	163.2838	Deficiency within Database	163.2838	4	653.1354	Ground manoeuvring	0		Removed D.G. because of NTSB db bias		
3	151	916	984	162.2096	Cabin issues	162.2096	6	973.2576	Ground equipment	0		Op Spec removed due to lack of responses	Corre- lation	0.637

Legend

Amber Study (TCS) Red Study (EBT Accid Study

0 Phase

Figure A5.11.16 cont.





Figure A5.11.17 – Bar Chart showing Gen 3 ranking of the threats and errors resulting from TCS (Amber Study) in the order of the ranking of the factors from the EBT accident study (Red Study)



## 11.15.2.1 Gen2 Jet

The correlation generation 2 Training Criticality Study (TCS) risk ranking to the EBT Accident-Incident Analysis is **0.553783408**.

Gen	Σ risk	Ans count	s_b	Correcte d Σ risk	Gen 2 Amber Rank	Corrected Σ risk	0 phase	x Phase s	Corrected for phase	Gen 2 Final Rank (Amber)	Rank no#	Values	Gen 2 Final Rank( Red)	Rank no#	Rank value
2	288	159	164	297.057	Adverse Weather/Ice	297.0566	Cabin issues	1	297.0566	Human Factors and CRM	305	1	Syst mal	6	31
2	267	159	164	275.396	Poor Visibility	275.3962	Compliance failure	1	275.3962	Adverse Weather/Ice	297	2	Man handling	10	27
2	262	159	164	270.239	ATC	270.239	Deficiency in Ops Data	1	270.239	Poor Visibility	275	3	Adverse Weather/Ice	2	35
2	218	159	164	224.855	System malfunction	224.8553	Deficiency within Charts	1	224.8553	ATC	270	4	Poor Visibility	3	34
2	196	159	164	202.164	Loss of comms	202.1635	Deficiency within Checklists	1	202.1635	Compliance failure	248	5	Eng Fail	27	10
2	182	159	164	187.723	Wind	187.7233	Deficiency within Database	1	187.7233	System malfunction	225	6	Fire	22	15
2	174	159	164	179.472	Wake vortex	179.4717	Deficiency within Manuals	1	179.4717	Mismanaged Aircraft State	215	7	Mis A/C State	7	30

Figure A5.11.18 – Analysis of generation 3 aircraft from the TCS (Amber Study) with the resultant ranking of factors in terms of risk and a correlation with the EBT Accident Study (Red Study) risk ranking of gen 3 aircraft.



_															
2	173	159	164	178.44	Windshear	178.4403	Fatigue	1	178.4403	Workload/ Distraction/ Pressure	210	8	CRM	1	36
2	157	159	164	161.937	Traffic	161.9371	Human Factors and CRM	1	161.9371	Loss of comms	202	9	Crosswind	12	25
2	153	159	164	157.811	Birds	157.8113	Loading/fuel/ Performance	1	157.8113	Mishanded Aircraft	198	10	Terrain	23	14
2	147	159	164	151.623	R/W incursion	151.6226	Mishanded Aircraft	1	151.6226	Other Mishandled system	198	11	Windshear	14	23
2	144	159	164	148.528	NAV	148.5283	Mishandled Auto Flight Systems	1	148.5283	Wind	188	12	Compliance	5	32
2	132	159	164	136.151	Upset	136.1509	Mismanaged Aircraft State	1	136.1509	Wake vortex	179	13	Runway/Tax i condition	29	8
2	130	159	164	134.088	Dangerous goods	134.0881	Other Mishandled system	0	0	Windshear	178	14	ATC	4	33
2	122	159	164	125.836	Fire	125.8365	Physiologica	1	125.8365	Traffic	162	15	Mis-Sys	11	26
2	122	159	164	125.836	Terrain	125.8365	Procedures	1	125.8365	Birds	158	16	Workload Distraction Pressure	8	29
2	106	159	164	109.333	MEL	109.3333	Workload/ Distraction/ Pressure	1	109.3333	R/W incursion	152	17	Def Manuals	31	6
2	105	159	164	108.302	Eng Fail	108.3019		1	108.3019	NAV	149	18	Fatique	20	17
2	88	159	164	90.7673	Runway/Taxi condition	90.7673		1	90.7673	Upset	136	19	Upset	19	18
2	78	159	164	80.4528	Pilot Incapacitation	80.45283		1	80.45283	Fatigue	132	20	Birds	16	21
2	43	159	164	44.3522	Ground manoeuvring	44.3522		0	0	Deficiency within Checklists	128	21	Traffic	15	22
2	37	159	164	38.1635	Human Factors and CRM	38.16352		8	305.3082	Fire	126	22	Def-Ops data	28	9
2	34	159	164	35.0692	Workload/ Distraction/ Pressure	35.06918		6	210.4151	Terrain	126	23	Cabin	35	2
2	32	159	164	33.0063	Fatigue	33.00629		4	132.0252	Mishandled Auto Flight Systems	124	24	LF.P	36	1
2	31	159	164	31.9748	Deficiency within Checklists	31.97484		4	127.8994	Procedures	116	25	MEL	26	11
2	30	159	164	30.9434	Compliance failure	30.9434		8	247.5472	MEL	109	26	Def-Proc's	32	5
2	30	159	164	30.9434	Mishandled Auto Flight Systems	30.9434		4	123.7736	Eng Fail	108	27	Mis-AFS	24	13
2	26	159	164	26.8176	Ground equipment	26.81761		0	0	Deficiency in Ops Data	99	28	Wake Vortex	13	24
2	26	159	164	26.8176	Mismanaged	26.81761		8	214.5409	Runway/Taxi	90.8	29	Def-Chk	21	16
2	24	159	164	24.7547	Deficiency in Ops Data	24.75472		4	99.01887	Deficiency within Database	86.6	30	Pilot Incap	33	4
2	24	159	164	24.7547	Mishanded Aircraft	24.75472		8	198.0377	Deficiency within Manuals	86.6	31	Loss of comms	9	28
2	24	159	164	24.7547	Other Mishandled system	24.75472		8	198.0377	Deficiency within Charts	82.5	32	R/W Incursion	17	20
2	23	159	164	23.7233	Loading/fuel/P	23.72327		1	23.72327	Pilot Incapacitation	80.5	33	Physio	34	3
2	21	159	164	21.6604	Deficiency within Database	21.66038		4	86.64151	Physiological	74.3	34	Def-DBs	30	7
2	21	159	164	21.6604	Deficiency within Manuals	21.66038		4	86.64151	Cabin issues	61.9	35	Def-Charts	32	5
2	20	159	164	20.6289	Deficiency within Charts	20.62893		4	82.51572	Loading/fuel/P	23.7	36	NAV	18	19
2	18	159	164	18.566	Physiological	18.56604		4	74.26415	Dangerous	0				
2	14	159	164	14.4403	Procedures	14.44025		8	115.522	Ground	0				
	10	150	164	10 31/15	Cabin issues	10 31447		6	61 89670	Ground	0			Corre-	0.554
2	10	159	104	10.3145	Cabin Issues	10.31447		0	01.000/9	equipment	0			lation	0.554

Legend

0 Phase Amber Study (TCS) Red Study (EBT Accid Study







## 11.15.3 Comparison of Gen 3 Jet and Gen 4 Jet in the TCS

Figure 5.11.20 shows a comparison of generation 4 aircraft in the TCS with generation 3 aircraft in the same study to provide a graphic representation of where the differences lie between these two generations.



Figure A5.11.20



# APPENDIX 12 Evidence table



# **12.1 EVIDENCE TABLE**

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
1	Unstable Apprs: 4% of approaches were unstable. 97% continued to landing.1% of such landings were abnormal. Both crew members willing to continue even if unstable.	1			APP	234	All	LOSA	Unstable APR/GA	Unstable APP Go Around	CRM Mis A/C State Compliance	Flight Management Guidance/Automation
2	Pilots did not know stable approach criteria.	1			APP	234	All	LOSA	Unstable APR/GA Training	Unstable APP Go Around	CRM	Knowledge
3	3% of Unstable Approaches are linked to weather and ATC.		1		APP	234	All	LOSA	Unstable APR/GA	Unstable APP WX	Adverse WX ATC	
4	Missed Approaches as result of Unstable Approaches are rarely handled well. Risk rises dramatically which is problematic.	1	1		APP GA	234	All	LOSA	Competencies Unstable APR/GA Training	Unstable APP Go Around	Mis A/C State	Application of Procedures/Knowledge
5	Usually a surprise to the crew. None occurred at standard missed approach height briefed.	1			APP	234	All	LOSA	Competencies Unstable APR/GA	Go Around Surprise	Compliance CRM	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control
6	28% of flights in the LOSA Archive have an Automation error. Almost 1% of total flights have Automation errors that have consequential results.	1			All	234	All	LOSA	Automation Error Training	Automation Error Mgt	Mis-AFS Mis A/C State	Flight Management Guidence/Automation
7	In terms of mismanaged errors guidance are far more prevalent than programming errors.				All	234	All	LOSA	Error Automation Training	Automation Error Mgt	Mis-AFS	Flight Management Guidance/Automation
8	Technical understanding of the Automation	1			All	234	All	LOSA	Automation Competencies Training	Automation	Mis-AFS CRM	Flight Management Guidance/Automation Knowledge
9	A lack of "verbalization" by crew to share mental models	1	1		All	234	All	LOSA	Competencies Automation Training	Automation Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Communication
10	The late engagement of autopilot after takeoff or early disengagement in Descent/Approach/Land,Basically hand flying at an inappropriate time. Common errors include hand flying in a busy Terminal Area.	1	1		CLB APP	234	All	LOSA	Automation Competencies	Automation Manual AC Control Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Problem Solving Decision Making
11	Control Zone, looking through the FD, not checking modifications to the SID, STAR or Approach profile and relying on the PM to effect FMC/FMGC changes.	1	1		CLB APP	234	All	LOSA	Automation Training	Automation Manual AC Control Monitor Xcheck	Mis-AFS CRM	Flight Management Guidance/Automation Workload Management Manual Aircraft Control Application of Procedures/Knowledge
12	The overarching element is Monitoring/Cross-Checking, with little to no dialogue between the pilots during most of the errors.	1			All	234	All	LOSA	Automation Error MonitoringXchecking Training	Automation Monitor Xcheck Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Communication SA
13	21% of the Automation induced undesired aircraft states result from SOP Cross-Verification errors	1	1		All	234	All	LOSA	Automation Error MonitoringXchecking UAS	Automation Monitor Xcheck Error Mgt	Mis-AFS CRM Mis A/C State	Flight Management Guidance/Automation SA
14	There are often misunderstandings of autopilot modes.	1	1		All	234	All	LOSA	Automation Competencies Training	Automation Error Mgt	Mis-AFS CRM	Flight Management Guidance/Automation Knowledge
15	There is a high prevalence of altimeter errors versus other aircraft systems and instruments. Wrong primary altimeter setting" errors occur on about 3-4% of flights. 46% of these errors are mismanaged.	1	1		All	234	All	LOSA	Error	Error Mgt	Mis-Sys Mis A/C State Compliance	SA Application of Procedures/Knowledge
16	Many flights have improperly set secondary altimeters. Proper use of secondary altimeters does not seem to be taught in training or imbedded in SOPs	1	1		All	234	All	LOSA	Error	Error Mgt Terrain	Mis-Sys Mis A/C State Def-Proc's	SA
17	MSA issues: In areas of high Terrain in many cases, no altimeter is set to QNH. Direct to – clearances rarely result in pilots checking revised MSA. In briefing, only the 25 mile airfield MSA is considered, not that for the descent corridor.	1	1		TO CLB APP LDG	234	All	LOSA	MonitoringXchecking	Monitor Xcheck Error Mgt Terain	Terrain Compliance CRM Mis-Sys	SA Leadership and Teamwork Application of Procedures/Knowledge
18	About 4% of all flights are rated poor or marginal on Monitoring/Cross-Checking in at least one phase of flight. Flights with poor or marginal monitoring/Cross-Checking ratings have double the rate of mismanaged threats than those with Good or above.	1	1		All	234	All	LOSA	MonitoringXchecking	Monitor Xcheck Error Mgt	CRM Workload Distraction Compliance	SA Workload Management Application of Procedures/Knowledge

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
19	Two of the more frequent Monitor/Cross-Checking errors logged in LOSA are Callout and SOP Cross verification errors.	1	1		All	234	All	LOSA	MonitoringXchecking	Monitor Xcheck Error Mgt	CRM Workload Distraction Compliance	SA Workload Management Application of Procedures/Knowledge
20	Among callout errors, the ones for omitted deviation callouts have the highest risk (65% UAS/added error rate).	1	1		All	234	All	LOSA	MonitoringXchecking UAS	Leadership Error Mgt Monitor Xcheck	Compliance	Leadership and Teamwork Application of Procedures/Knowledge
21	2% of omitted callouts are intentional.	1	1		All	234	All	LOSA	MonitoringXchecking Compliance	Leadership Error Mgt	Compliance	Communication SA Leadership and Teamwork Application of Procedures/Knowledge
22	There is a strong association between non compliance and poor TEM performance.	1	1		All	234	All	LOSA	Compliance	Error Mgt	Compliance CRM	Communication SA Leadership and Teamwork Workload Management Problem Solving Decision Making Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
23	28% of flights in the LOSA Archive have an SOP Cross-Verification error. 1% of these are mismanaged.	1	1		All	234	All	LOSA	MonitoringXchecking Training	Monitor Xcheck Error Mgt	Mis-AFS Mis A/C State Mis-Sys	Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
24	Most Frequent cross-verification errors: Omitted flight mode verification – 2%, Failure to cross-verify alt setting – 18%, Failure to cross-verify FMS settings – 16%, Failure to cross verify documentation and performance – 9%	1			All	234	All	LOSA	MonitoringXchecking Training	Monitor Xcheck Error Mgt	Mis-Sys Mis-AFS Compliance	SA Flight Management Guidance/Automation Application of Procedures/Knowledge
25	Most Risky cross-verification errors: Failure to cross-verify alt setting, Failure to cross-verify FMS settings (14% UAS/added error rate).	1	1		All	234	All	LOSA	MonitoringXchecking UAS Training	Monitor Xcheck Error Mgt	Mis-Sys Mis-AFS Compliance	SA Flight Management Guidance/Automation Application of Procedures/Knowledge
26	Most important mismanaged Threat: Terrain. Both omitted callouts and failure to select Terrain feature on Nav Display are a common and risky combination. Airlines that operate in high Terrain areas tend to get too used to this threat.	1			TO CLB DES APP LDG	234	All	LOSA	Terrain MonitoringXchecking Training	Terrain Monitor Xcheck Error Mgt	Mis-Sys Compliance	SA Application of Procedures/Knowledge
27	Thunderstorms/Turbulence: Common errors associated are ManualACControl, Flight control and System, Instrument and Radio error. – exacerbate the situation.	1			TO CLB DES APP	234	All	LOSA	ManualACControl Error	WX Error Mgt Manual AC Control	Adverse WX Workload Distraction Mis A/C State Mis-Sys	Communication SA Workload Management Application of Procedures/Knowledge Manual Aircraft Control
28	Unexpected aircraft malfunction. Crew applying engineering shortcuts or workarounds instead of following ECAM, QRH, MEL. High degree of intentional non-compliance.	1	1		All	234	All	LOSA	Compliance	Error Mgt System Malfunction Surprise	Syst mal Compliance CRM Workload Distraction	Application of Procedures/Knowledge
29	Icing and Snow – The most common error associated with this threat is failure to select anti-ice on. That situation leads to a UAS. Usually coupled with poor/marginal monitoring / cross-checking.	1	1		All	234	All	LOSA	Error MonitoringXchecking UAS	WX Error Mgt Monitor Xcheck	Adverse WX Compliance CRM Workload Distraction Mis-Sys	SA Workload Management Application of Procedures/Knowledge
30	Intentional Noncompliance: significant positive correlation between this and the number of mismanaged threats, unintentional errors, mismanaged errors and UAS.	1	1		All	234	All	LOSA	Compliance UAS Training	Error Mgt	Compliance CRM Mis-AFS Mis A/C State Mis-Sys	Leadership and Teamwork Application of Procedures/Knowledge
31	Number 1 non-compliance item: Non standard checklist protocol. Almost half during ground/taxi out.	1	1		All	234	All	LOSA	Compliance	Error Mgt Leadership	Ground manoeuvring CRM Compliance	Application of Procedures/Knowledge
32	Number 2 non-compliance item: Omitted altitude callouts	1	1		All	234	All	LOSA	Compliance Error	Monitor Xcheck Error Mgt	Compliance CRM Workload Distraction	Communication SA Application of Procedures/Knowledge



E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
33	Number 3 non-compliance item: Fail to execute missed appr when required	1	1		APP	234	All	LOSA	Unstable APR/GA Compliance	Unstable APP Landing Issues Go Around	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making Application of Procedures/Knowledge
34	Number 4 non-compliance item: PF makes own changes	1	1		All	234	All	LOSA	Compliance	Leadership Error Mgt Monitor Xcheck	Compliance CRM	Communication SA Leadership and Teamwork Application of Procedures/Knowledge
35	Number 5 non-compliance item: Taxi duties commence before runway exit	1	1		GND	234	All	LOSA	Compliance	Monitor Xcheck Error Mgt Leadership Landing Issues	Compliance CRM Ground manoeuvring	Communication SA Leadership and Teamwork Application of Procedures/Knowledge
36	Captains display significantly more non-compliance than first officers.	1	1		All	234	All	LOSA	Compliance	Leadership	Compliance CRM	Leadership and Teamwork Application of Procedures/Knowledge
37	Flights with outstanding ratings for Leadership and Communication Environment have on average 2.3 errors/flight vs 7. errors/flights for poor Leadership and Communication Environment. Flights with poor ratings have approximately 3 times the number of mismanaged threats.	1	1		All	234	All	LOSA	Leadership Communication Error	Leadership Error Mgt Surprise	CRM Mis A/C State	Communication Leadership and Teamwork
38	If communication is poor, TEM is poor despite good Leadership by captain.	1	1		All	234	All	LOSA	Leadership Communication Training	Error Mgt	CRM	Communication Leadership and Teamwork
39	Most common threat type: Adverse weather.	1	1		All	234	All	LOSA	wx	WX	Adverse WX Windshear Crosswind Poor Visibility	SA Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control
40	ATC threats are the second most common threat type observed in the LOSA Archive.	1			All	234	All	LOSA	Communication Training		ATC	Communication
41	ATC threat 1: Challenging clearances or tough to meet restrictions, leading to ManualACControl & Automation issues.	1	1		CLB DES APP	234	All	LOSA	ManualACControl Automation	Error Mgt Manual AC Control	ATC Workload Distraction Pressure Mis A/C State Mis-AFS	Flight Management Guidance/Automation Manual Aircraft Control
42	ATC threat 2: Runway Changes, leading to Automation Issues, Briefing errors, SOP errors, Aircraft configuration issues.	1	1		APP GND	234	All	LOSA	Communication Automation Error	Error Mgt Automation	ATC Workload Distraction Mis A/C State Mis-AFS CRM Compliance	Communication Application of Procedures/Knowledge Flight Management Guidance/Automation
43	ATC threat 3: Difficulty understanding Controller, leading to communication issues, mainly ground navigation related (5%).	1	1		All	234	All	LOSA	Communication	Error Mgt	Ground manoeuvring ATC R/W Incursion Compliance	Communication Application of Procedures/Knowledge
44	Crews often agree to ATC clearances in order to "help".		1		CLB DES APP	234	All	LOSA	Unstable APR/GA	Error Mgt Leadership	ATC Workload Distraction Mis A/C State Mis-AFS	Communication Flight Management Guidance/Automation Manual Aircraft Control Problem Solving Decision Making
45	ATC induced problems often linked with poor communication and cross-checking in the cockpit.	1	1		TO CLB DES APP	234	All	LOSA	Communication MonitoringXchecking Training	Error Mgt Monitor Xcheck	ATC CRM	Communication SA Application of Procedures/Knowledge
46	Weather radar usage: 8% of flights face Thunderstorm, 1% mismanaged; half of errors lead to UAS. Most common linked errors are: Wrong radar settings, Course or heading deviations without ATC clearance, Weather penetration.	1	1		All	234	All	LOSA	Compliance Error UAS WX	wx	Adverse WX ATC CRM Mis A/C State Mis-Sys Compliance	Knowledge Communication Application of Procedures/Knowledge

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
47	About 25% of Weather avoidance events involve intentional non-compliance: deviation without ATC clearance and deliberately penetrating bad weather. Offsets are often less than company requirements.	1	1		CLB CRZ DES	234	All	LOSA	Compliance Error WX	wx	Adverse WX ATC CRM Mis A/C State Mis-Sys Compliance	Communication Application of Procedures/Knowledge Problem Solving Decision Making
48	Key theme in weather avoidance errors is lack of forward planning. Late identification contributed in all penetration events.	1	1		All	234	All	LOSA	Error WX	wx	Adverse WX CRM Mis A/C State	SA Problem Solving Decision Making
49	The two most important radar errors were: radar not switched on and incorrect use of gain and especially tilt.	1	1		All	234	All	LOSA	Error WX	WX Error Mgt	Compliance CRM Mis-Sys	Knowledge Workload Management Application of Procedures/Knowledge
50	Flight phases: most threats in pre-departure.	1	1		GND	234	All	LOSA	Error Management	Error Mgt	Cabin CRM Workload Distraction	Leadership and Teamwork Workload Management
51	Flight phases: most mismanaged errors and UAS in DES, APP, LND	1	1		DES APP LDG	234	All	LOSA	Error Management UAS	Error Mgt	CRM Workload Distraction Pressure Mis A/C State Mis-Sys	Leadership and Teamwork Workload Management
52	In top 5 - UAS in DES/APP/LND: speed too high	1	1		DES APP LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP Landing Issues	ATC Compliance CRM Mis A/C State	SA Workload Management Problem Solving Decision Making Flight Management Guidance/Automation
53	In Top 5 - UAS in DES/APP/LND: Unstable App	1	1		DES APP LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP Landing Issues	ATC Compliance CRM Mis A/C State	SA Workload Management Problem Solving Decision Making Flight Management Guidance/Automation Application of Procedures/Knowledge
54	In top 5 - UAS in DES/APP/LND: incorrect A/C config-Automation	1	1		DES APP LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP	Compliance CRM Mis A/C State Mis-AFS Mis-Sys	Flight Management Guidance/Automation Application of Procedures/Knowledge
55	In top 5 - UAS in DES/APP/LND: incorrect A/C config-systems	1	1		DES APP LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP Go Around	Compliance CRM Mis A/C State Mis-Sys	Problem Solving Decision Making Application of Procedures/Knowledge
56	In top 5 - UAS in DES/APP/LND: continued landing after Unstable App	1	1		DES APP LDG	234	All	LOSA	Unstable APR/GA UAS	Unstable APP	Compliance CRM Mis A/C State	Leadership and Teamwork Problem Solving Decision Making
57	In all phases, according to LOSA, weather is either the most significant threat or in the top three.	1	1		All	234	All	LOSA	Error Management WX	WX	Adverse WX	
58	Predeparture/Taxi-out are extremely important phases from the point of view that they are fertile territory for mitigating threats by training. 4	1	1		GND	234	All	LOSA	Error Management Training	Error Mgt	Ground manoeuvring CRM	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
59	strong support for a new kind of training concept: Scenario-based, matter brought in blocks, gradually, adapted individually. Teach Automation Knowledge, the why's. Teach and test the conceptual Knowledge. [details: see Lyall]	1	1		All	All	All	Automation Lyall	Automation Generation		Mis-AFS	Knowledge Flight Management Guidance/Automation
60	Make sure flight crews learn to fly manually without the Automation.	1	1		All	All	34	Automation Lyall	ManualACControl Automation Generation Training	Manual AC Control Automation	Mis-AFS Pilot Incap	Manual Aircraft Control Flight Management Guidance/Automation



E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
61	Good CRM is especially important in automated aircraft; CRM should be integrated and used throughout the training.	1	1		All	All	34	Automation Lyall	Automation Generation Training	Automation Error Mgt	CRM Workload Distraction Mis A/C State	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
62	Decide what pilots really need to learn about the Automation. (don't try to teach everything).	1	1		All	All	34	Automation Lyall	Automation Error MonitoringXchecking Generation	Automation	CRM	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Communication Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
63	Train also to monitor Automation. (This point is strongly underlined by the LOSA data	1	1		All	All	34	Automation Lyall	Automation Generation Training	Automation Monitor Xcheck Error Mgt	Compliance CRM Workload Distraction	SA Communication Flight Management Guidance/Automation
64	Use multiple assessment techniques to evaluate Automation Knowledge.	1	1		All	All	34	Automation Lyall	Automation	Automation		Knowledge Flight Management Guidance/Automation
65	Pilots need to be taught how the components of Automation work together in the overall system.	1	1		All	All	34	Automation Lyall	Automation Generation Training	Automation		Knowledge Flight Management Guidance/Automation
66	Provide as much hands-on experience with the Automation as possible. (One cannot learn by just watching).	1	1		All	All	34	Automation Lyall	Automation Generation Training	Automation		Flight Management Guidance/Automation
67	There are tools for creating the training scenarios. Using a tool is better than creating them "manually" from scratch. (Objective 3)	1	1	1	All	All		Automation Lyall	Automation	Automation		
68	Teach the logic underlying the Automation and cover its limitations	1	1		All	All	34	Automation Lyall	Automation Generation Training	Automation		Knowledge Flight Management Guidance/Automation
69	<ul> <li>Flight crews should explicitly receive instruction and practice in when and how to:</li> <li>a. Appropriately use Automation;</li> <li>b. Transition between levels of Automation.</li> <li>c .Revert to manual flight."</li> </ul>	1	1		All	All	34	Automation Lyall	Automation ManualACControl generation Training	Automation Error Mgt Manual Aircraft Control	Mis-AFS	Knowledge SA Problem Solving Decision Making Manual Aircraft Control Flight Management Guidance/Automation Manual Aircraft Control
70	There is less skill decay for physical tasks compared to cognitive tasks.				All		All	Skill Decay & Skill Retention Studies	Skill Decay	Automation Surprise Error Mgt Manual Aircraft Control System Malfunction	Manual AC Control	Communication SA Problem Solving Decision Making Knowledge Manual Aircraft Control
71	Large regional variations in accident rates				All	All	all	ACC IATA	Criticality			All
72	IATA 29 ACC statistics: Flight Crew Errors fully in support of LOSA results (ManualACControl, compliance, failure to go-around, Automation)	1	1		All	All	all	ACC IATA	ManualACControl Compliance Automation	Manual AC Control Go Around Automation	Compliance CRM Mis A/C State Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control Flight Management Guidance/Automation
73	Top threat weather 29%	1	1		All	All	All	ACC IATA	Error Management WX	wx	Adverse WX Windshear Crosswind Poor Visibility	SA Problem Solving Decision Making Application of Procedures/Knowledge
74	Top errors Manual Handling (33%), SOP 30%, Fail to GA 11%	1			All	All	All	ACC IATA	Error	Manual AC Control Error Mgt Unstable APP Go Around	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Manual Aircraft Control
75	Top UAS: improper landing 21%	1			LDG	All	All	ACC IATA	Error ManualACControl UAS	Landing Issues	Runway/ Taxiway condition Mis A/C State	Problem Solving Decision Making Manual Aircraft Control

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
76	For 23% of 29 accidents, training could have been effective in reducing the likelihood	1			All	All	All	ACC IATA	Error Management	Error Mgt		
77	Countermeasures include monitoring / cross-checking and Automation mgt	1	1		All	All	All	ACC IATA	MonitoringXchecking Automation	Error Mgt Automation Monitor Xcheck	Mis-AFS CRM	SA Flight Management Guidance/Automation
78	ManualACControl needs to be reinforced in Training	1	1		All	All		ACC IATA Comments	ManualACControl	Manual AC Control Training Effect	Mis A/C State	Manual Aircraft Control
79	Flight Crews are becoming more reluctant to revert to manual flying when Automation fails.	1			All	All	34	ACC IATA Comments	Automation ManualACControl	Manual AC Control Error Mgt Automation	CRM Mis-AFS Syst mal Mis A/C State	Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
80	Gross error checks are required when inputting data in FMS.	1	1		All	All	34	ACC IATA Comments	Automation Error Management	Automation Error Mgt	CRM Mis-AFS	SA Flight Management Guidance/Automation
81	Decision to GA needs to be reinforced in training for abnormal landings (existing training counterproductive to this objective 4)	1			LDG	All	All	ACC IATA Comments	Unstable APR/GA Compliance Training effect	Go Around Landing Issues Error Mgt	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
82	Many abnormal events that crews face are not covered in training.	1			All	All	34	ACC IATA Comments	Surprise	Surprise		SA
83	Training should be designed to take pilots to the edge of the envelope. (black/grey Surprise)	1			All	All	All	ACC IATA Comments	Training effect	Surprise Upset		SA Problem Solving Decision Making Application of Procedures/Knowledge
84	Briefing should be adapted to the situation.	1			All	All	All	ACC IATA Comments	Error Management	Error Mgt	CRM	Communication SA
85	Introduce Unstable App training in simulators	1			APP	All	All	ACC IATA Comments	Unstable APR/GA Training Effect	Unstable APP	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
86	Go-Arounds need training in terms of Decision making, surprise, execution, two engine, any point during the approach and landing	1	1		APP LDG GA	All	All	ACC IATA Comments	GA Training Effect	Go Around Surprise	CRM Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Application of Procedures/Knowledge Manual Aircraft Control
87	CAA report supports main threats (compliance, HF/CRM, mishandling a/c, SOP's). Compared to LOSA, bigger bars in CRZ and APP.	1	1		All	All	All	ACC CAA	Compliance ManualACControl	Error Mgt	CRM Mis A/C State Compliance	Communication SA Leadership and Teamwork Workload Management Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
88	During ATQP implementation period, no significant variation in the Flight Ops risk value			1	All	34	34	ATQP airline	ATQP/AQP			
89	During ATQP implementation periodTop RV events have remained substantially unchanged			1	All	34	34	ATQP airline	ATQP/AQP			
90	During ATQP implementation period Slight increase in high speed descents below FL100 but APProach stability remaining			1	DES APP	34	34	ATQP airline FDA	Unstable APR			
91	During ATQP implementation period Stability remaining static at 1000' and 500'.			1	APP	34	34	ATQP airline FDA	Unstable APR	Unstable APP	Mis A/C State	Application of Procedures/Knowledge
92	During ATQP implementation period G/A's from Unstable Approaches account for approximately 1/2 of all G/A's	1		1	APP GA	34	34	ATQP airline	Unstable APR/GA Compliance	Go Around Unstable APP	Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge



E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
93	<ul> <li>Factors contributing to Unstable Approaches are:</li> <li>1. Accepting ATC vectors or speed control.</li> <li>2. Turning too tight when visual,</li> <li>3. FMGS mis-selections,</li> <li>4. Energy Management</li> <li>5. Lack of proficiency when manually flying instrument approaches.</li> </ul>	1	1		APP	34	34	ATQP airline	Unstable APR/GA	Unstable APP	ATC Mis A/C State Mis-AFS	SA Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
94	During ATQP implementation period There has been an increase in the number of fast touchdowns. AND There has been a reduction in landing events	1		1	LDG	34	34	ATQP airline	ATQP/AQP	Landing Issues	Mis A/C State	Manual Aircraft Control
95	During ATQP implementation period (Missed Approach 1. Approximately 1/10 G/A's failed to comply with SOP's and just over 1/10 G/A's resulted in a flap over speed.2. There has been no significant change in G/A rates3. Flight Management remains the biggest cause	1	1	1	APP GA	3 4	34	ATQP airline	GA	Go Around	Compliance CRM Mis-AFS Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation
96	During ATQP implementation period, the number of APProaches not meeting company criteria at 1000 ft has significantly reduced.	1		1	APP	3 4	34	ATQP airline	Unstable APR Training	Go Around	Compliance CRM Mis A/C State	Problem Solving Decision Making Application of Procedures/Knowledge
97	During ATQP implementation period, the training failure rate has dropped from approximately 4% during LPC/OPC checks to approximately 1%	1		1	All	3 4	34	ATQP airline	ATQP/AQP			
98	During ATQP implementation period, inadvertent mis-selections appear to occur most during operations that are not routinely practised	1	1	1	All	3 4	34	ATQP airline	Error Training	Error Mgt Surprise	Mis-Sys Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge
99	During ATQP implementation period, dual Inputs have reduced but need to be carefully monitored.	1	1	1	All	34	34	ATQP airline FDA	ManualACControl MonitoringXchecking	Error Mgt Manual AC Control	Mis-Sys Ops/Type Spec Compliance	SA Manual Aircraft Control Application of Procedures/Knowledge
100	Engine Failure on TO 1. Approximately a 1/5 failed or only passed with a repeat 2. Almost ½ were procedural errors 3. 1% related to Situational awareness or Decisions making	1	1	1	то	34	34	ATQP airline	ManualACControl	System Malfunction	Eng Fail Syst mal Compliance CRM Mis-Sys	SA Problem Solving Decision Making Application of Procedures/Knowledge
101	Single Engine NPA 1. Just over 1% failed 2. 5% were procedural errors, 3. 2% Automation, 4. 2% situational awareness. 5. 5% were handling errors	1	1	1	APP	34	34	ATQP airline	ManualACControl Automation	System Malfunction Manual AC Control Automation	Eng Fail Syst mal Compliance CRM Mis-Sys Mis A/C State	SA Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
102	SE Go-Around 1. Approximately 2% failed or only passed after a repeat 2. Of the repeats a. just over 4% were procedural errors, b. just over 4% handling 3. Of the failed a. 2% Automation and a 2% situational awareness. b. Approx 1/3 were procedural errors and ½ handling.	1	1	1	GA	34	34	ATQP airline	ManualACControl Automation GA	Go Around Automation Error Mgt System Malfunction	Eng Fail Compliance CRM Mis-AFS Mis A/C State	SA Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
103	Procedures not routinely flown, 2 Eng G/A, EFATO, SE NPA and SE G/A appear to present the greatest difficulty to crew, with procedural error and ManualACControl being the biggest factors.	1		1	TO GA	34	34	ATQP airline	ManualACControl GA	Go Around System Malfunction Error Mgt Surprise	Eng Fail Syst mal Compliance CRM Mis A/C State	Application of Procedures/Knowledge Manual Aircraft Control
104	Procedures not routinely flown, 2 Eng G/A, EFATO, SE NPA and SE G/A flown with Automation the error rate is reduced.			1	TO GA	34	34	ATQP airline	ManualACControl Automation GA Training	Manual AC Control	Workload Distraction Pressure	Problem Solving Decision Making Manual Aircraft Control
105	EFATO, SE NPA and SE GA should be retained in the ISS.	1	1	1	TO APP GA	34	34	ATQP airline	ManualACControl GA	System Malfunction Go Around	Eng Fail Syst mal	Manual Aircraft Control

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
106	2 Eng G/A should be scheduled into recurrent training.	1	1	1	GA	34	34	ATQP airline	GA ManualACControl	Go Around Surprise	Mis A/C State	Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
107	Training in energy Management and environmental descent planning needs to be more specific.	1	1	1	DES	34	34	ATQP airline	Unstable APR Training	Error Mgt Unstable APP	Mis A/C State	Problem Solving Decision Making SA
108	Innovative training solutions should be sought for crew to maintain currency with FMGS and technical / procedural Knowledge.	1	1	1	All	34	34	ATQP airline	Automation	Automation	Compliance CRM Mis-AFS	Knowledge Application of Procedures/Knowledge Flight Management Guidance/Automation
109	Data shows that leadership and workload mgt can be taught / learned. 7% to 2%.	1	1	1	All	3 4	34	ATQP airline	Leadership Training	Leadership	Workload Distraction Mis A/C State	Leadership and Teamwork Workload Management
110	ManualACControl/Flight Control error detection/action taken is notably stronger in Predeparture/Taxi-Out than in the other phases of flight	1			GND	234	All	LOSA 2	ManualACControl Error Management	Manual AC Control Error Mgt Monitor Xcheck	Mis-Sys Mis A/C State	SA Problem Solving Decision Making Manual Aircraft Control
111	Callout error detection is better in Takeoff/Climb.	1			CLB	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt Monitor Xcheck	Compliance CRM	Communication SA Application of Procedures/Knowledge
112	41% of Aircraft Handling errors are detected and acted upon vs. 16% of Procedural errors Automation has the best rate of all error types. (53%)	1	1		All	234	234	LOSA 2	Error ManualACControl MonitoringXchecking	Error Mgt Automation Monitor Xcheck	Compliance CRM Mis A/C State Mis-Sys	SA Leadership and Teamwork Workload Management Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control
113	Captains detect 27% of the First Officer mistakes; First Officers detect 18% of the Captain's errors.	1			All	234	234	LOSA 2	Error MonitoringXchecking	Error Mgt Monitor Xcheck	Compliance Mis-AFS Mis A/C State Mis-Sys	Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control Communication
114	Once an error has been committed, people are more capable of detecting other people's errors than their own.	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt Monitor Xcheck	Compliance Mis-AFS Mis A/C State Mis-Sys	Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control Communication
115	Across all three error groups, the Captain as PF detects/acts on more errors than does the First Officer as PF, particularly for Communication errors. There is little difference in PM rates.	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt Monitor Xcheck	Compliance Mis-AFS Mis A/C State Mis-Sys	Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control Communication
116	As the rate of Intentional Noncompliance increases, the rate of errors detected and acted on decreases.	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance	Application of Procedures/Knowledge
117	The LOSA Archive shows that 26% of all errors logged by observers are detected and acted upon by flight crews.	1			All	234	234	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
118	Error detection is most closely aligned with the quality of Monitoring/Cross-Checking in all phases of flight and the quality of the Briefing.	1			All	234	All	LOSA 2	Error MonitoringXchecking Training	Error Mgt Monitor Xcheck	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
119	One-quarter of all errors in the cockpit are detected, acted upon and inconsequential.	1			All	234	234	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
120	One-half of all errors in the cockpit go undetected/not acted upon and are also inconsequential.	1			All	234	234	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
121	'taking shortcuts' reinforces over and over that most errors are inconsequential, whether they act on them or not. PARADOX	1			All	234	234	LOSA 2	Error MonitoringXchecking	Error Mgt Complaince	CRM Compliance	Communication Application of Procedures/Knowledge Manual Aircraft Control



E ref	Evidence Statement	Need for change	Challenge Feedback Validate TCS of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies	
122	An error that is detected and acted upon does not guarantee an inconsequential outcome. In fact, 1% of errors detected and acted upon by a flight crew link to an additional error or undesired aircraft state due to active misManagement.	1		All	234	234	LOSA 2	Error MonitoringXchecking UAS	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control	
123	There is little difference amongst the first four phases of flight in that 25-30% of errors are detected and acted upon.	1		All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control	
124	Taxi/Park has the lowest rate of errors detected and acted upon (17%) because approximately one-half of the errors in Taxi/Park are Intentional Noncompliance errors vs. about one-quarter of errors in the other phases.	1		GND	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control	
125	Noncompliance errors are typically not corrected because they are intentionally committed by the crew.	1		All	234	All	LOSA 2	Compliance Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control	
126	ManualACControl/Flight Control errors - error detection/action is notably stronger in Predeparture/Taxi-Out than in the other phases of flight (53% of ManualACControl/Flight Control errors are detected and acted upon during Predeparture/Taxi-Out vs. 21-30% of ManualACControl/Flight Control errors being detected and acted upon in later phases of flight	1		GND All	234	All	LOSA 2	ManualACControl Error MonitoringXchecking	Error Mgt	Mis A/C State	Manual Aircraft Control	
127	When compared with the other Aircraft Handling error types, it seems that error detection for ManualACControl/Flight Control errors weakens notably after departure/Taxi-Out, while Automation and System/Instrument/Radio error detection rates stay relatively the same	1		gnd All	234	All	LOSA 2	Error ManualACControl MonitoringXchecking	Error Mgt	Mis A/C State	Manual Aircraft Control	
128	Procedural error types, Checklist error detection is better in Cruise and Descent/Approach/Land while Callout error detection is better in Takeoff/Climb.	1		TO CLB CRZ DES LDG	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Mis-Sys Compliance	Application of Procedures/Knowledge	
129	The rates of error detection and action are much higher for Aircraft Handling errors than for Procedural errors.	1		All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Mis-Sys Compliance Mis A/C State	Application of Procedures/Knowledge Manual Aircraft Control	
130	Specifically, 41% of Aircraft Handling errors are detected and acted upon vs. 34% of Communication errors and 16% of Procedural errors.	1		All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control	
131	The detection and action rates for Procedural errors are shown below: o Briefing 20% o Callout 22% o Checklist 20% o Documentation 30% o General Procedural 7% o PF/PM Duty 5% o SOP Cross-Verification 9%	1	1	All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt Monitor Xcheck	Compliance	Communication Application of Procedures/Knowledge	
132	Automation errors have the best detection with action rates of all error types - 53% of Automation errors are detected and acted upon by flight crews.	1		All	234	234	LOSA 2	Error MonitoringXchecking	Automation Error Mgt	Mis-AFS	Flight Management Guidance/Automation	
133	The Aircraft handling with the lowest rate of detection are: (Many are not detected until UAS) o Unintentional vertical deviation 41% o Wrong speed brakes setting 39% o Incorrect Nav Display setting 35% o Unintentional landing deviation 32% o Wrong radar setting 30% o Unintentional lateral deviation 29% o Unintentional speed deviation 24% o Wrong power/thrust setting 22% o Wrong anti-ice setting 19%	1	1	All	234	All	LOSA 2	Error ManualACControl MonitoringXchecking UAS Training	Landing Issues Manual AC Control Error Mgt	Mis-AFS Mis A/C State Mis-Sys	Problem Solving Decision Making Manual Aircraft Control	
E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
----------	---	-----------------------	---------------------------	------------------------	-----------------	-----------------	--------------------------	--------	--	--------------------------------	---	---
134	People are not good at detecting their own error.	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	CRM Workload Distraction	SA Problem Solving Decision Making Knowledge Flight Management Guidance/Automation
135	Both Captains and First Officers detect only 5-6% of the errors that they make.	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
136	About one-quarter of the time, the pilots detect the error together	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
137	First Officers detect 18% of Captain's errors, whereas Captains detect 27% of the First Officer's mistakes.	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
138	The general pattern is consistent across error types i.e. o Captains can detect 39% of the Aircraft Handling errors made by First Officers but only 9% of their own Aircraft Handling errors o First Officers can detect 12% of the Procedural errors made by Captains, but only 4% of their own Procedural errors.	1			All	234	All	LOSA 2	ManualACControl Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
139	There is very little difference in error rate detection between the crew member position as PF and PM and very little difference between Capt and F/O as error detectors with the Capt detecting slightly more in either case. o Capt as PF $- 7\%$ vs Capt as PM $- 7\%$ o F/O as PF $- 4\%$ vs F/O as PM $- 6\%$	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
140	There is however a difference between Capt's and F/Os when action is combined with detection. The Capt is much more likely to act when detecting own error while pilot flying VS the F/O (23% vs 13%)	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
141	When the Capt is PM the rate for detecting own error and taking action is about the same as F/O as PM (25% vs 22% respectively)	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance Mis-AFS Mis A/C State Mis-Sys	Communication Application of Procedures/Knowledge Manual Aircraft Control
142	25% of all errors are recorded as Intentional Noncompliance errors, of which 96% are not acted upon.	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt Leadership	Compliance	Application of Procedures/Knowledge
143	There is a negative correlation between the rate of noncompliance and the rate of errors, other than noncompliance, detected and acted upon. That is to say that noncompliance is an inhibitor to detection and correction. (multiplier in a negative sense) This is true across all error types	1			All	234	All	LOSA 2	Error MonitoringXchecking	Error Mgt	Compliance	Application of Procedures/Knowledge
144	The significant finding is the clear advantage of Gen4-type over the Gen 3 aircraft in Type Rating results.	1			All	234	34	AQP	ATQP/AQP Generation	Error Mgt Manual AC Control	Mis A/C State Mis-AFS Mis-Sys	All
145	There is a very significant peak in NCG in the 1 <sup>st</sup> flight (OE) on all types. The peak is most pronounced on the GEN 4 TYPE. The downhill after the peak reflects the huge amount of learning and training on the aircraft during IOE. Such significant learning at this stage of the training program is not desirable. It reflects that the training does not really prepare the trainees for the real operation	1			All	234	4	AQP	ATQP/AQP Generation Learning on Line. Trainability			All
146	Post-first flight, the Gen 4 type continues at the same low level as in TR, but the curve for Gen 3 increases for RT MV and forms a secondary peak for RT-LOE.	1			All	234	34	AQP	ATQP/AQP Generation Learing on line. Trainability			All
147	Compared to the significant advantage of the GEN 4 –TYPE in TR, this advantage has to a large extent disappeared post-first flight.	1			All	234	4	AQP	ATQP/AQP Generation Trainability			All



E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
148	Generally, the data supports the notion that generation 4 aircraft are easier to train. However, the training challenge on GEN 4 –TYPE for windshear scenarios illustrates that training data needs to be analysed to optimize the training program.	1	1		All	234	4	AQP	ATQP/AQP Generation WX. Trainability			All
149	Finally, it is worth mentioning that the sensitivity of the 6-grade grading system in use at this airline provides an excellent basis for analyses, such as these.			1	All	234	All	AQP	ATQP/AQP			
150	TR/MV validation data indicate that pilots have less difficulty to perform the defined maneuvers in the GEN 4 –TYPE (gen.4) vs. gen 3 -type – with the exception of the windshear maneuvers.	1	1		All	234	43	AQP	ATQP/AQP Generation WX. Trainability	Manual AC Control	Manual AC Control	Manual Aircraft Control
151	In the most extreme case (eng failure at V1) the failure rates were 0.208 (Gen 3 –type) and 0.074 (GEN 4 - TYPE) which indicates a significant difference in difficulty.	1	1		то	234	34	AQP	ATQP/AQP Generation Trainability	Manual AC Control	Eng Fail Manual AC control	Manual Aircraft Control
152	Exceptionally, the only two items in TR/MV where the GEN 4 –TYPE proved more difficult were the two windshear items (takeoff and approach). The most extreme case is approach where the failure rates were 0.084 (Gen 3 -type) and 0.154 (GEN 4 -TYPE).	1	1		TO APP	234	34	AQP	ATQP/AQP Generation LOSA support for threats with most threats. Trainability	Manual AC Control	Manual AC Control	Manual Aircraft Control
153	The two flight phases with the highest non-conforming grades in TR/LOE were the Ground and Descent phases, which could be considered planning or preparatory phases.	1	1		GND DES	234	All	AQP	ATQP/AQP Trainability		CRM Mis-AFS	Problem Solving Decision Making Application of Procedures/Knowledge Flight Management Guidance/Automation
154	In every phase the GEN 4 –TYPE (gen 4) has a significantly lower rate of non-conforming grades than types A, B and C (all gen 3). (the only exception is the slightly better performance of type A in the After landing phase). The effect is even greater in Takeoff, Climb and Cruise. The average over all flight phases for GEN 4 –TYPE is 6.4% and for the other types 13.3%, in other words the ratio is about 1:2.	1	1		TO CLB CRZ All	234	34	AQP	ATQP/AQP Generation. Trainability Phase			All
155	There is a very significant overall increase in the non-confirming grades compared to LOEs in TR and RT. The values have roughly doubled. This appears to be an indication that the type rating course is not adequately preparing the pilots for IOE.	1			All	234	All	AQP	ATQP/AQP. Trainability			All
156	The 1 <sup>st</sup> flight profiles are still different across all types, with differences exceeding 20 percentage points.	1			All	234	All	AQP	ATQP/AQP Generation Trainability			All
157	The two flight phases where the GEN 4 –TYPE has a significantly higher rate of non-conforming grades are Ground Operations and Cruise, which are preparatory phases. Based on instructor comments, in cruise the high rate is driven by difficulties with international procedures – some problems also related to the use of Automation. For the Ground phase, the instructor comments were not specific enough to determine the types of problems.	1	1		GND CRZ	234	34	AQP	ATQP/AQP Generation Automation generation phases of flight	Automation Compliance	CRM Mis-AFS	Application of Procedures/Knowledge Flight Management Guidance/Automation
158	The profile for OE cert for all four types is roughly the same: descent, approach and landing phases are in the range of 6%-12% whereas the other phases are at a much lower rate of around 2 % (3%-4% for ground operations). This kind of pattern is not visible in any other stage of training/checking.		1		All	234	All	AQP	ATQP/AQP generation phase			All
159	In the OE cert profiles, the only significant variation across types is the rate for GEN 4 –TYPE in cruise, which is around 10% whereas the other types are in the range 2%-3%. Based on instructor comments, the reason for the high GEN 4 –TYPE rate is international procedures related to navigation.	1			CRZ	234	34	AQP	ATQP/AQP Generation phase	Compliance	Compliance	Application of Procedures/Knowledge
160	The advantage of the GEN 4 –TYPE has disappeared to the point that the Type A (Gen 3) now shows less non- conforming grades (average 3.6%).				All	234	234	AQP	ATQP/AQP Generation Trainability			
161	Even though the overall performance is similar between these two best performing types (Type A (Gen 3) and GEN 4 -TYPE), their profiles are very different, indicating that what needs to be emphasized in training is very different.	1			All	234	34	AQP	ATQP/AQP Generation Trainability			

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase S	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
162	Overall, the grades in both generations are better than in TR-LOE but for Gen 3 significantly worse than in OE certification or RT-MV.	1			All	234	34	AQP	ATQP/AQP Generation Trainability	Manual Aircraft Control	Manual AC Control	Manual Aircraft Control
163	In RT-LOE, the GEN 4 –TYPE performs generally better than the gen 3 types, but not to the extent it does in TR. The main changes are in ground and approach phases where the advantage of the GEN 4 –TYPE has disappeared (otherwise its profile is similar to TRLOE). The GEN 4 –TYPE is significantly better than Gen 3 in takeoff, climb and cruise phases – by a factor of three to one or more.	1			GND APP All	234	34	AQP	ATQP/AQP Generation Trainability			All
164	At line check, the rates are quite similar for all types. In cruise, descent, approach and landing, the Type A (Gen 3) and GEN 4 –TYPE both have higher rates of non-confirming grades than the other two types. Paradoxically, these two were the best performers during training. This is an indicator that the initial training performance does not necessarily correlate well with the actual operational performance.	1			CRZ DES APP LDG	234	234	AQP	ATQP/AQP Generation Trainability			All
165	The descent phase has the highest non-confirming grades. Based on the instructor comments, the three areas of concern are Automation, system Management and briefings. Line check	1	1		DES	234	234	AQP	ATQP/AQP Generation Trainability	Automation Compliance	Mis-AFS Mis-Sys	Communication Application of Procedures/Knowledge Flight Management Guidance/Automation
166	The biggest error category is Policy. It is equally present for all types and makes about 50% of all errors. The second biggest category is Procedural.	1			All	234	All	AQP	Competencies Error ATQP/AQP Procedures	Error Mgt Compliance	Compliance	Application of Procedures/Knowledge
167	In the OE 1st flight error distribution charts, the Gen 3 types present errors related to Proficiency and Situational Awareness while this is not the case for GEN 4 -TYPE.	1			All	234	34	AQP	Competencies Error SA ATQP/AQP Generation Trainability	Error Mgt		SA
168	The more the training cycle advances towards the line check, the more the Gen 3 types present Intentional Non- Compliance and Decision Making errors. This is not the case for GEN 4 -TYPE, which, on the contrary, presents some Intentional Non-Compliance during TR. This difference is noticeable.	1			All	234	34	AQP	Competencies Error ATQP/AQP Generation Compliance Decision making	Error Mgt	Compliance	Problem Solving Decision Making Application of Procedures/Knowledge
169	The more the training cycle advances towards the line check, the more the Gen 3 types present errors related to non-technical skills, compared to the GEN 4 -TYPE	1			All	234	34	AQP	Competencies Error ATQP/AQP Generation trainability	Error Mgt	CRM	Communication SA Leadership and Teamwork Workload Management Problem Solving Decision Making
170	3.5% of approaches are unstable	1			APP	34	34	FDA	Unstable APR/GA	Unstable APP	Mis A/C State	
171	Only 1.4% of them lead to a Go-Around	1			APP	34	34	FDA	Unstable APR/GA	Unstable APP Go Around	Mis A/C State Compliance	Application of Procedures/Knowledge
172	(0.31% of <u>stable</u> approaches lead to a Go-Around)				APP	34	34	FDA	Unstable APR/GA	Unstable APP Go Around		
173	A GA from an Unstable App causes on average 1.6 FDA risk events				APP GA	34	34	FDA	Unstable APR/GA	Unstable APP Go Around	Mis A/C State	All
174	24% rate of hi risk events during GA from unstable apprs				APP GA	34	34	FDA	Unstable APR/GA	Unstable APP Go Around	Mis A/C State	All
175	FDA cannot detect many errors; e.g. Lat Flight Plan deviations.				APP GA	34	All	FDA	Unstable APR/GA	Go Around	Mis A/C State Mis-AFS Mis-Sys	All
176	Distribution of GAs by initiation altitude: 56% ABOVE 500 FT, 31% 500 FT to flare, and 13% at Flare				APP GA	34	34	ATQP	Unstable APR/GA	Go Around Surprise		All



E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
177	The ratio of GA>200' To GA ≤200' is more than 6:1 The ratio for Stable Approaches is higher				APP GA	34	34	FDA	Unstable APR/GA	Go Around Surprise		All
178	Frequency of fits having at least one FDA event (all severity levels) is the same for stable and Unstable Appr's (83.63 vs 81.11 stable vs unstable respectively) indicating there are landing problems with stable approaches as well.				APP	34	34	FDA	Unstable APR/GA	Landing Issues	Compliance Mis A/C State Mis-Sys	All
179	Comparing events per flt (all severities) stable vs unstable is 2.24:2:84 or r=1.3 (approx)				APP	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	All
180	Comparing event rates (high severity) stable vs unstable is 8.11% vs 19.53 (approximately 2.4 times) indicating that there are more than double the hi risk events on landing with Unstable Approaches				APP	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	All
181	Comparing event rates stable vs Unstable Approaches (all severities) for the selected 10 serious landing events stable vs unstable is 14.33% to 34.52% or r=2.4 (approx)				APP	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	All
182	Comparing event rate (high severity) stable vs unstable for the set of 10 serious events is 1.96% vs 5.47% or r=2.8 (approx) indicating that there are almost 3 times the hi risk events on landing with Unstable Approaches				APP	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	All
183	Unstable Approaches are not the cause of all landing problems. This is particularly concerning if we remember that the ratio of stable approaches over Unstable Approaches is approx 27:1				APP	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	Manual Aircraft Control
184	But if we drill down we see that when Unstable Approaches occur, ther are many more of severe events during landings (Things go more wrong when unstable.)				APP	34	34	FDA	Unstable APR/GA	Unstable APP Landing Issues Error Mgt	Compliance Mis A/C State Mis-Sys	Manual Aircraft Control
185	Flights with Unstable Approaches produce more events than flights with stable approaches even in phases of flight outside of APP and LDG				All	34	All	FDA	Unstable APR/GA	Unstable APP Error Mgt	Compliance Mis A/C State Mis-Sys	All
186	Unstable APP correlate with elevated FDA event frequency in other phases of flight other than APP and LDG. This trend increases with severity: Looking at the All Events/flt exclusive of APP & LDG, the rate is 1.22 for flts with stable approaches and:1.45 for Unstable APP (r=1.19). For Hi Sev events not related to Appr & LDG the rates are 14.32% to 19.4% respectively (r=1.35)				APP All	34	34	FDA	Unstable APR/GA	Unstable APP Error Mgt	Compliance Mis A/C State Mis-Sys	All
187	Looking at a cross secton of types (5 types and 9 models) over a three year period including 1.6 million flights and approximately 5700 go- arounds) the average height above the field was over 800 at the initiation of the GA. All types in the study had a least one GA from 0 ft agl. Many GAs occured close to 2000 agl.				APP	34	234	FDA	Unstable APR/GA	Go Around Surprise		All
188	The influence of the threshold crossing height appears to have the strongest influence on the airborne distance				LDG	34	All	NLR	Generation Automation Unstable APR/GA	Error Mgt Landing Issues	Compliance Mis A/C State	Application of Procedures/Knowledge Manual Aircraft Control
189	The speed loss from flare initiation to touchdown has a very significant influence on the airborne distance				LDG	34	All	NLR	Generation Automation Unstable APR/GA	Error Mgt Landing Issues	Mis A/C State	Manual Aircraft Control
190	The difference in the actual speed and the reference speed over the threshold has a strong influence on the airborne distance.		1		LDG	34	All	NLR	Generation Automation Unstable APR/GA	Error Mgt Landing Issues	Mis A/C State	Application of Procedures/Knowledge Manual Aircraft Control
191	The Gen 3 type shows a higher tendency to over speed at the threshold compared to the other types. This is most likely caused by the fact the fly-by-wire aircraft usually fly with the auto thrust (A/THR) engaged during a landing whereas a conventional controlled aircraft with wing mounted engines disengages the A/THR as soon as the auto pilot is disengaged to avoid pitch up tendencies (like on the B737). With A/THR engaged the speed control is more accurate	1	1		LDG	34	34	NLR	Generation Automation Unstable APR/GA	Landing Issues	Mis A/C State	Manual Aircraft Control

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
192	The autolands have a lower average airborne distance than manual landings and also show less deviation from the average airborne performance	1	1		LDG	34	34	NLR	Generation Automation Unstable APR/GA	Landing Issues	Mis A/C State	Manual Aircraft Control
193	From the evidence, identified issues that show vulnerabilities in flightcrew Management of Automation and situation awareness are: • Pilot understanding of the Automation's capabilities, limitations, modes, and operating principles and techniques. • Differing pilot Decisions about the appropriate Automation level to use.	1	1		All	34	34	FAA 1996 Automation Report	Automation Generation Error	Automation	Mis-AFS	SA Problem Solving Decision Making Knowledge Flight Management Guidance/Automation
194	Flightcrew situation awareness issues included vulnerabilities in: • Automation/mode awareness. • Flight path awareness: • including insufficient Terrain awareness sometimes involving loss of control or controlled flight into Terrain) and energy awareness (especially low energy state).	1	1		All	34	34	FAA 1996 Automation Report	Automation Generation SA Error UAS Competencies	Automation Terrain Error Mgt	Mis-AFS Mis A/C State Terrain	SA Flight Management Guidance/Automation
195	Processes used for design, training, and regulatory functions inadequately address human performance issues: • users can be surprised by subtle behavior • overwhelmed by the complexity embedded in current systems operated within the current operating environment	1	1		All	34	34	FAA 1996 Automation Report	Automation Generation Error	Surprise Automation	Ops/Type Spec Mis-AFS	SA Flight Management Guidance/Automation
196	Process improvements are needed to provide the framework for consistent application of principles and methods for eliminating vulnerabilities in design, training, and operations.	1			All	34	All	FAA 1996 Automation Report	Automation Generation Error	Automation		Flight Management Guidance/Automation
197	Insufficient criteria, methods, and tools for design, training, and evaluation. Existing methods, data, and tools are inadequate to evaluate and resolve many of the important human performance issues	1	1		All	34	All	FAA 1996 Automation Report	Automation Generation Error	Automation		Flight Management Guidance/Automation
198	Designers, pilots, operators, regulators, and researchers do not always possess adequate Knowledge and skills in certain areas related to human performance.	1			All	34	All	FAA 1996 Automation Report	Automation Generation Error	Automation		Flight Management Guidance/Automation
199	Two-thirds to three-quarters of all accidents have flightcrew error cited as a major factor. Flightcrew training investments should be re-balanced to ensure appropriate coverage of Automation issues.	1	1		All	34	34	FAA 1996 Automation Report	Automation Error	Error Mgt Automation	Mis-AFS	Flight Management Guidance/Automation
200	It is important to improve how design, training, operations, and certification are accomplished. Current Regulatory standards for type certification and operations have not kept pace with changes in technology and increased Knowledge about human performance.	1			All	34	34	FAA 1996 Automation Report	Automation Generation Error	Automation		Flight Management Guidance/Automation
201	Recommendation SA-1: The FAA should require operators to increase flightcrews' understanding of and sensitivity to maintaining situation awareness, particularly: • Mode and airplane energy awareness issues associated with autoflight systems (i.e., autopilot, autothrottle, flight Management system, and fly-by-wire flight control systems); • Position awareness with respect to the intended flight path and proximity to Terrain, obstacles, or traffic; and • Potential causes, flight crew detection, and recovery from hazardous pitch or bank angle Upsets while under autopilot control (e.g., wake vortex, subtle autopilot failures, engine failure in cruise, atmospheric turbulence).	1	1		All	34	34	FAA 1996 Automation Report	Automation Upset Generation Error	Error Mgt Automation Terrain	Mis-AFS Terrain	SA Flight Management Guidance/Automation
202	<ul> <li>Provide training to proficiency of the flight Management system capabilities to be used in operations.</li> </ul>	1			All	34	34	FAA 1996 Automation Report	Automation Generation	Error Mgt Automation	Mis-AFS	SA Flight Management Guidance/Automation
203	Recommendation SA-3: The FAA should encourage the aviation industry to develop and implement new concepts to provide better Terrain awareness.	1	1		All	34	All	FAA 1996 Automation Report	MonitoringXchecking Terrain SA	Terrain	Terrain	SA
204	Recommendation SA-5: The FAA should encourage the exploration, development, and testing of new ideas and approaches for providing effective feedback to the flightcrew to support error detection and improved situation awareness.	1			All	34	All	FAA 1996 Automation Report	MonitoringXchecking Error SA	Error Mgt	Compliance CRM	SA



E ret	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
20	<ul> <li>Recommendation SA-8: The FAA should ensure that flightcrews are educated about hazardous states of awareness and the need for countermeasures to maintain vigilance. The FAA should encourage operators to:</li> <li>Develop operational procedures and strategies to foster attention Management skills with the objective of avoiding hazardous states of awareness; and</li> <li>Develop techniques to apply during training to identify and minimize hazardous states of awareness.</li> </ul>	1			All	34	All	FAA 1996 Automation Report	MonitoringXchecking Error SA UAS	Error Mgt	Compliance CRM	SA
200	Recommendation Comm/ Coord-3: The FAA should lead an industry-wide effort to share safety information obtained from in-service data and from difficulties encountered in training. This effort should be capable of assisting in the identification and resolution of problems attributed to flight crew error.	1		1	All	34	All	FAA 1996 Automation Report	Criticality	Error Mgt	Mis A/C State Compliance Mis-Sys Mis-AFS	All
207	<ul> <li>Recommendation Knowledge-2: The FAA should reassess the requirements that determine the content, length, and type of initial and recurrent flightcrew training. Ensure that the content appropriately includes:</li> <li>Management and use of Automation, including mental models of the Automation and moving between levels of Automation;</li> <li>Flightcrew situation awareness, including mode and Automation awareness;</li> <li>Basic airmanship;</li> <li>Crew Resource Management;</li> <li>Decision making, including unanticipated event training;</li> <li>Examples of specific difficulties encountered either in service or in training; and</li> <li>Workload Management (task Management).</li> </ul>	1		1	All	34	All	FAA 1996 Automation Report	Automation Competencies Generation SA	Leadership Automation	Compliance CRM	SA Problem Solving Decision Making Workload Management
208	Recommendation Knowledge-3: The FAA should strongly encourage or provide incentives to make advanced maneuvers training an integral part of the training curriculum, especially in recurrent training.	1			All	34	All	FAA 1996 Automation Report	Competencies Generation ManualACControl Upset		Upset Adverse WX Mis A/C State	Manual Aircraft Control
209	Recommendation Knowledge-5: The FAA should reassess the airman certification criteria to ensure that pilots are released with a satisfactory level of skills for managing and using Automation. Since current training is often oriented toward preparing pilots for checkrides, the airman certification criteria should be reassessed to ensure appropriate coverage of the topics listed in Recommendation Knowledge-2.	1			All	34	34	FAA 1996 Automation Report	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation
21(	Recommendation Culture-1: The FAA should ensure that research is conducted to characterize cultural effects and provide better methods to adapt design, training, publications, and operational procedures to different cultures. The results of the research should also be used to identify significant vulnerabilities, if any, in existing flight deck designs, training, or operations, and how those vulnerabilities should be addressed.	1			All	34	All	FAA 1996 Automation Report	Criticality	Automation		
211	<ul> <li>From the evidence, the HF Team identified issues that show vulnerabilities in flightcrew Management of Automation and situation awareness. Issues associated with flightcrew Management of Automation include concerns about:</li> <li>Pilot understanding of the Automation's capabilities, limitations, modes, and operating principles and techniques. The HF Team frequently heard about Automation "surprises," where the Automation behaved in ways the flightcrew did not expect. "Why did it do that?" "What is it doing now?" and "What will it do next?" were common questions expressed by flightcrews from operational experience.</li> <li>Differing pilot Decisions about the appropriate Automation level to use or whether to turn the Automation on or off when they get into unusual or non-normal situations.</li> </ul>	1	1		All	34	34	FAA 1996 Automation Report	Automation SA Generation Error	Automation Surprise	Mis-AFS	Flight Management Guidance/Automation Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
212	<ul> <li>Flightcrew situation awareness issues included vulnerabilities in, for example:</li> <li>Automation/mode awareness. This was an area where we heard a universal message of concern about each of the aircraft in our charter.</li> <li>Flight path awareness, including insufficient Terrain awareness (sometimes involving loss of control or controlled flight into Terrain) and energy awareness (especially low energy state).</li> </ul>	1	1		All	34	34	FAA 1996 Automation Report	Terrain SA Automation UAS Competencies	Automation Terrain	Terrain Mis-AFS Mis A/C State	SA Flight Management Guidance/Automation Manual Aircraft Control
21:	Processes used for design, training, and regulatory functions inadequately address human performance issues. As a result, users can be surprised by subtle behavior or overwhelmed by the complexity embedded in current systems operated within the current operating environment. Process improvements are needed to provide the framework for consistent application of principles and methods for eliminating vulnerabilities in design, training, and operations.	1			All	34	All	FAA 1996 Automation Report	Automation Competencies	Surprise	Mis A/C State Mis-AFS Mis-Sys	SA Problem Solving Decision Making Knowledge
214	Insufficient criteria, methods, and tools for design, training, and evaluation. Existing methods, data, and tools are inadequate to evaluate and resolve many of the important human performance issues. It is relatively easy to get agreement that Automation should be human-centered, or that potentially hazardous situations should be avoided; it is much more difficult to get agreement on how to accomplish these objectives.	1			All	34	All	FAA 1996 Automation Report	Competencies	Automation Error Mgt	Mis-AFS Mis-Sys	SA Problem Solving Decision Making Knowledge Flight Management Guidance/Automation

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
215	Insufficient Knowledge and skills. Designers, pilots, operators, regulators, and researchers do not always possess adequate Knowledge and skills in certain areas related to human performance. It is of great concern to this team that investments in necessary levels of human expertise are being reduced in response to economic pressures when two-thirds to three-quarters of all accidents have flightcrew error cited as a major factor.	1			All	34	All	FAA 1996 Automation Report	Competencies Error	Automation		all
216	Flightcrew training investments should be re-balanced to ensure appropriate coverage of Automation issues.	1			All	34	34	FAA 1996 Automation Report	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation
217	Regulatory standards. Current standards for type certification and operations have not kept pace with changes in technology and increased Knowledge about human performance. For example, flightcrew workload is the major human performance consideration in existing Part 25 regulations; other factors should be evaluated as well, including the potential for designs to induce human error and reduce flightcrew situation awareness.	1			All	34	All	FAA 1996 Automation Report	Automation Generation Error Competencies	Automation		all
218	The HF Team's assessment of flightcrew Management of Automation issues includes concerns in two major areas: (1) Pilot understanding of the Automation, its capabilities, behavior, modes of operation, and procedures for use; and (2) Differing pilot Decisions about the appropriate Automation level to use (if any) in normal and non-normal circumstances.	1	1		All	34	34	FAA 1996 Automation Report	Knowledge Automation Generation Competencies	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge Problem Solving Decision Making
219	There have been situations where flightcrews have either inappropriately continued to use the Automation when they found themselves in an abnormal situation.	1			All	34	34	FAA 1996 Automation Report	Automation Error	Automation Surprise	Mis-AFS	Flight Management Guidance/Automation Knowledge Problem Solving Decision Making
220	Flightcrews should be given sufficient training on using the FMS to ensure proficiency at least for those capabilities used in normal day-to-day operations. The HF Team considers the practice of expecting flightcrews to acquire these basic skills while flying the line to be inappropriate.	1		1	All	34	34	FAA 1996 Automation Report	Automation Competencies	Automation Terrain Error Mgt	Mis-AFS	Flight Management Guidance/Automation
221	The flightcrew must be able to understand the Automation's status and behavior, especially during unusual or demanding situations.	1			All	34	34	FAA 1996 Automation Report	Automation Error SA	Automation Surprise	Mis-AFS Workload Distraction	Flight Management Guidance/Automation Knowledge
222	The way pilots operate airplanes has changed as the amount of Automation and the Automation's capabilities have increased	1			All	34	34	FAA 1996 Automation Report	Generation Automation	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge
223	In fact,many sources have shown how increased Automation creates new Knowledge and skill requirements." - Dr. David Woods	1			All	34	34	FAA 1996 Automation Report	Generation Automation Knowledge Competencies	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge
224	Industry investigations have shown that the complexities of the automated flight decks make it easy for pilots to develop oversimplified or erroneous mental models of system operation, particularly mode and transition logic.	1			All	34	34	FAA 1996 Automation Report	Generation Automation Knowledge Competencies	Automation Terrain Error Mgt	Mis-AFS	Flight Management Guidance/Automation Knowledge
225	The HF Team believes it is important for flightcrews to be prepared by their training (as opposed to "picking it up on the line"), so that they will be prepared to successfully cope with probable, but unusual situations.	1			All	34		FAA 1996 Automation Report	Competencies Surprise	Automation Surprise	Mis-AFS	Flight Management Guidance/Automation Knowledge
226	<ul> <li>Pilots must have the opportunities to practice what they have learned in realistic operational settings through Line Operational Simulations (LOS) and LOFT scenarios:</li> <li>Create a larger set of line-oriented scenarios to practice</li> <li>Update these scenarios regularly to reflect the latest information about vulnerabilities from incident reporting systems or other sources.</li> <li>Expand scenarios to focus more on unique error-vulnerable situations.</li> </ul>	1		1	All	34	All	FAA 1996 Automation Report	Error	Automation Surprise	Mis-AFS Workload Distraction	Flight Management Guidance/Automation Knowledge Problem Solving Decision Making
227	Invest in more coaching and less pass/fail testing.: • Improve the debriefing of flightcrew performance after simulator sessions, IOE, proficiency checks, etc. (e.g., standardization of instructor debriefs, video replays). • Focus more on practicing how to manage the different automated systems in different circumstances, especially the judgments that have to be made on transitioning between different levels of Automation (e.g., when to turn it off or on, or to change to a different level or mode). • Encourage initial/recurrent assessments or checks to be more "learning oriented." Emphasis should be focused so that learning becomes the primary objective rather than passing or failing.	1		1	All	34	All	FAA 1996 Automation Report	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge



E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors
228	In addition to using time better, such a system might incorporate progressive assessment of individual elements/maneuvers or event sets.	1		1	All	34	All	FAA 1996 Automation Report	Competencies	Automation	
229	Assessment may also provide for levels of individual performance based on a graduated scale, rather than an "all or nothing" grading system that may diminish opportunities for learning	1		1	All	34	All	FAA 1996 Automation Report	Criticality Competencies	Automation	
230	Use Automation surprises that occur on the line as subsequent training opportunities to learn more about the Automation and how to manage it.	1		1	All	34	34	FAA 1996 Automation Report	Criticality Competencies	Automation Surprise	Mis A/C Stat Mis-AFS Mis-Sys
231	Support follow-up of Automation surprises in a simulator environment in LOFT scenarios or line operational evaluations.	1		1	All	34	34	FAA 1996 Automation Report	Criticality Competencies	Automation Surprise	Mis A/C Stat Mis-AFS Mis-Sys
232	Provide more opportunities to learn and practice, especially how to handle surprising situations.	1		1	All	34	All	FAA 1996 Automation Report	Criticality Competencies Surprise	Automation Surprise	Mis A/C Stat Mis-AFS Mis-Sys
233	Identify and correct oversimplifications in pilots' mental models of system functions.	1		1	All	34	All	FAA 1996 Automation Report	Criticality Competencies Knowledge	Automation Error Mgt	Mis A/C Stat Mis-AFS Mis-Sys
234	Promote understanding rather than using rote training.	1		1	All	34	All	FAA 1996 Automation Report	Criticality Competencies Knowledge	Automation Surprise	Mis A/C Stat Mis-AFS Mis-Sys
235	Treat mistakes and errors as opportunities for learning.	1		1	All	34	All	FAA 1996 Automation Report	Criticality Competencies Error		
236	Allow sufficient time for questions and thorough understanding.	1		1	All	34	All	FAA 1996 Automation Report	Criticality Competencies		
237	Continuous learning is one way to help ensure that pilots have the Knowledge they will need in order to effectively manage and use the Automation in a wide range of situations.	1		1	All	34	All	FAA 1996 Automation Report	Automation Knowledge Criticality Competencies	Automation Surprise	Mis-AFS
238	Initial and recurrent training should provide a clear understanding of operationally relevant Automation principles and ensure user proficiency for the cockpit automated systems	1		1	All	34	34	FAA 1996 Automation Report	Automation	Automation	Mis-AFS
239	Pilots benefit from increased: Basic airmanship, unusual attitude recovery, CRM, team Decision making, awareness of operational aspects of aircraft design philosophy, Automation and mode Management;	1		1	All	34	All	FAA 1996 Automation Report	Automation Upset Criticality Competencies	Manual AC Control Monitor Xcheck Error Mgt Leadership	Upset Compliance CRM
240	<ul> <li>Based on the incident data, accident data, and pilot and operator input evaluated by the HF team the following concerns surfaced:</li> <li>degradation of manual flying skills of pilots who use Automation frequently, or who participate in long-haul operations,</li> <li>A second area of concern is in the skills needed to perform recovery from unusual aircraft attitudes.</li> </ul>	1	1		All	34	All	FAA 1996 Automation Report	Generation Automation Competencies Upset ManualACControl	Manual AC Control Automation	Upset Mis A/C Stat
241	Flightcrews should explicitly receive instruction and practice in when and how to: (1) appropriately use Automation; (2) transition between various levels of Automation,; and (3) revert to manual flight.	1		1	All	34	34	FAA 1996 Automation Report	Generation Automation Competencies	Manual AC Control Automation	Compliance CRM Mis-AFS
242	Other important Knowledge and skill areas for flightcrews are: • understanding of Decision making processes (including team Decision making and handling unanticipated events), 2 • workload and attention Management, and • understanding of other human cognitive processes (especially cognitive biases and limitations as they apply to flightcrew problem solving in airline operations).	1		1	All	34	All	FAA 1996 Automation Report	Competencies	Surprise Leadership	Workload Distra

	Competencies
	All
e	Flight Management Guidance/Automation Knowledge
	Flight Management Guidance/Automation Knowledge
	Flight Management Guidance/Automation Knowledge Problem Solving Decision Making
1	SA Leadership and Teamwork Problem Solving Decision Making Flight Management Guidance/Automation Manual Aircraft Control
e	Flight Management Guidance/Automation Manual Aircraft Control
	Flight Management Guidance/Automation Manual Aircraft Control Application of Procedures/Knowledge
ction	Leadership and Teamwork Problem Solving Decision Making Knowledge

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
243	Checkride criteria do not include or emphasize some of the skill areas mentioned above, such as Management of Automation or other known problem areas of line operation.	1		1	All	34	34	FAA 1996 Automation Report	Generation Automation Competencies	Automation Error Mgt	Mis-AFS Mis-AFS	Flight Management Guidance/Automation Knowledge Problem Solving Decision Making
244	Maneuvers included in checkrides should be evaluated for continued relevance, be phased out.	1		1	All	34	All	FAA 1996 Automation Report	Competencies Generation			All
245	Training should also be adapted to the background of the pilot.	1		1	All	34	All	Automation	Competencies Generation			
246	Difficulty with Automation in first 6 mos on type • 25% were prepared • 14% had one encounter • 61% had multiple encounters	1			All	234	34	Survey	Automation	Automation Surprise	Mis-AFS	Flight Management Guidance/Automation Knowledge
247	<ul> <li>42 % of the Pilots believe that the training of the FMS on the type they are currently flying needs to be improved</li> <li>Only 51% believed it was adequate</li> <li>32% believed it was minimal</li> </ul>	1			All	234	34	Survey	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge
248	Only 15% of pilots felt "comfortable" operating the FMS After type rating course, 41% acquired comfort after 3 months of operation 21% acquired comfort after 6 to 12 months of operation	1			All	234	34	Survey	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge
249	Distribution of learning the operational use of the FMS : • In training: 38% • On the line: 42% • Self study: 20%	1			All	234	34	Survey	Automation	Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge
250	62% acquired comfort during 3-12 months of line experience. The results suggest that comfort in using the FMS develops over time with 3 months of line experience being the critical learning period for the respondents followed by 6 months, then one year.	1			All	234	34	Survey		Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge
251	The results suggest that 41% of the respondents felt comfortable operating the FMS after completion of their initial operating experience (IOE). The remaining 59% acquired comfort during the 3 to 12 month period following completion of training	1			All	234	34	Survey		Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge
252	Pilots often report that the learning of the flight management system (FMS) occurs over time. FMS learning on the line—42%. • FMS learning from training—38%. • FMS learning through self study—20%.	1			All	234	34	Survey		Automation	Mis-AFS	Flight Management Guidance/Automation Knowledge
253	Areas where FMS training can be improved in order of importance per surveyed pilot opinion: 1. Automation surprises - 57.1% 2. Hands on use in the operational situation – 52% 3. Transitions between modes – 32.8% 4. Basic Knowledge of the system – 26.7% 5. Programming – 21%	1			All	234	34	Survey	Automation Criticality	Automation Surprise	Mis-AFS	Knowledge Flight Management Guidance/Automation Problem Solving Decision Making Knowledge
254	In cases where Go-arounds should have been performed: • 71% of the cases neither pilot suggested a go-around	1			All	234	All	Survey	GA	Go Around Leadership Compliance	Compliance CRM Mis A/C State	Flight Management Guidance/Automation Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
255	In almost 30% of the cases when a Go-around was suggested the other pilot disagreed (Influenced by rank)	1			APP	234	All	Survey		Go Around Leadership	Compliance CRM Mis A/C State	Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
256	Psychological barriers to a go around suggests more practice in training may be beneficial, especially for all engine scenarios	1			APP	234	All	Survey	Criticality	Go Around Leadership	Compliance CRM Mis A/C State	All



E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase \$	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
257	Neither pilot suggesting a go-around implies pilots are making it work by applying judgment.	1			APP	234	All	Survey		Go Around Unstable AP	Compliance CRM	Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
258	Reasons pilots give for not going-around from an Unstable App: 1. Pilot judgment that landing is still safe even though the approach is unstable (82%) 2. There is a psychological barrier because go-arounds are rare (37%) 3. Operational inconvenience (35%) 4. Embarrassment (24%) 5. Unfamiliar with criteria (17%) 6. Mandates a report	1			APP LDG GA	234	All	Survey	GA Descision making complaince	Go Around Leadership Unstable APP	Compliance CRM Mis A/C State	Knowledge Flight Management Guidance/Automation Problem Solving Decision Making Knowledge Application of Procedures/Knowledge Leadership and Teamwork
259	Pilot response to the question of whether monitoring and cross checking is taught in training: • 47% explicitly • 34% include it implicitly • 15% marginally • 4% not at all	1			All	234	All	Survey	MonitoringXchecking	Monitor Xcheck	CRM	SA Application of Procedures/Knowledge
260	Results imply gaps in Recurrent Training re Monitor/Cross check	1				234	All	Survey				
261	Survey implies that pilots believe that monitoring and cross-checking is the poorest during the CLIMB phase because of complanency (57%) and too many secondary duties (36%).	1			All	234	All	Survey	MonitoringXchecking	Monitor Xcheck	CRM Workload Distraction	SA Application of Procedures/Knowledge Workload Management
262	90% of surveyed pilots believe that detecting and managiung errors is the most effective strategy concerning errors on the flight deck	1			All	234	All	Survey	Error	Error Mgt Monitor Xcheck	CRM	SA Problem Solving Decision Making Knowledge
263	More than 2/3 of pilots report that they get a chance to practice approach briefings during training	1			CRZ APP	234	All	Survey	Error	Error Mgt	CRM	SA Application of Procedures/Knowledge Workload Management
264	The approach briefing is included and conducted in training. However based on comments, appropriate briefing content may not be known or practiced.	1			APP	234	All	Survey		Leadership	CRM	Communication Application of Procedures/Knowledge
265	<ul> <li>Pilot responses for deviating from SOPs:</li> <li>53% say they would deviate only if it increases safety</li> <li>29% say they would deviate if no reduction in safety</li> <li>7.5% say they would never deviate from SOPs.</li> </ul>	1			All	234	All	Survey	Error Compliance	Error Mgt Leadership	Compliance CRM	Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
266	18% if pilots admit to deviating from checklists frequently	1			All	234	All	Survey	Error Compliance	Error Mgt Leadership	Compliance CRM	Application of Procedures/Knowledge
267	Approximately 21% of the pilot respondents admit to call out deviations on virtually every flight. Approximately 28% of the pilot respondents admit to call out deviation on about every 10 flights.	1			All	234	All	Survey	Error Compliance	Error Mgt	Compliance CRM Workload Distraction	Leadership and Teamwork Application of Procedures/Knowledge
268	Unstalble approach deviations are infrequent but consistent	1			All	234	All	Survey	Unstable APR/GA Error	Unstable APP	Mis A/C State	SA Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
269	Unstable approach rate calculated from Pilot Survey Reponse is consistent with LOSA and FDA rates and Survey.	1			APP	234	All	Survey	Unstable APR/GA	Unstable APP	Mis A/C State	All
270	49% of deviations from SOPs occur on every 10 flights	1			All	234	All	Survey		Compliance	Compliance	Application of Procedures/Knowledge
271	Unstable approach rate calculated from Pilot Survey Reponse is consistent with LOSA and FDA rates and Survey.	1			APP	234	All	Survey	Unstable APR/GA Criticality	Unstable APP	Mis A/C State	All

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factor
272	54% had a negative experience in training in the last 5 years	1			All	234	All	Survey	Criticality		
273	Training should be about learning, developing, strengthening skills and Knowledge.	1			All	234	All	Survey	Competencies		
274	Ensure that instruction and assessment components of training delivery are improved. Instructor quality and consistency must be addressed	1			All	234	All	Survey	Competencies		
275	Analyze current training content and emphasis to ensure content gaps are identified.	1			All	234	All	Survey			
276	Training is multi-dimensional. All dimensions must be addressed for improvement to be successful and sustainable: • Content (operational and functional) • Delivery methods and tools • Airline Culture	1			All	234	All	Survey	Criticality		
277	Training needs (per analyzed survey comments) in terms of pilot-operational discomfort by order of priority: 1. Adverse weather 30% 2. Crew Resource Management 23% 3. Non-normal checklists 16% 4. Flight management 15% 5. Airplane handling 13% 6. Systems 12% 7. Maneuvers 10%	1	1		All	234	All	Survey	Criticality	WX Automation Manual AC Control	Syst ma CRM WX Manual AC C Mis AFS
278	Over the last 20 years the World fleet and flight cycles have increased almost linearly (except for a plateau (2001–2003) and 2007 –2008) by respectively 85% and 77%.				All	All	All	CAST+			
279	Most accidents happened during the takeoff or landing phases.		1		TO LDG	All	All	CAST+	Competencies		
280	The trend over the last 20 years shows that the number of accidents has decreased by 33%.		1		All	All	All	CAST+	Generation Automation		
281	Over the last 20 years, the hull loss accident rate has decreased 50%. The rate of fatal accidents has reduced by 65%		1		All	All	All	CAST+	Generation Automation		
282	From 1991 to 2010, Runway Excursion (RE) represented by far the main accident category, accounting for 28% of all events.	1			TO LDG	All	All	CAST+	ManualACControl	Landing Issues Manual AC Control	Mis A/C St
283	Runway Excursion, together with Controlled Flight Into Terrain (CFIT), Loss Of Control (LOC), System/Component Failure (SCF) and Abnormal Runway Contact (ARC) accounted for 78% of all accidents.	1	1		All	All	All	CAST+	ManualACControl	Manual AC Control Landing Issues System Malfunction	Upset Syst mal Mi
284	Runway excursion (RE), which accounted for 26% of all accidents between 1991 and 2000, increased by almost 10% in the 2001- 2010 period	1			TO LDG	All	All	CAST+	ManualACControl	Manual AC Control Landing Issues	Mis A/C St
285	Between the 90 decade and 2000 decade CFIT decreased 17% to 9%	1	1		All	All	All	CAST+	Terrain	Manual AC Control Landing Issues	Terrain
286	Between the 90 decade and 2000 decade Loss or Control accidents remained steady at around 13%.	1	1		All	All	All	CAST+	-	Terrain	Upset Mis A/C St
287	Between the 90 decade and 2000 decade System Malfunction accidents decreased (14% to 11%)	1			All	All	All	CAST+	-	System Malfunction	Syst ma
288	While abnormal runway contact remains relatively high, between the 90 decade and 2000 decadeit decreased significantly.	1	1		TO LDG	All	TO LDG	CAST+	ManualACControl	Landing Issues Manual AC Control	Manual AC C

tors	Competencies
mal RM /X C Ccontrol AFS	All
C State	
I Mis A/C State	All
C State	
rain	SA
set C State	All
mal	
C Control	



E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
289	Between the 90 decade and 2000 decade Land Short or Undershoot Runway Excursions doubled from 3% to 7% (Manual Handling)	1	1		APP LDG	All	All	CAST+	ManualACControl	Manual AC Control Landing Issues	Mis A/C State	Manual Aircraft Control SA
290	Looking at Runway Issues comparing the 90 decade and the 2000 decade, the percentage of accidents for wihich runway issues were considered causal was almost 50% (47% and 49%)	1			TO LDG	All	All	CAST+	ManualACControl	Manual AC Control Landing Issues	Mis A/C State	Manual Aircraft Control SA
291	Undershoot emerged as important categories (ie > 5%) during the 2000 decade a 8%	1			ΤΑΧΙ	All	All	CAST+	ManualACControl	Manual AC Control Landing Issues	Mis A/C State	Manual Aircraft Control SA
292	Over the last 20 years, 84% of all accidents happened during the approach/ landing or takeoff/climb phases. The approach/landing is by far the most critical of the flight phases, accounting for 63% of all occurrences. The takeoff/climb phase is the second most hazardous phase, accounting for 21% of all events.	1	1		APP LDG TO CLB	All	All	CAST+	Phase	Manual AC Control Landing Issues	Mis A/C State	Manual Aircraft Control SA
293	Accidents by Phase: o Parking/Taxi 4% o Takeoff/Initial Climb 16% o Climb 5% o Cruise 7% o Descent 5% o Approach & GA 22% (GA 3%) o Landing 41%	1	1		All	All	All	CAST+	Phase	Landing Issues Unstable APP	Mis A/C State	All
294	EGPWS / TAWS technology has entered airline and corporate operations during the last five years; to date no aircraft fitted with such a system has been involved in a CFIT accident.	1			All	All	All	TAWS Saves	Terrain	Landing Issues Terrain	Ground manoeuvring Mis A/C State	
295	The 'saves' confirm that TAWS is a very effective safety tool yet it still depends on crew action for the last defence; always pull up when a warning is given.	1			APP	All	All	TAWS Saves	Terrain	Terrain	Terrain Compliance	SA Application of Procedures/Knowledge
296	98.7 % of the Long aircraft variant landings had a maximum vertical acceleration less than 1.5g.	1		1	LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues	Terrain	SA Application of Procedures/Knowledge
297	Long aircraft type variant landings with vertical acceleration above 1.5g were more frequent compared to the shorter versions resulting in higher scatter of the landing assessment parameters.	1			LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Knowledge Application of Procedures/Knowledge Manual Aircraft Control
298	for 1.3% of the landings, the long aircraft type variant had a higher rate of high vertical acceleration landings compared to the shorter type variant. From the data - the probability of a landing > 1.75 g was found to be 0.25 % on long aircraft type variant compared to 0.04 % on shorter versions.	1			LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Manual Aircraft Control
299	it was noted that the obvious difference in inertia implied that in certain circumstances (such as recovery from a steep approach gradient) more anticipation would be needed in the long aircraft type/variant than the shorter versions	1			APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Manual Aircraft Control Knowledge
300	Speed tracking on approach is not significantly different between the two models, and statistical variations in approach speed are not related to vertical speed (Vz) at touchdown.	1			APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control Surprise	Manual AC Control	Manual Aircraft Control SA
301	Pitch stick inputs required for the flare do not change with cg, which implies that the pitch characteristics in the flare are not significantly affected by cg.	1			LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Unstable APP	Mis A/C State Compliance	Manual Aircraft Control Application of Procedures/Knowledge
302	One of the most interesting results is a strong correlation between high Vz at touchdown and a lack of effective pitch stick input. This is either due to insufficient or late aft input and provides a clear implication that pitch control authority is not in question	1			LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Manual Aircraft Control SA Application of Procedures/Knowledge
303	Compared to the shorter version, statistically the long aircraft type variant shows: – A slightly steeper approach gradient at the start of the flare – More forward stick input below 150 ft – A shorter time from flare to touchdown	1			APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control	Manual Aircraft Control SA

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase \$	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
304	A dedicated examination of all the hard landings* available in the database confirmed that a majority (60%) of these cases involved a late "Duck Under" (pilot action to steepen the slope at or just below 150 feet AFE to bring the touch down point closer to the threshold), followed by an insufficient flare (too low and/or not enough nose up pitch input) * Landings having a maximum vertical acceleration > 1.75g (Note that this is not the AMM definition of hard landing	1			APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control Mis A/C State	Manual Aircraft Control SA Application of Procedures/Knowledge
305	There is a need for pilots to better anticipate and monitor the final approach and flare on the long aircraft type variant has become evident.	1			APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control Mis A/C State	Manual Aircraft Control SA
306	To avoid hard landings, handling recommendations include: - Maintaining a stable slope prior to flare (no "duck under") - Avoidance of under flaring - Avoidance of significant nose down inputs during flare - Crosswind landing reminders - Reminder of pitch monitoring and aircraft pitch geometric limits	1			APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control Monitor xcheck Surprise	Manual AC Control Mis A/C State Compliance	Manual Aircraft Control SA Communication Application of Procedures/Knowledge
307	It is recommended to highlight differences to pilots receiving training to operate long aircraft type variant either in a mixed fleet or single fleet environment. These differences can be highlighted within the scope of type rating training and recurrent.	1			APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing issues Unstable APP Manual AC Control Compliance Error Mgt	Crosswind Compliance CRM mis A/C state	Knowledge Application of Procedures/Knowledge Manual Aircraft Control
308	On difficult runways, use of dedicated markings in conjunction with a predetermined Auto-brake setting may increase crew confidence to achieve the proper touchdown point without the need to duck under.	1			APP LDG	4	4	Long Aircraft FDA Study	Hard landing	Landing Issues Manual AC Control	Manual AC Control Mis A/C State Compliance	Knowledge Application of Procedures/Knowledge Manual Aircraft Control
309	<ul> <li>Airlines are also encouraged to use their own FDA system in order to monitor all operations for identification of precursors to hard landings. (e.g. duck under, high slope, pitch oscillations, specific airports, etc.)</li> </ul>	1			APP LDG	4	4	Long Aircraft FDA Study	Hard landing			
310	Long aircraft with high power tend to have: • Lower rotation rates which could result in degraded TO performance • Require a greater attention to making a smooth rotation to avoid PIO on takeoff.	1			то	4	All	Long Aircraft FDA Study	Rotation Technique PIO		Mis A/C State Compliance	Manual Aircraft Control SA Application of Procedures/Knowledge
311	Go-Around Maneuvers 1. I suggested a goaround, but the other pilot disagreed (20%). 2. The other pilot suggested a goaround, but I disagreed (8%). 3. Neither pilot suggested a goaround (72%).	1			APP LDG GA	All	All	Survey	GA Descision making compliance	Go Around Surprise	Compliance CRM	Communication Leadership and Teamwork
312	Pilots report high levels of assertiveness in 4 of the 5 categories, with taking control from the pilot flying registering the lowest at 49%. The level of assertiveness appears to be linked to the level of resulting intervention. Tasks such as identifying a deviation (92%) or proposing a checklist (91%) are more likely to be asserted than tasks such as proposing a GA (83%) or demanding a GA (80%).	1			APP LDG GA	All	Ali	Survey	GA Descision making assertiveness	Leadership Error Mgt MonitorXcheck Go Around	Compliance CRM	Communication Leadership Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
313	Most pilots (93%) believe detecting and managing errors is the most effective strategy for error management (Figure ). A small percentage of pilots (7%) believe that errors should not be committed.	1		1	All	All	All	Survey	MonitoringXchecking error management	Moniter Xcheck		Leadership and Teamwork Application of Procedures/Knowledge
314	a majority of the respondents (53%) would deviate if they believe it increases safety and twentynine percent would deviate if it resulted in no reduction in safety. Overall, most (83%) pilots would exercise judgment to intentionally deviate from company SOPs with their judgment being the pilot's assessment of safety. Another seven percent reported they would never deviate.	1			All	All	All	Survey	Compliance Error	Error Mgt Leadership	Compliance CRM	SA Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
315	Intentional deviations from checklists occurred a reported every ten flights by 13% of the respondents, a few times a year by 30% of the respondents, and once a year by 36% of the respondents. Very few (4%) reported a deviation on every flight. Checklist deviations occurring at this high of a rate suggest other factors may be involved not related to compliance.	1			All	All	All	Survey	Compliance Error	Error Mgt Leadership	Compliance CRM	Application of Procedures/Knowledge



E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase S	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
316	We asked, "In the last six months, did you encounter an operational situation where you did not feel comfortable?" Just over half (54%) of the respondents answered yes (Figure 18). Within that category, 57% of the reporting pilots were ranked captain and 43% were ranked first officer.	1			All	All	All	Survey	Knowledge Automation Competencies criticality	Surprise	Syst mal CRM Adverse WX Manual AC Control Mis AFS	SA Problem Solving Decision Making Knowledge Application of Procedures/Knowledge
317	Skill loss can be substantial and generally increases with the duration of non-use / non-practice	1			All	All	All	Skill Decay & Skill Retention Studies	Criticality	ManualACControl Go Arounds Automation Unstable APP Landing Issues	Manual AC Control	All
318	Retention of open-loop tasks was better than of closed-loop tasks.	1			All	All	All	Skill Decay & Skill Retention Studies	Criticality	Error Mgt Leadership System Malfunction		All
319	Skill decay for "accuracy" tasks was three times higher than for "speed" tasks, i.e. for tasks where it was necessary to perform the trained skill fast.	1			All	All	All	Skill Decay & Skill Retention Studies	Criticality	Automation		All
320	There was no evidence of significant skill decay among pilots in 12-month training cycle (Maneuver Validation vs. First Look grades).	1		1	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Landing Issues	Manual AC Control	Manual Aircraft Control Application of Procedures/Knowledge
321	There were no detectable trends in the MV-FL difference within the 2000 -2008 period.	1		1	All	All	All	Skill Decay & Skill Retention Studies	Criticality	Manual AC Control Landing Issues	Manual AC Control	Manual Aircraft Control Application of Procedures/Knowledge
322	There was no significant difference between normal vs. abnormal maneuvers; except for the takeoff flight phase, where the "normal" got significantly better grades at all times during the 12-month retention interval.	1		1	All	All	All	Skill Decay & Skill Retention Studies	Criticality	System Malfunction Compliance Manual AC Control	Syst mal Compliance	Manual Aircraft Control Application of Procedures/Knowledge
323	The results suggest pilots maintain their proficiency across the 12-month re-training interval				All	All	All	Skill Decay & Skill Retention Studies	Criticality	Go Arounds System Malfunction Landing Issues	Syst mal Compliance	Manual Aircraft Control Application of Procedures/Knowledge
324	Accidents by Phase of Flight: a. Pre-Flight and Taxi-Out – 0.7% b. Take-Off – 11.9% c. Climb – 19.1% d. Cruise – 15.8% e. Descent – 4.3% f. Approach – 35.6% g. Land – 11.9% h. Post-Flight and Taxi-In - 0.7%	1	1		All	All	All	ACC CAA	Phase Criticality			
325	General Operational Threats by Rank - (TEM Phase) a. Human Factors – 32.3% b. Compliance failure – 19.1% c. Mishandled Aircraft – 13% d. Mismanaged Aircraft State - 7.8% e. Procedures – 6.9% f. Performance – 4.2% g. Mishandled systems (other than FMS) – 3.8% h. Workload Distribution – 3.4% i. Fatigue – 3.4% j. Mishandled Auto-Flight – 1.9% k. Performance Miscalculation – 1.7% l. Deficiencies in Manuals – 0.8% m. Physiological – 0.8% n. Cabin – 0.6% o. Deficiencies in Charts – 0.4%	1	1		All	All	All	ACC CAA	Threats and Errors TEM	Automation Compliance Error Mgt	Compliance Def Manuals Def-Charts Fatique CRM Workload Distraction Pressure Mis-AFS Mis A/C State Mis- Sys Manual AC Control	Workload Management Application of Procedures/Knowledge Flight Management Guidance/Automation Manual Aircraft Control

E ref	Evidence Statement	Need for change	Challenge Validate TCS	Feedback of Changes	Flight Phase	Gen Specific	Applicability to Gens	Source	Keywords	Training Topics	Factors	Competencies
326	Five most common causal factor groups (CAP 780) a. Omission/inappropriate Action – 36% b. Filght Handling – 28% c. Lack of Positional awareness – 25% d. Failure of CRM – 22% e. Poor Judgment/Airmanship – 20%	1	1		All	All	All	ACC CAA	Causes Criticality Errors SA	Manual AC Control Error Mgt Leadership	CRM Manual AC Control	Application of Procedures/Knowledge Leadership and Teamwork Manual Aircraft Control
327	The global fatal accident data was re-analyzed by means of the ITQI Intuitive Threat Matrix.	1	1					ACC CAA				
328	Analysis, by phase of flight clearly shows that the greatest risk is within the approach phase of flight.	1	1		APP	All	All	ACC CAA	Phase Criticality			
329	Further analysis to determine the areas of general operational threat it is clear that the major threat is that of the non-technical area of human factors	1	1		All	All	All	ACC CAA	Criticality CRM	Error Mgt Leadership Compliance	CRM Workload Distraction Pressure Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge
330	The UK Civil Aviation Authority publications CAP 776 Global Fatal Accident Review 1997 – 2006 and CAP 780 Aviation Safety Review 2008 both suggest that the main areas of concern are non technical ones by nature	1	1		All	All	All	ACC CAA	Criticality CRM	Error Mgt Leadership Compliance	CRM Workload Distraction Pressure Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge
331	(CAP 776) demonstrates that the top two primary causal factors, accounting for 36.4% of accidents, are non technical in nature. This is further reinforced by data from the CAP 780 which shows that the top five most common causal factors groups contain a significant component of non-technical elements (Human Factors).	1	1		All	All	All	ACC CAA	Criticality CRM	Error Mgt Leadership Compliance	CRM Workload Distraction Pressure Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge
332	(CAP 780) again demonstrates that the most frequently occurring causal factors are crew related	1	1		All	All	All	ACC CAA	Criticality CRM	Error Mgt Leadership Compliance Manual AC Control Compliance	CRM Workload Distraction Pressure Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	SA Leadership and Teamwork Workload Management Problem Solving Decision Making Application of Procedures/Knowledge
333	Top 10 ASR's in operations in percentage of reports o Aircraft limit exceedance 9.2% o Unstable approach 8.3% o Turbulence 7.6% o Flight crew missed selection 6.3% o Traffic on runway during short final 5.9% o Windshear 4.2% o ATC traffic separation 3.8% o Checklist/SOP use 3.5% o Manual handling 3.4% o ATC communication lost 3.1%	1	1		All	All	All	Incid Anal STEADES		Manual AC Control Automation WX Unstable APP Compliance	Adverse WX ATC Loss of comms Traffic Windshear Compliance Mis A/C State Mis-Sys Manual AC Control	Communication Application of Procedures/Knowledge Workload Managementt SA
334	Top 10 ASR's in training flights o Unstable approach 16.7% o Manual handling 9.4% o Flight crew missed selection 9.2% o Heavy/hard Landings 7.5% o Deep (long) Landings 5.5% o Procedures (operational) 5.2% o EGPWS G/S Alert 4.3% o Aircraft limit exceedance 3.6% o Checklist/SOP use 3.3% o Aircraft anti/de-ice 3.1%	1	1		All	All	All	Incid Anal STEADES		Unstable APP Manual AC Control Error Mgt Landing Issues Compliance WX	Adverse WX Compliance Mis-AFS Mis A/C State Mis-Sys Manual AC Control	Leadership and Teamwork Application of Procedures/Knowledge Manual Aircraft Control Workload Management
335	There are twice the percentage of ASRs for unstable approaches during training flights compared to the main ASR database	1			All	All	All	Incid Anal STEADES	Criticality	Unstable APP	Mis A/C State Compliance	Leadership and Teamwork Application of Procedures/Knowledge Manual Aircraft Control Workload Management
336	Heavy/hard landings is number 4 in terms of percentage of reports during training flights but outside of the top twenty for normal ops.	1	1		All	All	All	Incid Anal STEADES	Criticality	Landing Issues	Mis A/C State	Manual Aircraft Control
337	Manual handling is number 2 in percentage of ASRs for training flights (9.2%) but number 9 for normal ops at 3,5%.	1	1		All	All	All	Incid Anal STEADES		Manual AC Control	Mis A/C State	Manual Aircraft Control
338	Flight crew mis-selection is ranked approximately the same in both databases but generates a 50% higher the percentage figure of reports during training flights as compared to normal operations.	1	1		All	All	All	Incid Anal STEADES		Error Mgt	Mis-Sys Mis A/C State Mis-AFS	Leadership and Teamwork Workload Management
339	Problems with checklist use and SOPs is ranked 8 <sup>th</sup> in ASR percentage in the main database and ranked 9 <sup>th</sup> for training flights. The percentage of occurrence for both is nearly the same at approximately 3.5%.	1	1		All	All	All	Incid Anal STEADES	Criticality	Compliance Error Mgt	Compliance Workload Distraction	Application of Procedures/Knowledge Workload Management

# **APPENDIX 13** MATRIX OF SUMMARIES FROM THE EVIDENCE TABLE

# INTRODUCTION

This appendix contains the 15x17 Summary Matrix and the 15 Analysis Worksheets, both of which are used to consolidate information from the Evidence Matrix. The Summary Matrix is essentially used to transform the results from the data sources to the training topics after which the worksheets further consolidate and structure the results to highlight training effect and criticality.

### **13.1 SUMMARY MATRIX**

	1	1	1	1	1	1	1	EVIDENCE TABL	E - SUMMARY ANALYSIS	1	1	1	1	1	1	1	
	Unstable Approach	Automation	Error Management	Manual Aircraft Control	Go-Around	Adverse Weather	System Malfunction	Terrain	Surprise	Landing Issues	Compliance	Leadership	Mismanaged Aircraft State	Upset	Generational Aspects	Phase of Flight	Training Effect
LOSA Study 4.1	Unstable approaches emain a consistent problem at a rai une sent a landing. The creas in more class two memory and anding. The creas in more class two memory and a submit and any efficience consistence appropriate stabilized approach creas. Landings are often performed in the winoig accost configuration.	The overacting problem with automation for the flight have at lead on automation error with amount and more at decide on automation error with amount and more and excellence and using the patients and the more attraction and using the automation and/or flying manually at ouppropriate times.	A key design for messaging tight once even is monotoning and crasscharking. The situation is critical as just one 25% of the errors made by the fight model of the strand strate of the fight model. The situation is a situation of the strand strate with the model of the situation of the situatio	According to LDGA, menual costor errors, white not the menu through type of error of 15% coordinated by Right, and end should be a metall. Then the imposed technique, fight crease groups or show the provide technique, fight crease groups or a through end with a fight crease groups or the imposed technique, fight crease groups or the advected section of the lacking exact that the imposed technique, the lacking exact the show the show the show the lacking exact the show the show the show the show the show the show the show the show the show the show the show the show the show the show the present end the show the show the show the show the show the show	According to 1054, go encore from unclash approaches according that the time portrary to differ L control by the difference of the time of the second second second second second second method of the one parameter from an unclash detabative When a go-amount from an unclash detabative When a go-amount from an unclash detabative the second second second second second detabative the second second second second second second second detabative the second second second second second second second detabative the second second second second second second second second detabative the second sec	Workburk is the number 1 head to the phase. NY of all Rights encounter phase. NY of all Rights encounter the second second second second second distribution of the second second second distribution of the second second second second second second second second and the second second second second second second second second second second second second second second second second second second second the second second second second the second second second second sectors is second second second the second second second second the second second second second sectors is second second second sectors is second second second sectors is second se	There is a high degree of interfaced non-compliance of unequested system methods in the food framework of the second system methods in its hogh of the second second system methods on its hogh of the SOL database. System methods or lands 3 of as a combuctly factor in UAS.	LOGA holicities that proper attinuity use to a stream in one of the most important terraria is one of the most important memory of the total stream in the stream environment tend to be completent to terral thread.	<sup>40</sup> Quis generally a surprise to crew and non- tracking and the second second second second second in number of the second second second second second mismanaged bread in LOSA database.	His of all landings in LOBA database ress in an abbornial landing. The number 3 no compliance item in the database is landin from an undataba sequencial. Arriva data detected as they rank 2 <sup>-th</sup> in lands databased detected as they rank 2 <sup>-th</sup> in landing and task detected as they rank 2 <sup>-th</sup> in landing and task detected as they rank 2 <sup>-th</sup> in landing and task detected as they rank 2 <sup>-th</sup> in landing and task detected as they rank 2 <sup>-th</sup> in landing and task detected as they rank 2 <sup>-th</sup> in landing and task detected as they rank 2 <sup>-th</sup> in landing and task detected as they rank 2 <sup>-th</sup> in landing and task detected as they rank 2 <sup>-th</sup> in landing and task detected as the landing as the landing and task detected as the landing as the landing as the detected as the landing as the landing as the landing as the detected as the landing as the landing as the landing as the detected as the landing as the landing as the landing as the detected as the landing as the landing as the landing as the detected as the landing as the landing as the landing as the detected as the landing as the landing as the landing as the landing as the detected as the landing as	Note to a significant genetities consistent to between the morphanese and LMBs, which there is a nonpartice constrained to there must an experiment of the advances are non-completed ensemble. The best must be the significant of the significant of the significant of the must be the complete the significant of the must be the complete the significant of the must be the complete the significant of the must be the complete the significant of the must be the must be the significant of the must be br>must	n Lastership is an effective positive catalysi in terms reading errors per tight, provide that it is accompanies by good commonitations.	Omthor calcul deviations are associated with the grantial calls, (DV) of orinazions combular constate posterior and the calculation of the calculation constate posterior and calculation of the calculation constate posterior and the calculation of the calculation building entropy and the calculation of the calculation building entropy and calculation of the calculation building entropy and calculation of the calculation and calculation of the calculation of the calculation of the calculation and the calculation of the calculation of the calculation of the calculation and the calculation of the calculation of the calculation of the calculation and the calculation of the calculation of the calculation of the calculation of the calculation and the calculation of	Intersonal Blank	Intertonal Bank	Weather is considered a major thread in all tight phases. LOIA data about the tight the top have differed mutacellicit in time of the top have differed mutacellicit in time of the top about the time of the top the top top the top top the top top the top	The LTSS shady area specifically improve in address investigation of the most synthetic thirdy is not the specifically improve the specifical synthesis and the s
EBT Flight Data analysis 4.2.1	The FIGA-instability approach date is sound 2.5%. This is consistent cares and types and geographical approxi- tions are as an entry field to the situation of the sound of the approaches. Sound the unrelated approaches geographical approaches approaches. Sound the unrelated approaches geographical approaches. Sound the unrelated approaches geographical approaches. Sound the unrelated approaches geographical and approaches and approaches becomes even and approaches and approaches becomes even and approaches and approaches becomes even and approaches and approaches becomes approaches and approaches and approaches becomes approaches and approaches and approaches becomes approaches and approaches and approaches approaches approaches approaches approaches approaches approaches and approaches.	n Interitorial Bank	Interioral Bank	Intertional Bank	Only 14% of unstable approaches load to a po- amonic who an PDA all over table of the amonic who are PDA all over table of the post- ance panel as Q24. Unit head not an experi- tation may of the over the fit cold could be heading different from Road brake. (Include heading different from Road brake.)	intentionall Blank	Interformal Blank	Intertional Blank	Intertional Blank	Interdonall Blank	Interforal Blank	Intertorial Blank	Interforal Blank	intentional Blank	Interctional Blank	Intertonal Blank	Interfored Bank
Long body aircraft Studies 4.2.2	interdonall Blank	Interioral Bank	Interstonal Bank	Long body asicraft are more prone to high "O" landings. Because of geometric considerations, because the second second second second second second second second second second second second steper approach gradients just profer the se and as an entities designeement in consenside. The androgen are observed, avoid set in these just- andings in crossived, avoid set in these just- ment of the second public induced descillations.	rinertonal Bank	In low visibility and/or crosswind conditions common errors such as 'duck under' and misalignment with the numary centreline are more critical in long body arrowt.	intertional Black	Hardonal Bank	Intentional Blank	Landing events are satisfically more like the long body strendt, especially with mapped to havy landings. Pilets need to be especially cogrant of not dtuding, under the gideatope. In addition, pilots ened to understandt han ad differences of ground speed and momentum as well as processful afferences to hill landing and vertically reaching from the extended angh between the main grad and coopsil	y In long alrcaft, following flat recommendations of th manufacture random is GPP and training implate the trackould used togeth of Trainings. Application of tails-of procedures is equally import in the prevention of "plot induced oscillation" during take of t	e re Interdoraal Baank	Interdonal Blank	Intentional Blank	Interdonal Blank	intentional Blank	Intertional Blank
LANDING DURING ILS APPROACHES 4.2.3	Intentionall Blank	Interitorial Blank	Interdonal Blank	Intentional Blank	Intentionall Blank	Intertionall Blank	Intentionall Blank	Intentionall Blank	Intentionall Blank	FDA statistical analysis on a large sample of Gen 3 and 4 jet aircraft indicated that automaticin (autoband and autothretishiautothnust) provide greater baing more accurate than Gen 3 jet aircraft. The lwo parameters most affecting airborne distance are threshold crossing height and airspeed over-speed at threshold, in that order.	at Intentional Blank	Intentional Blank	Intentionall Blank	Intentionall Blank	Intentional Blank	Intentional Blank	Intentional Blank
AQP Study 4.3.1	Hardonal Bank	Automation is an issue of concern regarding assessment In AZP in cost the parently and execution in teams of any it has index should execute a definition of the other and the index should execute a definition of the other index should be a state of the other other other other other index should be a state of the other other other other other index should be a state of the other other other other other index should be a state of the other other other other other index should be a state of the other other other other other other index should be a state of the other other other other other other other index should be a state of the other other other other other other other index should be a state of the other other other other other other other index should be a state of the other other other other other other other index should be a state of the other other other other other other index should be a state of the other other other other other other index should be a state of the other other other other other other other index should be a state of the other other other other other other other index should be a state other other other other other other other other other index should be a state other other other other other other other other other other index should be a state other	In all ACP evaluations, whether type railing counters (12) or neurometrizaning (CC), policy and procedural error types are instead 1 <sup>+</sup> and 2 <sup>+</sup> , accounting for the particip travel and the counter granting (CC) and errors relating to profession, statistical maternation of more relating to profession, statistical maternation of the statistical profession of the statistical maternation and the statistical of the statistical maternation and the training cycle progresses from the type railing to econtrol like chubics.	Training results in AQP show guicker mastery of manual handing skills in initial training, patiently the case in gen4 across and white any show the second straining to the case 4.	interdonal Bank	Interdonali Blank	Intertional Bank	Intertional Bank	Intertional Blank	Interdonal Blank	The baggest problem with NCGs (non-conforming promptions with an extra problem submitting both, promptions with an interplating submitting both, promote committel in addition, non-compliance with make where the create submitting both the problem procedures of BCS. Built from international fights show that the CPC place has significantly none WCIs than compare lights.	t t Interdonal Bank	Interdional Bank	intentional Blank	Certain manual askcaf control manouver skills are detained askar to acquire in Can 4 per ascad, when surgence of cars 1 per 1. The askcategies in manual to manual the cars 1 per 1. The askcategies in manual the manual the sing (Cars) takes in the single as a manual the sing (Cars) takes in the single ask and the basis and the first period of the single single askcategies and the single single single single single single single single single asks for the single single single single single single periodics, and to the toos of askschmitter is but parts and to the singl	During the type-rating course (H2) the crews of Gen 4 air anoral partormed coviderably totler observations. For exercise, the coviderably totler variations for exercise the solution of the coviderable over manufacted this advantage but to a laster over manufacted this advantage but to a laster totler business and anoralism and the coviderable advantage of the coviderable magnet to first properties of an advantage and the coviderable advantage of the coviderable magnet to first properties of the coviderable magnet to first properties of the coviderable magnet to first properties of the coviderable advantage was be solutional to solution the transfer advantage of the coviderable advantage and the coviderable advantage of the transfer properties for the operations and the coviderable advantage properties for the operations advantage of the coviderable advantage properties for the operations advantage of the coviderable advantage ad	Certain manual aircraft control manoaure skills are demonstrably assert to acquise in Cen 4 pH aircraft, shere and the control of the contr
ATQP 4.3.2	Unstable approaches were closely monitored during the transition to ATCP and the rate of unstable approach manuales constant, indicating that a major change in approaches are concerned. Approximately (5%) of go- anunds during the transition resulted from unstable approaches. The concerned Approaches in concerned approaches the concerned Approaches in detarances, mismanaged visual approaches, mismanaged energy, and poor manual aircraft control.	Mismanged tabl fight is a major factor, contributing to unstable approaches and go-around errors, both in maning and line operations. This remains constant, whether in the all engines operating, or engine-out case.	But possible and toning due contine that once have predicters with homoworks the aim out choose practiced. Proceeding and memal control will be enforcement, as these areas are where much of the enforcement, as these areas are where much of the monocourt in advance of courts planning and energy management also need specific training.	The evidence gathered during ATQP shoes that manual accurat control is a problem to model accurate and more practice in hosting is needed.	Mismanagement of stads flight systems, resulting in unstable approaches, are the stopped cause for ga- arounds in expections. A sparificant processing of a around is expections. A sparificant processing of a around is expection and a sparificant processing and violation and a sparificant processing and violation of any space of the space of the space of the space of any space of the space of the space of the space of any space of the space of the space of the space of any space of the space of the space of the space of any space of the space of the space of the space of any space of an	intertionali Blank	Proceedings and functing associated with monourses after anging failute result in the highest transformers after anging failute result in the highest result of uncorpolate proformance in transform. The advance of the advance of the second transformer of proceedings and manual angular control.	kterional Bank	Surprises need to be incorporated in training particularly with respect to both from a proactive and reactive perspective	Intertional Blank	Intentional Blank	ATOP training and operational data provide encouraging results showing that leadership advance remarkable improvement in training as well as bette performance on the line.	Budies during ATOP highlight the need for people training in glanning, and energy management to reduce minimanged arcard table. Co-arconaccionica to be minimanged approaches. During the go-arcourt, riserianged autoratifyti continees to result in minimanged aircraft states including tag over-opends and SOP violations.	Intentional Blank	interdoral Blank	APP TO and GA appear mod In the ATOP data is explored in Narling course. DSTs in note because of planning and energy management problem. Autofight accounts for most of the problem autofight accounts for most of the dynamic induce of the phase.	Data gathered from operations and training show that ATOP type training is effective in improving one performance. Indexing the side duratical exponences in addition to training disclosed to planning and energy management, as well as auchtight training in lighty dynamic and unexpected shattons
Pilot Survey TBD 4.4	The plot party share the unitable approaches are a and plot provide the plot of the plot plot plot plot plot plot plot plot	The point annuny was banky ortical of submatche banky damp the load type rating. Cell 2016 of the points and support is during the admittant when reasoning the mediate strength of the submatcher when reasoning the mediate having increases and the submatcher of the during the first is normaling ding where the mediate having having requiring them to learn to sub- matcher of the submatcher of the submatcher of the submatcher of the submatcher of the submatcher of the submatcher of the submatcher to the submatcher of the submatcher of the submatcher of the submatcher of the submatcher to the submatcher of the submatcher of the submatcher of the submatcher of the submatcher to the submatcher of the submatcher of the submatcher of the submatcher to the submatcher of the submatcher of the submatcher of the submatcher to the submatcher of the submatcher of the submatcher of the submatcher to the submatcher of the submatcher of the submatcher of the submatcher of the submatcher to the submatcher of the submatcher	Simoni all pido talleve that the most important balaxy on error management is monotoring and conscibucing and that is emphasized indicated the time. There are traverse, problems in error management that are not on all addressed taken the traverse are traverse, problems in error management that are not on all addressed taken that the traverse are traverse and the traverse problem and the traverse are traverse to the traverse and the traverse are traverse proceeding datas, the traverse are traverse and datas the monitoring pilot among datas the addressed taken the traverse are used and and the the monitoring pilot among datas the address that the traverse are traverse and the the monitoring pilot among datas the address that the traverse are traverse and the traverse and the traverse and the traverse are traverse and the traverse and the traverse are traverse and traverse and traverse and traverse and traverse are traverse	The plots were allowed to make whatever common or any training subject and head added to the results of the best added to the results of the the main array was adverted to the results of the the main array was adverted to the results of the the results are plottered accounts of the advected of the account costs, make a handling and account costs, make a handling and handling and the second of the handling and	The survey shows as pictor ready adnet that they are not going around per the adness 50°. The most is much and the start of the start of the most is much and the start of the start of the market is much and the start of the start of the approach. Pictor report a psychological barrier to adnessing a granoud.	The survey showed that in the option of the picture WK is the most important analysis of roundary comments made by the picture.	The survey aboved that in the option of the pilots. The survey aboved that in the option of the mild of the the management of valuationy comments made toy the pilots.	Hertional Bank	A high percentage of plots found fermines in a surprise aluminous for humans and a surprise aluminous for humans contrast in despite spectrom or allowing producting and an analysis responsible regroup to a surprise of important and an analysis of the same at the percentage of the same at the important of the same at the same at the important of the same at the same at the important of the same at the important of the same at the same at the import	Interdonal Blank	The pilot survey is probably most investing in the salayed complement. The stat LOBA provides a property of the state of the state of the state of the complement investigation of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state interaction as the sparse basis. The state matter pilot method as a the sparse basis.	The pict survey provided both encouraging and the pict survey provided both encouraging and provide the picture of the pictu	e Interdonal Elank	interdoral Blank	Hartural Bank	Hartonal Bank	The plot survey highlighted some important logics for which training a node of this social to be social or more and engines operating. This way also work to be more only the social social social to be more to be as social social to be more to be as social social to be associated and the logics where discriming is maded parallels the and all the social social to be associated and the logics where discriming in maded parallels the social social social social to be the social social to be associated and the logics where discriming in maded parallels the social socia
IATA Safety Report 2008 & 2009 4.5	The IRXI Audidet Reports Bid unstable approaches & lo a concern and a Reputer story. The report excension of STD training in order to reduce the problem.	The IATA accident reports generally support the LOBA facing with reparts another to application, they for ex- tension reparts another to application, they for ex- pendent to be the best constrained and the support periodic to be the best constrained as to might device should be made with missing addition. The to tage errors easily made with this function	Corr companyament statute bern the ATA studies edu En COA Adding. Entro insegnation to statute and being the next information contenensation to account particities and another accounteness and a statutes. Manual informations approvale a statutes. Manual improved by taining in addition to accountent provement by taining in addition to accountent. Oner locality areas noted are gross end onces set relactance to revert to manual filing when appropriate	The IATA report recommends reinforcing manual arrant control a kills through through an online and crease an exilicating to revert is manual lying netics as the number 1 error in their accident reports. The regord their accident addition to go-arounds.	The results from IATA accident statistics support the LOSA findings in terms of the high degree of fallow to paraunal when the approach is unstatis. The paraunal when the approach is unstatis. The and the report recommends training in g-aurounds with regard to descent anality and reacculation of any type of go-amound, at any point during the approach.	The top thread in the IATA accident reports is weather	Intentional Blank	kterional Blank	Maintaining situation axoreness by specific buildings as well as monitoring and cross checking are effective countermeasures for dealing well and the full accident reports recommend training to deal with unusual redge of the enreloyer situations as well as specific training to cope with supplie go-arounds.	According to the IATA accident reports, th number 11 UAS is improper landing. Training shaudramotore CA from abnormal landings.	The IATA reports exhib LOSA findings. Compliance rated as one of the tag entros and specific baking is SOPs (i.e. to g-around) when an approach is not stable, and when the landing is improper.	s Interforall Bank	Mismanaged alroadt states occur for many reardocement training in basic flying skills such annual handlig landing and ge actualds annual handlig landing and ge actualds that is longing and ge-arounds continue to be a problem. The reports produce that problems and confidence be licetered surg training and confidence be licetered surg training	Turning about strates plots to respond to manapacted events throughout the fight regime at various levels of difficulties	ktertonal Bank	Intertional Blank	As evidenced by the recommendations in the IATA accident reports, the analysis and surfaces believe that FSTD training the decision to go-arcond when appropriate as well as improve the performance of the go-arcond manoeuve itself.



-																	
Incidents during training 4.6	According to pilot reporting, not only do the unstable executing to pilot reports, one of the unstable to percentage of reports to twice as high during training fights	intentional Blank	Comparing the subjects of the incident reports for the training flights with the main ASR database provides some insight into the evolution of piots as they acquire more sequence on the line. The training flig thirds is, but not the coils for the main incident, but is not only two the training of the incident, but also for the percentages of actual reports with similar makings across the two groupings of flights.	Reported incident show manual alread costol responses as it is 3-9% of the total incident propriode. However, it is three times anon likely to be reported. However, it is three times anon likely to be reported when the fight is a training fight and it is the 2 <sup>erm</sup> another incident for the set of training fights.	Intentional Bank	Weather is a major threat for flight crews, and this source continues to corrobrate the threat. The total kit is named so low the threat the total kit is named so the k4 BN versus 17.0% in all efficient classes which are that new plots are absorbed with other concerns, related to entors.	intentional Blank	Intentional Blank	Intentional Blank	Reported landing incidents account for 13% of reports in the main ASR database This coupled with the fact that manual handling is ranked 2 <sup>st</sup> implies that there is all a considered around of learning skills are not fully acquired prior to IOE.	STEADES data draws little distinction between the two groupings of hights training and all flights). Most of the training lights are to the purposed dofter, and the training lights are to the purposed dofter, which are similar despite varying experience levels.	intentional Blank	The training flight database is heavily populated with incidents that are classified as minimaged the database of all fights. This task is not only use for the anished of the incidents, but also true for the percentages of actual reports with minimar rankings and the incidents, but also there for the percentages of actual reports with minimar rankings and the incident. EGRNUS and manual handling.	Intentionall Blank	Intertional Blank	Intentional Blank	intertional Blank
UK CAA Accident Reports 4.7	Intentional Blank	The ranking of automation as a causal factor is generally town a accident reporting and the CAA accident reporting is no exception at 1.9%. The prevailing option by many analysits is the baccause mismanages automation is further upstream in the error chain it is under reported in causal accident investigation	The CAA accident reports (CAP 776 & CAP 780) ofte numan factors as the major concern in accident causation. The top fire HF assues with their properties the section or contexture scales (1), flight mathematiling (28%), lack of positional awareness (25%), and failure of CRM (22%).	2 Fight mishanding is ranked second in percentage of occurrence in accidents (28%) by the UK Accident Report CAP 780.	Internionall Blank	Intentional Blank	intentional Blank	Intentional Blank	Intentional Blank	Intertionall Blank	Part of the Isam that authored CAA CAP 780 Report analysed the fatal accidents set used in the CAP 780 Report (Le. accurged during the particle between 1 January 1907 and 31 December 2008 (inclusive) Ibo memory of the head and errors of default in the Est Training Criticality Survey (TCS) and the skudy determined that compliance failure anited number 2 at a 19.1% rate of occurrence	intentional Blank	Intentional Blank	Intenfonall Blank	Intentional Blank	According to the UK Fatal Accident Report CAP 780, the APP phase of Right hosts the most set of the APP phase of Right hosts the most set of the APP phase of the Application of the APP set of the APP phase of the APP phase of the set of the APP phase of the APP phase of the set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the APP phase of the Set of the APP phase of the APP phase of the APP phase of the Set of the APP phase of the APP	Intentional Blank
Skill Retention after Training/Skill Decay 4.8	The skill decay study shows that skill losses can be substantial and easen without practice, making the case for souting energy management and recoverises from unstable approaches as part of a training Curriculum.	The skill decay study shows that skill losses can be substantial and decay without practice. This determinant automation alitis making it important to assess these skill automation alitis making it important to assess these skill notifinely.	Error management is cognitive in nature implying the Is rais of decay is greater than for many other the the important that error management be assessed and reinforced as necessary.	In a subscription of the second secon	Intentional Blank	Intentional Blank	The FAA sail docay shuly londs to support the rotice that system mathematics professiony is essature to a docay over time. The sail interestion subjuct conclusions are constant with this floring, Management of the applied of antiduction sincless biological spatial consequences in the same share and the same share consequences. It is lawly that sails required to deal worker waterstate to docay and the same share to deal worker waterstate to docay.	Intentional Black	Intentional Blank	Landings are generally practiced in the interval between training cycles and so no generally a problem for skill decay. This is shall decay is a problem for pilos without anding practice, and this may affect those involved in ultra long haul operations.	t Intendonali Blank	Intertional Blank	Intentional Blank	Summary – Upset still rank <u>e</u> as a major oause of accidents. <u>Its</u> percentage of total accidents has remained steady at around 13% in the last two decades.	Interdonal Bank	Intentional Blank	The FAA shill decay study tends to support the notion had when the shill retend to sharp consultance are consistent wit this final, Management of the majority of mathumcions and denoted to sharp or the sharp of the sharp of the and denoted assign, or one with unexpected consequence and denoted assign, or one with unexpected consequence public more mathumcion and anticipation public more mathumcion and anticipation public more mathumcion and anticipation public more mathumcion and the more vulnerable to decay
FAA Human Factors Team Report 1996 4.9	Intertonal Bank	The FAA submitter report found that pitcls have vertices statution anarometes toors with automation. They are substation anarometes toors with automation. They are substational and the substational substational and the substational automation and the substational automation automation and automational automation automation and automation automation automation and automation automation automation automation partice automation automation automation automation partice automation automation automation partice automation automation automation partice automation	The sport suggested and monotoring and assertions that show the sport and suggest and assertion of the sport of the sport and suggest and sport and suggestion of the first sport and sport and suggestion of the sport and sport and sport and sport memory and the stability assertions. But in the sport and sport and sport and sport and sport and sport responses that the substability and show the sport responses that the substability and show the sport responses that the substability of show the sport responses that the substability of show the sport responses that the substability of shows the modeled	a The FAA 1996 automation report found that pilots indicated automation report found that pilots manual and automation report of the second second manual and automation and recommended explicit and the second	Hertonal Bank	Interdonal Bank	Intertional Bank	The FAAAutomation report found disturbing occurrences of last of allustron assumption processing and the second	The region bourd that police could be anympted by subtle behaviour and systems operating the second secon	htertonal Bank	Interioral Bank	The report band that ladership in the complex automated antise environment is especially reported. The test is monitor index is unclearned to the second second second second second test, particularly in untential shadow.	The topol found watchess is prevention of mammaps of acrost states as well as in the stat to across that there in the stat state trans and entry assumeds. In the state of the states are stated with the states are stated managers and entry assumeds. The state of the states are stated transport managers and the states are state managers from hadwrited entries.	The FAA automation report deel detection and recovery from unusual atflutes as an aleas of concern it sum of our to recommend a sum of the sum of the sum of the sum of the automation supporting particular automation supporting automation automation supporting automation automation support and automation automation automation br>automation aut	The FAA additution report found that platfs here vertices studious avaiences issues with additution. Priors and a matching the bits and of the studious studious and the addition to bits and of the studious studious and the studious studious and energy assessments when indexing the bits and energy assessments when addition to bits and of the additional. They are addition to bits and of the additional of the studious and comparations of abundless and the additional and the studious studious and the studious and the the studious studious and the studious and the the additional the studious and the studious and the studious and the studious regards to addition, the report accommonsh that there additional studious. The report accommonsh that there additional studious the additional studious additional studious the additional studious additional studious the additional studious additional studious the studious and the studious additional studious the studious and the studious additional studious	t b Intertional Blank	The FAA 1000 submittee report strongly emphates the affect of training and incommends may: charges separate in order to entonine operational adary. The report flags and the entonine operational adary for report to the adarter of the advanced and and produced serving to denty the advanced and advanced on the advanced as advanced in a duration of a stress control and and advanced as a duration of the advanced in the management included another advanced in the advanced and advanced and the advanced in the management. The duration is stress to advanced and the advanced on the management. The determines the advanced in the memory advanced and the advanced on the advanced in the stress of advanced on the stress and advanced and be advanced on the stress and the advanced on the memory advanced advanced and advanced advanced advanced and advance
Automation Training Practitioners' Guide 4.10	Intentional Blank	The Automation Training Practitioners' Guide advocates we hanning concord, Specifically II recommends training in Blocks, adapting to individual training and the state of the state of the state of the logic deep program of imitation of the logic deep program of imitation of the adapting of managing assemblion throughout the various stelling of managing assemblion throughout the various tests including evension to manual light.	The Automation Training Practitioners' Guide stresses The Automation Training Practitioners' Guide stresses That good CPM is particularly monotonic with the stress of the stress of the stresses Pravity points that in order to able with unexpected Pravity points that in order to able with unexpected the stress stress point and the skiller of automation including reversion to manual fight.	The duternation Training Practitioner' Gold escalar guides the fight creater need to be add by manufacture and the fight creater need to be by manufacture and the fight creater of the second by any fight trainers should receive instruction on when and how event to manual fight and practice accordingly in training.	Intentional Bank	Intentional Blank	Intertonal Blank	Intentional Blank	Intertional Blank	Intentional Blank	Interdonal Blank	Intertional Bank	Intentional Blank	Intentional Blank	The Automaton Training Prositionerry Guide autocates a new saming concept for the new generations of aucott, gen- ding and 5, Specifically in Roommath Stating in Biolos, adapting in Inividual Internet, Inguing CRM Procycloud adapting in Inividual Inividual Initiation and Initiation ecomments using multiple assessment techniques, confirming the plation uncertained the long certain purposed practice in operational setting of managing automation manual tight .	a Intertonal Blank	The Automaton Training Positionerry Guide specifies crateria having to effect improved operational safely with regard to automatical. The guide begins by control out automation askety depends on teaching flight ores to be used on the second on teaching flight ores to second automatically in multi be bught. Plots need to the hand on executions using the autoffith and insuld be readed automatically, it must be bught. Plots need to were non. Finally the plots must understand the logic averaging and the initiations of the automatical neight and the second second automatical teacing and the initiation of the automatical teacing and the initiation of the automatical teacing and the initiation of the automatical teacing and the initiations of the automatical teacing automatical teacing the second teacing approximately in various situations.
TAWS 'Saves' 4.11	Intertional Blank	Intentional Blank	Intentional Blank	Intendonal Bank	Intentional Blank	Intentional Blank	Intentional Blank	The TAWS Saves report is essentially an accident report without an accident. Five incidents that the writes of the report thit would probably have resulted in accidents are tailed an an accident-investigation format. Firstly, a proper ECPWS is an effective tool relations (DFT accidents and second), that in matter how good the warming system is, terman avoidance all depends on a properly trained reaction of the flight cree.	Intentional Blank	Intertionall Blank	Intendonal Blank	Intertonal Blank	Intentional Blank	Intentionall Blank	Interdoral Bank	Intentional Blank	Intertional Blank
Accident Study using CAST+ Data 4.12	Intertonal Bank	Intertonal Blank	Interioral Bank	When tooling at accident data for over trends, years from the CAST accidence suggestation assumptions with the state from 2000 and 2010 from the NT-BR, it is clear the accidence where it is highly likely that states and the state of the state of the state of the states of the state of the state of the state of the states of the state of the state of the state of the states of the state of the state of the state of the states of the state of the state of the state of the states of the states of the states of the states of the states of the states of the case.	Intentional Blank	Intentional Blank	While system matterations still rook as a major cause of accidents (11%) their percentage of total accident has decreased more than 20% when comparing the last ten-years to the previous ten year-period.	White terrain still rank as a major cause of accidents (M), their percentage of total accidents (M), their percentage of total accidents (M), and the state of the accident state of the state when comparing the tast fen years to the previous ten year-period.	Intentional Blank	Landing issues are a major component of all ancraft accidents and are increasing as shown by the data in the last 20 years. 41% of all accidents happen in the landing phase, the leading phase in which are backed by the software in which the proportion of accidents related to writicle sunding space spratulatily with regard to runway excursions and landing short.	interdonal Blank	Intertonal Blank	Even though the accident rate has decreased in the last 20 years, he rate of accident due to intermanged alroad has increased. Runwy excursions and landing short exemptly the trend	Upset still ranks as a major cause of accidents, <u>its percentage of totals</u> accidents have remained stackag at anound 13% in th last two decades	Interformal Bank	89% of all accidents occur in the APRILDO phases of flight or in the TOCLE with the leading that is the total occurs of the test of the flight, which show an increasing tend in terms of percentage of total accidents, are LDG and TAXI.	Intertional Bank

Figure 13.1 (cont.)



Intentionally blank

## **13.2 ANALYSIS WORKSHEET FOR TOPIC**

# 13.2.1 Unstable Approach

	Summary Analysis - Unstable Approach												
Sources	Summaries	Outline	Excerpts	Narrative									
LOSA	Unstable approaches remain a consistent problem at a rate of approximately 4%. They almost always result in an uneventful landing. The crews in most cases have mismanaged the situation but are willing to continue the approach violate SOPs and/or are unsure of		Unstable approaches remain a consistent problem at a rate of approximately 4% LOSA The crews in most cases have mismanaged the situation but are willing to continue the approach, violate SOPs and/or are unsure of the appropriate stabilized approach criteria LOSA	The unstable approach rate remain a consistent problem at a rate of approximately between 3 - 4% across generations of aircraft and geographical areas. Increased risk is associated with unstable approaches becomes evident when examining event rates and event severity. Landings from unstable approaches have a higher									
	the approach, white Gori stabilized approach criteria. Landings are often performed in the wrong aircraft configuration.		The FDA unstable approach rate is around 3.5%. This is consistent across aircraft types and geographical regions <b>FDA-EBT</b> The increased risk associated with unstable approaches becomes evident when	risk and as the events themselves become more severe, the risk escalates at an accelerated rate. As pilots continue to make unstable approaches they continue to land from them instead of performing the mandated go-around.									
	The FDA unstable approach rate is around 3.5%. This is consistent across aircraft types and geographical regions. There are as many flights that have landing events following stable	Problem	examining event rates and event severity. Landings from unstable approaches have a higher event rate and as the events themselves become more severe, the event rate becomes even higher FDA-EBT The oilot survey shows that unstable approaches are a consistent problem, with rates	The pilots themselves admit to this violation, as they prefer not to go-around for many and various reasons, one very important reason is that they feel less comfortable with the go-around than the subsequent landing. The data support that go-arounds are usually not well performed.									
	approaches as there are following unstable approaches. Solving the unstable approach problem will not address all landing issues. The increased risk associated with unstable approaches becomes evident when examining		similar to those from LOSA and FDA data Pilot Survey The IATA Accident Reports find unstable approaches to be a concern and a frequent error IATA Safety Reports	Unstable approaches can be viewed as a barometer of the flight itself; flights with unstable approaches generally have more FDA risk events all in-flight phases, including phases not associated with the approach.									
FDA EBT	event rates and event severity. Landings from unstable approaches have a higher event rate and as the events themselves become more severe, the event rate becomes even higher.		Input from bullets Input from EBT Accident-Incident Study Landings are often performed in the wrong aircraft configuration LOSA The second study is the second study in the second study is the second stud	Training must clearly be implemented to mitigate this issue, not only for the approach, but the go-around as well. Associated issues of non-compliance and pilot confidence must also be addressed to effectively treat the continuing problem of the unstable approach.									
	Unstable approaches can be viewed as a barometer of the flight itself, flights with unstable approaches generally have more FDA events all in-flight phases, including		There are as many flights that have landing events following stable approaches as there are following unstable approaches. Solving the unstable approach problem will not address all landing issues <b>FDA-EBT</b>										
	phases not associated with the approach. Unstable approaches were closely monitored during the transition to ATQP and the rate of		approaches. The causes of unstable approaches in order of importance were poor decisions in accepting ATC clearances, mismanaged visual approaches, mismanaged energy, and poor manual aircraft control ATQP										
ATOD	unstable approach remained constant, indicating that a major change in training can be performed without increasing risk as far as approaches are concerned. Approximately 50% of concerned, Approximately	Specifics	The fact that pilots believe that they can and in most case do make a successful landing when unstable reinforces the continuation of this problem. (82% cite belief that landing can be safely made even though approach is not stable.) - Pilot Survey										
ATQP	10% of go-arounds during this transition esulted from unstable approaches. The auses of unstable approaches in order of mportance were poor decisions in accepting ITC clearances, mismanaged visual		Other reasons that pilots continue to land are that they admit to a psychological barrier inhibiting a go-around (37%); it is operationally inconvenient (35%); it is professionally embarrassing (24%); 17% admit that they are unfamiliar with the stable approach criteria and others simply do not want to write the mandatory report - <b>Pilot Survey</b>										
	approaches, mismanaged energy, and poor manual aircraft control.		Input from bullets Input from EBT Accident-Incident Study										
	approaches are a consistent problem, with rates similar to those from LOSA and FDA data. The fact that pilots believe that they can ared is mean table to make a supersoful	Training	Unstable approaches can be viewed as a barometer or the night itself; hights with unstable approaches generally have more FDA events all in-flight phases, including phases not associated with the approach - FDA-EBT										
	landing when unstable reinforces the continuation of this problem. (82% cite belief that landing can be safely made even though	Effect	of unstable approaches were closely moliticled during the transition to Artop and the rate of unstable approach remained constant, indicating that a major change in training can be performed without increasing risk as far as approaches are concerned - ATQP Input from bullets										
	approach is not stable.) Other reasons that pilots continue to land are that they admit to a		Input from EBT Accident-Incident Study										
Pilot Survey	psychological barrier inhibiting a go-around (37%); it is operationally inconvenient (35%); it is professionally embarrassing (24%); 17% admit that they are unfamiliar with the stable		From the pilot response it is clear that there are issues of knowledge, skills and particularly attitudes that foster an unstable approach culture, which needs to be treated on several levels, one certainly being training <b>Pilot Survey</b>										
	approach criteria and others simply do not want to write the mandatory report. From this information it is clear that there are issues of	Criticality	The report recommends FTSD training in order to reduce the problem IATA Safety Reports Input from bullets										
	knowledge, skills and particularly attitudes that foster an unstable approach culture, which needs to be treated on several levels, one certainly being training.		Input from EBT Accident-Incident Study										
IATA Safety	The IATA accident reports generally support the LOSA finding with regard to automation. Specifically, flight crews were found reluctant to revert to manual flying even when the situation required it. In addition, crosschecking is promoted to be the best countermeasure to mitigate automations errors and further finds that gross error checks should be made when imputing data into the EMS to tran errors easily												
Incident Study	made with this function. According to pilot reporting, not only do the unstable approaches rank high in reported incidents; but also the percentage of reports is twice as high during training fights												
Skill Decay	The skill decay study shows that skill losses can be substantial and decay without practice, making the case for including energy management and recoveries from unstable approaches as part of a training curriculum												



### 13.2.2 Automation

Sources	Summaries	Outline	Excerpts	Narrative		
LOSA	The overarching problem with automation for the flight crews is monitoring and cross checking. 28% of the flights have at least one automation error with almost half of them not detected or acted upon by the crew. In addition there is a basic problem with understanding the system, mode confusion and using the automation and/or flying manually at inappropriate times.		28% of the flights have at least one automation error with almost half of them not detected or acted upon by the crew LOSA Automation is an issue of concern regarding assessments in AQP in both the planning and execution phases of flight - AQP Mismanaged auto-flight is a major factor, contributing to unstable approaches and go- around errors, both in training and line operations. This remains constant, whether in the all engines operating, or engine-out case ATQP In reality 61% [of survey pilots] had multiple encounters on the line during their first 6 months of flight are they reorded being line line during their first 6 months of flight and the real to the line during their first 6 months of flight and the line line line line during their first 6 months of flight and the line line line line line line line lin	According to LOSA almost 30% of the flights have at least one automation error with almost half of them not detected or acted upon by the crew. Training reports that automation is an issue of concern regarding assessments in both the planning and execution phases of flight. Pilots themselves are heavily critical of automation training during the initial type rating with only 25% of the pilots feeling prepared to utilize the automation when released to line operations.		
AQP	Automation is an issue of concern regarding assessments in AQP in both the planning and execution phases of flight. The phases most concerned are CRZ and DES.	Problem	The IATA accident reports generally support the LOSA finding with regard to automation. Specifically, flight crews were found reluctant to revert to manual flying even when the situation required it IATA Safety	In major accident investigation agency believes that because mismanaged automation is further upstream in the error chain, it is under reported in causal accident investigation. Another authority states that many pilots use the autoflight when inappropriate and fail to revert to manual flight when required. The skill decay study shows that skill losses can be substantial and decay without		
ATQP	Mismanaged auto-flight is a major factor, contributing to unstable approaches and go- around errors, both in training and line operations. This remains constant, whether in the all engines operating, or engine-out case		The ranking of automation as a causal factor is generally low in accident reporting and the CAA accident reporting is no exception at 1.9% CAA Accident Reports The FAA automation report found that pilots have various situation awareness issues with automation FAA HF Report Manual the probability of the increase intercent to experime the properties.	shows that skill losses can be substantial and decay without practice. This deterioration is much greater for skilled tasks, such as certain automation skills making it important to assess these skills in training particularly for pilots that do on operate routinely. All of this points to a need to change the way current training is comprehend. A task of 60% of silds represented that negative		
Pilot Survey	The pilot survey was heavily critical of automation training during the initial type rating. Only 25% of the pilots felt prepared to utilize the automation when released to line operations. In reality 61% had multiple encounters on the line during their first 6 months of flying where they reported being involved in uncomfortable situations. Over 60% felt that the operational aspect of FMS training was missing during training requiring them to learn to use the system effectively during the first year after training. When asked how the training could be improved, the majority felt that automation surprises was the most important issue followed by hands on use in operational stuations; while about a third recommended better training sentiment was that the operational aspect of the FMS was seriously lacking in training, the focus being on the functional, such as basic knowledge and programming	Specifics	FAA HF Report         Input from Evidence Table         Input from EBT Accident-Incident Study         The overarching problem with automation for the flight crews is monitoring and cross checking - LOSA         The phases most concerned are CRZ and DES AQP         The prevailing opinion by many analysts is that because mismanaged automation is further upstream in the error chain, it is under reported in causal accident investigation CAA Accident Reports         They [Flight crews] are vulnerable to lack of flight path and energy awareness when using autoflight. In addition they are surprised by the subtleties and complexities of automation and the training courses fail to focus on operation principles of the autoflight architecture FAA HF Report         Input from EBT Accident-Incident Study         When asked how the training could be improved, the majority felt that automation surprises was the most important issue followed by hands on use in operational situations; while about a third recommended better training in transitioning between levels Pilot Survey         In addition, crosschecking is promoted to be the best countermeasure to mitigate automations errors IATA Safety	FMS training was not provided during initial training, and that they were left to self-learn during line operations Recommendations to improve training include that training enhances mode and position awareness when using automation, particularly with regard to terrain, energy and upset. In addition, there should be adequate training content to ensure airmanship, CRM, decision-making and workload management when utilising automation, especially in demanding situations. Training should also include multiple assessment techniques, confirming that pilots understand the logic, design purpose and limitations of the automation. Practice and reinforcement should be accomplished in an operational setting, managing automation at all levels and including reversions to manual flight.		
IATA Safety	The IATA accident reports generally support the LOSA finding with regard to automation. Specifically, flight crews were found reluctant to revert to manual flying even when the situation required it. In addition, crosschecking is promoted to be the best countermeasure to mitigate automations errors and further finds that gross error checks should be made when imputing data into the FMS to trap errors easily made with this function	Training Effect	The training courses at the time of the study tended to be checking farther than tearning oriented and had not kept pace with human factor issues in regard to automation FAA HF Report The Automation Training Practitioners' Guide advocates a new training concept. Specifically it recommends training in blocks, adapting to individual trainees, integrating CRM throughout training, and major emphasis on the "need to know" items AUTO PRACT GUIDE Input from Evidence Table Input from EBT Accident-Incident Study The pilot survey was heavily critical of automation training during the initial type rating. Or the CPU of the related to will be subtrained using the initial type rating.			
UK CAA Accident Study	The ranking of automation as a causal factor is generally low in accident reporting and the CAA accident reporting is no exception at 1.9%. The prevailing opinion by many analysts is that because mismanaged automation is further upstream in the error chain and under		Over 60% felt that the operational aspect of FMS training was missing during training requiring them to learn to use the system effectively during the first year after training Pilot Survey The prevailing sentiment was that the operational aspect of the FMS was seriously			
Skill Decay	reported in causal accident investigation The skill decay study shows that skill losses can be substantial and decay without practice. This deterioration is much greater for skilled tasks, such as certain automation skills making it important to assess these skills in training particularly for pilots that do on operate routinely.	Criticality	The skill decay study shows that skill losses can be substantial and decay without practice. This deterioration is much greater for skilled tasks, such as certain automation skills making it important to assess these skills in training particularly for pilots that do on operate routinely Skill Decay The report recommends that training enhance mode and position awareness when			
FAA HF Report	The FAA automation report found that pilots have various situation awareness issues with automation. They are vulnerable to lack of flight path and energy awareness when using autoflight. In addition they are surprised by the subtleties and complexities of automation and the training courses fail to focus on operation principles of the autoflight architecture. Many pilots use the autoflight architecture. Many pilots use the autoflight when inappropriate and fail to revert to manual flight. The training courses at the time of the study tended to be checking rather than learning oriented and had not kept pace with human factor issues in regard to automation. The report recommends that training enhance mode and position awareness when using automation, particularly with regard to terrain, energy and upset. In addition, the report recommends that there be adequate training content to insure airmanship, CRM, decision-making, workload/task management when utilizing automation		using automation, particularly with regard to terrain, energy and upset. In addition, the report recommends that there be adequate training content to insure airmanship, CRM, decision-making, workload/task management when utilizing automation especially in demanding situations FAA HF Report In addition it recommends using multiple assessment techniques, confirming that pilots understand the logic, design purpose and limitations of the automation. Lastly it recommends practice in operational setting of managing automation throughout the various levels including eversion to manual flight AUTO PRACT GUIDE Input from EVIDENT Table Input from EBT Accident-Incident Study			
Automation Practitioners Guide	I he Automation Training Practitioners' Guide advocates a new training concept. Specifically it recommends training in blocks, adapting to individual trainees, integrating CRM throughout training, and major emphasis on the "need to know" items. In addition it recommends using multiple assessment techniques, confirming that pilots understand the logic, design purpose and limitations of the automation. Lastly it recommends practice in operational					

setting of managing automation throughout the
various levels including eversion to manual
flight

# 13.2.3 Error Management

			Summary Analysis Error Management	
Sources	Summaries	Outline	Excerpts The situation is critical as 75% of the errors made by the flight crews are either not	Narrative
	is monitoring and crosschecking. The situation is critical as just over 25% of the errors made		detected or if detected, not rectified - LOSA There are however, problems in error management that are not so well addressed. Non-	Effective monitoring and error detection are increasingly important when operating highly reliable, automated aircraft. Multiple data
	by the flight crews are detected and rectified. The highest risk is crosschecking errors (e.g.		compliance with procedures is too high - Pilot Survey	management is reported as a very significant countermeasure in current onerations with one accident study espousing that it is the
	omitted deviations as they result 65% of UAS). The flight phase with the most threats is pre-		The issue of assertiveness was questioned and while the monitoring pilot almost always speaks up if there is a flight path deviation (90%), but less than half of the	most significant tool available to pilots for the prevention of accidents. Multiple sources of data show that there is a high level
LOSA	departure, while the most mismanaged errors occur in DES, APP and LDG. Error detection is		respondents (49%) reported that they would be willing to take control from the flying pilot - <b>Pilot Survey</b>	of intentional non-compliance and so any error management strategy must include greatly reducing its incidence.
	generally better in the early phases of flight with automation error capture being the best	Problem	Error management results from the IATA studies echo the LOSA findings IATA Safety	Error management skills are subject to decay. Error management currently does not form part of any strategy developed through the
	poorest. The Captain detects more errors than the First Officer (27% versus 18%) but neither		The CAA accident reports (CAP 776 & CAP 780) cite human factors as the major	regulation of flight crew training so consequently it is lacking in most training programmes. It is a key topic and needs to be
	rates highly at detecting their own errors (5- 6%).		The renet recognized that monitoring and oversees skills were leaving in the	situation awareness and further develop and the professional
	In all AQP evaluations, whether type rating		automation environment at the time the report was issued - FAA HF	
	courses (IQ) or recurrent training (CQ), policy and procedural error types are ranked 1st and		Input from Evidence Table Input from EBT Accident-Incident Study	
	2nd, accounting for the majority of all errors. Crews operating Gen 3 jet aircraft show proportionally a greater percentage of errors		The highest risk is crosschecking errors (e.g. omitted deviations as they result 65% of UAS - LOSA	
AQP	relating to proficiency, situation awareness, non-compliance and decision making when compared with crews operating Gen 4 jets.		The flight phase with the most threats is pre-departure, while the most mismanaged errors occur in DES, APP and LDG <b>LOSA</b>	
	This trend increases as the training cycle progresses from the type rating to recurrent		Error detection is generally better in the early phases of flight with automation error	
	line checks. Both operational and training data confirm that		Captain detects more errors than the First Officer (27% versus 18%) but neither rates highly at detecting their own errors (5-6%) - LOSA	
	crews have problems with manoeuvres that are not routinely practiced. Procedural and		Procedural and manual control skills need reinforcement, as these areas are where	-
ATQP	manual control skills need reinforcement, as these areas are where most of the errors	Specifics	most of the errors occur ATQP	
	occur. In addition, descent planning and energy management also need specific training		21% of pilots admit to call out deviations on virtually every flight, cross checking is particularly bad in the CLB phase because of complacency and too many secondary	
	Almost all pilots believe that the most		duties. Intentional non-compliance on a fairly regular basis was reported by 13% of those surveyed Pilot Survey	
	important strategy in error management is monitoring and crosschecking and that it is emphasized most of the time in training and taught explicitly obtained balf of the time. There		Other specific areas noted are gross error checks when inputting FMS data as well as dealing with pilot reluctance to revert to manual flying when appropriate - IATA Safety	-
	are however, problems in error management that are not so well addressed. Non-		The top five HF issues with their percentage rate of occurrence in accidents are	
	compliance with procedures is too high, for example, 21% of pilots admit to call out		awareness (25%) and failure of CRM (22%) CAA Reports	
Pilot Survey	deviations on virtually every flight, cross checking is particularly bad in the CLB phase because of complacency and too many		Input from EBT Accident-Incident Study	-
	secondary duties. Intentional non-compliance on a fairly regular basis was reported by 13%		In all AQP evaluations, whether type rating courses (IQ) or recurrent training (CQ), policy and procedural error types are ranked 1st and 2nd, accounting for the majority of	
	of those surveyed. The issue of assertiveness was questioned and while the monitoring pilot		all errors - AUP	-
	almost invariably intervenes there is a flight path deviation (90%), but less than half of the respondents (49%) reported that they would be		that are not routinely practiced - ATQP	-
	willing to take control from the flying pilot. Error management results from the IATA	Training Effect	Almost all pilots believe that the most important strategy in error management is monitoring and crosschecking and that it is emphasized most of the time in training and taught explicitly about half of the time - <b>Pilot Survey</b>	
	management is listed as being the most important countermeasure to accident		Manual aircraft handling is also cited as an area to be improved by training in addition to automation management i.e. flight path management - IATA Safety	
	prevention. In addition, training is recommended to reinforce go-around in		Input from Evidence Table	
IATA Safety	appropriate situations. Manual aircraft handling is also cited as an area to be improved by training in addition to sutematics management		Input from EBT Accident-Incident Study Crews operating Gen 3 jet aircraft show proportionally a greater percentage of errors	
	i.e. flight path management. The other specific area noted is gross error checks when		relating to proficiency, situation awareness, non-compliance and decision making when compared with crews operating Gen 4 jets. This trend increases as the training cycle	
	inputting FMS data as well as dealing with pilot reluctance to revert to manual flying when		progresses from the type rating to recurrent line checks AQP	-
	appropriate. Comparing the subjects of the incident reports		ATQP	-
	for the training flights with the main ASR database, provides some insight into the		Error management is listed as being the most important countermeasure to accident prevention. In addition, training is recommended to reinforce go-around in appropriate	
Incident	evolution of pilots as they acquire more experience on the line. The training flight		situations IATA Safety	-
Study	rather than threats, but this is not the case for the main database. This is not only true for the		Error management is cognitive in nature implying that its rate of decay is greater than for many other the tasks that pilot perform. This decay aspect makes it important that	
	rankings of the incidents, but also for the percentages of actual reports with similar	Criticality	en or management de assessed and reinforced as necessary - Skill Decay	4
	rankings across the two groupings of flights. The UK CAA accident reports (CAP 776 &	ontiounty	It [FAA HF report] begins by recommending education of the "hazardous states of awareness", a term it uses to denote a certain phenomenon with rest to situation	
UK CAA	CAP 780) cite human factors as the major concern in accident causation. The top five HF		Next it recommends sharing operational information to learn from crew errors, followed	4
Accident Study	in accidents are inappropriate actions or omissions (38%), flight mishandling (28%).		by proposing to improve the training of operational understanding of the automated systems in order to improve performance - FAA HF	
	lack of positional awareness (25%) and failure of CRM (22%).		The Automation Training Practitioners' Guide stresses that good CRM is particularly	
	Error management is cognitive in nature implying that its rate of decay is greater than		skill must be taught and practiced Auto Pract Guide	_
Skill Decay	for many other the tasks that pilot perform. This decay aspect makes it important that error management be assessed and reinforced as		Finally it points that in order to deal with unexpected situations, including crew errors, pilots must be skilled in managing the transition between the various levels of automation including reversion to manual flight - <b>Auto Pract Guide</b>	
	necessary.		Input from Evidence Table	
	awareness skills were lacking in the automation environment at the time the report		input nom EBT Accidentencident Study	•
	was issued. It begins by recommending education of the "hazardous states of			
	awareness", a term it uses to denote a certain phenomenon with respect to situation			
Report	awareness. It recommends sharing operational information in order to learn from crew errors, followed by proposing to improve			
	the training of operational understanding of the automated systems in order to improve			
	performance. Finally the report recognizes that the evaluation process simply does not			
	address automation skill and should be modified.			
	The Automation Training Practitioners' Guide stresses that good CRM is particularly			
Automation	important with automation. It espouses monitoring of automation and notes that this skill must be taught and practiced. Finally, it			
Practitioners Guide	points that in order to deal with unexpected situations, including crew errors, pilots must be			
	skilled in managing the transition between the various levels of automation including			
	reversion to manual flight.			



### 13.2.4 Manual Aircraft Control

		Sum	nary Analysis - Manual Aircraft Control	
Sources	Summaries	Outline	Excerpts	Narrative
LOSA	According to LOSA, manual control errors, while not the most frequent type of error (41% occurrence by flight), are only exceeded by automation errors. Many manual control errors result from the improper technique, flight crews ignoring or "flying through" the indicated flight guidance. Manual control problems are exacerbated in adverse weather. The leading error type is unintentional vertical deviation (32%) followed closely by deviations in landing, lateral, speed and improper thrust.mproper technique, flight crews ignoring or "flying through" the indicated flight guidance. Manual control problems are exacerbated in adverse weather. The leading error type is unintentional vertical deviation (32%) followed closely by deviations in landing, lateral, speed and improper thrust. Long body aircraft are more prone to high "G" landings. Because of geometric	Problem	According to LOSA, manual control errors, while not the most frequent type of error (41% occurrence by flight LOSA Poor manual aircraft control ranks as the number 1 error in their accident reports. The report cites problems during landing in addition to go-arounds. – IATA it is the 2nd most reported incident for the set of training flights. – STEADES Flight mishandling is ranked second in percentage of occurrences in accidents (28%) by the UK Accident Report CAP 780. – CAA it is clear that accidents where it is highly likely that the pilots are hand flying the aircraft, such as takeoff, landing and taxing; the data show a very significant percentage increase in these types of accidents. – CAST Input from Evidence Table Manual Aircraft Control is the most important competency issue in all accidents. In addition it	Manual aircraft control is one of the most important topics in operations and training. It ranks very highly as a competency issue in accident reports. Various sources of flight operations data show substantial competency issues associated with manual control. The phases of flight that routinely involve manual aircraft control such as take-off, landing and taxing show a very significant percentage increase in accidents over the last decade. Unintentional deviations and failure to follow flight guidance, plus speed and thrust errors, exacerbated by adverse weather, are some of the issues being observed. Landings with high vertical acceleration, difficulties in crosswinds, long touchdowns and substantial handling errors during go-arounds are amongst the problems revealed by flight data. While training data indicate rapid mastery of manual control especially in Gen 4 jets, this effect may be undermined in complex and unexpected situations. Results show that safety while using automation depends on flight crews having the confidence to fly manually. Data across the EBT study highlight the importance of training to mitigate an obvious deterioration in manual aircraft control skills. Pilots are well aware of the need for manual aircraft to the Airline
FDA Long Body	considerations, perspectives from the cockpit are slightly different laterally and vertically and tend to produce steeper approach gradients just prior to flare as well as centreline displacement in crosswinds. To compensate for this crews should be attentive to landings in crosswind, avoid last minute pitch-down and a tendency to under-flare. There is a tendency to under-rotate in long body aircraft, which degrades take-off performance; pilots should make smooth accurate rotations avoiding "pilot induced oscillations.		ranks very highly as one of the 40 factors in the analysis. The effect is even more exaggerated in accidents with high training effect emphasising the importance of training. The trend for manual aircraft control issues in fatal accidents is very concerning in recent years in all generations of aircraft but the biggest problems occur in older aircraft where the occurrence rate is around 50%. Input from EBT Accident-Incident Study flight crews ignoring or "flying through" the indicated flight guidance LOSA	Pilot Perceptions of Training Effectiveness Survey. Training data effectively shows that the trend can be reversed providing the skill is mastered. Skill retention data in two independent reports show that manual aircraft control skills are resistant to decay as long as they are practised. Good manual control skills include transitioning in and out of automation, with attendant and realistic distractions and threats from the environment, aircraft systems and ATC. Simply to continue practicing only traditional and rote manoeuvres is insufficient for crew confidence and proficiency required for modern aircraft in today's environment.
AQP	In all AQP evaluations, whether type rating courses (IQ) or recurrent training (CQ), policy and procedural error types are ranked 1 <sup>st</sup> and 2 <sup>nd</sup> , accounting for the majority of all errors. Crews operating Gen 3 jet aircraft show proportionally a greater percentage of errors relating to proficiency, situation awareness, non-compliance and decision making when compared with crews operating Gen 4 jets. This trend increases as the training cycle progresses from the type rating to recurrent line checks.	Specifics	Manual control problems are exacerbated in adverse weather LOSA The leading error type is unintentional vertical deviation (32%) followed closely by deviations in landing, lateral, speed and improper thrust LOSA Long body aircraft are more prone to high "G" landings -FDA To compensate for this crews should be attentive to landings in crosswind, avoid last minute pitch-down and a tendency to under-flare FDA	
ATQP	The evidence gathered during ATQP shows that manual aircraft control is a problem on modern aircraft and more practice in training is needed		Input from Evidence Table Input from EBT Accident-Incident Study Training results in AQP show quicker mastery of	
Pilot Survey	The pilots were allowed to make whatever comments on any training subject and these comments were subsequently analysed and added to the results from the formal survey questions. There were a significant number of comments on training needs and these needs were prioritized according to the analysis of the comments. Two categories referred to manual aircraft control, manual handling and manoeuvres. Together they indicated that pilots feel quite strongly that manual aircraft control is a high priority item in training	Training Effect	The case in gen 4 aircraft and while Gen 3 improves with experience it remains below Gen 4. AQP This advantage is minimized in recurrent training – AQP The guide begins by pointing out that automation safety depends on teaching flight crews to effectively fly manually - Automation Training Practitioners' Guide Input from Evidence Table The number 1 ranking of Manual aircraft control is even more exaggerated in accidents with high	
IATA Safety	The IATA report recommends reinforcing manual aircraft control skills through training and notes that crews are reluctant to revert to manual flying from automation. Poor manual aircraft control ranks as the number 1 error in their accident reports. The report cites problems during landing in addition to go- arounds.		training effect emphasising the importance of training Input from EBT Accident-Incident Study Two categories referred to manual aircraft control, manual handling and manoeuvres. Together they indicated that pilots feel quite strongly that manual aircraft control is a high priority item in training. Pilot Survey Manual aircraft control shows greater resistance to	
Incident Study	Reported incidents show manual aircraft control is a concern, as it is 3.4% of the total incidents reported. However it is three times more likely to be reported when the flight is a training flight and it is the 2 <sup>nd</sup> most reported incident for the set of training flights.		skill decay over time than other competencies – Skill Decay and Retention studies The FAA 1996 automation report found that pilots who utilized automation frequently and/or flew long haul flights experienced a degradation in manual aircraft control and recommended explicit instruction	
UK CAA Accident Study	Flight mishandling is ranked second in percentage of occurrences in accidents (28%) by the UK Accident Report CAP 780.	Criticality	and practice in reverting to manual flight path control – FAA Automation Study The Automation Training Practitioners' Guide	
Skill Decay	Flight mishandling is ranked second in percentage of occurrences in accidents (28%) by the UK Accident Report CAP 780.		explicitly states that flight crews need to be able to fly manually in automated aircraft Automation Training Practitioners' Guide	
FAA HF Report	The FAA 1996 automation report found that pilots who utilized automation frequently and/or flew long haul flights experienced a degradation in manual aircraft control and recommended explicit instruction and practice in reverting to manual flight path control		firstruction on when and how to revert to manual flight and practice accordingly in training Automation Training Practitioners' Guide Input from Evidence Table Input from EBT Accident-Incident Study	
Automation Practitioners Guide	The Automation Training Practitioners' Guide explicitly states that flight crews need to be able to fly manually in automated aircraft. It continues by saying that trainees should receive instruction on when and how to revert to manual flight and practice accordingly in training.			
CAST	When looking at accident data for over twenty years from the CAST archives augmented with data from 2009 and 2010 from the NTSB, it is clear that accidents where it is highly likely that the pilots are hand flying the aircraft, such as takeoff, landing and taxing; the data show a very significant percentage increase in these types of accidents. While this does not definitively confirm that manual aircraft control skills are decreasing, the trend is consistent with that hypothesis supported by other very different kinds of sources that this is indeed the case.			



### 13,2,5 Go-Around

Summary Analysis Go-Around					
Sources	Summaries	Outline	Excerpts		
	According to LOSA, go-around from unstable approaches occur only 3% of the time (contrary to		According to LOSA, go-around from unstable approaches occur only 3% of the time (contrary to SOP's) LOSA		
LOSA	SOP's). Landings from unstable approaches rank in the top 5 UAS during the LDG phase and are the number 3 non-compliance item in the LOSA		When a go-around from an unstable approach is performed it is usually a surprise to the crew and poorly executed - LOSA	go-arounds should rate of unstable app	
	database). When a go-around from an unstable		Only 1.4% of unstable approaches lead to a go-around - FDA/EBT	that flight crews sim	
	approach is performed it is usually a surprise to the	Problem	A significant percentage of go-arounds result in flap over-speeds and violations of SOP ATQP	concern of unstable	
			The survey shows as pilots readily admit that they are not going around per the airline SOP Pilot Survey	entire flight. Accord	
	Only 1.4% of unstable approaches lead to a go- around, with an FDA all event rate of 1.6		The results from IATA accident statistics support the LOSA findings in terms of the high degree of failure to go-around when the approach is unstable IATA Safety	violation factor" in te unstable approach.	
	around (GA, CLB). The high-risk event rate for the		Input from Evidence Table	Unstable approach	
FDA EBT	same period is 0.24. Both these rates are		Input from EBT Accident-Incident Study	the data that the rat	
	conservative because the flight recorder cannot capture many of the crew errors that could occur. Go-around initiation heights overwhelmingly occur	-	Landings from unstable approaches rank in the top 5 UAS during the LDG phase and are the number 3 non-compliance item in the LOSA database) <b>LOSA</b>	the entire flight, acc operational and trai	
	ATQP       At heights different from those briefed.         Mismanagement of auto-flight systems, resulting in unstable approaches, are the biggest cause for goarounds in operations. A significant percentage of go-arounds result in flap over-speeds and violations of SOP. Engine out go-arounds form part of the regulated training programme, but still result in a significant percentage of unacceptable performance grades. Surprise go-arounds do not form part of the training programme, and are not well executed by crews in line operations. Consequently, the all –engines go-around is a target for improvement in ATQP.	Specifics	[Unstable approaches leading] to a go-around have an FDA all event rate of 1.6 occurrences in the immediate phases after go-around (GA, CLB) <b>FDA/EBT</b>	universality have not usually expec demanding condi	
			The high-risk event rate for the same period is 0.24 [24% for go-arounds from unstable approaches]. Both these rates are conservative because the flight recorder cannot capture many of the crew errors that could occur <b>FDA/EBT</b>	those practiced in the paradox, one issue acquire the necess activities within the interest of the the the second	
ATQP			Go-around initiation heights overwhelmingly occur at heights different from those briefed - FDA/EBT	situation, utilising a	
			Mismanagement of auto-flight systems, resulting in unstable approaches, are the biggest cause for go- arounds in operations <b>ATQP</b>	The multi-source da the go-around in op Around manageme of any strategy dev training. It is a key	
			The reason most often cited is a feeling that the landing can be successful despite the unstable condition. In the majority of the cases the prospect of a go-around is not discussed during an unstable approach. Pilots report a psychological barrier to performing a go-around <b>Pilot Survey</b>		
	The survey shows as pilots readily admit that they are not going around per the airline SOP. The		Input from Evidence Table		
	reason most often cited is a feeling that the landing		Input from EBT Accident-Incident Study	1	
Pilot Survey	can be successful despite the unstable condition. In the majority of the cases the prospect of a go- around is not discussed during an unstable approach. Pilots report a psychological barrier to	Training	This crew error is ranked high in IATA accident analysis and the report recommends training in go-arounds with regard to decision-making and execution of any type of go-around, at any point during the approach IATA Safety		
	performing a go-around.	Lifect	Input from Evidence Table		
	The results from IATA accident statistics support the		Input from EBT Accident-Incident Study		
	to go-around when the approach is unstable. This crew error is ranked high in IATA accident analysis		Engine out go-arounds form part of the regulated training programme, but still result in a significant percentage of unacceptable performance grades <b>ATQP</b>		
	and the report recommends training in go-arounds with regard to decision-making and execution of any type of go-around, at any point during the	Criticality	Surprise go-arounds do not form part of the training programme, and are not well executed by crews in line operations. Consequently, the all –engines go-around is a target for improvement in ATQP <b>ATQP</b>		
	approach.		Input from Evidence Table		
			Input from EBT Accident-Incident Study		

#### Narrative

aradicate unstable approaches and to mandate an unstable approach occur, the occurrence proaches remains significant as well as the fact nply do not go around as mandated. A major e approaches is the disregard of the SOP's, in eacy of threat and error management during the ling to the LOSA report, there is a "90% (SOP) terms of not executing a go-around from an

es are often a barometer for the flight itself. If orly executed, there are strong indications from ite of errors and risk events will be higher across cording to FDA and LOSA. Data from multiple ining sources indicate that crews almost roblems with the go-around. This is because it is ed, and may have to be executed under ons, from altitudes and energy states other than training. When unravelling the unstable approach e remained clear throughout; flight crews must sary capability to execute a go-around from any automation and/or manual control skills as

ata are quite compelling on the current state of perations and training today. Yet variable Go ent with all engines operating does not form part veloped through the regulation of flight crew topic and needs a training strategy to raise to the necessary capabilities of pilots.



### 13.2.6 Weather

			Summary Analysis Weather (WX)		
Sources	Summaries	Outline	Excerpts		
	Weather is the number 1 threat in the LOSA database and significant in all flight phases. 8% of		Weather is the number 1 threat in the LOSA database and significant in all flight phases - LOSA	Despite improvements i clear from multi-source	
	all flights encounter thunderstorms with over 6% of		The top threat in the IATA accident reports is weather IATA	threat to the safety of co	
LOSA	unstable approaches are due to weather. Turbulence exacerbates other common errors,		Weather is a major threat for flight crews, and this source continues to corroborate the threat <b>Incident Study</b>	factor, and this is corrol concerning in Gen 2 air	
	specifically manual aircraft control. Weather	Droblom	Weather is the number 1 threat or in top three in all phases of flight LOSA	which weather has been	
	compliance (25%), poor planning and radar misuse.	Problem	Weather threats are reported at 17.8% in the all-flight database - Incident Study	tasks, including monitor	
	The number 1 error associated with ice and snow is		Input from Evidence Table	crew error.	
FDA Long	failure to select the anti-ice system on.         In low visibility and/or crosswind conditions common errors such as "duck under" and misalignment with the runway centreline are more		Averse weather is the number 1 factor in all accidents in recent years for all generations with the exception of Gen 2 jets where it is 2nd. It has decreased along with the accident rate but not nearly to the same extent.	The data indicate that of trainable, and that the of dynamic and variable w manage, avoid and read	
Body			Input from EBT Accident-Incident Study	data about adverse wea	
Pilot Survey	The survey showed that in the opinion of the pilots, WX is the most important training need. This result came from the analysis of voluntary comments	Specifics	8% of all flights encounter thunderstorms with over 6% of these encounters resulting in UAS <b>LOSA</b>	flight crews from advers	
			Turbulence exacerbates other common errors, specifically manual aircraft control		
	made by the pilots <b>Pilot Survey</b> The top threat in the IATA accident reports is		Weather avoidance errors are associated with SOP non-compliance (25%), poor planning and radar misuse <b>LOSA</b>		
IATA Safety	weather - IATA		In low visibility and/or crosswind conditions common errors such as "duck under" and misalignment with the runway centreline are more critical in long body aircraft. <b>FDA/LB</b>		
	source continues to corroborate the threat. The fact		Input from Evidence Table		
Incident	that it is ranked so low according to the training		Input from EBT Accident-Incident Study		
Study	database), indicates that new pilots are absorbed	Training	Input from Evidence Table		
	with other concerns, related to errors <b>Incident</b>	Effect	Input from EBT Accident-Incident Study		
	Study		The survey showed that in the opinion of the pilots, WX is the most important training need <b>Pilot Survey</b>		
		Criticality	Input from Evidence Table		
			Input from EBT Accident-Incident Study		

#### Narrative

in aircraft design and automation systems, it is data that adverse weather is still a very substantial commercial air transport operations. Accident and idicate a strong presence of adverse weather as a borated by operations data. The trend is particularly rcraft where the percentage of fatal accidents in en a factor has doubled in the last 15 years. ases workload, distracts the crew from normal ring, and increases the risk of mismanagement of

operations in adverse weather should be effectively creation of training scenarios should include veather conditions, forcing crews to consider and loct as conditions require. This EBT study is rich with ather from many sources offering the opportunity to to mitigate the seemingly ever-present threats to se weather.



## 13.2.7 System Malfunction

Summary Analysis System Malfunction				
Sources	Summaries	Outline	Excerpts	
	There is a high degree of intentional non- compliance associated with procedures during the management of unexpected system		unexpected system malfunction is in the top 5 threats as well as in the top 5 mismanaged threats in LOSA database. System malfunction ranks 3rd as a contributory factor in UAS - <b>LOSA</b>	According to EBT a reduced as a factor reliability of moderr
LOSA	malfunctions. In addition, unexpected system malfunction is in the top 5 threats as well as in the top 5 mismanaged threats in LOSA		Procedures and handling associated with manoeuvres after engine failure result in the highest rates of unacceptable performance in training <b>ATQP</b>	significant contribut
	database. System malfunction ranks 3rd as a contributory factor in UAS.	Problem	Sys Mal is an important training need in terms of the non-normal checklists (ranked 3rd). Result is from the analysis of voluntary comments made by the pilots. <b>Sys Ma</b> l	unexpected malfun operations data, reported
	Procedures and handling associated with manoeuvres after engine failure result in the	FIODIeIII	system malfunctions still rank as a major cause of accidents (11%) their percentage of total accidents <b>CAST</b>	vulnerability of clos
ΑΤΟΡ	highest rates of unacceptable performance in training on		Input from Evidence Table	understood, and the
Alter	engine failure, its effects continue to be problematic to crews in terms of procedures and manual aircraft control.		System Malfunction is much less of a factor in newer generation aircraft as compared to older generation aircraft by about 3 to 1. However the trend for all aircraft is rising and aircraft malufunctions remain important in air crew training.	substantially. Howe aircraft in unexpect to crews, and there the psychomotor sk
	The survey showed that in the opinion of the		Input from EBT Accident-Incident Study	engine inoperative
Pilot Survey terms	pilots, Sys Mai is an important training need in terms of the non-normal checklists (ranked 3rd). This result came from the analysis of	Spacifics	There is a high degree of intentional non-compliance associated with procedures during the management of unexpected system malfunctions LOSA	
	voluntary comments made by the pilots.	Specifics	Input from Evidence Table	
	The FAA skill decay study tends to support the		Input from EBT Accident-Incident Study	
	notion that system malfunction proficiency is resistant to skill decay over time. The skill retention study conclusions are consistent with this finding. Management of the majority of malfunctions involves following defined procedures and checklists, the exception	Training Effect	Despite the emphasis in training on engine failure, its effects continue to be problematic to crews in terms of procedures and manual aircraft control <b>ATQP</b>	
Skill Decay			The FAA skill decay study tends to support the notion that system malfunction proficiency is resistant to skill decay over time. The skill retention study conclusions are consistent with this finding - <b>Skill Decay</b>	
	being a malfunction not anticipated by		Input from Evidence Table	
	unexpected consequences. It is likely that		Input from EBT Accident-Incident Study	
	skills required to deal with a less defined problem or malfunction will be more vulnerable		It is likely that skills required to deal with a less defined problem or malfunction will be more vulnerable to decay <b>Skill Decay</b>	
	to decay. While system malfunctions still rank as a major cause of accidents (11%) their percentage of	Criticality	[The percentage of total accidents [attributed to system malfunctions] has decreased approximately 20% when comparing the last ten-years to the previous ten year-period CAST	
CAST	total accidents has decreased more than 20%		Input from Evidence Table	
	previous ten year-period.		Input from EBT Accident-Incident Study	

#### Narrative

accident-incident data, systems malfunction has or in accidents and major incidents as design and on aircrafts have evolved. However, this is not ration 2 aircraft and system malfunctions are a utor to undesired aircraft states, which are a pres and accidents. The management of an inction induces crew error, and according to emains a threat partly due to the distraction from entional noncompliance with procedures and the sed loop tasks.

engine reliability are well documented and ne rate of engine failures has reduced ever, training data indicate that handling the cted engine-out situations still presents difficulty e remains a clear need to continue to practice skills based capability to fly the aircraft with an e as part of an EBT programme.



### 13.2.8 Terrain

			Summary Analysis - Terrain	
Sources	Summaries	Outline	Excerpts	
LOSA indicates that proper altimeter use should be emphasized during training and terrain is one of the most important mismanaged threats in LOSA database. In addition, Airlines that operate in high terrai environment tend to be complaisant to terr threat.	LOSA indicates that proper altimeter use should be emphasized during training and that		LOSA indicatesthat terrain is one of the most important mismanaged threats in LOSA database LOSA	There has a been a with terrain as a fac
	terrain is one of the most important mismanaged threats in LOSA database. In addition, Airlines that operate in high terrain	Problem	While terrain still rank as a major cause of accidents (9%) their percentage of total accidents has decreased approximately 50% when comparing the last ten-years to the previous ten year-period <b>CAST</b>	regulation. Howeve decline in flight crev and terrain remains
	environment tend to be complaisant to terrain		Input from Evidence Table	effective alerting sys
			Terrain as a factor generally ranks lower in recent years and that effect is much more pronounced in newer aircraft.	to ensure crews are not become compla
FAA HF Report	The FAA Automation report found disturbing occurrences of lack of situation awareness in		Input from EBT Accident-Incident Study	
	regards to flight path proximity to terrain. It recommends increasing the understanding of	Specifics	Airlines that operate in high terrain environment tend to be complaisant to terrain threat. - <b>LOSA</b>	
	the crews with regard to this deficiency and the potential risks involved.		The FAA Automation report found disturbing occurrences of lack of situation awareness in regards to flight path proximity to terrain - <b>FAA HF</b>	
	The TAWS Saves report is essentially an		Pilot vulnerabilities are flight path, terrain and energy awareness FAA HF	
	accident report without an accident. Five		Input from Evidence Table	
	incidents that the writers of the report felt would probably have resulted in accidents are studied in an accident-investigation format. Two major points emerge from this report. Firstly, a proper EGPWS is an effective tool in reducing CFIT accidents and secondly, that no		Input from EBT Accident-Incident Study	
		Training	Input from Evidence Table	
TAWS		Effect	Input from EBT Accident-Incident Study	
			It recommends increasing the understanding of the crews with regard to this deficiency and the potential risks involved FAA HF	
	matter how good the warning system is, terrain avoidance still depends on a properly trained reaction of the flight crew.	Criticality	Firstly, a proper EGPWS is an effective tool in reducing CFIT accidents and secondly, that no matter how good the warning system is, terrain avoidance still depends on a properly trained reaction of the flight crew TAWS	
	While terrain still rank as a major cause of		Input from Evidence Table	
	accidents (9%) their percentage of total		Input from EBT Accident-Incident Study	
CAST	accidents has decreased approximately 50% when comparing the last ten-years to the previous ten year-period.			

#### Narrative

a significant reduction in accidents and incidents ctor since the inception of recent TAWS eer, the data from several sources indicate a ew situation awareness with regard to and terrain s one of the most important mismanaged threats lst advancing technology has provided a very system, attention needs to be placed on the need e vigilant and maintain at a high level of SA and aisant with regards to terrain.



### 13.2.9 Surprise

Summary Analysis - Surprise				
Sources	Summaries	Outline	Excerpts	
LOSA	GA is generally a surprise to crew and not well performed. An unexpected malfunction is number 4 threat as well as number 4		A high percentage of pilots found themselves in a 'surprise' situation after initial training. These uncomfortable situations continued in despite experience on type <b>Pilot Survey</b>	As design and relia specific malfunction unexpected events improved but atten
	Surprises need to be incorporated in training		It is clear from what the pilots are saying that current training does not deal adequately with unexpected operational situations <b>Pilot Survey</b>	complex. A lack of e of automation often
ATQP	particularly with respect to automation and engine failure situations both from a proactive	Problem	The report found that pilots could be surprised by subtle behaviour and overwhelmed by complexity of current systems operated in current flight environment <b>FAA HF</b>	that cognitive tasks control in dynamic s where there are atte
	and reactive perspective		Input from Evidence Table	system or ATC.
A high percentage of pilots foun in a 'surprise' situation after initia These uncomfortable situations despite experience on type. Au surprises are particularly proble majority of respondents report th number 1 topic for automation to improvement. It is clear from wh are saying that current training of adequately with unexpected ope situations.	A high percentage of pilots found themselves in a 'surprise' situation after initial training. These uncomfortable situations continued in despite experience on type. Automation		The trend for situational awareness as a competency issue is improving slightly or remaining stabe for older aircraft but becoming worse for newer aircraft. It is ranked 2nd in occurrence after manual aircraft control for all accidents and serious incidents.	Pilots reported that they have not been accident and seriou situation awareness
	surprises are particularly problematic as the		Input from EBT Accident-Incident Study	Despite all the data
	majority of respondents report this issue as the number 1 topic for automation training improvement. It is clear from what the pilots		GA is generally a surprise to crew and not well performed. An unexpected malfunction is number 4 threat as well as number 4 mismanaged threat in LOSA database <b>LOSA</b>	regulatory requirem training programme
	are saying that current training does not deal adequately with unexpected operational	Specifics	Automation surprises are particularly problematic as the majority of respondents report this issue as the number 1 topic for automation training improvement - <b>Pilot Survey</b>	crews face substan
	situations.		Input from Evidence Table	go-around, simply b
IATA Safety	Maintaining situation awareness by specific briefings as well as monitoring and cross checking are effective countermeasures for dealing with all operational situations, including surprises. The IATA accident reports		Input from EBT Accident-Incident Study	performed in condit
			Maintaining situation awareness by specific briefings as well as monitoring and cross checking are effective countermeasures for dealing with all operational situations, including surprises <b>IATA Safety</b>	
	recommend training to deal with unusual "edge of the envelope" situations as well as specific training to cope with surprise go-arounds.	Training Effect	The IATA accident reports recommend training to deal with unusual "edge of the envelope" situations as well as specific training to cope with surprise go-arounds IATA Safety	
	The report found that pilots could be surprised by subtle behaviour and overwhelmed by complexity of current systems operated in	Lincot	The evidence shows vulnerabilities to surprise because of incomplete system understanding as well as the lack of appropriate responses in terms of utilizing the appropriate responses in dealing with the situations <b>FAA HF</b>	
	current flight environment. The evidence		Input from Evidence Table	
	shows vulnerabilities to surprise because of incomplete system understanding as well as		Input from EBT Accident-Incident Study	
FAA HF	the lack of appropriate responses in terms of utilizing the appropriate responses in dealing		Surprises need to be incorporated in training particularly with respect to automation and engine failure situations both from a proactive and reactive perspective - <b>ATQP</b>	
Report	with the situations. The report recommends dedicated LOFT type training to give pilots practice in responding to system surprises, promoting better system understanding through training and developing good	Criticality	The report recommends dedicated LOFT type training to give pilots practice in responding to system surprises, promoting better system understanding through training and developing good decisions and proper execution regarding reversion to appropriate levels of automation when surprises occur. <b>FAA HF</b>	
	decisions and proper execution regarding		Input from Evidence Table	
	when surprises occur.		Input from EBT Accident-Incident Study	
	'			

#### Narrative

ability improve, the likelihood of crews facing ns and events reduces. Isolated and s become more problematic as reliability is iding to the overall system becomes more effective procedural and conceptual knowledge n leads to surprises in operations. Data indicate s have potential for skills decay and flight path situations is often more demanding especially tendant distractions from the environment,

t they often face operational surprises for which n trained. In modern generation aircraft, the us incident data show an increase in poor s when things go wrong.

a, current training is driven by highly prescriptive nents based on evidence from early jets and es contain many elements, most of which are Data from operations and training indicate ntial problems when dealing with unexpected e executing an unanticipated all engine operative because they are unexpected and often itions not experienced in training.



# 13.2.10 Landing Issues

Summary Analysis - Landing Issues						
Sources	Summaries	Outline	Excerpts	Narrative		
	1% of all landings in LOSA database result in		1% of all landings in LOSA database result in an abnormal landing LOSA	According to multiple accident studies the landing phase ranks first		
	an abnormal landing. The number 3 non- compliance item in the database is landing from an unstable approach. Aircraft handling		According to the IATA accident reports, the number 1 UAS is improper landing IATA Safety	According to multiple accident studies the landing phase ranks first or second as the phase with the highest percentage of accidents and this trend is increasing. One study shows that accidents		
LOSA	errors on landing are not well detected as they rank 2 <sup>nd</sup> in least detected error during landing		Landing issues are a major component of all aircraft accidents and are increasing as shown by the data in the last 20 years <b>CAST</b>	involving a landing short of the runway have doubled in the last decade. Landing problems are complex, as the accident-Incident data ranks landings accidents number 1 in the dustoring of factors		
	phase. The early commencement of after landing and taxi-in during the landing rollout is		Reported landing incidents account for 13% of reports in the main ASR database Incidents	data ranks landings accidents number 1 in the clustering of factors. According to operational data the third most frequent non- compliance item is landing from an unstable approach; the same		
	prevalent and ranked 5 overall in non- compliance.		In the last two decades the statistics show a significant increase in the proportion of accidents related to various landing issues particularly with regard to runway excursions and landing short CAST	study also indicated that handling errors on landing are not well detected. Training data indicates that landing skills take time to develop,		
	long body aircraft, especially with respect to heavy landings. Pilots need to be especially	Problem	The phase with the highest percentage of accidents is the landing phase at $\underline{41}\%$ - CAST	In the skills necessary in landing without practice, as well as the need for emphasis on training to better understand environmental and aerodynamic		
FDA Long body	In addition, pilots need to under the glideslope. In addition, pilots need to understand the and differences in ground speed and momentum		In the last decade landing short (undershoots) were 6%, more than double the previous decade - <b>CAST</b>	effects associated with landing. Most importantly realistic training should continually emphasise when and how to apply the go – around as a landing escape manoeuvre		
	as well as perceptual differences both laterally		The top UAS in the IATA accident reports is improper landings at 21% IATA Safety			
	and vertically resulting from the extended length between the main gear and cockpit.		Input from Evidence Table The landing phase is ranked number 1 or 2 in terms of accidents for all aircraft generations. The newer generation aircraft seem to have less problems than the earlier aircraft with the excention of gen 2 props where mechanical issues greatly affect			
	Gen 3 and 4 jet aircraft indicated that automation (autoland and		the results. Input from EBT Accident-Incident Study			
Landing Study T d a	autothrottle/autothrust) provide greater touchdown accuracy, with Gen 4 jet aircraft being more accurate than Gen 3 jet aircraft. The two parameters most affecting airborne distance are threshold crossing height and airspeed over-speed at threshold, in that order. According to the IATA accident reports, the number 1 UAS is improper landing. Training should reinforce GA from abnormal landings.	Specifics	Landing events are statistically more likely with long body aircraft, especially with respect to heavy landings - <b>FDA LB</b>			
			41% of all accidents happen in the landing phase, by far the leading phase in which accidents occur <b>CAST</b>			
			there are landing problems with stable approaches as well as unstable approaches <b>EBT FDA</b>			
IATA Safety			Speed control is major error LOSA			
			Low error detection rates relating to specific aircraft handling issues LOSA			
	Reported landing incidents account for 13% of		Input from Evidence Table			
Incident	coupled with the fact that manual handling is		Interestingly, the factors in landing have the greatest clustering factor.			
Study	ranked 2 <sup>nd</sup> implies that there is still a		Input from EBT Accident-Incident Study	-		
	considerable amount of learning skills are not fully acquired prior to IOE. Landings are generally practiced in the interval		FDA statistical analysis on a large sample of Gen 3 and 4 jet aircraft indicated that automation (autoland and autothrottle/autothrust) provide greater touchdown accuracy, with Gen 4 jet aircraft being more accurate than Gen 3 jet aircraftLanding Study			
	between training cycles and so not generally a problem for skill decay. This is indicated in the	Training Effect	The two parameters most affecting airborne distance are threshold crossing height and airspeed over-speed at threshold, in that order Landing Study			
Skill Decay	problem for pilots without landing practice, and		Input from Evidence Table			
	this may affect those involved in ultra long haul		Input from EBT Accident-Incident Study			
	operations.		Pilots need to be especially cognizant of not 'ducking under' the glideslope FDA LB			
	Landing issues are a major component of all aircraft accidents and are increasing as shown by the data in the last 20 years. 41% of all		In addition, pilots need to understand the and differences in ground speed and momentum as well as perceptual differences both laterally and vertically resulting from the extended length between the main gear and cockpit <b>FDA LB</b>			
	accidents happen in the landing phase, the		Training should reinforce GA from abnormal landings IATA Safety	1		
CAST	leading phase in which accidents occur. In the last two decades the statistics show a significant increase in the proportion of accidents related to various landing issues	Criticality	This [13% report rate] coupled with the fact that manual handling is ranked 2nd implies that there is still a considerable amount of learning skills are not fully acquired prior to IOE <b>Incidence Study</b>			
	particularly with regard to runway excursions and landing short.		Skill decay is a problem for pilots without landing practice, and this may affect those involved in ultra long haul operations <b>Skill Decay</b>			
			Input from Evidence Table			
			Input from EBT Accident-Incident Study			



### 13.2.11 Compliance

	Summary Analysis - Compliance							
Sources	Summaries	Outline	Excerpts	Narrative				
<ul> <li>There is a significant positive correlation between non-compliance and UAS, while there is a negative correlation between non-compliance and error. 25% of all errors are non-compliance errors. The top ranked non-compliance error is checklist protocol, followed by omitted call-outs. Omitted call-outs results have highest risk (65% lead to UAS). The 3<sup>rd</sup> ranked non-compliance issue is failure to execute a missed approach when required. The 4<sup>th</sup> and 5<sup>th</sup> ranked non-compliances are PF making their own changes and PM commencing taxi duties before leaving runway respectively. With respect to weather avoidance errors, 25% result from deviations without ATC clearances. Paradoxically, the fact that most errors are inconsequential reinforces crew inaction, creating additional non-compliance with associated negative effects.</li> </ul>	There is a significant positive correlation between non-compliance and UAS, while there is a negative correlation between non- compliance and error. 25% of all errors are non-compliance errors. The top ranked non- compliance error is checklist protocol, followed by omitted call-outs. Omitted call-outs results have highest risk (65% lead to UAS). The 3 <sup>rd</sup>		There is a significant positive correlation between non-compliance and UAS, while there is a negative correlation between non-compliance and error LOSA 25% of all errors are non-compliance errors LOSA The biggest problem with NCGs (non-conforming grades) throughout all operational evaluations is non-compliance with airline policy, amounting to 50% of errors committed - AQP 21% of pilots admit to call out Intentional deviations on virtually every flight - Pilot	Intentional non-compliance remains a substantial problem, and whilst the level of crew non-technical competency has shown signs of improvement over the most recent periods examined, intentional non - compliance remains a serious weakness in current operations. It has decreased somewhat in the last 15 years but not at the same rate as has accidents. A notable exception to this is generation 2 where the rate has actually increased. There are				
	Problem	Survey         13% if pilots admit to intentional deviations from checklists on a frequent basis Pilot         Survey         The IATA reports echo LOSA findings. Compliance is rated as one of the top errors - IATA Safety         The 1 <sup>st</sup> ranked non-compliance issue is checklist protocol with 50% occurring on the ground - LOSA         18% of pilots admit that they deviate from checklists frequently - Pilot Survey         Input from Evidence Table	many potential reasons for crews to deviate routinely from SOP's and these include attempts to optimise the operation, particularly ir time constrained situations. Complacency due to familiarity may be another factor. However, the data show significant correlation between non – compliance and large increases in risk of undetected errors and undesired aircraft states. Checklist and call- out protocols show substantial signs of weakness. The failure of crews to execute a Go-round under conditions when SOP requires is a very significant area of intentional non-compliance. Pilots admi to call-out and checklist deviations on a regular basis, as well as the failure to adhere to approach procedures and execute Go- rounds when required.					
FDA Long body	In long aircraft, following the recommendations of the manufacturer provided in SOP's and training mitigates the tendency toward high "G" landings. Application of take-off procedures is equally important in the prevention of "pilot		The issue of compliance in accidents has been decreasing in the last 15 years as opposed to the previous time period. A notable exception to this are the Gen 2 aircraft, both jet and prop where the trend is reversed. Input from EBT Accident-Incident Study	Crew discipline has always been assumed to be a pillar supporting operational safety and now the data show its breakdown. Crews must understand that intentional non-compliance, correlates highly with errors resulting in undesired aircraft states and that compliance failures also rank highly in accident data.				
induced oscillations" during take-off           The biggest problem with NCGs (non conforming grades) throughout all op evaluations is non-compliance with a policy, amounting to 50% of errors co. In addition, non-compliance with interprocedures is also substantial. The fl where the crews have the most difficifollowing procedures is DES. Data from international flights show that the CF has significantly more NCGs than do flights	Induced oscillations" during take-off The biggest problem with NCGs (non- conforming grades) throughout all operational evaluations is non-compliance with airline policy, amounting to 50% of errors committed. In addition, non-compliance with international		The top ranked non-compliance error is checklist protocol, followed by omitted call- outs. Omitted call-outs results have highest risk (65% lead to UAS) LOSA The 3rd ranked non-compliance issue is failure to execute a missed approach when required -LOSA With respect to weather avoidance errors, 25% result from deviations without ATC	Crews are currently trained to comply and demonstrate adherence to SOP, but detecting and addressing non-compliance is not a feature of existing training programmes. Data indicate that effective training and appropriate focus on areas such as leadership can address non-compliance.				
	procedures is also substantial. The flight phase where the crews have the most difficulty in following procedures is DES. Data from international flights show that the CRZ phase has significantly more NCGs than domestic flights	Specifics	clearances LOSA The flight phase where the crews have the most difficulty in following procedures is DES - AQP In a go around situation 71% of time, neither pilot mentioned a go-around - Pilot Survey					
	Pilot Survey is probably most revealing in the subject of compliance. If what LOSA postulates is true i.e. that the error rate is multiplicative when non compliance is involved, then the following statistics speak for themselves:         Pilot Survey       • 21% of pilots admit to call out Intentional deviations on virtually every flight.         • 13% if pilots admit to intentional deviations from checklists on a frequent basis.         • In a go around situation 71% of time neither pilot mentioned a go-around.		Input from Evidence Table Input from EBT Accident-Incident Study Input generatif following the recommendations of the menufactures provided in SOP/a					
Pilot Survey		Training Effect	and training mitigates the tendency toward high "G" landings. FDA LB Data indicate issues with checklists and SOPs, which are similar despite varying experience levels - Incident Study Input from Evidence Table For accidents with high training effect the rate of compliance as an issue is significantly					
			higher. Input from EBT Accident-Incident Study					
IATA Safety	The TATA reports echo LOSA findings. Compliance is rated as one of the top errors and specific training is recommended		the fact that most errors are inconsequential reinforces crew inaction, creating additional non-compliance with associated negative effects LOSA	-				
	particularly with respect to following SOPs (i.e. to go-around) when an approach is not stable, and when the landing is improper.		around) when an approach is not stable, and when the landing is improper - IATA Safety					
Incident Study	STEADES data draws little distinction between the two groupings of flights (training and all flights). Most of the training flights are for the purpose of IOE, and data indicates issues with checklists and SOPs, which are similar despite varying experience levels.         Criticali		LOSA advocates TEM for intentional non-compliance - LOSA (4.1.15) Crews operating Gen 3 jet aircraft show a greater percentage of intentional non- compliance and decision making errors than crews operating Gen 4.jet aircraft. This difference increases as the training cycle progresses AQP (4.3.1.2) Input from Evidence Table					
UK CAA Accident Study	Part of the team that authored CAA CAP 780 Report analysed the fatal accidents set used in the CAP 780 Report (i.e. occurring during the period between 1 January 1997 and 31 December 2008 (inclusive)) for the EBT Data Report. The analysis was made in terms of the threats and errors defined in the EBT Training Criticality Survey (TCS) and the study determined that compliance failure ranked number 2 at a 19.1% rate of occurrence		Input from EBT Accident-Incident Study					



### 13.2.12 Leadership

	Summary Analysis - Leadership						
Sources	Summaries	Outline	Excerpts	Narrative			
LOSA	Leadership is an effective positive catalyst in terms of reducing errors per flight, provided		The pilot survey provided both encouraging and discouraging results with regard to leadership - <b>Pilot Survey</b>	Leadership and teamwork as an comp			
LOOA	that it is accompanied by good communications.		Flights with poor ratings [in Leadership] have approximately 3 times the number of mismanaged threats to those without poor ratings <b>LOSA</b>	even more pronounced for modern gen the prevalence of a non-compliance cul			
	ATQP training and operational data provide	Problem	Input from Evidence Table	appropriate leadership focus. Several of			
ATQP	encouraging results showing that leadership showed remarkable improvement in training as well as better performance on the line.		Leadership and teamwork as an competency issue has more than doubled in recent years. This is the case for all generations but it is even more pronounced for modern generation aircraft.	Data from pilots indicate a willingness to leadership and make decisions enhanc of operational safety.			
	The pilot survey provided both encouraging		Input from EBT Accident-Incident Study	The absence of effective leadership in t			
	and discouraging results with regard to leadership. On the one hand most pilots are willing to make appropriate decisions to		there is too often a casual attitude indicated by significant intentional disregard for procedural compliance <b>Pilot Survey</b>	to undesired aircraft states. Conversely with effective communication proves to			
Pilot Survey	promote safety. However, there is too often a casual attitude indicated by significant	Specifics	In cases where a GA should have been performed, 71% of the times neither pilot mentioned GA <b>Pilot Survey</b>	for managing threats and both reducing From a training perspective, data indica			
	intentional disregard for procedural		Input from Evidence Table	which in turn necessitates the careful de			
	Compliance.		Input from EBT Accident-Incident Study	procedures and adherence to them. The			
FAA HF Report	complex automated airline environment is especially important. The traits involved relate to understanding the process as well as making good decisions as a team, particularly in unfamiliar situations.	Training Effect	ATQP training and operational data provide encouraging results showing that leadership showed remarkable improvement in training as well as better performance on the line <b>ATQP</b>	teamwork is not reported as a competer incidents indicates the importance of it a accidents as well as its importance in tr Strengthening leadership in training imp			
			The traits involved relate to understanding the process as well as making good decisions as a team, particularly in unfamiliar situations <b>FAA HF</b>	risk will be reduced crews should be a as a team with today's complex enviro			
			Flights with outstanding ratings for "Leadership and Communication Environment" have on average 2.3 errors per flight, versus 7 Errors per flight for poor "Leadership and Communication Environment." - <b>LOSA</b>	effectively when faced with unfamiliar si			
			Effective training encourages and enhances leadership, and this is demonstrated by improved leadership and workload management performance grades data in training, in addition to better adherence to company criteria in operations <b>ATQP</b>				
			ATQP data shows that leadership can be effectively be improved through training <b>ATQP</b>				
			Input from Evidence Table				
			The fact that leadership and teamwork is not reported as a competency issue in serious incidents indicates the importance of it as a mitagating agent in accidents as well as its importance in training.				
			Input from EBT Accident-Incident Study				
			Leadership is an effective positive catalyst in terms of reducing errors per flight, provided that it is accompanied by good communications <b>LOSA</b>				
		Criticality	The report found that leadership in the complex automated airline environment is especially important - <b>FAA HF</b>				
			Input from Evidence Table				
			Input from EBT Accident-Incident Study	1			



the cockpit adds d threats and errors leading y, leadership when coupled b be a very effective catalyst g and managing errors. ate that leadership can be strong compliance culture, design of effective he fact that leadership and

e fact that leadership and ency issue in serious as a mitagating agent in raining.

proves compliance, hence ble to deal more effectively mment and function more ituations.



### 13.2.13 Mismanaged Aircraft State

	Summary Analysis - Mismanaged Aircraft State							
Sources	Summaries	Outline	Excerpts	Narrative				
	Omitted callout deviations are associated with the greatest risk; 65% of omissions contribute		The report found weakness in prevention of mismanaged aircraft states as well as in the skills to recover from them after entry - <b>FAA HF</b>	Mismanaged aircraft state is a leading factor in the a serious incident reports in all generations and during				
LOSA	towards UAS. Intentional non-compliances correlate positively with UAS rates. The flight		Even though the accident rate has decreased in the last 20 years, the rate of accidents due to mismanaged aircraft has increased - <b>CAST</b>	periods. There is a reported weakness in prevention mismanaged aircraft states as well as in the skills to				
LODA	phases having the most mismanaged aircraft states are DES, APP and LDG. Detected handling errors account for between 20% -	Problem	The training flight database is heavily populated with incidents that are classified as mismanaged aircraft states - <b>Incidents</b>	them after entry. Examples are landing incidents follo approaches and manual aircraft control competency				
	40%, but most are not detected until a mismanaged aircraft state occurs.		Go-arounds continue to be mismanaged and 50% of them result from mismanaged approaches <b>ATQP</b>	are of significance from a training perspective. Aircraft states cited include flight path issues involvir				
	Studies during ATQP highlight the need for		Input from Evidence Table	and actual loss of control, terrain and energy awarer				
	specific training in planning and energy management to reduce mismanaged aircraft		Mismanaged aircraft state is a leading factor in the accident and serious incident report in all generations and during all time periods.	phases having the most mismanaged aircraft states approach and landing. Effort needs to focused on de				
ATQP	mismanaged and 50% of them result from		Input from EBT Accident-Incident Study	during these dynamic phases a large percentage are				
	mismanaged approaches. During the go- around, mismanaged autoflight continues to result in mismanaged aircraft states including		The flight phases having the most mismanaged aircraft states are DES, APP and LDG. Detected handling errors account for between 20% - 40%, but most are not detected until a mismanaged aircraft state occurs - <b>LOSA</b>	until after the state becomes critical. Recommendations include regular training to avoid r aircraft states as well as recovery from inadvertent e				
	flap over-speeds and SOP violations. Mismanaged aircraft states occur for many		During the go-around, mismanaged autoflight continues to result in mismanaged aircraft states including flap over-speeds and SOP violations <b>ATQP</b>	reinforcement training in basic flying skills such as m handling, landings and go-arounds. Flight crews are revert to manual flight from automation, while basic r				
IATA Safety	reasons. The IATA report recommends reinforcement training in basic flying skills such as manual handling, landings and go-arounds. Flight crews are reluctant to revert to manual flight from automation, while basic manoeuvres such as landings and go-arounds continue to be a problem. The reports propose that proficiency and confidence be fostered during training.	Specifics	Flight crews are reluctant to revert to manual flight from automation, while basic manoeuvres such as landings and go-arounds continue to be a problem IATA Safety	such as landings and go-arounds continue to be a preports propose that proficiency, discipline and confid				
			The states cited include flight path issues involving loss of control, terrain and energy awareness. <b>FAA HF</b>	fostered during training to combat mismanaged aircr				
			Runway excursions, landing short and ground collision are all up and exemplify this trend - <b>CAST</b>					
			Input from Evidence Table	1				
The popu misn	The training flight database is heavily populated with incidents that are classified as mismanaged aircraft states while this is not nearly the case for the database of all flights. This fact is not only true for the rankings of the incidents, but also true for the percentages of actual reports with similar rankings across the	Training Effect	Omitted callout deviations are associated with the greatest risk; 65% of omissions contribute towards UAS. Intentional non-compliances correlate positively with UAS rates - LOSA					
Incident Study			Mismanaged aircraft states occur for many reasons. The IATA report recommends reinforcement training in basic flying skills such as manual handling, landings and go- arounds - <b>IATA Safety</b>					
	two groupings of flights. Examples of this are		Input from Evidence Table	]				
	unstable approaches (16.7% versus 8.3%), landing with incident EGPWS and manual		Input from EBT Accident-Incident Study					
	handling.		Studies during ATQP highlight the need for specific training in planning and energy management to reduce mismanaged aircraft states - <b>ATQP</b>					
	The report found weakness in prevention of mismanaged aircraft states as well as in the	Criticality	The reports propose that proficiency and confidence be fostered during training - IATA Safety					
FAA HF	skills to recover from them after entry. The states cited include flight path issues involving loss of control, terrain and energy awareness	onticality	Recommendations include regular training to avoid mismanage aircraft states as well as recovery from inadvertent entries. <b>FAA HF</b>					
	Recommendations include regular training to		Input from Evidence Table					
	avoid mismanage aircraft states as well as recovery from inadvertent entries.		Input from EBT Accident-Incident Study					
CAST	Even though the accident rate has decreased in the last 20 years, the rate of accidents due to mismanaged aircraft has increased. Runway excursions, landing short and ground collision are all up and exemplify this trend.							

#### accident and g all time n of o recover from lowing unstable y issues. a, all of which

ing potential eness. The flight s are descent, letecting the shows that re not detected

mismanaged entries and manual e reluctant to manoeuvres problem. The fidence be craft states.



# 13.2.14 Upset

Summary Analysis - Upset						
Sources	Summaries	Outline	Excerpts	Narrative		
IATA Safety	Training should enable pilots to respond to unexpected events throughout the flight regime at various levels of difficulties		The FAA automation report cited detection and recovery from unusual attitudes as an area of concern - <b>FAA HF</b>	While upset still ranks as a major cause of accidents when measured as a category in several accident reports, its perc of total accidents has remained steady in the last two decad		
FAA HF	The FAA automation report cited detection and recovery from unusual attitudes as an area of concern. It went on to recommend increasing flight crew understanding and sensitivity in maintaining situation awareness regarding	Problem	Upset still ranks as a major cause of accidents. Its percentage of total accidents has remained steady at around 13% in the last two decades. - <b>CAST</b>	Several reports in the meta-study list this category of accide a concern. Training should prepare pilots for any contingency whether expected or not. Manual aircraft skills are important as reiter many times in this report and pilots must have the skills to ex-		
Report	potential causes and detection of upsets from		Input from Evidence Table	the recoveries from the precursor states to those defined as		
wake vortex, autop and atmospheric d recommending adv an integral part of t	wake vortex, autopilot failures, engine failures		Input from EBT Accident-Incident Study	upsets. However prevention is key, with a strong focus on the detection and early intervention to prevent upsets from occur		
	recommending advance manoeuvre training	Specifics	Input from Evidence Table	This is the essential strategy that must become an integral p		
	an integral part of training.		Input from EBT Accident-Incident Study	training.		
	Upset still ranks as a major cause of accidents. Its_percentage of total accidents has remained steady at around 13% in the last two decades	Training	Input from Evidence Table			
CASI		Effect	Input from EBT Accident-Incident Study			
steady at around 13% in the last two deca		Criticality	Training should enable pilots to respond to unexpected events throughout the flight regime at various levels of difficulties - <b>IATA Safety</b>			
			It [FAA HF report] went on to recommend increasing flight crew understanding and sensitivity in maintaining situation awareness regarding potential causes and detection of upsets from wake vortex, autopilot failures, engine failures and atmospheric disturbances as well as recommending advance manoeuvre training an integral part of training <b>FAA HF</b>			
			Input from Evidence Table Input from EBT Accident-Incident Study			



he urring. part of



# APPENDIX 14 Graphic Visualisation of Ebt Accident-incident data

# INTRODUCTION

This appendix contains and analysis of most of the accident and serious incidents from the EBT accidentincident database. There is no Generation 1 Jet aircraft events nor is there any events from Generation 2 and 3 Prop. For this reasons no results were used in Chapter 2 - Major Results nor in Chapter 4 - Analysis. The benefit of this study is two fold:

- 1. To provide a verification of the main analysis of the EBT Accident-Incident Analysis detailed in Chapter 3 and 4.
- 2. Provide an intuitive visualization of the data and the basic processes of the analysis used in the EBT Accident-Incident analysis. With very large data sets this is not an easy task and the statistician who performed this study use some very interesting techniques and pictorials to do this.

Most of the analyses done here were also completed in the main study using a more complete data set. The study shown is this appendix is not replicated in the main study as it entailed analysis of all generations, which was not the objective of the EBT Accident-Incident study. However the graphics are illustrative and so, they are shown here.

Only a small excerpt of the study is shown in this appendix. Additionally, in the entire work, there are similar sets of illustrations by generations, periods of time and severity.

Some of the techniques used here are very interesting for futures development, particularly in the area of clustering. Factors can be clustered in various ways, such as the way it is done in the main study and in the way it is done here using correlations. There are other ways as well and the interest lies in seeing similarities in the clusters themselves and how this could relate to accident types and how that could provide a breakdown of skills required to be trained.



### 14.1 EBT ACCIDENT-INCIDENT DATASET PARTITION



Figure A14.1 – Severity distribution of a subsample of accidents and incident from EBT study

- F represents Fatal accidents
- N represents Nonfatal accidents
- I represents Serious Incidents
- U represents unclassified



Figure A14.1a - Visual representation of Accident - incident distribution

- F Fatal accidents
- F+N All accidents
- I Incidents



DATA SET PARTITION						
			2	675	LAST 15Y	129
			2	075	OLDER	546
		1160	3	303	LAST 15Y	295
	INCIDENTS	1100	5	393	OLDER	98
			4	02	LAST 11Y	76
			-	92	OLDER	16
	FATAL	188	2	107	LAST 15Y	70
			2	121	OLDER	57
			3	48	LAST 15Y	34
<b>ALL</b> 2306				40	OLDER	14
			4	13	LAST 11Y	9
					OLDER	4
			2	636	LAST 15Y	179
			2	030	OLDER	457
	EATAL + NON EATAL	1136	3	301	LAST 15Y	305
		1150	5	591	OLDER	86
			Δ	100	LAST 11Y	87
			-	109	OLDER	22
	U	10				

Figure A14.1b – Partition of the dataset showing raw numbers



### **14.2 STATISTICAL BREAKDOWN OF FACTORS AND COMPETENCIES**

Factor and Competency in terms of:

- Ranking by frequency of occurrence
- Number of accidents or incidents in which the factor/competency appears.
- Percentage of occurrence per event (flight with accident/incident).
- Rate of occurrence per flight in general (Normalized by 1 million Takeoffs)).
- Note: Rows with dotted background indicate Competencies.

Rank	Factor/ Competency Occurrence	Accidents/Incidents	%	Rate
1	Syst mal	859	37.3	1.66E-06
2	CRM	602	26.1	1.17E-06
3	Adverse Weather/Ice	585	25.4	1.13E-06
4	Mis A/C State	526	22.8	1.02E-06
5	Manual Aircraft Control	480	20.8	9.30E-07
6	Compliance	357	15.5	6.92E-07
7	SA	340	14.7	6.59E-07
8	Eng Fail	314	13.6	6.08E-07
9	Application of Procedures & Knowledge:	303	13.1	5.87E-07
10	Ground manoeuvring	279	12.1	5.40E-07
11	Fire	259	11.2	5.02E-07
12	Problem Solving Decision Making	217	9.4	4.20E-07
13	ATC	180	7.8	3.49E-07
14	Poor Visibility	175	7.6	3.39E-07
15	Ground equipment	138	6.0	2.67E-07
16	Runway/Taxi condition	135	5.9	2.62E-07
17	Traffic	119	5.2	2.31E-07
18	Cabin	119	5.2	2.31E-07
19	Leadership and Teamwork		3.8	1.70E-07
20	Mis-Svs	79	3.4	1.53E-07
21	Crosswind	76	3.3	1.47E-07
22	Communication	75	3.3	1.45E-07
23	Ons/Type Spec	59	2.6	1 14F-07
24	R/W Incursion	57	2.5	1.10E-07
25	Workload Distraction Pressure	52	2.3	1.01E-07
26	Terrain	51	2.2	9.88E-08
27	Knowledge	45	2.0	8.72E-08
28	Windshear	41	1.8	7.94E-08
29	Def-Proc's	40	1.7	7.75E-08
30	Flight Management: Guidance and Auton	40	1.7	7.75E-08
31	Def-Ops data	39	1.7	7.56E-08
32	Upset	34	1.5	6.59E-08
33	Mis-AFS	33	14	6 39E-08
34	Def Manuals	29	13	5 62E-08
35	Workload Management		12	5 23E-08
36	Birds	26	11	5.04E-08
37	Pilot Incap	24	1.1	4 65E-08
38	MFI	24	1.0	4 65E-08
39	Wake Vortex	16	0.7	3 10E-08
40	Physio	16	0.7	3 10E-08
40		12	0.7	2 32E-08
42	I FP	12	0.5	2 32E-08
43	Fatigue	10	0.0	1.94E-08
44	Def-Chk lists	0	0.4	1 74F-08
45	Loss of comms	9	0.4	1 165-08
46	Def-Charts	5	0.3	9.69E-00
47	NAV	5	0.2	7 75E-00
48	Def-DBs	4	0.2	3.87E-09
	50.230	2	0.1	0.07 - 00

Figure A14.2
#### 14.3 GRAPHIC DEMONSTRATING INTUITIVE SENSE OF OCCURRENCE RANKING FOR FACTORS AND COMPETENCIES

The Histogram shows a bar graph representation of the chart in figure A14.2:

• The columns are numbered left to right according to ranking of the factors/competencies in the same figure



Figure A14.3



The graphic below is a 3 dimensional representation of the rankings for frequency of occurrence of the factors/competencies in all accidents and incidents for all generations. The visual effect of this representation gives a sense of the relative importance of the factors by clearly showing the steep drop of importance as the ranking progresses. The vertical and horizontal axes are mirror images of each other and are labeled in the same order as the rank in fig A14.2 (e.g. the apex being number 1 = Sys mal)



Figure A14.3a



# Data Report for Evidence-Based Training

Figure A14.3b forms a matrix of the number of factor pairings or factor/competency pairings for all accidents and serious incidents:

- Column and row numbers are titled the same as the ranking in previous graphic (e.g. 1=Sys Mal).
- Darkness of shading depicts a measure of occurrence.

0																		00	ccu	irrend	ce of	f Fac	tor F	Pairin	gs																		
		1	2 3	34	5	6 7	7 <u>8</u>	9	10	11	12	13	14	15	16	17	18 19	20	2'	1 22	23	24 2	25 2	6 27	28	29	30	31	32 33	3 34	35	36	37 3	8 39	9 40	41	42	43	44	45	46	47	48
	1 8	59 1	16 87	7 82 1	123	69 54	232	68	66	194	40	6	53	16	20	1	29 12	37	28	8 12	26	0 1	4	8 19	15	13	10	4	11 7	' 11	8	11	3 1	5 (	03	2	2	1	8	2	2	1	0
	2 1	16 6	209	383 2	289 3	03 304	42	276	97	40	202	79	108	31	81	29	14 86	67	43	3 67	26	13 4	4 3	2 38	23	25 -	36	19	19 28	3 21	25	3	2 1	5 7	75	3	7	9	3	4	4	4	2
	3	87 2	09 585	5 170 1	160 1	16 103	60	96	32	53	113	34	126	. 11	82	. 7	48 29	19	65	5 27	14	10 1	0 1	8 10	36	11	14	30	7 10	13	3	.1	0	8 <sup>.</sup>	1 2	. 1 .	0	.6	. 1 .	. 0	.2	1	0
	4	32 3	33 170	526 3	377 2	02 205	28	194	68	22	140	44	92	15	99	10	3 57	42	52	2 21	30	4 3	31 2	9 27	24	23	34	12	19 25	16	10	3	2 1	6	2 5	2	7	10	3	1	1	3	2
	5 1	23 2	39 160	377 4	180	42 152	68	143	70	61	96	37	108	19	79	15	7 54	39	64	4 18	32	:::6:::2	2 1	8 25	:33	20	31	11	18 22	19	б.	3	2 1	3	3 4	3	4	6	1	1	0	2	2
	6	69 3	03 116	5 202 1	42 3	57 163	20	220	45	18	116	38	58	27	46	19	7 47	58	19	9 :33	15	7 3	37 2	1 21	12	14	23	. 11	10 18	3 10	14	2	2 1	1 4	4 5	. 1	7	7	5	1	4	3	_1
	7	54 3	04 10	3 205 1	52 1	53 340	18	110	94	16	64	58	70	26	40	28	3 18	31	18	8 32	10	13 2	23 2	5 12	7	15	27	-8	12 21	8	13	1	2	5	2 2	0	4	6	2	з	4	3	1
	8 2	32 4	12 60	):28:	68	20 : 18	314	23	18	127	17	3	. 46	. 10	. 7.	. 0	7 5	: 10	. 25	5 :: 2:	8 .	. 0	6	4 8	14	3	5	. 2 .	.0.2	2.7	- 5	18	1 .	2.0	0.0	. 1 .	. 1	1.	. 2 .	. 0	.0.	0	0
	9	<u>3</u> 8 2	76 90	5 194 1	143 2	20 110	23	303	33	19	89	26	48	13	43	13	5 34	56	- 19	9 14	12	3 3	32 1	9 18	12	9	13	12	6 11	7	12	3	1 1	2	2 3	111	7	7	2	4	2	3	0
1	0	66	97 32	2 :68 :	70	45 : 94	: 18	33	279	26	24	33	29	73	25	15	7 : : 5	3	9	9 :20	1	14	7	0 5	2	5 :	3	1	0 5	5 2	8	0	1 :	2 '	1 1	0	1	1	2	0	0	0	0
1	11	94	40 53	3 22	61	18 10	127	19	26	259	- 18	3	43	12	6	. 0	18 7	5	27	7 3	7		3	5 4	14	2	3	1	0 0	) 5	4	3	1	5 (	0 0	. 4	0	1	1	0	0	0	0
1	2 ::	40 2	02 11	3 140	96 1	16 64	17	89	24	18	217	:21	49	:::5:	:49	6	8 13	18	- 20	6 8	10	11111	5	9 9	12	15	9	11	2 7	12	1	:2:::	0	2:::	5 4	:::1::	1	: 3	3	::1:::	:: <b>!</b> :::	0	: 1
1	3	6	79 34	44	37	38 58	3 3	26	33	3	21	180	35	7	13	83	0 11	: 3	4	4 24	2	39	7	8 4	7	2	8	7	0 8	3 3	6	0	1 (	0 1	1 0	0	0	2	0	3	3	1	0
1	4	53 10	08 126	5 92 1	108	58 70	46	48	29	43	49	35	175	13	33	9	1 16	: 7	35	5 14	2	10 1	3 1	6 1	22	1 :	14	7	6 7	4	6	3	1 (	0 0	0 3	0	0	7	0	0	1	3	1
1	5	16 3	31 1'	1 15	19	27 26	10	13	73	12	5	7	13	138	6	1	3 3	1	3	3 13	0	4	4	0 0	1	1 :	1	1	0 1	0	3	1	0 (	0 0	0 0	0	0	0	0	0	0	0	0
1	6	20 8	31 82	2 99	79	46 40	7	43	25	6	49	13	33	6	135	2	8 0	: 9	28	5 6	2	3	6	1 3	5	3 :	α	7	0 2	2 3	2	1	1	5 (	0 0	0	0	3	0	0	0	1	0
1	7	1 :	29 7	10	15	19 28	0	13	15	0	6	83	9	1	2	119	1 5	: 3		1 8	1	23	4	0 0	0	1	2	1	2 2	2 1	3	0	0	0 '	1 0	0	0	0	1	1	1	0	0
1	8	29	14 48	3		6	· <u>(</u> .	5	· <u>(</u> .	. 18		0	1				119 5	2	· . · .	0			3	0 0		2 . :	0		3 0		a		0 0		1 1			· . · , · .		. 0			
1	9 ::	12	36 29	57	54	47 18	5	- 34	:::5:		13	: 11	16	. 3	8	:::5	5 88	15		6 10	- 4	:::2::::	6	5 2	- 4	2	8	:::2:::	3 4	4	Z	::0:::	0	2:1:1	1::::1:	11	:: Z :	::1::	0	0	0	: <u>1</u> : : :	.0
2	0	37 0	57 19	42	39	58 31	10	56	3	5	18	3		1	9	3	2 15	/9		5 3	10	0 1	5	3 12	5	11 :	6	2	4 5	· /	2	0	2		0 1	0	2	1	1	0	1	1	2
2	1	28 4	13 65	52	64	19 18	25	19	9	. 27	26	4	35	3	25	1	0 6	5		5 2		1 :•:4:•:•	1	1 5	17	6	2	4	0 1	6	1	1	0 0	0 1 .:.:.:	1 0	1		.:.:.:	0			1	1
2	2	12: : :	37 27	21	18	33 32	:::2:	14	20	::3	8	:24	14	: 13:	6	8	7 10	3		2 75	1	8	7	3 0	2	1	2	0	3 2	1	2	::0:::	0	2	1::::1::	2	0	::1:	0	:1::	:: <b>!</b> :::	1	0
2	3	26 2	26 14	4 . 30	32	15 10	8	12	1		10	2	2	0	2	1	3 4	: 10		( 1	59	0	3	1 11	4	8 :	8	0	7 6	6 4	0	0	0	1 1	1 0	2	0	1	0	0	0	0	0
2	4	0	13 10	4	6	7 10	. 0	- 3	14	0		39	10	4	3	23	0 2	0	1	1 8	0	57	2	0 0	0	0 :	0	0	0 0	) 1	2	0	0		0 0	0	0	0	0	1	0	0	0
	5	14 4	44 10	31	40	3/ 23	5 6	32		3	15		13	4	6	4	3 6	15		1 7	3	2 5	5 5	4	2	4	5	0	3 4	F 1	10	1	1		0 3	1	0	2	2	0	2	1	1
			2 10	29	10	21 20	4	19		.:						:	0 0		. : . :		: taale	:.:	5 5	45				: • : • : • :	0 3	· · · ·	2	:		41 - 1 - 4	0 0	:.:	:-:-:		: . : . : : :		<u>.</u>		
	( i:	19		2. 21	20	40		10		4	10											· · · · · · · · · · · · · · · · · · ·	#	45				:::4:::	5		D.		0	34	2::::0:		:::!::		· · · <del>/</del> · · ·			. u	
		10 1	23 30	24	-33	12 1	14	12	2	14	14		22	1	5	1	0.4	: D		<u> </u>	4	0	2	0 5	41	4	2	2	1 4	2 45		1	0			1	1		0	0	1	0	1
	9	13	25 1	23	20	14 15	3	9		:.:.;;	15	2	1				2 2		:•:•				4	9	4	40	40	. : . ; . : .	1 4	15		·:,:·:			2 0			:.:	.:.;.:.	:	1		
0		10	20:11	4 34	31	23 21		13		:::P		- 0	:::::4:	::: <u>}</u> :		:: <u>×</u> ::	. U . Q		:::*	2 Z	::: <b>0</b> ::	:::0::::	P : : :		: 3:		40	20	0	4	2	::!::			0.:::0:	:::•	1.11	:::	199	: 22:::	1211	.0	::::
2	2	4	19 30	7 10	10	10 10	2 2	12		0			6	0	6	2	0 2	: 4		4 0	7	0	2 1	2	2	1		39	24 6	2	0	0	0	1 1	1 0	1	2	2		0	1	0	0
2	2		19 1	19	22	10 12		11	5	0			7	1	2	2	0			1 3	6	0	4	2 10	2	1	27	1	6 22	2	4	1	1		0 0	0	1	1	0	0	1	1	1
3		11 .	20 10	10 20	10	10 2	2		2	5	12	3	4	0	2	4	0 4		,	<b>∠</b>	4	1	4	0 8	2	15	27	2	2 5	5 20	1	0	0	2 .	1 0	0	2	0	2	1	0	0	0
3	5		25	10		4		12		:::/	1			:::	:::	:::::::::::::::::::::::::::::::::::::::		:::;;	111	1	::	:::::::::		2 0	:		2	::		23	27	::6:::		.::::		::::	:	::4::	េះដ៏លោ		::4:::		::
3	6	P::: 11	3	1 9	3	2 1	18	2	0	:::#		0	3	1	::: <u>-</u> ::: 1		0 0		÷÷;	1 0		0	1	2 0	1	0	4			0	27	26	0		0 0		0	::!::	0	0	0	0	0
3	7	3	2 (	2		2	1	1	1	1	0	1	1	0	1	0	0 0	2		n	0	0	1	n 0	0	0	0	0	0 1	0	1	0	24		0 4	0	0	1	0	0	0	1	0
3	8	15	15 8	16	13	11	2	12	2	5		0		0	5	0	0	- 7		1 2	1	0	1	1 3	1	0	0	1	1 0	2	n	0	0 2	4 (	0 0	0	1	0	0	0	0	0	0
3	a	0	7 1		3	4	0	2	1	0	5	1	0	0	0	1	1 1	: 6	1	1 1	1	0	0 1	n 2	0	2	0	0	1 0	, <u>-</u> 1	n	0	0 1	1 16	6 0	0	0	0	0	0	0	0	0
4		3	5 3		4	5 0	0	2	1	0	4	0	3	0	0	0	1 1	: 1	ć	n 1	0	0	3 1	n	0	0	0	1	0 0	0	n	0	4 (		0 16	0	0	1	0	0	0	0	0
	1	2	3 .	1 2		1 0	1	1	0	4	1	0	0	0	0	0	2			1 2	2	0	1	0	1	0	n	0	1 0	0	0	0	0		0 0	12	0	0	ő	0	0	0	0
	2	2	7 (	7	4	7		7	1	0		0	0	0	0	0	- -	2	(	n n	0	0	0	n 1	0	1	1	2	0 1	2	n	0	0	1 (	0 0	0	12	1	Ő	0	0	0	0
	3	1	9 6	10	6	7 6	1	7	1	1		2	7	0	3	0	0 1	: 1		1 1	1	0	2	2 0	1	0	1	2	0 1	0	ĩ	0	1 1		0 1	0	1	10	Ő	0	0	1	0
	4	8	3 1		1	5	2	2	2	1		0	0	0	0	1	0.0	1	(	n 0	0	0	2 1	n 2	0	3	1	1	0 0	2	4	0	0			0	0	0	ä	0	0	0	0
4	5	2	4 (	) 1	1	1	0	4	0	0	1	3	0	0	0	1	0 0	0	0	0 1	0	1	0	0	0	1	0	0	0 0	) 1	α	0	0		0 0	0	0	0	0	6	õ	0	0
4	6	2	4 3	2 1	0	4 4	0	2	0	0	1	3	1	0	0	1	1 0	1	0	1	0	0	2	2 0	0	1	1	1	1 1	0	1	0	0 0		0 0	0	0	0	0	0	5	0	0
4	7	1	4 1	3	2	3 3	0	3	0	0	Ó	1	3	0	1	0	0 1	: 1	1	1 1	0	0	1	1 0	0	0	0	0	0 1	0	1	0	1 (		0 0	0	0	1	0	0	0	4	0
4	8	0	2 (	) 2	2	1 1	0	a	0	0	1	0	1	0	0	0	0 0	2	1	1 0	0	0	1	1 1	1	1	1	0	0 1	0	0	0	0 0		0 0	0	0	0	0	0	0	0	2
-	~ L_	2	- (		4					5		5		5	v	v					0	0	•					0	5 1	0		v	5 1		- J	0	0	v		-			-

The graphic below (Figure A14.3c) is a visual depiction of chart above (fig A14.3b) with the measure of pair-occurrence a function of the area size of the rectangles in the matrix. Additionally pair-occurrence is also denoted by the change of shading to emphasize the effect.

All flights

														gine																			
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16 17	18	19	20 21	22	23 2	4 25	26 27	28	29 30	31 3	12 33	34 35	36 37 1	38 39 4	0 41 42	43 44	45 46 47 48
					1	1			1				=			1		= 1	i i		1.7							11	11	11	111	:1	LIVE
																							li		1			ÎΪ	1 i	<u> </u>	Π		hi 🗆
-					the second se			Ш.								6			17	1			- 1	Ť		Î	11	11	îή.		114	Ìì	
		-					2 1							_											i I		1		i !	i ! !		ÎŻ.	취문
					100								-	_		Ì					j					i		i i	1¦	i H	itti	IJ.	îiil
64		-										and the second			ī											i		1	÷÷.	Цĕ	답답	11	封行
67		-		-									-		Ē	. 2		9								I		11	1 i l	157			1 - 1
10 4				-											i I								19			1		6 1	ì		ίI		ret i
ŵ			Terrorite State										=				Ĩ		2 1	īē						Í.	10	<u>.</u>	12	١į.		i.	
~						=															ī			-	1 -				13)	11			돌란
œ																			2 8		-					1	i D		ίĿ.		i Ri	i	취문
8 0																	ī		22				0 3	-	1	i			11				1411
E	(and the second s	34																2						Ľ.		i					i i i	11	[] [
2												Ξ			ſ				21			-	2 8	-		i		8	11	11	신문		날아날
51413	-											Ξ												-	1 2		0 0		23	12		• · ·	111
817161				$\equiv$			$\equiv$	Ξ			Ξ.		Ê	Ξ					1 7	iī		=	2 8			÷		21	불분	1 I I			신신
20191		10						Ξ											31				-	=		ŝ			1				분석
3221									_			Ξ	Ē	=	= [		Ē			<u> </u>				111		-	Ĩ		-		i i i	. 1	111
2625242		L			$\equiv$			Ξ			Ξ		11			Ξ.		=	<u> </u>		-	1					1 -		i.			- 1 1 - 1	1111
92827.										Ξ	Ξ	Ξ	Ξ			Ξ.3		Ξ						-				0 0				1	111
9231300								=		Ξ	Ξ				Ξ								- 0	111	8 1					8 I 1	112	0 -	친음
353433	$\equiv$				$\equiv$		$\equiv$	Ξ		Ξ	Ξ	Ξ		Ξ	Ξ	Ξ				Ξ			-	111	55						- P		
967883	_			_	=	$\equiv$			=	$\Xi$	Ξ	==	Ξ	=		= =	12	= ;	22	83		Ξ	110	Ξ	1.0	1		1.1	41			1	i i i
图412		==	=	$\equiv$		$\equiv$		=	=	Ξ		$\equiv$	Ξ	===	=		-	Ξ		Ξ		=		Ξ			12	100	21				
81514(3				$\equiv$	=	$\equiv$	Ξ	丟		Ξ	=	Ξ	111				E.	Ξŝ	33	12		E		Ξ							1.1		HT.
赴 IB¥	373					-	=	122	525	533	E.	=	æ	=	# 3	# 5	12	= ;	= =	32	33	Ξ		9		3	: 3		1	191		0 	5511

Figure A14.3c

#### 14.4 THE TOP FOUR

The chart below denotes the leading four parameters in terms of occurrence with regard to:

- Individual factor measured in raw numbers and rates normalized by takeoffs.
- Individual competencies measured in raw numbers and rates normalized by takeoffs.
- Factor pairings measured in raw numbers and rates normalized by takeoffs.
- Factor and competency pairing measured in raw numbers and rates normalized by takeoffs.

Top 4 par	ameters	
Top 4 factors	Accident/incidents	Normalized Rates
Syst mal	859	1.66405E-06
CRM	602	1.16619E-06
Adverse weather	585	1.13326E-06
Mis A/C state	526	1.01896E-06
Top 4 Competencies	Accident/incidents	Normalized Rates
Manual aircraft control	480	9.29854E-07
SA	340	6.58646E-07
Application of Procedures & Knowledge	303	5.8697E-07
Problem Solving Decision Making	217	4.20371E-07
Top 4 pairs of factors	Accident/incidents	Normalized Rates
Mis A/C state - CRM	383	7.41946E-07
Compliance - CRM	303	5.8697E-07
Engine failure - sys mal	232	4.49429E-07
Adverse weather - CRM	209	4.04874E-07
Top 4 pairs of factors with Competencies	Accident/incidents	Normalized Rates
Manual A/C control - Mis A/C state	377	7.30322E-07
SA - CRM	304	5.88907E-07
Manual A/C control - CRM	289	5.59849E-07
Application of procedures and knowledge	202	3.91313E-07

Figure A14.4

.

#### 14.5 CORRELATIONS AMONG FACTOR/COMPETENCY PAIRINGS

The 48X48 matrix below denotes the statistical correlations among all the factors and competencies for all accidents and serious incidents:

- Column and row numbers are titled the same as the ranking in figure A14.2 (e.g. 1=Sys Mal).
- Darkness of shading depicts the strength of correlation.

																						Co	rrel	ati	ons																				
		1	2 3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25 2	26 2	27 28	29	30	31	32	33	34	35 3	36 37	38	39	40	41	42	43	44	45	46 4	7 48
	1	2.	2 2.7	2.4	1.2	1.6	1.8	3.0	1.2	1.0	2.8	1.3	2.0	0.4	1.3	1.2	1.8	0.6	1.0	0.4	0.0	<b>3.8</b>	0.2 1	1.2 (	0.3 0	.7 0	.1 0.0	0.1	0.3	0.7	0.1	0.4	0.0	0.2 0	.1 0.	5 0.5	0.6	0.3	0.3	0.3	0.4	0.7	0.0	0.0 0.0	.1 0.2
2	2.	2 1	1.3	5.8	4.0	5.7	6.0	1.2	5.8	0.7	0.9	4.9	1.2	2.3	0.2	1.9	0.1	0.8	3.2	2.5	1.3	2.6	0.7 0	0.1	2.0 1	.3 1	.9 0.9	1.1	1.9	0.7	0.8	1.6	1.2	1.6 0	.4 0.4	0.8	0.3	0.1	0.0	0.5	1.0	0.1	0.5 (	0.6 0	.7 0.5
:	2.	7 <sup>.</sup> 1.	3 10	0.9	0.9	0.7	0.5	0.6	0.6	1.2	0.4	2.0	0.4	3.1	1.0	2.0	1.0	0.8	0.3	0.1	2.6	0.4	0.1 0	0.3 (	0.2 0	.3 0	.1 1.9	0.1	0.3	1.6	0.1	0.1	0.5	0.4 0	.5 0.0	0.2	0.4	0.2	0.3	0.4	0.5	0.2	0.3 (	0.2 0	.0 0.2
4	2.	4 5.	8 0.9	10	6.8	3.4	3.7	1.3	3.8	0.1	1.2	3.2	0.1	2.0	0.7	3.0	0.8	1.1	2.0	1.4	2.0	0.2	1.1 0	0.6	1.3 1	.2 1	.3 1.1	1.1	2.0	0.2	1.0	1.5	0.9	0.4 0	.3 0.4	1.1	0.2	0.2	0.1	0.6	1.2	0.2	0.1 (	0.0	.5 0.5
. (	1.	2 4.	0.9	6.8	8 10	2.0	2.4	0.1	2.5	0.4	0.2	1.9	0.0	2.9	0.4	2.3	0.5	0.9	2.0	1.3	2.9	D.1	1.3 (	).4 (	0.8 0	.4 1	.2 2.0	1.0	1.9	0.2	1.0	1.4	1.2	0.0 0	.2 0.3	8 0.8	0.0	0.1	0.1	0.2	0.6	0.1	0.1 (	0.2 0	.3 0.6
6	1.	5.	7 0.7	3.4	2.0	10	3.4	1.0	6.1	0.1	0.8	3.4	0.5	1.4	0.3	1.3	0.0	0.6	2.1	3.0	0.5	1.4	0.4 (	0.1	2.3 1	.1 1	.2 0.5	0.7	1.5	0.5	0.5	1.3	0.6	1.1 0	.2 0.2	2 0.9	0.2	0.4	0.1	0.9	1.0	0.7	0.0	0.8.0	.7 0.3
. 7	1.	B 6.	0.5	3.7	2.4	3.4	10	1.0	2.4	2.0	0.9	1.3	1.4	2.0	0.3	1.0	0.6	0.8	0.3	1.3	0.5	1.4	0.1 0	0.4	1.3 1	.5 0	.5 0.1	0.9	2.0	0.2	0.7	1.7	0.4	1.0 0	.3 0.2	2 0.2	0.1	0.1	0.3	0.4	0.8	0.1	0.5	0.9 0	.7 0.3
8	3.	0 1.	2 0.6	1.3	0.1	1.0	1.0	10	0.7	0.8	3.7	0.5	1.0	1.1	0.5	0.6	0.9	0.5	0.5	0.1	1.0 (	0.6	0.0	0.6	0.1 0	.3 0	.2 0.8	0.2	0.0	0.3	0.5	0.3	0.3	0.2 1	.7 0.3	0.2	0.3	0.3	0.1	0.1	0.1	0.2	0.2 (	0.2 0	.2 0.1
9	1.	2 5.	8 0.6	3.8	2.5	6.1	2.4	0.7	10	0.1	0.6	2.7	0.1	1.2	0.3	1.4	0.2	0.6	1.5	3.2	0.6	0.3	0.3 (	).4	2.2 1	.1 1	.1 0.6	0.4	0.8	0.7	0.2	0.7	0.4	1.0 0	.1 0.3	3 1.1	0.0	0.1	0.1	1.0	1.1	0.2	0.8	0.4 0	.8 0.1
10	1.	0.	7 1.2	0.1	0.4	0.1	2.0	0.8	0.1	10	0.2	0.1	0.6	0.4	3.2	0.5	0.0	0.4	0.4	0.5	0.0	0.8	0.5 0	0.6	0.1 0	.6 0	.0 0.3	0.0	0.2	0.4	0.5	0.1	0.2	0.6 0	.4 0.2	2 0.1	0.1	0.1	0.3	0.1	0.0	0.2	0.2 (	0.2 0	.2 0.1
11	2.	в О.	9 0.4	1.2	2 0.2	0.8	0.9	3.7	0.6	0.2	10	0.3	0.9	1.2	0.2	0.5	0.8	0.3	0.2	0.3	1.4 (	0.4	0.0 0	0.6	0.3 0	.1 0	.1 1.0	0.3	0.2	0.4	0.4	0.4	0.2	0.1 0	.0 0.3	2 0.3	0.3	0.3	0.5	0.3	0.0	0.0	0.2 (	0.2 0	.1 0.1
12	1.	3 4.	9 2.0	3.2	2 1.9	3.4	1.3	0.5	2.7	0.1	0.3	10	0.2	1.8	0.5	2.3	0.3	0.2	0.4	0.9	1.6	0.1	0.4 0	).4	1.0 0	.4 0	.5 0.9	1.3	0.6	0.8	0.1	0.5	1.2	0.2 0	.1 0.3	3 0.0	0.6	0.4	0.0	0.0	0.5	0.5	0.1 (	0.2 0	.1 0.4
_13	2.	0 1.	2 0.4	0.1	0.0	0.5	1.4	1.0	0.1	0.6	0.9	0.2	10	1.3	0.3	0.2	5.4	0.7	0.3	0.3	0.2	1.7	0.3 3	3.6	0.3 0	.4 0	.1 0.5	0.1	0.6	0.5	0.4	0.7	0.1	0.6 0	.3 0.	0.3	0.0	0.2	0.2	0.2	0.3	0.2	0.8 0	0.9 0	.3 0.1
14	0.	4 2.	3 3.1	2.0	2.9	1.4	2.0	1.1	1.2	0.4	1.2	1.8	1.3	10	0.2	1.6	0.0	0.6	0.8	0.1	2.7 (	0.8	0.3 0	0.6	1.0 1	.4 0	.3 2.3	0.3	1.4	0.5	0.5	0.6	0.3	0.6 0	.2 0.	0.3	0.2	0.4	0.2	0.2	1.6	0.2	0.1 (	0.2 1	.1 0.5
15	1.	3 0.	2 1.0	0.7	0.4	0.3	0.3	0.5	0.3	3.2	0.2	0.5	0.3	0.2	10	0.2	0.5	0.3	0.2	0.4	0.2	0.9	0.4 0	D.1	0.1 0	.4 0	.4 0.2	0.2	0.2	0.2	0.3	0.2	0.3	0.2 0	.1 0.:	3 0.3	0.2	0.2	0.2	0.2	0.2	0.2	0.1 (	J.1 0	.1 0.1
10	1.	2 1.	9 2.0	3.0	2.3	1.3	1.0	0.6	1.4	0.5	0.5	2.3	0.2	1.6	0.2	10	0.4	0.6	0.3	0.4	2.1 (	0.2	0.2 0	0.0	0.4 0	.2 0	.0 0.4	0.1	0.3	0.7	0.3	0.0	0.2	0.1 0	.1 0.	0.7	0.2	0.2	0.2	0.2	0.7	0.2	0.1 0	0.1 0.	.3 0.1
17	1.	в О.	1 1.0	0.8	0.5	0.0	0.6	0.9	0.2	0.0	0.8	0.3	5.4	0.0	0.5	0.4	10	0.5	0.0	0.1	0.3 (	0.5	0.3 2	2.5	0.2 0	.4 0	.3 0.3	0.2	0.0	0.2	0.0	0.0	0.1	0.3 0	.2 0.3	2 0.2	0.0	0.2	0.2	0.2	0.2	0.2	0.3 0	0.3 0.	.1 0.1
18	0.	<b>6</b> 0.	8 0.8	1.1	0.9	0.6	0.8	0.5	0.6	0.4	0.3	0.2	0.7	0.6	0.3	0.6	0.5	10	0.0	0.2	0.4 (	0.3	0.0 C	0.4	0.0 0	.4 0	.3 0.3	0.0	0.3	0.6	0.2	0.3	0.3	0.3 0	.2 0.2	2 0.2	0.0	0.0	0.4	0.2	0.2	0.1	0.1 0	0.3 0.	.1 0.1
19	1.	3.	2 0.3	2.0	2.0	2.1	0.3	0.5	1.5	0.4	0.2	0.4	0.3	0.8	0.2	0.3	0.0	0.0	10	1.5	0.4 (	0.9	0.3 0	0.0	0.6 0	.5 0	.0 0.4	0.1	1.1	0.1	0.3	0.5	0.6	0.2 0	.2 0.3	2 0.2	0.1	0.1	0.2	0.5	0.2	0.1	0.1 0	J.1 0.	.5 0.1
20	0.	4 2.	5 0.1	1.4	1.3	3.0	1.3	0.1	3.2	0.5	0.3	0.9	0.3	0.1	0.4	0.4	0.1	0.2	1.5	10	0.3 0	J.1	1.2 0	0.3	2.1 0	.2 1	.8 0.6	1.8	0.8	0.1	0.6	8.0	1.3	0.2 0	.2 0.3	3 1.5	0.2	0.1	0.1	0.5	0.2	0.3	0.1 0	J.4 0.	.5 1.6
2	0.	J 1.	3 2.6	2.0	2.9	0.5	0.5	1.0	0.6	0.0	1.4	1.6	0.2	2.7	0.2	2.1	0.3	0.4	0.4	0.3		0.1	0.8 0	0.1	0.1 0	.1 0	.6 2.9	0.9	0.1	0.5	0.2	0.0	1.1	0.0 0	.0 0.2	2 0.2	0.1	0.2	0.2	0.1	0.2	0.1	0.1 0	J.1 0.	.5 0.8
24	0.	5 Z.	0.4	0.2	2 0.1	1.4	1.4	0.6	0.3	0.8	0.4	0.1	1.7	0.8	0.9	0.2	0.5	0.3	0.9	0.1	0.1		0.1 1	1.0	0.9 0	.2 0	.3 0.1	0.1	0.1	0.2	0.4	0.2	0.0	0.3 0	.2 0.	2 0.3	0.1	0.1	0.5	0.1	0.3	0.1	0.4 (	J.4 U.	.5 0.1
2	0.	2 0.	1 0.1	1.1	1.3	0.4	0.1	0.0	0.3	0.5	0.0	0.4	0.3	0.3	0.4	0.2	0.3	0.0	0.3	1.2	0.8	J.1		10	0.3 0	.1 2	0 0.6	1.5	1.5	0.2	1.4	1.2	0.8	0.2 0	.2 0.	2 0.1	0.2	0.1	0.6	0.1	0.3	0.1	0.1 0	J.1 U.	1 0.0
24	1.	20.	0.3	1.2	0.4	2.2	1.2	0.0	2.2	0.0	0.0	1.0	0.2	1.0	0.1	0.0	2.5	0.4	0.0	2.1	0.1	1.0	0.3		10 0	.2 0	6 0.2	0.2	0.2	0.2	0.2	0.2	0.1	4.2 0	1 0.	2 0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.5	12 0	6 0.0
26	0.	7 1	3 0.2	1.3	0.0	1 1	1.5	0.1	1 1	0.1	0.3	0.4	0.3	1.0	0.1	0.4	0.2	0.0	0.0	0.2	0.1 (	12	0.1 (	12 1		0 0	2 0.2	0.7	1.4	0.2	0.5	0.6	0.1	4.2 0	2 0	2 0.1	0.1	0.5	0.3	0.1	0.8	0.0	0.1	1.2 0	6 10
2	0.	1 1	9 0.1	1.3	12	12	0.5	0.0	1.1	0.0	0.1	0.5	0.1	0.3	0.4	0.0	0.3	0.3	0.0	1.8	0.1	13	20 0	12	0.6.0	2 1	0 0.5	20	2.5	0.3	1 1	2.5	21	0.7 0	2 0	0.1	0.6	0.1	0.1	0.3	0.0	0.9	0.1	0.1 0	1 10
28	0	0	9 1 9	1 1	2.0	0.5	0.1	0.8	0.6	0.3	1.0	0.9	0.5	2.3	0.2	0.4	0.3	0.3	0.4	0.6	29	11	0.6 (	12	02 0	2 0	5 10	0.8	0.6	0.3	0.1	0.4	0.4	020	2 0	0.2	0.1	0.1	0.4	0.1	0.4	0.1	01 (	0 1 0	1 1 1
29	0.	1 1.	1 0.1	1.1	1.0	0.7	0.9	0.2	0.4	0.0	0.3	1.3	0.1	0.3	0.2	0.1	0.2	0.0	0.1	1.8	0.9	0.1	1.5 (	0.2	0.7 0	.2 2	.0 0.8	10	1.1	0.2	0.1	1.0	4.3	0.2 0	.1 0.1	0.1	0.7	0.1	0.1	0.4	0.1	1.5	0.6 (	0.7 0	1 1.1
30	0.	3 1.	9 0.3	2.0	1.9	1.5	2.0	0.0	0.8	0.2	0.2	0.6	0.6	1.4	0.2	0.3	0.0	0.3	1.1	0.8	0.1 (	0.1	1.5 (	).2	0.9 1	.4 2	.5 0.6	1.1	10	0.1	2.0	7.4	1.0	0.5 0	.2 0.	0.1	0.1	0.1	0.1	0.4	0.4	0.4	0.1 (	0.7 0	.1 1.1
31	0.	7 0.	7 1.6	0.2	2 0.2	0.5	0.2	0.3	0.7	0.4	0.4	0.8	0.5	0.5	0.2	0.7	0.2	0.6	0.1	0.1	0.5	0.2	0.2 (	).2 (	0.2 0	.2 0	.3 0.3	0.2	0.1	10	0.1	0.1	0.5	0.1 0	.1 0.	0.2	0.1	0.3	0.1	0.8	0.9	0.5	0.1	0.7 0	.1 0.0
32	0.	1 0.	8 0.1	1.0	1.0	0.5	0.7	0.5	0.2	0.5	0.4	0.1	0.4	0.5	0.3	0.3	0.0	0.2	0.3	0.6	0.2 (	0.4	1.4 (	).2	0.5 0	.2 1	.1 0.1	0.1	2.0	0.1	10	1.7	0.5	0.5 0	.1 0.	0.2	0.3	0.1	0.4	0.1	0.1	0.1	0.1	0.7 0	.1 0.0
33	0.	4 1.	6 0.1	1.5	5 1.4	1.3	1.7	0.3	0.7	0.1	0.4	0.5	0.7	0.6	0.2	0.0	0.0	0.3	0.5	0.8	0.0	0.2	1.2 0	).2	0.8 0	.6 2	.5 0.4	1.0	7.4	0.1	1.7	10	1.5	0.9 0	.2 0.3	2 0.1	0.1	0.1	0.1	0.4	0.5	0.1	0.1	0.7 0	.8 1.2
34	0.	0 1.	2 0.5	0.9	1.2	0.6	0.4	0.3	0.4	0.2	0.2	1.2	0.1	0.3	0.3	0.2	0.1	0.3	0.6	1.3	1.1 (	0.0	0.8 0	0.1 (	0.1 0	.2 2	.1 0.4	4.3	1.0	0.5	0.5	1.5	10	0.2 0	.1 0.	0.7	0.4	0.1	0.1	1.0	0.1	1.2	0.7 (	0.1 0	.0 0.0
35	0.	2 1.	6 0.4	0.4	0.0	1.1	1.0	0.2	1.0	0.6	0.1	0.2	0.6	0.6	0.2	0.1	0.3	0.3	0.2	0.2	0.0	0.3	0.2 0	0.3	4.2 0	.4 0	.2 0.2	0.2	0.5	0.1	0.5	0.9	0.2	10 0	.1 0.3	3 0.1	0.1	0.1	0.1	0.1	0.5	0.6	0.1	0.8 0	.9 0.0
- 36	0.	1 0.	4 0.5	0.3	0.2	0.2	0.3	1.7	0.1	0.4	0.0	0.1	0.3	0.2	0.1	0.1	0.2	0.2	0.2	0.2	0.0	0.2	0.2 (	).2 (	0.1 0	.2 0	.2 0.2	0.1	0.2	0.1	0.1	0.2	0.1	0.1 1	0 0.	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1 (	0.0.0	.0 0.0
37	0.	50.	4 0.6	0.4	0.3	0.2	0.2	0.3	0.3	0.2	0.2	0.3	0.1	0.1	0.3	0.1	0.2	0.2	0.2	0.3	0.2 (	0.2	0.2 (	).2 (	0.1 0	.2 0	.1 0.1	0.1	0.1	0.1	0.1	0.2	0.1	0.3 0	.1 10	0.1	0.1	2.0	0.1	0.1	0.6	0.1	0.1 (	0.0 1	.0 0.0
38	0.	5 0.	8 0.2	1.1	0.8	0.9	0.2	0.2	1.1	0.1	0.3	0.0	0.3	0.3	0.3	0.7	0.2	0.2	0.2	1.5	0.2 (	0.3	0.1 0	).2 (	0.1 0	.1 0	.8 0.2	0.1	0.1	0.2	0.2	0.1	0.7	0.1 0	.1 0.	10	0.1	0.1	0.1	0.5	0.1	0.1	0.1 (	0.0	.0 0.0
39	0.	<b>6</b> 0.	3 0.4	0.2	2 0.0	0.2	0.1	0.3	0.0	0.1	0.3	0.6	0.0	0.2	0.2	0.2	0.0	0.0	0.1	0.2	0.1 (	0.1	0.2 0	0.1 (	0.1 0	.1 0	.6 0.1	0.7	0.1	0.1	0.3	0.1	0.4	0.1 0	.1 0.	0.1	10	0.1	0.1	0.1	0.1	0.1	0.0	0 0.0	.0 0.0
40	0.	3 0.	1 0.2	0.2	2 0.1	0.4	0.1	0.3	0.1	0.1	0.3	0.4	0.2	0.4	0.2	0.2	0.2	0.0	0.1	0.1	0.2 (	0.1	0.1 0	0.1 (	0.9 0	.1 0	.1 0.1	0.1	0.1	0.3	0.1	0.1	0.1	0.1 0	.1 2.0	0.1	0.1	10	0.1	0.1	0.7	0.1	0.0	0.0 0.0	.0 0.0
4	0.	3 0.	0 0.3	0.1	0.1	0.1	0.3	0.1	0.1	0.3	0.5	0.0	0.2	0.2	0.2	0.2	0.2	0.4	0.2	0.1	0.2 (	0.5	0.6 0	0.1 (	0.3 0	.1 0	.1 0.4	0.1	0.1	0.1	0.4	0.1	0.1	0.1 0	.1 0.	0.1	0.1	0.1	10	0.1	0.0	0.0	0.0	0.0 0.0	.0 0.0
42	0.	3 0.	5 0.4	0.6	6 0.2	0.9	0.4	0.1	1.0	0.1	0.3	0.0	0.2	0.2	0.2	0.2	0.2	0.2	0.5	0.5	D.1 (	0.1	0.1 0	0.1 (	0.1 0	.1 0	.3 0.1	0.4	0.4	0.8	0.1	0.4	1.0	0.1 0	.1 0.	0.5	0.1	0.1	0.1	10	0.9	0.0	0.0	0.0 0.0	.0 0.0
43	0.	4 1.	0 0.5	1.2	2 0.6	1.0	0.8	0.1	1.1	0.0	0.0	0.5	0.3	1.6	0.2	0.7	0.2	0.2	0.2	0.2	0.2 (	0.3	0.3 0	0.1	0.8.0	.8 0	.1 0.4	0.1	0.4	0.9	0.1	0.5	0.1	0.5 0	.1 0.0	6 0.1	0.1	0.7	0.0	0.9	10	0.0	0.0	J.O 1	.6 0.0
44	0.	70.	1 0.2	0.2	2 0.1	0.7	0.1	0.2	0.2	0.2	0.0	0.5	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.3	D.1 (	0.1	0.1 C	0.1 (	0.8 0	.1 0	.9 0.1	1.5	0.4	0.5	0.1	0.1	1.2	0.6 0	.1 0.1	0.1	0.1	0.1	0.0	0.0	0.0	10	0.0	J.O 0.	.0 0.0
4	0.	0.	5 0.3	0.1	0.1	0.0	0.5	0.2	0.8	0.2	0.2	0.1	0.8	0.1	0.1	0.1	0.3	0.1	0.1	0.1	D.1 (	0.4	0.1 C	0.5	0.1 0	.1 0	.1 0.1	0.6	0.1	0.1	0.1	0.1	0.7	0.1 0	.1 0.	0.1	0.0	0.0	0.0	0.0	0.0	0.0	10 0	J.O 0.	.0 0.0
46	0.	0.	6 0.2	0.0	0.2	0.8	0.9	0.2	0.4	0.2	0.2	0.2	0.9	0.2	0.1	0.1	0.3	0.3	0.1	0.4	D.1 (	0.4	0.1 C	0.1	1.2 1	.2 0	.1 0.1	0.7	0.7	0.7	0.7	0.7	0.1	0.8 0	.0 0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	10 0.	.0 0.0
4	0.	1 0.	0.0	0.5	0.3	0.7	0.7	0.2	0.8	0.2	0.1	0.1	0.3	1.1	0.1	0.3	0.1	0.1	0.5	0.5	0.5 (	J.5	0.1 C	J.1 (	J.6 0.	.6 0	.1 0.1	0.1	0.1	0.1	0.1	0.8	0.0	0.9 0	.0 1.0	0.0	0.0	0.0	0.0	0.0	1.6	0.0	0.0 0	J.0 1	0.0
48	0.	∠ 0.	5 0.2	0.5	0.6	0.3	0.3	0.1	0.1	0.1	0.1	0.4	0.1	0.5	0.1	0.1	0.1	0.1	0.1	1.6	J.8 (	J.1 I	U.U C	J.U (	0.9 1	.0 1	.0 1.1	1.1	1.1	0.0	0.0	1.2	0.0	0.0 0	.0 0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0 (	J.U 0.	.0 10

Figure A14.5

# **APPENDIX 15** CAST DATA FOR JET ACCIDENTS 1987 - 2008

## INTRODUCTION

This appendix contains a replication of the Jet accident database provided to EBT by CAST. It also contains certain results in graphic format from the CAST analysis as well as some further analysis by the EBT data subgroup of the aforementioned cast data (1991-2008) augmented with two more recent years (2009 & 2010) from the NTSB Accident Database.

### 15.1 CAST DATA FOR JET ACCIDENTS 1987 - 2008

Accident ID	Category Definition	Severity (Portion of People on Board Eatal)	Working Column - Serverity (Calculation)	Pax. Dead	Crew Dead Tot Fatal (onBd)	<ul> <li>Ser-ious</li> <li>(OnBd)</li> </ul>	Pax OnBd	OnBd Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
1	LUC-I Midair	0.982	0.982	38 1.	2 50	1	39 12		15/01/1987	1987	Varig	Brazii	Western	Abidjan, Ivory Coast	B/0/ SA-226	Jet TP-Small	I anding - Approach	XX	NO	100	Latin America & Caribbean	SA/CA	SA Mercosur	X 2 Ground	yes
2	Widen		1.000			Ŭ		2	13/01/1307	1307	okywest	007	Western	itteams, or	04-220			^^	1.0		North America	INA-Odi	00-0anada	fatal	yes
3	LOC-I	0.504	0.504	7 2	9	10	16 3	0 (	04/03/1987	1987	Northwest Ex	USA	Western	Romulus, Mi	C-212	TP-Small	Landing - Approach	хх	No	100	North America	NA-Car	US-Canada	x	yes
			0.000							1987	Braathens Sverige										_				
4	RE-Takeoff		0.000				21	(	06/01/1987	1087	AB	Sweden		Stockholm	Caravelle-	Jet	TAKEOFF				Europe	EUROPE	Sweden	HULL LOSS	ASEDB
5	SCF-NP		0.000			1	167		12/02/1987	1907	Conair A/S	Denmark		SALZBURG	720-518	Jet	LANDING				Europe	EUROPE	Denmark	HULL LOSS	ASEDB
6	LOC-I	0.333	0.333	2 0	2	0	4 2	0 (	08/05/1987	1987	American Eagle	USA	Western	Mayaguez	C-212	TP-Small	Landing - Approach	хх	No	100	North America	NA-Car	US-Canada		
			70.000							1987	(Exec)													x	yes
7	ARC		0.000				102		23/02/1987		SAS	Sweden		TRONDHEIM	DC-9-41	Jet	LANDING				Europe	EUROPE	Sweden	HULL LOSS	ASEDB
8	USOS	0.623	0.623	23 4	27	18	37 8	0 (	04/04/1987	1987	Garuda	Indonesia	Western	Medan, Sumatra,	DC-9	Jet	Landing - Approach	T-Storm	No	100	Asia	Asia	Asia-Low-Mdl Income		
			70.000							1987				Indonesia										x	yes
9	SCF-NP		0.000						06/04/1987		Conair A/S	Denmark		ROME	720-051B	Jet	LANDING				Europe	EUROPE	Denmark	HULL LOSS	ASEDB
10	CFIT	1	1.000	0 2	2	0	0 2	0	12/10/1987	1987	AeroEjecutivos SA	Colombia	Western	(near) Ocana, CO	DHC-6	TP-Large	Landing - Initial Descent?	Vis	No	100	Latin America & Caribbean	SA/CA	SA (Northern)		
11		1	<b>A</b> 000	34 3	37	0	34 3	-	15/10/1087	1087	Aero Transporto	Italy	Western	Mount Crezzo, italy		TPLarge	En Pouto	leing	No	100	Europo	Europa		x	yes
		'	1.000	34 3	57	Ŭ	34 3	U I	13/10/1907	1907	Aero mansporte	italy	western	Mount Crezzo, italy	AIIX-42	IT-Large		loing	NO	100	Luiope	Luiope		x	ves
12	FUEL	1	1.000	0 2	2	0	0 2	0 2	28/10/1987	1987	SMB Stage	USA	Western	Bartlesville Ok	Convair 640 (340D)	TP-Large	Landing - Rollout	хх	No	100	North America	NA-Car	US-Canada		,
-			0.000							1007														х	yes
13	RE-Landing		0.000						11/04/1987	1907	Transbrasil	Brazil		MANAUS	707-330C	Jet	LANDING				Latin America & Caribbean	CARIBBEAN	Brazil	HULL LOSS	ASEDB
14	ICE	0.865	0.865	16 2	18	3	19 2	0 2	23/11/1987	1987	Ryan	USA	Western	Homer, Ak	BE1900	TP-Small	Landing - Approach	Icing	No	100	North America	NA-Car	US-Canada		
45			1 000			0			40/04/4007	1007	Duffele	1104	10/		D707	1-4	Landina. Anna a sh	<b>F</b>	Na	100	North Arrendon	NA Osa	LIQ Querada	X	yes
15		1	1.000	13 3	16	0	13 3	0	21/12/1987	1987	Air Littoral	France	Western	Bordeaux, FR	EMB-120	TP-Small	Landing - Approach	год хх	No	100	Europe	Europe	EU-EFTA	X	yes
						-								,										x	yes
17	ADRM	0.492	0.492	1 0	1	34	0 6	0 (	04/08/1987	1987	LanChile	Chile	Western	Calama, CL	B737	Jet	Landing - Rollout	ХХ	No	100	Latin America & Caribbean	SA/CA	Asia-Low-Mdl Income	X	yes
18	Other	0.533	0.003	7 2	1	1	324	0	11/08/1987	1987	Trans Colorado	Japan	Western	WASHINGTON Bayfield Co	747-200 SA-227	Jet TP-Small	PARKED Sabotage	Wind	No	100	Asia North America		Japan US-Canada	NONE	ASEDB
10		0.000	0.000	'   <sup>-</sup>	ľ		10 2	ľ	10/01/1000			00,1	Western	Baylicia, Co	0/(22/			VVIII G	10	100	North America			х	yes
20	RE-Landing	ARC 0.014	0.014	0 0	0	1	0 4	0	29/01/1988	1988	ICS - Inter Ciel	France	Western	Toulouse, FR	BAC Vanguard	TP-Large	T/O Aborted	хх	No	100	Europe	Europe	EU-EFTA		
21		1	<b>A</b> 000	10 2	21	0	10 2		08/02/1088	1088	Service	Cormany	Western	Mulhoim DE	Epirchild (Swpan) Motro	TD Small	Landing Approach	T Storm	No	100	Europo	Europa		x	yes
21	SCI -INF	'	1.000	15 2	21	Ŭ	19 2		00/02/1900	1900	AG	Germany	western					1-310111	NO	100	Luiope	Luiope		x	ves
22	LOC-I	0.833	0.833	10 2	10	0	10 2	0	19/02/1988	1988	AvAir-AmEagle	USA	Western	Cary, NC	SA-227	TP-Small	T/O Initial Climb	хх	No	100	North America	NA-Car	US-Canada		
22		0.004	50.004	149 6	154	1	140 6	1	16/00/1007	1097	Northweat	1164	Weatorn	Bomuluo		lot	T/O Initial Climb	<b>V</b> V	No	100	North Amorica	NA Cor	LIS Conodo	X 1 Cround	yes
23		0.554	0.554	140 0	134		145 0	11	10/00/1907	1907	Northwest	USA	western	Komulus	00-9	Jei		^^	NO	100	North America	INA-Cal	03-Callada	fatal	ves
24	SCF-NP	1	1.000	20 3	23	0	20 3	0 (	04/03/1988	1988	TAT European	France	Western	Fontainebleau, FR	Fairchild FH-227	TP-Small	Initial Descent	IMC	No	100	Europe	Europe	EU-EFTA		,
25		1	<b>7</b> 000	74 0	02	0	74 0		21/00/1007	1007	Airlines	Theiland	Weatern	Dhukot Theiland	P727	lot	Londing Approach	<u></u>	No	100	Acia	Asia	Asia Low MdL Incomo	X	yes
25		0.361	0.361	25 3	28	28	77 5		15/11/1987	1987	Continental	USA	Western	DEN	DC-9	Jet	T/O Initial Climb	Snow	No	100	North America	NA-Car	US-Canada	x	ves
27	FIRE-NI	1	1.000	140 1	9 159	0	140 19		28/11/1987	1987	South African	So Africa	Western	134nm NE of Mauritius,	B747	Jet	En Route	XX	No	100	Africa	Africa	Africa	~	,
									00/05/1000	1000	Airways			MU	5110 7					100				х	yes
28	CFIT	1	1.000	33 3	36	0	33 3	0 0	06/05/1988	1988	vvideroe	Norway	vvestern	Bronnoysund, Norway	DHC-7	IP-Large	Landing - Approach	Cloud	NO	100	Europe	Europe	EU-EFTA	x	ves
29	ARC	0	0.000	0 0	0	0	98 5	0	27/12/1987	1987	Eastern	USA	DC-9	Pensacola, Fla	B727	Jet	Landing - Rollout	Wind, Echo	No	100	North America	NA-Car	US-Canada	x	yes
30	LOC-I	0.5	0.500	0 2	2	0	2 2	0 2	26/05/1988	1988	Star Air	Sudan	Western	Hanover, DE	Fokker F.27	TP-Large	Landing - Approach	хх	Yes	100	Africa	Africa	Africa		
31	CEIT	1	1 000	11 5	16	0	11 5	0.0	02/01/1089	1088	Condor	Germany	Western	Izmir Turkev	B737	let	Initial Descent	Rain	No	100	Europe	Europe	FLLEFTA	X	yes
32	CFIT	1	1.000	1 3	4	0	1 3	0	16/06/1988	1988	Myanma Airways	Myanmar	Western	Putao, BU	Fokker F.27	TP-Large	Initial Descent	Cloud	No	100	Asia	Asia	Asia-Low-Mdl Income	~	,00
																5								х	yes
33	LOC-I	0.375	0.375	0 3	3	0	5 3	0 (	06/07/1988	1988	Lineas Aereas	Colombia	Western	Barranquilla, CO	Canadair CL-44	TP-Large	T/O Climb to Cruise	хх	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	Y	Ves
34	CFIT	1	1.000	11 4	15	0	11 4	0	27/02/1988	1988	Talia Air	Turkey	Western	No. Cyprus	B727	Jet	Landing - Approach	Fog	No	100	Europe	Europe	NoAfr/MidEast	x	yes
35	CFIT	1	1.000	137 6	143	0	137 6	0	17/03/1988	1988	Avianca	Colombia	Western	Cucuta, CO	B727	Jet	T/O Climb to Cruise	Fog	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	x	yes



Accident ID	Category Definition	Severity (Portion of People on Board Fatal)	Working Column Serverity (Calculatio	Pax. Dead	Crew Dead	Tot Fatal (onBd) Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
36	LOC-I	1	1.000	0	4 4	0	0 4	4 0	31/03/1988	1988	ARAX Airlines	Egypt	Western	Cairo, EG	DC-8	Jet	T/O Initial Climb	XX	No	100	Africa	Africa	NoAfr/MidEast	x	yes
37	SCF-NP	0.01	0.010	0	1 1	0	96 7	7 0	28/04/1988	1988	Aloha	USA	Western	Maui	B737	Jet	En Route	ХХ	No	100	North America	NA-Car	US-Canada	x	yes
38	SCF-NP	0.5	0.500	0	2 2	0	2 2	2 0	15/09/1988	1988	First Air	Canada	Western	Ottawa, CA	BAE (HS) 748	TP-Large	Initial Descent	ХХ	No	100	North America	NA-Car	US-Canada		
															( - / -									x	ves
39	RE-Takeoff		0.000			2	240		21/05/1988	1988	American Airlines	USA		DALLAS	DC-10	Jet	TAKEOFF				North America	NA-Car	USA	HULL LOSS	ASEDB
40	RE-Takeoff	0.002	0.002	0	0 0	1	16 9	9 0	23/05/1988	1988	LACSA	Honduras	Western	San Jose, CR	B727	Jet	T/O Run	ХХ	Yes	100	Latin America & Caribbean	SA/CA	CA/Carib	x	yes
41	CFIT	1	1.000	15	7 22	2 0	15 7	70	12/06/1988	1988	Austral	Argentina	Western	Posadas, Argentina	MD-81	Jet	Landing - Approach	Fog	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	x	yes
42	CFIT	1	1.000	0	6 6	0	0 6	6 0	21/07/1988	1988	TAAG (Angola Air	Angola	Western	Lagos, NG	B707	Jet	Approach	XX	XX	100	Africa	Africa	Africa		ĺ
											Charter)													x	ves
43	SCF-PP	0	0.000	0	0 0	0	260 1	15 0	24/07/1988	1988	Air France	France	Western	Delhi, IN	B747	Jet	Landing - Rollout	xx	No	91	Europe	Europe	EU-EFTA	x	ves
44	CFIT	1	1.000	31	3 34	1 0	31 3	3 0	19/10/1988	1988	Vavudoot	India	Western	Gauhati, India	Fokker F.27	TP-Large	Landing - Approach	Rain	No	100	Asia	Asia	Asia-Low-Mdl Income		<b>,</b>
																								x	Ves
			0.000							1988											North America				,
45			0.000				7		27/09/1099	1300	TINIA	1164		CHICAGO	727 100	lot					North America	NA Cor	1104		
40		0.202	0.202	4	2 6	2	14	2 0	2//00/1900	1000	Pothia Elight	Einland	Montorn		T21-100	TD Small	LANDING	IMC	No	100	Furana	NA-Cal		HULL LOSS	ASEDB
40		0.302	0.302	4	2 0	<sup>2</sup>	14 2	2 10	14/11/1900	1900		Fillianu	western	Selliajuki, FI		TP-Smail	Lanuing - Approach	IIVIC	INO	100	Europe	Europe	EU-EFTA		
47		0	0.000	0	0 0			0 0	00/40/4000	1000	Air Oreshes	Ossada	Marchanna	Westerneich OA		TDIANN	Lending Annuals	0	N.	400	North America			x	yes
47	UFII	0	0.000	0	0 0	0	0 3	3 0	03/12/1988	1988	Air Creebec	Canada	vvestern	waskaganish, CA	BAE (HS) 748	IP-Large	Landing - Approach	Snow	NO	100	North America	NA-Car	US-Canada		
					_																		<u> </u>	x	yes
48	JSOS	0.081	0.081	1	6 7	13	89 7	7 0	31/08/1988	1988	CAAC	China	Western	Hong Kong	Trident-2	Jet	Landing - Approach	Rain-Wind	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
49	LOC-I	0.144	0.143	12	2 14	4 26	101 7	7 0	31/08/1988	1988	Delta	USA	Western	DFW	B727	Jet	T/O Aborted	XX	No	100	North America	NA-Car	US-Canada	x	yes
50	CFIT	1	1.000	0	2 2	0	0 2	2 0	12/01/1989	1989	First Air	Canada	Western	Dayton, Ohio	BAE (HS) 748	TP-Large	T/O Initial Climb	хх	No	100	North America	NA-Car	US-Canada		
																								x	yes
51	OTHER-	0.332	0.332	35	0 35	5 27	104 6	6 0	15/09/1988	1988	Ethiopian AL	Ethiopia	Western	Bahir Dar, Ethiopia	B737	Jet	T/O Initial Climb	XX	No	100	Africa	Africa	Africa		
	BIRD																							x	yes
52	RE-Landing ARC	0	0.000	0	0 0	0	56 6	6 0	26/09/1988	1988	Aerolineas	Argentina	Western	Ushuaia. AR	B737	Jet	Landing - Rollout	Wind	No	100	Latin America & Caribbean	SA/CA	SA Mercosur		
											Argentinas													x	ves
53	ARC	0	0 000	0	0 0	0	125 7	7 0	15/10/1988	1988	Nigeria Airways	Nigeria	Western	Port Harcourt NG	B737	Jet	Landing - Rollout	T-Storm	No	100	Africa	Africa	Africa	x	ves
54	CEIT	0.633	0.633	26	7 32	2 16	45 7	7 0	17/10/1988	1988	Lloanada Al	Uganda	Western	Rome	B707	Jet	Landing - Approach	Fog	No	100	Africa	Africa	Africa	Y	ves
55		0.000	0.000	127	6 13	23 2	120 6		10/10/1089	1088		India	Western	Abmedabad India	B737	lot	Landing - Approach	Hazo	No	100	Asia	Asia	Asia-Low-MdL Income		Ves
56		0.300	0.300	127	1 12	2 6	65 /		25/10/100	1300	Aoro Poru	Doru	Western	Juliaca Poru	Eokkor 29	lot		TIGZE	No	100	Latin Amorica & Caribboan		SA (Northorn)	×	yes woo
50		0.173	1 000	2	5 0	- 0	2 4	- 0	12/12/1000	1000	CAS Air Nigorio	Nigorio	Western		D707	Jot	Initial Descent	NA Vio	No	100	Africo	Africa	Africo	^ 	yes
59	SCE DD	0.407	0.407	3	0 47	7 74	110		09/04/4000	1000	British Midland		Western	East Midlanda LIK	D737	lot	T/O Climb to Cruico	v15	No	100	Furono	Europo		^   v	yes
50		0.407	10.407	41	2 47	14	110 0		00/01/1985	1909	Swedowers Al	Sweden	Western	Last Willianus, UN	C00	TD Cmr		XX XX	Vec	100	Europe	Europe		^	yes
29	100-1	1	1.000	14	2 16		14 2	2 0	08/05/1985	1989	Swedeways AL	Sweden	western	virkvams, Sweden	099	1P-Small	Lanuing - Approach	**	res	100	Europe	Europe	EU-EFIA		
60		4	3.000	407	7 4	11	107	7 0	00/00/4000	1000	Independent Air		Machan	4=0+00	D707	lat	Landing Initial Description	Claud	No	100	North Amoriac	NA Car	LIC Canada	X	yes
00	JEII	1	0.000	137	7 14	+4 0	13/ /	/ 0	08/02/1989	1989	independent Air	USA	western	Azores	BIUI	Jet	Lanuing - Initial Descent	Cioua	INO	100	North America	INA-Car	US-Canada	x	yes
			0.000				100		00/00/4000	1989					707.000							455104			10500
61	RE-Landing ARC		2				103		09/02/1989	)		Mozambique		LICHINGA	737-200	Jet	LANDING				Africa	AFRICA	Mozambique	HULL LOSS	ASEDB
			0.000							1989	Evergreen										North America				
62	Other				1 1				09/02/1989	)	International A/L	USA		SALT LAKE CITY	DC-9-	Jet	CLIMB					NA-Car	USA	NONE	ASEDB
63	CFIT	1	1.000	0	4 4	0	0 4	4 0	19/02/1989	1989	Flying Tiger	USA	Western	Malaysia	B747	Jet	Landing - Approach	Cloud-fog	No	100	North America	NA-Car	US-Canada	x	yes
64	SCF-NP	0.026	0.026	9	09	5	337 1	18 0	24/02/1989	1989	United	USA	Western	HNL	B747	Jet	T/O Climb to Cruise	XX	No	100	North America	NA-Car	US-Canada	x	yes
65	CE	0.364	0.364	21	3 24	4 19	65 4	4 0	10/03/1989	1989	Air Ontario	Canada	Western	Dryden, Ont	Fokker 28	Jet	T/O Initial Climb	Snow	No	100	North America	NA-Car	US-Canada	x	yes
66	LOC-I	1	1.000	0	2 2	0	0 2	2 0	18/03/1989	1989	Evergreen	USA	Western	Saginaw, Tex	DC-9	Jet	T/O Initial Climb	XX	No	100	North America	NA-Car	US-Canada	x	yes
67	CFIT	1	1.000	0	3 3	0	0 3	3 #	21/03/1989	1989	Transbrasil	Brazil	Western	Sao Paulo	B707	Jet	Landing - Approach	XX	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	22 Ground	
																	<b>U</b>							fatal	ves
68	ARC	0	0.000	0	0 0	0	133 6	6 0	03/04/1989	1989	Faucett	Peru	Western	lauitos. PE	B737	Jet	Landing - Rollout	Rain, x-	No	100	Latin America & Caribbean	SA/CA	SA (Northern)		
																		wind					( ,	x	ves
69	00-1	1	1 000	2	3 5	0	3 2	2 2	26/04/1980	1989	Aerosucre Colombia	Colombia	Western	Barranguilla CO	Caravelle	Jet	T/O Initial Climb	XX	Yes	100	Latin America & Caribbean	SA/CA	SA (Northern)	2 Ground	,
				-	Ŭ Ŭ	ľ	ľ ľ	- 1		1.000						001			100					fatal	Ves
70	CEIT	1	1 000	18	2 20		18	2 0	28/10/1090	1080	Aloha Island Air	USA	Western	Malawi Bay	DHC-6	TP-Small	En Route	Cloud	No	100	North America	NA-Car	US-Canada	iatai	,03
10			1.000	10	2 20		10 2	2 0	20/10/1908	1909	Aloria Islanu All	007	Westelli	Ivialawi Day	0110-0		LITTOULE	Ciouu	NO	100	North America	In-Cai	00-Callaua	x	Ves
																								^	,00

Accident ID	Category Definition	Previously ARC	Severity Portion of eople on Board Fatal)	Working Column - Serverity (Calculation	رر Pax. Dead	Crew Dead	Tot Fatal (onBd) Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	, Weigh - C/G	AIR Claims Loss	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
71	RE-Takeoff	0		0.000	0 (	0 0	0	69 8	0	17/05/1989	1989	Somali Airlines	Somalia	Western	Nairobi, KE	B707	Jet	T/O Aborted	Heavy Rain	No	100	Africa	Africa	Africa	х	yes
72	ICE	1	[	1.000	4	2 6	0	4 2	0	26/12/1989	1989	United Express	USA	western	Pasco, wa	BAe31	P-Smai	Landing - Approach	Icing	NO	100	North America	NA-Car	US-Canada	~	Ves
73	CFIT	0.9	54	0.954	169	9 17	78 7	178 9	0	07/06/1989	1989	Surinam Awy	Surinam	Western	Paramaribo, Surinam	DC-8	Jet	Landing - Approach	ХХ	No	100	Latin America & Caribbean	SA/CA	CA/Carib	x	yes
74	CFIT	1		1.000	20 3	3 23	3 0	20 3	0	15/01/1990	1990	SANSA	Costa R	Western	San Jose, CR	Casa-212	TP-Smal	T/O Climb to Cruise	IMC	No	100	Latin America & Caribbean	SA/CA	CA/Carib		ĺ
																									х	yes
75	RE-Landing		[	0.000				66		11/07/1080	1989	Kenva Ainwave	Kenva			707-351B	lot					Africa		Kenva		
76	CFIT	1		1.000	11 4	4 15	5 0	11 4	0	05/02/1990	1990	Helicol	Colombia	Western	Ibaque, Colombia	G-159	TP-Large	En Route	Clouds	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	HOLL LOSS	AGEDD
																									x	yes
77	LOC-I	0		0.000	0 (	0 0	0	36 4	2	12/02/1990	1990	TAM	Brazil	Western	Bauru, Brazil	Fokker F.27	TP-Large	Go Around	хх	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	2 Ground	
78	SCE-PP	0.3	87	0 387	111	1 11	12 /6	285 11	1 0	10/07/1080	1080	United		Western	Sioux City	DC-10	lot	Landing - Approach	vv	No	100	North America	NA_Car	LIS-Canada		yes
79	CFIT	1	.07	1.000	0 3	3 3	0	0 3	0	21/03/1990	1990	TAN Honduras	Honduras	Western	Tegucigalpa, HN	L-188 Electra	TP-Large	e Landing - Approach	Rain-Fog	No	100	Latin America & Caribbean	SA/CA	CA/Carib	^	yes
															0 0 1 7		Ű	0 11	Ű						x	yes
00	DE Londing		ľ	0.000						24/07/4000	1989	Dhilipping Airlings	Dhilippings			DAC 4 44 500	lat					Anin		Dhilippings		
81	SCF-NP	1		1 000	3 3	2 5	0	3 2	0	12/04/1990	1990	Wideroe	Norway	Western	Vaerov Norway	DHC-6	TP-Smal	LANDING	Turb	No	100	Furope		FUIIIPPINES	HULL LUSS	ASEDD
									-																x	yes
82	LOC-I	0.5		0.500	15 5	5 20	0 0	35 5	0	10/05/1990	1990	Noroeste	Mexico	Western	Tuxtla Gutierrez, Mex	SA-227	TP-Smal	I Landing - Approach	xx	No	100	Latin America & Caribbean	SA/CA	CA/Carib	x	ves
83	CFIT	0.3	62	0.362	68 4	4 72	2 0	181 18	86	27/07/1989	1989	Korean Air	Korea	Western	Tripoli, Kibya	DC-10	Jet	Landing - Approach	Fog	No	100	Asia	Asia	Asia-Low-Mdl Income	6 Ground	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
																									fatal	yes
84	RE-Landing		ſ	0.000	0 0	0 0	0			10/08/1989	1989	Apisa Air Cargo	Peru		IQUITOS	DC-8-33F	Jet	LANDING				Latin America & Caribbean	CARIBBEAN	Peru	HULL LOSS	ASEDB
85	SCF-PP	1		1.000	19	2 21	1 0	19 2	0	18/05/1990	1990	Aerolift	Philippines	Western	Manila	BE 1900	TP-Smal	I T/O Initial Climb	ХХ	Yes	100	Asia	Asia	Asia-Low-Mdl Income		
96	DE Takooff	0.0	0.0	0.009	0	0 0	0	50 6	0	16/00/1000	1000		Argontino	Mostorn	San Carlos do Parilasha	Fokkor F 29	lot	T/O Dup	Snow	-	100	Latin Amorica & Caribbaan	SA/CA	SA Morocour	x	yes
00	RE-Takeon	0.0	00	0.000			9	59 0	0	10/00/1908	1909	LADE	Argentina	western	AR	FURKEI F.20	Jei		Slush		100		SAVCA	SA INIELCOSUL	x	ves
87	LOC-I	1		1.000	33 5	5 38	3 0	33 5	0	21/11/1990	1990	Bangkok A.W.	Thailand	Western	Koh Samui, Thailand	DHC-8	TP-Smal	I Go Around	Rain	No	100	Asia	Asia	Asia-Low-Mdl Income		,
				000							3000														х	yes
88	CEIT		ſ	0.000				165		25/08/1980	1989	Toros Air	Turkey			727-247	let	INITIAL CLIMB				Furope	FUROPE	Turkey		
89	FUEL	0.2	4	0.240	12 (	0 12	2 17	48 6	0	03/09/1989	1989	Varig	Brazil	Western	San Jose do Xingu, Brazil	B737	Jet	En Route	ХХ	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	X	yes
90	CFIT	0.0	48	0.048	1 (	0 1	0	18 3	0	30/01/1991	1991	Merpati Nusantara	Indonesia	Western	Gorontalo, ID	IPTN 212	TP-Smal	I Initial Descent	T-Storm	No	100	Asia	Asia	Asia-Low-Mdl Income		ľ
01		0.0	20	0.020	0	0 0	12	17 2		20/01/1001	1001	CCAir		Montorn			TD Small	L Landing Dollaut	loing	No	100	North Amorico	NA Cor	LIE Canada	x	yes
91	ICE	0.0	39	0.039			13		0	30/01/1991	1991	CCAII	USA	western	Deckley, US	DAE 31	1 P-Siliai	Lanuing - Rollout	licing	INU	100	North America	INA-Cal	US-Callaua	x	ves
			1	0.000							1989															
92	ARC	0.0	05	0.004		0 0		88	_	07/09/1989	)	Okada Air	Nigeria	10/	PORT HARCOURT	BAC 1-11-	Jet	LANDING	1140	N	100	Africa	AFRICA	Nigeria	HULL LOSS	ASEDB
93	FIRE-NI	0.0	35	0.034	2 0	0 2	3	5/ 0 12 7	0	20/09/1989	1989	Delta		Western	SIC	B737	Jei	Ground Parked		No	100	North America	NA-Car	US-Canada	X	yes
95	CFIT	0.9	1	0.910	129	3 13	32 14	139 7	0	21/10/1989	1989	Sahsa	Honduras	Western	Tegucigalpa, HN	B727	Jet	Descent	Clouds-	No	100	Latin America & Caribbean	SA/CA	CA/Carib		,
	0.517					-							-						wind		100				x	yes
96		1	22	1.000	47	7 54	1 0	47 7	0	26/10/1989	1989	China Airlines	laiwan	Western	Hualien, laiwan	B737	Jet	T/O Initial Climb		No	100	Asia	Asia	HI-Income Asia-Pac	X	yes
98	SCF-PP	1	22	1.000	20 3	3 23	3 0	20 3	0	05/04/1991	1909	Atlantic Southeast	USA	Western	Brunswick, US	EMB-120	TP-Smal	I Approach	XX	No	100	North America	NA-Car	US-Canada	^	yes
									-			Airlines													x	yes
99	SCF-PP	0.5	1	0.510	10	1 11	4	19 3	0	19/04/1991	1991	Air Tahiti	Tahiti	Western	Marquess Islands, PF	DO 228	TP-Smal	I Approach	xx	No	100	Aust	Aust/asia	Pacific	x	ves
				0.000							1989	America West										North America				
100	SCF-NP			0.000				125		30/12/1989	1000	Airlines	USA		TUCSON	737-200	Jet	LANDING					NA-Car	USA	HULL LOSS	ASEDB
10	RE-Landing			0.000				66		30/12/1989	1989	Air Ivoire	Cote d'Ivoire		MAN	F-28	Jet	LANDING				Africa	AFRICA	Cote d'Ivoire	HULL LOSS	ASEDB
10	ARC	0		0.000	0 (	0 0	0	14 3	0	09/06/1991	1991	Royal Nepal Airlines	Nepal	Western	Lukla, NP	DHC-6	TP-Smal	Landing - Rollout	Clouds	No	100	Asia	Asia	Asia-Low-Mdl Income		
10	DELonding			0.000	0	0 0		05 5	0	05/04/4000	1000	Aprolinges	Argontino	Moster		Fokker F 29	lot	Londing Dellast	Doin	Nic	100	Lotin America <sup>9</sup> Coribberry	SA/CA	SA Maragour	x	yes
10.	RE-Landing	0		0.000			0	00 0	0	05/01/1990	1990	Argentinas	Argenuna	western	Villa Gesell, AK	FURKEL F.20	Jei	Lanuing - Rollout	Rain	INO	100	Laun America & Caribbean	SAICA	SAWERCOSUL	x	yes
104	LOC-I	0.8	74	0.874	12	1 13	3 2	13 2	0	10/07/1991	1991	L'Express	USA	Western	(near) Birmingham, US	BE 99	TP-Smal	I Approach	T-Storm- Wind	No	100	North America	NA-Car	US-Canada	×	Ves
10	FUEL	0.4	92	0.491	65 8	8 73	3 81	149 9	0	25/01/1990	1990	Avianca	Colombia	Western	Long Is., NY	B707	Jet	Landing - Approach	Rain-Wind	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	x	yes



Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation	( Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd	Date	١	/ear Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub Region	- Note	Accidents in 1987-2007 data set
106	USOS		0.639	0.639	88	4 92	22	139	7 0	) 14/02/19	90 1	990 Indian Airlines	India	Western	Bangalore, India	A320	Jet	Landing - Approach	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
107	SCF-NP		1	1.000	11	3 14	0	11	3 0	) 11/09/19	91 1	991 Continental Express	USA	Western	(near) Eagle Lake, US	EMB-120	TP-Small	Initial Descent	ХХ	No	100	North America	NA-Car	US-Canada		
108			1	1 000	0	1 1	0	0	1 0	17/00/10	01 1	001 Ethiopian Airlings	Ethiopia	Western	Diibouti City D I	Horoulos	TPLargo	Initial Descent	Cloude	No	100	Africo	Africa	Africa	X	yes
100			1	1.000	ľ	7 7	ľ	ľ	4	11/08/18	51 [1		сипоріа	WESIEIII		TICICUICS	IF-Laige		Ciouus		100	Ainca	Anica	Ainca	x	Ves
109	LOC-I		1	1.000	0	2 2	0	0	2 0	18/09/19	91 1	991 Canair	Canada	Western	Belvidere Centre, US	CV 580	TP-Large	En Route	хх	No	100	North America	NA-Car	US-Canada	x	ves
110	CFIT		1	1.000	13	2 15	0	13	2 0	) 27/09/19	91 1	991 Solomon Airlines	Solomon Is	Western	Avuavu, SB	DHC-6	TP-Small	Initial Descent	Rain-Cloud	No	100	Aust	Aust/asia	Pacific	x	ves
				0.000							1	990													<u>^</u>	<b>J</b> 00
111	ARC							82		17/02/19	90	AVIACO	Spain		PALMA	DC-9-32	Jet	LANDING				Europe	EUROPE	Spain	HULL LOSS	ASEDB
				0.000							1	990												Congo, The		
110	11000							2		01/02/10		Katale Aero	Conzo		0014	707 2200	let					Africo		Democratic Republic		
112	RE-Landing	ARC	0	0.000	0	0 0	0	102	5 0	22/03/19			China	Western	GUMA Guilin CN	707-3290 BAE (HS) Trident	Jet	Landing - Rollout	T-Storm	No	100			Asia-Low-MdLIncome	HULL LUSS	ASEDB
110		/	U	0.000	ľ	Ĭ	ľ	102	ľ		~' `		Omina	Western								7.510	1.010		x	ves
114	CFIT		0.5	0.500	1	1 2	0	2	2 0	03/01/19	92 1	992 Commutair	USA	Western	(near) Saranac Lake, US	BE 1900	TP-Small	Approach	IMC	No	100	North America	NA-Car	US-Canada	x	ves
115	SCF-NP		1	0.000	0	0 0	0	175	20 0	07/05/19	90 1	990 Air India	India	Western	New Delhi	B747-200	Jet	Landing - Rollout	ХХ	No	100	Asia	Asia	Asia-Low-Mdl Income		,
116			0.067	0.067	0	0 0	0	112	6 0	11/05/10	00 1	000 Dhilipping Al	Dhilippingg	Weatorn	Mapila	P727	lot	Cround Darkod	WW	No	100	Asia	Anin	Asia Low MdL Income	X	yes
117			0.007	0.007	26	4 30	26	50	6 0	0 09/02/19	90 1	990 Afrique Airlink	Sudan	Western	Kafoutine SN	CV 640	TP-Large	Landing - Rollout	XX	No	100	Africa	Africa	Asia-Low-iviul income	X	yes
			0.002	0.002	2	.	1-0		ľ		~_ `		Cuuun					Landing Ronout					/ unou	/ Inou	x	yes
118	ARC			0.000				25		14/07/19	90	990 Trans Arabian Air Transport	Sudan		KHARTOUM	707-349C	Jet	LANDING				Africa	AFRICA	Sudan	HULL LOSS	ASEDB
				0.000							1	990										North America				
119	SCF-NP							22		22/07/19	90	US Airways	USA		KINSTON	737-200	Jet	TAKEOFF					NA-Car	USA	HULL LOSS	ASEDB
120	LOC-I		0.029	0.029	0	0 0	1	0	2 0	) 19/03/19	92 1	992 Bearskin Airlines	Canada	Western	Red Lake, CA	DHC-6	TP-Large	T/O Initial Climb	хх	XX	100	North America	NA-Car	US-Canada		
				000		_						000													X	yes
121	RF-Takeoff			0.000	0	0 0	0			25/07/19	90 ['	Ethionian Airlines	Ethionia		ADDIS ABABA	707-300	let	TAKEOFE				Africa	AFRICA	Ethionia		ASEDB
122	TURB			0.043	1	1	2	26		03/10/19	90 1	990 Eastern Air Lines	USA		WEST PALM BEACH	DC-9-31	Jet	CRUISE				North America	NA-Car	USA	NONE	ASEDB
123	Other			1.000	1	1	-	1		05/11/19	90 1	990 Indian Airlines	India		GOA	A300-	Jet	LOAD/UNLOAD				Asia	ASIA (EX CHINA)	India	NONE	ASEDB
124	CFIT		1	1.000	40	0 46	0	40	6 0	) 14/11/19	90 1	990 Alitalia	Italy	Western	Zurich	DC-9	Jet	Landing - Approach	Rain	No	100	Europe	Europe	EU-EFTA	x	ves
125	RI		0.097	0.195	7	1 8	10	39	5 0	03/12/19	90 1	990 Northwest	USA	Western	Detroit	B727-200/ DC-9-14	Jet					North America	NA-Car	US-Canada	x	yes
126	CFIT		1	1.000	3	7 10	0	3	7 0	04/12/19	90 1	990 Sudania Air Cargo	Sudan	Western	Nairobi	B707	Jet	Go Around	Fog	No	100	Africa	Africa	Africa	Х	yes
127	SCF-PP		1	1.000	3	2 5	0	3	2 0	07/06/19	92 1	992 Executive Airlines	USA	Western	Mayaguez, US	CASA 212	TP-Small	Approach	хх	No	100	North America	NA-Car	US-Canada	x	Ves
128	CFIT		0.529	0.529	2	1 3	3	4	2 0	08/06/19	92 1	992 GP Express Airlines	USA	Western	(near) Anniston, US	BE 99	TP-Small	Approach	Fog	No	100	North America	NA-Car	US-Canada		,
100	DI		0.627	1 000	10	2 12	0	10	2 0	01/02/40	01 4	001 Skywoot (USA)/	1184	Westors		SA 227 (Motro)/ B727	lot					North Amorica	NA Car	LIS Canada	X	yes
129			0.027	1.000	10	2 12	0	10	2 0	01/02/19	9111	USAir (USA)	054	western	LAX	300	Jel				100	Notifi America	INA-Cal		x	yes
130	CEII		1	1.000	63	/ /0	U	63	/ 0	24/07/19	92 1	992 Mandala Airlines	Indonesia	vvestern	Ambon, ID	BAC VISCOUNT	TP-Large	Approacn	Rain	NO	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
131	ICE		1	1.000	0	2 2	0	0	2 0	) 17/02/19	91 1	991 Ryan International Airlines	USA	Western	Cleveland, US	MD DC-9	Jet	T/O Initial Climb	Snow, icing	No	100	North America	NA-Car	US-Canada	x	yes
132	RE-Landing	ARC	0.279	0.279	20	0 20	2	65	7 0	) 20/02/19	91 1	991 LanChile	Chile	Western	Puerto Williams, CL	BAE-146	Jet	Landing - Rollout	Rain	No	100	Latin America & Caribbean	SA/CA	Asia-Low-Mdl Income	x	yes
133	LOC-I		1	1.000	20	5 25	0	20	5 0	03/03/19	91 1	991 United Airlines	USA	Western	Colorado Springs, US	B737	Jet	Approach	Wind	No	100	North America	NA-Car	US-Canada	Х	yes
134	CFIT		1	1.000	40	5 45	0	40	5 0	05/03/19	91 1	991 Aeropostal	Venezuela	Western	Valesa, VE	DC-9	Jet	Initial Descent		No	100	Latin America & Caribbean	SA/CA	SA (Northern)	Х	yes
135	RE-Takeoff		0.014	0.014	0	0 0	1	0	4 0	) 12/03/19	91 1	991 Air Transport International	USA	Western	New York, US	MD DC-8	Jet	T/O Aborted	XX	Yes	100	North America	NA-Car	US-Canada	x	yes
136	SCF-NP		0	0.000	0	0 0	0	15	2 0	) 29/10/19	92 1	992 Talair	Papua NG	Western	Esa'ala, PG	DHC-6	TP-Small	Landing - Rollout	хх	No	100	Aust	Aust/asia	Pacific	x	ves
137	SCF-PP		0	0.000	0	0 0	0	0	3 0	03/05/19	91 1	991 Ryan International Airlines	USA	Western	Hartford, US	B727	Jet	T/O Run	хх	No	100	North America	NA-Car	US-Canada	x	ves
138	SCF-PP		1	1.000	213	10 223	0	213	10 0	) 26/05/19	91 1	991 Lauda Air	Austria	Western	94nm. NW of Bangkok, TH	B767	Jet	T/O Climb to Cruise	хх	No	100	Europe	Europe	Hi-Income Asia-Pac	x	ves
120	APC			0.000				110		13/06/10	1	991 Koroan Air	South Koroo		TAEGU	727 200	lot					Asia		South Koree		ASEDP
140	FUE		0.053	0.054	4	0 3	0	53	3 0	26/06/19	91 1	991 Okada Air	Nigeria	Western	Sokoto NG	BAC 1-11	Jet	Initial Descent	IMC	No	100	Africa	Africa	Africa	X	Ves
1 10			0.000	0.001			l.	00		20,00,10	2 T T				00.000, 110	5	001			1.10	100					1/

Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	Ye	ar Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigh - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
141	CFIT		1	1.000	31 6	37	0	31	6 0	13/12/199	92 19	2 Scibe Airlift	Congo, Zr	Western	Goma, ZR	Fokker F.27	TP-Large	Initial Descent	ХХ	No	100	Africa	Africa	Africa		
1/2	SCE ND		1	M 000	247 1	1 261	-	247	14 0	11/07/100	1 90	1 Nationair Canada	Canada	Western	leddah SA		lot	T/O Initial Climb	vv	No	100	North America	NA Car	LIS Canada	x j	yes
142	CFIT		1	1.000	63 6	69	0	63	6 0	16/08/199	1 19	1 Indian Airlines	India	Western	Imphal, IN	B737	Jet	Initial Descent	Rain-Cloud	No	100	Asia	Asia	Asia-Low-Mdl Income	^ ) X \	ves
144	ICE		0	0.000	0 0	0	0	28	3 0	02/01/199	3 19	3 Express Airlines	USA	Western	Hibbing, US	Saab 340	TP-Small	Landing - Rollout	lcing	No	100	North America	NA-Car	US-Canada	,	,
145	CFIT		0.194	0.194	4 0	4	8	19	4 0	06/01/199	3 19	3 Lufthansa CityLine	Germany	Western	Paris, FR	Dash 8	TP-Large	Approach	Rain-Fog	No	100	Europe	Europe	EU-EFTA	x y	yes
146	SCE DD		0.415	0 415	12 4	17	22	20	5 0	00/01/100	2 70	2 Pourog Indonosia	Indonosia	Western	Surabaya ID		TD Lorgo		VV	No	100	Acio	Acia	Asia Low MdLIncomo	x y	yes
140	3CF-PP		0.415	0.415	15 4	17	22	39	5 0	09/01/195	5 19		Indonesia	western	Surabaya, iD	BAE (HS) 746	TP-Large		**	INO	100	Asia	Asia		x y	yes
147	ARC			0.000						14/09/199	7199 91	1 Kabo Air	Nigeria		PORT HARCOURT	BAC 1-11-200	Jet	LANDING				Africa	AFRICA	Nigeria	HULL LOSS A	ASEDB
148	FUEL		0	0.000	0 0	0	0	30	5 0	24/03/199	93 19	3 Air West Express	Sudan	Western	Addis Ababa, ET	Fokker F.27	TP-Large	En Route	XX	No	100	Africa	Africa	Africa	x	ves
149	SCF-NP			0.000						29/09/199	-199 91	1 Aerosucre	Colombia		BOGOTA	Caravelle-	Jet	TAKEOFF				Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	Colombia	HULL LOSS /	ASEDB
				0.000							19	1											LATIN AMERICA &			
150	SCF-NP			<b>T</b> 000			_	_	$\vdash$	10/11/199	1		Nicaragua		MANAGUA	727-25	Jet	PARKED				Latin America & Caribbean		Nicaragua	HULL LOSS	ASEDB
151	ARC			0.000				36		17/11/199	1	SAHSA	Honduras		SAN JOSE	737-200	Jet					Latin America & Caribbean	CARIBBEAN	Honduras		ASEDB
152	RE-Takeoff		0	0.000	0 0	0	0	189	10 0	07/12/199	1 19	1 Libyan Arab Airline	s Libya	Western	Tripoli, LY	B707	Jet	T/O Run	XX	No	100	Africa	Africa	NoAfr/MidEast	x	yes
153	RF-I anding			0.000				90		17/12/199	<b>7</b> 199	1 Alitalia	Italy		WARSAW	DC-9-32	Jet					Europe	FUROPE	Italy		ASEDB
154	RE-Landing	ARC	0	0.000	0 0	0	0	14	3 0	29/04/199	3 19	3 Cont Exp	USA	Western	Pine Bluff, Ark	EMB-120	TP-Small	T/O Climb to cruise	Ice - wind	No	100	North America	NA-Car	US-Canada	Y N	
155	SCF-PP		0.001	0.001	0 0	0	3	123	6 0	27/12/199	1 19	1 SAS	Multi-Nat	Western	Stockholm, SE	MD-80	Jet	T/O Initial Climb	ХХ	No	100	Europe	Europe	EU-EFTA	x y	ves
156	SCF-PP		1	1.000	0 5	5	0	0	5 0	29/12/199	1 19	1 China Airlines	Taiwan	Western	Taipei, TW	B747	Jet	T/O Climb to Cruise	ХХ	No	100	Asia	Asia	Hi-Income Asia-Pac	x j	yes
157	ARC		0.003	0.003	0 0	0	2	36	5 0	18/01/199	92 19	2 US Airways	USA	Western	Elmira, US	MD DC-9	Jet	Landing - Rollout	Wind	No	100	North America	NA-Car	US-Canada	x y	yes
158	CFIT		0.909	0.909	82 5	87	5	90	6 0	20/01/199	2 19	2 Air France Europe	France	Western	Strasbourg, FR	A320	Jet	Approach	ХХ	No	100	Europe	Europe	EU-EFTA	x y	yes
159	CFIT		0.023	0.023	0 0	0	2	0	5 0	15/02/199	2 19	2 MK Airlines	Ghana	Western	Kano, NG	DC-8	Jet	Approach	XX	No	100	Africa	Africa	Africa	x y	yes
160	LOC-I		1	1.000	0 4	4	0	0	4 0	15/02/199	92 19	2 BAX Global dba Ai	r USA	Western	Toledo, US	MD DC-8	Jet	Go Around	Rain, fog,	No	100	North America	NA-Car	US-Canada		
161	ICE		0.54	0.540	25 2	27	-	47	1 0	22/03/100	2 10		1184	Western	New York US	Eokkor E 28	lot	T/O Initial Climb	WIND	No	100	North America	NA Car	US Canada	x j	yes
162	RE-Landing	ARC	0.54	0.040	0 0	0	0	38	7 0	06/10/199	3 79	3 Myanma Airways	Myanmar	Western	Kawthaung BU	Fokker F 27	TP-Large	Landing - Rollout	Rain-Wind	No	100	Asia	Asia	Asia-Low-MdLIncome	^ )	yes
102		/	<u> </u>	0.000	Ů		ľ.			0.4/00/400											100				x y	yes
103	GFII		1	1.000	4 3	<i>'</i>	0	4	3 0	24/03/195	92 F19:	Cargo	Sudan	western	Athens, GR	B/0/	Jet	Approach	Cloud-Iviist	INO	100	Ainca	Amca	AIIICa	x y	yes
164	CFIT		0.385	0.384	4 3	7	12	17	3 0	27/10/199	93 19	3 Wideroe's Flyveselskap	Norway	Western	Namsos, NO	DHC-6	TP-Small	Approach	Rain-Wind	No	100	Europe	Europe	EU-EFTA	x y	yes
165	ARC		0	0.000	0 0	0	0	88	4 0	26/03/199	2 19	2 Inter (Colombia)	Colombia	Western	Tumaco, CO	DC-9	Jet	Landing - Rollout	XX	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	x )	yes
166	LOC-I		1	1.000	4 3	7	0	4	3 0	10/11/199	3 19	3 Air Manitoba	Canada	Western	Sandy Lake, CA	BAE (HS) 748	TP-Large	T/O Initial Climb	XX	No	100	North America	NA-Car	US-Canada	x y	yes
167	SCF-NP			0.000				3		28/03/199	19! 92	2 Export Air Leasing	USA		IQUITOS	DC-8-33AF	Jet	LANDING				North America	NA-Car	USA	HULL LOSS /	ASEDB
168	ARC		0.002	0.002	0 0	0	4	94	5 0	30/03/199	2 19	2 Aviaco	Spain	Western	Granada, ES	DC-9	Jet	Landing - Rollout	Wind	No	100	Europe	Europe	EU-EFTA	x )	yes
169	CFIT		1	1.000	16 2	18	0	16	2 0	01/12/199	93 19	3 Express Airlines	USA	Western	Hibbing, US	BAE 31	TP-Small	Approach	Rain, Cloud, ice	No	100	North America	NA-Car	US-Canada	x y	yes
170	MIDAIR		1	1.000	1 2	3	0	1	2 0	09/12/199	93 19	3 Air Senegal	Senegal	Western	Dakar, SN	DHC-6	TP-Small	Approach	хх	No	100	Africa	Africa	Africa	x y	yes
171	LOC-I		1	1.000	2 3	5	0	2	3 0	07/01/199	94 719	4 Atlantic Coast Airlines	USA	Western	(near) Columbus, US	BAE 41	TP-Small	Approach	Snow, ice	No	100	North America	NA-Car	US-Canada	x y	yes
172	LOC-I		0.529	0.529	0 1	1	1	0	2 0	25/02/199	94 19	4 British World Airline	es UK	Western	(nr) Uttoxeter, GB	BAC Viscount	TP-Large	En Route	lcing	No	100	Europe	Europe	EU-EFTA	x	yes
173	SCF-NP		0	0.000	0 0	0	0	0	5 0	31/03/199	2 19	2 Kabo Air	Nigeria	Western	Orange, FR	B707	Jet	En Route	Turb	No	100	Africa	Africa	Africa	x y	yes
174	SCF-NP		1	1.000	40 7	47	0	40	70	06/06/199	2 19	2 COPA Airlines	Panama	Western	Tocuti, PA	B737	Jet	En Route	XX	No	100	Latin America & Caribbean	SA/CA	CA/Carib	x y	yes
175	SCF-PP		0.147	0.147	2 1	3	9	21	3 0	04/04/199	94 19	4 KLM cityhopper	Nederland	Western	Amsterdam, NL	Saab 340	TP-Small	Go Around	XX	No	100	Europe	Europe	EU-EFTA	x y	yes



Accident ID	Category Definitior	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
176	CFIT		1	1.000	1 2	3	0	1	20	22/06/1992	992 VA	SP	Brazil	Western	Cruzeiro do Sul, BR	B737	Jet	Initial Descent	XX	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
177	SCF-NP	_	0	0.000	0 0	0	1	280	12 0	30/07/1992	992 Tra	ans World Airlines	USA	Western	New York, US	L-1011	Jet	T/O Initial Climb	XX Dain alaud	No	100	North America	NA-Car	US-Canada	Х	yes
1/8	CFII		1	1.000	1 2	9	0	1	2 0	13/06/1994	1994 Aer	ro Cuanonte	Mexico	vvestern	Uruapan, MX	Metro	IP-Small	Go Around	Rain-cloud	NO	100	Latin America & Caribbean	SA/CA	CA/Carib	v	Ves
179	CFIT		1	1.000	7 5	12	0	7	5 0	18/06/1994 🖣	994 Me	erpati Nusantara	Indonesia	Western	Palu, ID	Fokker F.27	TP-Large	Approach	хх	No	100	Asia	Asia	Asia-Low-Mdl Income	x	ves
180	CFIT		1	1.000	99 14	4 113	0	99	14 0	31/07/1992	992 Tha	ai Airways ernational	Thailand	Western	Kathmandu, NP	A310	Jet	Go Around	T-Storm	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
181	SCF-PP		0	0.000	0 0	0	0	38 4	4 0	05/07/1994	994 Pal	kistan ernational	Pakistan	Western	Dera Ismail Khan, PK	Fokker F.27	TP-Large	Go Around	ХХ	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
182	ARC	_	0	0.000	0 0	0	0	53 4	4 0	23/08/1992	992 Kat	bo Air	Nigeria	Western	Sokoto, NG	BAC 1-11	Jet	Landing - Rollout	XX	No	100	Africa	Africa	Africa	Х	yes
183	RE-Landin	1		0.000				66		29/08/1992	992 Hol Ser	id-Trade Air rvices	Nigeria		KADUNA	BAC 1-11-200	Jet	LANDING				Africa	AFRICA	Nigeria	HULL LOSS	ASEDB
184	CFIT		1	1.000	155 12	2 167	0	155	12 0	28/09/1992	992 Pal	kistan ernational	Pakistan	Western	Kathmandu, NP	A300	Jet	Approach	хх	No	100	Asia	Asia	Asia-Low-Mdl Income	Y	VAS
185	SCF-PP		1	1.000	1 3	4	0	1 ;	3 0	04/10/1992	992 ELA	Al	Israel	Western	Amsterdam, NL	B747	Jet	T/O Climb to Cruise	хх	No	100	Middle East	Asia	NoAfr/MidEast	X	ves
100	DE Londin			0.000						15/10/1002	992	C Airlinea	Colombia				lat					Latin America & Caribbaan	LATIN AMERICA &	Colombia		
187	ICE	,	1	1.000	64 4	68	0	64	4 0	31/10/1992	994 Sin	mmons Airlines	USA	Western	35sm Southeast of Gary,	ATR 72	TP-Large	Initial Descent	lcing	No	100	North America	NA-Car	US-Canada	HULL LUSS	ASEDD
188	SCF-NP		0	0.000	0 0	0	0	14	2 0	20/11/1992	992 Aer	rolineas	Argentina	Western	US San Luis, AR	B737	Jet	T/O Aborted	xx	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	x	yes
180		_	0.764	0 764	12 2	15	5	10	2 0	13/12/100/	Arg	gentinas		Western	Palaigh Durham US		TD Small	Approach	vv	No	100	North Amorica	NA Car		x	yes
103			0.704	0.704			5	10	2 0	13/12/1334			004	western					~~	NO	100	North America	INA-Odi		x	yes
190	LOC-I		1	1.000	133 8	141	0	133	8 0	24/11/1992 1	Airl	lina Southern lines	China	Western	Guilin, CN	B/3/	Jet	Approach	IMC	NO	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
191	CFIT		0	0.000	0 0	0	0	0	4 0	25/11/1992	992 DA	AS Air	Uganda	Western	Kano, NG	B707	Jet	Approach	Vis	No	100	Africa	Africa	Africa	Х	yes
192	RE-Takeof		0	0.000	0 0	0	0	36	4 0	22/12/1994	994 Llo	oyd Aereo	Bolivia	Western	Guayaramerin, BO	Fokker F.27	TP-Large	T/O Aborted	хх	No	100	Latin America & Caribbean	SA/CA	SA Mercosur		
103	RE-Landin	1	0	000		0	0		1 0	26/11/1002	B01	IIVIano IroBrasil	Brazil	Western	Manaus BR	B707	lot	T/O Initial Climb	<b>vv</b>	No	100	Latin America & Caribbean	SA/CA		X	yes
193			0 183	0.000	54 2	56	106	327	13 0	21/12/1992	992 Aei	artinair Holland	Nederland	Western	Faro PT	DC-10	let	Landing - Rollout	Windshear	No	100		Furone		x x	Ves
195	RE-Takeof		0.088	0.088	1 1	2	2	21	3 0	17/01/1995 1	995 Ro	yal Nepal Airlines	Nepal	Western	Kathmandu, NP	DHC-6	TP-Small	T/O Run	XX	Yes	100	Asia	Asia	Asia-Low-Mdl Income	<u>^</u>	yes
196	MIDAIR		1	1 000	147 10	) 157	0	147	10 0	22/12/1992 1	992 Lib	wan Arab Airlines	Libva	Western	Tripoli I Y	B727	let	Approach	YY	No	100	Africa	Africa	NoAfr/MidEast	X X	Ves
100	inite/ ur (			0.000						1	993	yan a ab a annoo	Libya	TTOOLOITT		0121	001			110	100	, inou	7 11100		X	900
197	USOS									15/01/1993	Air	Afrique	Cote d'Ivoire		ABIDJAN	707-321C	Jet	LANDING				Africa	AFRICA	Cote d'Ivoire	HULL LOSS	ASEDB
198	MIDAIR		1	1.000	1 2	3	0	1	2 5	01/05/1995 1	995 Bea	arskin Airlines	Canada	Western	Sioux Lookout, CA	Metro	TP-Small	Approach	xx	No	100	North America	NA-Car	US-Canada	5 fatal in other A/C	yes
199	SCF-NP		1	1.000	9 3	12	0	9	3 0	24/05/1995 1	995 Kni	ight Air	UK	Western	Leeds, GB	EMB-110	TP-Small	T/O Climb to Cruise	Rain-Turb	No	100	Europe	Europe	EU-EFTA	x	yes
200	SCF-NP			0.000				156		31/01/1993	993	DE	Argentina		RECIFE	707-300B	Jet	LANDING				Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	Argentina	HULLLOSS	ASEDB
201	CFIT		0.274	0.274	4 1	5	13	18	3 0	09/06/1995 1	995 Qa	antas New	New Zealand	Western	Palmerston North, NZ	Dash 8	TP-Large	Approach	Rain-	No	100	Aust	Aust/asia	Hi-Income Asia-Pac	v	VOS
202	LOC-I		1	1.000	13 2	15	0	13	2 0	12/07/1995 1	995 MB	BA - PNG	Papua NG	Western	Alotau, PG	DHC-6	TP-Small	En Route	XX	No	100	Aust	Aust/asia	Pacific	x	Ves
203	ICE		0.863	0.863	79 4	83	13	92	5 0	05/03/1993 1	993 Pal	lair Macedonian	Macedonia	Western	Skopie, MK	Fokker 100	Jet	T/O Initial Climb	Snow	No	100	Europe	Europe	Euro Central	X	ves
204	RE-Landin	3	0	0.000	0 0	0	0	12	2 0	20/08/1995 1	995 Hai	iti Air Express	Haiti	Western	Jeremie, HT	ASTA Nomad	TP-Small	Landing - Rollout	xx	No	100	Latin America & Caribbean	NA-Car	CA/Carib		,
205	SCF-PP		0.336	0.336	8 1	9	13	26	3 0	21/08/1995 1	995 Atla	antic Southeast	USA	Western	40 miles SW of Atlanta,	EMB-120	TP-Small	T/O Climb to Cruise	хх	No	100	North America	NA-Car	US-Canada	x	yes
206	CFIT		0.957	0.957	17 4	21	1	18	4 0	09/09/1995 1	Airl 995 SA	TENA	Colombia	Western	US (near) La Macarena, CO	CASA 212	TP-Small	Landing - Approach	Rain - Fog		100	Latin America & Caribbean	SA/CA	SA (Northern)	X	yes
207	RE-Landin	ARC	0.642	0.642	32 2	34	0	49	4 0	15/09/1995 1	995 Ma	alaysia Airlines	Malaysia	Western	Tawau, MY	Fokker 50	TP-Large	Landing - Rollout	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	X	yes
208	SCF-PP		0.076	0.076	0 1	1	1	12	2 0	03/10/1995 1	995 Sal	bang Merauke	Indonesia	Western	Bakongan-Tapak Tuan, ID	IPTN 212	TP-Small	En Route	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
200			0.012	0.011	0 0	0	4	17	3 0	22/10/1005	Ray	iya Air Charter	Ethionia	Westorn			TP-Small	Approach	vv	No	100	Africa	Africa	Africa	х	yes
209	BIRD		0.012	0.011		0	4	17		22/10/1993				western					~~	NU	100				x	yes
210	RE-Landin	ARC	U	0.000	0 0	0	0	227	9 0	05/04/1993 1	993 TA	CA	Salvador	western	Guatemala City, GT	B/0/	Jet	Landing - Rollout	XX	NO	73	Latin America & Caribbean	SA/CA	CA/Carib	x	yes

n																							
CI te po Definition V	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculatior	Pax. Dead	Crew Dead	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal Date	Y	ear Operator	Operator Country	A/C Mn Region	f Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigl	AIR Claims Loss	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
211 LOC-I	0.011	0.011	2	0 2	15	248 16	0 06/04/19	993 19	993 China Eastern	China	Westerr	off Shemya, US	MD MD-11	Jet	En Route	XX	ХХ	1	Asia	Asia	Asia-Low-Mdl Income		
212 DE Landing Al	20 0 001	0.001	0	0 0	2	180 13	0 14/04/10	03 10	Airlines	1194	DC 10	DEW	DC 10	lot	Landing Pollout	Wind (Tail)	No	100	North Amorica	NA Car	LIS Canada	x	yes
	10.001	0.001	ľ		1		0 14/04/18	555 13	American				00-10		Landing - Rollout			100	North America		00-Canada	x	yes
213 LOC-I	0.98	0.980	137	4 14	1 3	139 5	0 18/12/19	995 19	995 Trans Service Airlift	Congo, Zr	Westerr	I Jamba, AO	L-188 Electra	TP-Large	T/O Initial Climb	XX	No	100	Africa	Africa	Africa		
214 ARC	0	0 000	0	0 0	0	115 5	0 18/04/19	993 79	993 Japan Air System	Japan	Westerr	h Hanamaki Japan	MD DC-9	Jet	Approach-Landing	Windshear	No	100	Asia	Asia	Asia-High Income	X	yes ves
		0.000	<u> </u>					19	993						r pprodon zanalig							~	J
215 RAMP	0.492	n 492	50	4 56	15	314	24/04/19	993	Air France Europe	France	Westerr	MONTPELLIER	A300-B2	Jet	TAXI	NV.	No	100	Europe	EUROPE	France	HULL LOSS	ASEDB
216 CFI1 217 LOC-I	0.462	0.462	9	4 50 2 11	4	13 2	0 26/04/19	995 F19	996 Haiti Air Express	Haiti	Westerr	Port-au-Prince, HT	ASTA Nomad	TP-Small	T/O Initial Climb	XX	Yes	100	Latin America & Caribbean	NA-Car	CA/Carib	X	yes
												,										x	yes
218 CFIT	1	1.000	125	7 13	2 0	125 7	0 19/05/19		993 SAM Colombia	Colombia	Westerr	Medellin, CO	B727	Jet TP-Small	Initial Descent	XX Rain-Fog	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	x	yes
213 0111	0.000	0.000	ľ		ľ		0 00/04/18	550 13			westen		00 220		Approach	I taili-i og		100				x	yes
000 400		0.000				70	04/00/40	19	993 Osnuda ladanasia	Indepede			DO 0 00	1-4					Ania		Indenesia		
220 ARC 221 ARC	0	0.000	0	0 0	0	11 2	0 03/05/19	993 996 19	996 Penair	USA	Westerr	DENPASAR	Metro	Jet TP-Small	LANDING Landing - Rollout	XX	No	100	Asia North America	NA-Car	Indonesia US-Canada	HULL LUSS	ASEDB
	-			-								g-,										x	yes
222 CFIT	0.956	0.956	37	4 41	2	39 4	0 01/07/19		993 Merpati Nusantara	Indonesia	Westerr	Norong, ID	Fokker F.28	Jet	Approach	Rain-Fog	No	100	Asia	Asia	Asia-Low-Mdl Income	X	yes
224 RE-Takeoff	0.495	0.495	54	1 55	16	108 5	0 23/07/19	993 19	993 China Northwest	China	Westerr	Yinchuan, CN	BAE-146	Jet	T/O Run	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	^	yes
							0.00/07//		Airlines				0.000					100				x	yes
225 CFII	0.621	0.620	64	4 68	26	106 6	0 26/07/19	993 19	993 Asiana Airlines	Korea	Western	n Mokpo, KR	B/3/ MD DC-8	Jet	Approach	Rain-Wind	No No	100	Asia North America	Asia NA-Car	Asia-Low-Mdl Income	X	yes
	0.000	0.007	Ŭ	Ů	ľ	Ů	0 10/00/10		International	00/1	mootom				, pprouon			100				x	yes
227 Eiro NI		0.000				0.0	05/00/10	19	993 Dominisono Airlinoo	Dominiaan Banublia			707 001	lot	CDUISE				Latin America & Caribbaan	LATIN AMERICA &	Dominican Bopublia		
227 FITE-INI 228 SCF-PP	1	1.000	0	4 4	0	90 4	0 20/07/19	995 996 19	296 No Air Cargo	USA	Westerr	Russian Missn	DC-6	Piston	En Route	XX	No	100	North America	NA-Car	US-Canada	X	Ves
229 USOS	0.182	0.182	8	0 8	16	44 5	0 24/07/19	996 19	996 Myanma Airways	Myanmar	Westerr	n Myeik, BU	Fokker F.27	TP-Large	Approach	Rain-	No	100	Asia	Asia	Asia-Low-Mdl Income		,
230 RE-Landing Al	RC 0.036	0.035	1	1 2	9	64 7	0 14/09/19	993 19	993 Lufthansa	Germany	Westerr	n Warsaw	A320	Jet	Landing - Rollout	Rain-Wind	No	100	Europe	Europe	EU-EFTA	X	yes
231 SCF-PP	0	0.000	0	0 0	0	152 8	0 25/10/19	993 19	993 Far Eastern Air	Taiwan	Westerr	N Kaohsiung, TW	MD-80	Jet	T/O Initial Climb	xx	No	100	Asia	Asia	Hi-Income Asia-Pac	*	yes
		0.039						19	993 China Eastern													X	yes
232 RE-Landing			2	2	13	71	26/10/19	993	Airlines	China		FUZHOU	MD-82-	Jet	LANDING				Asia	CHINA	China	HULL LOSS	ASEDB
233 RE-Landing	0	0.000	0	0 0	1	274 22	0 04/11/19	93 19	093 China Airlines	Taiwan	Westerr	Hong Kong, HK	B747	Jet	Landing - Rollout	Typhoon	No	100	Asia Middlo East	Asia	Hi-Income Asia-Pac		yes
234 Other		0.039	1	1	1	27	08/11/19	993	Saudia	Saudi Arabia		MANILA	747-100	Jet	PARKED					MIDDLE EAST	Saudi Arabia	DAMAGE	ASEDB
235 CFIT	0.122	0.122	8	4 12	7	92 10	0 13/11/19	993 19	993 China Northern	China	Westerr	u Urumqi, CN	MD-80	Jet	Approach	XX	No	100	Asia	Asia	Asia-Low-Mdl Income		
236 FUEL	0	0.000	0	0 0	0	250 13	0 15/11/19	93 19	Airlines 993 Indian Airlines	India	Westerr	Tirupati. IN	A300	Jet	En Route	Fog	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes ves
237 RI	1	1.000	10	2 12	0	10 2	2 19/11/19	996 19	996 Great Lakes Airlines	USA	Westerr	Quincy, US	BE 1900	TP-Small	Landing - Rollout	XX	No	100	North America	NA-Car	US-Canada	2 fatal in	,
		0.000						10	003													other A/C	yes
238 RE-Landing		0.000				86	20/11/19	993	COPA Airlines	Panama		PANAMA CITY	737-100	Jet	LANDING				Latin America & Caribbean	CARIBBEAN	Panama	HULL LOSS	ASEDB
239 CFIT	0.623	0.623	2	1 3	2	3 2	0 08/01/19	997 19	997 Polynesian Airlines	Polynesia	Westerr	n Apia, WS	DHC-6	TP-Small	En Route	Rain- Clouds	No	100	Aust	Aust/asia	Pacific	x	ves
240 LOC-I	1	1.000	26	3 29	0	26 3	0 09/01/19	997 19	997 Comair	USA	Westerr	25 miles S. of Detroit, US	EMB-120	TP-Small	Initial Descent	lcing	No	100	North America	NA-Car	US-Canada	x	ves
241 RE-Takeoff	0	0.000	0	0 0	0	9 2	0 10/01/19	997 19	997 Mesa/USAir Exp	USA	Westerr	Bangor, Me	BE1900	TP-Small	T/O Run	Ice - wind	No	100	North America	NA-Car	US-Canada	x	yes
242 DE Londing		0.000				6	15/00/40	19	994	Colombia		Pagata	Caravalla	lot					Lotin Amorice & Caribbase	LATIN AMERICA &	Colombia		
243 USOS	0.001	0.001	0	0 0	2	110 6	0 21/03/19	994 19	994 Aviaco	Spain	Westerr	1 Vigo, ES	DC-9	Jet	Approach	Rain-Fog0-	No	100	Europe	Europe	EU-EFTA	HOLL LUSS	ROEDB
																Wind						x	yes
244 RE-Takeoff	0.215	0.215	0	1 1	5	0 6	0 14/04/19	997 19	Airlines	Angola	Westerr	Brazzaville, CG	Fokker F.27	TP-Large	1/O Initial Climb	XX	Yes	100	Africa	Africa	Africa	x	ves
245 SCF-PP	0.283	0.283	11	4 15	0	48 5	0 19/04/19	997 19	997 Merpati Nusantara	Indonesia	Westerr	Tandjungpandan, ID	BAE (HS) ATP	TP-Large	Go Around	Wind	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes



Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd	Date	e Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
246	LOC-I		1	1.000	63	12 75	0	63	12 0	23/03/1	994 1994	Aeroflot Russian	Russia	Western	40nm East of	A310	Jet	En Route	хх	No	100	CIS	Europe	Euro East		
247	SCF-PP	-	0.6	0.600	25	5 30	0	45	5 0	0 17/07/1	997 1997	Sempati Air	Indonesia	Western	Bandung, ID	Fokker F.27	TP-Large	e T/O Climb to Cruise	xx	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
248	LOC-I	_	0.976	0.976	249	15 264	7	256	15 0	26/04/1	994 1994	China Airlines	Taiwan	Western	Nagova, JP	A300	Jet	Go Around	XX	No	100	Asia	Asia	Hi-Income Asia-Pac	x	yes ves
249	RE-Landing	ARC	0.059	0.059	0	1 1	0	14	3 0	30/07/1	997 1997	Air Littoral	France	Western	Florence, IT	ATR 42	TP-Large	e Landing - Rollout	XX	No	100	Europe	Europe	EU-EFTA		,
250	USOS	_	0	0.000	0	) 0	0	0	3 7	7 27/04/1	994 1994	TransAfrik	Sao Tome	Western	M'Banza Congo, AQ	B727	Jet	Approach	XX	No	100	Africa	Africa	Africa	x 7 Ground	yes
			-	2.005			-	-	-						, , , , , , , , , , , , , , , , , , ,										fatals	yes
251	ARC			0.905	76	4 80	9	89		01/07/1	994	Air Mauritanie	Mauritania		TIDJIKJA	F-28	Jet	LANDING				Africa	AFRICA	Mauritania	HULL LOSS	ASEDB
252	WSTRW		0.665	0.665	37	) 37	16	52	5 0	02/07/1	994 1994	US Airways	USA	Western	Charlotte, US	MD DC-9	Jet	Go Around	T-Storm-	No	100	North America	NA-Car	US-Canada	×	100
253	RE-Landing	ARC	0	0.000	0	0	0	140	8 0	20/07/1	994 1994	China Yunnan	China	Western	Kunming, CN	B737	Jet	Landing - Rollout	XX	No	100	Asia	Asia	Asia-Low-Mdl Income		yes
254	CEIT	_	1	1 000	14	2 16	0	14	2 0	10/08/1	997 1997	Formosa Airlines	Taiwan	Western	Matsu TW	DO 228	TP-Smal	II Go Around	Rain	No	100	Asia	Asia	Hi-Income Asia-Pac	x	yes
201				1.000			Ŭ			10/00/1				Webtern			in ond				100	7.614			x	yes
255	RE-Landing	ARC	0	0.000	0	0	0	152	8 0	10/08/1	994 1994	Korean Air	Korea	Western	Cheju, KR	A300	Jet	Landing - Rollout	Rain-Cloud- Wind	- No	100	Asia	Asia	Asia-Low-Mdl Income	x	ves
256	RE-Landing	ARC	0	0.000	0	0	0	79	7 0	) 18/08/1	994 1994	ADC Airlines	Nigeria	Western	Monrovia, LR	DC-9	Jet	Landing - Rollout	Rain	No	100	Africa	Africa	Africa		,
257	LOC-I	+	1	1.000	127	5 132	0	127	5 0	08/09/1	994 1994	US Airways	USA	Western	20nm NW of Pittsburgh,	B737	Jet	Approach	xx	No	100	North America	NA-Car	US-Canada	x	yes
258	SCE-PP	_	0.019	0.019			4	10	2 0	1 24/11/1	007 1007	Rollins Air	Honduras	Western	US La Ceiba, HN	ASTA Nomad	TP-Smal	I Initial Descent	IMC	No	100	Latin America & Caribbean	SA/CA	CA/Carib	x	yes
200	001-11		0.013	0.010	Ŭ		-	10		24/11/1	007 1007		Tionduras	western			II -Ollia	initial Descent			100				x	yes
259	RE-Landing	1	0	0.000	0	0	0	50	4 0	07/12/1	997 1997	KLM uk	UK	Western	St. Peter Port, GB	Fokker F.27	TP-Large	e Landing - Rollout	Rain-Wind	No	100	Europe	Europe	EU-EFTA	x	ves
260	CFIT		0.279	0.279	3	1 4	13	15	2 0	09/12/1	997 1997	Sowind Air	Canada	Western	Little Grand Rapids, CA	EMB-110	TP-Smal	II Approach	Fog	Yes	100	North America	NA-Car	US-Canada	×	
261	FUEL	_	0.178	0.178	2	3 5	34	32	7 0	0 18/09/1	994 1994	Oriental Airlines	Nigeria	Western	Tamanrasset, DZ	BAC 1-11	Jet	Approach	Fog	No	100	Africa	Africa	Africa	x	yes
262	SCE-NP			0.000				2		09/10/1	1994 994	LAB	Bolivia		SAO PAULO	707-300	Jet					Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	Bolivia	HULLIOSS	ASEDB
				1.119							1994	Iran Asseman										Middle East				
263 264	UNK		0	0.000	59	7 66	0	59 132	5 2	12/10/1	994 994 1994	Airlines	Iran USA	Western	NATANZ STL	F-28-1000 MD-82	Jet Jet	T/O Run	XX	No	100	North America	MIDDLE EAST NA-Car	Iran US-Canada	HULL LOSS	ASEDB
				0.001							1004	Morpoti Nucoptoro													fatal	yes
265	RE-Landing	,		0.001			2	78		30/11/1	994	Airlines	Indonesia		SEMARANG	F-28-4000	Jet	LANDING				Asia	ASIA (EX CHINA)	Indonesia	HULL LOSS	ASEDB
266	CFIT		0.623	0.623	0	3 3	2	0	5 0	) 19/12/1	994 1994	Nigeria Airways	Nigeria	Western	170km. NE of Kano, NG	B707	Jet	Initial Descent	XX	No	100	Africa	Africa	Africa	х	yes
267	CFIT		1	1.000	0	5 5	0	0	5 0	) 21/12/1	994 1994	Air Algerie Bropair	Algeria	Western	(near) Coventry, GB	B737 Metro	Jet	Landing - Approach	XX	XX	100	Africa	Africa	NoAfr/MidEast	x	yes
200	501-11		1	1.000			Ŭ	J	2	5 10/00/1	330 1330	Торан	Canada	Western	Montreal	Metro	II -Silla		^^	NO	100	North America	INA-Cal	00-Carlada	x	yes
269	MIDAIR		1	1.000	12	2 14	0	12	2 1	1 30/07/1	998 1998	Proteus Airlines	France	Western	Vannes, FR	BE 1900	TP-Smal	II En Route	XX	No	100	Europe	Europe	EU-EFTA	1 fatal in other A/C	ves
270	CFIT		0.764	0.764	52	5 57	19	69	7 0	) 29/12/1	994 1994	THY - Turkish	Turkey	Western	Van, TR	B737	Jet	Approach	Snow	No	100	Europe	Europe	NoAfr/MidEast	v	Vec
				0.000							1995	Ainines												Congo, The	^	yes
074	DE Londin									00/04/4	005		0			707 000	1-4					Africa		Democratic Republic		
271	USOS	,	0.061	0.061	1 (	) 1	6	20	2 0	28/09/1	995 998 1998	TACV Cabo Verde	Congo, Capr Verde	Western	Praia, CV	DHC-6	TP-Smal	Approach	T-Storm-	No	100	Africa	Africa	Africa	HULL LUSS	ASEDD
273	CEIT	_	0.982	0.982	46	5 51	1	47	5 0	11/01/1	005 1005	Inter (Colombia)	Colombia	Western	40km South of Cartagena		let	Initial Descent	Wind	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	x	yes
210	0111		0.302	0.002			'			, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	000 1000		Colombia	western	CO	50-5	001	initial Descent	Cioud		100				x	yes
274	RE-Landing			0.000				52		16/01/1	995	Sempati Air Transport	Indonesia		YOGYAKARTA	737-200	Jet	LANDING				Asia	ASIA (EX CHINA)	Indonesia	HULL LOSS	ASEDB
275	PE Londing			0.000						31/01/4	1995	Angola Air Charter	Angola		Huambo Airport	727 100	let					Africa				
215				0.001						51/01/1	1995					121-100	Jei						LATIN AMERICA &	Angola	LUSS	HOLDD
276	SCF-NP		1	1 000	0	2 2	2	121	2 0	01/02/1	995	VASP Airlines	Brazil	Western	SAO PAULO St. Peter Port. GB	737-200 Fokker F 27	Jet	LANDING	XX	No	100	Latin America & Caribbean	CARIBBEAN	Brazil EU-EETA	HULL LOSS	ASEDB
					Ľ	2	ľ				1000														x	yes
278	RE-Landing	ARC	0.133	0.133	3	1 4	2	27	4 0	25/02/1	999 1999	Minerva Italy	Italy	Western	Genoa, IT	Fairchild/Dornier 328	TP-Smal	I Landing - Rollout	Wind	No	100	Europe	Europe	EU-EFTA	x	ves
279	LOC-I		1	1.000	50	10 60	0	50	10 0	0 31/03/1	995 1995	TAROM	Romania	Western	Bucharest, RO	A310	Jet	T/O Climb to Cruise	XX	No	100	Europe	Europe	Euro East	x	yes
280	CFIT		1	1.000	3	2 5	0	3	2 0	0 08/04/1	999 1999	Aerotaca	Colombia	Western	Malaga, CO	DHC-6	TP-Smal	ll Approach	Clouds- Wind	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	x	yes

Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column Serverity (Calculatio	Pax. Dead	Crew Dead	Tot Fatal (onBd)	Ser-Ious (Unba)	Pax OnBd Crew OnBd	Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigl - C/0	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
281	RE-Landing	ARC	0.019	0.019	0	0 0	) 1	0	) 3	6 28	8/04/1995	1995	Millon Air	USA	Western	Guatemala City, GT	MD DC-8	Jet	Landing - Rollout	Rain	No	100	North America	NA-Car	US-Canada	6 Ground fatal	ves
282	CFIT		0.583	0.583	6	1 7	0	1	11 1	30 0	8/05/1999	7999	Vanair	Vanuata	Western	Port Vila, NH	DHC-6	TP-Small	Approach	Rain	No	100	Aust	Aust/asia	Pacific	x	ves
283	RE-Landing			0.000				3	35	3	1/05/1995	1995	Air Niugini	Panua New Guinea		MADANG	F-28-	Jet					Aust	Oceania	Panua New Guinea		
284	CFIT		1	1.000	4	4 8	3 0	4	4	0 02	2/07/1999	1999	Myanma Airways	Myanmar	Western	Sittwe, BU	Fokker F.27	TP-Large	Approach	Cloud-Fog	No	100	Asia	Asia	Asia-Low-Mdl Income		HOLDD
285	SCF-PP		0.001	0 001	0	0 0	) 1	5	5 5	0 08	8/06/1995	1995	Valuiet	USA	Western	Atlanta US	MD DC-9	Jet	T/O Aborted	XX	No	100	North America	NA-Car	US-Canada	X X	yes
286	CFIT		1	1.000	15	2 1	7 0	1	15 2	0 24	4/07/1999	1999	Air Fiji	Fiji	Western	Suva, FJ	EMB-110	TP-Small	En Route	XX	Yes	100	Aust	Aust/asia	Pacific	~	1,000
287	CFIT		0.264	0.264	0	1 1	1	2	2 2	0 12	2/08/1999	1999	Regionnair	Canada	Western	Sept-Iles, CA	BE-1900	TP-Small	Landing - Approach	Fog	xx	100	North America	NA-Car	US-Canada	X	yes
				0.000			-					1995										-				Х	yes
288	USOS		1	1 000	50	7 0	-	8	32	26	6/07/1995	1005	ADC Airlines	Nigeria	14/	MONROVIA	DC-9-	Jet	LANDING	TOL	NL.	100	Africa	AFRICA	Nigeria	HULL LOSS	ASEDB
289	CFII		1	0.000	58	1 6	5 0	5	08 /	0 05	9/08/1995	1995	Aviateca	Mexico	vvestern	San Salvador, Sv	8/3/	Jet	Approach	1-Storm	NO	100	Latin America & Caribbean	SA/CA	CA/Carib	X	yes
290	RE-Landing									17	7/08/1995		Air Afrique	Cote d'Ivoire		N'DJAMENA	707-320C	Jet	LANDING				Africa	EUROPE	Cote d'Ivoire	HULL LOSS	ASEDB
291	CFIT		1	1.000	10	5 1	5 0	1	10 5	0 05	5/09/1999	1999	Necon Air	Nepal	Western	Ramkot, NP	BAE (HS) 748	TP-Large	Initial Descent	Clouds	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
292	RE-Landing	ARC	0.067	0.067	9	09	) 4	1	129 8	0 13	3/11/1995	1995	Nigeria Airways	Nigeria	Western	Kaduna, NG	B737	Jet	Landing - Rollout	ХХ	No	100	Africa	Africa	Africa	x	ves
293	CFIT		0.333	0.333	0	2 2	2 0	0	) 6	0 30	0/11/1995	7995	Azerbaijan Airlines /AZAL Avia	Azerbaijan	Western	Baku, AZ	B707	Jet	Go Around	хх	No	100	CIS	Europe	Europe - E/.SE	x	ves
294	RE-Landing	ARC	0	0.000	0	0 0	) 0	1	102 6	0 02	2/12/1995	1995	Indian Airlines	India	Western	Delhi, IN	B737	Jet	Landing - Rollout	хх	No	100	Asia	Asia	Asia-Low-Mdl Income	y	Ves
205				1.005	60	4 7	22 6	7	72	0	2/12/1005	1995	Comercen Airlinee	Comoroon			727 200	lot	CLIMP				Africa	AERICA	Comercen		
296	CFIT		1	1.000	21	3 2	2 0	2	21 3	0 12	2/11/1999	1999	Si Fly	Italy	Western	Pristina, YU	ATR 42	TP-Large	Landing - Approach	Clouds	No	100	Europe	Europe	EU-EFTA	HOLL LOSS	AGEDB
297	CFIT		1	1.000	31	4 3	5 0	3	31 4	0 11	1/12/1999	1999	SATA	Portugal	Western	Azores	ATP	TP-Large	Descent	T-Storm	No	100	Europe	Europe	EU-EFTA	X	yes
298	CEIT	$\left  \right $	0 977	0.977	152	8 1	60 4	1	156 8	0 20	0/12/1995	1005	American Airlines	1154	Western	Cali Co (Buga)	B757	let	Initial Descent	vy.	No	100	North America	NA-Car	US-Canada	X	yes
299	LOC-G		0.377	0.000	0			4	177 15	0 20	0/12/1995	1995	Tower Air	USA	Western	New York, US	B747	Jet	T/O Aborted	XX	No	100	North America	NA-Car	US-Canada	x x	yes
300	CFIT		1	1.000	7	3 1	0 0	7	7 3	0 25	5/12/1999	1999	Skyline Airways	Nepal	Western	Bhojpur, NP	DHC-6	TP-Small	T/O Climb to Cruise	Clouds	No	100	Asia	Asia	Asia-Low-Mdl Income		1
301	LOC-I		1	1.000	7	3 1	0 0	7	7 3	0 10	0/01/2000	2000	Crossair	Switzerland	Western	Zurich, CH	Saab 340	TP-Small	T/O Climb to Cruise	Cloud	No	100	Europe	Europe	EU-EFTA	x	yes
				0.000								1995	TAROM - Romanian													X	yes
302	ARC			0.000		$\vdash$		7	/5	30	0/12/1995	1996	Air Transport	Romania		ISTANBUL	BAC 1-11	Jet	LANDING				Europe	EUROPE	Romania	HULL LOSS	ASEDB
303	RE-Landing		1	1.000	170	12 4	80 0	4	76 12	28	8/01/1996	1000	AFFRETAIR	Zimbabwe	Mostor	HARARE	DC-8-F55	Jet	LANDING	VV	No	100	Africa	AFRICA	Zimbabwe	HULL LOSS	ASEDB
504	100-1		1	0.000	1/0	13 1	09 0	1	10 13	0 00	0/02/1990	1996	Dirgenali	TUREY	vvestern	Fuerto Flata, DU	5131	Jei		~~	UNU	100	North America		NUAII/IVIIUEASL	^	yes
305	ARC							8	32	19	9/02/1996		Continental Airlines	USA		Houston	DC-9-	Jet	LANDING					NA-Car	USA	HULL LOSS	ASEDB
306	CFIT		1	1.000	117	6 1	23 0	1	17 6	0 29	9/02/1996	1996	Faucett	Peru	Western	Arequipa, PE	B737	Jet	Approach	Cloud	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	Х	yes
307	SCF-PP		0	0.000	0	0 0	0	3	5 3	0 17	7/03/2000	2000	Skypower Express Airways		western	Kaduna, NG	EMB-110	TP-Small	Approach	XX	NO	100	Africa	ATTICA	Africa	х	yes
308	RE-lakeoff		0.001	0.001	0	0 0	10 0	7	105 5	0 01	1/05/1996	1996	Fly Lineas Aereas	Brazil	Western	Quito, EC	B/27	Jet	T/O Aborted	Rain	Yes	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
000				0.000	100						1/05/1990	1990		Maulas	Western	US				^^	No	100			CA/Carib	x	yes
310	CFIT		1	1.000	17	2 1	9 0	4	+2 4	0 12	4/05/1996 8/07/2000	2000	Allegro Alf	Mexico	Western	Villahermosa MX	BAE 31	TP-Small	En Route	IMC	NO	100	Latin America & Caribbean	SA/CA	CA/Carib	X	yes
310	DE Londing	ARC	0.013	0.012	0				260 15	0 1	3/06/1006	1000	Caruda Indonasia	Indonosia	Wostor					NV V	No	100		Asia	Asia Low Md Income	x	yes
512		ARC	0.015	0.013	3	0 3	, 12		15		0,00,1990	1990	Garuua muonesia	Indunesia	western	T UKUUKA, JF	00-10	Jei	TO ADDITED	~~	NU	100	noid	Asia	Asid-LOW-IVIUI INCOME	x	yes
313	WSTRW		0	0.000	0	0 0	) 0	0	) 4	0 30	0/06/1996	1996	DAS Air	Uganda	Western	Bamako, ML	B707	Jet	Landing - Rollout	Rain-Wind	No	100	Africa	Africa	Africa	х	yes
314	SCF-PP		0.015	0.015	2	0 2	2 2	1	37 5	0 00	6/07/1996	1996	Delta	USA	Western	Pensacola	MD-88	Jet	T/O Run	XX	No	100	North America	NA-Car	US-Canada	Х	yes
315	FIKE-NI		1	1.000	212	18 2	30 0	2	12 18	0 17	7107/1996	1996	Trans world Alfilhes	USA	vvestern	Island), US	D/4/	Jet	TO Climb to Cruise	XX	INO	100	North America	INA-Car	US-Canada	х	yes



Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation	ા Pax. Dead	Crew Dead	Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	e Ye	ear Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	, Weigh - C/G	AIR Claims Loss	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
316	CFIT		1	1.000	22	3 25	0	22	3 0	27/07/20	000 20	00 Royal Nepal Airlines	Nepal	Western	Dhangarhi, NP	DHC-6	TP-Sma	all Initial Descent	Rain-	No	100	Asia	Asia	Asia-Low-Mdl Income	Y	Ves
317	RE-Landing		0	0.000	0	0 0	0	120	8 0	21/08/19	996 19	96 Egyptair	Eavot	Western	Istanbul, TR	B707	Jet	Landing - Rollout	Rain	No	100	Africa	Africa	NoAfr/MidEast	x	ves
318	FIRE-NI	<u> </u>	0	0.000	0	0 0	0	0	5 0	0 05/09/19	996 19	96 FedEx	USA	Western	Newburgh, NY	DC-10	Jet	En Route	XX	No	100	North America	NA-Car	US-Canada	X	ves
319	CFIT		1	1.000	61	9 70	0	61	9 0	02/10/19	996 19	96 Aero Peru	Peru	Western	off Ancon, PE	B757	Jet	T/O Climb to Cruise	XX	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	х	yes
320	LOC-I		0	0.000	0	0 0	0	15	2 0	01/11/20	000 20	00 West Coast Air	Canada	Western	Vancouver, CA	DHC-6	TP-Sma	all T/O Initial Climb	XX	No	100	North America	NA-Car	US-Canada	x	yes
321	ARC			0.000						10/10/19	996	Occidental Airlines	Belaium		DJERBA	707-320C	Jet	LANDING				Europe	EUROPE	Belaium	HULL LOSS	ASEDB
322	LOC-I		1	1.000	0	4 4	0	0	4 #	# 22/10/19	996 19	96 Millon Air	USA	Western	Manta, EC	B707	Jet	T/O Initial Climb	ХХ	No	100	North America	NA-Car	US-Canada	30 Ground fatal	yes
303	WCTDW			0.000		2 2	6			23/10/10	19	196 I ADE	Argonting			707 3720	lot					Latin America & Caribbean	LATIN AMERICA &	Argontina		ASEDR
324	SCE-PP	-	1	1 000	89	6 95	0	89	6 0	31/10/19	996 79	196 TAM Brasil	Brazil	Western	Sao Paulo BR	Fokker 100	Jet	T/O Initial Climb	XX	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Y Y	Ves
325	LOC-I		1	1.000	134	9 14	3 0	134	9 0	07/11/19	996 19	96 ADC Airlines	Nigeria	Western	40km, ENE of Lagos, NG	B727	Jet	Initial Descent	XX	No	100	Africa	Africa	Africa	x	ves
326	MIDAIR		1	1.000	289	23 31	2 0	289	23 #	# 12/11/19	996 19	96 Saudi Arabian Airlines/Chimkentavi	Saudi Arabia		50 miles W. of Delhi, IN	IL76/B747	Jet					Middle East	Asia	NoAfr/MidEast	37 fatal in	vec
327	LOC-I		1	<b>1</b> .000	17	2 19	0	17	2 0	24/03/20	001 20	01 Air Caraibes	Guadeloupe	Western	St.Barthelemy, GP	DHC-6	TP-Sma	all Landing - Approach	xx	No	100	Latin America & Caribbean	NA-Car	CA/Carib	x	yes
328	SCF-PP		0.088	0.088	3	1 4	2	44	3 0	29/08/20	001 20	01 Binter Mediterraneo	Spain	Western	Malaga, ES	CASA CN-235	TP-Sma	all Landing - Approach	ХХ	No	100	Europe	Europe	EU-EFTA	v	VAS
329	CFIT		0	0.000	0	0 0	0	0	4 0	) 17/12/19	996 79	96 MK Airlines	Ghana	Western	Port Harcourt, NG	DC-8	Jet	Approach	XX	No	100	Africa	Africa	Africa	x	yes
				0.000							19	97 First International														
330	SCF-NP	_	0.004	0.004		_	1	- 40		17/01/19	997	Airways	Belgium	10/	KANANGA	707-320	Jet	LANDING	Mar d Con		400	Europe	EUROPE	Belgium	HULL LOSS	ASEDB
331	ARC	1	0.024	0.024	0	1 1	4	40	0	14/02/1	997 19	197 VARIG	Brazii	vvestern	Carajas, BR	8/3/	Jet	Landing - Rollout	rain	XX	100	Latin America & Caribbean	SA/CA	SA Mercosur	x	ves
332	RE-Takeoff		0.002	0.002	0	0 0	4	107	8 0	) 10/03/19	997 19	97 Gulf Air	Qatar (Multi-Nati)	Western	Abu Dhabi, AE	A320	Jet	T/O Aborted	Wind	No	100	Middle East	Asia	NoAfr/MidEast	х	yes
333	RE-Landing			0.000				97		12/04/19	키9 997	97 Ghana Airways	Ghana		ABIDJAN	DC-9	Jet	LANDING				Africa	AFRICA	Ghana	HULL LOSS	ASEDB
334	ARC		0.000	0.004	0	0 0	1	10	3 0	11/30/01	20	01 European Executive	Sweden	Western	Skien NO	Jetstream 31	TP-Sma	all Landing	xx	No	100	Europe	Europe	EU-EFTA	x	Ves
335	ARC		0.473	0.473	33	2 35	0	65	9 0	08/05/19	997 19	97 China Southern	China	Western	Shenzhen, CN	B737	Jet	Landing - Rollout	Rain-T-	No	100	Asia	Asia	Asia-Low-Mdl Income	~	,
				0.000							19	97 TAROM - Romanian							Storm						X	yes
336	RE-Landing		0.000	0.000				20		07/06/19	997	Air Transport	Romania		STOCKHOLM	BAC 1-11	Jet	LANDING				Europe	EUROPE	Romania	HULL LOSS	ASEDB
337	LOC-I		0.000	0.000	0	0 0	0	20	4 0	02/17/02	2	Services	Congo, Zr	Western	(near) Kananga, ZR	CL-44	TP-Larg	e En Route	xx	No	100	Allica	Allica	Allica	x	yes
338	ARC		0	0.000	0	0 0	0	49	6 0	29/07/19	997 19	97 ADC	Nigeria		Calabar	BAC-1-11	Jet	Landing - Approach	ХХ	No	100	Africa	Africa	Africa	Х	yes
339	ARC		0	0.000	0	0 0	0	0	4 0	31/07/19	997 19	97  FedEx	USA	Western	Newark, US	MD-11	Jet	Landing - Rollout	XX	No	100	North America	NA-Car	US-Canada	х	yes
340	RE-Landing		0.000	0.000				10	E .	04/40/04	20		Co Africo	Master	Dilanaahara 74	110 740	TD	anding Dellaut		No	100	Africa	Africa	Atrica		1400
3/11	Other			0.007	1	0 0	0	43	5 0	02/08/10	∠ 007 10	All Qual lus Aviation		western	I IMA	757-200	Let		XX	INO	100	North America	NA-Car		NONE	ASEDB
341	RE-Takeoff		0	0.007	0	0 0	0	118	8 0	02/08/19	997 19 997 19	97 Air Afrique	Cote d Ivorie (Multi-	Western	Douala, CM	B737	Jet	T/O Aborted	ХХ	No	100	Africa	Africa	Africa	NUNE	ASEDB
343	CFIT		0.907	0.907	215	14 22	9 25	237	17 0	06/08/19	997 19	97 Korean Air	Korea	Western	Agana, GU	B747	Jet	Approach	Rain-T-	No	100	Asia	Asia	Asia-Low-Mdl Income	x	ves
344	LOC-I		1	1.000	0	4 4	0	0	4 0	07/08/19	997 19	97 Fine Air	USA	Western	Miami, US	MD DC-8	Jet	T/O Initial Climb	XX	Yes	100	North America	NA-Car	US-Canada	x	yes
345	CEIT		1.000	1.000		2 3	0	0	3 0	06/01/01	2 20	02 AirQuarius Aviation	So Africa	Western	(near) George 74	HS 748	TP-L are	e Go Around	Winds	No	100	Africa	Africa	Africa	x	Ves
346	RE-Landing	ARC	0	0.000	0	0 0	0	26	9 0	) 12/08/19	997 19	97 Olympic Airways	Greece	Western	Thessaloniki, GR	B727	Jet	Landing - Rollout	Rain	No	100	Europe	Europe	EU-EFTA	<u>л</u>	100
347	ARC			0.000						15/08/19	997	97 Angola Air Charter	Angola			727-100	Jet					Africa	AFRICA	Angola		ASEDB
• 11				0.000							19	97											LATIN AMERICA &			
348	USOS		0.000	0.000				42		17/08/19	997	SAETA S.A.	Ecuador		SAN CRISTOBAL	727-200	Jet	LANDING				Latin America & Caribbean	CARIBBEAN Europe	Ecuador EU-EFTA	HULL LOSS	ASEDB
349	ADRM		1 000	1 000	0	0 0	0	20	4 0	07/10/02	2	Swiss	Suiss	Western	Werneuchen, DE	Saab 2000	TP-Larg	ge Landing - Rollout	Rain, ceiling	g No	100	Asia	Asia	Asia-Low-MdL Income	Emergency	yes
350	CFIT		1.000	1.000	2	2 4	0	0	4 0	07/17/02	2	Skyline Airways	Nepal	Western	(near) Surkhet, NP	DHC-6	TP-Sma	all Descent	IMC	No	100	/ loid	7.014		x	yes

Accident ID	Category Definition	Previously ARC	Severity Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Crew Dead	lot Fatal (onbd) Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal	ite	Year Operator	Operator Country	A/C Mn Region	f Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigh - C/G	AIR Claims Loss	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
351	SCF-PP	0		°0.000	0	0 0	0	79 6	0 06/09/	1997	1997 Saudi Arabian Airlines	Saudi Arabia	Western	Nejran, SA	B737	Jet	T/O Aborted	хх	No	100	Middle East	Asia	NoAfr/MidEast	x	ves
252	CEIT	٩.(	000	1.000	15	2 10		15 2	0 00/22	/0.2	2002 Changei La Air	Nerel	Western			TD Small	Approach		No	100	Asia	Asia	Asia-Low-Mdl Income	~	100
352	CFIT	1		1.000	222	12 23	34 0	222 12	0 26/09/	1997	1997 Garuda Indonesia	Indonesia	Western	Medan, ID	A300	Jet	Approach	Smoke	No	100	Asia	Asia	Asia-Low-Mdl Income	x X	yes
		0.1	767	0.782							2002				<b>END</b> (00 D			Heavy Rain,	,		Latin America & Caribbean	SA/CA	SA Mercosur		ĺ.
354	RE-Landing		000	0.000	20	3 23	8 8	28 2	0 08/30/	/02	RICO Linhas Aerea	as Brazil	Western	(near) Rio Branco, BR	EMB-120 Brasilia	TP-Small	Approach	Wind	No	100	Asia	Asia	Asia-Low-MdLIncome	X	yes
	· · · · · · · · · · · · · · · · ·				0	0 0	0	45 4	0 09/05/	/02	Asian Spirit	Philippines	Western	Manila, PH	DHC 7	TP-Large	Landing - Rollout	хх	No	100				SCF NPP	yes
356	LOC-I	1.0	000	1.000	0	2 2	0	0 2	0 09/14/	/02	Total Linhas Aerea	s Brazil	Western	(near) Paranapanema, BR	ATR 42	TP-Large	En Route	Heavy Rain	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	x	ves
0.57				0.000					0.1/10	4007	1997 Ryan International				707 540		TA)/	,			North America				
357	RE-Landing	ARC 0.0	000	0.000			1		01/10/	1997	Airlines	USA		DENVER	727-510	Jet	IAXI			_	Europe	NA-Car Europe	USA EU-EFTA	HULL LOSS	ASEDB
	· · · · · · · · · · · · · · · · · · ·				0	0 0	0	36 4	0 11/02/	02	EuroCeltic Airways	UK	Western	Sligo, IE	Fokker F.27	TP-Large	Landing - Rollout	Tailwind	No	100				х	yes
359	100-1	°0.9	909	0.914	18	2 20	2	19 3	0 11/06/	02	2002 Luxair - Luxembou Airlines	rg Luxenmbourg	Western	Niederanven IU	Fokker 50	TP-Large	Approach	Icina?	No	100	Europe	Furope	FU-FFTA	x	ves
		0.9	559	0.566						-	2002 Laoag Internationa										Asia	Asia	Asia-Low-Mdl Income		,
360	LOC-I		000	1000	17	2 19	9 4	29 5	0 11/11/	02	Airways	Philippines	Western	Manila, PH	Fokker F.27	TP-Large	T/O Initial Climb	XX	No	100	Latin America & Caribbean	SA/CA	CA/Carib	Fuel Man	yes
361	USOS	0.0	000	0.000	0	0 0	0	6 4	0 12/06/	/02	Aerotaxi	Cuba	Western	(near) Havana, CU	EMB-110	TP-Small	Approach	Heavy Rain	No	100		0/10/1	o, vouno	х	yes
362	I OC-I	<b>P</b> 1.0	000	1.000	0	2 2	0	0 2	0 12/21/	/02	2002 TransAsia Airways	Taiwan	Western	15nm SW of Makung TW	ATR 72	TP-Large	Descent	Icina	No	100	Asia	Asia	Hi-Income Asia-Pac	x	ves
002	2001	1.0	000	1.000					0 12/2 //		2003							lonig			North America	NA-Car	US-Canada	SCF Trim	,
363	LOC-I			P 072	19	2 21	0	19 2	0 01/08/	/03	Air Midwest	USA	Western	Charlotte, US	BE-1900	TP-Small	T/O Initial Climb	ХХ	Yes	100		LATIN AMERICA &		Tab	yes
364	LOC-I			1.072	69	5 74		69	10/10/	1997	del Sur S.A.	Argentina		NUEVO BERLIN	DC-9-32	Jet	CRUISE				Latin America & Caribbean	CARIBBEAN	Argentina	HULL LOSS	ASEDB
365	APC			0.000				67	15/10	/1007	1997	Mexico				let					Latin America & Caribbean	LATIN AMERICA &	Mexico		
366	RE-Landing	·0.0	000	0.000				07	13/10/	1997	2003	MEXICO		MEXICO CITT	00-9-92	Jei					Europe	Europe	EU-EFTA	HOLL LOSS	AGEDD
				0.000	0	0 0	0	14 5	0 01/17/	/03	Air Nostrum	Spain	Western	Melilla, ES	Fokker 50	TP-Large	Landing - Rollout	хх	No	100			Congo Tho	х	yes
				0.000						[	1997												Democratic Republic		
367	RE-Landing		010	0.010	0	0 0		20 2	01/11/	1997	Congo Airlines	Congo	Meeter	KINSHASA	707-323C	Jet	LANDING	Fag	No	100	Africa	AFRICA	of the	HULL LOSS	ASEDB
300	ARG	0.0	000	0.000			9	39 3	0 10/12/	1997	2003	Callaua	western	Fredericion, CA		Jei	Go Alound	FUY		100	Africa	Africa	Africa	x	yes
369	LOC-I			0.000	0	0 0	0	0 5	0 03/15/	/03	748 Air Services	Kenya	Western	Rumbek, SD	HS 748	TP-Large	T/O Initial Climb	хх	No	100				SCF PP	yes
370	CFIT			0.000				84	22/12/	1997	Airlines	Bangladesh		SYLHET	F-28-	Jet	FINAL APPROACH				Asia	ASIA (EX CHINA)	Bangladesh	HULL LOSS	ASEDB
074	1.001	0.2	278	0.310		4 5	10	45 0	0 00/07	100	2003	la den este	14/		DUO 0		T/O latitial Oliver		NIE	400	Asia	Asia	Asia-Low-Mdl Income		
3/1	LUC-I	0.0	000	0.000	4	1 5	10	15 3	0 03/27/	103	2003	Indonesia	vvestern	6nm SW of Prince Albert,		TP-Smail		**		100	North America	NA-Car	US-Canada	X	yes
372	SCF-NP		000	0.000	0	0 0	0	4 2	0 04/23/	/03	Transwest Air	Canada	Western	CA	BE-99	TP-Small			No	100	A.6.:			х	yes
373	LOC-G	0.0	000	0.000	0	0 0	0	13 2	0 04/29/	/03	Avirex Gabon	Gabon	Western	Kinshasa, ZR	BE-1900	TP-Small			No	100	Ainca	Africa	Africa	x	yes
274	100.0	0.0	000	0.000		0	0	41 4	0 06/10	/02	2003 Mid Airlings	Sudan	Wester		Fokkor 50	TD			No	100	Africa	Africa	Africa	X	1/00
574	100-0			0.006	0	0 0	0	41 4	0 06/16/	03	1997	Suuan	western	Audiyale, SD	FUKKEI DU	TP-Large			INO	100	North America			MINOR	yes
375	TURB			0.000	1	1	18	355	28/12/	1997	United Airlines	USA		HONOLULU	747-100	Jet	CRUISE					NA-Car	USA	DAMAGE	ASEDB
376	CFIT			0.000				104	05/01/	1998	Iran Air	Iran		ISFAHAN	F-100	Jet	LANDING				muule East	MIDDLE EAST	Iran	HULL LOSS	ASEDB
077	105	1.(	000	1.000					0 40/00	100	2003 Air Freight New			(7.D. ).17	0 500	<b>TD</b> 1				400	Aust	Aust/asia	Hi-Income Asia-Pac		
378	RE-Landing	0.0	000	0.000	0	2 2	0	0 2	0 10/03/	103	2003	New Zealand	vvestern		Convair 580	TP-Large	Descent	ICING	INO	100	Latin America & Caribbean	SA/CA	SA Mercosur	x	yes
	Ĵ		000	1 000	0	0 0	0	20 3	0 10/20/	/03	TAVAJ	Brazil	Western	Tarauaca, BR	Fokker F.27	TP-Large	Landing - Rollout	ХХ	No	100	Latin America A.O., "L			х	yes
379	LOC-I	1.0	000	1.000	3	2 5	0	3 2	0 10/26/	/03	SA	Argentina	Western	(near) Buenos Aires, AR	Fairchild FH-227	TP-Large	T/O Initial Climb	xx	No	100	Laun America & Caribbean	SAVCA	SA Mercosur	x	yes
000	DE La l'			0.000						4000	1998 Turkish Airlines	Turkey		CAMOUN	D 1400	1-4					E	FUDODE	Turkey		
380	RE-Landing			1.051				68	11/01/	1998	1998	Тигкеу		SAMSUN	RJ100	Jet	LANDING				Europe	EUROPE	Тигкеу	HULL LOSS	ASEDB
381	CFIT			0.000	99	5 10	)4	99	02/02/	1998	Cebu Pacific Air	Philippines		ENRT TAC-CGY	DC-9	Jet	DESCENT			100	Asia	ASIA (EX CHINA)	Philippines	HULL LOSS	ASEDB
382	LOC-I	0		1.000	182	0 0	0	115 6	6 16/02/	1998	1998 American Airlines 1998 China Airlines	Taiwan	Western	Taipei, TW	B727 A300	Jet	Approach Go Around	xx Rain-Fog	No No	100	North America Asia	Asia	US-Canada Hi-Income Asia-Pac	x 6 Ground	yes
																								fatal	yes
384	LOC-I CEIT	1		1.000	0	6 6 10 45	0	0 6	0 10/03/	1998	1998 Air Memphis	Egypt	Western	Mombasa, KE	B707	Jet	T/O Initial Climb	xx Rain-	Yes	100	Africa	Africa	NoAfr/MidEast	х	yes
000	0.11	'				.0 73	ľ		0 10/00/	.000		, ugnamotan	1103tell		5.21			Clouds		100				х	yes



Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
386	RE-Landing	ARC	0.001	0.001	0 0	0	2	128	8 3	22/03/1998	1998	Philippine Airlines	Philippines	Western	Bacolod, PH	A320	Jet	Landing - Rollout	хх	No	100	Asia	Asia	Asia-Low-Mdl Income	3 Ground	
207	CEIT		0.200	0.223	0 1	1	2	2	2 0	01/28/04	2004	Tassili Airlinas	Algoria	Western	(near) Chardaia DZ	RE 1000	TD Smal			No	100	Africa	Africa	NoAfr/MidEast		yes
307	GITI		0.935	0.939		<u> </u>	2		2 0	01/20/04	2004	Tassiii Airiires	Aigena	Western		BE-1900				NO	100	Middle East	Asia	NoAfr/MidEast	^	yes
388	LOC-I			0.000	37 6	43	3	40	6 0	02/10/04	1998	Kish Air	Iran	Western	(near) Sharjah, AE	Fokker 50	TP-Large	9		No	100	CIS			X	yes
389	RE-Landing		4	3.000	42 40	50		80	12 0	12/04/1998	3000	Orient Eagle Airways	Kazakhstan	M/a aka wa	ALMATY	737-200	Jet		Claud		100	Latin America & Caribbaan	CIS	Kazakhstan	HULL LOSS	ASEDB
390			0.000	0.000	43 10	0 55			43 0	20/04/1996	2004	Central African		western	(near) bogola, CO	B/2/	Jel		Cioua	**	100	Africa	Africa	Africa	x	yes
391	ARC		0.000	0.000	0 0	0	0	0	4 0	04/03/04	2004	Cargo	Cent African rep	Western	Shabunda, ZR	Convair 580	TP-Large	9		No	100	North America	NA-Car	US-Canada	х	yes
392	FIRE-NI			0.005	0 0	0	0	0	3 0	04/27/04	<b>1000</b>	Mountain Air Cargo	USA	Western	(near) Melo, UY	Fokker F.27	TP-Large	9		No	100	North Amorica			x	yes
393	CFIT			0.935	69 6	75	13	81		05/05/1998	1998	Petroleum Corp	USA		(Near) Andoas	737-200	Jet	LANDING				north America	NA-Car	USA	HULL LOSS	ASEDB
394	ARC		0.000	0.000	0 0	0	0	0	2 0	05/09/04	2004	Executive Airlines	USA	Western	San Juan, PR	ATR 72	TP-Large	e		No	100	North America	NA-Car	US-Canada	x	yes
395	UNK		0.524	0.524	30 3	33	0	30	33 0	05/14/04	2004	RICO Linhas Aereas	Brazil	Western	(near) Manaus, BR	EMB-120	TP-Smal			No	100	Latin America & Caribbean	SA/CA	SA Mercosur	x	yes
206			0.000	0.010	0 0	0	2	14	2 0	05/17/04	2004	Trans Maldivian	Maldivas	Western			TD Smal			No	100	Asia	Asia	Asia-Low-Mdl Income	v	
390	100-1		0.633	0.654		0	3	14	3 0	05/17/04	2004	Allways	Maldives	vvestern			TP-SITIAL			INO	100	Africa			X	yes
397	LOC-I		0.000	0.000	18 1	19	11	26	4 0	06/08/04	2004	Gabon Express Pakistan	Gabon	Western	off Libreville, GA	HS 748	TP-Large	e		No	100	Asia	Africa Asia	Africa Asia-Low-Mdl Income	x	yes
398	RE-Landing			0.000	0 0	0	0	36	4 0	06/16/04	1008	International Airlines	Pakistan	Western	Chitral, PK	Fokker F.27	TP-Large	e		No	100				х	yes
399	RE-Takeoff			0.000				57		15/05/1998	1990	Airlines	Indonesia		KENDARI	F-28-4000	Jet	TAKEOFF				Asia	ASIA (EX CHINA)	Indonesia	HULL LOSS	ASEDB
400	RE-Landing			0.000				73		16/05/1998	1998	Manunggal Air	Indonesia		SINGAPORE	F-28	Jet	LANDING				Asia	ASIA (EX CHINA)	Indonesia	HULL LOSS	ASEDB
401	FUEL		0.500	0.529	0 1	1	1	0	2 0	08/13/04	2004	Air Tahoma	USA	Western	Cincinnati, US	Convair 580	TP-Large	e		Yes	100	North America	NA-Car	US-Canada	x	yes
402	RE-Landing			0.000				91		19/07/1998	1998	Sudan Airways	Sudan		KHARTOUM	737-200	Jet					Africa	AFRICA	Sudan		ASEDB
102			0.000	0.000				01			2004					Fairchild (Swearingen)					100	North America	NA-Car	US-Canada		NOLDD
403	SCF-NP			0.000	0 0	0	0	9	2 0	09/21/04	1998	Norcanair Airlines	Canada	vvestern	La Ronge, CA	Metro	TP-Smai			NO	100				x	yes
404	RE-Landing			0.000				376		05/08/1998	1998	Korean Air	South Korea		SEOUL	747-400	Jet	LANDING				Asia North America	ASIA (EX CHINA)	South Korea	HULL LOSS	ASEDB
405	SCF-NP		0.967	0.974						31/08/1998	2004	DHL Airways	USA		NEW YORK	727-200	Jet	TAKEOFF				North Amorico	NA-Car	USA	HULL LOSS	ASEDB
406	CFIT		0.007	0.074	11 2	13	2	13	2 0	10/18/04	2004	RegionsAir	USA	Western	(near) Kirksville, US	Jetstream 31	TP-Smal	П		No	100	North America	NA-Cai	03-Callada	x	yes
407	SCF-PP		0.000	0.000	0 0	0	0	8	2 0	10/22/04	2004	Southern Air Charter	Bahamas	Western	(near) Nassau, BS	BE-1900	TP-Smal			No	100	Latin America & Caribbean			x	ves
408	SCF-NP		1	1.000	215 14	229	0	215	14 0	02/09/1998	1998	Swissair	Switzerland	Western	Nova Scotia	MD 11	Jet	En Route	ХХ	No	100	Europe	Europe	EU-EFTA	х	yes
409	RE-Landing			0.000				102		16/09/1998	1998	Continental Airlines	USA		GUADALAJARA	737-500	Jet	LANDING					NA-Car	USA	HULL LOSS	ASEDB
410	RE-Landing		0.190	0.237	4 0	4	17	19	2 0	11/18/04	2004	Venezolana	Venezuela	Western	Caracas, VE	Jetstream 31	TP-Smal			No	100	Latin America & Caribbean	SA/CA	SA (Northern)	x	ves
411	CFIT		1	1.000	34 4	38	0	34	4 0	25/09/1998	1998	Paukn Air	Spain	Western	Melilla, MA	BAE-146	Jet	Approach	хх	No	100	Europe	Europe	EU-EFTA	x	yes
412	SCF-PP			0.000				97		05/10/1998	1998	LAM	Mozambique		MAPUTO	747-SP	Jet	CLIMB				Africa	AFRICA	Mozambique	HULL LOSS	ASEDB
413	RE-Landing			0.000				100		01/11/1998	1998	AirTran Airways	USA		ATLANTA	737-200	Jet	LANDING				North America	NA-Car	USA	HULL LOSS	ASEDB
414	SCF-PP		0	0.000	0 0	0	0	0	5 0	14/11/1998	1998	IAT Cargo	Nigeria	Western	Ostend, BE	B707	Jet	Landing - Rollout	Turb	No	100	Africa	Africa	Africa	х	yes
415	CFII		U	0.000	0 0	0	0	61	11 0	10/12/1998	1998	Azerbaijan Airlines /AZAL Avia	Azerbaijan	vvestern	Baku, AZ	B121	Jet	Landing - Go Around	IMC	XX	100		Europe	Europe - E/.SE	x	yes
416	LOC-I		0.699	0.699	91 11	102	0	132	14 0	11/12/1998	1998	Thai Airways International	Thailand	Western	Surat Thani, TH	A310	Jet	Go Around	Rain-Wind	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
417	RE-Landing		0.000	0.000	0 0	0	0	0	2 0	02/15/05	2005	African Commuter Services	Kenya	Western	Oldfangak, SD	HS 748	TP-Large	e		No	100	Africa	Africa	Africa	x	yes
418	SCF-PP		0.000	0.032	0 0	0	28	45	5 0	02/22/05	2005	TAM - Transporte Aereo Militar	Bolivia	Western	Trinidad, BO	Convair 580	TP-Large			No	100	Latin America & Caribbean	SA/CA	SA Mercosur	x	ves
419	ARC		0	0.000	0 0	0	0	36	4 0	28/12/1998	1998	Rio Sul	Brazil	Western	Curitiba, BR	EMB ERJ-145	Jet	Landing - Rollout	Clouds	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	х	yes
420	ARC		0	0.000	0 0	0	0	78	6	1/28/1999	1999	Alitalia	Italy	Western	CATANIA	MD-82	Jet	LANDING	XX	XX	XX	Europe	Europe	EU-EFTA		NO

Accident ID	Category Definition	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd) Pax OnBd	Crew OnBd	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
421	CFIT	1.000	1.000	14 3	17 0	0 14	3 0	0 04/12/05	2005	GT Air	Indonesia	Western	(near) Enarotali, ID	DHC-6	TP-Small			No	100	Asia	Asia	Asia-Low-Mdl Income	x	ves
	450	0.000	0.000			0 05			2005	Maria		Martin			TD				100	Europe	Europe	EU-EFTA	~	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
422	ARC	1.000	1.000			0 25	3 (	05/01/05	2005	Aero-Tropics Air	Norway	vvestern	Hammerrest, NO	Fairchild (Swearingen)	TP-Large			NO	100	Aust	Aust/asia	Hi-Income Asia-Pac	x	yes
423	CFIT		0.000	13 2	15 (	0 13	2 (	0 05/07/05	4000	Services	Australia	Western	(near) Lockhart River, AU	Metro	TP-Small			No	100	Africa		No Afr/Add To at	х	yes
424	RE-Landing	0.000	0.000	0 0		0 92	10	1/31/1999	2005	Air Aigerie	Aigeria	vvestern	CONSTANTINE	B727-200	Jet	LANDING	XX	XX	XX	Anca Asia	Asia	Asia-Low-Mdl Income		INO
425	USOS RE Takooff	0	0.000	0 0	0 0	0 10	3 (	0 06/30/05	1000	Gorkha Airlines	Nepal	Western	Lukla, NP	Fairchild/Dornier 228	TP-Small		vv	No	100	Europo	Europo		х	yes
427	RE-Landing	0	0.000	0 0		0 91	6	3/4/1999	1999	Air France	France	Western	BIARRITZ	B737-200	Jet	LANDING	XX	XX	XX	Europe	Europe	EU-EFTA		No
		0.410	0.426						2005											Aust	Europe	NoAfr/MidEast		
428 429	ARC	0	0.011	15 1	16 1 0 1	11 35 1 0	4 (	3/5/1999	1999	SevenAir Air France	Tunisia	Western	12sm off Palermo, IT MADRAS	AIR 72 B747-200	IP-Large		XX	NO XX	100 xx	Furope	Europe	FU-FETA	Х	yes
430	RE-Landing	ARC 0.001	0.001	0 0	0 2	2 150	6 0	0 15/03/1999	1999	Korean Air	Korea	Western	Pohang, KR	MD-80	Jet	Landing - Rollout	Rain-Wind	No	100	Asia	Asia	Asia-Low-Mdl Income		
			0.000						1000		Linited Arab									Middle East			х	yes
431	RE-Landing	0	0.000	0 0	0 0	0 252	19	3/24/1999	1333	Emirates	Emirates	Western	RHODES ISLAND	A300-600	Jet	LANDING	хх	xx	xx		MIDDLE EAST	NoAfr/MidEast		No
422		1	1.000	0 6		0	6	4/7/1000	1999	Turkish Airlines	Turkov	Western		P727 400	lot	CLIMP	WW	W		Europe	Europe	NoAfr/MidEast		No
452	LUC-1	0.000	0.000			0 0	0	4/1/1999	2005		Congo, Zr	WESIEIII		B737-400	JEL		^^		~~	Africa	Africa	Africa		
433	SCF-PP	4	<b>1</b> 000	0 0	0 0	0 18	2 0	0 09/08/05	1000	TMK Air Commuter	Kanaa	Western	(near) Goma, ZR	DHC-6	TP-Small	T/O Olizah ta Ozuiza	Dein	No	100	Asia			X 5 Oray and	yes
434	LUC-I		1.000	0 3			3 5	5 15/04/1999	1999	Kolean All	Kolea	western	Shanghai, Civ		Jei		Clouds		100	Asia	ASId	Asia-Low-indi Income	fatal	yes
435	WSTRW	0	0.000	0 0	0 0	0 60	6	4/22/1999	1999	Million Air Charters	South Africa	Western	JOHANNESBURG	B727-200	Jet	INITIAL APPROACH	XX	XX	XX	Africa	Africa	Africa		No
436	WSTRW	0.094	0.094	10 1	11 4	45 139	6 (	0 01/06/1999	1999	American Airlines	USA	Western	Little Rock	MD-80	Jet	Landing - Approach	T-Storm	No	100	North America	NA-Car	US-Canada	Х	yes
437	ARC	0	0.000	0 0	0 0	0 81	9	6/9/1999	1999	Airlines	China	Western	ZHANGJIANG	B737-300	Jet	LANDING	хх	xx	xx	Asia	CHINA	Asia-Low-Mdl Income		No
438	CFIT	1	<b>1</b> .000	0 5	5 (	0 0	5 0	07/07/1999	1999	Hinduja Cargo	India	Western	Kathmandu, NP	B727	Jet	T/O Climb to Cruise	Rain-Fog	No	100	Asia	Asia	Asia-Low-Mdl Income	v	WOC
		0.000	0.000	+			+		2005	Services										Latin America & Caribbean	SA/CA	CA/Carib	x	yes
439	ARC	<b>1</b> 000	<b>M</b> 000	0 0	0 (	0 40	4 (	0 12/16/05	2005	NatureAir	Costa Rica	Western	Tamarindo, CR	DHC-6	TP-Small			No	100	North Amorica	NA Cor	LIS Canada	х	yes
440	SCF-NP	1.000	1.000	18 2 2	20 0	0 18	2 0	0 12/19/05	2005	Airlines	USA	Western	Miami, US	Gulfstream Mallard	TP-Small			No	100	North America	INA-Odi	US-Callaua	x	yes
441	FIRE-NI	0.000	0.000	0	0 0	0	3 (	02/07/06	2006	LIPS Airlines		Western	Philadelphia LIS	DC-8	TP-I argo			No	100	North America	NA-Car	US-Canada	v	Ves
		0.000	0.000					02/01/00	2006	Of O Annies		Western			TI -Laige				100	Asia	Asia	Asia-Low-Mdl Income	^	yes
442	RE-Landing	0.032	0.032	0 0	0 0	0 27	3 (	0 03/11/06	2006	Deccan	India	Western	Bangalore, IN	ATR 72	TP-Large			No	100	Latin America & Caribbean	SA/CA	SA Mercosur	х	yes
443	RE-Landing	0.002	0.002	1 0	1 (	0 27	4 (	04/16/06	2000	Aereo Militar	Brazil	Western	Guayaramerin, BO	Fokker F.27	TP-Large			No	100		0.001	c. timorocoul	х	yes
444	SCE-NP	1.000	1.000	4 4	8 0	0 4	4 0	04/27/06	2006	LAC Skycongo	Congo, Zr	Western	(near) Lubutu ZR	Convair 580	TP-Large			No	100	Atrica	Africa	Africa	x	ves
445	RE-Landing	ARC	0.000						1999	Trans Arabian Air					Luigo						Africa	Africa		,
		0	0.006	0 0	0 0	0 0	3	8/14/1999	2006	Transport	Sudan	Western	JUBA	B707-328C	Jet	LANDING	ХХ	XX	XX	Africa	SA/CA	CA/Carib		No
446	RE-Landing	0.000	0.000	0 0	0 2	2 16	4 0	0 06/01/06	2000	Air Panama	Panama	Western	Bocas de Toro, PA	Jetstream 31	TP-Small			No	100			c ourio	x	yes
447	ARC	0.019	0.019	3 0 3	3 5	50 300	15 0	0 22/08/1999	1999	China Airlines	Taiwan	Western	Hong Kong, HK	MD-11	Jet	Landing - Rollout	Rain-Wind	No	100	Asia	Asia	Hi-Income Asia-Pac	х	yes
448	RE-Landing	0.000	0.019	0 0	0 6	6 15	3 0	06/05/06	2000	Airlines	Indonesia	Western	Bandanaira, ID	212	TP-Small			No	100	Лыа	ASIA .		x	yes
449	FIRE-NI	0.018	0.018	1 0	1 1	13 90	6 (	0 24/08/1999	1999	UNI Air	Taiwan	Western	Hualien, TW	MD-90	Jet	Landing - Rollout	ХХ	No	100	Asia	Asia	Hi-Income Asia-Pac	X	yes
450	RE- lakeoff	0.63	0.630	61 3	64 1	15 98	5 5	5 31/08/1999	1999	LAPA	Argentina	Western	Buenos Aires, AR	B737	Jet	I/O Aborted	XX	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	5 Ground fatal	ves
454	1001	1.000	1.000					0.00/04/00	2006		Negel	14/201			TD C II			N	400	Asia	Asia	Asia-Low-Mdl Income		
451	ARC	0	0.000	0 0	9 0	0 6	3 (	9/9/1999	1000	TWA	USA	Western	(near) Jumia, NP	DHC-6 DC-9-31	Jet		XX	NO XX	100 XX	North America	NA-Car	US-Canada	X	No
.02		1.000	1.000		-		Ť		2006	Pakistan	- 5.								7.01	Asia	Asia	Asia-Low-Mdl Income		
453	SCF-PP	0.004	0.000	41 4	45 (	0 41	4 (	0 07/10/06	1000	International Airlines	Pakistan	Western	Multan, PK	Fokker F.27	TP-Large	Londing Dalls (	Dain Mr.	No	100	<b>F</b>			x	yes
454	ARC	0.001	0.000	0 0 0	0 2	2 236	9 (	J 14/09/1999	2006	Britannia Airways	UK	Western	Gerona, ES	B/5/	Jet	Landing - Rollout	Rain-Wind	No	100	Europe	Europe	EU-EFTA NoAfr/MidEast	X	yes
455	LOC-I	1.000	1.000	0 3	3 (	0 0	3 0	0 08/13/06	2000	Air Algerie	Algeria	Western	(near) Piacenza, IT	Lockheed Hercules	TP-Large			No	100	Annou	/ strive	i tor un wide dot	х	yes



	Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set	
bit         bit <th>456</th> <th>ARC</th> <th></th> <th>0</th> <th>0.000</th> <th>0 0</th> <th>0 0</th> <th>0</th> <th>3</th> <th>5 0</th> <th>16/10/1999</th> <th>1999</th> <th>Continental Cargo</th> <th>Ghana</th> <th>Western</th> <th>Kinshasa, ZR</th> <th>DC-8</th> <th>Jet</th> <th>Landing - Rollout</th> <th>хх</th> <th>No</th> <th>100</th> <th>Africa</th> <th>Africa</th> <th>Africa</th> <th></th> <th></th>	456	ARC		0	0.000	0 0	0 0	0	3	5 0	16/10/1999	1999	Continental Cargo	Ghana	Western	Kinshasa, ZR	DC-8	Jet	Landing - Rollout	хх	No	100	Africa	Africa	Africa			
000         000        000         000         000	457			0	0.000			_		2 0	17/10/1000	8000	Airlines			Cubia Day, Dh	MD 44	lat	Landing Dellaut	Dein	No	100	North America	NA Cor	UC Canada	X	yes	
Processe         rocesse         Processe         Processe        <	407	RE-Landing		0	0.000	12 0	J U	0	12	2 0	17/10/1999	1999	TAESA	USA	Weatorn	Subic Bay, Pfi		Jel	Landing - Rollout	Rain	INO No	100	North America	NA-Cal	US-Cariada	X	yes	
	400	LUU-I DE Landing	ADC	0.051	0.051	0 0	2 16	0	206	0 0 10 0	21/12/1000	1999	Cubana	Cuba	Western		DC-9	Jel	1/0 Initial Climb	XX Doin	No	100	Latin America & Caribbean	SA/CA	CA/Carib	X 2 Ground	yes	
m         m	409		ARC	0.001	0.001	0	5 10	0	290	10 2	21/12/1999	1999	Cuballa	Cuba	western	Guatemaia City, GT	DC-10	Jel		Naili		100		NA-Cal		fatal	yes	
Profile         Profile <t< td=""><td>460</td><td>RE-Landing</td><td></td><td>0.000</td><td>0.000</td><td>0</td><td></td><td>0</td><td></td><td>0</td><td>10/02/06</td><td>2006</td><td>Malu Aviation</td><td>Congo, Zr</td><td>Western</td><td>Kikwit 7R</td><td>Nord 262</td><td>TP-I arne</td><td></td><td></td><td>No</td><td>100</td><td>Africa</td><td>Africa</td><td>Africa</td><td>v</td><td>VAS</td></t<>	460	RE-Landing		0.000	0.000	0		0		0	10/02/06	2006	Malu Aviation	Congo, Zr	Western	Kikwit 7R	Nord 262	TP-I arne			No	100	Africa	Africa	Africa	v	VAS	
Image         Image <t< td=""><td>461</td><td>LOC-I</td><td></td><td>1</td><td>1.000</td><td>0 4</td><td>4 4</td><td>0</td><td>0</td><td>4 0</td><td>22/12/1999</td><td>1999</td><td>Korean Air</td><td>Korea</td><td>Western</td><td>Bishops Stortford, GB</td><td>B747</td><td>Jet</td><td>T/O Initial Climb</td><td>Wind-</td><td>No</td><td>100</td><td>Asia</td><td>Asia</td><td>Asia-Low-Mdl Income</td><td>^</td><td>yco</td></t<>	461	LOC-I		1	1.000	0 4	4 4	0	0	4 0	22/12/1999	1999	Korean Air	Korea	Western	Bishops Stortford, GB	B747	Jet	T/O Initial Climb	Wind-	No	100	Asia	Asia	Asia-Low-Mdl Income	^	yco	
																				Clouds						x	yes	
B         B         I	462	CFIT		0.944	0.944	159 1	10 169	0	169	10 0	30/01/2000	2000	Kenya Airways	Kenya	Western	off Abidjan, Cl	A310	Jet	T/O Initial Climb	ΧХ	No	100	Africa	Africa	Africa	х	yes	
H         H	463	SCF-NP		1	1.000	83 5	5 88	0	83	5 0	31/01/2000	2000	Alaska	USA	Western	Point Mugu, Ca	MD-83	Jet	En Route	XX	No	100	North America	NA-Car	US-Canada	Х	yes	
68         68         69        69        69        69 <td></td> <td></td> <td></td> <td>0.000</td> <td>0.000</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2006</td> <td></td> <td></td> <td></td> <td></td> <td>Fairchild (Swearingen)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>North America</td> <td>NA-Car</td> <td>US-Canada</td> <td></td> <td></td>				0.000	0.000							2006					Fairchild (Swearingen)						North America	NA-Car	US-Canada			
b         b	464	RE-Landing				0 (	) ()	0	7	2 0	11/08/06		Perimeter Airlines	Canada	Western	Norway House, CA	Metro	TP-Small			No	100				Х	yes	
20         1	105			0	0.000					_	0/0/0000	2000	Trans Arabian Air	Quidan	\A/		D707 0400	1-4					A.6.:	Africa	Africa		No	
m         m	405	CFII Other		0	0.000			0	1170	5	2/3/2000	2000		Sudan Cata d'Iluaira	Western		B707-310C	Jet		XX	XX	XX	Africa		Africa		INO No	
1         1         1         0	400	Ulliel		0 000	0.000	0 (	0	0	1/9		2/11/2000	2000	All Allique		western	DANAR	A300D4	Jel	ΙΑΛΙ	XX	XX	**	Allica	AFRICA	Allica		INU	
No. 100         No. 0         <	467	RF-Landing		0.000	0.000	0		0	156	6 0	12/12/06	2000	Sudan Airways	Sudan	Western	Healia SD	Fokker 50	TP-Large			No	100	Allica	Allica	Allica	x	Ves	
440         100 <td>468</td> <td>ARC</td> <td></td> <td>0</td> <td>0.000</td> <td>0 0</td> <td></td> <td>0</td> <td>0</td> <td>7 0</td> <td>12/02/2000</td> <td>2000</td> <td>TransAfrik</td> <td>Sao Tome</td> <td>Western</td> <td>Luanda, AO</td> <td>B727</td> <td>Jet</td> <td>Landing - Rollout</td> <td>Rain-Wind</td> <td>No</td> <td>100</td> <td>Africa</td> <td>Africa</td> <td>Africa</td> <td>x</td> <td>ves</td>	468	ARC		0	0.000	0 0		0	0	7 0	12/02/2000	2000	TransAfrik	Sao Tome	Western	Luanda, AO	B727	Jet	Landing - Rollout	Rain-Wind	No	100	Africa	Africa	Africa	x	ves	
Image: Note of the stand of the st	469	LOC-I		1	1.000	0 3	3 3	0	0	3 0	16/02/2000	2000	Emery	USA	Western	Rancho Cordova, Ca	DC-8-71	Jet	T/O Initial Climb	XX	No	100	North America	NA-Car	US-Canada	X	ves	
4/1         1/2 <td></td> <td></td> <td></td> <td>0.000</td> <td>0.000</td> <td></td> <td></td> <td>-</td> <td></td> <td></td> <td></td> <td>2007</td> <td></td> <td>North America</td> <td>NA-Car</td> <td>US-Canada</td> <td></td> <td></td>				0.000	0.000			-				2007											North America	NA-Car	US-Canada			
All         All<         All         All         All <td>470</td> <td>USOS</td> <td></td> <td></td> <td></td> <td>0 0</td> <td>0 0</td> <td>0</td> <td>10</td> <td>2 0</td> <td>01/09/07</td> <td></td> <td>Peace Air</td> <td>Canada</td> <td>Western</td> <td>Fort St John, CA</td> <td>Jetstream 31</td> <td>TP-Small</td> <td></td> <td></td> <td>No</td> <td>100</td> <td></td> <td></td> <td></td> <td>x</td> <td>yes</td>	470	USOS				0 0	0 0	0	10	2 0	01/09/07		Peace Air	Canada	Western	Fort St John, CA	Jetstream 31	TP-Small			No	100				x	yes	
Image: bolic	471	RE-Landing	ARC	0	0.000	0 0	) ()	0	137	5 0	05/03/2000	2000	Southwest	USA	Western	Burbank, California	B737	Jet	Landing - Rollout	XX	No	100	North America	NA-Car	US-Canada			
dr2         dr3         dr3 <td></td> <td>х</td> <td>yes</td>																										х	yes	
Ar3       ReLanding       Bo	472	CFIT		1	1.000	124 7	7 131	0	124	70	19/04/2000	2000	Air Philippines	Philippines	Western	Davao, PH	B737	Jet	Approach	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes	
I         I	473	RE-Landing		0	0.000	0 0	0 0	0	42	4 0	22/04/2000	2000	THY - Turkish	Turkey	Western	Siirt, TR	BAE (Avro) RJ	Jet	Landing - Rollout	Wind	No	100	Europe	Europe	NoAfr/MidEast			
4/4         4/4         A/4         A/4 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>_</td> <td></td> <td></td> <td>Airlines</td> <td></td> <td>Х</td> <td>yes</td>										_			Airlines													Х	yes	
4/3         A×C         0 <td>474</td> <td>RE-Landing</td> <td></td> <td>0</td> <td>0.000</td> <td>0 (</td> <td>) ()</td> <td>0</td> <td>0</td> <td>7 0</td> <td>30/04/2000</td> <td>2000</td> <td>DAS Air</td> <td>Uganda</td> <td>Western</td> <td>Entebbe, UG</td> <td>DC-10</td> <td>Jet</td> <td>Landing - Rollout</td> <td>Rain</td> <td>No</td> <td>100</td> <td>Africa</td> <td>Africa</td> <td>Africa</td> <td>Х</td> <td>yes</td>	474	RE-Landing		0	0.000	0 (	) ()	0	0	7 0	30/04/2000	2000	DAS Air	Uganda	Western	Entebbe, UG	DC-10	Jet	Landing - Rollout	Rain	No	100	Africa	Africa	Africa	Х	yes	
dr         dr<	4/5	ARC		0	0.000	0 0	) ()	0	0	5	6/26/2000	2000	remenia	Yemen	western	KHARTOUM	B727-200	Jet	LANDING	XX	XX	XX	Middle East		NOATT/MIDEast		NO	
4/7       U.C-1       0.099       0.099       0.099       0       0       0       0.0       Adda East	470	FUEL		0	0.000	0 0	0	0	142	8 0	12/07/2000	2000	Hapag-Lioyo	Germany	vvestern	Vienna, Al	A300	Jet	Landing - Approach	XX	INO	100	Europe	Europe	EU-EFTA	X	yes	
478       RE-Landing       0 <t< td=""><td>4//</td><td>LUU-I</td><td></td><td>0.899</td><td>0.899</td><td>40 0</td><td>5 52</td><td>2</td><td>52</td><td>0 0</td><td>17/07/2000</td><td>2000</td><td>Alliance All</td><td>India</td><td>western</td><td>Patha, IN</td><td>8/3/</td><td>Jei</td><td>Approach</td><td>XX</td><td>INO</td><td>100</td><td>Asia Middle East</td><td>Asia</td><td>Asia-Low-Ividi Income</td><td>X</td><td>yes</td></t<>	4//	LUU-I		0.899	0.899	40 0	5 52	2	52	0 0	17/07/2000	2000	Alliance All	India	western	Patha, IN	8/3/	Jei	Approach	XX	INO	100	Asia Middle East	Asia	Asia-Low-Ividi Income	X	yes	
419         ReLanding         APC         0.00         0.0	478	RE-Landing		0	0.000	0 0	0 0	0	84	4	7/18/2000	2000	Airlines	Iran	Western	AHWAZ	F-28-4000	Jet	LANDING	хх	xx	xx		MIDDLE EAST	NoAfr/MidEast		No	
Image: Constraint of the	479	RE-Landing	ARC	0.000	0.000				40	1 0	07/01/07	2007	lot Ainwovo	India	Montorn	Indoro IN		TD Lorgo			No	100	Asia	Asia	Asia-Low-Mdl Income		¥22	
No.         No. <td>480</td> <td>SCE-PP</td> <td></td> <td>1</td> <td>1 000</td> <td></td> <td>2 2</td> <td>0</td> <td>0</td> <td>2 0</td> <td>19/07/2000</td> <td>2000</td> <td>Airwaye Transport</td> <td>Canada</td> <td>Western</td> <td>(near) Linneus LIS</td> <td>Gulfstream</td> <td>let</td> <td>En Route</td> <td>T-Storm -</td> <td></td> <td>100</td> <td>North America</td> <td>NA-Car</td> <td>US-Canada</td> <td>^</td> <td>yes</td>	480	SCE-PP		1	1 000		2 2	0	0	2 0	19/07/2000	2000	Airwaye Transport	Canada	Western	(near) Linneus LIS	Gulfstream	let	En Route	T-Storm -		100	North America	NA-Car	US-Canada	^	yes	
All       FIRE-NI       1       0.00       100       9       100       9       100       100       9       100       100       100       100       100       100       100       100       100       100       100       100       100       100       Europe       Europe       Europe       Europe       Europe       Europe       Europe       Asia	400			'	1.000	ľ	- 1-	ľ	ľ	2	10/01/2000	2000	All wave manopole	Cunudu	western	(near) Ennicad, 00	Guildireann	001		Turbulence			North America		00 oundu	Y	Ves	
ABC         ACC         ACC <td>481</td> <td>FIRE-NI</td> <td></td> <td>1</td> <td>1.000</td> <td>100</td> <td>9 100</td> <td>0</td> <td>100</td> <td>9 0</td> <td>25/07/2000</td> <td>2000</td> <td>Air France</td> <td>France</td> <td>Western</td> <td>Paris, FR</td> <td>Concorde</td> <td>Jet</td> <td>T/O Initial Climb</td> <td>XX</td> <td>No</td> <td>100</td> <td>Europe</td> <td>Europe</td> <td>EU-EFTA</td> <td>x</td> <td>ves</td>	481	FIRE-NI		1	1.000	100	9 100	0	100	9 0	25/07/2000	2000	Air France	France	Western	Paris, FR	Concorde	Jet	T/O Initial Climb	XX	No	100	Europe	Europe	EU-EFTA	x	ves	
482       ICO-1       ICO-1       ICO-0       I				1.000	1.000					-	20/01/2000	2007											Aust	20.000		~	,	
Re-Landing         0.000         0        <	482	LOC-I				19 1	1 20	0	19	1 0	08/09/07		Air Moorea	France (Tahiti)	Western	Moorea, PF	DHC-6	TP-Small			No	100				x	yes	
483       RE-Landing       1       0 <t< td=""><td></td><td></td><td></td><td>0.000</td><td>0.000</td><td></td><td></td><td></td><td></td><td></td><td></td><td>2007</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>Asia</td><td>Asia</td><td>Asia-Low-Mdl Income</td><td></td><td></td></t<>				0.000	0.000							2007											Asia	Asia	Asia-Low-Mdl Income			
484       ARC       0       0.000       0	483	RE-Landing				0 0	0 (	0	74	5 0	08/12/07		Jeju Air	Korea	Western	Pusan, KR	DHC 8	TP-Large			No	100				Х	yes	
485       SCF-NP       0.000       0.000       0	484	ARC		0	0.000	0 0	0 0	0	0	3	8/7/2000	2000	Air Memphis	Egypt	Western	CAIRO	707-328C	Jet	LANDING	XX	XX	XX	Africa	AFRICA	NoAfr/MidEast		No	
485       SCF-NP       0<				0.000	0.000							2007											Europe	_				
486       SCF-NP       0       0.000       0 <t< td=""><td>485</td><td>SCF-NP</td><td></td><td></td><td></td><td>0 0</td><td>0</td><td>0</td><td>69</td><td>4 0</td><td>09/09/07</td><td></td><td>SAS</td><td>Denmark</td><td>Western</td><td>Aalborg, DK</td><td>DHC 8</td><td>TP-Large</td><td>01.11.15</td><td></td><td>No</td><td>100</td><td></td><td>Europe</td><td>EU-EFTA</td><td>Х</td><td>yes</td></t<>	485	SCF-NP				0 0	0	0	69	4 0	09/09/07		SAS	Denmark	Western	Aalborg, DK	DHC 8	TP-Large	01.11.15		No	100		Europe	EU-EFTA	Х	yes	
Hor       Loc-1       I       Loc-1       Loc-1 <th loc-<="" td=""><td>486</td><td>SCF-NP</td><td></td><td>0</td><td>0.000</td><td>125 0</td><td></td><td>0</td><td>58</td><td>5</td><td>8/8/2000</td><td>2000</td><td>Air Iran Airways</td><td>USA</td><td>Western</td><td>GREENSBURU</td><td>DC-9-32</td><td>Jet</td><td></td><td>XX</td><td>XX</td><td>XX</td><td>North America</td><td>NA-Car</td><td>US-Canada</td><td>N N</td><td>INO NO</td></th>	<td>486</td> <td>SCF-NP</td> <td></td> <td>0</td> <td>0.000</td> <td>125 0</td> <td></td> <td>0</td> <td>58</td> <td>5</td> <td>8/8/2000</td> <td>2000</td> <td>Air Iran Airways</td> <td>USA</td> <td>Western</td> <td>GREENSBURU</td> <td>DC-9-32</td> <td>Jet</td> <td></td> <td>XX</td> <td>XX</td> <td>XX</td> <td>North America</td> <td>NA-Car</td> <td>US-Canada</td> <td>N N</td> <td>INO NO</td>	486	SCF-NP		0	0.000	125 0		0	58	5	8/8/2000	2000	Air Iran Airways	USA	Western	GREENSBURU	DC-9-32	Jet		XX	XX	XX	North America	NA-Car	US-Canada	N N	INO NO
488       ARC       Image: ARC       I	487	100-1		1	0.000	135 8	5 143		135	0 0	23/08/2000	2000	Gull All		vvestern	Malialia, BH	A320	Jei	GUAIOUIIU	XX	NO	100	windle East	Asid	NUAII/IVIIUEASI	X	yes	
Association	488	ARC			0.000				2		21/09/2000	2000	Republic of Togo	Τοσο		NIAMEY	707-312B	Jet	INITIAL APPROACH				Africa	AFRICA	Τοαο	HULLOSS	ASEDB	
489       RE-Takeoff       0       0       0       0       9       4       0       10/31/07       Air Panama       Panama       Western       Panama City, PA       Fokker F.27       TP-Large       No       100       International Accession       Air Panama       Yes         490       RE-Landing       ARC       0	100			0.000	0.000				-		2110012000	2007	- topublic of fogo					001					Latin America & Caribbean	SA/CA	CA/Carib			
490       RE-Landing       ARC       0       0       0       0       83       5       4       06/10/2000       2000       Aeromexico       Mexico       Western       Reynosa, MX       DC-9       Jet       Landing - Rollout       Rain       No       100       Latin America & Caribbean       SA/CA       CA/Carib       4 Ground         fatal       ves	489	RE-Takeoff				0 0	0 0	0	9	4 0	10/31/07		Air Panama	Panama	Western	Panama City, PA	Fokker F.27	TP-Large			No	100				х	yes	
	490	RE-Landing	ARC	0	0.000	0 0	0 0	0	83	5 4	06/10/2000	2000	Aeromexico	Mexico	Western	Reynosa, MX	DC-9	Jet	Landing - Rollout	Rain	No	100	Latin America & Caribbean	SA/CA	CA/Carib	4 Ground fatal	ves	

Accident ID	Category Definition	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Date	Year	r Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigh - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
49	RI	0.479	0.479	79 4	83	48	159 20 0	) 31/10/2000	2000	Singapore Airlines	Singapore	Western	Taipei, TW	B747	Jet	T/O Run	Typhoon	No	100	Asia	Asia	Asia	Х	yes
492	RE-Landing	0	0.000	0 0	0	0	183 16 (	05/11/2000	2000	Cameroon Airlines	Cameroon	Western	Paris, FR	B747	Jet	Landing - Rollout	Rain-Wind	No	100	Africa	Africa	Africa	Х	yes
		0.000	0.000						2007	Atlantic Airlines De										Latin America & Caribbean	SA/CA	CA/Carib		
493	RE-Takeoff			0 0	0	0	31 3 0	0 12/16/07		Honduras	Honduras	Western	La Ceiba, HN	Fairchild F-27	<b>TP-Small</b>			No	100				х	yes
494	ARC	0	0.000	0 0	0	0	42 8	11/13/2000	2000	) Ghana Airways	Ghana	Western	CONAKRY	DC-9-51	Jet	LANDING	ХХ	XX	100	Africa	Africa	Africa		No
49	SCF-NP	0.009	0.009	0 1	1	0	106 10 0	0 20/11/2000	2000	American	USA	Western	Miami	A300	Jet	Ground, taxi		No	100	North America	NA-Car	US-Canada	Х	yes
496	USOS	0	0.000	0 0	0	0	6 4 1	1 05/01/2001	2001	Air Gemini	Angola	Western	Dundo, AO	B727	Jet	Landing - Approach	ХХ	No	100	Africa	Africa	Africa	1 Ground	
																							fatal	yes
			0.000						2001												LATIN AMERICA &			
49	SCF-NP	0		0 0	0	0	138 8	1/9/2001		LAB	Bolivia	Western	BUENOS AIRES	B727-200	Jet	TAKEOFF	хх	xx	xx	Latin America & Caribbean	CARIBBEAN	SA Mercosur		No
498	LOC-I	0.529	0.529	2 1	3	3	3 3 0	0 31/01/2001	2001	Lineas Aereas	Colombia	Western	El Yopal, CO	Caravelle	Jet	Landing - Approach	ХХ	No	100	Latin America & Caribbean	SA/CA	SA (Northern)		
										Suramericanas												, ,	х	yes
499	ARC	0	0.000	0 0	0	0	136 6	2/7/2001	2001	Iberia Airlines	Spain	Western	BILBAO	A320-210	Jet	LANDING	ХХ	XX	XX	Europe	Europe	EU-EFTA		No
500	FIRE-NI	0.2	0.200	0 1	1	0	0 5 0	0 03/03/2001	2001	Thai Airways	Thailand	Western	Bangkok, TH	B737	Jet	Ground, Parked	ХХ	No	100	Asia	Asia	Asia-Low-Mdl Income		
										International													х	yes
			0.000						2001												LATIN AMERICA &			
501	USOS	0		0 0	0	0	0 3	3/7/2001		Skymaster Air Lines	Brazil	Western	SAO PAULO	B707-300	Jet	LANDING	ХХ	XX	xx	Latin America & Caribbean	CARIBBEAN	SA Mercosur		No
			0.000						2001	Express One										North America				
502	USOS	0		0 0	0	0	0 3	3/11/2001		International	USA	Western	PONAPE	B727-200	Jet	LANDING	ХХ	XX	xx		NA-Car	US-Canada		No
503	ARC	0	0.000	0 0	0	0	175 7 (	23/03/2001	2001	Luxor Air	Egypt	Western	Monrovia, LR	B707	Jet	Landing - Rollout	Fog	No	100	Africa	Africa	NoAfr/MidEast	Х	yes
			0.000						2001	Canada 3000										North America				
504	RE-Landing	0		0 0	0	0	0 2	4/4/2001		Airlines	Canada	Western	ST. JOHNS	B737-200	Jet	LANDING	ХХ	XX	XX		NA-Car	US-Canada		No
505	USOS	0	0.000	0 0	0	0	6 5	5/10/2001	2001	Angola Air Charter	Angola	Western	NZAGI	B727-100	Jet	LANDING	ХХ	XX	XX	Africa	AFRICA	Africa		No
506	ARC	0	0.000	0 0	0	0	98 6	5/22/2001	2001	First Air	Canada	Western	YELLOWKNIFE	B737-200	Jet	LANDING	XX	XX	XX	North America	NA-Car	US-Canada		No
507	SCF-NP	0	0.000	0 0	0	0	88 4	5/23/2001	2001	American Airlines	USA	Western	DALLAS	F-100	Jet	LANDING	XX	XX	XX	North America	NA-Car	US-Canada		No
508	RE-Landing	0	0.000	0 0	0	0	132 8	8/1/2001	2001	Yemenia	Yemen	Western	ASMARA	B727-200	Jet	LANDING	XX	XX	XX	Middle East	MIDDLE EAST	NoAfr/MidEast		No
509	RE-Landing	0	0.000	0 0	0	0	4 6	8/28/2001	2001	Eagle Aviation	Kenya	Western	LIBREVILLE	BAC 1-11-400	Jet	LANDING	XX	XX	XX	Africa	Africa	Africa		No
			0.011						2001												LATIN AMERICA &			
510	SCF-PP	0.011364		1 0	1	0	82 6	9/15/2001		TAME	Ecuador	Western	BELO HORIZONTE	F-100	Jet	CRUISE	XX	XX	XX	Latin America & Caribbean	CARIBBEAN	SA (Northern)		No
511	ARC	0	0.000	0 0	0	0	62 5 0	0 16/09/2001	2001	VARIG	Brazil	Western	Goiania, BR	B737	Jet	Landing - Rollout	Rain	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
512	RI	1	1.000	104 6	110	0	104 6 0	08/10/2001	2001	SAS	Sweden (Multi-Nat)	Western	Milan, IT	MD-80	Jet	1/O Run	Fog	No	100	Europe	Europe	EU-EFTA	Х	yes
			0.000				100 10	40/47/0000	2001	Delister Lill At I	Delister		DUDAL	400004	1.1					A . ! .	Asia	Asia-Low-Mdl Income		N.,
513	SCF-NP	0	0.007	0 0	0	0	193 12	10/17/2001	0004	Pakistan Int'i Airlines	Pakistan	vvestern	DUBAI	A300B4	Jet		XX	XX	XX	Asia				INO
514	Other	0.006757	0.007	0 1	1	1	134 14	10/20/2001	2001	TUTIISAIF	Tunisia	Western	DJEKBA	A300-600	Jet	PARKED	XX	XX	XX	Airica		INOAII/IVIIOEASI	E Cround	INO
51	LUC-1	1	1.000	251 9	260	0	243 17 5	12/11/2001	2001	American Airlines	USA	western	Delle Harbor, NY	A300-000	Jei	TO Climb to cruise	XX	INO	100	North America	INA-Car	US-Canada	o Ground	
E44	CEIT	0 707	0 727	21 0	24	0	20 5 0	0 24/11/2004	2004	Crosseir	Switzorland	Mostore	(near) Zurich CLL		lot	Londing Approach	Spour	Nic	100	Europo	Europo		ialai	yes
510		0.727	0.727	21 3	24	0		) 24/11/2001 ) 11/27/01	2001	British Global	Switzenand	Western	(near) Zuricii, CH		Jet	Landing Approach	SHOW	No	100	Europe	Europe		X	yes
510	DSUS DE Takaoff	0.077	0.077		0	1		01/14/02	2001		Indonosio	Western	Rekenberu ID		Jet		××	No	100		Asia	LU-EFTA	X	yes
510	RE-Idkeoli	0.000	0.001	0 0	0	1	30 / (	5 01/14/02	2002		Indunesid	western			Jei		Heavy Dain	NU	100	Asia	Λοία Δεία	Asia-Low-Mdl Income	٨	yes
510	SCE DD	0.042	0.042	0 1	1	0	20 4	01/16/02	2002	Garuda Indonosia	Indonosia	Western	(noar) Voquakarta ID	P737 (CEMI)	lot	Doccont	Hoil	No	100	noid	noia	Asia-Low-Iviul Income	v	1/00
513	JUF-FF		P1 000	0 1	1	U	20 4 (	J 01/10/02	2002		Indunesia	Western	(Ilear) Tuyyakarta, ID		JEI	Descent		INU	100				X	yes
520	CEIT	1	1.000	83 0	92	0	83 0	1/28/2002	2002		Ecuador	Western	(near) Iniales	B727-100	let		vv	VV	vv	Latin America & Caribboan		SA (Northern)		No
520	Other	0	0.000	0 0	0	0	0 3	2/28/2002	2002			Western	SINGAPORE	DC-8-62C			××		××	North America	NA_Car			No
52	RE-Landing	0 000	0.000		0	0		03/18/02	2002		Brazil	Western	Belo Horizonte RP	B727	let	Landing - Rollout	××	No	100	Latin America & Caribboan	SA/CA	SA Mercosur	Y	VAS
522	TL-Lanung	0.000	0.000	0 0	0	5		00/10/02	2002		Diazii	Testeril	Doit Hunzonite, DIX	DIEI	001	Eunality - Nollout			100		SA/CA	CA/Carib	Λ	,00
52	Fuel	XX	0.000	0 0	0	0	29 3	9/6/2001	2001	Aeromexico Connect	Mexico	Western	(near) Tijuana MX	Saah 340	TP-Small					Latin America & Caribbean	0/10/1	Or V Carlo		No
520	1 001	0 771	0 781	0 0	U	5	20 0	01012001	2002		MCAIOU	Western					Rain miet			Asia	Asia	Asia-Low-MdLIncome		10
524	CEIT	0.771	0.701	120 8	128	28	155 11 0	0 04/15/02	2002	Air China	China	Western	Pusan KR	B767	Jet	Approach	vis	No	100	100			x	ves
52	RE-Landing	0.000	0.000	0 0	0	0	0 4 0	04/26/02	2002	Hewa Bora Airwavs	Congo, Zr	Western	Kinshasa, ZR	B707	Jet	Landing - Rollout	Wind, vis	No	100	Africa	Africa	Africa	X	ves
1.000										1.								1						1.



Accident ID	Category Definition	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd) Pax OnBd Crew OnBd	Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
500		0.948	0.950	07 0 7		70 7	# 05/0	2	2002	Ni:	Marada		Kana NO	DA 0 4 44	1			Vee	100	Africa	Africa	Africa	30 Ground	(
526	LUC-I	1 226	1 237	6/ 6 /3	3 2	10 1	# 05/0	04/02	2002	NICON AIrways	Nigeria	vvestern	Kano, NG	BAC-1-11	Jet	1/0 Initial Climb	XX Pain T	res	100	Africa	Africa	NoAfr/MidEast	tatai	yes
527	CEIT	0.220	0.237	11 3 14	4 1	2 56 6	0 05/0	07/02	2002	Favotair	Equat	Western	(near) Tunis TN	B737 (CEMI)	Jet	Annroach	Storm	No	100	Allica	Allua	NUAII/IVIIUEdSt	Y	Ves
021		1 000	1 000		- IA	2 00 0		01102	2002	Lgyptan		Western	20nm N of Penghu				Otomi		100	Asia	Asia	Hi-Income Asia-Pac	x	900
528	SCF-NP			206 19 22	25 0	206 19	0 05/2	25/02		China Airlines	Taiwan	Western	Islands, TW	B747	Jet	En Route	хх	No	100				^	ves
			0.000					2	2002											Europe	Europe	EU-EFTA		Ť
529	RI	xx		0 0 0	0	16 4	6/10	0/2002		Swiss	Switzerland	Western	Werneuchen, DE	Saab 2000	TP-Large									No
530	RE-Landing	0.000	0.000	0 0 0	0	63 5	0 06/1	14/02	2002	Inter (Colombia)	Colombia	Western	Neiva, CO	DC-9	Jet	Landing - Rollout	ХХ	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	Х	yes
		1.000	1.000					2	2002	DHL International										Middle East	Asia	NoAfr/MidEast	69 fatal in	4
531	MIDAIR	0.000	0.005	0 2 2	0	0 2	# 07/0	01/02	0000	B.S.C.	Bahrain	Western	(near) Uberlingen, DE	B/5/	Jet	En Route	XX	NO	100	A 6-1	Africa	Africa	other A/C	yes
532		0.920	0.925		3 2	1/ 8	0 07/0	04/02 2 26/02	2002	New Gomair	Congo, Zr	Western	(near) Bangul, CF	B707	Jet	Approach	XX	NO No	100	Affica North America	Africa	Affica	Color blind	yes
555	CITI	10.000	0.000		- 0	0 5	0 0112	20/02 2	2002	America West	007	WESIEIII		DIZI	JEI	Арргоасн	~~	NU	100	North America	INA-Odi	00-0dildud		yes
534	RE-Landing	0	0.000	0 0 0	1	154 5	8/28	8/2002		Airlines	USA	Western	PHOENIX	A320-231	Jet	LANDING	xx	xx	xx	i torari anonou	NA-Car	US-Canada		No
535	Fuel	0.000	0.000	0 0 0	0	24 9	0 08/3	30/02	2002	TAM Linhas Aereas	Brazil	Western	Birigui, BR	Fokker 100	Jet	Landing	ХХ	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Fuel Pump	yes
536	RE-Landing	0.000	0.000					2	2002								Rain &			Latin America & Caribbean	SA/CA	CA/Carib		Ť.
				0 0 0	0	86 4	0 10/3	31/02		Aeromexico	Mexico	Western	Monterrey, MX	DC-9	Jet	Landing - Rollout	ceiling	No	100				х	yes
537	RE-Landing	0	0.000	0 0 0	0	0 4	12/1	13/2002	2002	Arrow Air	USA	Western	SINGAPORE	DC-8-62C	Jet	LANDING	ХХ	XX	XX	North America	NA-Car	US-Canada		No
		0.938	0.941		-  -			4	2003	Turkish Airlines	<b>-</b> .				Jet		_		100	Europe	Europe	NoAfr/MidEast		4
538		<b>1</b> 000	<b>P</b> 000	10 5 75	5 5	/5 5	0 01/0	08/03	2002	(THY)	Turkey	Western	Diyarbakir, TR	Avro RJ Avroliner	lot	Approach	Fog	N0	100	Latin Amarica & Caribbaan	<u> </u>	CA (Northorn)	X	yes
539		0.000	0.000	41 5 40	0 0	41 D 87 6	0 01/0	26/03	2003		Pelu Brazil	Western	Pio Branco BP		Jel	Approach	VISIDIIILY	No	100	Latin America & Caribbean	SAICA	SA (NOITHEITI)	X	yes
541	100-1	0.000	0.000	97 6 10	03 1	98 6	0 03/0	06/03	2003	Air Algerie	Algeria	Western	Tamanrasset D7	B737 (JT8D)	Jet	T/O Initial Climb	XX	No	100	Africa	Africa	NoAfr/MidEast	SCE PP	Ves
542	RI	0	0.000	0 0 0	0	170 5	3/21	1/2003	2003	Transasia Airways	Taiwan	Western	TAINAN	A321-131	Jet	LANDING	XX	XX	XX	Asia	Asia	Hi-Income Asia-Pac		No
543	USOS	0.000	0.000	0 0 0	0	53 7	0 03/2	26/03	2003	Royal Air Maroc	Morrocco	Western	Oujda, MA	B737 (CFMI)	Jet	Approach	Fog	No	100	Africa	Africa	NoAfr/MidEast	Х	yes
544	CFIT	0.042	0.046	0 1 1	2	21 3	0 06/2	22/03	2003	Brit Air	France	Western	Brest, FR	CRJ Regional Jet	Jet			No	100	Europe	Europe	EU-EFTA	Х	yes
545	LOC-I	0.991	0.992	105 11 11	16 1	106 11	0 07/0	08/03	2003	Sudan Airways	Sudan	Western	(near) Port Sudan, SD	B737 (JT8D)	Jet			No	100	Africa	Africa	Africa	Х	yes
			0.000					2	2007												SA/CA	CA/Carib		
546	Ramp	XX	<b>Z</b> 000	0 0 0	0	0 3	3/29	9/2007	0007	Vigo Jet	Mexico	Western	Panama City, PA	L-188 Electra	TP-Large					Latin America & Caribbean	04/04	04/0		No
547			0.000		6		1/20	0/2007	2007	Pahamasair	Pahamas	Western	Coverners Harbour PS	Dach 9 200	TRIargo					Latin Amorica & Caribboan	SA/CA	CA/Carib		No
547			0.000				7/20	0/2001	2007	Danamasan	Danamas	WC3tCIII		Da311-0-000							Asia	Asia-Low-MdLIncome		
548	SCF-NP	xx		0 0 0	0	0 2	6/15	5/2007		First Flight Couriers	India	Western	Chennai, IN	BAE ATP	TP-Large					Asia				No
549	SCF-NP	XX	0.000	0 0 0	0	24 4	8/11	1/2003	2003	Garuda Indonesia	Indonesia	Western	JAKARTA	F-28-3000	Jet	LANDING	ХХ	ХХ	ХХ	Asia	Asia	Asia-Low-Mdl Income		No
550	RI	0	0.000	0 0 0	0	2 7	11/2	29/2003 2	2003	Hydro Air	South Africa	Western	LAGOS	B747-200	Jet	LANDING	ХХ	XX	XX	Africa	Africa	Africa		No
			0.000					2	2008															
551	RE-Landing	XX	<b>5</b> ,000	0 0 0	0	37 3	1/28	8/2008	2000	Aires Colombia	Colombia	Western	Bogota, CO	Dash 8-200	TP-Large			XX	XX	Latin America & Caribbean	SA/CA	SA (Northern)		No
550	Bamp	NY.	0.000				2/4/	2009	2008	Atlantia Airlinga		Mostore	Ediphurah CD	E 27 500	TDLorge					Europe	Europe	EU-EFTA		No
552	Railip PE Landing	XX	0.000	0 0 0	0	0 2	2/1/	2006	2003	Allantic Allines	UK	western	Euliiburgii, GB	F.27-000	IP-Large					Africa	Africa	Africa		INU
555		0.000	0.000	0 0 0	0	40 4	0 12/0	07/03	2005	Air Express	Kenva	Western	Lokichogio KE	Fokker F 28	Jei	Landing - Rollout	XX	No	100	niiua	ninod	Amoa	ADRM	Ves
554	ARC	0.000	0.000		0	94 4	0 12/1	13/03	2003	Nuevo Continente	Peru	Western	Lima, PE	B737 (JT8D)	Jet	Landing	XX	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	X	ves
		1.000	1.000		ľ			1	2003	Lineas Aereas				()						Latin America & Caribbean	SA/CA	SA (Northern)		
555	LOC-I			0 3 3	0	0 3	0 12/1	18/03		Suramericanas	Colombia	Western	(near) Mitu, CO	DC-9	Jet	Descent	хх	No	100			, , , , , , , , , , , , , , , , , , ,	х	yes
			0.000					4	2008												Asia	Asia-Low-Mdl Income		
556	RE-Takeoff	XX		0 0 0	0	57 3	2/19	9/2008	0000	Air Bagan	Myanmar	Western	Putao, MM	ATR-72-210	TP-Large					Asia	04/04	04.01.0		No
557	CEIT	NY.	1.000	12 2 40		12 2	2/24	1/2009	2008	Santa Barbara	Vonozuolo	Mostore	(noor) Morido V/E	ATD 42 200	TDLorge					Latin Amorica & Caribbear	SA/CA	SA (Northern)		No
558	ARC	0.000	0.000			43 3	0 12/1	18/03	2003	FedEx		Western		DC-10	let	Landing	Crosswind	No	100	North America	NA-Car	US-Canada	Y	Ves
559	RE-Landing	0.000	0.000		0	0 9	0 12/1	10/00 2	2003			Testern			Jet	Landing	Rain - T-	110	100	Africa			~	,00
	g			0 0 0	0	125 6	0 12/1	19/03		Air Gabon	Gabon	Western	Libreville, GA	B737 (CFMI)		Landing - Rollout	Storm	Yes	100		Africa	Africa	х	yes
560	RE-Landing	XX	0.000	0 0 0	0	24 3	3/19	9/2008 2	2008	Cirrus Airlines	Germany	Western	Mannheim, DE	Dornier 328	100				100	Europe	Europe	EU-EFTA		No

Accident ID	Category Definition	Severity (Portion ) People c Board Fatal)	n (Calculati	n ty Pax. Dead	Crew Dead	Tot Fatal (onBd)	Ser-lous (OnBd) Pax OnBd	Crew OnBd Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigh - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
561	RE-Takeoff	0.865	0.873	136	6 5 1	41 22	153 1	10 0	12/25/03	2003	UTA Guinee	Guinee	Western	Cotonou, BJ	B727	Jet	T/O Run	XX	No	100	Africa	Africa	Africa	Х	yes
562	LOC-I	1.000	1.000	141	7 1	48 0	141 7	7 0	01/03/04	2004	Flash Airlines	Egypt	Western	off Sharm-el-Sheikh, EG	B737 (CFMI)	Jet	T/O Initial Climb	XX	No	100	Africa	Africa	NoAfr/MidEast	Automation	yes
563	SCF-NP	0	0.000	0	0 0	0	154 2	26	1/15/2004	2004	Iran Air	Iran	Western	BEIJING	B747-SP	Jet	LANDING	XX	XX	XX	Middle East	MIDDLE EAST	NoAfr/MidEast		No
564	RE-Landing	YY	0.000	0	0 0	0	0 4	4	4/29/2008	2008	Blue Bird Aviation	Kenva	Western	Waiir KF	Eokker 50	TP-I arne					Africa	Africa	Africa		No
001			1 000	- Ŭ		ľ		<u> </u>	1/20/2000	2008	Southern Sudan Air		110010111	110jii, 10		TT Largo				_	7 11100	Africa	Africa		
EGE	1001	1	1.000	10			10		E/2/2000	2000	Connection	Sudan	Western	(near) Rumbal CD	DE 10000						Africa	Ainea	Allica		No
505	100-1	0.000	0.000	19	2 2	1 0	19 2	2	5/2/2000	0004	Delvieter	Suuan	western	(fiear) Ruffiber, SD	DE-1900C	TF-SIIIdii				_	Allica	Asia	A significant Mall Incomes		INU
		0.000	10.000							2004	Pakislan										Asia	Asia	Asia-Low-wai income		
566	SCF-NP			0	0 0	0	261 1	12 0	03/01/04		International Airlines	Pakistan	western	Jeddan, SA	Airbus A300	Jet			NO	100				х	yes
567	SCF-NP	0.000	0.000	0	0 0	0	0 /	/  0	04/02/04	2004	Air Memphis	Egypt	Western	Cairo, EG	B/0/	Jet			No	100	Africa	Africa	NoAfr/MidEast	х	yes
568	RI	0	0.000	0	0 0	0	82 6	6	4/20/2004	2004	Alitalia	Italy	Western	TRIESTE	MD-82	Jet	TAXI	XX	XX	XX	Europe	Europe	EU-EFTA		No
		0.000	0.000							2004											North America	NA-Car	US-Canada		
569	RE-Landing A	RC		0	0 0	0	0 3	3 0	04/28/04		Centurion Air Cargo	USA	Western	Bogota, CO	DC-10	Jet			No	100				Х	yes
570	WSTRW	0.000	0.001	0	0 0	1	53 4	4 0	07/21/04	2004	Aerocalifornia	Mexico	Western	Mexico City, MX	DC-9	Jet			No	100	Latin America & Caribbean	SA/CA	CA/Carib	х	ves
571	RE-Takeoff	0.000	0.000	0	0 0	0	116 8	8 0	08/11/04	2004	Air Guinee Express	Guinee	Western	Freetown, SL	B737 (JT8D)	Jet			No	100	Africa	Africa	Africa	Х	ves
-		0.000	0 000	-		-		-		2004	Trans Air Cargo			, .	- ( /						Africa	Africa	Africa		,
572	RE-Landing	0.000	0.000	0	0 0	0	0 3	3 0	08/28/04		Services	Swaziland	Western	Gisenvi RW	Aerospatiale Caravello	let			No	100				Y	Ves
512		_	0.029	- 0	0 0				00/20/04	2000	TAM Transporto	Owazilaliu	WCOLCIII	70nm from Cuovoromorin		JCI			NO	100				^	ycs
570			0.020	1			22		00001000	2000	Aaroo Militor	Delivie	Western		E 27 400	TDLorgo	CLIMD				Latin Amarica & Caribbaan		CA Morecour		No
5/3	SCF-PP	XX			0 1	0	32 4	4	1/23/2008	0000	Aereo Militar	Bolivia	western	во	F.27-400	TP-Large	CLIMB			_	Latin America & Caribbean		SA Wercosur		INO
			1.000							2008												Africa	Africa		l
574	CEII	XX		0	3 3	0	0 3	3	8/13/2008		Fly540	Sudan	Western	Mogadishu, SO	F.27-500RF	TP-Large	Approach				Africa				NO
		0.000	0.003							2004	Biman Bangladesh					Jet					Asia	Asia	Asia-Low-Mdl Income		
575	RE-Landing A	RC		0	0 0	4	83 4	4 0	10/08/04		Airlines	Bangladesh	Western	Sylhet, BD	Fokker F.28				No	100				х	yes
		1.000	1.000							2004	MK dba British										Africa				
576	RE-Takeoff			0	7 7	0	0 7	7 0	10/14/04		Global	Ghana	Western	Halifax. CA	B747	Jet			No	100		Africa	Africa	х	ves
577	SCF-NP	0.000	0.000	0	0 0	0	0 3	3 0	10/23/04	2004	Beta Cargo	Brazil	Western	Manaus, BR	B707	Jet			No	100	Latin America & Caribbean	SA/CA	SA Mercosur	х	ves
			0.000	-		-		-		2008															7
578	2021	VV V	0.000	0			12 2	2	0/13/2008	2000	MASWings	Malaysia	Western	Ba Kelalan MV		TP_Small	Annroach				Δsia				No
570	DE Tekeeff	0.000	0.000	0			0 12	4 0	11/07/04	2004	Lufthanaa Cargo	Cormonu	Western	Shariah AF	DTI0-0-300	Int-Official	Approach		No	100	Furana	Furana		v	110
579	RE-Idkeuli	0.000	0.000	0	0 0	0		+  0	11/07/04	2004	China Vunnan	Germany	western	Shaljah, AE	D/4/	Jet			INU	100	Luiope		EU-EFIA	X O amound	yes
500		1.000	1.000						11/04/04	2004						Jet				100	Asia	Asia	Asia-Low-Ividi Income	2 ground	
580	LUC-I			47	6 5	3 0	47 6	0 2	11/21/04	10000	Airlines	China	vvestern	Baotou, CN	CRJ Regional Jet				NO	100	-			tatal	yes
		0.000	0.000							2004	KLM Royal Dutch										Europe	Europe	EU-EFTA		
581	SCF-NP			0	0 0	0	140 6	6 0	11/28/04		Airlines	Neder	Western	Barcelona, ES	B737 (CFMI)	Jet			No	100				Х	yes
			0.950							2008												Asia	Asia-Low-Mdl Income		
582	USOS	XX		16	2 1	8 1	16 3	3	10/8/2008		Yeti Airlines	Nepal	Western	Lukla, NP	DHC-6-300	<b>TP-Small</b>	Approach				Asia				No
		0.153	0.174							2004											Asia	Asia	Asia-Low-Mdl Income		
583	RE-Landing A	RC		23	2 2	5 59	156 7	7 0	11/30/04		Lion Air	Indonesia	Western	Solo, ID	MD-80	Jet			No	100				х	ves
	, i i i i i i i i i i i i i i i i i i i		0.000							2008													Asia-Low-Mdl Income		
584	USOS	XX		0	0 0	0	32 4	4	11/6/2008		Express Air	Indonesia	Western	Fak Fak, ID	Dornier 328	TP-Small					Asia	Asia			No
585	RI-A	0	0.000	0	0 0	0	0 4	4	1/3/2005	2005	Asia Airlines	Indonesia	Western	BANDAACEH	B737-200	Jet	LANDING	XX	XX	xx	Asia	Asia	Asia-Low-MdLIncome		No
000			0.000	0	1 U	- V		·  -	10.2000	2008					2.01 200						North America				
596	ARC	VV	0.000	0			4	2	11/27/2000	2000	Northwootorn Air	Canada	Western	Fort Smith CA	lototroom 21				NV.	VV	North America	NA Cor	US Canada		No
500		AA	0.000	0	0 0	0	4 4	4 0	01/04/05	2005		Indenesia	Western	Pende Asek ID		IF-OINdi			AA No	100	Asia	Asia			NO
587	RI-A	0.000	0.000	0	0 0	0	0 4	4 0	01/04/05	2005		Indonesia	western	Banda Acen, ID	B/3/ (J18D)	Jei			INO	100	Asia	ASIa	Asia-Low-ividi Income	x	yes
		0.000	0.000							2005	AeroRepublica										Latin America & Caribbean	SA/CA	SA (Northern)		
588	ARC			0	0 0	0	106 6	0 0	01/08/05		Colombia	Colombia	Western	Call, CO	MD-80	Jet			No	100				Х	yes
589	RE-Landing	0	0.000	0	0 0	0	0 3	3	1/24/2005	2005	Atlas Air	USA	Western	DUSSELDORF	B747-200	Jet	LANDING	XX	XX	XX	North America	NA-Car	US-Canada		No
590	Ramp	0.01	0.000	0	1 1	0			2/1/2005	2005	Air France	France	Western	PARIS	A319	Jet	PARKED	XX	XX	XX	Europe	Europe	EU-EFTA		No
591	CFIT	1.000	1.000	98	6 1	04 0	98 6	6 0	02/03/05	2005	Kam Air	Afghanistan	Western	Afghanistan	B737 (JT8D)	Jet			No	100	Asia	Asia	ASIA CEN	Х	yes
		0.000	0.000							2005	Cargo Plus Aviation										Africa	Africa	Africa		
											dba Rainbow Air														
592	CFIT			0	0 0	0	0 5	5 0	03/19/05		Cargo	Ethiopia	Western	(near) Kampala UG	B707	Jet			No	100				х	ves
		0.000	0.001		0	,			00/10/00	2005	00.90				5.0	let				100	Latin America & Caribbean	SA/CA	SA (Northern)	~	,
593	USOS	0.000	0.001	0	0 0	1	61 4	4 0	04/07/05	2005	ICARO Air	Ecuador	Western	Coca, EC	Fokker F.28	001			No	100				Х	yes
594	GCOL	0.000	0.001	0	0 0	1	5 9	94 0	05/10/05	2005	Northwest	USA	Western	Minneapolis, US	DC-9	Jet			No	100	North America	NA-Car	US-Canada	Х	yes
		0.000	0.000							2005	Biman Bangladesh										Asia	Asia	Asia-Low-Mdl Income		
595	RE-Landing			0	0 0	0	201 1	14 0	07/01/05		Airlines	Bangladesh	Western	Chittagong, BD	DC-10	Jet			No	100				Х	yes



Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculatior	Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor	? Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
		1	0.000	0.000						4	2005											Europe	Europe	EU-EFTA		
596	RE-Landing	ARC			0 0	0	0	297 12	0 08	3/02/05		Air France	France	Western	Toronto, CA	Airbus A340	Jet			No	100				Х	yes
597	OTHER		1.000	1.000	115 6	121	0	115 6	0 08	3/14/05	2005	Helios	Greece	Western	(near) Grammatikos, GR	B737 (CFMI)	Jet			No	100	Europe	Europe	EU-EFTA	Х	yes
			1.000	1.000						4	2005	West Caribbean										Latin America & Caribbean	SA/CA	SA (Northern)		
598	LOC-I				152 8	160	0	152 8	0 08	3/16/05		Airways	Colombia	Western	(near) Machiques, VE	MD-80	Jet			No	100				Х	yes
599	SCF-NP		0	0.000	0 0	0	0	318 16	8/1	19/2005	2005	Northwest Airlines	USA	Western	GUAM	B747-200	Jet	LANDING	XX	XX	XX	North America	NA-Car	US-Canada		No
600	CHI		0.408	0.408	35 5	40	0	91 7	0 08	3/23/05	2005	IANS	Peru	Western	(near) Pucalipa, PE	B737 (J18D)	Jet	Approach	I-Storm	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	X	yes
		ľ	1.000	1.000						4	2005											Asia	Asia	Asia-Low-Mdl Income	44 Ground	
601	LOC-I	100		0.000	99 5	104	0	99 5	# 09	3/05/05	0005	Mandala Airlines	Indonesia	Western	Medan, ID	B/37 (J18D)	Jet			NO	100		A	A 1 1 M H I	fatal	yes
602	RE-Landing	ARC	•	0.000							2005	O ale and the disc Airdin as	la d'a	Martana	DOMDAY	D707 400	1.4					A . ! .	Asia	Asia-Low-Mdl Income		N.
000			0	1 000	0 0	0	0	113 8	10	J/9/2005	0005	Sanara India Airlines	India	western		B737-400	Jet	LANDING	XX	XX	XX	Asia	Africa	Africa		NO
603	UNK DE Londing		0.000	0.000		117	0		0 10	JIZZIUS 74	2005	Beliview Ainines	INIGERIA	Western	(near) Lissa, NG	B/37 (JI8D)	Jet			INO No	100	Africa	Africa	Africa	X	yes
004 605	RE-Landing		0.000	0.000		0	0		0 10		2005	MIBA AVIALION	Dhilippingo	Western	NIIIUU, ZR	D/2/	Jel			INO No	100	Allica	Allica	Allica	X	yes
600	RE-Landing		0.000	0.000	0 0	0	0	32 0	0 11	14/00	2005	Asian Spint	Philippines	western			Jel		Chow	INO	100	ASia North Amorico	Asia	Asia-Low-Ividi Income	X	yes
000	RE-Lanuing		0.000	0.000		0	0	09 5	1 00	2/12/2005	2005	Southwoot	1104	Westorn	Chicago Midway	P727 700	lot	Landing Pollout	froozing for		70	NULII AMERICA	NA Cor	LIS Canada		WOO
607	20211		0 001	0 001	101 7	108	1	102 7	0 12	0/10/05	2005	Socolico Airlines	Nigeria	Western	Port Harcourt NG			Lanuing - Ronout		No	100	Africa	NA-Odi Africa	Africa		yes
608	RE-Landing		0.991	0.991		100	0	138 6	3//	4/2006	2005	Lion Air	Indonesia	Western	SURABAVA	MD_82			vv		100		Δείο	Asia-Low-Mdl Income	^	No
600			9 000	1 000	105 8	113	0	105 8	0 05	5/03/06	2000		Armenia	Western	off Sochi RU				^^	No	100		Furone	Furo East	v	Ves
610	RE-Landing		0.000	0.000	0 0	0	0	0 3	0 06	5/04/06	2006	Arrow Cargo	USA	Western	Managua NI	DC-10	Jet			No	100	North America	NA-Car	US-Canada	x x	Ves
611	RE-Takeoff		0.000	0.000		0	0	0 5	0 06	6/07/06	2006	TradeWinds Airlines	USA	Western	Medellin CO	B747	Jet			No	100	North America	NA-Car	US-Canada	x	ves
612	USOS		0.000	0.000	0 0	0	0	0 2	0 06	6/15/06	2006	TNT Airways	Belaium	Western	Birmingham, GB	B737 (CFMI)	Jet			No	100	Europe	Europe	EU-EFTA	X	ves
613	RE-Landing		0	0.000	0 0	0	0	14 10	6/2	23/2006	2006	AMC Aviation	Eavot	Western	JUBA	MD-83	Jet	LANDING	XX	XX	XX	Africa	AFRICA	NoAfr/MidEast		No
614	RE-Landing		0.616	0.627	120 5	125	41	195 8	0 07	7/09/06	2006	S7 Airlines	Russia	Western	Irkutsk. RU	Airbus A310	Jet			No	100	CIS	Europe	Euro East	Х	ves
615	SCF-NP		0.000	0.000	0 0	0	0	0 3	0 07	7/28/06	2006	FedEx	USA	Western	Memphis, US	DC-10	Jet			No	100	North America	NA-Car	US-Canada	Х	ves
616	SCF-NP		0.000	0.000	0 0	0	0	0 3	0 08	3/17/06	2006	Aerosucre Colombia	Colombia	Western	Bogota, CO	B727	Jet			No	100	Latin America & Caribbean	SA/CA	SA (Northern)	Х	yes
617	RE-Takeoff		0.980	0.981	47 2	49	1	47 3	0 08	3/27/06	2006	Comair	USA	Western	Lexington, US	CRJ Regional Jet	Jet			No	100	North America	NA-Car	US-Canada	Х	yes
618	RE-Landing		0.000	0.000	0 0	0	0	0 3	0 09	9/07/06	2006	DHL Aviation	So Africa	Western	Lagos, NG	B727	Jet			No	100	Africa	Africa	Africa	Х	yes
			1.000	1.000						1	2006				(near) Peixote Azevedo,							Latin America & Caribbean	SA/CA	SA Mercosur		ŕ
<mark>619</mark>	MIDAIR				148 6	154	0	148 6	0 09	9/29/06		GOL Linhas Aereas	Brazil	Western	BR	B737 (NG)	Jet			No	100				х	yes
620	RE-Landing		0.000	0.000	0 0	0	0	104 6	0 10	)/03/06	2006	Mandala Airlines	Indonesia	Western	Tarakan, ID	B737 (JT8D)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
			0.250	0.272						4	2006	Atlantic Airways					Jet					Europe				
621	RE-Landing				3 1	4	6	13 3	0 10	0/10/06		(Faroe Islands)	Faroe Islands	Western	Stord, NO	HS 146				No	100		Europe	EU-EFTA	Х	yes
622	WSTRW		0.914	0.919	92 4	96	8	100 5	0 10	)/29/06	2006	ADC Airlines	Nigeria	Western	Abuja, NG	B737 (JT8D)	Jet			No	100	Africa	Africa	Africa	Х	yes
623	RE-Landing		0.000	0.000	0 0	0	0	4 3	0 11	/17/06	2006	Cielos Airlines	Peru	Western	Barranquilla, CO	DC-10	Jet			No	100	Latin America & Caribbean	SA/CA	SA (Northern)	X	yes
624	CFIT		1.000	1.000	2 3	5	0	2 3	0 11	/18/06	2006	Aerosucre Colombia	Colombia	Western	(near) Leticia, CO	B727	Jet			No	100	Latin America & Caribbean	SA/CA	SA (Northern)	Х	yes
625	ARC		0.000	0.000	0 0	0	0	157 7	0 12	2/24/06	2006	Lion Air	Indonesia	Western	Ujung Pandang, ID	B737 (CFMI)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
626	LOC-I		1.000	1.000	96 6	102	0	96 6	0 01	1/01/07	2007	Adam Air	Indonesia	Western	off Makassar, ID	B/37 (CFMI)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
007	11000		0.000	<sup>.</sup> 0.000						40/07	2007	Gading Sari Aviation	Malauria	14/	Kuching MV		1.4			N.,	100	Asia	Asia	Asia-Low-Mdl Income		
627	0505		0.000	0.000	0 0	0	0	0 4	0 01	1/13/07	0007	Services	Ivialaysia	vvestern	Kuching, MY	B131 (JI8D)	Jet			NO	100	Furene	Furene		X 1. Oracumal	yes
000	DE Tekee"		0.000	0.000				50 4	1 04	105/07	2007	Designal	France	Mastar		Falling 100	let.			No	100	Europe	Europe	EU-EFTA	r Ground	
620	RE-TAKEOT		0	0.000	0 0	0	0	0 2	1 01	4/2007	2007	Tempo Corco	Colombia	Western	Pau, FR		Jet		N/V	INO	100	Latin America & Caribbear	SV/CV	CA (Northorn)	19(9)	yes
029 630	ARC		0 000	0.000		0	0	148 6	0 02	4/2007	2007	Adam Air		Western	Surahava ID	B737 (CEMI)	Jei	LANDING	XX	XX No	100	Laun America & Canobean	SA/GA	SA (NOITHEITI)	Y	
000			0.000	0.000		0	0		0 02		2007	Auditi Ali	Induncoid	THE SIGHT	ourabaya, ib		001			NO	100	Asid	Asia	Asid-Low-War Income	^	yeo

Accident ID	Category Definition	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	, Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
631	RE-Landing	ARC 0.150	0.155							2007											Asia	Asia	Asia-Low-Mdl Income		
			<b>D</b> 000	20 1	1 21	12	133 7	0 03	3/07/07	2007	Garuda Indonesia	Indonesia	Western	Yogyakarta, ID	B737 (CFMI)	Jet			No	100		Ania		Х	yes
632	Other	0	0.000			0	236 14	3/	/12/2007	2007	Airlines	Bandladesh	Western		A310-325	let		vv	vv	vv	۵sia	Asia	Asia-Low-Ividi Income		No
002	Outor	0.000	0.000				200 14	0/	12/2001	2007	Ariana Afghan	Durigiducom	Webtern	Bobra	/1010 020	000		~~	~~	~~	Asia	Asia	ASIA CEN		
633	RE-Landing			0 0	0 0	0	30 20	0 03	3/23/07		Airlines	Afghanistan	Western	Istanbul, TR	Airbus A300	Jet			No	100				х	yes
634	LOC-I	1.000	1.000	105 9	9 114	0	105 9	0 05	5/05/07	2007	Kenya Airways	Kenya	Western	(near) Douala, CM	B737 (NG)	Jet			No	100	Africa	Africa	Africa	Х	yes
635	ARC	0.000	0.000	0 0	0	0	37 3	0 05	5/20/07	2007	Air Canada Jazz	Canada	Western	Toronto, CA	CRJ Regional Jet	Jet			No	100	North America	NA-Car	US-Canada	X	yes
626	11606	0.063	0.063		1 5	0	74 6	1 06	6/20/07	2007	IAAG - Angola	Angolo	Western	M'Panza Canga AO		lot			No	100	Africa	Africa	Africa	1 Ground	1/00
030	0303	M 000	1 000	4 1	1 5	0	74 0		0/20/07	2007	Airinies	Aliguia	Western	INI Daliza Collyo, AO		JEI				100	Latin America & Caribbean	SA/CA	SA Mercosur	12 Ground	yes
637	RE-Landing	1.000	1.000	181 6	6 187	0	181 6	# 07	7/17/07	2001	TAM Linhas Aereas	Brazil	Western	Sao Paulo, BR	Airbus A320	Jet			No	100				fatal	ves
		0.000	0.000							2007	AeroRepublica										Latin America & Caribbean	SA/CA	SA (Northern)		,
638	RE-Landing			0 0	0 0	0	54 5	0 07	7/17/07		Colombia	Colombia	Western	Santa Marta, CO	EMB 190	Jet			No	100				х	yes
639	SCF-NP	0.000	0.000	0 0	) ()	0	157 8	0 08	8/20/07	2007	China Airlines	Taiwan	Western	Naha, JP	B737 (NG)	Jet			No	100	Asia	Asia	Hi-Income Asia-Pac	Х	yes
640	ARC	0.529	0.529	85 5	5 90	0	40 ##	0 09	9/16/07	2007	One-Two-Go	Thailand	Western	Phuket, TH	MD-80	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	X	yes
641	SCF-NP RE-Landing	10.000	0.000	0 0	J U	U	100 /		0/11/07	2007	AIVIC AIRINES	Тигкеу	western	istandul, IR	IVID-80	Jet			INO	100	Europe Asia	Lurope	NOAIT/IVIIdEast	X	yes
042			0.000	0 0		0	148 6	0 10	0/26/07	2001	Philippine Airlines	Philippines	Western	Butuan City PH	Airbus A320	let			No	100	~3ia	noia		x	Ves
643	ARC	0.000	0.000	0 0		0	89 5	0 11	1/01/07	2007	Mandala Airlines	Indonesia	Western	Malang, ID	B737 (JT8D)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	x	ves
644	ARC	0.000	0.000	0 0	0 0	0	335 14	0 11	1/09/07	2007	Iberia	Spain	Western	Quito, EC	Airbus A340	Jet			No	100	Europe	Europe	EU-EFTA	х	yes
		1.000	1.000							2007											Europe	Europe	NoAfr/MidEast		
											World Focus Airlines														
645	CFIT		<b>D</b> 000	50 7	7 57	0	50 7	0 11	1/30/07	0007	dba Atlasjet Airlines	Turkey	Western	(near) Isparta, TR	MD-80	Jet			No	100				Х	yes
646	RI	0.000	0.000	0 0		0	117 6	0 12	2/30/07	2007		Romania	Western	Bucharest, RO	B/37 (CFMI)	Jet		201	NO	100	Europe Middle Feet		EURO East	X	yes
648	EUC-I EUEI	0	0.000			1	137 16	1/2	12/2006	2008	Rritish Ainways	I Inited Kingdom	Western		B777-200				XX VV	XX VV	Furone		FLIFETA		No
0+0	IULL	0	0.000						111/2000	2008	Dittion Aliways	Onited Ringdom	Western	LONDON	D111-200						Luiope	LATIN AMERICA &			
649	FUEL	0		0 0	0 0	0	159 8	2/	/1/2008		LAB	Bolivia	Western	Near Trinidad	B727-200	Jet	FINAL APPROACH	хх	xx	xx	Latin America & Caribbean	CARIBBEAN	SA Mercosur		No
650	Other	0	0.000	0 0	0 0	0	0	2/2	/2/2008	2008	Atlas Air	USA	Western	LOME	B747-200FM	Jet	INITIAL CLIMB	XX	ХХ	ХХ	North America	NA-Car	US-Canada		No
651	ICE	XX	0.027	0 0	0 (	10	18 3	2/	/14/2008	2008	Belavia	Belarus	Western	Yerevan, AM	CRJ-100	Jet					CIS	CIS	Euro East		No
652	SCF-NP	0	0.000	0 0	) ()	0	5 3	3/	/6/2008	2008	Manunggal Air	Indonesia	Western	Wamena, ID	Transall C-160	Jet					Asia	Asia	Asia-Low-Mdl Income		No
653	ARC	0	0.000	0 0		0	169 5	3/	10/2008	2008	Adam Air	Indonesia	Western	IBAIAM, BAIU BESAR	B/3/-400	Jet		XX	XX	XX	Asia Middle Feet		Asia-Low-Mdl Income		NO
655	SCF-NP RE-Takeoff	0 17//10	0.000	15 0	) 15	0	70 7	3/1	125/2008	2008	Saudia Hewa Bora Ainways	Saudi Arabia	Western		B747-300	Jet		XX	XX	XX	Africa		Africa		NO No
656	RE-Landing	0.174413	0.213		$\frac{1}{10}$	00	67 6	4/	/13/2000	2008	Carnatair	Romania	Western	BUCHAREST	BAe 146-200	Jet		XX	××	××	Furone	Furone	Furo Fast		No
657	RE-Takeoff	0	0.000	0 0		0	0 5	5/	/25/2008	2008	Kalitta Air	USA	Western	BRUSSELS	B747-200FM	Jet	TAKEOFF	XX	XX	XX	North America	NA-Car	US-Canada		No
658	RE-Landing	ARC	0.047							2008	TACA International														
		0.021739		2 1	1 3	60	131 7	5/3	/30/2008		Airlines	El Salvador	Western	TEGUCIGALPA	A320-200	Jet	LANDING	хх	ХХ	ХХ	Latin America & Caribbean	SA/CA	CA/Carib		No
659	RE-Landing	ARC	0.131							2008												Africa	Africa		
000		0.125	<b>F</b> D 000	32 1	1 33	27	252 12	6/	/10/2008	2000	Sudan Airways	Sudan	Western		A310-300	Jet		XX	XX	XX	Africa	NA Car	LIC Canada		No
661	CEIT	0.5	0.000		1 1	0	0 2	0/2	12012008	2008	ADA All		Western		DC-9-15	Jet		XX		XX	North America	NA-Gar	US-Canada		No
001		0.5	0.023				0 2		012000	2008	Kallitta as Centurion		western		00-0-10	Jei		~~	~~	~~	North America	nn-oai	00-0anaud		
662	SCF-PP	0	J.J.L	0 0	0 0	3	0 8	7/	/7/2008	2000	Air Cargo	USA	Western	(near) BOGOTA	747-200FM	Jet	INITIAL CLIMB	xx	xx	xx		NA-Car	US-Canada		No
663	RE-Landing	ARC	0.000							2008	Ŭ Ŭ														
		XX		0 0	0 (	0	41 6	7/	/14/2008		Chanchangi Airlines	Nigeria	Western	Port Harcourt, NG	B737-200	Jet					Africa	Africa	Africa		No
664	LOC-I	0.895349	0.901	148 6	6 154	18	166 6	8/3	/20/2008	2008	Spanair	Spain	Western	MADRID	MD-82	Jet	TAKEOFF	XX	XX	XX	Europe	Europe	EU-EFTA		No
605	CEIT	0 700000	U./38	65	0 65	25	04	0.4	124/2000	2008	AirCompony	Kurauzatan	Mastar	International Airmort	P727 200	lot		NV	NY		CIS	CIE	ASIA CEN		No
000	UFII	0.122222		00 10	00	120	04 0	0/1	24/2000		AirCompany	ryryyzsian	western	International Allport	0131-200	Jei		^^	172	172		00			NU



Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column Serverity (Calculatio	Pax. Dead	Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
666	RE-Landing		0	0.007	0	0 0	0 1	6	123 6	8/	/27/2008	2008	Sriwijaya Air	Indonesia	Western	JAMBI	B737-200	Jet	LANDING	xx	XX	XX	Asia	Asia	Asia-Low-Mdl Income		No
667	LOC-I		1	1.000	82	6 8	88 0	)	82 6	9/	/14/2008	2008	Aeroflot-Nord	Russia	Western	Near Perm, Russia	B737-500	Jet	INITIAL APPROACH	xx	XX	XX	CIS	CIS	Euro East		No
				0.003								2008												LATIN AMERICA &			
668	RE-Takeoff		xx		0	0 0	0 3	;	62 4	9/	/22/2008		ICARO	Ecuador	Western	QUITO	F-28-4000	Jet	TAKEOFF	xx	xx	xx	Latin America & Caribbean	CARIBBEAN	SA (Northern)		No
669	ARC		0	0.000	0	0 (	0 0	)	138 6	10	0/1/2008	2008	Kaliningradavia	Russia	Western	KALININGRAD	B737-300	Jet	LANDING	xx	XX	хх	CIS	CIS	Euro East		No
670	RE-Landing	ARC		0.000								2008												SA/CA	SA (Northern)		
			0		0	0 0	0 0	)	47 7	10	0/16/2008		Rutaca	Venezuela	Western	CARACAS	B737-200	Jet	LANDING	xx	xx	xx	Latin America & Caribbean				No
671	Other-Bird		0	0.000	0	0 0	0 0	)	166 6	11	1/10/2008	2008	Ryanair	Ireland	Western	ROME	B737-800	Jet	FINAL APPROACH	xx	XX	XX	Europe	Europe	EU-EFTA		No
672	RE-Takeoff		0	0.002	0	0 0	0 5		110 5	12	2/20/2008	2008	Continental Airlines	USA	Western	DENVER	B737-500	Jet	TAKEOFF	XX	XX	XX	North America	NA-Car	US-Canada		No

Accident ID	Category Definition	sviously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Fatal (onBd)	ү r-ious (OnBd)	Pax OnBd	<ul> <li>Trew OnBd</li> <li>Other Fatal</li> </ul>	Date	Yea	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
680	LOC-I		0.982	0.982	38 1	2 50	1	39	12 0	03/01/198	37 1987	Varig	Brazil	Western	Abidjan, Ivory Coast	B707	Jet	T/O Climb to Cruise	XX	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
681	RE-Takeoff			0.000				21		06/01/198	1987 37	Braathens Sverige AB	Sweden		Stockholm	Caravelle-	Jet	TAKEOFF				Europe	EUROPE	Sweden	HULL LOSS	ASEDB
682	SCF-NP			0.000			1	167		12/02/198	37	Conair A/S	Denmark		SALZBURG	720-518	Jet	LANDING				Europe	EUROPE	Denmark	HULL LOSS	ASEDB
683	ARC			0.000				102		23/02/198	1987 37	SAS	Sweden		TRONDHEIM	DC-9-41	Jet	LANDING				Europe	EUROPE	Sweden	HULL LOSS	ASEDB
684	USOS		0.623	0.623	23 4	27	18	37	8 0	04/04/198	87 1987	Garuda	Indonesia	Western	Medan, Sumatra, Indonesia	DC-9	Jet	Landing - Approach	T-Storm	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
685	SCF-NP			0.000						06/04/198	1987 37	Conair A/S	Denmark		ROME	720-051B	Jet	LANDING				Europe	EUROPE	Denmark	HULL LOSS	ASEDB
686	RE-Landing			0.000						11/04/198	71987 87	Transbrasil	Brazil		MANAUS	707-330C	Jet	LANDING				Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	Brazil	HULL LOSS	ASEDB
687	CFIT		1	1.000	0 4	4	0	0	4 0	13/04/198	37 1987	Buffalo	USA	Western	KCI	B707	Jet	Landing - Approach	Fog	No	100	North America	NA-Car	US-Canada	Х	yes
688	ADRM		0.492	0.492	1 0	1	34	0	6 0	04/08/198	37 1987	LanChile	Chile	Western	Calama, CL	B737	Jet	Landing - Rollout	XX	No	100	Latin America & Caribbean	SA/CA	Asia-Low-Mdl Income	Х	yes
689	Other			0.003	1	1		324		11/08/198	87 1987	All Nippon Airways	Japan		WASHINGTON	747-200	Jet	PARKED				Asia	ASIA (EX CHINA)	Japan	NONE	ASEDB
690	LOC-I		0.994	0.994	148 6	154	1	149	6 1	16/08/198	37 1987	Northwest	USA	Western	Romulus	DC-9	Jet	T/O Initial Climb	XX	No	100	North America	NA-Car	US-Canada	1 Ground fatal	yes
691	LOC-I		1	1.000	74 9	83	0	74	9 0	31/08/198	37 1987	Tahi Int	Thailand	Western	Phuket, Thailand	B737	Jet	Landing - Approach	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
692	ICE		0.361	0.361	25 3	28	28	77	5 0	15/11/198	87 1987	Continental	USA	Western	DEN	DC-9	Jet	T/O Initial Climb	Snow	No	100	North America	NA-Car	US-Canada	Х	yes
693	FIRE-NI		1	1.000	140 1	9 159	0	140	19 0	28/11/198	87 1987	South African Airways	So Africa	Western	134nm NE of Mauritius, MU	B747	Jet	En Route	ХХ	No	100	Africa	Africa	Africa	x	yes
694	ARC		0	0.000	0 0	0	0	98	5 0	27/12/198	37 1987	Eastern	USA	DC-9	Pensacola, Fla	B727	Jet	Landing - Rollout	Wind, Echo	No	100	North America	NA-Car	US-Canada	Х	yes
695	CFIT		1	1.000	11 5	16	0	11	5 0	02/01/198	88 1988	Condor	Germany	Western	Izmir, Turkey	B737	Jet	Initial Descent	Rain	No	100	Europe	Europe	EU-EFTA	Х	yes
696	CFIT		1	1.000	11 4	15	0	11	4 0	27/02/198	38 1988	Talia Air	Turkey	Western	No. Cyprus	B727	Jet	Landing - Approach	Fog	No	100	Europe	Europe	NoAfr/MidEast	Х	yes
697	CFIT		1	1.000	137 6	143	0	137	6 0	17/03/198	38 1988	Avianca	Colombia	Western	Cucuta, CO	B727	Jet	T/O Climb to Cruise	Fog	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	Х	yes
698	LOC-I		1	1.000	0 4	4	0	0	4 0	31/03/198	88 1988	ARAX Airlines	Egypt	Western	Cairo, EG	DC-8	Jet	T/O Initial Climb	XX	No	100	Africa	Africa	NoAfr/MidEast	Х	yes
699	SCF-NP		0.01	0.010	0 1	1	0	96	7 0	28/04/198	88 1988	Aloha	USA	Western	Maui	B737	Jet	En Route	XX	No	100	North America	NA-Car	US-Canada	Х	yes
700	RE-Takeoff			0.000			2	240		21/05/198	1988 38	American Airlines	USA		DALLAS	DC-10	Jet	TAKEOFF				North America	NA-Car	USA	HULL LOSS	ASEDB



Category	a K Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal	÷ ۱	Year Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
701 RE-Takeoff	ff	0.002	0.002	0 0	0	1	16 9	0 23/05/1	988 1	988 LACSA	Honduras	Western	San Jose, CR	B727	Jet	T/O Run	XX	Yes	100	Latin America & Caribbean	SA/CA	CA/Carib	Х	yes
702 CFIT	1	1	1.000	15 7	22	0	15 7	0 12/06/1	988 1	988 Austral	Argentina	Western	Posadas, Argentina	MD-81	Jet	Landing - Approach	Fog	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
703 CFIT	1	1	1.000	0 6	6	0	0 6	0 21/07/1	988 1	988 TAAG (Angola Air	Angola	Western	Lagos, NG	B707	Jet	Approach	XX	XX	100	Africa	Africa	Africa		
										Charter)													х	yes
704 SCF-PP	(	0	0.000	0 0	0	0	260 15	0 24/07/1	988 1	988 Air France	France	Western	Delhi, IN	B747	Jet	Landing - Rollout	XX	No	91	Europe	Europe	EU-EFTA	Х	yes
			0.000						7	988										North America				
705 SCF-NP							7	27/08/1	988	TWA	USA		CHICAGO	727-100	Jet	LANDING					NA-Car	USA	HULL LOSS	ASEDB
706 USOS	(	0.081	0.081	1 6	7	13	89 7	0 31/08/1	988 1	988 CAAC	China	Western	Hong Kong	Trident-2	Jet	Landing - Approach	Rain-Wind	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
707 LOC-I		0.144	0.143	12 2	14	26	101 7	0 31/08/1	988 1	988 Delta	USA	vvestern	DFW	B/2/	Jet	T/O Aborted	XX	NO	100	North America	NA-Car	US-Canada	X	yes
708 UTHER-		0.332	0.332	35 0	30	21	104 0	0 15/09/1	966 1	988 Ethiopian AL	Ethiopia	western	Banir Dar, Ethiopia	B/3/	Jet		XX	INO	100	Airica	Airica	Ainca	V	100
700 PE Landing		0	0.000	0 0	0	0	56 6	0 26/00/1	099 1	088 Aarolinoas	Argonting	Western	Llehuaia AP	P737	lot	Landing Pollout	Wind	No	100	Latin America & Caribbean	SNICA	SA Moreosur	X	yes
	IS ARC I	0	0.000	0 0	0	0		0 20/09/1	300 1	Argentinas	Aigentina	western	Usiluala, Alt	0101	Jei	Landing - Nollout	WING		100		UNUK		Y	Ves
710 ARC		0	0.000	0 0	0	0	125 7	0 15/10/1	988 1	988 Nigeria Airways	Nigeria	Western	Port Harcourt NG	B737	let	Landing - Rollout	T-Storm	No	100	Africa	Africa	Africa	X	Ves
711 CFIT		0.633	0.633	26 7	32	16	45 7	0 17/10/1	988 1	988 Uganada AL	Uganda	Western	Rome	B707	Jet	Landing - Approach	Fog	No	100	Africa	Africa	Africa	x	ves
712 CFIT		0.986	0.986	127 6	133	2	129 6	0 19/10/1	988 1	988 Indian Airlines	India	Western	Ahmedabad, India	B737	Jet	Landing - Approach	Haze	No	100	Asia	Asia	Asia-Low-Mdl Income	X	ves
713 LOC-I		0.179	0.179	11 1	12	6	65 4	0 25/10/1	988 1	988 Aero Peru	Peru	Western	Juliaca, Peru	Fokker 28	Jet	T/O Initial Climb	XX	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	x	ves
714 FUEL	1	1	1.000	3 5	8	0	3 5	0 13/12/1	988 1	988 GAS Air Nigeria	Nigeria	Western	Luxor, EG	B707	Jet	Initial Descent	Vis	No	100	Africa	Africa	Africa	х	yes
715 SCF-PP		0.407	0.407	47 0	47	74	118 8	0 08/01/1	989 1	989 British Midland	UK	Western	East Midlands, UK	B737	Jet	T/O Climb to Cruise	XX	No	100	Europe	Europe	EU-EFTA	X	yes
716 CFIT	1	1	1.000	137 7	144	0	137 7	0 08/02/1	989 1	989 Independent Air	USA	Western	Azores	B707	Jet	Landing - Initial Descent	Cloud	No	100	North America	NA-Car	US-Canada	Х	yes
			0.000						1	989														
717 RE-Landing	ng ARC						103	09/02/1	989	LAM	Mozambique		LICHINGA	737-200	Jet	LANDING				Africa	AFRICA	Mozambique	HULL LOSS	ASEDB
			0.000						٩	989 Evergreen										North America				
718 Other			1.000	1	1	<u> </u>		09/02/1	989	International A/L	USA		SALI LAKE CITY	DC-9-	Jet	CLIMB			100		NA-Car	USA	NONE	ASEDB
719 CFII	1	1	1.000	0 4	4	0	0 4	0 19/02/1	989 1	989 Flying liger	USA	Western	Malaysia	B/4/	Jet	Landing - Approach	Cloud-fog	No	100	North America	NA-Car	US-Canada	X	yes
720 SCF-NP		0.026	0.026	9 0	9	5	337 18	0 24/02/1	989	989 United	USA	vvestern	HNL Daular Oat	B/4/	Jet	T/O Climb to Cruise	XX	NO	100	North America	NA-Car	US-Canada	X	yes
721 ICE		0.364	0.304	21 3	24	19	05 4	0 10/03/1	989			vvestern	Dryden, Ont	FOKKEF 28	Jet		Snow	INO	100	North America	INA-Car	US-Canada	X	yes
722 LUC-I		1	1.000	0 2	2	0	0 2	U 18/03/1		989 Evergreen	USA	Western	Saginaw, lex	DC-9 P707	Jet	1/U Initial Climb	XX	INO No	100	North America	INA-Gar	US-Canada	X 22 Cround	yes
725 CFI1		1	1.000	0 3	3	ľ		# 21/03/1	909 1		DIAZII	western	540 Paulo	D/V/	Jei	Landing - Approach	XX	INO	100		SAICA	SA Mercosur	Izz Grounu	VOC
724 ARC		0	0.000	0 0	0	0	133 6	0 03/04/1	989 7	989 Faucett	Peru	Western	Iquitos PE	B737	Jet	Landing - Rollout	Rain x-	No	100	Latin America & Caribbean	SA/CA	SA (Northern)		yco
121 / 10		Č	0.000	ľ	ľ	ľ					i olu						wind						x	ves
725 LOC-I	1	1	1.000	2 3	5	0	3 2	2 26/04/1	989 1	989 Aerosucre Colombia	Colombia	Western	Barranguilla, CO	Caravelle	Jet	T/O Initial Climb	XX	Yes	100	Latin America & Caribbean	SA/CA	SA (Northern)	2 Ground	,
																						, ,	fatal	yes
726 RE-Takeoff	ff (	0	0.000	0 0	0	0	69 8	0 17/05/1	989 1	989 Somali Airlines	Somalia	Western	Nairobi, KE	B707	Jet	T/O Aborted	Heavy Rain	No	100	Africa	Africa	Africa	Х	yes
727 CFIT	(	0.954	0.954	169 9	178	7	178 9	0 07/06/1	989 1	989 Surinam Awy	Surinam	Western	Paramaribo, Surinam	DC-8	Jet	Landing - Approach	XX	No	100	Latin America & Caribbean	SA/CA	CA/Carib	Х	yes
			0.000						1	989														
728 RE-Landing	ng						66	11/07/19	989	Kenya Airways	Kenya		ADDIS ABABA	707-351B	Jet	LANDING				Africa	AFRICA	Kenya	HULL LOSS	ASEDB
729 SCF-PP	(	0.387	0.387	111 1	112	46	285 11	0 19/07/1	989 1	989 United	USA	Western	Sioux City	DC-10	Jet	Landing - Approach	XX	No	100	North America	NA-Car	US-Canada	Х	yes
			0.000						F1	989					1							D		
730 RE-Landing	ng	0.000	0.000	00 4	70	0	91	21/07/1	989	Philippine Airlines	Philippines	Ma stars	MANILA	BAC 1-11-500	Jet	LANDING	<b>F</b>	N	400	Asia	ASIA (EX CHINA)	Philippines	HULL LOSS	ASEDB
731 CFII		0.362	0.362	68 4	12	0	181 18	6 2//0//1	989 1	989 Korean Air	Korea	vvestern	Ппроп, Кіруа	DC-10	Jet	Landing - Approach	⊢og	INO	100	Asia	Asia	Asia-Low-Ividi Income	6 Ground	1/00
			0.000		_	-			P	989											LATIN AMERICA &		Ididi	yes
732 RE-Landing	na		0.000	0 0	0	0		10/08/1	989	Apisa Air Cargo	Peru		IQUITOS	DC-8-33F	Jet					Latin America & Caribbean	CARIBBEAN	Peru	HULLOSS	ASEDB
	.0		0.000		0	0	59 6	0 16/08/1	080 1			Western	San Carlos de Bariloche	Fokker F 28	Jet	T/O Run	Snow -		100	Latin America & Caribbean	SA/CA	SA Mercosur		
733 RF-Takeoff	ff	0.008	10.008	10 10		13		0 10/00/1	303 1															
733 RE-Takeoff	ff	0.008	0.008	0 0	U	5		10/00/1	303 1		Aigentina	Western	AR				Slush					SA MERCOSUL	x	ves
733 RE-Takeoff	ff (	0.008	0.008		U	9	00 0	0 10/00/1	303 1	989		Western	AR				Slush						x	yes
733 RE-Takeoff	ff C	0.008	0.008		0	5	165	25/08/1	989	989 Toros Air	Turkey	Western	AR ANKARA	727-247	Jet	INITIAL CLIMB	Slush			Europe	EUROPE	Turkey	x HULL LOSS	yes ASEDB

Accident ID	Category Definition	Severity (Portion of People on Board Fatal)	Working Column Serverity (Calculatio	Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigh - C/G	AIR Claims Loss	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
700			0.000						07/00/1000	1989	Okada Air	Nigorio			DAC 1 11	lat					Africo		Nigoria		
730	RE-Takeoff	0.035	0.034	2	0 2	3	57 6	3 0	20/00/1080	1080			Western		BAC 1-11- B737	Jel		IMC	No	100	North America		Nigeria	NULL LUSS	NASEDB
738	FIRE-NI	0.000	0.004	0	0 0	0	12 7		14/10/1989	1909	Delta		Western	ISIC	B737	Jet	Ground Parked		No	100	North America	NA-Car	US-Canada	x y	Ves
739	CEIT	0.91	0.000	129	3 132	2 14	139 7	7 0	21/10/1989	1989	Sahsa	Honduras	Western	Tegucigalna HN	B727	Jet	Descent	Clouds-	No	100	Latin America & Caribbean	SA/CA	CA/Carib	<u> </u>	<i>y</i> co
100	0111	0.01		120		-		ľ	21110/1000	1000	Curiou	Tionaalao	110010111		5121			wind		100				x	ves
740	CFIT	1	1.000	47	7 54	0	47 7	7 0	26/10/1989	1989	China Airlines	Taiwan	Western	Hualien, Taiwan	B737	Jet	T/O Initial Climb	IMC	No	100	Asia	Asia	Hi-Income Asia-Pac	Х	yes
741	ICE	0.022	0.022	1	0 1	3	47 6	3 0	25/11/1989	1989	Korean Air	Korea	Western	Seoul	F28	Jet	T/O Aborted	Ice	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
			0.000							1989	America West										North America				
742	SCF-NP						125		30/12/1989		Airlines	USA		TUCSON	737-200	Jet	LANDING					NA-Car	USA	HULL LOSS	ASEDB
740	DELEVITO		0.000						0014014000	1989	A1.1				F 00						A.C.1.				
743	RE-Landing	0	0.000	0	0 0	-	00		30/12/1989	2000	Air ivoire	Cote d'Ivoire	Mastara		F-28	Jet	LANDING	Dein	No	100	Affica	AFRICA	Cote d'Ivoire	HULL LOSS	ASEDB
744	RE-Landing	0	0.000	0	0 0	0	05 5		05/01/1990	1990	Acronineas	Argentina	western	Villa Gesell, AR	FUKKEI F.20	Jei	Lanuing - Rollout	Rain	INO	100	Laun America & Caribbean	SAVCA	SA Mercosur	Y	VAS
745	FUEL	0.492	0.491	65	8 73	81	149 9	) ()	25/01/1990	1990	Avianca	Colombia	Western	Long Is., NY	B707	Jet	Landing - Approach	Rain-Wind	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	x	ves
746	USOS	0.639	0.639	88	4 92	22	139 7	7 0	14/02/1990	1990	Indian Airlines	India	Western	Bangalore, India	A320	Jet	Landing - Approach	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	X	yes
			0.000							1990															
747	ARC						82		17/02/1990		AVIACO	Spain		PALMA	DC-9-32	Jet	LANDING				Europe	EUROPE	Spain	HULL LOSS	ASEDB
			0.000							1990													Congo, The		
											Katale Aero												Democratic Republic		
748	USOS		0.000			_	3		01/03/1990		Transport	Congo,		GOMA	707-329C	Jet	FINAL APPROACH	TO		100	Africa	AFRICA	of the	HULL LOSS	ASEDB
749	RE-Landing ARC	0	0.000	0	0 0	0	102 5		22/03/1990	1990	Air China	China	Western	Guilin, CN	BAE (HS) Irident	Jet	Landing - Rollout	1-Storm	NO	100	Asia	Asia	Asia-Low-Mdl Income		
750		1	0.000	0	0 0	0	175 2	0 0	07/05/1000	1000	Air India	India	Mostorn	Now Dolhi	D747 200	lot	Londing Pollout	VV.	No	100	Acia	Acia	Asia Low MdLIncomo	X	yes
100			0.000	Ŭ	0	Ŭ	115 2	-0 0	01100/1000	1000		India	WCSICIII		5141-200	001	Eanding - Ronout	~~	NO	100	Asia	7510	Asia-Low-Mai Income	х	yes
751	FIRE-NI	0.067	0.067	8	08	0	113 6	6 0	11/05/1990	1990	Philippine AL	Philippines	Western	Manila	B737	Jet	Ground, Parked	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
			0.000							1990	Trans Arabian Air	<b>.</b> .													
752	ARC		0.000				25		14/07/1990	3000	Transport	Sudan		KHARTOUM	707-3490	Jet	LANDING			_	Africa	AFRICA	Sudan	HULL LOSS	ASEDB
752			0.000				22		22/07/1000	1990		1164		KINSTON	737 200	lot	TAKEOEE				North America	NA Cor			
755	SUF-INF		0.000			+			22/07/1990	7990	US All Ways	USA		KINGTON	131-200	Jei				_		INA-Odi	USA	HULL LUSS	ASEDD
754	RF-Takeoff		0.000	0	0 0	0			25/07/1990	1000	Ethiopian Airlines	Ethiopia		ADDIS ABABA	707-300	Jet	TAKEOFE				Africa	AFRICA	Ethiopia	HULLOSS	ASEDB
755	TURB		0.043	1	1	2	26		03/10/1990	1990	Eastern Air Lines	USA		WEST PALM BEACH	DC-9-31	Jet	CRUISE				North America	NA-Car	USA	NONE	ASEDB
756	Other		1.000	1	1		1		05/11/1990	1990	Indian Airlines	India		GOA	A300-	Jet	LOAD/UNLOAD				Asia	ASIA (EX CHINA)	India	NONE	ASEDB
757	CFIT	1	1.000	40	0 46	0	40 6	6 0	14/11/1990	1990	Alitalia	Italy	Western	Zurich	DC-9	Jet	Landing - Approach	Rain	No	100	Europe	Europe	EU-EFTA	Х	yes
758	RI	0.097	0.195	7	1 8	10	39 5	5 0	03/12/1990	1990	Northwest	USA	Western	Detroit	B727-200/ DC-9-14	Jet					North America	NA-Car	US-Canada	х	yes
759	CFIT	1	1.000	3	7 10	0	3 7	7 0	04/12/1990	1990	Sudania Air Cargo	Sudan	Western	Nairobi	B707	Jet	Go Around	Fog	No	100	Africa	Africa	Africa	Х	yes
760	RI	0.627	1.000	10	2 12	0	10 2	2 0	01/02/1991	1991	Skywest (USA)/	USA	Western	LAX	SA-227 (Metro)/ B737-	Jet					North America	NA-Car	US-Canada		
764		1	1 000	0	2 0	0			17/00/4004	2004	USAIr (USA)		Moctor			lot	T/O Initial Climb	Spour ising	Nic	100	North Amoriac	NA Cor	LIS Conode	Х	yes
101	ICE		1.000	0	2 2	0	0 2		17/02/1991	1991		USA	western		ND DC-9	Jei		Show, Icing	INO	100	North America	INA-Cal	05-Canada	v	VAS
762	RE-Landing APC	0 279	0.279	20	0 20	2	65 7	7 0	20/02/1001	1001		Chile	Western	Puerto Williams Cl	BAE-146	let	Landing - Rollout	Rain	No	100	Latin America & Caribbean	SA/CA	Asia-Low-Mdl Income	<b>A</b>	yes
102		0.210	0.219	20	20	2	03 /	0	20/02/1991	1331	Lunonino	onilo	TTC3ICIII			001	Landing - Rollout	1 Call		100				x	ves
763	LOC-I	1	1.000	20	5 25	0	20 5	5 0	03/03/1991	1991	United Airlines	USA	Western	Colorado Springs. US	B737	Jet	Approach	Wind	No	100	North America	NA-Car	US-Canada	X	ves
764	CFIT	1	1.000	40	5 45	0	40 5	5 0	05/03/1991	1991	Aeropostal	Venezuela	Western	Valesa, VE	DC-9	Jet	Initial Descent		No	100	Latin America & Caribbean	SA/CA	SA (Northern)	х	yes
765	RE-Takeoff	0.014	0.014	0	0 0	1	0 4	4 0	12/03/1991	1991	Air Transport	USA	Western	New York, US	MD DC-8	Jet	T/O Aborted	XX	Yes	100	North America	NA-Car	US-Canada		
											International													х	yes
766	SCF-PP	0	0.000	0	0 0	0	0 3	3 0	03/05/1991	1991	Ryan International	USA	Western	Hartford, US	B727	Jet	T/O Run	ХХ	No	100	North America	NA-Car	US-Canada		
707		4	4.000	0.10	10 000		01011		00/05/4004	1004	Airlines	Austria	Marti		D707	let	T/O Olimb to O inte		NI	400		<b>E</b>		Х	yes
101	50F-PP		1.000	213	10 223	5 0	213 1		20/05/1991	1991	Lauda Air	Austria	vvestern	194nm. NVV of Bangkok, TH	B/0/	Jet	THO Climb to Cruise	XX	NO	100	Europe	Europe	HI-INCOME ASIA-Pac	V	VOC
			0.000							1001															yes
768	ARC		0.000				119		13/06/1991	1001	Korean Air	South Korea		TAEGU	727-200	Jet	LANDING				Asia	ASIA (EX CHINA)	South Korea	HULLIOSS	ASEDB
769	FUEL	0.053	0.054	4	0 3	0	53 3	3 0	26/06/1991	1991	Okada Air	Nigeria	Western	Sokoto, NG	BAC 1-11	Jet	Initial Descent	IMC	No	100	Africa	Africa	Africa	X	yes
770	SCF-NP	1	1.000	247	14 26	1 0	247 1	14 0	11/07/1991	1991	Nationair Canada	Canada	Western	Jeddah, SA	DC-8	Jet	T/O Initial Climb	XX	No	100	North America	NA-Car	US-Canada	Х	yes



Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column Serverity (Calculatic	(u.	Crew Dead	Tot Fatal (onBd)	Ser-Ious (Unbu) Pax OnBd	Crew OnBd	Other Fatal Date	Y	ear Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor	Weigh - C/G	AIR Claims Loss	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
771	CFIT		1	1.000	63	66	69 0	63	3 6	0 16/08/19	91 19	991 Indian Airlines	India	Western	Imphal, IN	B737	Jet	Initial Descent	Rain-Cloud	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
772	ARC			0.000						14/09/19	91 91	991 Kabo Air	Nigeria		PORT HARCOURT	BAC 1-11-200	Jet	LANDING				Africa	AFRICA	Nigeria	HULL LOSS	ASEDB
773	SCF-NP			0.000						29/09/19	91 91	991 Aerosucre	Colombia		BOGOTA	Caravelle-	Jet	TAKEOFF				Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	Colombia	HULL LOSS	ASEDB
774	SCF-NP			0.000						10/11/19	키 91	AERONICA	Nicaragua		MANAGUA	727-25	Jet	PARKED				Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	Nicaragua	HULL LOSS	ASEDB
775	ARC		-	0.000				36	6	17/11/19	91	991 SAHSA	Honduras		SAN JOSE	737-200	Jet	LANDING				Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	Honduras	HULL LOSS	ASEDB
776	RE-Takeoff		0	0.000	0	0 0	0 0	18	39 10	0 07/12/19	91 19	991 Libyan Arab Airlines	Libya	Western	Tripoli, LY	B707	Jet	T/O Run	XX	No	100	Africa	Africa	NoAfr/MidEast	Х	yes
777	RE-Landing			0.000				or		17/12/10	01 <sup>[1</sup>	Alitalia	Italy		WARSAW	DC-9-32	let					Europe	FUROPE	Italy		
778			0.001	0.001	0	0 0	0 3	12	23 6	0 27/12/19			Multi-Nat	Western	Stockholm SE	MD-80			vv	No	100	Europe	Europe		V V	AGEDD VAS
779	SCE-PP		1	1 000	0	5 4	5 0	0	5	0 29/12/19	91 70	91 China Airlines	Taiwan	Western	Tainei TW	R747	Jet	T/O Climb to Cruise		No	100	Asia	Asia	Hi-Income Asia-Pac	^ Y	Ves
780	ARC		0 003	0.003	0		0 2	36	3 5	0 18/01/19	92 19	992 US Airways	USA	Western	Flmira US	MD DC-9	Jet	Landing - Rollout	Wind	No	100	North America	NA-Car	US-Canada	x	ves
781	CFIT		0.909	0.909	82	5 8	87 5	90	) 6	0 20/01/19	92 1	92 Air France Europe	France	Western	Strasbourg, FR	A320	Jet	Approach	XX	No	100	Europe	Europe	EU-EFTA	x	ves
782	CFIT		0.023	0.023	0	0 0	0 2	0	5	0 15/02/19	92 1	992 MK Airlines	Ghana	Western	Kano, NG	DC-8	Jet	Approach	XX	No	100	Africa	Africa	Africa	Х	yes
783	LOC-I		1	1.000	0	4 4	4 0	0	4	0 15/02/19	92 1	992 BAX Global dba Air Transpt Int	USA	Western	Toledo, US	MD DC-8	Jet	Go Around	Rain, fog, wind	No	100	North America	NA-Car	US-Canada	x	ves
784	ICE		0.54	0.540	25	2 2	27 9	47	7 4	0 22/03/19	92 1	992 US Airways	USA	Western	New York, US	Fokker F.28	Jet	T/O Initial Climb	Icing	No	100	North America	NA-Car	US-Canada	Х	yes
785	CFIT		1	1.000	4	3 7	7 0	4	3	0 24/03/19	92 19	992 Golden Star Air Cargo	Sudan	Western	Athens, GR	B707	Jet	Approach	Cloud-Mist	No	100	Africa	Africa	Africa	x	yes
786	ARC		0	0.000	0	0 0	0 0	88	3 4	0 26/03/19	92 19	992 Inter (Colombia)	Colombia	Western	Tumaco, CO	DC-9	Jet	Landing - Rollout	XX	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	Х	yes
787	SCF-NP			0.000				3		28/03/19	92	992 Export Air Leasing	USA		IQUITOS	DC-8-33AF	Jet	LANDING				North America	NA-Car	USA	HULL LOSS	ASEDB
788	ARC		0.002	0.002	0	0 0	0 4	94	4 5	0 30/03/19	92 19	992 Aviaco	Spain	Western	Granada, ES	DC-9	Jet	Landing - Rollout	Wind	No	100	Europe	Europe	EU-EFTA	Х	yes
789	SCF-NP		0	0.000	0	0 (	0 0	0	5	0 31/03/19	92 19	992 Kabo Air	Nigeria	Western	Orange, FR	B707	Jet	En Route	Turb	No	100	Africa	Africa	Africa	Х	yes
790	SCF-NP		1	1.000	40	7 4	47 0	40	) 7	0 06/06/19	92 19	992 COPA Airlines	Panama	Western	Tocuti, PA	B737	Jet	En Route	XX	No	100	Latin America & Caribbean	SA/CA	CA/Carib	X	yes
791	CFIT		1	1.000	1	2 3	3 0	1	2	0 22/06/19	92 19	992 VASP	Brazil	Western	Cruzeiro do Sul, BR	B737	Jet	Initial Descent	XX	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
792	SCF-NP		0	0.000	0	0 (	0 1	28	30 12	0 30/07/19	92 19	992 Trans World Airlines	USA	Western	New York, US	L-1011	Jet	1/O Initial Climb	XX	No	100	North America	NA-Car	US-Canada	X	yes
793	GFII		1	1.000	99	14	113 0	95	9 14	0 31/07/19	92 1	International	Inaliand	vvestern		A310	Jet	Go Around	1-Storm	INO	100	Asia	Asia	Asia-Low-Ividi Income	x	yes
794	ARC		0	0.000	0	0 (	0 0	53	3 4	0 23/08/19	92 19	992 Kabo Air	Nigeria	Western	Sokoto, NG	BAC 1-11	Jet	Landing - Rollout	XX	No	100	Africa	Atrica	Africa	Х	yes
795	RE-Landing			0.000	455	10	107 0	66	6	29/08/19	92	Services	Nigeria		KADUNA	BAC 1-11-200	Jet	LANDING			100	Africa	AFRICA	Nigeria	HULL LOSS	ASEDB
196	CFII		I	1.000	155	12 1	107 0	15	12	0 28/09/19	92 1	International	Pakistan	vvestern	Rathmandu, NP	A300	Jei	Approach	XX	INO	100	Asid	Asia	Asia-Low-ividi Income	x	Ves
797	SCE-PP		1	1 000	1	3 4	4 0	1	3	0 04/10/19	92 1	192 FLAI	Israel	Western	Amsterdam NI	B747	Jet	T/O Climb to Cruise	XX	No	100	Middle Fast	Asia	NoAfr/MidEast	^ X	Ves
	50111			0.000						0 0 1/ 10/ 10	19	992		1100torn							100		LATIN AMERICA &			,
798	RE-Landing									15/10/19	92	LAC Airlines	Colombia		MEDELLIN	DC-8	Jet	LANDING				Latin America & Caribbean	CARIBBEAN	Colombia	HULL LOSS	ASEDB
799	SCF-NP		0	0.000	0	0 0	0 0	14	4 2	0 20/11/19	92 19	992 Aerolineas Argentinas	Argentina	Western	San Luis, AR	B737	Jet	T/O Aborted	XX	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	х	ves
800	LOC-I		1	1.000	133	8 1	141 0	13	33 8	0 24/11/19	92 1	992 China Southern Airlines	China	Western	Guilin, CN	B737	Jet	Approach	IMC	No	100	Asia	Asia	Asia-Low-Mdl Income	x	ves
801	CFIT		0	0.000	0	0 0	0 0	0	4	0 25/11/19	92 1	992 DAS Air	Uganda	Western	Kano, NG	B707	Jet	Approach	Vis	No	100	Africa	Africa	Africa	Х	yes
802	RE-Landing		0	0.000	0	0 0	0 0	0	4	0 26/11/19	92 1	992 AeroBrasil	Brazil	Western	Manaus, BR	B707	Jet	T/O Initial Climb	XX	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
803	ARC		0.183	0.183	54	2 5	56 10	6 32	27 13	0 21/12/19	92 1	992 Martinair Holland	Nederland	Western	Faro, PT	DC-10	Jet	Landing - Rollout	Windshear	No	100	Europe	Europe	EU-EFTA	х	yes
804	MIDAIR		1	1.000	147	10 1	157 0	14	47 10	0 22/12/19	92 1	992 Libyan Arab Airlines	Libya	Western	Tripoli, LY	B727	Jet	Approach	XX	No	100	Africa	Africa	NoAfr/MidEast	Х	yes
805	USOS			0.000						15/01/19	93 193	993 Air Afrique	Cote d'Ivoire		ABIDJAN	707-321C	Jet	LANDING				Africa	AFRICA	Cote d'Ivoire	HULL LOSS	ASEDB

Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation	🖲 Pax. Dead	Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigh - C/G	AIR Claims Loss	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
006				0.000					156		21/01/1002	1993		Argontino		DECIEE	707 200P	lot					Latin Amorica & Caribboan	LATIN AMERICA &	Argontino		
807		0	1 863	0.863	79	4 8	3 1	3	92 5	0	05/03/1003	1003	Palair Macedonian	Macedonia	Western	Skonie MK	Fokker 100	Jet	T/O Initial Climb	Snow	No	100			Argentina Euro Central	NULL LUSS	ASEDB
808	RE-Landing A	ARC	)	0.000	0			5	227 9	0 0	05/04/1993	1993	TACA	Salvador	Western	Guatemala City GT	B767	Jet	Landing - Rollout	XX	No	73	Latin America & Caribbean	SA/CA	CA/Carib	^	yes
000			, ,	0.000	Ŭ	ľ	ĺ	ľ		ľ	00/01/1000			Carrador	mootom		5101	000	Landing Ronout			10		0,10,1	of totallo	x	ves
809	LOC-I	0	0.011	0.011	2	0 2	! 1	5	248 16	0 (	06/04/1993	1993	China Eastern Airlines	China	Western	off Shemya, US	MD MD-11	Jet	En Route	ХХ	хх	1	Asia	Asia	Asia-Low-Mdl Income	x	yes
810	RE-Landing A	ARC 0	0.001	0.001	0	0 0	2		189 13	0	14/04/1993	1993	American	USA	DC-10	DFW	DC-10	Jet	Landing - Rollout	Wind (Tail)	No	100	North America	NA-Car	US-Canada	x	yes
811	ARC	0	)	0.000	0	0 0	0		115 5	0	18/04/1993	1993	Japan Air System	Japan	Western	Hanamaki, Japan	MD DC-9	Jet	Approach-Landing	Windshear	No	100	Asia	Asia	Asia-High Income	х	yes
040	DAMO			0.000					244		04/04/4000	1993		<b>F</b>			A 000 D0	1-4	TAM				<b>F</b>		<b>F</b>		
012	RAMP		1 400	0 400	52	1 5	6 1	5	314	0	24/04/1993	1002	Air France Europe	France	Montorn		A300-B2	Jet	T/O Initial Climb	N/V	No	100	Europe		France	HULL LUSS	ASEDB
81/		1	J.40Z 1	1 000	125	4 0	32 0	5	12 0		10/05/1003	1993	SAM Colombia	Colombia	Western	Medellin CO	B727	Jet		××	No	100	Asid		SA (Northern)	X	ves
014	UTTI I			0.000	125	/ I	52 0		125 1		19/00/1990	1993	SAM COlombia	COIOITIDIA	Western		0121	JEL		^^		100		JAIOA	on (Northern)	^	yes
815	ARC			0.000					72		21/06/1993		Garuda Indonesia	Indonesia		DENPASAR	DC-9-32	Jet	LANDING				Asia	ASIA (EX CHINA)	Indonesia	HULL LOSS	ASEDB
816	CFIT	0	).956	0.956	37	4 4	1 2		39 4	0 (	01/07/1993	1993	Merpati Nusantara	Indonesia	Western	Sorong, ID	Fokker F.28	Jet	Approach	Rain-Fog	No	100	Asia	Asia	Asia-Low-Mdl Income	х	yes
817	ARC	0	0.009	0.009	0	0 0	) 1	4	88 6	0	18/07/1993	1993	SAHSA	Honduras	Western	Managua, NI	B737	Jet	Landing - Rollout	Rain	No	100	Latin America & Caribbean	SA/CA	CA/Carib	х	yes
818	RE-Takeoff	0	).495	0.495	54	1 5	5 1	6	108 5	0 2	23/07/1993	1993	China Northwest Airlines	China	Western	Yinchuan, CN	BAE-146	Jet	T/O Run	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
819	CFIT	0	).621	0.620	64	4 6	8 2	6	106 6	0 2	26/07/1993	1993	Asiana Airlines	Korea	Western	Mokpo, KR	B737	Jet	Approach	Rain-Wind	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
820	LOC-I	0	0.058	0.057	0	0 0	) 3		0 3	0	18/08/1993	1993	Kitty Hawk International	USA	Western	Guantanamo Bay, CU	MD DC-8	Jet	Approach	XX	No	100	North America	NA-Car	US-Canada	x	yes
0.04	Fire All			0.000					00		05/00/4002	1993	Deminiaana Airlinea	Deminican Depublic			707 004	lat					Latin America & Caribbaan	LATIN AMERICA &	Dominican Donublic		
822	RE-Landing A	ARC 0	0.036	0.035	1	1 2	9	· · · · ·	64 7	0	14/09/1993	1993	Lufthansa	Germany	Western	Warsaw	A320	Jet	Landing - Rollout	Rain-Wind	No	100	Europe	Europe	EU-EFTA	Y	Ves
823	SCF-PP	0	)	0.000	0	0 0	0		152 8	0	25/10/1993	1993	Far Eastern Air Transport	Taiwan	Western	Kaohsiung, TW	MD-80	Jet	T/O Initial Climb	хх	No	100	Asia	Asia	Hi-Income Asia-Pac	x	ves
824	RE-Landing			0.039	2	2	2 1	3	71		26/10/1993	1993	China Eastern Airlines	China		FUZHOU	MD-82-	Jet	LANDING				Asia	CHINA	China	HULL LOSS	ASEDB
825	RE-Landing	0	)	0.000	0	0 0	) 1		274 22	0 (	04/11/1993	1993	China Airlines	Taiwan	Western	Hong Kong, HK	B747	Jet	Landing - Rollout	Typhoon	No	100	Asia	Asia	Hi-Income Asia-Pac	Х	yes
826	Other			0.039	1	1	1		27		08/11/1993	1993	Saudia	Saudi Arabia		MANILA	747-100	Jet	PARKED				Middle East	MIDDLE EAST	Saudi Arabia	MINOR DAMAGE	ASEDB
827	CFIT	0	).122	0.122	8	4 1	2 7		92 10	0	13/11/1993	1993	China Northern Airlines	China	Western	Urumqi, CN	MD-80	Jet	Approach	xx	No	100	Asia	Asia	Asia-Low-MdI Income	x	yes
828	FUEL	0	)	0.000	0	0 0	0		250 13	0	15/11/1993	1993	Indian Airlines	India	Western	Tirupati, IN	A300	Jet	En Route	Fog	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
				0.000								1993		_										LATIN AMERICA &			
829	RE-Landing			0.000					86		20/11/1993	4004	COPA Airlines	Panama		PANAMA CITY	/3/-100	Jet	LANDING				Latin America & Caribbean		Panama	HULL LOSS	ASEDB
830	RE-Landing			0.000					6		15/03/1004	1994	Sec Colombia	Colombia		Bogota	Caravelle	lot					Latin America & Caribboan	CARIBBEAN	Colombia		ASEDP
831	USOS	0	0.001	0.001	0	0 0	2		110 6	0	21/03/1994	1994	Aviaco	Spain	Western	Vigo, ES	DC-9	Jet	Approach	Rain-Fog0-	No	100	Europe	Europe	EU-EFTA	Y	Ves
832	LOC-I	1	1	1.000	63	12 7	5 0		63 12	0	23/03/1994	1994	Aeroflot Russian Airlines	Russia	Western	40nm East of Novokuznetsk, RU	A310	Jet	En Route	XX	No	100	CIS	Europe	Euro East	x	ves
833	LOC-I	0	0.976	0.976	249	15 2	64 7		256 15	0	26/04/1994	1994	China Airlines	Taiwan	Western	Nagoya, JP	A300	Jet	Go Around	ХХ	No	100	Asia	Asia	Hi-Income Asia-Pac	х	yes
834	USOS	0	)	0.000	0	0 0	0		0 3	7	27/04/1994	1994	TransAfrik	Sao Tome	Western	M'Banza Congo, AO	B727	Jet	Approach	ХХ	No	100	Africa	Africa	Africa	7 Ground fatals	yes
				0.905								1994															
835	ARC				76	4 8	0 9		89	(	01/07/1994		Air Mauritanie	Mauritania		TIDJIKJA	F-28	Jet	LANDING				Africa	AFRICA	Mauritania	HULL LOSS	ASEDB
836	WSTRW	0	0.665	0.665	37	0 3	57 1	6	52 5	0 (	02/07/1994	1994	US Airways	USA	Western	Charlotte, US	MD DC-9	Jet	Go Around	T-Storm- Wind	No	100	North America	NA-Car	US-Canada	x	yes
837	RE-Landing A		)	0.000	0	0 0	0		140 8	0	20/07/1994	1994		China	Western	Kunming, CN	B/3/	Jet	Landing - Rollout	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
838	RE-Landing A		,	0.000	0	0 0	0		152 ð	0	10/08/1994	1994	ADC Airlings	Nigoria	Western			Jet	Landing - Kollout	Wind Rain-Cloud-	No	100	Asia	Asia	Asia-Low-Mai Income	х	yes
839	RE-Landing A		,	1.000	107	0 0	0		19 /	0	18/08/1994	1994	ADC AIRINES		Western		DC-9	Jet		Rain	NO	100	Airica	Allica		x	yes
840	100-1	1	1	1.000	127	0 1	32 0		127 5	0	08/09/1994	1994	US Airways	USA	vvestern	US	B/3/	Jet	Approach	XX	INO	100	INOI (II AMERICA	INA-Car	US-Canada	x	yes



Accident ID	Category Definitior	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column Serverity (Calculatio	Pax. Dead	Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd		: Y	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	, Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
841	FUEL	_	0.178	0.178	2	3	5	34	32	7 (	18/09/19	994 1	994 Orie	ental Airlines	Nigeria	Western	Tamanrasset, DZ	BAC 1-11	Jet	Approach	Fog	No	100	Africa	Africa	Africa	X	yes
842	SCF-NP			0.000					2		09/10/19	994	994 LAB	1	Bolivia		SAO PAULO	707-300	Jet	LANDING				Latin America & Caribbean	CARIBBEAN	Bolivia	HULL LOSS	ASEDB
843				1.119	50	7	66		50		12/10/10	1	994 Iran	Asseman	Iran		ΝΑΤΑΝΖ	E 28 1000	let					Middle East		Iran		
844	RI		0	0.000	0	0	0	0	132	5 2	2 22/11/19	994 1	994 TW/	A	USA	Western	STL	MD-82	Jet	T/O Run	XX	No	100	North America	NA-Car	US-Canada	2 Ground	AOLDD
				0.001								7	994 Mer	nati Nusantara													fatal	yes
845	RE-Landin	g	0.000	0.000				2	78		30/11/19	994	Airli	nes	Indonesia		SEMARANG	F-28-4000	Jet	LANDING			100	Asia	ASIA (EX CHINA)	Indonesia	HULL LOSS	ASEDB
846	CEII	_	0.623	0.623	0	3	3	2	0	5 (	) 19/12/19	994 1	994 Nige	eria Airways	Nigeria	Western	170km. NE of Kano, NG	B/0/	Jet	Initial Descent	XX	NO	100	Africa	Africa	Africa	X	yes
847	CEIT	_	1	1.000	0	5	5	0	0	5 (	21/12/19	994 1	994 Air A	Algerie	Algeria	Western	(near) Coventry, GB	B/3/	Jet	Landing - Approach	XX	XX	100	Africa	Africa	NoAfr/MidEast	X	yes
848	CFII		0.764	0.764	52	э	5/	19	69		29/12/19	994	994 Airli	nes	тигкеу	western	van, TR	B/3/	Jet	Approach	Snow	INO	100	Europe	Europe	NOAII/MIDEast	x	ves
849	RE-Landin	ıg	0.092	0.000	46	5	51	1	47	5 (	02/01/19	995	995 LAC	(Colombia)	Congo,	Western	KINSHASA	737-200	Jet	LANDING	Claud	No	100	Africa	AFRICA	Congo, The Democratic Republic of the	HULL LOSS	ASEDB
000	GFII		0.962	0.902	40	5	51	1	47	5 (	11/01/18	995 1	990 IIIIEI		COIDINDIA	western	CO	DC-9	Jel		Ciouu	INU	100		SHUA	SA (Northern)	x	yes
851	RE-Landin	g		0.000					52		16/01/19	995 -	995 Serr Trar	npati Air nsport	Indonesia		YOGYAKARTA	737-200	Jet	LANDING				Asia	ASIA (EX CHINA)	Indonesia	HULL LOSS	ASEDB
852	RE-Landin	a		0.000							31/01/19	995 1	995 Ang	ola Air Charter	Angola		Huambo Airport	727-100	Jet	LANDING				Africa	AFRICA	Angola	HULL LOSS	ASEDB
052		<u> </u>		0.001				<u>ე</u>	121		01/02/10	7	995	D Airlings	Prozil			727 200	lot					Latin America & Caribbaan	LATIN AMERICA &	Prozil		
854			1	1 000	50	10	60	2	50	10 0	31/03/10			OM	Bomania	Western	Bucharest RO	A310	Jei	T/O Climb to Cruise	vv	No	100			Furo Fast	V NULL LUSS	NOS
855	RE-Landin		: 0.019	0.019	0	0	0	1	0	3 6	28/04/19	995 1	995 Millo	n Air	USA	Western	Guatemala City GT	MD DC-8	Jet	Landing - Rollout	Rain	No	100	North America	NA-Car	US-Canada	6 Ground	yco
				0.010	ľ	Ŭ	Ŭ		ľ	ľ										Landing ronout						ee canada	fatal	yes
856	RE-Landin	a		0.000					35		31/05/19	995	995 Air N	Niuaini	Papua New Guinea		MADANG	F-28-	Jet	LANDING				Aust	Oceania	Papua New Guinea	HULL LOSS	ASEDB
857	SCF-PP	<u> </u>	0.001	0.001	0	0	0	1	55	5 (	08/06/19	995 1	995 Valu	ijet	USA	Western	Atlanta, US	MD DC-9	Jet	T/O Aborted	XX	No	100	North America	NA-Car	US-Canada	X	yes
858	2021			0.000					82		26/07/10	1	995	Airlines	Nigeria			DC-9-	let					Africa		Nigeria		
859	CEIT		1	1 000	58	7	65	0	58	7 (	09/08/19	995	995 Avia	iteca	Mexico	Western	San Salvador SV	B737	Jet	Approach	T-Storm	No	100	Latin America & Caribbean	SA/CA	CA/Carib	X	Ves
860	DE Landin		1	0.000							17/08/10	7	995 Air /	Afrique				707 3200	lot					Africa	EUPOPE	Cote d'Ivoire		
861	RE-Landin	ig ARC	0.067	0.067	9	0	9	4	129	8 (	) 13/11/19	995 <b>1</b>	995 Nige	eria Airways	Nigeria	Western	Kaduna, NG	B737	Jet	Landing - Rollout	XX	No	100	Africa	Africa	Africa	HOLL LOGG	AGEDB
862	CFIT		0.333	0.333	0	2	2	0	0	6 (	) 30/11/19	995 1	995 Aze	rbaijan Airlines	Azerbaijan	Western	Baku, AZ	B707	Jet	Go Around	XX	No	100	CIS	Europe	Europe - E/.SE	X	yes
863	RE-Landin	g ARC	0	0.000	0	0	0	0	102	6 (	) 02/12/19	995 1	/AZA 995 India	AL Avia an Airlines	India	Western	Delhi, IN	B737	Jet	Landing - Rollout	xx	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
				1.005									005														x	yes
864	LOC-I			1.005	68	4	72	6	72		03/12/19	995	Sec Can	neroon Airlines	Cameroon		DOUALA	737-200	Jet	CLIMB				Africa	AFRICA	Cameroon	HULL LOSS	ASEDB
865	CFIT		0.977	0.977	152	8	160	4	156	8 (	20/12/19	995 1	995 Ame	erican Airlines	USA	Western	Cali, Co (Buga)	B757	Jet	Initial Descent	XX	No	100	North America	NA-Car	US-Canada	Х	yes
866	LOC-G		0	0.000	0	0	0	0	477	15 (	20/12/19	995 1	995 Tow	er Air	USA	Western	New York, US	B747	Jet	T/O Aborted	XX	No	100	North America	NA-Car	US-Canada	Х	yes
867	ARC			0.000					75		30/12/19	995 1	995 TAR Air 1	OM - Romanian	Romania		ISTANBUL	BAC 1-11	Jet	LANDING				Europe	EUROPE	Romania	HULL LOSS	ASEDB
868	RE-Landin	a		0.000							28/01/19	996	996 AFF	RETAIR	Zimbabwe		HARARE	DC-8-F55	Jet	LANDING				Africa	AFRICA	Zimbabwe	HULLLOSS	ASEDB
869		.9	1	1 000	176	13	189	0	176	13 (	06/02/10	996	996 Birg	enair	Turkey	Western	Puerto Plata DO	B757	Jet	T/O Climb to Cruise	XX	No	100	Furope	Furope	NoAfr/MidEast	X	Ves
070				0.000	110		100	5			40/00/14	1	996			TOOLOTT	Llauster						100	North America				
8/0	ARC		1	1.000	447	6	100	0	82	6	19/02/19	996	Con	unental Airlines	Doru	Moster		DC-9-	Jet	LANDING	Claud	No	100	Latin America & Caribbar	NA-Car	USA CA (Northorn)	HULL LOSS	ASEDB
0/1	DE Takar	¥	0.001	1.000	117	0	123	1	77	0		1 066	990 Fau		Peru	Western	Arequipa, PE	D131 D727	Jet	Approach	Roin	NO	100	Laun America & Caribbean	SAUCA	SA (Normenn)	X	yes
873	FIRE NI		0.001	1.000	105	5	110	0	105	5 0	11/05/19	1 066	990 FIY L	lineas Aereas		Western	15 miles W of Opa Looka		Jei	T/O Climb to Cruise	rain	No	100	North America	NA_Car	US-Canada	X	yes
075				1.000	105	5	110	0	105	5 (					Maria	western	US		Jet		**		100				x	yes
8/4	SCF-NP		0	0.000	0	0	0	12	42	4 (	14/05/19	996 1	996 Alle	gro Alf	Indepenie	Western	Lampico, MX	DC-9	Jet	En Koute	XX	NO	100	Laun America & Caribbean	SAVUA	CA/Carib	X	yes
8/5	RE-Landin	IY ARC	0.013	0.013	3	0	3	12	260	15 (	13/06/19	190	990 Gari	uda moonesia	Indonesia	vvestern	Fukuoka, JP	00-10	Jet	T/U Aborted	XX	NO	100	ASId	ASId	Asia-Low-IVIOI Income	х	yes

Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	Yea	ar Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
876	WSTRW		0	0.000	0 0	0	0	0	4 0	30/06/199	6 199	6 DAS Air	Uganda	Western	Bamako, ML	B707	Jet	Landing - Rollout	Rain-Wind	No	100	Africa	Africa	Africa	х	yes
877	SCF-PP		0.015	0.015	2 0	2	2	137	5 0	06/07/199	6 199	6 Delta	USA	Western	Pensacola	MD-88	Jet	T/O Run	XX	No	100	North America	NA-Car	US-Canada	х	yes
878	FIRE-NI		1	1.000	212 18	8 230	0	212	18 0	17/07/199	6 199	6 Trans World Airline	s USA	Western	(near) Mastic Beach (Long Island), US	B747	Jet	T/O Climb to Cruise	XX	No	100	North America	NA-Car	US-Canada	x	yes
879	RE-Landing		0	0.000	0 0	0	0	120	8 0	21/08/199	6 199	6 Egyptair	Egypt	Western	Istanbul, TR	B707	Jet	Landing - Rollout	Rain	No	100	Africa	Africa	NoAfr/MidEast	х	yes
880	FIRE-NI		0	0.000	0 0	0	0	0	5 0	05/09/199	6 199	6 FedEx	USA	Western	Newburgh, NY	DC-10	Jet	En Route	XX	No	100	North America	NA-Car	US-Canada	х	yes
881	CFIT		1	1.000	61 9	70	0	61	9 0	02/10/199	6 199	6 Aero Peru	Peru	Western	off Ancon, PE	B757	Jet	T/O Climb to Cruise	XX	No	100	Latin America & Caribbean	SA/CA	SA (Northern)	х	yes
882	ARC			0.000						10/10/199	199 6	6 Occidental Airlines	Belgium		DJERBA	707-320C	Jet	LANDING				Europe	EUROPE	Belgium	HULL LOSS	ASEDB
883	LOC-I		1	1.000	0 4	4	0	0	4 #	22/10/199	6 199	6 Millon Air	USA	Western	Manta, EC	B707	Jet	T/O Initial Climb	XX	No	100	North America	NA-Car	US-Canada	30 Ground fatal	yes
884				0.000		2	6			23/10/100	6 199		Argenting			707 3720	lot					Latin America & Caribbean		Argenting		
004 885	SCE DD		1	1 000	80 6	2	0	80	6 0	23/10/199	6 700	6 TAM Brasil	Brazil	Western	Sao Paulo RP	Fokker 100	Jei	T/O Initial Climb		No	100	Latin America & Caribbean		Algenuna SA Marcosur	V NULL LUGG	AGEDD
886			1	1.000	13/ 0	1/3	0	13/		07/11/100	6 100	6 ADC Airlines	Nigeria	Western	40km ENE of Lagos NG	B727		Initial Descent		No	100	Africa	Africa	Africa	x v	yes
887	MIDAIR		1	1.000	289 23	3 312	0	289	23 #	12/11/1990	6 199	6 Saudi Arabian Airlines/Chimkenta	Saudi Arabia	western	50 miles W. of Delhi, IN	IL76/B747	Jet				100	Middle East	Asia	NoAfr/MidEast	^ 37 fatal in	yes
												а													other A/C	yes
888	CFIT		0	0.000	0 0	0	0	0	4 0	17/12/199	6 199	6 MK Airlines	Ghana	Western	Port Harcourt, NG	DC-8	Jet	Approach	XX	No	100	Africa	Africa	Africa	Х	yes
889	SCF-NP			0.000						17/01/199	7	Airways	Belgium		KANANGA	707-320	Jet	LANDING				Europe	EUROPE	Belgium	HULL LOSS	ASEDB
890	ARC		0.024	0.024	0 1	1	4	46	6 0	14/02/199	7 199	7 VARIG	Brazil	Western	Carajas, BR	B737	Jet	Landing - Rollout	Wind-fog- rain	XX	100	Latin America & Caribbean	SA/CA	SA Mercosur	x	yes
891	RE-Takeoff		0.002	0.002	0 0	0	4	107	80	10/03/199	7 199	7 Gulf Air	Qatar (Multi-Nati)	Western	Abu Dhabi, AE	A320	Jet	T/O Aborted	Wind	No	100	Middle East	Asia	NoAfr/MidEast	Х	yes
802	DE Landing			0.000				07		12/04/100	7 199	7 Chana Ainwaye	Ghana				lot					Africa		Ghana		
893	ARC		0.473	0.473	33 2	35	0	65	9 0	08/05/199	7 199	7 China Southern	China	Western	Shenzhen, CN	B737	Jet	Landing - Rollout	Rain-T-	No	100	Asia	Asia	Asia-Low-Mdl Income		AGEDB
				0.000							199	7 TAROM - Romania	n						Storm						x	yes
894	RE-Landing		0	0.000		_	-	20		07/06/199	7	Air Transport	Romania		STOCKHOLM	BAC 1-11	Jet	LANDING			100	Europe	EUROPE	Romania	HULL LOSS	ASEDB
895	ARC		0	0.000	0 0	0	0	49	6 0	29/07/199	7 199		Nigeria		Calabar	BAC-1-11	Jet	Landing - Approach	XX	NO	100	Africa	Africa	Africa	Х	yes
896	ARC		0	0.000	0 0	0	0	0	4 0	31/07/199	7 199	7 FedEx	USA	Western	Newark, US	MD MD-11	Jet	Landing - Rollout	XX	NO	100	North America	NA-Car	US-Canada	X	yes
897 898	Other RE-Takeoff		0	0.007	1 0 0	0	0	142	8 0	02/08/199	7 199 7 199	7 Continental Airlines 7 Air Afrique	Cote d Ivorie (Multi-	- Western	LIMA Douala, CM	757-200 B737	Jet Jet	T/O Aborted	хх	No	100	North America Africa	NA-Car Africa	USA Africa	NONE	ASEDB
899	CFIT		0.907	0.907	215 14	4 229	25	237	17 0	06/08/199	7 199	7 Korean Air	Korea	Western	Agana, GU	B747	Jet	Approach	Rain-T-	No	100	Asia	Asia	Asia-Low-Mdl Income	×	Vec
900	100-1		1	1 000	0 4	4	0	0	4 0	07/08/100	7 100	7 Fine Air	USA	Western	Miami US	MD DC-8	Jet	T/O Initial Climb		Yes	100	North America	NA-Car	US-Canada	X	ves
901	RE-Landing	ARC	0	0.000		0	0	26	9 0	12/08/100	7 100	7 Olympic Ainways	Greece	Western	Thessaloniki GR	B727	Jet	Landing - Rollout	Rain	No	100	Furone	Furone	FU-FFTA	~	,
301				0.000				20	5 0	12/00/133	199	7		Western							100				x	yes
902	ARC			0.000						15/08/199	7	Angola Air Charter	Angola		LUKAPA	727-100	Jet	LANDING				Africa		Angola	HULL LOSS	ASEDB
903	USOS			0.000				42		17/08/199	7	SAETA S.A.	Ecuador		SAN CRISTOBAL	727-200	Jet	LANDING				Latin America & Caribbean		Ecuador	HULL LOSS	ASEDB
904	SCF-PP		0	0.000	0 0	0	0	79	6 0	06/09/199	7 199	7 Saudi Arabian Airlines	Saudi Arabia	Western	Nejran, SA	B737	Jet	T/O Aborted	XX	No	100	Middle East	Asia	NoAfr/MidEast	х	yes
905	CFIT		1	1.000	222 12	2 234	0	222	12 0	26/09/199	7 199	7 Garuda Indonesia	Indonesia	Western	Medan, ID	A300	Jet	Approach	Smoke	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
906	RI			0.000			1			01/10/199	7 7	7 Ryan International Airlines	USA		DENVER	727-51C	Jet	TAXI				North America	NA-Car	USA	HULL LOSS	ASEDB
907	LOC-I			1.072	69 5	74		69		10/10/199	199 7	7 AUSTRAL - Cielos del Sur S.A.	Argentina		NUEVO BERLIN	DC-9-32	Jet	CRUISE				Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	Argentina	HULL LOSS	ASEDB
908	ARC			0.000				67		15/10/199	199 7	7 Aeromexico	Mexico		MEXICO CITY	DC-9-32	Jet	LANDING				Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	Mexico	HULL LOSS	ASEDB
				0.000						10.101100	199	7	Congo, The Democratic											Congo, The Democratic Republic		
909	RE-Landing									01/11/199	7	Congo Airlines	Republic of the		KINSHASA	707-323C	Jet	LANDING				Africa	AFRICA	of the	HULL LOSS	ASEDB
910	ARC		0.012	0.012	0 0	0	9	39	3 0	16/12/199	7 199	7 Air Canada	Canada	Western	Fredericton, CA	Canadair CRJ	Jet	Go Around	Fog	No	100	North America	NA-Car	US-Canada	Х	yes



Accident ID	Category Category Definition	Severity (Portion People o Board Fatal)	n (Calcula	ing nn - rity Aax. Dead	Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	f Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weig - C/0	<sup>CD</sup> 피 AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
911	CFIT		0.000					84		22/12/1997	1997	Biman Bangladesh Airlines	Bangladesh		SYLHET	F-28-	Jet	FINAL APPROACH				Asia	ASIA (EX CHINA)	Bangladesh	HULL LOSS	ASEDB
912	TURB		0.006	1		1	18	355		28/12/1997	1997	United Airlines	USA		HONOLULU	747-100	Jet	CRUISE				North America	NA-Car	USA	MINOR	ASEDB
913	CFIT		0.000				-	104		05/01/1998	1998	Iran Air	Iran		ISFAHAN	F-100	Jet	LANDING				Middle East	MIDDLE EAST	Iran	HULL LOSS	ASEDB
914	RE-Landing		0.000					68		11/01/1998	71998	Turkish Airlines (THY)	Turkey		SAMSUN	RJ100	Jet	LANDING				Europe	EUROPE	Turkey	HULL LOSS	ASEDB
915	CFIT		1.051	99	5	104		99		02/02/1998	1998	Cebu Pacific Air	Philippines		ENRT TAC-CGY	DC-9	Jet	DESCENT				Asia	ASIA (EX CHINA)	Philippines	HULL LOSS	ASEDB
916	USOS	0	0.000	0	0	0 0	0	115 6	0	09/02/1998	1998	American Airlines	USA	Western	n Chicago, US	B727	Jet	Approach	XX	No	100	North America	NA-Car	US-Canada	Х	yes
917	LOC-I	1	1.000	182	14	196 (	0	182 14	4 6	16/02/1998	1998	China Airlines	Taiwan	Western	Taipei, TW	A300	Jet	Go Around	Rain-Fog	No	100	Asia	Asia	Hi-Income Asia-Pac	6 Ground	VOC
018	1.001	1	1 000		6	6 (	0	0 6	0	10/03/1008	1008	Air Momphie	Equat	Western	Mombasa KE	B707	lot	T/O Initial Climb	VV	Voc	100	Africa	Africa	NoAfr/MidEast	Ididi	yes
919	CEIT	1	1.000	35	10	45 0	0	35 10		19/03/1998	1998	Ariana Afghan	Afghanistan	Western		B707	Jet	Approach	Rain-	No	100	Asia	Asia	ASIACEN	^	yes
010	orn		1.000	00	10	10	Ŭ			10/00/1000	1000	/ india / lightin	Aighanistan	Western		0121	001	Approach	Clouds		100	7.014	7,614	NOINCEN	х	yes
920	RE-Landing AR	C 0.001	0.001	0	0	0 2	2	128 8	3	22/03/1998	1998	Philippine Airlines	Philippines	Western	Bacolod, PH	A320	Jet	Landing - Rollout	хх	No	100	Asia	Asia	Asia-Low-Mdl Income	3 Ground fatal	yes
			0.000								1998											CIS				
921	RE-Landing							80	_	12/04/1998		Orient Eagle Airways	Kazakhstan		ALMATY	737-200	Jet	LANDING					CIS	Kazakhstan	HULL LOSS	ASEDB
922	CFII	1	1.000	43	10	53 (	0	10 43	3 0	20/04/1998	1998	IAME Ecuador	Ecuador	Western	n (near) Bogota, CO	B727	Jet	T/O Climb to Cruise	Cloud	XX	100	Latin America & Caribbean	SA/CA	SA (Northern)	Х	yes
923	CFIT		0.935	69	6	75 <sup>-</sup>	13	81		05/05/1998	1998	Petroleum Corp	USA		(Near) Andoas	737-200	Jet	LANDING				North America	NA-Car	USA	HULL LOSS	ASEDB
924	RE-Takeoff		0.000					57		15/05/1998	1998	Merpati Nusantara Airlines	Indonesia		KENDARI	F-28-4000	Jet	TAKEOFF				Asia	ASIA (EX CHINA)	Indonesia	HULL LOSS	ASEDB
925	RE-Landing		0.000					73		16/05/1998	1998	Manunggal Air	Indonesia		SINGAPORE	F-28	Jet	LANDING				Asia	ASIA (EX CHINA)	Indonesia	HULL LOSS	ASEDB
926	RE-Landing		0.000					91		19/07/1998	1998	Sudan Airways	Sudan		KHARTOUM	737-200	Jet	LANDING				Africa	AFRICA	Sudan	HULL LOSS	ASEDB
927	RE-Landing		0.000					376		05/08/1998	1998	Korean Air	South Korea		SEOUL	747-400	Jet	LANDING				Asia	ASIA (EX CHINA)	South Korea	HULL LOSS	ASEDB
000			0.000							04/00/4000	1998	DI II Alaman	1104			707.000	1.1	TAKEOFE				North America		1104		40500
928	SCF-NP	1	1 000	015	14	220 0	0	215 14	4 0	31/08/1998	1000	DHL Airways	USA	Meetern	NEW YORK	727-200 MD 11	Jet		200	No	100	Europo	NA-Car		HULLLUSS	ASEDB
929	SCF-NP	1	1.000	215	14	229 (	0	215 14	4 0	02/09/1998	1998	Swissair	Switzenand	western	i Inova Scotia	MUTI	Jet	En Route	XX	INO	100	Europe	Europe	EU-EFTA	X	yes
930	RE-Landing		0.000					102		16/09/1998	1990	Continental Airlines	USA		GUADALAJARA	737-500	Jet	LANDING				INOI III AIIIEIICa	NA-Car	USA	HULL LOSS	ASEDB
931	CFIT	1	1.000	34	4	38 (	0	34 4	0	25/09/1998	1998	Paukn Air	Spain	Western	Melilla, MA	BAE-146	Jet	Approach	XX	No	100	Europe	Europe	EU-EFTA	Х	yes
			0.000								1998															
932	SCF-PP		0.000					97		05/10/1998	4000	LAM	Mozambique		MAPUTO	747-SP	Jet	CLIMB				Africa	AFRICA	Mozambique	HULL LOSS	ASEDB
933	RE-Landing		0.000					100		01/11/1998	1998	AirTran Airways	USA		ATLANTA	737-200	Jet	LANDING				North America	NA-Car	USA	HULL LOSS	ASEDB
934	SCF-PP	0	0.000	0	0	0 (	0	0 5	0	14/11/1998	1998	IAT Cargo	Nigeria	Western	Ostend, BE	B707	Jet	Landing - Rollout	Turb	No	100	Africa	Africa	Africa	Х	yes
935	CFIT	0	0.000	0	0	0 (	0	61 11	1 0	10/12/1998	1998	Azerbaijan Airlines /AZAL Avia	Azerbaijan	Western	n Baku, AZ	B727	Jet	Landing - Go Around	IMC	XX	100	CIS	Europe	Europe - E/.SE	x	yes
936	LOC-I	0.699	0.699	91	11	102 (	0	132 14	4 0	11/12/1998	1998	Thai Airways International	Thailand	Western	Surat Thani, TH	A310	Jet	Go Around	Rain-Wind	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
937	ARC	0	0.000	0	0	0 (	0	36 4	0	28/12/1998	1998	Rio Sul	Brazil	Western	Curitiba, BR	EMB ERJ-145	Jet	Landing - Rollout	Clouds	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
938	ARC	0	0.000	0	0	0 (	0	78 6		1/28/1999	1999	Alitalia	Italy	Western	CATANIA	MD-82	Jet	LANDING	XX	XX	XX	Europe	Europe	EU-EFTA		No
939	RE-Landing	0	0.000	0	0	0 (	0	92 10	0	1/31/1999	1999	Air Algerie	Algeria	Western	CONSTANTINE	B727-200	Jet	LANDING	XX	XX	XX	Africa	AFRICA	NoAfr/MidEast		No
940	RE-Takeoff	0	0.000	0	0	0 (	0	0 3		2/7/1999	1999	Clipper International	Switzerland	Western	BRATISLAVA	B707-328C	Jet	TAKEOFF	XX	XX	XX	Europe	Europe	EU-EFTA		No
941	RE-Landing	0	0.000	0	0	0 (	0	91 6		3/4/1999	1999	Air France	France	Western	BIARRITZ	B737-200	Jet	LANDING	XX	XX	XX	Europe	Europe	EU-EFTA		No
942	ARC	0	0.011	0	0	0	1	0 5		3/5/1999	1999	Air France	France	Western	MADRAS	B747-200	Jet	LANDING	XX	XX	XX	Europe	Europe	EU-EFTA		No
943	RE-Landing AR	C 0.001	0.001	0	0	0 2	2	150 6	0	15/03/1999	1999	Korean Air	Korea	Western	Pohang, KR	MD-80	Jet	Landing - Rollout	Rain-Wind	No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
944	RE-Landing	0	0.000	0	0	0 (	0	252 19	9	3/24/1999	1999	Emirates	United Arab Emirates	Western	RHODES ISLAND	A300-600	Jet	LANDING	xx	xx	xx	Middle East	MIDDLE EAST	NoAfr/MidEast		No
945	LOC-I	1	1.000	0	6	6 (	0	0 6		4/7/1999	1999	Turkish Airlines (THY)	Turkey	Western	ADANA	B737-400	Jet	CLIMB	хх	xx	хх	Europe	Europe	NoAfr/MidEast		No

Accident ID	Category Definition	C Severity (Portion of People o Board Fatal)	of Working n Serverity (Calculation)	) Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal Date	e Ye	ar Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
946	LOC-I	1	1.000	0 3	3 3	0	0 3	5 15/04/1	999 19	99 Korean Air	Korea	Western	Shanghai, CN	MD-11	Jet	T/O Climb to Cruise	Rain-	No	100	Asia	Asia	Asia-Low-Mdl Income	5 Ground	
0.47		0	0.000	0		0	00 0	4/00/40	00 80		O suth Africa	14/		D707 000	1-4		Clouds			A6-i	A.6.1	Africa	fatal	yes
947	WSIRW	0 004	0.000	10 1		0	120 6	4/22/19	99 19	99 Million Air Charters	South Africa	Western	JUHANNESBURG	B/2/-200	Jet	INITIAL APPROACH	XX T Storm	XX	XX	Affica	Affica	ATTICa	<u>v</u>	NO
940	WOIRW	0.094	0.094			40	139 0	0 01/00/1	999 19 Plo	99 China Southern	USA	Western		WID-00	Jei	Lanung - Approach	1-3101111	INU	100	NUTLIT AITIETICA	INA-Cal	US-Callaud	X	yes
949	ARC	0	0.000	0 0	0 0	0	81 9	6/9/199	9	Airlines	China	Western	ZHANGJIANG	B737-300	Jet		xx	xx	xx	Asia	CHINA	Asia-Low-MdLIncome		No
950	CFIT	1	1.000	0 5	5 5	0	0 5	0 07/07/1	999 19	99 Hinduja Cargo	India	Western	Kathmandu, NP	B727	Jet	T/O Climb to Cruise	Rain-Fog	No	100	Asia	Asia	Asia-Low-Mdl Income		
										Services			,				Ĭ						х	yes
951	RE-Landing	ARC	0.000						19	99 Trans Arabian Air											Africa	Africa		ſ
		0		0 0	) ()	0	0 3	8/14/19	99	Transport	Sudan	Western	JUBA	B707-328C	Jet	LANDING	XX	XX	XX	Africa				No
952	ARC	0.019	0.019	3 0	) 3	50	300 15	0 22/08/1	999 19	99 China Airlines	Taiwan	Western	Hong Kong, HK	MD-11	Jet	Landing - Rollout	Rain-Wind	No	100	Asia	Asia	Hi-Income Asia-Pac	Х	yes
953	FIRE-NI	0.018	0.018	1 (	) 1	13	90 6	0 24/08/1	999 19	99 UNI Air	laiwan	Western	Hualien, IW	MD-90	Jet	Landing - Rollout	XX	No	100	Asia	Asia	Hi-Income Asia-Pac	X 5 October 1	yes
954	RE-Takeom	0.63	0.630	01 3	5 04	15	98 5	5 31/08/1	999 19		Argentina	vvestern	Buenos Aires, AR	B/3/	Jet	T/O Aborted	XX	NO	100	Latin America & Caribbean	SA/CA	SA Mercosur	5 Ground	VOO
955	ARC	0	0.000	0 0	) ()	0	41 5	0/0/100	a 🕫			Western	NASHVILLE	DC-9-31	let		YY.	vy	vv	North America	NA-Car	US-Canada	Ididi	No
956	ARC	0.001	0.000	0 0		2	236 9	0 14/09/1	999 19	99 Britannia Airways	UK	Western	Gerona, ES	B757	Jet	Landing - Rollout	Rain-Wind	No	100	Europe	Europe	EU-EFTA	x	ves
957	ARC	0	0.000	0 0	) ()	0	3 5	0 16/10/1	999 19	99 Continental Cargo	Ghana	Western	Kinshasa, ZR	DC-8	Jet	Landing - Rollout	XX	No	100	Africa	Africa	Africa	<u> </u>	1,00
										Airlines													х	yes
958	RE-Landing	0	0.000	0 0	) ()	0	0 2	0 17/10/1	999 19	99 FedEx	USA		Subic Bay, Ph	MD-11	Jet	Landing - Rollout	Rain	No	100	North America	NA-Car	US-Canada	Х	yes
959	LOC-I	1	1.000	13 5	5 18	0	13 5	0 09/11/1	999 19	99 TAESA	Mexico	Western	Uruapan, MX	DC-9	Jet	T/O Initial Climb	XX	No	100	Latin America & Caribbean	SA/CA	CA/Carib	X	yes
960	RE-Landing	ARC 0.051	0.051	8 8	3 16	0	296 18	2 21/12/1	999 19	99 Cubana	Cuba	Western	Guatemala City, GT	DC-10	Jet	Landing - Rollout	Rain	No	100	Latin America & Caribbean	NA-Car	CA/Carib	2 Ground	
004	1.001	1	1 000			-	0 4	0 00/40/4	000 30		Karaa	Western	Dishana Chartford, CD	D747	lat	T/O Initial Olimb	Mind	No	100	Acia	Anin	Asia Law MdLIncome	fatal	yes
961	LUC-1	1	1.000	0 4	4	0	0 4	0 22/12/1	999 19	99 Korean Air	Korea	vvestern	Bisnops Stortford, GB	B/4/	Jet		VVING-	NO	100	Asia	Asia	Asia-Low-Ividi Income	v	Vec
962	CEIT	0 944	0 944	159 1	10 169	0	169 10	0 30/01/2	000 20	0 Kenva Airways	Kenva	Western	off Abidian, Cl	A310	Jet	T/O Initial Climb	YY SIDUUS	No	100	Africa	Africa	Africa	x x	Ves
963	SCF-NP	1	1.000	83 5	5 88	0	83 5	0 31/01/2	000 20	0 Alaska	USA	Western	Point Mugu, Ca	MD-83	Jet	En Route	XX	No	100	North America	NA-Car	US-Canada	x	ves
			0.000			-			20	00 Trans Arabian Air											Africa	Africa		
964	CFIT	0		0 0	0 0	0	0 5	2/3/200	0	Transport	Sudan	Western	MWANZA	B707-310C	Jet	FINAL APPROACH	xx	хх	хх	Africa				No
965	Other	0	0.000	0 0	) ()	0	179 11	2/11/20	00 20	00 Air Afrique	Cote d'Ivoire	Western	DAKAR	A300B4	Jet	TAXI	XX	XX	XX	Africa	AFRICA	Africa		No
966	ARC	0	0.000	0 0	) ()	0	0 7	0 12/02/2	000 20	00 TransAfrik	Sao Tome	Western	Luanda, AO	B727	Jet	Landing - Rollout	Rain-Wind	No	100	Africa	Africa	Africa	Х	yes
967	LOC-I	1	1.000	0 3	3 3	0	0 3	0 16/02/2	000 20	00 Emery	USA	Western	Rancho Cordova, Ca	DC-8-71	Jet	T/O Initial Climb	XX	No	100	North America	NA-Car	US-Canada	Х	yes
968	RE-Landing	ARCIU	0.000	0	0	0	137 5	0 05/03/2	000 20	JU Southwest	USA	vvestern	Burbank, California	B/3/	Jet	Landing - Rollout	XX	NO	100	North America	NA-Car	US-Canada	v	VOO
969	CEIT	1	1 000	124 7	7 131	0	124 7	0 19/04/2	000 20	0 Air Philippines	Philippines	Western	Davao PH	B737	Jet	Approach	XX	No	100	Asia	Asia	Asia-Low-MdLIncome	x	Ves
970	RE-Landing	0	0.000	0 0	) ()	0	42 4	0 22/04/2	000 20	00 THY - Turkish	Turkey	Western	Siirt. TR	BAE (Avro) RJ	Jet	Landing - Rollout	Wind	No	100	Europe	Europe	NoAfr/MidEast	^	,00
	g									Airlines				(									х	ves
971	RE-Landing	0	0.000	0 0	) ()	0	0 7	0 30/04/2	000 20	00 DAS Air	Uganda	Western	Entebbe, UG	DC-10	Jet	Landing - Rollout	Rain	No	100	Africa	Africa	Africa	Х	yes
972	ARC	0	0.000	0 0	) ()	0	0 5	6/26/20	00 20	00 Yemenia	Yemen	Western	KHARTOUM	B727-200	Jet	LANDING	XX	XX	XX	Middle East	MIDDLE EAST	NoAfr/MidEast		No
973	FUEL	0	0.000	0 0	) ()	0	142 8	0 12/07/2	000 20	00 Hapag-Lloyd	Germany	Western	Vienna, AT	A300	Jet	Landing - Approach	XX	No	100	Europe	Europe	EU-EFTA	Х	yes
974	LOC-I	0.899	0.899	46 6	52	2	52 6	0 17/07/2	000 20	00 Alliance Air	India	Western	Patna, IN	B737	Jet	Approach	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
075			0.000					7/10/00	20	00 Iran Asseman	lana	N/- 1	AL IVA/A 7	E 00 4000	1-4					Middle East				N
9/5	RE-Landing	0	1.000	0 0		0	84 4	1/18/20	00	Airlines	Iran	Western	AHWAZ	F-28-4000	Jet	LANDING En Pouto	XX T Storm	XX	XX	North America	MIDDLE EAST	INOATT/MIDEAST		INO
9/0	305-22	1	1.000	0 2	2	0	0 2	0 19/07/2	000 20	Allwave transport	Canada	western	(near) Linneus, US	Guistean	Jei		Turbulanco	XX	100	North America	INA-Cal	US-Callaud	v	VAS
977	FIRE-NI	1	1 000	100 0	109	0	100 9	0 25/07/2	000 20	0 Air France	France	Western	Paris FR	Concorde	Jet	T/O Initial Climb	xx	No	100	Europe	Europe	FU-FETA	X	Ves
978	ARC	0	0.000	0 0	) 0	0	0 3	8/7/200	0 20	00 Air Memphis	Egypt	Western	CAIRO	707-328C	Jet	LANDING	XX	XX	XX	Africa	AFRICA	NoAfr/MidEast		No
979	SCF-NP	0	0.000	0 0	) ()	0	58 5	8/8/200	0 20	00 AirTran Airways	USA	Western	GREENSBORO	DC-9-32	Jet	CLIMB	XX	XX	XX	North America	NA-Car	US-Canada		No
980	LOC-I	1	1.000	135 8	3 143	0	135 8	0 23/08/2	000 20	00 Gulf Air	Qatar (Multi-Nati)	Western	Manama, BH	A320	Jet	Go Around	XX	No	100	Middle East	Asia	NoAfr/MidEast	X	yes



Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation	Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd	Date	Ye	ar Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigh - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
				0.000							200	00														
981	ARC							2		21/09/200	0	Republic of Togo	Togo		NIAMEY	707-312B	Jet	INITIAL APPROACH				Africa	AFRICA	Togo	HULL LOSS	ASEDB
982	RE-Landing	ARC	0	0.000	0	0 0	0	83	5 4	06/10/200	0 200	00 Aeromexico	Mexico	Western	Reynosa, MX	DC-9	Jet	Landing - Rollout	Rain	No	100	Latin America & Caribbean	SA/CA	CA/Carib	4 Ground	
000			0.470	0.470	70	4 00	40	150	20 0	0.01/10/000	0 000		Cinconoro	Mastara		D747	lat		Tunhaan	Na	100	Asia	Asia	Asia	fatal	yes
983	KI DE Londing		0.479	0.479	/9	4 83	48	159	20 0	) 31/10/200		00 Singapore Airlines	Singapore	Western	Taipei, Tw	B/4/	Jet	1/0 Run Landing Dollaut	Typnoon Dain Wind	NO No	100	Asia	Asia	Asia	X	yes
904			0	0.000	0		0	100	0	11/12/200		00 Cameroon Ainuava	Chana	Western		DC 0.51	Jet		Raill-Willu	INU	100	Africa	Allica	Africa	X	yes No
900			0 000	0.000	0		0	42	0	20/11/200				Western	Miami	A300	Jet	Cround taxi	**	No	100	North America	Allica NA Car	Allica US Canada	v	NO
900			0.009	0.009	0		0	100				00 American 01 Air Comini	Angolo	Western		A300	Jel	Giouriu, laxi	VV	No	100	Africa	NA-Odi Africo	Africo	A 1 Cround	yes
907	0303		0	0.000			0	0	4	03/01/200	1 200		Aliyula	western	Dulluo, AO	DIZI	Jel	Lanung - Approach	**	INU	100	Allica	Allica	Allica	fatal	VAS
				0.000		_					200	Ŋ1											Ι ΔΤΙΝ ΔΜΕΡΙCΔ &		ialai	yes
988	SCE-NP		0	0.000			0	138	8	1/9/2001	200		Bolivia	Western	BUENOS AIRES	B727-200	let		vv	vv	vv	Latin America & Caribbean	CARIBREAN	SA Mercosur		No
989			0 529	0 529	2	1 3	3	3	3 0	31/01/2001	1 200	1 Lineas Aereas	Colombia	Western	El Yonal CO	Caravelle	Jet	Landing - Approach	77 77	No	100	Latin America & Caribbean	SA/CA	SA (Northern)		110
000	2001		0.020	0.020		ľ	ľ	ľ	ľ	011011200	1200	Suramericanas	Colombia	Webtern		Odravene		Landing Approach	~~				0/10/1	or (normenn)	x	ves
990	ARC		0	0 000	0	0 0	0	136	6	2/7/2001	200	01 Iberia Airlines	Spain	Western	BII BAO	A320-210	Jet	I ANDING	xx	XX	XX	Furope	Furope	FU-FFTA	<u>^</u>	No
991	FIRE-NI		0.2	0.200	0	1 1	0	0	5 0	03/03/200	1 200	01 Thai Airways	Thailand	Western	Bangkok, TH	B737	Jet	Ground, Parked	XX	No	100	Asia	Asia	Asia-Low-Mdl Income		
								1				International													х	ves
				0.000							200	01											LATIN AMERICA &			7
992	USOS		0		0	0 0	0	0	3	3/7/2001		Skymaster Air Lines	Brazil	Western	SAO PAULO	B707-300	Jet	LANDING	xx	хх	xx	Latin America & Caribbean	CARIBBEAN	SA Mercosur		No
				0.000							200	01 Express One										North America				
993	USOS		0		0	0 0	0	0	3	3/11/2001		International	USA	Western	PONAPE	B727-200	Jet	LANDING	xx	хх	XX		NA-Car	US-Canada		No
994	ARC		0	0.000	0	0 0	0	175	7 0	) 23/03/200	1 200	01 Luxor Air	Egypt	Western	Monrovia, LR	B707	Jet	Landing - Rollout	Fog	No	100	Africa	Africa	NoAfr/MidEast	Х	yes
				0.000							200	01 Canada 3000										North America				
995	<b>RE-Landing</b>		0		0	0 0	0	0	2	4/4/2001		Airlines	Canada	Western	ST. JOHNS	B737-200	Jet	LANDING	хх	ΧХ	XX		NA-Car	US-Canada		No
996	USOS		0	0.000	0	0 0	0	6	5	5/10/2001	200	01 Angola Air Charter	Angola	Western	NZAGI	B727-100	Jet	LANDING	XX	XX	XX	Africa	AFRICA	Africa		No
997	ARC		0	0.000	0	0 0	0	98	6	5/22/2001	200	01 First Air	Canada	Western	YELLOWKNIFE	B737-200	Jet	LANDING	XX	XX	XX	North America	NA-Car	US-Canada		No
998	SCF-NP		0	0.000	0	0 0	0	88	4	5/23/2001	200	01 American Airlines	USA	Western	DALLAS	F-100	Jet	LANDING	XX	XX	XX	North America	NA-Car	US-Canada		No
999	RE-Landing		0	0.000	0	0 0	0	132	8	8/1/2001	200	01 Yemenia	Yemen	Western	ASMARA	B727-200	Jet	LANDING	XX	XX	XX	Middle East	MIDDLE EAST	NoAfr/MidEast		No
1000	RE-Landing		0	0.000	0	0 0	0	4	6	8/28/2001	200	01 Eagle Aviation	Kenya	Western	LIBREVILLE	BAC 1-11-400	Jet	LANDING	XX	XX	XX	Africa	Africa	Africa		No
				0.011							200	01											LATIN AMERICA &			
1001	SCF-PP		0.011364		1	0 1	0	82	6	9/15/2001		TAME	Ecuador	Western	BELO HORIZONTE	F-100	Jet	CRUISE	XX	ХХ	XX	Latin America & Caribbean	CARIBBEAN	SA (Northern)		No
1002	ARC		0	0.000	0	0 0	0	62	5 0	) 16/09/200	1 200	01 VARIG	Brazil	Western	Goiania, BR	B737	Jet	Landing - Rollout	Rain	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
1003	RI		1	1.000	104	6 110	0	104	6 0	08/10/200	1 200	01 SAS	Sweden (Multi-Nat)	Western	Milan, IT	MD-80	Jet	T/O Run	Fog	No	100	Europe	Europe	EU-EFTA	Х	yes
				0.000							200	01											Asia	Asia-Low-Mdl Income		
1004	SCF-NP		0		0	0 0	0	193	12	10/17/200	1	Pakistan Int'l Airlines	Pakistan	Western	DUBAI	A300B4	Jet	LANDING	XX	XX	XX	Asia				No
1005	Other		0.006757	0.007	0	1 1	1	134	14	10/20/200	1 200	01 TunisAir	Tunisia	Western	DJERBA	A300-600	Jet	PARKED	XX	XX	XX	Africa	AFRICA	NoAfr/MidEast		No
1006	LOC-I		1	1.000	251	9 260	0	243	17 5	5 12/11/200	1 200	01 American Airlines	USA	Western	Belle Harbor, NY	A300-600	Jet	T/O Climb to cruise	XX	No	100	North America	NA-Car	US-Canada	5 Ground fatal	yes
1007	CFIT		0.727	0.727	21	3 24	0	28	5 0	24/11/200	1 200	01 Crossair	Switzerland	Western	(near) Zurich, CH	BAE (Avro) RJ	Jet	Landing - Approach	Snow	No	100	Europe	Europe	EU-EFTA	Х	yes
1008	USOS		0.077	0.077	1	0 1	0	8	5 0	) 11/27/01	200	01 British Global	UK	Western	(near) Port Harcourt, NG	B747	Jet	Landing - Approach	XX	No	100	Europe	Europe	EU-EFTA	Х	yes
1010	RE-Takeoff		0.000	0.001	0	0 0	1	96	7 0	01/14/02	200	02 Lion Air	Indonesia	Western	Pekanbaru, ID	B737 (JT8D)	Jet	T/O Run	XX	No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
			0.042	0.042							200	02							Heavy Rain,			Asia	Asia	Asia-Low-Mdl Income		
1011	SCF-PP				0	1 1	0	20	4 0	01/16/02		Garuda Indonesia	Indonesia	Western	(near) Yogyakarta, ID	B737 (CFMI)	Jet	Descent	Hail	No	100				Х	yes
				1.000							200	02											LATIN AMERICA &			
1012	CFIT		1		83	9 92	0	83	9	1/28/2002		TAME	Ecuador	Western	(near) Ipiales	B727-100	Jet	INITIAL APPROACH	XX	XX	XX	Latin America & Caribbean	CARIBBEAN	SA (Northern)		No
1013	Other		0	0.000	0	0 0	0	0	3	2/28/2002	200	02 Fine Air	USA	Western	SINGAPORE	DC-8-62C	Jet	TAXI	XX	XX	XX	North America	NA-Car	US-Canada		No
1014	RE-Landing		0.000	0.000	0	0 0	0	0	3 0	03/18/02	200	02 VARIG	Brazil	Western	Belo Horizonte, BR	B727	Jet	Landing - Rollout	XX	No	100	Latin America & Caribbean	SA/CA	SA Mercosur	Х	yes
			0.771	0.781							200	02							Rain, mist,			Asia	Asia	Asia-Low-Mdl Income		
1015	CHI				120	8 128	28	155	11  0	04/15/02		Air China	China	Western	Pusan, KR	B767	Jet	Approach	VIS	No	100				X	yes
Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
-------------	------------------------	------------------	---	---	------------------------	------------------	-----------------	----------	--------------------------	------------	------	------------------------	------------------	-------------------	-------------------------------------	-------------------	------	--------------------	------------	-----------------	----------------------	---------------------------------------	--	---------------------------------	-------------	---
1016	RE-Landing		0.000	0.000	0 0	0	0	0	4 0	04/26/02	2002	Hewa Bora Airways	Congo, Zr	Western	Kinshasa, ZR	B707	Jet	Landing - Rollout	Wind, vis	No	100	Africa A	frica	Africa	Х	yes
			0.948	0.950							2002											Africa A	frica	Africa	30 Ground	
1017	LOC-I				67 6	73	2	70	7 #	05/04/02		Nicon Airways	Nigeria	Western	Kano, NG	BAC-1-11	Jet	T/O Initial Climb	XX	Yes	100				fatal	yes
	0.517		0.226	0.237		1					2002				( ) <del>-</del> ( -)				Rain - T-			Africa A	frica	NoAfr/MidEast		
1018	CFII		1 000	1 000	11 3	14	12	56	6 U	05/07/02	2002	Egyptair	Egypt	vvestern	(near) Tunis, TN	B737 (CFMI)	Jet	Approach	Storm	INO	100		aia	Hi Incomo Acio Doo	X	yes
1010	SCE ND		1.000	1.000	206 10	225	0	206	10 0	05/25/02	2002	China Airlines	Taiwan	Western	Zunini. N. di Pengnu Jelande, TW	B7/7	lot	En Pouto	vv	No	100	Asid	Sid	HI-INCOME ASIA-Pac	X	VOC
1019	RE-Landing		0.000	0.000	0 0	0	0	63	5 0	06/14/02	2002	Inter (Colombia)	Colombia	Western	Neiva CO	DC-9	Jet	Landing - Rollout	77 77	No	100	Latin America & Caribbean S	A/CA	SA (Northern)	Y	Ves
1020	rte Landing		1.000	1.000		Ť			• •	00/11/02	2002	DHL International						Landing Honout	701			Middle East A	sia	NoAfr/MidEast	69 fatal in	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
1021	MIDAIR				0 2	2	0	0	2 #	07/01/02		B.S.C.	Bahrain	Western	(near) Uberlingen, DE	B757	Jet	En Route	хх	No	100				other A/C	yes
1022	Fuel		0.920	0.925	16 7	23	2	17	80	07/04/02	2002	New Gomair	Congo, Zr	Western	(near) Bangui, CF	B707	Jet	Approach	XX	No	100	Africa A	frica	Africa	Fuel Exh	yes
1023	CFIT		0.000	0.000	0 0	0	0	0	30	07/26/02	2002	FedEx	USA	Western	Tallahasse, US	B727	Jet	Approach	XX	No	100	North America N	IA-Car	US-Canada	Color-blind	yes
				0.000							2002	America West										North America				
1024	RE-Landing		0		0 0	0	1	154	5	8/28/2002		Airlines	USA	Western	PHOENIX	A320-231	Jet	LANDING	XX	XX	XX	N	IA-Car	US-Canada		No
1025	Fuel		0.000	0.000	0 0	0	0	24	9 0	08/30/02	2002	TAM Linhas Aereas	Brazil	Western	Birigui, BR	Fokker 100	Jet	Landing	XX	No	100	Latin America & Caribbean S	A/CA	SA Mercosur	Fuel Pump	yes
1026	RE-Landing		0.000	0.000				00	4	10/21/02	2002	Acromovico	Maviaa	Mastara	Montorroy MV		let	Londing Dollaut	Rain &	No	100	Latin America & Caribbean 5	A/CA	CA/Carib		
1027	PE Landing		0	0.000		0	0	00	4 0	12/13/2003	2002			Western	SINGADORE	DC-9	Jel		vv			North America N	IA Car	LIS Canada	X	yes No
1021			0 938	0.000	0 0	-	0	0	т	12/10/2002	2002	Turkish Airlines	000	Western		00-0-020	Jet		^^	^^	~~	Furone F		NoAfr/MidEast		
1028	USOS		0.000	0.011	70 5	75	5	75	5 0	01/08/03	2000	(THY)	Turkey	Western	Divarbakir. TR	Avro RJ Avroliner		Approach	Fog	No	100				x	ves
1029	CFIT		1.000	1.000	41 5	46	0	41	50	01/09/03	2003	TANŚ	Peru	Western	(near) Chachapoyas, PE	Fokker F.28	Jet	Approach	Visibility	No	100	Latin America & Caribbean S	A/CA	SA (Northern)	Х	yes
1030	USOS		0.000	0.000	0 0	0	0	87	60	01/26/03	2003	VASP	Brazil	Western	Rio Branco, BR	B737 (JT8D)	Jet	Landing - Approach	Mist	No	100	Latin America & Caribbean S	A/CA	SA Mercosur	Х	yes
1031	LOC-I		0.990	0.991	97 6	103	1	98	60	03/06/03	2003	Air Algerie	Algeria	Western	Tamanrasset, DZ	B737 (JT8D)	Jet	T/O Initial Climb	XX	No	100	Africa A	frica	NoAfr/MidEast	SCF PP	yes
1032	RI		0	0.000	0 0	0	0	170	5	3/21/2003	2003	Transasia Airways	Taiwan	Western	TAINAN	A321-131	Jet	LANDING	XX	XX	XX	Asia A	sia	Hi-Income Asia-Pac		No
1033	USOS		0.000	0.000	0 0	0	0	53	7 0	03/26/03	2003	Royal Air Maroc	Morrocco	Western	Oujda, MA	B737 (CFMI)	Jet	Approach	Fog	No	100	Atrica A	frica	NoAfr/MidEast	Х	yes
1034			0.042	0.046	0 1	1	2	21	3 0	06/22/03	2003	Brit Air	France	Western	Brest, FK		Jet			INO No	100	Europe E	urope	EU-EF IA	X	yes
1035	SCE-NP		0.991 vv	0.992		0	0	24	11 0	8/11/2003	2003	Garuda Indonesia	Indonesia	Western		E-28-3000	Jel		vv		100	Allica A	eia	Allica Asia-Low-Mdl Income	X	No
1030	RI		0	0.000		0	0	2	7	11/29/2003	2003	Hvdro Air	South Africa	Western	LAGOS	B747-200	Jet		xx			Africa A	frica	Africa		No
1038	RE-Landing		0.000	0.000		Ť	Ŭ	-		11120/2000	2003	East African Safari		Trootom		5111 200	Jet		701	700	701	Africa A	frica	Africa		
	J J				0 0	0	0	40	4 0	12/07/03		Air Express	Kenya	Western	Lokichogio, KE	Fokker F.28		Landing - Rollout	хх	No	100				ADRM	yes
1039	ARC		0.000	0.000	0 0	0	0	94	4 0	12/13/03	2003	Nuevo Continente	Peru	Western	Lima, PE	B737 (JT8D)	Jet	Landing	ΧХ	No	100	Latin America & Caribbean S	A/CA	SA (Northern)	Х	yes
			1.000	1.000							2003	Lineas Aereas										Latin America & Caribbean S	A/CA	SA (Northern)		
1040	LOC-I				0 3	3	0	0	3 0	12/18/03		Suramericanas	Colombia	Western	(near) Mitu, CO	DC-9	Jet	Descent	XX	No	100				Х	yes
1041	ARC		0.000	0.000	0 0	0	0	0	9 0	12/18/03	2003	FedEx	USA	Western	Memphis, US	DC-10	Jet	Landing	Crosswind	No	100	North America N	A-Car	US-Canada	Х	yes
1042	RE-Landing		0.000	0.000				125	6 0	12/10/02	2003	Air Cohon	Caban	Western	Librovillo, CA		Jet	Londing Bollout	Rain - I-	Vaa	100	Africa	frico	Africo	N N	
10/3	DE Takooff		0.865	0.873	136 5	1/1	22	120	0 0	12/19/03	2003		Gabon	Western	Cotopou BI	B737 (CFIVII)	lot	Landing - Rollout	510111	No	100	A A A A A A A A A A A A A A A A A A A	frica	Allica	X	yes
1043		$\left  \right $	1 000	1 000	141 7	141	0	141	7 0	01/03/04	2003	Flash Airlines	Favat	Western	off Sharm-el-Sheikh EG	B737 (CEMI)		T/O Initial Climb	^^ YY	No	100		frica	NoΔfr/MidEast	Automation	Ves
1045	SCF-NP		0	0.000	0 0	0	0	154	26	1/15/2004	2004	Iran Air	Iran	Western	BEIJING	B747-SP	Jet	LANDING	XX	XX	XX	Middle East	IDDLE EAST	NoAfr/MidEast	natomation	No
			0.000	0.000		-	-				2004	Pakistan										Asia A	sia	Asia-Low-Mdl Income		
1046	SCF-NP				0 0	0	0	261	12 0	03/01/04		International Airlines	Pakistan	Western	Jeddah, SA	Airbus A300	Jet			No	100				х	yes
1047	SCF-NP		0.000	0.000	0 0	0	0	0	70	04/02/04	2004	Air Memphis	Egypt	Western	Cairo, EG	B707	Jet			No	100	Africa A	frica	NoAfr/MidEast	Х	yes
1048	RI		0	0.000	0 0	0	0	82	6	4/20/2004	2004	Alitalia	Italy	Western	TRIESTE	MD-82	Jet	TAXI	XX	XX	XX	Europe E	urope	EU-EFTA		No
			0.000	0.000							2004											North America N	A-Car	US-Canada		
1049	RE-Landing	ARC			0 0	0	0	0	3 0	04/28/04		Centurion Air Cargo	USA	Western	Bogota, CO	DC-10	Jet			No	100			01/0 "	X	yes
1000	WOIKW		0.000	0.001	0 0	U	11	100	4 0	07/21/04	2004	Aerocamornia	INIEXICO	western	INIEXICO CILY, IVIX	100-9	Jei			110	100	Latin America & Caribbean S	A/CA	CA/Carib	X	yes



Category Teory Definition	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculatior	l) Pax. Dead	Crew Dead Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Other Fatal ated	Yea	ar Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor	? Veight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
1051 RE-Takeoff	0.000	0.000	0 0	0 (	0	116 8	0 08/11/04	200	04 Air Guinee Express	Guinee	Western	Freetown, SL	B737 (JT8D)	Jet			No	100	Africa	Africa	Africa	X	yes
	0.000	0.000						200	04 Trans Air Cargo										Africa	Africa	Africa		
1052 RE-Landing			0 0	0 0	0	0 3	0 08/28/04		Services	Swaziland	Western	Gisenyi, RW	Aerospatiale Caravelle	Jet			No	100				x	yes
	0.000	0.003						200	04 Biman Bangladesh					Jet					Asia	Asia	Asia-Low-Mdl Income		
1053 RE-Landing AR	C		0 0	0 0	4	83 4	0 10/08/04		Airlines	Bangladesh	Western	Sylhet, BD	Fokker F.28				No	100				x	yes
	1.000	1.000						200	04 MK dba British	-									Africa				
1054 RE-Takeoff			0 7	7 7	0	0 7	0 10/14/04		Global	Ghana	Western	Halifax, CA	B747	Jet			No	100		Africa	Africa	x	yes
1055 SCF-NP	0.000	0.000	0 0	) ()	0	0 3	0 10/23/04	200	04 Beta Cargo	Brazil	Western	Manaus, BR	B707	Jet			No	100	Latin America & Caribbean	SA/CA	SA Mercosur	X	yes
1056 RE-Takeoff	0.000	0.000	0 0	) ()	0	0 4	0 11/07/04	200	04 Lufthansa Cargo	Germany	Western	Sharjah, AE	B747	Jet			No	100	Europe	Europe	EU-EFTA	X	yes
	1.000	1.000						200	04 China Yunnan					Jet					Asia	Asia	Asia-Low-Mdl Income	2 ground	
1057 LOC-I			47 6	5 53	0	47 6	2 11/21/04		Airlines	China	Western	Baotou, CN	CRJ Regional Jet				No	100				fatal	yes
	0.000	0.000						200	04 KLM Royal Dutch										Europe	Europe	EU-EFTA		
1058 SCF-NP			0 0	0 0	0	140 6	0 11/28/04		Airlines	Neder	Western	Barcelona, ES	B737 (CFMI)	Jet			No	100				х	yes
	0.153	0.174						200	)4										Asia	Asia	Asia-Low-Mdl Income		
1059 RE-Landing AR	C		23 2	2 25	59	156 7	0 11/30/04		Lion Air	Indonesia	Western	Solo, ID	MD-80	Jet			No	100				Х	yes
1060 RI-A	0	0.000	0 0	) ()	0	0 4	1/3/2005	200	05 Asia Airlines	Indonesia	Western	BANDA ACEH	B737-200	Jet	LANDING	XX	XX	XX	Asia	Asia	Asia-Low-Mdl Income		No
1061 RI-A	0.000	0.000	0 0	0 0	0	0 4	0 01/04/05	200	05 Tri MG Airlines	Indonesia	Western	Banda Aceh, ID	B737 (JT8D)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
	0.000	0.000						200	05 AeroRepublica										Latin America & Caribbean	SA/CA	SA (Northern)		
1062 ARC			0 0	0 (	0	106 6	0 01/08/05		Colombia	Colombia	Western	Cali, CO	MD-80	Jet			No	100				Х	yes
1063 RE-Landing	0	0.000	0 0	0 (	0	0 3	1/24/2008	5 200	05 Atlas Air	USA	Western	DUSSELDORF	B747-200	Jet	LANDING	XX	XX	XX	North America	NA-Car	US-Canada		No
1064 Ramp	0.01	0.000	0 1	1 1	0		2/1/2005	200	05 Air France	France	Western	PARIS	A319	Jet	PARKED	XX	XX	XX	Europe	Europe	EU-EFTA		No
1065 CFIT	1.000	1.000	98 6	5 104	0	98 6	0 02/03/05	200	05 Kam Air	Afghanistan	Western	Afghanistan	B737 (JT8D)	Jet			No	100	Asia	Asia	ASIA CEN	Х	yes
	0.000	0.000						200	05 Cargo Plus Aviation dba Rainbow Air										Africa	Africa	Africa		
1066 CFIT			0 0	0	0	0 5	0 03/19/05		Cargo	Ethiopia	Western	(near) Kampala, UG	B707	Jet			No	100				X	yes
1067 USOS	0.000	0.001	0 0	0	1	61 4	0 04/07/05	200	05 ICARO Air	Ecuador	Western	Coca, EC	Fokker F.28	Jet			No	100	Latin America & Caribbean	SA/CA	SA (Northern)	X	yes
1068 GCOL	0.000	0.001	0 0	) ()	1	5 94	0 05/10/05	200	05 Northwest	USA	Western	Minneapolis, US	DC-9	Jet			No	100	North America	NA-Car	US-Canada	Х	yes
1069 RE-Landing	0.000	0.000	0 0	0 0	0	201 14	0 07/01/05	200	05 Biman Bangladesh Airlines	Bangladesh	Western	Chittagong, BD	DC-10	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
	0.000	0.000						200	)5	_		-							Europe	Europe	EU-EF IA		
10/0 RE-Landing AF	0 1 000	1.000	0 0		0	29/ 12	0 08/02/05	000	Air France	France	Western	Toronto, CA	AIRDUS A340	Jet			NO	100	Furene			X	yes
10/1 UTHER	1.000	1.000	115 6	121	0	115 6	0 08/14/05	200	Jo Hellos	Greece	vvestern	(near) Grammatikos, GR	B/3/ (CFMI)	Jet			INO	100	Europe		EU-EFTA	X	yes
1072 1 0 0 1	1.000	1.000	150 0	100	0	152 0	0 00/40/05	200	Ainvovo	Colombia	Master	(near) Machimuse V/F		let			Nic	100	Laun America & Caribbean	SAVCA	SA (Northern)	,	1/00
1072 LOG-1	0	0.000	152 0		0	318 16	8/10/200	5 200	All ways		Western	GUAM	R747 200	Jei		vv	NU VV	100	North Amorica	NA Cor	LIS Canada	٨	No
	0.409	0.000	35 5	5 40	0	01 7	0 08/22/05	200	5 TANS	Doru	Western		B737 (JT8D)	Jei	Approach	T-Storm	No	100	Latin America & Caribboon	SA/CA	SA (Northern)	V	VAC
	1.000	1 000	55 5	40	0	51 /	0 00/23/05	200			western	(iicai) Fucalipa, FE		Jei	πρρισασι	1-310111	NU	100			Asia-Low-MdLIncomo	A Ground	yes
1075 1 0 0 1	1.000	1.000	00 5	104	0	00 5	# 00/05/05	200	Mandala Airlines	Indonosia	Westorn	Modan ID		lot			No	100	Asia	Asia	Asia-Low-Initi Income	fatal	VOC
1076 RE-Landing AE	C	0.000	35 0	, 104	0	33 3	# 03/03/03	200		indulicaid	WESIEIII	moudil, iD		JEI			NU	100		Asia	Asia-Low-MdL Incomo		yes
	0	0.000	0		0	113 8	10/0/2004	5	Sahara India Airlinos	India	Western	BOMBAY	B737-400	let		vv	YY	vv	Asia	noid			No
	1 000	1 000	111 6	3 117	0	111 6	0 10/3/200	200	5 Bellyiew Airlines	Nigeria	Western		B737 (JT8D)	let		~~	No	100	Africa	Africa	Africa	Y	VAS
1078 RE-Landing	0.000	0.000			0	0 3	0 10/22/05	200	5 MIRA Aviation	Congo Zr	Western	Kindu 7R	B727	let			No	100	Africa	Africa	Africa	N N	Ves
1070 RE-Landing	0.000	0.000			0	32 6	0 11/1//05	200	15 Asian Spirit	Philippines	Western	Catarman PH	HS 146	let			No	100	Asia		Asia-Low-MdLincomo	N N	Ves
1080 RE-Landing	0.000	0.000			0	02 0	0 11/14/00	200		r milippines	Western			001		Snow	110	100	North America	noid		A	,00
	0.000	0.000	0		0	98 5	1 08/12/200	15	Southwest	USA	Western	Chicago Midway	B737-700	let	Landing - Rollout	freezing for	No	70	non nanonoa	NA-Car	US-Canada	ADRM	Ves
1081 USOS	0 901	0 991	101 7	7 108	1	102 7	0 12/10/05	200	15 Sosoliso Airlines	Nigeria	Western	Port Harcourt NG	DC-9	Jet			No	100	Africa	Africa	Africa	Y	Ves
1082 RE-Landing	0	0.000	0 0	) ()	0	138 6	3/4/2006	200	)6 I ion Air	Indonesia	Western	SURABAYA	MD-82	Jet	LANDING	XX	XX	XX	Asia	Asia	Asia-Low-MdLIncome	~	No
1083    OC-	1 000	1 000	105 8	3 113	0	105 8	0 05/03/06	200	)6 Armavia	Armenia	Western	off Sochi RU	Airbus A320	Jet			No	100	CIS	Europe	Furo Fast	X	ves
1084 RE-Landing	0.000	0.000	0 0		0	0 3	0 06/04/06	200	6 Arrow Cargo	USA	Western	Managua NI	DC-10	Jet			No	100	North America	NA-Car	US-Canada	X	ves
1085 RE-Takeoff	0.000	0.000	0 0		Ő	0 5	0 06/07/06	200	6 TradeWinds Airlines	USA	Western	Medellin, CO	B747	Jet			No	100	North America	NA-Car	US-Canada	X	ves
	0.000	0.000		-				200			1												

Category Definition	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead Crew Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd Crew OnBd	Date	Year	r Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weigl - C/C	AIR Claims Loss	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
1086 USOS	0.000	0.000	0 0	0 (	0	0 2 0	06/15/06	2006	TNT Airways	Belgium	Western	Birmingham, GB	B737 (CFMI)	Jet			No	100	Europe	Europe	EU-EFTA	Х	yes
1087 RE-Landing	0	0.000	0 0	0 (	0	14 10	6/23/2006	2006	AMC Aviation	Egypt	Western	JUBA	MD-83	Jet	LANDING	XX	XX	XX	Africa	AFRICA	NoAfr/MidEast		No
1088 RE-Landing	0.616	0.627	120 5	125 4	41	195 8 0	07/09/06	2006	S7 Airlines	Russia	Western	Irkutsk, RU	Airbus A310	Jet			No	100	CIS	Europe	Euro East	Х	yes
1089 SCF-NP	0.000	0.000	0 0	0 (	0	0 3 0	07/28/06	2006	FedEx	USA	Western	Memphis, US	DC-10	Jet			No	100	North America	NA-Car	US-Canada	Х	yes
1090 SCF-NP	0.000	0.000	0 0	0 (	0	0 3 0	0 08/17/06	2006	Aerosucre Colombia	Colombia	Western	Bogota, CO	B727	Jet			No	100	Latin America & Caribbean	ISA/CA	SA (Northern)	Х	yes
1091 RE-Takeoff	0.980	0.981	47 2	49	1	47 3 0	08/27/06	2006	Comair	USA	Western	Lexington, US	CRJ Regional Jet	Jet			No	100	North America	NA-Car	US-Canada	Х	yes
1092 RE-Landing	0.000	0.000	0 0	0 (	0	0 3 0	) 09/07/06	2006	DHL Aviation	So Africa	Western	Lagos, NG	B727	Jet			No	100	Africa	Africa	Africa	Х	yes
1093 MIDAIR	1.000	1.000	148 6	154 (	0	148 6 0	0 09/29/06	2006	GOL Linhas Aereas	Brazil	Western	(near) Peixote Azevedo, BR	B737 (NG)	Jet			No	100	Latin America & Caribbean	SA/CA	SA Mercosur	x	yes
1094 RE-Landing	0.000	0.000	0 0	0 (	0	104 6 0	) 10/03/06	2006	Mandala Airlines	Indonesia	Western	Tarakan, ID	B737 (JT8D)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
1095 RE-Landing	0.250	0.272	3 1	4 6	6	13 3 0	0 10/10/06	2006	6 Atlantic Airways (Faroe Islands)	Faroe Islands	Western	Stord, NO	HS 146	Jet			No	100	Europe	Europe	EU-EFTA	x	yes
1096 WSTRW	0.914	0.919	92 4	96 8	8	100 5 0	) 10/29/06	2006	ADC Airlines	Nigeria	Western	Abuja, NG	B737 (JT8D)	Jet			No	100	Africa	Africa	Africa	X	yes
1097 RE-Landing	0.000	0.000	0 0	0 (	0	4 3 C	) 11/17/06	2006	Cielos Airlines	Peru	Western	Barranquilla, CO	DC-10	Jet			No	100	Latin America & Caribbean	SA/CA	SA (Northern)	х	yes
1098 CFIT	1.000	1.000	2 3	5 (	0	2 3 0	) 11/18/06	2006	Aerosucre Colombia	Colombia	Western	(near) Leticia, CO	B727	Jet			No	100	Latin America & Caribbean	SA/CA	SA (Northern)	Х	yes
1099 ARC	0.000	0.000	0 0	0 (	0	157 7 0	) 12/24/06	2006	Lion Air	Indonesia	Western	Ujung Pandang, ID	B737 (CFMI)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
1100 LOC-I	1.000	1.000	96 6	102 (	0	96 6 C	01/01/07	2007	Adam Air	Indonesia	Western	off Makassar, ID	B737 (CFMI)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	Х	yes
1101 USOS	0.000	0.000	0 0	0 0	0	0 4 0	01/13/07	2007	Gading Sari Aviation	Malaysia	Western	Kuching, MY	B737 (JT8D)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
1102 RE-Takeoff	0.000	0.000	0 0	0 0	0	50 4 1	1 01/25/07	2007	Regional	France	Western	Pau, FR	Fokker 100	Jet			No	100	Europe	Europe	EU-EFTA	1 Ground fatal	ves
1103 SCF-NP	0	0.000	0 0	0 (	0	0 3	2/4/2007	2007	/ Tampa Cargo	Colombia	Western	MIAMI	DC-8-71F	Jet	LANDING	XX	XX	XX	Latin America & Caribbean	SA/CA	SA (Northern)		No
1104 ARC	0.000	0.000	0 0	0 (	0	148 6 0	02/21/07	2007	Adam Air	Indonesia	Western	Surabaya, ID	B737 (CFMI)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	х	yes
1105 RE-Landing	ARC 0.150	0.155						2007	·				, , , , , , , , , , , , , , , , , , ,						Asia	Asia	Asia-Low-Mdl Income		,
			20 1	21 '	12	133 7 0	03/07/07		Garuda Indonesia	Indonesia	Western	Yogyakarta, ID	B737 (CFMI)	Jet			No	100				х	yes
		0.000					0.11.0.0007	2007	Biman Bangladesh				1010 005		THEOFE					Asia	Asia-Low-Mdl Income		
1106 Other	0	0.000	0 0	0 (	0	236 14	3/12/2007	0007	Airlines	Bangladesh	Western	DORVI	A310-325	Jet	TAKEOFF	XX	XX	XX	Asia	A - ' -			NO
1107 DE Londing	0.000	0.000			<u> </u>	20 20 0	70/22/07	2007	Ariana Argnan	Afabanistan	Western	latanhul TD	Airbus A200	lot			No	100	Asia	Asia	ASIA CEN	v	1400
1107 RE-Landing	1 000	1 000	105 0	111	0		05/05/07	2007		Kenva	Western	(near) Douala, CM	B737 (NC)	Jel			No	100	Africa	Africa	Africa	X	yes
1100 ARC	0.000	0.000	0 0	0 0	0	37 3 0	05/20/07	2007	Air Canada Jazz	Canada	Western	Toronto CA	CR.I Regional Jet	Jet			No	100	North America	NA-Car	US-Canada	^ Y	Ves
	0.063	0.063			-		00/20/01	2007	TAAG - Angola		1100(0111							100	Africa	Africa	Africa	1 Ground	,
1110 USOS			4 1	5 (	0	74 6 1	1 06/28/07		Airlines	Angola	Western	M'Banza Congo, AO	B737 (JT8D)	Jet			No	100				fatal	yes
	1.000	1.000						2007	'				(				-		Latin America & Caribbean	SA/CA	SA Mercosur	12 Ground	
1111 RE-Landing			181 6	187 (	0	181 6 #	# 07/17/07		TAM Linhas Aereas	Brazil	Western	Sao Paulo, BR	Airbus A320	Jet			No	100				fatal	yes
	0.000	0.000						2007	AeroRepublica										Latin America & Caribbean	SA/CA	SA (Northern)		
1112 RE-Landing			0 0	0 (	0	54 5 C	07/17/07		Colombia	Colombia	Western	Santa Marta, CO	EMB 190	Jet			No	100				х	yes
1113 SCF-NP	0.000	0.000	0 0	0 (	0	157 8 0	08/20/07	2007	China Airlines	Taiwan	Western	Naha, JP	B737 (NG)	Jet			No	100	Asia	Asia	Hi-Income Asia-Pac	Х	yes
1114 ARC	0.529	0.529	85 5	90 (	0	40 ## C	09/16/07	2007	One-Two-Go	Thailand	Western	Phuket, TH	MD-80	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	х	yes
1115 SCF-NP	0.000	0.000	0 0	0 (	0	156 7 0	10/11/07	2007	AMC Airlines	Turkey	Western	Istanbul, TR	MD-80	Jet			No	100	Europe	Europe	NoAfr/MidEast	X	yes
1116 RE-Landing	ARC 0.000	0.000	0 0	0 (	0	148 6 0	0 10/26/07	2007	Philippine Airlines	Philippines	Western	Butuan City, PH	Airbus A320	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	x	yes
1117 ARC	0.000	0.000	0 0	0 (	0	89 <u>5</u> C	) 11/01/07	2007	Mandala Airlines	Indonesia	Western	Malang, ID	B737 (JT8D)	Jet			No	100	Asia	Asia	Asia-Low-Mdl Income	X	yes
1118 ARC	0.000	0.000	0 0	0 (	0	335 14 0	) 11/09/07	2007	Iberia	Spain	Western	Quito, EC	Airbus A340	Jet			No	100	Europe	Europe	EU-EFTA	Х	yes
	1.000	1.000						2007	World Focus Airlines	;									Europe	Europe	NoAfr/MidEast		
1119 CFIT			50 7	57 (	0	50 7 0	) 11/30/07		dba Atlasjet Airlines	Turkey	Western	(near) Isparta, TR	MD-80	Jet			No	100				x	yes
1120 RI	0.000	0.000	0 0	0 (	0	117 6 0	) 12/30/07	2007	TAROM	Romania	Western	Bucharest, RO	B737 (CFMI)	Jet			No	100	Europe	Europe	Euro East	Х	yes



Accident ID	Category Definition	Previously ARC	Severity (Portion of People on Board Fatal)	Working Column - Serverity (Calculation)	Pax. Dead	Tot Fatal (onBd)	Ser-ious (OnBd)	Pax OnBd	Crew OnBd Other Fatal	Date	Year	Operator	Operator Country	A/C Mnf Region	Location	Aircraft	Jet?	Phase of Flight	Wx Factor?	Weight - C/G	AIR Claims Loss %	Operator Country Region (ICAO)	Operator Country Region (Airclaims)	Operator Country Sub- Region	Note	Accidents in 1987-2007 data set
1121	LOC-I		XX	0.000	0 0	0	0	107	6	1/2/2008	2008	Iran Air	Iran	Western	TEHRAN	F-100	Jet	TAKEOFF	XX	XX	XX	Middle East	MIDDLE EAST	NoAfr/MidEast		No
1122	FUEL		0	0.000	0 0	0	1	137	16	1/17/2008	2008	British Airways	United Kingdom	Western	LONDON	B777-200	Jet	FINAL APPROACH	XX	XX	XX	Europe	Europe	EU-EFTA		No
1123	FUEL		0	0.000	0 0	0	0	159	8	2/1/2008	2008	LAB	Bolivia	Western	Near Trinidad	B727-200	Jet	FINAL APPROACH	xx	xx	xx	Latin America & Caribbean	LATIN AMERICA & CARIBBEAN	SA Mercosur		No
1124	Other		0	0.000	0 0	0	0	0	-	2/2/2008	2008	Atlas Air	USA	Western	LOME	B747-200FM	Jet	INITIAL CLIMB	XX	XX	XX	North America	NA-Car	US-Canada		No
1125	ICE		XX	0.027	0 0	0	10	18	3	2/14/2008	2008	Belavia	Belarus	Western	Yerevan, AM	CRJ-100	Jet					CIS	CIS	Euro East		No
1126	SCF-NP		0	0.000	0 0	0	0	5	3	3/6/2008	2008	Manunggal Air	Indonesia	Western	Wamena, ID	Transall C-160	Jet					Asia	Asia	Asia-Low-Mdl Income		No
1127	ARC		0	0.000	0 0	0	0	169	5	3/10/2008	2008	Adam Air	Indonesia	Western	BATAM, BATU BESAR	B737-400	Jet	LANDING	XX	XX	XX	Asia	Asia	Asia-Low-Mdl Income		No
1128	SCF-NP		0	0.000	0 0	0	0	307	19	3/25/2008	2008	Saudia	Saudi Arabia	Western	DACCA	B747-300	Jet		XX	XX	XX	Middle East	MIDDLE EAST	NoAfr/MidEast		No
1129	RE-Takeoff		0.174419	0.215	15 0	15	60	79	7	4/15/2008	2008	Hewa Bora Airways	Congo, ZR	Western	GOMA	DC-9-51	Jet	TAKEOFF	XX	XX	XX	Africa	Africa	Africa		No
1130	RE-Landing		0	0.000	0 0	0	0	67	6	4/22/2008	2008	Carpatair	Romania	Western	BUCHAREST	BAe 146-200	Jet	LANDING	XX	XX	XX	Europe	Europe	Euro East		No
1131	RE-Takeoff		0	0.000	0 0	0	0	0	5	5/25/2008	2008	Kalitta Air	USA	Western	BRUSSELS	B747-200FM	Jet	TAKEOFF	XX	XX	XX	North America	NA-Car	US-Canada		No
1132	RE-Landing	ARC	0.021739	0.047	2 1	3	60	131	7	5/30/2008	2008	IACA International Airlines	El Salvador	Western	TEGUCIGALPA	A320-200	Jet	LANDING	xx	xx	хх	Latin America & Caribbean	SA/CA	CA/Carib		No
1133	RE-Landing	ARC	0.125	0.131	32 1	33	27	252	12	6/10/2008	2008	Sudan Airways	Sudan	Western	KHARTOUM	A310-300	Jet	LANDING	xx	xx	xx	Africa	Africa	Africa		No
1134	SCF-NP		0	0.000	0 0	0	0	0	2	6/28/2008	2008	ABX Air	USA	Western	SAN FRANCISCO	B767-200	Jet	PARKED	XX	XX	XX	North America	NA-Car	US-Canada		No
1135	CFIT		0.5	0.529	0 1	1	1	0	2	7/6/2008	2008	U.S.A. Jet Airlines	USA	Western	SALTILLO	DC-9-15	Jet	FINAL APPROACH	XX	XX	ΧХ	North America	NA-Car	US-Canada		No
1136	SCF-PP		0	0.022	0 0	0	3	0	8	7/7/2008	2008	Kallitta as Centurion Air Cargo	USA	Western	(near) BOGOTA	747-200FM	Jet	INITIAL CLIMB	xx	xx	xx	North America	NA-Car	US-Canada		No
1137	RE-Landing	ARC	vv	0.000	0 0	0	0	11	6	7/14/2008	2008	Chanchangi Airlinos	Nigoria	Western	Port Harcourt, NG	R737 200	lot					Africa	Africa	Africa		No
1138			0 895349	0.901	148 6	154	18	166	6	8/20/2008	2008	Snanair	Snain	Western		MD_82			1 YY	VY V	vv	Furone	Furone	FILEETA		No
1100	2001		0.000040	0.331	140 0	104	10		<u> </u>	0/20/2000	2008	"ITEK AIR"	opun	Western	Near Bishkek-Manas		001	IN INCLOIT				CIS		ASIA CEN		
1139	CEIT		0 722222	0.100	65 0	65	25	84	6	8/24/2008		AirCompany	Kyrovzstan	Western	International Airport	B737-200	Jet	FINAL APPROACH	xx	xx	xx	0.0	CIS			No
1140	RE-Landing		0	0.007	0 0	0	16	123	6	8/27/2008	2008	Sriwijava Air	Indonesia	Western	JAMBI	B737-200	Jet	LANDING	XX	XX	XX	Asia	Asia	Asia-Low-Mdl Income		No
1141	LOC-I		1	1.000	82 6	88	0	82	6	9/14/2008	2008	Aeroflot-Nord	Russia	Western	Near Perm, Russia	B737-500	Jet	INITIAL APPROACH	XX	XX	XX	CIS	CIS	Euro East		No
1142	RF-Takeoff		yy	0.003	0 0	0	3	62	4	9/22/2008	2008	ICARO	Ecuador	Western		E-28-4000	let		yy	vv	vy	Latin America & Caribbean		SA (Northern)		No
1143	ARC		0	0.000		0	0	138	6	10/1/2008	2008	Kaliningradavia	Russia	Western		B737-300	Jet		XX	XX	YY	CIS	CIS	Furo Fast		No
1144	RE-Landing	ARC	•	0.000	ř ľ		<u> </u>	100	~	10/11/2000	2008	i talimingradavia					001			~	~		ISA/CA	SA (Northern)		
	Lunung		0	0.000	0 0	0	0	47	7	10/16/2008		Rutaca	Venezuela	Western	CARACAS	B737-200	Jet	LANDING	xx	xx	xx	Latin America & Caribbean				No
1145	Other-Bird		0	0.000	0 0	0	0	166	6	11/10/2008	2008	Ryanair	Ireland	Western	ROME	B737-800	Jet	FINAL APPROACH	XX	XX	XX	Europe	Europe	EU-EFTA		No
1146	RE-Takeoff		0	0.002	0 0	0	5	110	5	12/20/2008	2008	Continental Airlines	USA	Western	DENVER	B737-500	Jet	TAKEOFF	XX	XX	xx	North America	NA-Car	US-Canada		No

Ъ



World Wide Hull Loss and Fatal Jet Accidents\*

\*CAST Data - CICTT Categories, Western Built Jet Airplanes, Part 121 Equivalent Operations

Figure A15.1a

# 1987-2001 (329 accidents) 2002-2008 (137 accidents)





Intentionally blank



## **15.2 EBT ANALYSIS OF CAST+ DATA**



Figure 4.2.13.1 dup





Figure 4.2.13.1a du





Figure 4.2.13.1b dup



Figure 4.2.13.4 d



## APPENDIX 16 SUMMARY TRAINING TOPIC DERIVATION PROCESS

#### RESULTS

Results of the Evidence Table analysis combined with Accident and Incident analysis:

Combine and collate threats/errors and states to develop Training Topics for Baseline Program

Critical Threats, Errors & Manoeuvres for training programme design

Training Topics for the Baseline Program, frequency as follows:

- A to be included in every module
- B to be included in every other module
- C to be included once in the 3-year cycle



#### **EVIDENCE TABLE**

The sources listed were analysed and the table complied as follows

- 1. Statements that meet the objectives of the EBT Data Report
- 2. Statements containing evidence that is compelling in terms of convergence with other sources
- 3. Statements from scientifically reliable and statistically significant studies where applicable
- 4. Statements considering topics according to training criticality
  - LOSA Reports
  - EBT Flight Data Analysis
  - **UK CAA Accident Studies**
  - IATA Safety Reports
  - AQP Study

  - ATQP Study STEADES Training Query
  - Airline Pilot Survey on Training
  - Effectiveness
  - Factors that influence skill decay and retention
  - Skill retention after training
  - Automation training practitioners guide
  - The interfaces between flight crews &
  - modern flight deck systems FAA Long aircraft type/variant difference
  - on landing
  - A study of the normal operational landing performance on subsonic civil narrow body jet aircraft during ILS approaches -NIR
  - TAWS "Saves"
  - CAST Accident Study

Statements allocated priority A, B, C

#### EBT ACCIDENT INCIDENT ANALYSIS

(All reported accident, fatal and non-fatal, plus serious incidents (NTSB Database) 1962-2010, involving jet aircraft with a minimum of 50 seats, turboprop aircraft with a minimum of 30 seats) Steps are as follows:

- Factor analysis (39 factors from the TCS)
- Analysis of competency issues (coincident with factor analysis)
- Analysis of all factors
- All 6 steps taken unless otherwise indicated, or when data are statistically not relevant

#### Note 1 – Normalisation according to:

- All Accidents & Incidents
- Aircraft Generation & Severity
  - (All accidents, fatal accidents only, serious incidents only)
- Number of departures (except turbopropsno normalisation data)

Note 2 – Results expressed as rates and sometimes as risk (global analysis only likelihood times severity)

- Filter Generation (for global analysis show also values combined across generations) 2
- Filter Competency (global analysis only) Trend over time (Last 15 years versus 3 previous except Gen4 jets which is Last
- 11 years versus previous) Clustering of factors 4
- 5. Flight phase
- 6. Training Effect
  7. FSTD Trainability
- 8. Conclusion, with relative weighting, for training programme design

#### 9. Priority allocation A, B, C

#### TRAINING CRITICALITY SURVEY

39 factors were considered

#### Step 1

For a given generation take the median of the distribution of the calculated results from the risk matrix (product of likelihood, severity and training effect) across all phases. Everything above the median should be considered provided the Training Effect is 3 or above.

#### Step 2

Take the median of the distribution of the risk (product of likelihood and severity) across all flight phases. Retain everything that is above this median and has not been already considered in Step 1.

#### Step 3

Take all items with a training benefit 4 or above. Retain everything that has not been already considered in Phase 1 or 2.

Any item evaluated to be relevant in only one flight phase needs to be considered in that specific phase. Any item evaluated to be relevant in multiple phases can be trained in any of these phases.

Step 4 – Correlation with EBT Accident and Incident Analysis

Note as a result of relatively low submission numbers it was decided not to adjust any training programme priorities or topics as a result of TCS correlations. The methodology and results are published because the process was considered very useful for future studies. Correlations in general were very strong given the limited data set.



## **Background – Prioritization**

Prioritization of the training topics is probably the most important result from the EBT data analysis. It is a key part in the process for translating data into useful events and scenarios to assess and develop pilot performance in recurrent training programs. This result is the first rigorous attempt to rank parameters such as threats, errors and competencies, along with factors affecting accidents and serious incidents, from multiple data sources systematically to formulate a recurrent training program.

The exercise shows the feasibility of collecting an adequate set of operational and training data; developing the necessary methods to analyze that data, while corroborating results to produce a criticality ranking of training topics. The prioritization process occurs for each of the 6 generations of aircraft by ordering critical parameters so as to highlight differences and commonality. There is sufficient flexibility in the process to allow enhancement according to mission, culture and type of aircraft. The data in the process are also used as material to build scenarios for use in recurrent assessment and training conducted in an FSTD qualified for the purpose according to the *Manual of Criteria for the Qualification of Flight Simulation Training Devices* (Doc 9625), Volume I – Aeroplanes.

The process used is transparent and repeatable and results in a unique prioritization, according to aircraft generation. Three levels of priority A, B and C were used to determine the frequency of pilot exposure to the defined training topics within a 3-year rolling recurrent training program (see Section 7, paragraph 3).

Most of the data referred to in this report has been analyzed and are contained within the Evidence Table, and the EBT Accident and Incident Study. The Evidence Table consists of data from multiple sources and has the capability to sort as well as corroborate analytical results. It represents a robust set of evidence and it is a primary tool used in determining results. The EBT Accident and Incident Study has 3045 reports feeding the analysis, making it comprehensive as well as sensitive in developing prioritization of results and discriminating by aircraft generation. Prioritization of training topics by generation uses both of these tools. In some cases, depending on the data, the assessment and training topics are drawn from both sources, or from the Evidence Table alone or from the Accident and Incident Study alone. While the prioritization itself results from an algorithmic process, all analytical results were provided to the EBT Project Group comprising training experts and professionals in training scenario creation. Their utilization of the results served as an experiential validation.

Any set of historical data is necessarily finite. Using these data assumes a large set of experience will have strong predictive validity even though the environment is constantly changing. These challenges were accepted because statistical and quality control principles were adhered to and, more importantly, the results from data analysis were applied in the context of professional experience and expertise.

For the creation of the EBT recurrent training program defined in this manual, a cautious approach was taken, and the suggested frequency of training is higher than the results indicate unless the corroborating data is very strong. An example of this could be illustrated in the EBT Accident and Incident Study where the data imply different training frequency in adjacent generations. If the data are quite strong in the generation that demands more training, the training category in the adjacent generation is upgraded.

Operational and training data from multiple sources indicate that pilots operating the more modern generation aircraft take less time to achieve competence in the performance of certain maneuvers. Modern generation aircraft are also more complex, and pilots have more to learn for achieving a defined level of competency to operate. While the number of assessment and training topics is slightly fewer in early aircraft generations, the training time in the FTSD should be largely the same.



## Summary of training topics

The following table represents the lists of training topics derived from data analysis, to which have been added topics that, despite not being indicated by significant data, were considered to be an important facet of a recurrent assessment and training program. These are highlighted in grey.

## **Generation 4 Jets**

		Adverse weather		Adverse wind		ATC
		Automation management		Aircraft system malfunction		Engine failure
s		Competencies non-technical (CRM)		Aircraft System management		Fire and smoke management
pic		Compliance		Approach, visibility close to minimum		Loss of communications
P		Error management		Landing		Managing loading, fuel, performance errors
jing		Go-Around management		Runway or taxiway condition		Navigation
rair	Α	Manual aircraft control	В	Surprise	С	Operations or type specific
et T		Mismanaged aircraft state		Terrain		Pilot incapcitation
4 J		Monitoring & cross-checking		Workload, distraction, pressure		Traffic
3en		Unstable approach				Upset recovery
0						Windshear recovery

## **Generation 3 Jets**

		Adverse weather		Adverse wind		ATC
		Automation management		Aircraft system malfunction		Engine failure
S		Competencies non-technical (CRM)		Aircraft system management		Fire and smoke management
pic		Compliance		Approach, visibility close to minimum		Loss of communications
1 To		Error management		Landing		Managing loading, fuel, performance errors
jing		Go-Around management		Surprise		Navigation
rair	Α	Manual aircraft control	В	Windshear recovery	С	Operations or type specific
et T		Mismanaged aircraft state		Workload, distraction, pressure		Pilot incapcitation
3 J		Monitoring & cross-checking				Runway or taxiway condition
3en		Unstable approach				Terrain
0						Traffic
						Upset recovery



## **Generation 3 Turboprops**

		Adverse weather		Aircraft system malfunctions		Adverse wind
ş		Automation management		Aircraft system management		Engine Failure
ppic		Competencies non-technical (CRM)		Approach, visibility close to minimum		Fire and smoke management
дŢ		Compliance		Landing		Loss of communications
ning		Error management		Surprise		Managing loading, fuel, performance errors
<b>I</b> rai		Go-Around management		Terrain		Navigation
ď	Α	Manual aircraft control	В	Upset recovery	С	Operations or type specific
pro		Mismanaged aircraft state		Workload, distraction, pressure		Pilot incapcitation
rba		Monitoring & cross-checking				Runway or taxiway condition
ЗŢ		Unstable approach				Traffic
en.						Windshear recovery
0						

## **Generation 2 Jets**

		Adverse weather		Adverse wind		Loss of communications
		Approach, visibility close to minimum		Aircraft system malfunction		Managing loading, fuel, performance errors
s		Automation management		Compliance		Navigation
pic		Competencies non-technical (CRM)		Engine Failure		Operations or type specific
1		Error management		Fire and smoke management		Pilot incapcitation
jing		Go-Around management		Landing		Runway or taxiway condition
rair	Α	Manual aircraft control	В	Mismanaged aircraft state	С	Terrain
et T		Monitoring & cross-checking		Surprise		Traffic
2 J		Unstable approach		Windshear recovery		Upset recovery
3en						
0						

## **Generation 2 Turboprops**

		Adverse weather		Aircraft system malfunctions		Adverse wind
Ś		Automation management		Aircraft system management		Engine Failure
ppic		Competencies non-technical (CRM)		Approach, visibility close to minimum		Fire and smoke management
ац		Compliance		Landing		Loss of communications
ning		Error management		Surprise		Managing loading, fuel, performance errors
<u></u> Lrai		Go-Around management		Terrain		Navigation
d	Α	Manual aircraft control	В	Upset recovery	C	Operations or type specific
opro		Mismanaged aircraft state		Workload, distraction, pressure		Pilot incapcitation
rrba		Monitoring & cross-checking				Runway or taxiway condition
ЗŢ		Unstable approach				Traffic
en						Windshear recovery
Ċ						



## APPENDIX 17 LINKS TO DATA ADDITIONAL DATA SOURCES

The following list contains links to studies referenced in this report:

UK CAA CAP 776	http://www.caa.co.uk/application.aspx?catid=33&pagetype=65&appid=11&mo de=detail&id=3198
UK CAA CAP 780	http://www.caa.co.uk/application.aspx?catid=33&pagetype=65&appid=11&mo de=detail&id=3325
FAA Factors that Influence Skill Decay and Retention	http://www.owlnet.rice.edu/~antonvillado/courses/09a_psyc630001/Arthur, Bennett, Stanush, & McNelly (1998) HP.pdf
NLR A Study of Normal Operational Landing Performance on Subsonic Civil Narrow Body Jet Aircraft during ILS Approaches	http://www.tc.faa.gov/its/worldpac/techrpt/ar077.pdf
IATA Safety Report 2008	http://www.iata.org/about//iata- annual- report- 2008.pdf
IATA Safety Report 2009	http://www.iata.org/pressroom/Documents/IATAAnnualReport2009.pdf



## Data Report for Evidence-Based Training

July 2013



International Air Transport Association Montreal–Geneva

## NOTICE

DISCLAIMER. The information contained in this publication is subject to constant review in the light of changing government requirements and regulations. No subscriber or other reader should act on the basis of any such information without referring to applicable laws and regulations and/or without taking appropriate professional advice. Although every effort has been made to ensure accuracy, the International Air Transport Association shall not be held responsible for any loss or damage caused by errors, omissions, misprints or misinterpretation of the contents hereof. Furthermore, the International Air Transport Association expressly disclaims any and all liability to any person or entity, whether a purchaser of this publication or not, in respect of anything done or omitted, and the consequences of anything done or omitted, by any such person or entity in reliance on the contents of this publication.

© International Air Transport Association. All Rights Reserved. No part of this publication may be reproduced, recast, reformatted or transmitted in any form by any means, electronic or mechanical, including photocopying, recording or any information storage and retrieval system, without the prior written permission from:

> Senior Vice President Safety and Flight Operations International Air Transport Association 800 Place Victoria P.O. Box 113 Montreal, Quebec CANADA H4Z 1M1

Data Report for Evidence-Based Training ISBN 978-92-9252-228-5 © 2013 International Air Transport Association. All rights reserved. Montreal–Geneva